

Separating regular languages by piecewise testable and unambiguous languages

Thomas Place, Lrijn van Rooijen, Marc Zeitoun

LaBRI · Univ. Bordeaux · CNRS



September, 2013 · Highlights of Logic, Games and Automata

Separation problem

- S is a fixed class of languages.

In this talk, $S = \mathcal{BS}\Sigma_1(<), \text{FO}^2(<)$.

Separation problem

- S is a fixed class of languages.

In this talk, $S = \mathcal{B}\Sigma_1(<), \text{FO}^2(<)$.

- $L_1, L_2 \in \text{Reg}$ are **S -separable** iff there exists $K \in S$ such that




Separation problem

- S is a fixed class of languages.

In this talk, $S = \mathcal{BS}\Sigma_1(<), \text{FO}^2(<)$.

- $L_1, L_2 \in \text{Reg}$ are **S -separable** iff there exists $K \in S$ such that



- Decision problem: Given $L_1, L_2 \in \text{Reg}$, are they S-separable?


- Decision problem: Given $L_1, L_2 \in \text{Reg}$, are they **S-separable**?
- Can we compute a separator?

- Decision problem: Given $L_1, L_2 \in \text{Reg}$, are they **S-separable**?
- Can we compute a separator?
- What is the complexity of the decision problem?
And of computing a separator?


- Captures discriminative power of logics

- Captures discriminative power of logics
- Generalization of membership problem

- Captures discriminative power of logics
- Generalization of membership problem



- Captures discriminative power of logics
- Generalization of membership problem



- Piecewise testable languages: definable by $\mathcal{BS}\Sigma_1(<)$ formulas (recall previous talk).
- Unambiguous languages: definable by $\text{FO}^2(<)$ formulas.

- Piecewise testable languages: definable by $\mathcal{BS}_1(<)$ formulas (recall previous talk).
- Unambiguous languages: definable by $\text{FO}^2(<)$ formulas.

Membership is decidable for both $\mathcal{BS}_1(<)$ and $\text{FO}^2(<)$ languages.

Simon '75
Schützenberger '76, Thérien, Wilke '98

- In general, there is no smallest separator in S .
→ Restriction of S to quantifier depth k : $S[k]$.

- In general, there is no smallest separator in S .
→ Restriction of S to quantifier depth k : $S[k]$.
- If two languages are $S[k]$ -separable, there is a smallest separator in $S[k]$.

- In general, there is no smallest separator in S .
→ Restriction of S to quantifier depth k : $S[k]$.
- If two languages are $S[k]$ -separable, there is a smallest separator in $S[k]$.
- Eg. $(a^2)^*$ and $b(b^2)^*$ have no smallest $\mathcal{BS}_1(<)$ -separator, while $a^* \setminus \{a, a^3, a^5\}$ is the smallest $\mathcal{BS}_1(<)[6]$ -separator.

Quantifier depth provides indexed equivalence relations for $\mathcal{BS}_1(<)$
resp. $\text{FO}^2(<)$ languages:

Computing smallest separator for $S[k]$

Quantifier depth provides indexed equivalence relations for $\mathcal{BS}_1(<)$
resp. $\text{FO}^2(<)$ languages:

$$w_1 \sim_k w_2 \iff w_1 \text{ and } w_2 \text{ satisfy the same } \mathcal{BS}_1(<) \\ \text{resp. } \text{FO}^2(<) \text{ formulas up to depth } k.$$

Computing smallest separator for $S[k]$

Quantifier depth provides indexed equivalence relations for $\mathcal{BS}_1(<)$ resp. $\text{FO}^2(<)$ languages:

$$w_1 \sim_k w_2 \iff w_1 \text{ and } w_2 \text{ satisfy the same } \mathcal{BS}_1(<) \text{ resp. } \text{FO}^2(<) \text{ formulas up to depth } k.$$

L is a $\mathcal{BS}_1(<)$ resp. $\text{FO}^2(<)$ language

$$\iff$$


L is a union of \sim_k -classes for some $k \in \mathbb{N}$.

Computing smallest separator for $S[k]$

Increasing k refines the smallest potential separator:


Computing smallest separator for $S[k]$

Increasing k refines the smallest potential separator:




Computing smallest separator for $S[k]$

Increasing k refines the smallest potential separator:




Computing smallest separator for $S[k]$

Increasing k refines the smallest potential separator:




Computing smallest separator for $S[k]$

Increasing k refines the smallest potential separator:




Computing smallest separator for $S[k]$

Increasing k refines the smallest potential separator:



Computing smallest separator for $S[k]$


Increasing k refines the smallest potential separator:



Refining $[L]_{\sim_k}$ gives a semi-algorithm for separability.

Computing smallest separator for $S[k]$

Increasing k refines the smallest potential separator:



Refining $[L]_{\sim_k}$ gives a semi-algorithm for separability.

From which level of refinement can we conclude non-separability?

Testing non-separability

A pair of words $w_1 \in L_1, w_2 \in L_2$ is a k -witness of non-separability provided


$$w_1 \sim_k w_2.$$

Testing non-separability

A pair of words $w_1 \in L_1, w_2 \in L_2$ is a k -witness of non-separability provided

$$w_1 \sim_k w_2.$$


Abstraction: tuples (i_1, f_1, i_2, f_2)



Testing non-separability

A pair of words $w_1 \in L_1, w_2 \in L_2$ is a k -witness of non-separability provided

$$w_1 \sim_k w_2.$$




- L_1, L_2 are k -separable $\Leftrightarrow \{k\text{-witnesses}\} = \emptyset$.
- $\{k+1\text{-witnesses}\} \subseteq \{k\text{-witnesses}\}$.

Testing non-separability

A pair of words $w_1 \in L_1, w_2 \in L_2$ is a k -witness of non-separability provided

$$w_1 \sim_k w_2.$$




- L_1, L_2 are k -separable $\Leftrightarrow \{k\text{-witnesses}\} = \emptyset$.
- $\{k+1\text{-witnesses}\} \subseteq \{k\text{-witnesses}\}$.
- Limit behaviour?

Testing non-separability

A pair of words $w_1 \in L_1, w_2 \in L_2$ is a k -witness of non-separability provided

$$w_1 \sim_k w_2.$$



- L_1, L_2 are k -separable $\Leftrightarrow \{k\text{-witnesses}\} = \emptyset$.
- $\{k+1\text{-witnesses}\} \subseteq \{k\text{-witnesses}\}$.
- Limit behaviour?

We can compute K such that

$$\text{limit} = \emptyset \quad \Leftrightarrow \quad \{K\text{-witnesses}\} = \emptyset$$

Testing non-separability

- 1 Verify that the languages are not separable by any language of a sufficient, computable, index K .
- 2 Find a pattern in the automata producing k -witnesses for arbitrarily large k . (For $\mathcal{BS}_1(<)$: same as in previous talk)

Testing non-separability

- 1 Verify that the languages are not separable by any language of a sufficient, computable, index K .
- 2 Find a pattern in the automata producing k -witnesses for arbitrarily large k . (For $\mathcal{BS}_1(<)$: same as in previous talk)

Patterns in the automata, independently of the bound K , provide

- Better complexity
- A yes/no answer for separability
- But no separator

Theorem

For $S = \mathcal{BS}\Sigma_1(<)$, $\text{FO}^2(<)$, we *can compute* $K \in \mathbb{N}$ such that
TFAE

- i. L_1, L_2 are S -separable.
- ii. L_1, L_2 are $S[K]$ -separable.
- iii. $[L_1]_{\sim_K}$ separates L_1 from L_2 .
- iv. $\mathcal{A}_1, \mathcal{A}_2$ do not contain a *pattern* witnessing non-separability.

Condition iv. yields the following complexity results:

Theorem

Given NFAs $\mathcal{A}_1, \mathcal{A}_2$, one can determine whether the languages $L(\mathcal{A}_1)$ and $L(\mathcal{A}_2)$ are

- $\mathcal{BS}_1(<)$ -separable in **PTIME**,
- $\text{FO}^2(<)$ -separable in **EXPTIME**,

with respect to $|Q_1|, |Q_2|, |A|$.

- Obtain tight bounds on the size of $\mathcal{BS}_1(<)$ resp. $\text{FO}^2(<)$ - separators

- Obtain tight bounds on the size of $\mathcal{BS}_1(<)$ resp. $\text{FO}^2(<)$ - separators
- Efficient computation of the separators


- Obtain tight bounds on the size of $\mathcal{BS}_1(<)$ resp. $\text{FO}^2(<)$ - separators
- Efficient computation of the separators
- Consider other classes \mathcal{S}

Thank you

$L(\mathcal{A}_1)$ and $L(\mathcal{A}_2)$ are **not** $\mathcal{BS}\Sigma_1(<)$ -separable
iff
both \mathcal{A}_1 and \mathcal{A}_2 have a (\vec{u}, \vec{B}) -path:


$\mathcal{B}\Sigma_1(<)$: Witnesses in automata

$L(\mathcal{A}_1)$ and $L(\mathcal{A}_2)$ are **not** $\mathcal{B}\Sigma_1(<)$ -separable
iff
both \mathcal{A}_1 and \mathcal{A}_2 have a (\vec{u}, \vec{B}) -path:




$\mathcal{BS}_1(<)$: Witnesses in automata

$L(\mathcal{A}_1)$ and $L(\mathcal{A}_2)$ are **not** $\mathcal{BS}_1(<)$ -separable
iff
both \mathcal{A}_1 and \mathcal{A}_2 have a (\vec{u}, \vec{B}) -path:



$L(\mathcal{A}_1)$ and $L(\mathcal{A}_2)$ are **not** $\mathcal{BS}_1(<)$ -separable
iff
both \mathcal{A}_1 and \mathcal{A}_2 have a (\vec{u}, \vec{B}) -path:



This can be determined in $\text{PTIME}(|Q_1|, |Q_2|, |A|)$.

Detecting forbidden patterns



One can determine in $\text{PTIME}(|Q_1|, |Q_2|, |A|)$ whether $\exists (\vec{u}, \vec{B})$ such that both \mathcal{A}_1 and \mathcal{A}_2 have a (\vec{u}, \vec{B}) -path.

Detecting forbidden patterns

One can determine in $\text{PTIME}(|Q_1|, |Q_2|, |A|)$ whether $\exists (\vec{u}, \vec{B})$ such that both \mathcal{A}_1 and \mathcal{A}_2 have a (\vec{u}, \vec{B}) -path.

- By adding meta-transitions in \mathcal{A}_i , finding a (\vec{u}, \vec{B}) -witness reduces to:

Given states p_i, q_i, r_i of \mathcal{A}_i , is there $B \subseteq A$ st. the paths





occur in \mathcal{A}_1 resp. \mathcal{A}_2 ?

Detecting forbidden patterns

One can determine in $\text{PTIME}(|Q_1|, |Q_2|, |A|)$ whether $\exists (\vec{u}, \vec{B})$ such that both \mathcal{A}_1 and \mathcal{A}_2 have a (\vec{u}, \vec{B}) -path.

- By adding meta-transitions in \mathcal{A}_i , finding a (\vec{u}, \vec{B}) -witness reduces to:

Given states p_i, q_i, r_i of \mathcal{A}_i , is there $B \subseteq A$ st. the paths



occur in \mathcal{A}_1 resp. \mathcal{A}_2 ?

- This is in PTIME : iteratively use Tarjan's algorithm.

Detecting forbidden patterns

- If B exists, $B \subseteq C_1 \stackrel{\text{def}}{=} \text{alph_scc}(q_1, \mathcal{A}_1) \cap \text{alph_scc}(q_2, \mathcal{A}_2)$
(LINEAR)
- Restrict the automata to alphabet C_1 , and repeat the process:

$$C_{i+1} \stackrel{\text{def}}{=} \text{alph_scc}(q_1, \mathcal{A}_1 \upharpoonright_{C_i}) \cap \text{alph_scc}(q_2, \mathcal{A}_2 \upharpoonright_{C_i}).$$

- After $n \leq |A|$ iterations, $C_n = C_{n+1}$.
 - If $C_n = \emptyset$, the answer is no.
 - If $C_n \neq \emptyset$, it is the maximal possible B with $(= B)$ -loops around q_1, q_2 .
- Then, determine the remaining paths. (LINEAR)
- Overall LINEAR algorithm.