

Deciding the value 1 problem for probabilistic leaktight automata ¹

Nathanaël Fijalkow,
joint work with Hugo Gimbert and Youssef Oualhadj

LIAFA, Université Paris 7, France,
University of Warsaw, Poland,
École Normale Supérieure de Cachan, France.

WATA, Dresden, Germany
May 31st 2012


¹To appear in LICS 2012

- 1 The value 1 problem for probabilistic automata
- 2 Towards an algebraic treatment of probabilistic automata

- 1 The value 1 problem for probabilistic automata
- 2 Towards an algebraic treatment of probabilistic automata

Probabilistic automata (Rabin, 1963)

1



$$\mathbb{P}_{\mathcal{A}} : A^* \rightarrow [0, 1]$$

The value 1 problem

The value 1 problem is, given a probabilistic automaton \mathcal{A} :

“are there words accepted by \mathcal{A} with arbitrarily high probability?”

The value 1 problem

The value 1 problem is, given a probabilistic automaton \mathcal{A} :

“are there words accepted by \mathcal{A} with arbitrarily high probability?”

Define $\text{val}(\mathcal{A}) = \sup_w \mathbb{P}_{\mathcal{A}}(w)$. An equivalent formulation of this problem is:

“ $\text{val}(\mathcal{A}) \stackrel{?}{=} 1$ ”.

The value 1 problem is, given a probabilistic automaton \mathcal{A} :

“are there words accepted by \mathcal{A} with arbitrarily high probability?”


Define $\text{val}(\mathcal{A}) = \sup_w \mathbb{P}_{\mathcal{A}}(w)$. An equivalent formulation of this problem is:


“ $\text{val}(\mathcal{A}) \stackrel{?}{=} 1$ ”.

Theorem (Gimbert, Oualhadj, 2010)

The value 1 problem is undecidable.

An intuition






has value 1 if and only if $x > \frac{1}{2}$.

- 1 The value 1 problem for probabilistic automata
- 2 Towards an algebraic treatment of probabilistic automata


Weighted automata using algebra (Schützenberger)



$$\langle a \rangle = \begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & .3 & .7 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

$$\langle b \rangle = \begin{pmatrix} 1 & 0 & 0 & 0 \\ 1 & 0 & 0 & 0 \\ 0 & .5 & .5 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

$$I = \begin{pmatrix} 0 & 1 & 0 & 0 \end{pmatrix} \quad F = \begin{pmatrix} 0 \\ 0 \\ 0 \\ 1 \end{pmatrix}$$



$$\langle a \rangle = \begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & .3 & .7 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

$$\langle b \rangle = \begin{pmatrix} 1 & 0 & 0 & 0 \\ 1 & 0 & 0 & 0 \\ 0 & .5 & .5 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

$$I \cdot \langle aaabaa \rangle \cdot F = \mathbb{P}_{\mathcal{A}}(aaabaa)$$

Decide the value 1 problem for a *subclass* of probabilistic automata,
by **algebraic** and **non-numerical** means.

Decide the value 1 problem for a *subclass* of probabilistic automata, by **algebraic** and **non-numerical** means.

- **algebraic:** focus on the automaton structure,
- **non-numerical:** abstract away the values.

Decide the value 1 problem for a *subclass* of probabilistic automata, by **algebraic** and **non-numerical** means.


- **algebraic:** focus on the automaton structure,
- **non-numerical:** abstract away the values.


Hence we consider non-deterministic automata: we project $(\mathbb{R}, +, \times)$ into the boolean semiring $(\{0, 1\}, +, \times)$.

Decide the value 1 problem for a *subclass* of probabilistic automata, by **algebraic** and **non-numerical** means.

- **algebraic**: focus on the automaton structure,
- **non-numerical**: abstract away the values.


Hence we consider non-deterministic automata: we project $(\mathbb{R}, +, \times)$ into the boolean semiring $(\{0, 1\}, +, \times)$.






$$\langle a \rangle = \begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 1 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix} \quad \langle b \rangle = \begin{pmatrix} 1 & 0 & 0 & 0 \\ 1 & 0 & 0 & 0 \\ 0 & 1 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

$$I \cdot \langle u \rangle \cdot F = 1 \quad \text{if and only if} \quad \mathbb{P}_{\mathcal{A}}(u) > 0$$




$$\langle a \rangle = \begin{pmatrix} 1 & 1 \\ 0 & 1 \end{pmatrix}$$

In $\langle a \rangle$, the state 1 is transient and the state 2 is recurrent.



$$\langle a \rangle = \begin{pmatrix} 1 & 1 \\ 0 & 1 \end{pmatrix} \quad \langle a^\# \rangle = \begin{pmatrix} 0 & 1 \\ 0 & 1 \end{pmatrix}$$

In $\langle a \rangle$, the state 1 is transient and the state 2 is recurrent.



$$\langle a \rangle = \begin{pmatrix} 1 & 1 \\ 0 & 1 \end{pmatrix} \quad \langle a^\sharp \rangle = \begin{pmatrix} 0 & 1 \\ 0 & 1 \end{pmatrix}$$

In $\langle a \rangle$, the state 1 is transient and the state 2 is recurrent.

$$M^\sharp(s, t) = \begin{cases} 1 & \text{if } M(s, t) = 1 \text{ and } t \text{ recurrent in } M, \\ 0 & \text{otherwise.} \end{cases}$$

Compute a monoid inside the **finite** monoid $\mathcal{M}_{Q \times Q}(\{0, 1\}, +, \times)$.

- Compute $\langle a \rangle$ for $a \in A$:

$$\langle a \rangle(s, t) = \begin{cases} 1 & \text{if } \mathbb{P}_{\mathcal{A}}(s \xrightarrow{a} t) > 0, \\ 0 & \text{otherwise.} \end{cases}$$

- Close under product and stabilization.

Compute a monoid inside the **finite** monoid $\mathcal{M}_{Q \times Q}(\{0, 1\}, +, \times)$.

- Compute $\langle a \rangle$ for $a \in A$:


$$\langle a \rangle(s, t) = \begin{cases} 1 & \text{if } \mathbb{P}_{\mathcal{A}}(s \xrightarrow{a} t) > 0, \\ 0 & \text{otherwise.} \end{cases}$$

- Close under product and stabilization.
- If there exists a matrix M such that


$$\forall t \in Q, \quad M(s_0, t) = 1 \Rightarrow t \in F$$

then “ \mathcal{A} has value 1”, otherwise “ \mathcal{A} does not have value 1”.


An example




An example






An example





An example




An example



An example



An example



Theorem

If there exists a matrix M such that

$$\forall t \in Q, \quad M(s_0, t) = 1 \Rightarrow t \in F$$

then \mathcal{A} has value 1.


Theorem

If there exists a matrix M such that

$$\forall t \in Q, \quad M(s_0, t) = 1 \Rightarrow t \in F$$

then \mathcal{A} has value 1.


But the value 1 problem is undecidable, so...



Left and right parts are symmetric, so for all M :


$$M(0, L_2) = 1 \iff M(0, R_2) = 1.$$


A leak




A leak

12





There is a leak from 1 to 2.



There is a leak from 1 to 2.

Definition

An automaton \mathcal{A} is leaktight if it has no leak.

Theorem (Fijalkow, Gimbert, Oualhadj)

The value 1 problem is decidable for leaktight automata.

The proof relies on Simon's factorization forest theorem.

- We defined a subclass of probabilistic automata which subsumes all subclasses of probabilistic automata whose value 1 problem is known to be decidable,

- We defined a subclass of probabilistic automata which subsumes all subclasses of probabilistic automata whose value 1 problem is known to be decidable,
- We defined an algebraic algorithm (similar to Leung's algorithm) for the value 1 problem and proved its completeness for the class of leaktight automata.

- We defined a subclass of probabilistic automata which subsumes all subclasses of probabilistic automata whose value 1 problem is known to be decidable,
- We defined an algebraic algorithm (similar to Leung's algorithm) for the value 1 problem and proved its completeness for the class of leaktight automata.
- What does this algorithm actually compute?

- We defined a subclass of probabilistic automata which subsumes all subclasses of probabilistic automata whose value 1 problem is known to be decidable,
- We defined an algebraic algorithm (similar to Leung's algorithm) for the value 1 problem and proved its completeness for the class of leaktight automata.
- What does this algorithm actually compute?
- Can we use similar algorithms for other semirings?