

# Turing Machines with Atoms

(LICS 2013)

M. Bojańczyk, **B. Klin**, S. Lasota, S. Toruńczyk  
University of Warsaw

Highlights, Paris, 20 Sep. 2013

# Summary

- TMs with atoms model limited access to data

**Theorem.** In sets with atoms, there is a language that is decidable in nondeterministic polynomial time, but not deterministically semi-decidable.

(proof technique: Cai-Fürer-Immerman graphs)

# Sorting

## Comparison model

- numbers given as units
- compared in one step
- nothing else is allowed

$$\textcircled{3} < \textcircled{7}$$

# Sorting

## Comparison model

- numbers given as units
- compared in one step
- nothing else is allowed

$$\textcircled{3} < \textcircled{7}$$

## Turing machines

- numbers represented as strings
- arbitrary manipulation allowed

0	I	I
I	I	I

# Sets with atoms

(nominal sets, sets with urelements, permutation models)

# Sets with atoms


(nominal sets, sets with urelements, permutation models)

$\mathcal{A}$

# Sets with atoms

(nominal sets, sets with urelements, permutation models)

$A$




# Sets with atoms

(nominal sets, sets with urelements, permutation models)

$\emptyset$

$A$






# Sets with atoms


(nominal sets, sets with urelements, permutation models)

$\emptyset$

$A$



$A^2$




# Sets with atoms


(nominal sets, sets with urelements, permutation models)

$\emptyset$

$A$



$A^2$



$\binom{A}{2}$




# Sets with atoms


(nominal sets, sets with urelements, permutation models)

$\emptyset$

$\mathbb{A}$



$\mathbb{A}^2$



$\binom{\mathbb{A}}{2}$




$$\mathbb{A}^{\triangleleft} = \{ \{ (a, b, c), (b, c, a), (c, a, b) \} \mid a, b, c \in \mathbb{A} \}$$

# Sets with atoms


(nominal sets, sets with urelements, permutation models)

$\emptyset$

$A$




$A^2$



$\binom{A}{2}$



$A^\triangleleft$




# Sets with atoms


(nominal sets, sets with urelements, permutation models)

$\emptyset$


$A$




$A^2$



$\binom{A}{2}$




$A^\triangleleft$




(must be “hereditarily finitely supported”)


# Actions and orbits




# Actions and orbits



# Actions and orbits




$$(\text{blue circle}, \text{yellow circle}) \xrightarrow{\pi} (\text{yellow circle}, \text{pink circle})$$







# Actions and orbits



$$(\text{blue circle}, \text{yellow circle}) \xrightarrow{\pi} (\text{yellow circle}, \text{pink circle})$$




# Actions and orbits



$$\text{Orbit}(x) = \{\pi(x) \mid \pi \in \text{Perm}(\mathbb{A})\}$$

# Actions and orbits



$$\text{Orbit}(x) = \{\pi(x) \mid \pi \in \text{Perm}(\mathbb{A})\}$$

**Equivariant function  $f : X \rightarrow Y$ :**

$$f(\pi(x)) = \pi(f(x))$$

**for all**  $x \in X, \pi \in \text{Perm}(\mathbb{A})$

# Turing machines **with atoms**

- **orbit**-finite tape alphabet  $\Gamma$
- **orbit**-finite input alphabet  $\Sigma \subseteq \Gamma$
- **orbit**-finite set of states  $Q$
- initial state  $q_0 \in Q$ , final states  $F \subseteq Q$
- **equivariant** transition function

$$\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{-1, 0, 1\}$$

# Example 1

“last letter appears before”  $\Sigma = \mathcal{A}$

## Nondeterministic:

- read left-to-right
- guess that a current letter will be last
- read to the end
- check the last letter

# Example 1

“last letter appears before”  $\Sigma = \mathbb{A}$

## Nondeterministic:


- read left-to-right
- guess that a current letter will be last
- read to the end
- check the last letter

## Deterministic:

- read to the end
- store last letter
- come back and check


## Example 2

“compatible chains of rotating triangles”



## Example 2

“compatible chains of rotating triangles”






# Example 2

“compatible chains of rotating triangles”


Nondeterministic:



# Example 2

“compatible chains of rotating triangles”


Nondeterministic:



# Example 2

“compatible chains of rotating triangles”


Nondeterministic:



# Example 2

“compatible chains of rotating triangles”


Deterministic:



# Example 2

“compatible chains of rotating triangles”


Deterministic:



# Example 2

“compatible chains of rotating triangles”


Deterministic:



# Example 2

“compatible chains of rotating triangles”


Deterministic:



# Example 2

“compatible chains of rotating triangles”

Deterministic:






# Example 2

“compatible chains of rotating triangles”


Deterministic:



# Example 2

“compatible chains of rotating triangles”



Deterministic:




# Example 2

“compatible chains of rotating triangles”

Deterministic:





Not an equivariant function!




# Example 2

“compatible chains of rotating triangles”

Deterministic:



Not an equivariant function!



Determinisation fails.

# Summary

- TMs with atoms model limited access to data

**Theorem.** In sets with atoms, there is a language that is decidable in nondeterministic polynomial time, but not deterministically semi-decidable.

(proof technique: Cai-Fürer-Immerman graphs)