

Higher-Order Probabilistic Programming

A Tutorial at POPL 2019

Part IV

Ugo Dal Lago

(Based on joint work with *Flavien Breuvert*, *Raphaëlle Crubillé*, *Charles Grellois*, *Davide Sangiorgi*, . . .)



ALMA MATER STUDIORUM
UNIVERSITÀ DI BOLOGNA



POPL 2019, Lisbon, January 14th

The Landscape: *Type* Theory

Simple Types
 $\tau ::= \iota \mid \tau \rightarrow \tau$

The Landscape: *Type* Theory

Simple Types


$$\tau ::= \iota \quad | \quad \tau \rightarrow \tau$$

- ▶ Sound for termination, in absence of recursion.
- ▶ Poor expressive power.
- ▶ Intuitionistic Logic.

The Landscape: *Type* Theory

Simple Types

$\tau ::= \iota \mid \tau \rightarrow \tau$



Polymorphic
Types

$\tau ::= \dots \mid \alpha \mid \forall \alpha. \tau$

The Landscape: *Type* Theory


Simple Types

- ▶ Second-order Intuitionistic Logic.
- ▶ Very expressive, extensionally.
- ▶ Still poor, intensionally.

Polymorphic
Types

$\tau ::= \dots \mid \alpha \mid \forall \alpha. \tau$

The Landscape: *Type* Theory



The Landscape: *Type* Theory

Simple Types

- ▶ Motivated by Semantics.
- ▶ *Complete* for termination.
- ▶ Type inference is undecidable.


Polymorphic
Types

$\tau ::= \dots \mid \alpha \mid \forall \alpha. \tau$


Intersection
Types

$\tau ::= \dots \mid \tau \wedge \tau$

The Landscape: *Type* Theory



The Landscape: *Type* Theory



The Landscape: *Recursion* Theory

Determinism

$$M_{\bar{s}} \rightarrow^* N_s$$

The Landscape: *Recursion* Theory

Determinism

$$M\bar{s} \rightarrow^* N_s$$

Probabilism

$$\llbracket M\bar{s} \rrbracket = \mathcal{D}_s$$

The Landscape: *Recursion* Theory

$\sum \mathcal{D}_s$ can be smaller than 1.

Determinism

$$M\bar{s} \rightarrow^* N_s$$

Probabilism

$$\llbracket M\bar{s} \rrbracket = \mathcal{D}_s$$

The Landscape: *Recursion* Theory

Determinism

$$M\bar{s} \rightarrow^* N_s$$

Probabilism

$$\llbracket M\bar{s} \rrbracket = \mathcal{D}_s$$

Termination

$$\exists N_s \in NF$$

The Landscape: *Recursion* Theory

Undecidable;
 Σ_1^0 -complete.

$$M\bar{s} \dashv^* N_s$$

$$\exists N_s \in NF$$

Termination

Probabilism

$$\llbracket M\bar{s} \rrbracket = \mathcal{D}_s$$

The Landscape: *Recursion* Theory

Determinism

$$M\bar{s} \rightarrow^* N_s$$

Probabilism


$$\llbracket M\bar{s} \rrbracket = \mathcal{D}_s$$

Termination

$$\exists N_s \in NF$$

$$\sum \mathcal{D}_s = 1$$

The Landscape: *Recursion* Theory



Termination

The Landscape: *Recursion* Theory

Determinism

$$M\bar{s} \rightarrow^* N_s$$

$$\exists N_s \in NF$$

$$\forall s. \exists N_s \in NF$$

Probabilism


$$\llbracket M\bar{s} \rrbracket = \mathcal{D}_s$$

$$\sum \mathcal{D}_s = 1$$

Termination

**Uniform
Termination**

The Landscape: *Recursion* Theory



The Landscape: *Recursion* Theory

Determinism

Probabilism

$$M\bar{s} \rightarrow^* N_s$$

$$\llbracket M\bar{s} \rrbracket = \mathcal{D}_s$$

Termination

$$\exists N_s \in NF$$

$$\sum \mathcal{D}_s = 1$$

Uniform Termination

$$\forall s. \exists N_s \in NF$$

$$\forall s. \sum \mathcal{D}_s = 1$$

The Landscape: *Recursion* Theory

| | Determinism | Probabilism |
|---------------------|---------------------------------|-------------------------------------|
| | $M\bar{s} \rightarrow^* N_s$ | Π_2^0 -complete. |
| Termination | $\exists N_s \in NF$ | $\sum \mathcal{D}_s = 1$ |
| Uniform Termination | $\forall s. \exists N_s \in NF$ | $\forall s. \sum \mathcal{D}_s = 1$ |

Section 1


Sized Types

Deterministic Sized Types

- ▶ Pure λ -calculus with simple types is terminating.
 - ▶ This can be proved in many ways, including by **reducibility**.
 - ▶ But useless as a programming language.

Deterministic Sized Types

- ▶ Pure λ -calculus with simple types is terminating.
 - ▶ This can be proved in many ways, including by **reducibility**.
 - ▶ But useless as a programming language.

- 
- ▶ For every type τ , define a set of reducible terms Red_τ .
 - ▶ Prove that all reducible terms are normalizing...
 - ▶ ...and that all typable terms are reducible.

Deterministic Sized Types

- ▶ Pure λ -calculus with simple types is terminating.
 - ▶ This can be proved in many ways, including by **reducibility**.
 - ▶ But useless as a programming language.
- ▶ What if we endow it with **full recursion** as a **fix** binder?

Deterministic Sized Types

- ▶ Pure λ -calculus with simple types is terminating.
 - ▶ This can be proved in many ways, including by **reducibility**.
 - ▶ But useless as a programming language.
- ▶ What if we endow it with **full recursion** as a **fix** binder?


$$(\mathbf{fix} \ x.M)V \rightarrow M\{\mathbf{fix} \ x.M/x\}V$$

Deterministic Sized Types

- ▶ Pure λ -calculus with simple types is terminating.
 - ▶ This can be proved in many ways, including by **reducibility**.
 - ▶ But useless as a programming language.
- ▶ What if we endow it with **full recursion** as a **fix** binder?
- ▶ All the termination properties are **lost**, for very good reasons.

Deterministic Sized Types


- ▶ Pure λ -calculus with simple types is terminating.
 - ▶ This can be proved in many ways, including by **reducibility**.
 - ▶ But useless as a programming language.
- ▶ What if we endow it with **full recursion** as a **fix** binder?
- ▶ All the termination properties are **lost**, for very good reasons.
- ▶ Is **everything** lost?

Deterministic Sized Types

- ▶ Pure λ -calculus with simple types is terminating.
 - ▶ This can be proved in many ways, including by **reducibility**.
 - ▶ But useless as a programming language.
- ▶ What if we endow it with **full recursion** as a **fix** binder?
- ▶ All the termination properties are **lost**, for very good reasons.
- ▶ Is **everything** lost?
- ▶ **NO!**



Deterministic Sized Types

- ▶ Pure λ -calculus with simple types is terminating.
 - ▶ This can be proved in many ways, including by **reducibility**.
 - ▶ But useless as a programming language.
- ▶ What if we endow it with **full recursion** as a **fix** binder?
- ▶ All the termination properties are **lost**, for very good reasons.
- ▶ Is **everything** lost?
- ▶ **NO!**



Deterministic Sized Types

- ▶ Pure λ -calculus with simple types is terminating.
 - ▶ This can be proved in many ways, including by **reducibility**.
 - ▶ But useless as a programming language.
- ▶ What if we endow it with **full recursion** as a **fix** binder?
- ▶ All the termination properties are **lost**, for very good reasons.
- ▶ Is **everything** lost?
- ▶ **NO!**



Deterministic Sized Types, Technically

- **Types.**


$$\xi ::= a \mid \omega \mid \xi + 1; \qquad \tau ::= \iota[\xi] \mid \tau \rightarrow \tau.$$

Deterministic Sized Types, Technically

► **Types.**

$$\xi ::= a \mid \omega \mid \xi + 1;$$

$$\tau ::= \iota[\xi] \mid \tau \rightarrow \tau.$$



Index Terms

Deterministic Sized Types, Technically

- **Types.**

$$\xi ::= a \mid \omega \mid \xi + 1; \qquad \tau ::= \iota[\xi] \mid \tau \rightarrow \tau.$$

- **Typing Fixpoints.**

$$\frac{\Gamma, x : \iota[a] \rightarrow \tau \vdash M : \iota[a + 1] \rightarrow \tau}{\Gamma \vdash \mathbf{fix} \, x.M : \iota[\xi] \rightarrow \tau}$$

Deterministic Sized Types, Technically

- ▶ **Types.**

$$\xi ::= a \mid \omega \mid \xi + 1; \qquad \tau ::= \iota[\xi] \mid \tau \rightarrow \tau.$$

- ▶ **Typing Fixpoints.**

$$\frac{\Gamma, x : \iota[a] \rightarrow \tau \vdash M : \iota[a + 1] \rightarrow \tau}{\Gamma \vdash \mathbf{fix} \, x.M : \iota[\xi] \rightarrow \tau}$$

- ▶ **Quite Powerful.**

- ▶ Can type many forms of structural recursion.

Deterministic Sized Types, Technically

- ▶ **Types.**

$$\xi ::= a \mid \omega \mid \xi + 1; \qquad \tau ::= \iota[\xi] \mid \tau \rightarrow \tau.$$

- ▶ **Typing Fixpoints.**

$$\frac{\Gamma, x : \iota[a] \rightarrow \tau \vdash M : \iota[a + 1] \rightarrow \tau}{\Gamma \vdash \mathbf{fix} \, x.M : \iota[\xi] \rightarrow \tau}$$

- ▶ **Quite Powerful.**

- ▶ Can type many forms of structural recursion.

- ▶ **Termination.**

- ▶ Proved by **Reducibility**.
- ▶ ...but of an indexed form.

Deterministic Sized Types, Technically

► Types.

$$\xi ::= a \mid \omega \mid \xi + 1; \quad \tau ::= \iota[\xi] \mid \tau \rightarrow \tau.$$

► Typing Fixpoints.

$$\frac{\Gamma \ x \cdot \iota[a] \rightarrow \tau \vdash M \cdot \iota[a+1] \rightarrow \tau}{\text{Reducibility sets are of the form } Red_{\tau}^{\theta}.$$

- Reducibility sets are of the form Red_{τ}^{θ} .
- θ is an environment for index variables.
- Proof of reducibility for **fix** $x.M$ is rather delicate.
 - Can type many forms of structural recursion.
- **Termination.**
 - Proved by **Reducibility**.
 - ...but of an indexed form.

Deterministic Sized Types, Technically

- ▶ **Types.**

$$\xi ::= a \mid \omega \mid \xi + 1; \qquad \tau ::= \iota[\xi] \mid \tau \rightarrow \tau.$$

- ▶ **Typing Fixpoints.**

$$\frac{\Gamma, x : \iota[a] \rightarrow \tau \vdash M : \iota[a + 1] \rightarrow \tau}{\Gamma \vdash \mathbf{fix} \, x.M : \iota[\xi] \rightarrow \tau}$$

- ▶ **Quite Powerful.**

- ▶ Can type many forms of structural recursion.

- ▶ **Termination.**

- ▶ Proved by **Reducibility**.
- ▶ ...but of an indexed form.

- ▶ **Type Inference.**

- ▶ It is indeed *decidable*.
- ▶ But *nontrivial*.

Probabilistic Termination

► **Examples:**

```
fix f.λx.if x > 0 then if FairCoin then f(x - 1) else f(x + 1);  
fix f.λx.if x > 0 then if BiasedCoin then f(x - 1) else f(x + 1);  
fix f.λx.if BiasedCoin then f(x + 1) else x.
```

Probabilistic Termination

► Examples:

`fix f.λx.if x > 0 then if FairCoin then f(x - 1) else f(x + 1);`

`fix f.λx.if x > 0 then if BiasedCoin then f(x - 1) else f(x + 1);`

`fix f.λx.if BiasedCoin then f(x + 1) else x.`

Unbiased Random Walk

Probabilistic Termination

► Examples:

`fix f.λx.if x > 0 then if FairCoin then f(x - 1) else f(x + 1);`

`fix f.λx.if x > 0 then if BiasedCoin then f(x - 1) else f(x + 1);`

`fix f.λx.if BiasedCoin then f(x + 1) else x.`

Unbiased Random Walk

Biased Randomn Walk

Probabilistic Termination

► Examples:

```
fix f.λx.if x > 0 then if FairCoin then f(x - 1) else f(x + 1);  
fix f.λx.if x > 0 then if BiasedCoin then f(x - 1) else f(x + 1);  
fix f.λx.if BiasedCoin then f(x + 1) else x.
```

► Non-Examples:

```
fix f.λx.if FairCoin then f(x - 1) else (f(x + 1); f(x + 1));  
fix f.λx.if BiasedCoin then f(x + 1) else f(x - 1);
```

Probabilistic Termination

► Examples:

```
fix f.λx.if x > 0 then if FairCoin then f(x - 1) else f(x + 1);  
fix f.λx.if x > 0 then if BiasedCoin then f(x - 1) else f(x + 1);  
fix f.λx.if BiasedCoin then f(x + 1) else x.
```

► Non-Examples:

```
fix f.λx.if FairCoin then f(x - 1) else (f(x + 1); f(x + 1));  
fix f.λx.if BiasedCoin then f(x + 1) else f(x - 1);
```

Unbiased Random Walk, with **two** upward calls.

Probabilistic Termination

► Examples:

```
fix f.λx.if x > 0 then if FairCoin then f(x - 1) else f(x + 1);  
fix f.λx.if x > 0 then if BiasedCoin then f(x - 1) else f(x + 1);  
fix f.λx.if BiasedCoin then f(x + 1) else x.
```

► Non-Examples:

```
fix f.λx.if FairCoin then f(x - 1) else (f(x + 1); f(x + 1));  
fix f.λx.if BiasedCoin then f(x + 1) else f(x - 1);
```

Unbiased Random Walk, with **two** upward calls.

Biased Random Walk, the “wrong” way.

Probabilistic Termination

- ▶ **Examples:**

```
fix f.λx.if x > 0 then if FairCoin then f(x - 1) else f(x + 1);  
fix f.λx.if x > 0 then if BiasedCoin then f(x - 1) else f(x + 1);  
fix f.λx.if BiasedCoin then f(x + 1) else x.
```

- ▶ **Non-Examples:**

```
fix f.λx.if FairCoin then f(x - 1) else (f(x + 1); f(x + 1));  
fix f.λx.if BiasedCoin then f(x + 1) else f(x - 1);
```

- ▶ Probabilistic termination **is** thus:

- ▶ Sensitive to *the actual distribution* from which we sample.
- ▶ Sensitive to *how many recursive calls* we perform.

One-Counter Blind Markov Chains

- ▶ They are automata of the form (Q, δ) where
 - ▶ Q is a finite set of *states*.
 - ▶ $\delta : Q \rightarrow \text{Dist}(Q \times \{-1, 0, 1\})$.
- ▶ They are a very special form of One-Counter Markov Decision Processes [BBEK2011].
 - ▶ Everything is purely deterministic.
 - ▶ The counter value is ignored.

One-Counter Blind Markov Chains

- ▶ They are automata of the form (Q, δ) where
 - ▶ Q is a finite set of *states*.
 - ▶ $\delta : Q \rightarrow \text{Dist}(Q \times \{-1, 0, 1\})$.
- ▶ They are a very special form of One-Counter Markov Decision Processes [BBEK2011].
 - ▶ Everything is purely deterministic.
 - ▶ The counter value is ignored.
- ▶ The probability of reaching a configuration where the counter is 0 can be approximated arbitrarily well *in polynomial time*.

Probabilistic Sized Types [DLGrellois2017]

- ▶ **Basic Idea:** craft a sized-type system in such a way as to mimick the recursive structure by a OCBMC.

Probabilistic Sized Types [DLGrellois2017]

- ▶ **Basic Idea:** craft a sized-type system in such a way as to mimick the recursive structure by a OCBMC.
- ▶ **Judgments.**

$$\Gamma \mid \Delta \vdash M : \mu$$

Probabilistic Sized Types [DLGrellois2017]

- ▶ **Basic Idea:** craft a type system for recursive structures by a GCDMC.
- ▶ **Judgments.**

$$\Gamma \mid \Delta \vdash M : \mu$$

Every higher-order variable occurs **at most once**.

Probabilistic Sized Types [DLGrellois2017]

- ▶ **Basic Idea:** craft a sized-type system in such a way as to mimick the recursive structure by a OCBMC.
- ▶ **Judgments.**

$$\Gamma \mid \Delta \vdash M : \mu$$

- ▶ **Typing Fixpoints.**

$$\frac{\Gamma \mid x : \sigma \vdash V : \iota[a + 1] \rightarrow \tau \quad \text{OCBMC}(\sigma) \text{ terminates.}}{\Gamma \mid \Theta \vdash \mathbf{fix} \ x.V : \iota[\xi] \rightarrow \tau}$$

Probabilistic Sized Types [DLGrellois2017]

- ▶ **Basic Idea:** craft a recursive structure b
- ▶ **Judgments.**

Form σ , one can build a OCBMC:

- ▶ σ is a distribution type.
- ▶ It keeps track of the probability of each recursive call.

- ▶ **Typing Fixpoints.**

$$\frac{\Gamma \mid x : \sigma \vdash V : \iota[a + 1] \rightarrow \tau \quad \text{OCBMC}(\sigma) \text{ terminates.}}{\Gamma \mid \Theta \vdash \mathbf{fix} \ x.V : \iota[\xi] \rightarrow \tau}$$

This is sufficient for typing:

- ▶ Unbiased random walks;
- ▶ Biased random walks.

Probabilistic Sized Types [DLGrellois2017]

- ▶ **Basic Idea:** craft a sized-type system in such a way as to mimick the recursive structure by a OCBMC.
- ▶ **Judgments.**

$$\Gamma \mid \Delta \vdash M : \mu$$

- ▶ **Typing Fixpoints.**

$$\frac{\Gamma \mid x : \sigma \vdash V : \iota[a + 1] \rightarrow \tau \quad \text{OCBMC}(\sigma) \text{ terminates.}}{\Gamma \mid \Theta \vdash \text{fix } x.V : \iota[\xi] \rightarrow \tau}$$

- ▶ **Typing Probabilistic Choice**

$$\frac{\Gamma \mid \Delta \vdash M : \tau \quad \Gamma \mid \Omega \vdash N : \rho}{\Gamma \mid \frac{1}{2}\Delta + \frac{1}{2}\Omega \vdash M \oplus N : \frac{1}{2}\tau + \frac{1}{2}\rho}$$

Probabilistic Sized Types [DLGrellois2017]

- ▶ **Basic Idea:** craft a sized-type system in such a way as to mimick the recursive structure by a OCBMC.
- ▶ **Judgments.**

$$\Gamma \mid \Delta \vdash M : \mu$$

- ▶ **Typing Fixpoints.**

$$\frac{\Gamma \mid x : \sigma \vdash V : \iota[a + 1] \rightarrow \tau \quad \text{OCBMC}(\sigma) \text{ terminates.}}{\Gamma \mid \Theta \vdash \text{fix } x.V : \iota[\xi] \rightarrow \tau}$$

- ▶ **Typing Probabilistic Choice**

$$\frac{\Gamma \mid \Delta \vdash M : \tau \quad \Gamma \mid \Omega \vdash N : \rho}{\Gamma \mid \frac{1}{2}\Delta + \frac{1}{2}\Omega \vdash M \oplus N : \frac{1}{2}\tau + \frac{1}{2}\rho}$$

- ▶ **Termination.**

- ▶ By a quantitative nontrivial refinement of reducibility.

Probabilistic Sized Types [DLGrellois2017]

- ▶ **Basic Idea:** craft a sized-type system in such a way as to mimick the recursive structure by a OCBMC.
- ▶ **Judgments.**

$$\Gamma \mid \Delta \vdash M : \mu$$

- ▶ Reducibility sets are now on the form $Red_{\tau}^{\theta,p}$
- ▶ p stands for the *probability* of being reducible.
- ▶ Reducibility sets are continuous:

$$Red_{\tau}^{\theta,p} = \bigcup_{q < p} Red_{\tau}^{\theta,q}$$

es.

$$\frac{}{\Gamma \mid \frac{1}{2}\Delta + \frac{1}{2}\Omega \vdash M \odot N : \frac{1}{2}\tau + \frac{1}{2}\rho}$$

- ▶ **Termination.**
 - ▶ By a quantitative nontrivial refinement of reducibility.

Section 2

Intersection Types

Deterministic Intersection Types

- ▶ **Question:** what are simple types *missing* as a way to precisely capture *termination*?

Deterministic Intersection Types

- ▶ **Question:** what are simple types *missing* as a way to precisely capture *termination*?
- ▶ Very simple examples of normalizing terms which *cannot* be typed:

$$\Delta = \lambda x.xx \qquad \Delta(\lambda x.x).$$

Deterministic Intersection Types

- ▶ **Question:** what are simple types *missing* as a way to precisely capture *termination*?
- ▶ Very simple examples of normalizing terms which *cannot* be typed:

$$\Delta = \lambda x.xx \qquad \Delta(\lambda x.x).$$

- ▶ **Types**

$$\tau ::= \star \mid A \rightarrow B \qquad A ::= \{\tau_1, \dots, \tau_n\}$$

Deterministic Intersection Types

- ▶ **Question:** what are simple types *missing* as a way to precisely capture *termination*?
- ▶ Very simple examples of normalizing terms which *cannot* be typed:

$$\Delta = \lambda x.xx \qquad \Delta(\lambda x.x).$$

- ▶ **Types**

$$\tau ::= \star \mid A \rightarrow B \qquad A ::= \{\tau_1, \dots, \tau_n\}$$

- ▶ **Typing Rules: Examples**

$$\frac{\{\Gamma \vdash M : \tau_i\}_{1 \leq i \leq n}}{\Gamma \vdash M : \{\tau_1, \dots, \tau_n\}}$$

$$\frac{\Gamma \vdash M : \{A \rightarrow B\} \quad \Gamma \vdash N : A}{\Gamma \vdash MN : B}$$

Deterministic Intersection Types

- ▶ **Question:** what are simple types *missing* as a way to precisely capture *termination*?
- ▶ Very simple examples of normalizing terms which *cannot* be typed:

$$\Delta = \lambda x.xx \qquad \Delta(\lambda x.x).$$

- ▶ **Types**

$$\tau ::= \star \mid A \rightarrow B \qquad A ::= \{\tau_1, \dots, \tau_n\}$$

- ▶ **Typing Rules: Examples**

$$\frac{\{\Gamma \vdash M : \tau_i\}_{1 \leq i \leq n}}{\Gamma \vdash M : \{\tau_1, \dots, \tau_n\}}$$

$$\frac{\Gamma \vdash M : \{A \rightarrow B\} \quad \Gamma \vdash N : A}{\Gamma \vdash MN : B}$$

- ▶ **Termination**

- ▶ Again by reducibility.

Deterministic Intersection Types

- ▶ **Question:** what are simple types *missing* as a way to precisely capture *termination*?
- ▶ Very simple examples of normalizing terms which *cannot* be typed:

$$\Delta = \lambda x.xx \qquad \Delta(\lambda x.x).$$

- ▶ **Types**

$$\tau ::= \star \mid A \rightarrow B \qquad A ::= \{\tau_1, \dots, \tau_n\}$$

- ▶ **Typing Rules: Examples**

$$\frac{\{\Gamma \vdash M : \tau_i\}_{1 \leq i \leq n}}{\Gamma \vdash M : \{\tau_1, \dots, \tau_n\}} \qquad \frac{\Gamma \vdash M : \{A \rightarrow B\} \quad \Gamma \vdash N : A}{\Gamma \vdash MN : B}$$

- ▶ **Termination**

- ▶ Again by reducibility.

- ▶ **Completeness**

- ▶ By *subject expansion*, the dual of subject reduction.

Oracle Intersection Types [BreuvarDL2018]

- Probabilistic choice can be seen as a form of read operation:

$$M \oplus N = \text{if } \textit{BitInput} \text{ then } M \text{ else } N$$

Oracle Intersection Types [BreuvartDL2018]

- Probabilistic choice can be seen as a form of read operation:

$$M \oplus N = \text{if } \textit{BitInput} \text{ then } M \text{ else } N$$

- **Types**

$$\tau ::= \star \mid A \rightarrow s \cdot B \quad A ::= \{\tau_1, \dots, \tau_n\} \quad s \in \{0, 1\}^*$$

Oracle Intersection Types [BreuvartDL2018]

- Probabilistic choice can be seen as a form of read operation:

$$M \oplus N = \text{if } \textit{BitInput} \text{ then } M \text{ else } N$$

- **Types**

$$\tau ::= \star \mid A \rightarrow s \cdot B \quad A ::= \{\tau_1, \dots, \tau_n\} \quad s \in \{0, 1\}^*$$

- **Typing Rules: Examples**

$$\frac{\Gamma \vdash M : s \cdot A}{\Gamma \vdash M \oplus N : 0s \cdot A} \quad \frac{\Gamma \vdash M : r \cdot \{A \rightarrow s \cdot B\} \quad \Gamma \vdash N : q \cdot A}{\Gamma \vdash MN : (rqs) \cdot B}$$

Oracle Intersection Types [BreuvarDL2018]

- ▶ Probabilistic choice can be seen as a form of read operation:

$$M \oplus N = \text{if } \textit{BitInput} \text{ then } M \text{ else } N$$

- ▶ **Types**

$$\tau ::= \star \mid A \rightarrow s \cdot B \quad A ::= \{\tau_1, \dots, \tau_n\} \quad s \in \{0, 1\}^*$$

- ▶ **Typing Rules: Examples**

$$\frac{\Gamma \vdash M : s \cdot A}{\Gamma \vdash M \oplus N : 0s \cdot A} \quad \frac{\Gamma \vdash M : r \cdot \{A \rightarrow s \cdot B\} \quad \Gamma \vdash N : q \cdot A}{\Gamma \vdash MN : (rqs) \cdot B}$$

- ▶ **Termination and Completeness**

- ▶ Formulated in a rather *unusual* way.
- ▶ Proved as usual, but relative to a single probabilistic branch

Oracle Intersection Types [BreuvarDL2018]

- ▶ Probabilistic choice can be seen as a form of read operation:

$$M \oplus N = \text{if } \textit{BitInput} \text{ then } M \text{ else } N$$

- ▶ **Types**

$$\tau ::= \star \mid A \rightarrow s \cdot B \quad A ::= \{\tau_1, \dots, \tau_n\} \quad s \in \{0, 1\}^*$$

- ▶ **Typing Rules**

$$\mathbb{P}(M \downarrow) = \sum_{\vdash M : s \cdot \star} 2^{|s|}$$

$$\frac{\Gamma \vdash M : s \cdot A}{\Gamma \vdash M \oplus N : 0s \cdot A}$$

$$\frac{\Gamma \vdash M : r \cdot \{A \rightarrow s \cdot B\} \quad \Gamma \vdash N : q \cdot A}{\Gamma \vdash MN : (rqs) \cdot B}$$

- ▶ **Termination and Completeness**

- ▶ Formulated in a rather *unusual* way.
- ▶ Proved as usual, but relative to a single probabilistic branch

Oracle Intersection Types [BreuvarDL2018]

- ▶ Probabilistic choice can be seen as a form of read operation:

$$M \oplus N = \text{if } \textit{BitInput} \text{ then } M \text{ else } N$$

- ▶ **Types**

$$\tau ::= \star \mid A \rightarrow s \cdot B \quad A ::= \{\tau_1, \dots, \tau_n\} \quad s \in \{0, 1\}^*$$

- ▶ **Typing Rules**

$$\mathbb{P}(M \downarrow) = \sum_{\vdash M : s \cdot \star} 2^{|s|}$$

$$\Gamma \vdash M : s \cdot A$$

$$\Gamma \vdash M : r \cdot \{A \rightarrow s \cdot B\}$$

$$\Gamma \vdash N : q \cdot A$$


This is **unavoidable**, due to recursion theory.

B


- ▶ **Termination and Completeness**

- ▶ Formulated in a rather *unusual* way.
- ▶ Proved as usual, but relative to a single probabilistic branch



Intersection Types and Computations




Intersection Types and Computations






Intersection Types and Computations



Intersection Types and Computations




Intersection Types and Computations



Intersection Types and Computations

Monadic Intersection Types [BDL2018]

- ▶ They are a combination of oracle and sized types.
- ▶ Intersections are needed for preciseness.
- ▶ Distributions of types allow to analyse more than one probabilistic branch in the same type derivation.



Ongoing and Future Work

- ▶ **Non-Idempotent Intersection Types**

- ▶ Monadic and Oracle Intersection Types are idempotent.

Ongoing and Future Work

- ▶ **Non-Idempotent Intersection Types**

- ▶ Monadic and Oracle Intersection Types are idempotent.
- ▶ Conjecture:

$$\text{IDEMP} : AST = \text{NONIDEMP} : PAST$$

Ongoing and Future Work

- ▶ **Non-Idempotent Intersection Types**

- ▶ Monadic and Oracle Intersection Types are idempotent.
- ▶ Conjecture:

$$\text{IDEMP} : AST = \text{NONIDEMP} : PAST$$

- ▶ **Linear Dependent Types**

- ▶ Intersection Types are complete, but only for computations.
- ▶ In linear dependent types [DLG2011], one is (relatively complete) for deterministic first-order functions.

Ongoing and Future Work

► Non-Idempotent Intersection Types

- Monadic and Oracle Intersection Types are idempotent.
- Conjecture:

$$\text{IDEMP} : AST = \text{NONIDEMP} : PAST$$

► Linear Dependent Types

- Intersection Types are complete, but only for computations.
- In linear dependent types [DLG2011], one is (relatively complete) for deterministic first-order functions.
- How about probabilism?
 - Monadic types becomes indexed:

$$\mu ::= \{\sigma[i] : p[i]\}_{i \in I}$$

- Subtyping is coupling-based.

Thank You!

Questions?