

Original citation:

Figueira, Diego, Lazic, Ranko, Leroux, Jerome, Mazowiecki, Filip and Sutre, Grégoire (2017) Polynomial-space completeness of reachability for succinct branching VASS in dimension one. In: The 44th International Colloquium on Automata, Languages, and Programming (ICALP), Warsaw, Poland, 10-14 July 2017. Published in: Proceedings of the 44rd International Colloquium on Automata, Languages, and Programming

Permanent WRAP URL:

<http://wrap.warwick.ac.uk/87998>

Copyright and reuse:

The Warwick Research Archive Portal (WRAP) makes this work of researchers of the University of Warwick available open access under the following conditions.

This article is made available under the Creative Commons Attribution 4.0 International license (CC BY 4.0) and may be reused according to the conditions of the license. For more details see: <http://creativecommons.org/licenses/by/4.0/>

A note on versions:

The version presented in WRAP is the published version, or, version of record, and may be cited as it appears here.

For more information, please contact the WRAP Team at: wrap@warwick.ac.uk

Polynomial-Space Completeness of Reachability for Succinct Branching VASS in Dimension One*

Diego Figueira¹, Ranko Lazić², Jérôme Leroux¹, Filip Mazowiecki², and Grégoire Sutre¹

¹ LaBRI, CNRS, France

² DIMAP, University of Warwick, UK

Abstract

Whether the reachability problem for branching vector addition systems, or equivalently the provability problem for multiplicative exponential linear logic, is decidable has been a long-standing open question. The one-dimensional case is a generalisation of the extensively studied one-counter nets, and it was recently established polynomial-time complete provided counter updates are given in unary. Our main contribution is to determine the complexity when the encoding is binary: polynomial-space complete.

1998 ACM Subject Classification F.1.1 Models of Computation

Keywords and phrases branching vector addition systems, reachability problem

Digital Object Identifier 10.4230/LIPIcs.ICALP.2017.

1 Introduction

Background Vector addition systems, also known as Petri nets (cf., e.g., Reisig’s book [21]), are one of the longest established, most extensively studied, and most widely applied models of concurrent computing systems. Their branching generalisation has attracted considerable attention in recent years from the research community on logic in computer science. In addition to the simplicity and elegance of the model, this popularity is due to remarkably close connections with computational linguistics [20, 22], cryptographic protocols [25], linear logic [8, 16], semi-structured databases [13, 1], recursively parallel programs [5], game semantics [7], and timed pushdown systems [6].

A central decision problem for branching vector addition systems is reachability: whether a computation tree exists that has the given root and leaves. Similarly to the simpler setting of Petri nets, this problem has turned out to be very challenging. However, in contrast to Petri nets where the challenge is determining the complexity of reachability below a currently best cubic-Ackermann bound [17], even decidability is still open for the branching vector addition systems reachability problem. For reasons indicated above, the latter question was recently highlighted by Bojańczyk as one of a handful of most interesting open problems in computer science logic [4].¹

The decidability of the branching reachability problem is in fact open already in two dimensions. However, in one dimension, i.e. when there is only one counter, Göller et al. [10] established decidability, and more precisely polynomial-time completeness provided

* Partially supported by EPSRC grant EP/M011801/1 and Royal Society grant IE150122.

¹ Although decidability has been stated in a published journal article [2], we believe that claim has not been accepted by the community due to lack of proof, cf. [23, Footnote 4].



© D. Figueira, R. Lazić, J. Leroux, F. Mazowiecki, and G. Sutre;
licensed under Creative Commons License CC-BY

44th International Colloquium on Automata, Languages, and Programming (ICALP 2017).

Editors: Ioannis Chatzigiannakis, Piotr Indyk, Fabian Kuhn, and Anca Muscholl;

Article No. ; pp. 1–21



Leibniz International Proceedings in Informatics

LIPICs Schloss Dagstuhl – Leibniz-Zentrum für Informatik, Dagstuhl Publishing, Germany



| | unary | binary |
|--------|----------------------|------------------|
| 1VASS | NL-complete [24, 15] | NP-complete [11] |
| 1BVASS | P-complete [10] | PSPACE-complete |

■ **Table 1** Complexity of reachability for one-dimensional vector addition systems with states, depending on the presence of branching and the encoding of counter updates

the numbers that specify the counter updates in the system are given in unary. The precise complexity with the encoding in binary remained undetermined.

From another point of view, our investigation builds on the voluminous literature on decision problems for one-counter automata, a ubiquitous class obtained by either dropping one counter from Minsky (two-counter) machines or restricting pushdown automata to one stack symbol. In particular, the complexity of the reachability problem for one-counter systems is known: NL-completeness with the updates given in unary is a classical result [24, 15], and NP-completeness for succinct systems is due to Haase et al. [11] (cf. the latter paper for further references on the subject).

Contributions Our main result is the closure of the complexity gap for the reachability problem on succinct one-dimensional branching vector addition systems with states (1BVASS), which was between NP hardness inherited from 1VASS [11] and EXPTIME membership that follows from the P membership for unary 1BVASS [10].² We show that the problem is in fact PSPACE-complete, which fills the little Table 1.

The fact that the complexities for 1BVASS correspond exactly to ‘adding alternation’ to the complexities for 1VASS makes them easy to remember. However, it is quite misleading in terms of proofs, at least as far as we can see. The branchings in computations of BVASS are not alternations: counter valuations at child nodes are summed, not compared for equality.³ Already in the unary case, the proof of P-completeness for 1BVASS [10] is considerably more involved than of NL-completeness for 1VASS [24, 15]. In our proof of PSPACE-completeness for binary 1BVASS, there are several substantial new insights in comparison to both unary 1BVASS and binary 1VASS [11]:

- we introduce a novel notion of implicit reachability witnesses, show that such a witness of at most an exponential size always exists, and hence argue that it can be guessed and checked in polynomial space;
- for the exponential bound on the size of witnesses, a polynomial bound on their counter valuations as for unary 1BVASS [10] is not sufficient because trees with exponentially long branches may be doubly exponentially large;
- one of the techniques we employ for establishing the exponential bound involves a novel rewriting strategy, which may be of wider interest since it transforms fragments of computation trees to a normal form that features principal branches, whereas the lack of such a structure has hitherto been an obstacle to generalising Kosaraju’s approach [14, 17] to BVASS;

² We remark that we write ‘with states’ because stateless (B)VAS are sometimes considered in higher dimensions since states can be encoded at the expense of three additional counters; and that 1VASS, i.e. one-counter nets, are as hard as one-counter systems in this context since the ability to zero-test the counter does not make reachability significantly more complex.

³ Reachability for alternating VASS is actually undecidable, for relatively trivial reasons [19].

- in contrast to the other three hardness results summarised in Table 1, our lower bound proof is highly intricate, resting on a system of encodings and checks through which alternation can be simulated by additive branching up to a linear depth.

Organisation After the next section in which we define the systems we consider and observe some of their basic properties, the two sections that follow contain the PSPACE-membership proof. In the penultimate section, we present the PSPACE-hardness construction, and then finish with some concluding remarks.

2 Preliminaries

1BVASS A *one-dimensional branching vector addition system with states* (1BVASS for short) is a triple $B = (Q, \Delta, I)$ where Q is a non-empty finite set of *states*, Δ is a non-empty finite subset of $Q \times Q \times \mathbb{Z} \times Q$, and $I \subseteq Q$ is a finite set of *initial states*. An element $\delta = (q_L, q_R, z, q)$ in Δ is called a *transition*, and the integer z is called the *displacement* of the transition. In the sequel, the maximal absolute displacement is denoted by M . A *configuration* is a pair in $Q \times \mathbb{N}$, and a configuration in $I \times \{0\}$ is called an *initial configuration*. Since the displacements are given in binary, we define the size of B as $|B| = |Q| + |\Delta| \log_2(M + 1)$.

Trees We write $u \preceq v$ if u is a prefix of v and $u \prec v$ if u is a strict prefix. A *tree* is a non-empty finite prefix-closed subset T of $\{L, R\}^*$ satisfying the property that $tL \in T$ if, and only if, $tR \in T$ for every $t \in T$. Elements of T are called *nodes*. Its *root* is the empty word ε . An *ancestor* s of a node t is a prefix of t . In that case t is called a *descendant* of s . By writing *strict* descendants and ancestors we exclude $s = t$. A *child* of a node t is a node tL or tR in T . A node is called a *leaf* if it has no child, and it is said *internal* otherwise. The *sibling* of a node $t \neq \varepsilon$ in the tree T is the node obtained by swapping the last letter. The *height* of a node t is $|t|$. The size of a tree T is its cardinality $|T|$. The *height* of T is the maximal height of any of its nodes. The *subtree* of T rooted at a node t in T is the tree $t^{-1}T = \{t' \in \{L, R\}^* \mid tt' \in T\}$. The *truncation* of T at a node t is the tree $T \setminus t\{L, R\}^+$. Notice that t becomes a leaf of that truncated tree.

Runs and Reachability We consider labeled trees T where each node t is labeled by a state $q_t \in Q$ and a value $n_t \in \mathbb{N}$ defining a configuration (q_t, n_t) . A *run* ρ is a labeled tree such that for every internal node t , there exists an integer z such that (q_{tL}, q_{tR}, z, q_t) is a transition in Δ and such that $n_t = n_{tL} + n_{tR} + z$. The notions of height, size, subtree (called subrun in that context), and truncation are extended from trees to runs as one would expect. Notice that the labels are ignored in the size of a run.

A run is said to be *complete* if every leaf is labeled by an initial configuration. We write *partial run*, instead of run, when we want to emphasize that the run could be not complete. A configuration is said to be *reachable* if it is the root configuration of a complete run. We are mostly interested in the *reachability problem*: given a 1BVASS B and a configuration (q, n) decide whether (q, n) is reachable. The size of the input is $|B| + \log_2(n + 1)$.

► **Example 1.** Fix numbers n, b such that $0 \leq b \leq 2^n$. We define the 1BVASS $B = (Q, \Delta, I)$, where $Q = \{q_1 \dots q_n\} \cup \{q_I, q_F\}$ and $I = \{q_I\}$. There are three types of transitions:

$$(q_I, q_I, 0, q_1), (q_I, q_I, 1, q_1); \quad (q_i, q_i, 0, q_{i+1}) \text{ for all } i < n; \quad (q_n, q_n, -b, q_F).$$

The first two transitions initialize q_1 with 0 or 1; the next n transitions build a full binary tree below each state q_i ; and the last transition decreases the value of the counter by b . Consider the reachability problem of $(q_F, 0)$. The complete runs with $(q_F, 0)$ in the root are full binary trees of height $n + 1$ such that the number of nodes with state q_1 is 2^n and exactly b of them have value 1.

Contexts and Concatenation A *context* $\pi = (\rho, t)$ is a run ρ equipped with a distinguished leaf t called the *source* of π . The label of t is called the *source configuration* of π . Such a context is also called a context from the source configuration up to the root configuration of ρ . Given a node t in a run ρ and an ancestor s of t , i.e. such that $t = su$ for some word u , we define the context between (s, t) as the subrun rooted at s of the truncation at t of ρ , equipped with u as the source node. An ancestor of the source t is called a *main node* of π . The set of main nodes of π is called the *main branch*. A *dangling node* in π is a node that is a sibling of a main node. A *dangling configuration* is a configuration of such a node.

The concatenation $\pi\rho$ of a context π with a run ρ is defined if the source configuration (p, m) of π and the root configuration (q, n) of ρ satisfy $p = q$ and if the natural numbers labeling the main nodes of π are larger than or equal to $m - n$. Then $\pi\rho$ is defined by adding to the main nodes of π the integer $n - m$, and replacing the leaf node t of that context with ρ . Notice that $\pi\rho$ is a run. Contexts can be *concatenated* a similar way. The concatenation $\pi\pi'$ of a context $\pi = (\rho, t)$ with a context $\pi' = (\rho', t')$ is defined if $\pi\rho'$ is defined. In that case $\pi\pi'$ is the context $(\pi\rho', tt')$.

Cycles and Minimal Nodes A context from (p, m) up to (q, n) is called a *cycle* if the source is distinct from the root node and $p = q$. The cycle is said to be *simple* if on the main branch only the source and the root have the same states. A main node v is said to be *minimal* in a cycle if its value is minimal on the main branch, i.e., $n_v \leq n_{v'}$ for any other main node v' . We write *d-cycle* to emphasize the growth of the cycle, where $d = n - m$. The cycle is said to be *increasing* if $d > 0$, *zero* if $d = 0$, and *decreasing* if $d < 0$.

Let π be a d -cycle, and let p be the state of its source node. Let $\rho = \rho_1\pi\rho_2$ be a context or a run. By *removing* π from ρ we obtain $\rho' = \rho_1\rho_2$ (provided there is no drop below 0). Similarly, let $\rho = \rho_1\rho_2$ be a context or a run such that the source of ρ_1 has state label p . By *inserting* π into ρ we obtain $\rho_1\pi\rho_2$ (provided that there is no drop below 0). Notice that it is always safe to remove decreasing cycles and to add increasing cycles.

3 *d*-Coverability

A key role in our polynomial-space algorithm for the reachability problem is played by a more relaxed notion of ‘coverability modulo d ’: instead of reaching a value x exactly, it is allowed to reach any value which is at least x , provided the difference with x is a multiple of d . More formally, a configuration (q, n) is said to be *d-coverable* where $d > 0$ is a natural number if there exists a reachable configuration (q, x) with $x \in n + \mathbb{N}.d$. A *d-coverability run* of a configuration (q, n) is a complete run rooted by a configuration (q, x) with $x \in n + \mathbb{N}.d$. Note that a similar notion of *d-reachability* was used to show P-completeness for reachability of unary 1BVASS [10].

This section culminates by establishing that every *d-coverable* configuration (q, n) admits a ‘small’ *d-coverability run*, namely of size bounded by $(n + 5) \cdot (d2^{|B|})^6$. We present most of the proof, which is an orchestration of pigeonhole arguments and safe collapses, as a sequence of lemmas. Let us start with a simple observation about divisibility of subset sums.

► **Lemma 2.** *Let z_1, \dots, z_d be a non-empty sequence of integers. There exists a non-empty finite set $J \subseteq \{1, \dots, d\}$ such that d divides $\sum_{j \in J} z_j$.*

► **Lemma 3.** *Let (q, n) be a configuration and let ρ be a d -coverability run of (q, n) of minimal size. If the size of ρ is larger than $|Q|.2^{|Q|}.d^2$ then ρ contains an increasing cycle.*

Proof. Let ρ be a d -coverability run of (q, n) . Suppose: (1) the height of ρ is smaller than $|Q|.d$; and (2) for every height $\ell \geq 1$ the number of nodes in ρ of height ℓ is smaller than $2^{|Q|}.d$. Then it follows that the number of nodes of ρ is bounded by 1 (the root) plus $|Q|.d$ times $2^{|Q|}.d - 1$ (the remaining nodes). Hence the size is bounded by $|Q|.2^{|Q|}.d^2$. It remains to show that if (1) or (2) does not hold then ρ is not minimal or contains an increasing cycle.

In the first case (1) assume that the height of ρ is at least $|Q|.d$. In that case, there exists a node t such that $|t| = |Q|.d$. The nodes on the branch from the root to t are the prefixes of t . It follows that the number of nodes on that branch is equal to $|Q|.d + 1$. Notice that if every state of Q occurs at most d times on that branch, then the number of nodes of that branch is bounded by $|Q|.d$ and we get a contradiction. It follows that some state q occurs at least $d + 1$ times as a label of a node in that branch. If ρ does not contain any increasing cycle, then all repetitions induce zero or decreasing cycles. Lemma 2 shows that by removing at most d such cycles in that branch we get another d -coverability run of (q, n) , smaller than ρ .

In the second case (2) assume that there exists a level $\ell \geq 1$ such that the number of nodes in ρ of height ℓ is at least $2^{|Q|}.d$. It follows that $\ell \geq |Q|$. Notice that these nodes have ancestors in level $\ell - |Q|$. Since the number of elements in level ℓ that have the same ancestors in level $\ell - |Q|$ is bounded by $2^{|Q|}$, it follows that the level $\ell - |Q|$ contains at least d distinct nodes t_1, \dots, t_d such that, for some words u_1, \dots, u_d of length $|Q|$, we have $t_i u_i \in \rho$ for every $1 \leq i \leq d$. The pigeon-hole principle shows that we can extract a cycle in the context between $(t_i, t_i u_i)$ for every i . If ρ contains no increasing cycles, then these cycles are zero or decreasing. Lemma 2 shows that by removing at most d such cycles we get another d -coverability run of (q, n) , smaller than ρ . ◀

Small d -coverability runs are obtained thanks to the class of *witnesses of d -coverability* defined as follows. A *witness of d -coverability* of a configuration (q, n) is a partial run ψ with the root labeled (q, x) , where $x \in n + \mathbb{N}.d$. Every leaf labeled by a configuration (p, m) that is not initial is equipped with a complete run with root label (p, y) with $y \equiv m \pmod{d}$ and containing an increasing cycle. A node of ψ is said to be *modular* when it is an ancestor of such a leaf. We show in the sequel that the existence of d -coverability runs implies the existence of small witnesses of d -coverability. Moreover we provide a way to forge small d -coverability runs from small witnesses of d -coverability.

► **Lemma 4.** *Every d -coverable configuration (q, n) has a witness ψ such that:*

- *the subruns of ψ rooted at non-modular nodes have size at most $|Q|.2^{|Q|}.d^2$, and*
- *the complete runs attached to modular leaves have size at most $2|Q|.2^{|Q|}.d^2 + 1$.*

Proof sketch. We truncate a minimal d -coverability run, bottom-up, at the first increasing cycles. The bounds follow from Lemma 3. ◀

To reduce the number of modular nodes, we introduce an operation on d -coverability witnesses that collapses cycles between modular nodes, as follows. Given a modular leaf ℓ and two ancestors u, v satisfying $u \prec v \preceq \ell$ such that $q_u = q_v$, we transform the witness as follows. First, we introduce the minimal $k \geq 0$ such that $r = kd - n_u + n_v$ is non-negative. Second, we relabel the branch from the root to the leaf ℓ by adding r on nodes s such that

$\varepsilon \preceq s \preceq u$ and by adding kd on nodes s such that $v \preceq s \preceq \ell$. It is readily seen that the new labels of u and v are equal. Third, we remove the cycle between u and v by collapsing⁴ the nodes $u \prec v$. Notice that after this transformation we get a witness of d -coverability for $(q, n+r)$ where (q, n) was the root label of the original witness of d -coverability. We obtain the following lemma whose proof is along the same lines as that of Lemma 3.

► **Lemma 5.** *Let (q, n) be a configuration. By iteratively collapsing cycles, every witness of d -coverability of (q, n) can be simplified into a witness with at most $|Q|.2^{|Q|}.d^2$ modular nodes and where the height of each modular node is smaller than $|Q|.d$.*

► **Lemma 6.** *We may relabel modular nodes of any witness of d -coverability of (q, n) in such a way that $n_\ell < n + d + |Q|.d.M$ for every modular leaf ℓ .*

► **Theorem 7.** *Every d -coverable configuration (q, n) admits a d -coverability run of size at most $(n + 5).(d2^{|B|})^6$.*

Proof. By applying Lemmas 4, 5, and 6 in succession, we get a witness of d -coverability for (q, n) satisfying the bounds in these lemmas. Assume first that the root node of that witness is not a modular node. In that case the witness of d -coverability of (q, n) is in fact a d -coverability run of (q, n) and by Lemma 4 the size of this run is bounded by $|Q|.2^{|Q|}.d^2$.

Now, suppose that the root node of the witness is a modular node. Let μ be the number of all modular nodes, and ζ the number of all non-modular nodes. By Lemma 5 we get $\mu \leq |Q|.2^{|Q|}.d^2$. We bound ζ as follows. A non-modular node t is called a side node if it is the sibling of a modular node. Observe that non-modular nodes are descendant of side nodes and by Lemma 4 subruns rooted in side nodes have sizes bounded by $|Q|.2^{|Q|}.d^2$. Since the number of side nodes is bounded by μ , we derive that $\zeta \leq \mu.|Q|.2^{|Q|}.d^2$.

To build a d -coverability run from the witness we iterate the following process for each modular leaf ℓ in the witness. As a first step, we transform the attached complete run ρ_ℓ of ℓ in such a way its root label (q_ℓ, x) satisfies $x \in n_\ell + \mathbb{N}d$. Recall that ρ_ℓ contains an increasing cycle π . The above-mentioned transformation simply amounts to iterating this cycle $d.n_\ell$ times. By Lemma 4 the size of ρ_ℓ is bounded by $2.|Q|.2^{|Q|}.d^2 + 1$, which also bounds the size of π . The size of the resulting complete run ρ'_ℓ is bounded by $2.|Q|.2^{|Q|}.d^2 + 1$ (the size of ρ_ℓ) plus $d.n_\ell.2.|Q|.2^{|Q|}.d^2$ (the result of iterating the increasing cycle). It follows that the size of ρ'_ℓ is bounded by $2.(d.n_\ell + 1).|Q|.2^{|Q|}.d^2 + 1$. By Lemma 6 we have $n_\ell < n + d + |Q|.d.M$, so we get that the size of ρ'_ℓ is bounded by $2(n + 3).M.|Q|^2.2^{|Q|}.d^4 + 1$.

Let (q_ℓ, m_ℓ) be the configuration of the root of ρ'_ℓ . Observe that $m_\ell \in n_\ell + \mathbb{N}d$. In the second step we add $m_\ell - n_\ell$ to each node on the branch from ℓ to the root of the witness. After this step, the new label of ℓ is equal to the root label of ρ'_ℓ . As a third step, we simply replace the leaf ℓ by the complete run ρ'_ℓ .

We obtain a d -coverability run ρ for (q, n) of size $\mu + \zeta$, plus the sum of the sizes of the complete runs ρ'_ℓ for each modular leaf ℓ . This is bounded by

$$\mu + \mu.|Q|.2^{|Q|}.d^2 + \mu.(2(n + 3).M.|Q|^2.2^{|Q|}.d^4 + 1) \leq (2n + 9).M.|Q|^3.4^{|Q|}.d^6.$$

Since $M.2^{|Q|} \leq 2^{|B|}$, we get that the size of ρ is at most $(n + 5).(d2^{|B|})^6$. ◀

⁴ Collapsing two nodes $u \prec v$ consists in replacing the labeled subtree rooted in u by the labeled subtree rooted in v .

4 Reachability

This section is devoted to the proof of the following theorem.

► **Theorem 8.** *The reachability problem for 1BVASS is in PSPACE.*


The complexity is w.r.t. the sizes of the input 1BVASS and root configuration, both encoded in binary. Our proof relies on the following small witness property⁵.

► **Lemma 9.** *If c is a reachable configuration with a value bounded by $2^{|B|}$ in a given 1BVASS B then there exists a complete run of size at most $2^{60|B|^3}$ with root configuration c .*

Indeed, Lemma 9 implies Theorem 8. First, notice that for configurations with value bigger than $2^{|B|}$ it suffices to solve the problem for value 0 with an auxiliary step in the given BVASS. More precisely, if we ask for reachability of (q, n) we can add two states r, r' such that r is initial, a new transition $(q, r, -n, r')$, and change the question to reachability of $(r', 0)$. To verify if a configuration c with a value bounded by $2^{|B|}$ is reachable, we guess a complete run for c in nondeterministic polynomial space. Since it is impossible to maintain, in polynomial space, all nodes of the run in the memory, we only maintain the ancestors of the currently processed node whose other child was not processed yet. For every processed node v if it is an initial configuration then we go back to the closest ancestor a whose other child was not verified and proceed with that child. In this case we remove the ancestor a from the memory. Otherwise, we guess nondeterministically two children of v such that their triple satisfies some transition in Δ and continue with one of the children. The procedure nondeterministically guesses to proceed with the child whose subtree contains at most half of the leaves in the complete run. It remains to observe that the procedure does not need to remember more than $60|B|^3$ ancestors, otherwise the complete run would require more than $2^{60|B|^3}$ nodes. Notice that it is possible that a node has an exponential number of ancestors, but the procedure does not need to remember them all. The rest of this section is devoted to prove Lemma 9.

Small complete runs are forged from the so-called witnesses of reachability. Formally, the class of *witnesses of reachability* is defined inductively as follows. A witness of reachability w of a configuration c is a partial run with root labeled by c and such that every leaf labeled by (p, m) that is not an initial configuration is a reachable configuration equipped with an *implicit* decreasing simple cycle up to the configuration $(p, 0)$. Implicit means that only the main branch and the dangling nodes of the decreasing cycle are given explicitly. Each dangling configuration is equipped with a witness of reachability. Notice that every configuration admitting a witness is reachable since the leaves of the top most partial run of that witness are labeled by reachable configurations. The *depth* of a witness of reachability is defined as follows. The depth of a complete run is zero, and the depth of a witness of reachability that is not a complete run is one plus the maximal depth of the witnesses of reachability defining the dangling configurations of the decreasing cycles. The depth of a witness of reachability w is denoted by $\text{depth}(w)$. Figure 1 shows an example witness of reachability, suggesting how we turn it into a complete run. To bound the sizes of complete runs obtained from reachability witnesses we introduce the value $\text{maxsize}(w)$ denoting the size of the biggest partial runs occurring in a witness of reachability w . The following lemma shows that $\text{maxsize}(w)$ provides a simple way to bound values occurring in w .

⁵ In [6] it is proved that reachable configurations of 1BVASS admit complete runs with at most exponential values, but this is not enough to prove the PSPACE upper bound.



■ **Figure 1** A witness whose topmost partial run has two leaves that are not initial. Decreasing cycles are attached, and the dangling configurations are provided with their subwitnesses.

► **Lemma 10.** *For every witness of reachability w of a configuration with a value bounded by $2^{|B|}$, the root values of the partial runs used by w are bounded by $2^{|B|}$. Moreover, any value occurring in w is bounded by $2^{2|B|} \cdot \text{maxsize}(w)$.*

Proof. The maximal root values can be bounded by observing that, except for the top most partial run of w , partial runs provide root configurations that are dangling configurations of simple decreasing cycles. It follows that these values cannot exceed $|Q| \cdot M \leq 2^{|B|}$. We bound the other values as follows. Observe that the total sum of displacements plus the leave values of a partial run is equal to its root value. It follows that every value of w is bounded by $2^{|B|} + \text{maxsize}(w) \cdot M \leq 2^{2|B|} \cdot \text{maxsize}(w)$. ◀

► **Lemma 11.** *Let w be a witness of reachability of a configuration (q, n) satisfying $n \leq 2^{|B|}$ in a 1BVASS B . There exists a complete run ρ_w with root label (q, n) and size bounded by $(2^{10|B|} \cdot \text{maxsize}(w))^{2(\text{depth}(w)+1)}$.*

Proof. We associate to $s, \ell \in \mathbb{N}$ the set $C_{s,\ell}$ of configurations (q, n) such that $n \leq 2^{|B|}$ and such that there exists a witness of reachability w of (q, n) such that $\text{maxsize}(w) \leq s$ and $\text{depth}(w) \leq \ell$. We also define $f(s, \ell) = \max_{c \in C_{s,\ell}} (|\rho_c|)$, where $|\rho_c|$ is the minimal size of a complete run rooted at c . Such a run always exist since c is reachable. Notice that $f(s, 0) \leq s$ since a witness of reachability of depth 0 is a complete run.

We provide a bound for $f(s, \ell + 1)$ using $f(s, \ell)$. Consider a configuration $c \in C_{s,\ell+1}$. There exists a witness of reachability of c with depth bounded by $\ell + 1$ such that $\text{maxsize}(w) \leq s$. Let ρ be the top most partial run of w . Suppose there is a leaf labeled by a non-initial configuration (p, m) that is provided with an implicit simple decreasing cycle up to $(p, 0)$. Let us denote by $-d$ the effect of that cycle. As the cycle is simple, it follows that $d \leq |Q| \cdot M \leq 2^{|B|}$. The dangling configurations c_1, \dots, c_k of that cycle are given by witnesses of reachability w_1, \dots, w_k such that $\text{depth}(w_j) \leq \ell$ and $\text{maxsize}(w_j) \leq s$. It follows that $c_1, \dots, c_k \in C_{\ell,s}$. By induction, the dangling configurations c_1, \dots, c_k can be replaced by complete runs of size bounded by $f(s, \ell)$. Since the cycle is simple, $k \leq |Q|$. After these replacements we obtain an (explicit) simple cycle π of size at most $|Q| + |Q| \cdot f(s, \ell)$. Moreover, since (p, m) is reachable, it is d -coverable. Theorem 7 shows that there exists a d -coverability run for (p, m) of size at most $(m + 5) \cdot (d \cdot 2^{|B|})^6$. Lemma 10 shows that $m \leq 2^{2|B|} \cdot \text{maxsize}(w)$. Since $5 \leq 2^{3|B|} \cdot \text{maxsize}(w)$ we get $m + 5 \leq 2^{4|B|} \cdot \text{maxsize}(w)$. We derive that there is a d -coverability run ρ of (p, m) of size bounded by $\lambda = 2^{16|B|} \cdot \text{maxsize}(w) \leq 2^{16|B|} \cdot s$.

There exists $k \in \mathbb{N}$ such that $(p, m + k \cdot d)$ is the root configuration of ρ . In order to obtain a complete run with root configuration (p, m) , we just have to consider $\pi^k \rho$. Notice that we can never reach a value below zero since π is a decreasing cycle up to $(p, 0)$. As $m + k \cdot d \leq \lambda \cdot M$, it follows that $k \leq \lambda \cdot M$. We have proved that there exists a complete run with root configuration (p, m) and of size bounded by $\lambda \cdot M \cdot (|Q| + |Q| \cdot f(s, \ell)) + \lambda \leq 2^{19|B|} \cdot s \cdot f(s, \ell)$. Finally, by replacing every non-terminal leaf by a complete run as performed previously, we

get a complete run with root configuration c and size bounded by $2^{19|B|} \cdot s^2 \cdot f(s, \ell)$. We have proved that $f(s, \ell + 1)$ is bounded by that value. An immediate induction shows that

$$f(s, \ell) \leq (2^{19|B|} \cdot s^2)^\ell \cdot f(s, 0) \leq (2^{19|B|} \cdot s^2)^\ell \cdot s \leq (2^{10|B|} \cdot s)^{2(\ell+1)}.$$

By Lemma 11, to prove Lemma 9 it suffices to find a witness w such that $\text{maxsize}(w)$ is bounded exponentially and $\text{depth}(w)$ is bounded polynomially in the size of the given 1BVASS. Before we prove that we introduce some notation and two auxiliary lemmas.

Before the next lemma we introduce an operation that intuitively moves increasing cycles from left branches to right branches. By applying that operation as many times as possible, we obtain a so-called *saturated* partial run. Formally, a partial run ρ is said to be *reducible* in a node s if there exists an increasing cycle π between (sL, t) for some node $t \succeq sL$, and a minimal node v in π such that q_v is the state of some descendant of sR . A partial run that is not reducible is said to be *saturated*.

► **Lemma 12.** *For every partial run ρ there exists a saturated partial run ρ' with the same root configuration, the same number of nodes, and the same mutiset of leaf configurations.*

Proof. Assume that a partial run ρ is reducible on a node s . Let us denote by π an increasing d -cycle between (sL, t) in ρ for some node $t \succeq sL$ and a minimal node v in π such that $q_v = q_{v'}$ for some v' , a descendant of sR . Let $\pi = \pi_1 \pi_2$ be such that π_1 is the fragment of π with the source node v . We define $\pi' = \pi_2 \pi'_1$, where π'_1 is obtained from π_1 by decreasing all values on the main branch by n_v . Since v is minimal, notice that π' is an increasing d -cycle from $(q_v, 0)$ up to (q_v, d) such that the multiset of configurations of nodes not on the main branch in π and π' are equal. By removing from ρ the increasing cycle π , and inserting the increasing cycle π' into v' , we get a partial run ρ' such that the root configuration, the number of nodes, and the mutiset of leaf configurations remain the same as in ρ . Notice that by removing π we decrease the value of s by d , but by inserting π' its value is increased by d , therefore, these operations do not cause a drop below 0. Since this transformation can be performed only a finite number of times, at some point, we get a saturated run satisfying the lemma. ◀

► **Lemma 13.** *The number of nodes of a saturated run with root labeled (q, n) with $n \leq 2^{|B|}$ that does not contain any decreasing or zero cycles is bounded by $2^{5|B|^2}$.*

To prove Lemma 9 we will decompose partial runs that contain a decreasing cycle. Since such cycles are not necessarily simple, we provide the following lemma.

► **Lemma 14.** *For every decreasing cycle π there exists a state p that labels a main node of π and a simple decreasing cycle π' up to $(p, 0)$ such that the set of dangling configurations of π' is included in the set of dangling configurations of π .*

Proof of Lemma 9. We consider a reachable configuration c with a value bounded by $2^{|B|}$. Obviously c admits a witness of reachability because every complete run is a witness. By Lemma 11 we need to find a witness w of c such that $\text{maxsize}(w)$, $\text{depth}(w)$ have proper bounds. To do so, we associate to every witness w the sequence of natural numbers $s(w) = (s_j)_{j \geq 1}$, where s_j is the number of partial runs of size j in w , called the *rank* of w . These sequences are ordered colexicographically by the total order \sqsubseteq defined by $(s_j)_{j \geq 1} \sqsubseteq (s'_j)_{j \geq 1}$ if the two sequences are equal or there exists $j \geq 1$ such that $s_j < s'_j$ and $s_i = s'_i$ for every $i > j$. Notice that sequences $s(w)$ have finite support, i.e., $\{j \mid s_j \neq 0\}$ is finite. When restricted to sequences with finite support the order \sqsubseteq is well-founded, i.e., there are no

infinite decreasing sequences. We consider for the remainder of the proof a reachability witness w with a minimal rank (for \sqsubseteq).

Suppose w has depth $\ell > |Q|$. Then there exists a sequence $\pi_1 \dots \pi_\ell$ of implicit decreasing simple cycles such that π_{i+1} is a cycle equipped to the partial run of a dangling node in π_i . Then there exist $i < j$ such that π_i and π_j have the same state in the root. We replace π_i with π_j . In particular we remove all cycles $\pi_i \dots \pi_{j-1}$ and all partial runs that were associated to them. The resulting witness has a smaller rank which contradicts our minimality assumption on w .

Now, suppose that w contains partial runs of size bigger than $2^{5|B|^2}$. Let σ be a partial run having the maximal size and such that its depth is maximal (with respect to others of the same size). Notice that all partial runs of larger depth are smaller than σ . Using Lemma 12 we turn σ into a saturated run without changing the multiset of configurations of the leaves. Lemma 10 shows that the run σ has root value at most $2^{|B|}$ and thus by Lemma 13 there exists a decreasing or a zero cycle π in σ . If π is a zero cycle then we just remove it obtaining a smaller rank which contradicts our minimality assumption on w . Otherwise, π is a decreasing cycle. By Lemma 14 there exists a state p that labels a main node u of π and a simple decreasing cycle π' up to $(p, 0)$ such that the set of dangling configurations of π' is included in the set of dangling configurations of π . Since π is a cycle, we can assume w.l.o.g. that u is distinct from the source of π . Let v be the original node of u in σ . By assumption on u , notice that v is an internal node of σ . We define σ' as the partial run truncated at v and equip it with the simple decreasing cycle π' . Since v is an internal node, σ' is smaller from σ . The configurations of dangling nodes in π' are also configurations of dangling nodes in π , which come from σ . We use the partial subruns of σ as partial runs for dangling nodes in π' . These subruns come with implicit simple decreasing cycles and additional partial runs of smaller depth. Notice that, possibly, we have introduced double copies of partial runs of smaller depth. Let us show that the resulting witness w' has a smaller rank which will contradict our minimality assumption on w . Recall that all partial runs of bigger depth are smaller than σ . Since we have decreased the size of σ , and all introduced partial runs are of smaller size than σ it follows that $s(w') \sqsubset s(w)$.

We have proved that $\text{depth}(w) \leq |Q|$ and $\text{maxsize}(w) \leq 2^{5|B|^2}$. From Lemma 11, we get a complete run rooted by (q, n) with size bounded by $2^{60|B|^3}$. ◀

5 Hardness

We prove that the reachability problem for 1BVASS is PSPACE-hard. Intuitively, one would like to encode runs of an alternating PTIME Turing machine: the tape configuration is maintained as the binary representation of the counter value, and alternation is represented by the branching structure of the run. At first sight, binary rules of BVASS are not compatible with any sort of alternation: the value ℓ of a node may come from two arbitrary values ℓ_1, ℓ_2 from children with the sole restriction that $\ell = \ell_1 + \ell_2$. It thus seems pointless to pretend to replicate information encoded in ℓ into both ℓ_1 and ℓ_2 . However, we show that one can enforce—in a highly restricted setting—that transitions behave in a regular way, where $\ell = 2 \cdot \ell_1 = 2 \cdot \ell_2$. Using this, child nodes can recover information from the parent node: the i -th bit of the child has a 1 iff the $i+1$ -th bit of the parent has a 1. In this way information can be ‘copied’ into different branches, and we can benefit from some form of alternation.

► **Theorem 15.** *The reachability problem for 1BVASS is PSPACE-hard.*

Proof idea. The proof goes by reduction from the PSPACE-complete problem of validity for

Quantified Boolean Formulas. Given a QBF sentence, such as

$$\varphi = \forall P_1 \exists P_2 \forall P_3 (P_1 \vee \neg P_2 \vee P_3) \wedge (\neg P_1 \vee P_2),$$

we define a polynomial size 1BVASS \mathcal{B} , in such a way that the configuration $(q_1, 0)$ is reachable if, and only if, φ is valid. Transitions in \mathcal{B} enforce that any complete run for $(q_1, 0)$ encodes a ‘certificate’ of the validity of φ . In particular, this certificate contains

- nondeterministic choices for the valuation of existentially quantified variables such as P_2 ;
- one branch for each of the exponentially-many valuations for universally quantified variables, such as P_1 and P_3 ;
- for each branch encoding a valuation, a sub-branch for each disjunctive clause, certifying that the clause is true under that valuation.

Levels. For this reduction, it is natural to think of runs as proceeding top-down instead of bottom-up as done hitherto. That is, we start with a configuration $(q_1, 0)$ at the root, and we build valuations going downward until eventually finding an initial configuration on every branch. From this perspective, transitions of \mathcal{B} ‘increment’ a value $c > 0$ before ‘splitting’ the value into children with states q', q'' with a transition of the form $(q', q'', -c, q)$. The behaviour of \mathcal{B} ensure that any complete run for $(q_1, 0)$ can be divided into ‘levels’, so that the i -th level of the tree contains encodings for the choices of valuations for the first i variables of φ . For the purpose of this sketch, the level i is the set of all nodes of height $2 \cdot i$ in the run (*e.g.*, in the run of Figure 2, nodes at level i are those labelled q_{i+1}).

Valuation encoding. Variable valuations are encoded in the counter value by exploiting its compact binary representation, which throughout the run remains always a bitstring of quadratic length in the size of the sentence φ . The counter value bitstring can be split into equal length *segments*, one for each variable, so that the i -th segment is a $2m$ substring encoding the valuation of the i -th variable of φ , where m is the number of universally quantified variables plus the \log_2 of the number of conjuncts of φ —in our running example, $m = 3$. The encoding of a valuation for a variable will evolve along the run, for example the encoding for P_1 being true at nodes at different levels may differ. This is because branchings change the counter value and thus its binary representation. For a node at level j , the encoding for a *true* (\top) valuation of a variable P_i with $i \leq j$ is through a bitstring $0^{u(j)-1}10^{2m-u(j)}$ at the i -th segment, where $u(j)$ is the number of universally quantified variables P_i with $i \leq j$ in the input sentence —in our example, $u = \{(1, 1), (2, 1), (3, 2)\}$. Similarly, the way to encode a *false* (\perp) valuation is through the bitstring $0^{m+u(j)-1}10^{m-u(j)}$. For φ as above, where $m = 3$, the valuation $\{(P_1, \top), (P_2, \perp), (P_3, \perp)\}$ at level 3 (*i.e.*, $j = 3$, $u(j) = 2$) is represented by the bitstring $z = (010|000)(000|010)(000|010)$ (parentheses and pipes are only to improve readability). Let us call the ‘ (i, j) -bit’ the j -th most significant bit of the i -th most significant segment in the bitstring, and let $c_{i,j} \in \mathbb{N}$ be the number whose sole (i, j) -bit is 1 in its binary representation (*e.g.*, for z as above, $z = c_{1,2} + c_{2,5} + c_{3,5}$).

As discussed before, for this reduction to work we need that already defined valuation are somehow ‘replicated’ in all the subtrees, that is, when a configuration branches, information on the valuations is preserved in both children configurations and remains uncorrupted. For this, we enforce that, for every internal node t inside a complete run for $(q_1, 0)$ of \mathcal{B} , either:

- (1) t has a right child with the initial configuration $(q_I, 0)$, or, otherwise,
- (2) both children of t have the same value, that is, $n_t = 2 \cdot n_{tL} = 2 \cdot n_{tR}$.

Assuming such a property (as verified by the run of Fig. 2), information can be ‘spread’ along branches of a run: at any node t of type (2) the i -th least significant bit of n_t is 1 iff the $(i - 1)$ -th least significant bit of n_{tL} and n_{tR} are 1. We use transitions of type (1) to generate a new valuation for the i -th variable, and transitions of type (2) to split the current

References

- 1 Sergio Abriola, Diego Figueira, and Santiago Figueira. Logics of repeating values on data trees and branching counter systems. In *FoSSACS*, volume 10203 of *LNCS*. Springer, 2017, to appear.
- 2 Katalin Bimbó. The decidability of the intensional fragment of classical linear logic. *Theor. Comput. Sci.*, 597:1–17, 2015.
- 3 Michael Blondin, Alain Finkel, Stefan Göller, Christoph Haase, and Pierre McKenzie. Reachability in two-dimensional vector addition systems with states is PSPACE-complete. In *LICS*, pages 32–43. IEEE Computer Society, 2015.
- 4 Mikołaj Bojańczyk. Automata column. *SIGLOG News*, 1(2):3–12, 2014.
- 5 Ahmed Bouajjani and Michael Emmi. Analysis of recursively parallel programs. *ACM Trans. Program. Lang. Syst.*, 35(3):10:1–10:49, 2013.
- 6 Lorenzo Clemente, Sławomir Lasota, Ranko Lazić, and Filip Mazowiecki. Timed pushdown automata and branching vector addition systems. Submitted, 2017.
- 7 Conrad Cotton-Barratt, Andrzej S. Murawski, and C.-H. Luke Ong. ML and extended BVASS. In *ESOP*, 2017. To appear.
- 8 Philippe de Groote, Bruno Guillaume, and Sylvain Salvati. Vector addition tree automata. In *LICS*, pages 64–73. IEEE Computer Society, 2004.
- 9 Matthias Englert, Ranko Lazić, and Patrick Totzke. Reachability in two-dimensional unary vector addition systems with states is NL-complete. In *LICS*, pages 477–484. ACM, 2016.
- 10 Stefan Göller, Christoph Haase, Ranko Lazić, and Patrick Totzke. A polynomial-time algorithm for reachability in branching VASS in dimension one. In *ICALP*, volume 55 of *LIPIcs*, pages 105:1–105:13. Schloss Dagstuhl, 2016.
- 11 Christoph Haase, Stephan Kreutzer, Joël Ouaknine, and James Worrell. Reachability in succinct and parametric one-counter automata. In *CONCUR*, volume 5710 of *LNCS*, pages 369–383. Springer, 2009.
- 12 John E. Hopcroft and Jean-Jacques Pansiot. On the reachability problem for 5-dimensional vector addition systems. *Theor. Comput. Sci.*, 8:135–159, 1979.
- 13 Florent Jacquemard, Luc Segoufin, and Jérémie Dimino. $\text{FO2}(<, +1, \sim)$ on data trees, data tree automata and branching vector addition systems. *Log. Meth. Comput. Sci.*, 12(2), 2016.
- 14 S. Rao Kosaraju. Decidability of reachability in vector addition systems (preliminary version). In *STOC*, pages 267–281. ACM, 1982.
- 15 Pascal Lafourcade, Denis Lugiez, and Ralf Treinen. Intruder deduction for AC-like equational theories with homomorphisms. Research Report LSV-04-16, ENS de Cachan, 2004.
- 16 Ranko Lazić and Sylvain Schmitz. Nonelementary complexities for branching VASS, MELL, and extensions. *ACM Trans. Comput. Log.*, 16(3):20:1–20:30, 2015.
- 17 Jérôme Leroux and Sylvain Schmitz. Ideal decompositions for vector addition systems (invited talk). In *STACS*, volume 47 of *LIPIcs*, pages 1:1–1:13. Schloss Dagstuhl, 2016.
- 18 Jérôme Leroux and Grégoire Sutre. On flatness for 2-dimensional vector addition systems with states. In *CONCUR*, volume 3170 of *LNCS*, pages 402–416. Springer, 2004.
- 19 Patrick Lincoln, John C. Mitchell, Andre Scedrov, and Natarajan Shankar. Decision problems for propositional linear logic. *Ann. Pure Appl. Logic*, 56(1-3):239–311, 1992.
- 20 Owen Rambow. Multiset-valued linear index grammars: Imposing dominance constraints on derivations. In *ACL*, pages 263–270. Morgan Kaufmann Publishers / ACL, 1994.
- 21 Wolfgang Reisig. *Understanding Petri Nets - Modeling Techniques, Analysis Methods, Case Studies*. Springer, 2013.
- 22 Sylvain Schmitz. On the computational complexity of dominance links in grammatical formalisms. In *ACL*, pages 514–524. The Association for Computer Linguistics, 2010.

- 23 Sylvain Schmitz. The complexity of reachability in vector addition systems. *SIGLOG News*, 3(1):4–21, 2016.
- 24 Leslie G. Valiant and Mike Paterson. Deterministic one-counter automata. *J. Comput. Syst. Sci.*, 10(3):340–350, 1975.
- 25 Kumar Neeraj Verma and Jean Goubault-Larrecq. Karp-Miller trees for a branching extension of VASS. *Discr. Math. & Theor. Comput. Sci.*, 7(1):217–230, 2005.

A Missing proofs of Section 3

Proof of Lemma 2. We introduce the remainder r_j of $z_1 + \dots + z_j$ by d . Notice that $r_j \in \{0, \dots, d-1\}$ for every $0 \leq j \leq d$. The pigeon-hole principle shows that there exist $i < j$ such that $r_i = r_j$. It follows that $r_j - r_i = 0$. Notice that this difference is the remainder of $z_{i+1} + \dots + z_j$ by d . So the lemma is proved with $J = \{i+1, \dots, j\}$. ◀

Proof of Lemma 4. Let ρ be a d -coverability run of (q, n) of minimal size. We say that a node t of ρ is a *cut* node if the subrun rooted at t contains an increasing cycle (hence t is internal), but the subruns rooted at tL and tR do not contain any increasing cycle. Cut nodes are pair-wise incomparable for \preceq , meaning that no cut node is an ancestor of another cut node. It follows that we can decompose ρ into a witness of d -coverability by replacing each cut node t by a leaf equipped with the subrun of ρ rooted at t . We show that, in the resulting witness, the subrun rooted at each non-modular node contains no increasing cycle. By contradiction, take a maximal (for \preceq) non-modular node t violating the claim. By maximality, t is a cut node of ρ which contradicts the assumption that t is not modular in the witness. The desired bounds follow from the observation that by Lemma 3, the size of each subrun of ρ with no increasing cycle is bounded by $|Q|.2^{|Q|}.d^2$. ◀

Proof of Lemma 5. Let ψ be a witness of d -coverability of (q, n) . We prove that if there is a modular node of height at least $|Q|.d$, or if there exists a height with $2^{|Q|}.d$ different modular nodes, then ψ can be simplified into a smaller witness. These two properties bound the number of modular nodes by $|Q|.2^{|Q|}.d^2$.

Suppose there exists a modular leaf ℓ of height $|\ell| \geq |Q|.d$. The pigeon-hole principle shows that there exist two ancestors $u \prec v$ of ℓ such that $q_u = q_v$ and $n_u \equiv n_v \pmod{d}$. Collapsing the cycle between u and v provides a smaller witness of d -coverability of (q, n) .

Next, suppose that for some h , the number of modular nodes of height h is at least $2^{|Q|}.d$. Since the tree is binary and $d \geq 1$, we deduce that $h \geq |Q|$. Moreover, it follows that there exist d distinct modular nodes t_1, \dots, t_d of height $h - |Q|$ that admit descendants ℓ_1, \dots, ℓ_d that are modular leaves of height at least h . From the pigeon-hole principle, it follows that for every $1 \leq j \leq d$, there exist two modular nodes u_j, v_j such that $t_j \preceq u_j \prec v_j \preceq \ell_j$ and $q_{u_j} = q_{v_j}$. By introducing $z_j = n_{v_j} - n_{u_j}$, Lemma 2 provides a non-empty set $J \subseteq \{1, \dots, d\}$ such that d divides $\sum_{j \in J} z_j$. By collapsing cycles in between u_j and v_j for each $j \in J$, we get a smaller witness of d -coverability of (q, n) . ◀

B Missing proofs of Section 4

Proof of Lemma 13. We have shown in the main text that for all internal nodes t either $Q(tL) < Q(t)$ or $Q(tR) < Q(t)$. Let r be the root of ρ and set $k = Q(r)$. We bound the size of ρ using n and k with the function $f(k, n)$. Consider a root-to-leaf path $v_0 \dots v_\ell$ ($v_0 = r$) that maximizes the function $Q(t)$, and let $(q_i, n_i)_{0 \leq i \leq \ell}$ be the sequence of configurations on this path. Notice that if $q_i = q_j$ for some $i < j$ then $n_i > n_j$ since ρ does not contain any zero or decreasing cycles. Moreover, observe that $n_i \leq n_{i-1} + M$ for every $1 \leq i \leq \ell$. It follows that $n_i \leq n + |Q|.M$ for every $1 \leq i \leq \ell$. We deduce that $\ell \leq (n + |Q|.M).|Q|$. For every v_i let v'_i be its sibling. Similarly we deduce $n_{v'_i} \leq n + |Q|.M$, and by the observation from the first paragraph we know that $Q(v'_i) < k$. We have proved that

$$f(k, n) \leq (n + |Q|.M).|Q|. (1 + f(k - 1, n + |Q|.M)).$$

It follows that

$$f(k, n) \leq \sum_{j=1}^k \prod_{j'=1}^j (n + j' \cdot |Q| \cdot M) \cdot |Q| \leq |Q| \cdot \prod_{j'=1}^{|Q|} (n + j' \cdot |Q| \cdot M) \cdot |Q| \leq |Q| \cdot ((n + |Q|^2 \cdot M) \cdot |Q|)^{|Q|}.$$

To conclude, observe that $n + |Q|^2 \cdot M \leq 2^{|B|} + 2^{2|B|} \cdot M \leq 2^{3|B|}$. \blacktriangleleft

Proof of Lemma 14. We prove by induction on the length of the main branch $\ell \geq 1$ that for every decreasing cycle π there exists a simple decreasing cycle π' such that any state labeling a main node of π' also labels a main node of π , and such that the set of dangling configurations of π' is included in the set of dangling configurations of π . The base case $\ell = 1$ is immediate. Let us assume the lemma proved for cycles with a number of main nodes bounded by ℓ . Now, suppose the length of π is $\ell + 1$, and suppose that π is not simple. Then there exists a simple cycle θ on the main branch of π . If θ is decreasing then we define $\pi' = \theta$. If θ is a zero cycle then we remove θ from π and proceed by induction. Finally, if θ is increasing then we remove it from π , however, this time it could cause a drop below zero. If that is the case we uniformly increase the value of all nodes on the main branch, so they remain nonnegative. The choice of the value added on the main branch is not important. It remains to observe that by removing an increasing cycle from π the obtained cycle remains decreasing, we do not introduce new states on the main branch, and new dangling configurations. We proceed by induction.

Now it remains to prove the lemma when π is a simple d -cycle with $d < 0$. Let v be a minimal node in π and let (q, n) be its label. We decompose π into $\pi_1 \pi_2$ such that π_1 is the fragment of π with the source node v . By a v -rotation of π we understand $\pi' = \pi'_2 \pi'_1$, where π'_1 and π'_2 are obtained from π_1 and π_2 by decreasing all values on the main branch by $n + d$ and n respectively. Since v is minimal, notice that π' is a simple decreasing d -cycle from $(q, -d)$ up to $(q, 0)$ satisfying the lemma. \blacktriangleleft

C Missing proofs of Section 5

Proof of Theorem 15. We prove PSPACE hardness through a polynomial time reduction from the validity problem for Quantified Boolean Formulas. Suppose we are given a QBF sentence of the form

$$\varphi = \forall Q_1 \exists P_1 \dots \forall Q_n \exists P_n \bigwedge_{i \in \{1, \dots, \ell\}} \bigvee_{j \in \{1, \dots, m\}} V_{i,j}$$

where $n, \ell, m \in \mathbb{N}$ and $V_{i,j} \in \mathcal{V}$ for $\mathcal{V} = \{Q_1, P_1, \dots, Q_n, P_n, \neg Q_1, \neg P_1, \dots, \neg Q_n, \neg P_n\}$ for all i, j . We will show how to construct, in polynomial time, a 1BVASS \mathcal{B} so that its configuration $(q_1, 0)$ is reachable if and only if φ is valid. To simplify our construction we will assume that $\ell = 2^{\ell'}$ for some ℓ' —this is without loss of generality since one can always add conjuncts $P_1 \vee \neg P_1$ in order to complete to a power of 2. Let $\mathcal{S} \subseteq 2^{\{1, \dots, \ell\}}$ be the smallest set satisfying: (i) $\{1, \dots, \ell\} \in \mathcal{S}$, and (ii) if $\{i, \dots, j\} \in \mathcal{S}$ with $i < j$ then $\{i, \dots, (i+j-1)/2\} \in \mathcal{S}$ and $\{(i+j+1)/2, \dots, j\} \in \mathcal{S}$. Note that $|\mathcal{S}| = 2\ell - 1$.

For this reduction it is convenient to make use of ‘unary’ transitions of the form $(p, z, q) \in Q \times \mathbb{Z} \times Q$ as short for (p, q_L, z, q) , and ‘binary’ transitions of the form $(q_L, q_R, q) \in Q \times Q \times Q$ as short for $(q_L, q_R, 0, q)$. These are the only two kinds of transitions we will use. Further, in the context of this proof it seems more natural to see the run as *top-down* since we would like to think that information flows downwards in the run, as information about all possible



■ **Figure 3** Separation into bitstring blocks of the binary representation of values.

variables valuations to test will be built incrementally by traversing each branch downwards. Thus, when we say that we ‘increase’ a value z from a state q to a state q' we are implicitly making reference to a unary transition of the form $(q', -z, q)$.

The 1BVASS $\mathcal{B} = (Q, \delta, \{q_I\})$ we define has a set of states Q consisting of

- states $q_i, q_i^\top, q_i^\perp, p_i$ for $i \in \{1, \dots, n\}$, which will be used to encode all valuations that need to be tested for;
- states s_S for $S \in \mathcal{S}$ to consider all possible conjuncts $\bigvee_j V_{ij}$ —the idea being that each distinct $s_{\{i\}}$ will appear in a different branch of the run;
- states r_i^V and \hat{r}_i^V for all $i \in \{1, \dots, n\}$ and $V \in \mathcal{V}$, which will ensure that for the conjunct considered in the branch there is a disjunct which is satisfied by the current valuation;
- the state q_I , which is the only initial state.

As we will see, \mathcal{B} forces runs whose every branch has exactly $n' = n + \ell'$ binary rules: the first n to encode all possible valuations induced by $\forall Q_1, \dots, \forall Q_n$, and the last ℓ' to encode every possible choice among the ℓ conjuncts —since we are in a binary tree, the ℓ possibilities will be encoded using subtrees of height $\log(\ell) = \ell'$.

We make use of $4n \cdot n'$ bits of the binary representation. A 1-bit among the first n' most significant bits $\{1, \dots, n'\}$ encodes a valuation for Q_1 being true, a 1-bit among $\{n' + 1, \dots, 2n'\}$ encodes Q_1 being false; $\{2n' + 1, \dots, 3n'\}$ encodes P_1 being true; $\{3n' + 1, \dots, 4n'\}$ encodes P_1 being false; $\{4n' + 1, \dots, 5n'\}$ encodes Q_2 being false; etc. Figure 3 depicts the different blocks of bits assigned to each valuation of a propositional variables (ignore the bottom line of $|_i$ for now).

In light of this coding, we define constants c_j^V to denote the number that has a 1-bit in the j -th least significant bit of the block corresponding to V . Formally, we define for every i, j :

- $c_j^{Q_i} = 2^{4n'(n-i)+j-1}$,
- $c_j^{\neg Q_i} = 2^{4n'(n-i)+n+j-1}$,
- $c_j^{P_i} = 2^{4n'(n-i)+2n+j-1}$,
- $c_j^{\neg P_i} = 2^{4n'(n-i)+3n+j-1}$.

For example, $c_j^{\neg P_i}$ is the value having the j -th least significant bit of the block for $\neg P_i$ set in one.

Finally, the transitions of δ are the following:

- $(q_i^\top, q_i^\perp, q_i)$, $(p_i, -c_{n'-i+1}^{Q_i}, q_i^\top)$, and $(p_i, -c_{n'-i+1}^{\neg Q_i}, q_i^\perp)$ for every i ; that is, from q_i we always split the counter into children q_i^\top and q_i^\perp and we turn the $(n' - i + 1)$ -th bit to 1 for the representation of Q_i or $\neg Q_i$ respectively —this corresponds to the universal quantifier ‘ $\forall Q_i$ ’ demanding both partial valuations to be considered.
- $(q_{i+1}, -c_{n'-i+1}^{P_i}, p_i)$ and $(q_{i+1}, -c_{n'-i+1}^{\neg P_i}, p_i)$ for every $i < n$; that is, from p_i we descend to q_{i+1} by nondeterministically choosing between turning the $(n' - i + 1)$ -th bit of P_i or that of $\neg P_i$ —this corresponds to the existential choice ‘ $\exists P_i$ ’.

- $(s_{\{1,\dots,\ell\}}, -c_{n'-n+1}^{P_n}, p_n)$ and $(s_{\{1,\dots,\ell\}}, -c_{n'-n+1}^{\neg P_n}, p_n)$; that is, when we finished with the valuation building phase of $q_i, q_i^\top, q_i^\perp, p_i$, we pass to the satisfaction phase of the s_S 's.
- $(s_{\{i_1,\dots,i_2\}}, s_{\{i_2+1,\dots,i_3\}}, s_{\{i_1,\dots,i_3\}})$ for every $i_1 \leq i_2 \leq i_3$ with $i_1 < i_3$ and $\{i_1, \dots, i_2\}, \{i_2+1, \dots, i_3\}, \{i_1, \dots, i_3\} \in \mathcal{S}$; this encodes the complete binary tree of height ℓ' needed to take into account all possible conjuncts.
- $(r_1^{V_{ij}}, 0, s_{\{i\}})$ for all i, j ; that is, we choose which disjunct j will be the witness for conjunct i .
- Finally, from $r_1^{V_{ij}}$ we have a series of unary transitions that decrement the first bit corresponding to R or the first bit of $\neg R$ for every $R \in \{Q_1, P_1, \dots, Q_n, P_n\}$, except for the propositional variable of V_{ij} for which only the first bit corresponding to the block of V_{ij} is decremented. Concretely, for every i and $V \in \mathcal{V}$ we have transitions
 - $(\hat{r}_i^V, c_1^{Q_i}, r_i^V)$ if $V \neq \neg Q_i$,
 - $(\hat{r}_i^V, c_1^{\neg Q_i}, r_i^V)$ if $V \neq Q_i$,
 - $(r_{i+1}^V, c_1^{P_i}, \hat{r}_i^V)$ if $V \neq \neg P_i$,
 - $(r_{i+1}^V, c_1^{\neg P_i}, \hat{r}_i^V)$ if $V \neq P_i$,
 - $(q_i, c_1^{P_i}, \hat{r}_i^V)$ if $V \neq \neg P_i$,
 - $(q_i, c_1^{\neg P_i}, \hat{r}_i^V)$ if $V \neq P_i$.

Let ρ be a complete run of \mathcal{B} whose root label is $(q_1, 0)$. The crucial property of ρ in order to verify that the reduction works, is that *all binary transitions split the value in two halves*. To show this, we will need to reason inductively on the blocks of n' -bit substrings of the binary representation of the values in ρ . The inductive idea is that that there cannot be an uneven split affecting the most significant block, and further that there cannot be an uneven split affecting the i -th most significant block, assuming that all other strictly more significant blocks are unaffected.

For $z \in \mathbb{N}$, let $z \upharpoonright_i \in \{0, \dots, 2^{n'} - 1\}$ be the number represented by the bits $\{n'(i-1) + 1, \dots, n'i\}$ of the binary representation of z (where the bit 1 is the most significant one). Thus, $z \upharpoonright_1$ is the number denoted by the n' most significant bits of z , $z \upharpoonright_2$ is the one denoted by the following block of n' bits, and so on. Figure 3 depicts the block numbers. Note that for any value z in ρ , $z = z \upharpoonright_{4n} + 2^{n'} \cdot z \upharpoonright_{4n-1} + \dots + 2^{4nn'-n'} \cdot z \upharpoonright_1$.

The following statement follows straight from the definition of the transitions on the r_j 's and s_j 's.

► **Claim 15.1.** For every node t of ρ labelled with a state r_1^V , $V \in \mathcal{V}$, and for every $i \in \{1, \dots, 4n\}$, $k \leq n$ we have that the $4n'k$ least significant bits of n_t encode a value

$$n_t \upharpoonright_k = c_1^{V_{n-s+1}} + c_1^{V'_{n-s+1}} + c_1^{V_{n-s}} + c_1^{V'_{n-s}} + \dots + c_1^{V_n} + c_1^{V'_n}$$

for some choice $V_i \in \{Q_i, \neg Q_i\}$ and $V'_i \in \{P_i, \neg P_i\}$ for each i . In particular,

$$n_t \upharpoonright_k \leq c_1^{Q_1} + c_1^{P_1} + \dots + c_1^{Q_n} + c_1^{P_n}$$

by definition of the constants c_i^V 's.

Thus, the configuration of the r_j^V 's contain only 1's and 0's in the blocks. As a consequence of this, every binary transition of the q_j 's evenly splits the blocks among the children, as stated next.

► **Claim 15.2.** For every node t of ρ with no q_I -labeled child and for every $i \in \{1, \dots, 4n\}$ we have $n_t \upharpoonright_i = 2 \cdot n_{tL} \upharpoonright_i = 2 \cdot n_{tR} \upharpoonright_i$. In particular, $n_{tL} = n_{tR}$.

To see this suppose, my means of contradiction, that it is not true. Let i be minimal so that the property does not hold, and let t be a \prec -minimal node contradicting the property on i . Let us assume that $n_{tL} \upharpoonright_i > n_{tR} \upharpoonright_i$ —the case $n_{tL} \upharpoonright_i < n_{tR} \upharpoonright_i$ is equivalent. By definition of \mathcal{B} , the state of tL is either: (1) s_S for some S , or (2) q_j^\top for some j . Note that $n_t \upharpoonright_i \neq 0$ since otherwise either t would verify the condition, or i would not be minimal. Further, $n_t \upharpoonright_i = 2^{n'-k}$ for $k = j$ in the case (1) or $k = n + \ell' - \log(|S|)$ in the case (2). Since $n_{tL} \upharpoonright_i > n_{tR} \upharpoonright_i$ and $n_{tL} \upharpoonright_{i'} = n_{tR} \upharpoonright_{i'}$ for all $i' < i$ by minimality of i , necessarily we have that

$$n_{tL} \upharpoonright_i \cdot 2^{4in'} + \dots + n_{tL} \upharpoonright_{4n-1} \cdot 2^{4n'} + n_{tL} \upharpoonright_{4n} \cdot 2^0 > 2^{n-k-1} \cdot 2^{4in'}.$$

We now follow from tL a downward path until finding a node t' with state r_1^V for some $V \in \mathcal{V}$. Let π be such a path, obtained by always choosing the largest value of the configuration at every split. It then follows that $n_{t'}$ is *too large* to be reachable, that is,

$$2^{4in'-n'} \cdot n_{t'} \upharpoonright_{4n} + \dots + 2^{4nn'-n'} \cdot n_{t'} \upharpoonright_{4i} > c_1^{Q_i} + c_1^{P_i} + \dots + c_1^{Q_n} + c_1^{P_n}.$$

This is in contradiction with our previous claim, and therefore all binary transitions split the value in halves.

Using the fact that all binary transitions split evenly the value or, in other words, have the effect of producing a ‘right-shift’ on the bitstring representing the value, it is straightforward to verify that $(q_1, 0)$ is reachable on \mathcal{B} if and only if φ is valid. ◀

D A different presentation?

Let us fix a 1BVASS $\mathcal{B} = (Q, \Delta, I)$, and let M be its absolute maximum displacement.

A *first decreasing run* is a run so that every branch contains at most one decreasing cycle, and every leaf not labelled $(q_I, 0)$ is the target of a decreasing cycle. If further all decreasing cycles are simple, we say that it is a first *simple* decreasing run. The *first decreasing prefix* (*f-d prefix* for short) of a complete run is the maximal prefix that is a first decreasing run, that is, the result of removing all nodes strictly below a decreasing cycle. We say that a node is *internal* to the f-d prefix if it is an internal node of the f-d prefix.

► **Lemma 16.** *For every minimal complete run for $(q_F, 0)$, its f-d prefix is of size at most exponential in \mathcal{B} .*

Proof. First observe that any cycle (t, t') in a minimal run internal to the f-d prefix has to be, necessarily, strictly increasing. In the context of a run, let $Q(t) \subseteq Q$ be the set of all states q_v appearing at strict descendants $v \succ t$ which are internal to the f-d prefix. We show that there is a minimal run whose every node t verifies

$$\text{if } tL \text{ or } tR \text{ are internal to the f-d prefix, } Q(tL) \subsetneq Q(t) \text{ or } Q(tR) \subsetneq Q(t). \quad (\dagger)$$

Let ρ be a minimal complete run for $(q_F, 0)$ of size N . Let $(s_i)_{i \leq N}$ be a vector of numbers so that its i -th component has the sum of all n_{tR} for every node t of height i internal to the f-d prefix. Consider the alphabetical ordering on these vectors. Let t be a node internal to the prefix not satisfying (\dagger) , that is, so that $Q(tL) = Q(t) = Q(tR)$. Then, there is some $r \succ tR$ and some $l \succ tL$ internal to the prefix with $q_{tR} = q_r = q_l$. Let ρ_l [resp. ρ_r] be the subrun of ρ rooted at l [resp. at r]. There are two possibilities, either $n_r > n_l$ or $n_r \leq n_l$. In the first case, we can safely swap the subrun ρ_l rooted at l with the subrun rooted at tR ; in the second case we can plug the subrun ρ_r at node tR , and insert the concatenation $\pi\rho_l$ at position l , where, π is the context between tR and r . Observe that in both cases:

(1) the size of the run remains unchanged and thus the dimension of $(s_i)_i$, (2) the value of n_{tR} strictly decreases, (3) the reordering of the run is only internal to the subtree rooted at t , and (4) in both cases the value of n_t remains unchanged. Due to (2), (3) we have that the value of $s_{|t|}$ strictly decreases while due to (3), (4) we have that s_i remains unchanged for all $i < |t|$. We can therefore apply this procedure a finite number of times since the alphabetical ordering is a well ordering, until we finish with a minimal run that verifies (\dagger) for all nodes of the strict f-d prefix.

For any f-d prefix with property (\dagger) , if it is sufficiently big (bigger than an exponential bound) it must have an exponentially long branch. Since values of runs are exponentially bounded, this means that once we collapsed all 0-cycles we obtain an exponential run. ◀

A *reachability witness* is a first simple decreasing run so that every leaf t labelled $(q, m) \neq (q_I, 0)$ which is the target of a d -decreasing cycle (t', t) contains a d -coverability witness for $(q_{t'}, n_{t'})$.

► **Lemma 17.** *Tfae*

1. *There is a complete run for (q_F, n) .*
2. *There is a reachability witness for (q_F, n) .*

1 \Rightarrow 2. Take any minimal complete run ρ for (q_F, n) and consider its f-d prefix ρ' , where we attach a d -coverability witness for $(q_{t'}, n_{t'})$ to every non-initial leaf t being the target of a d -decreasing cycle (t', t) . Note that, however, this may still not be a reachability witness since it may contain non-simple decreasing cycles. We build a reachability witness from ρ' which will preserve the prefix given by all the sources of decreasing cycles. Suppose then that there is a non-initial leaf t which is the target of a d -decreasing cycle (t', t) which is not simple. Then, there are $t' \preceq \hat{t}' \prec \hat{t} \prec t$ so that $q_{\hat{t}'} = q_{\hat{t}}$ and $n_{\hat{t}'} \geq n_{\hat{t}}$. Consider the result of removing the cycle (\hat{t}', \hat{t}) , and incrementing all the values of nodes between \hat{t} and t of an amount $\delta = n_{\hat{t}'} - n_{\hat{t}}$, and attaching a $(d + \delta)$ -coverability witness for $(q_{t'}, n_{t'})$ at the leaf (since $(q_{t'}, n_{t'})$ is reachable as witnessed by ρ , it is d -coverable for every d). xxxx

[2 \Rightarrow 1]

◀

In the context of any $(Q \times \mathbb{N})$ -labelled tree (not necessarily a run), a decreasing cycle [resp. increasing cycle] is a pair of nodes $t < t'$ so that $q_t = q_{t'}$ and $n_{t'} > n_t$ [resp. $n_t < n_{t'}$]. A *minimal decreasing cycle* is the first decreasing simple cycle that appears in a branch from the root. In particular, the target node of a minimal decreasing cycle is a leaf of the f-d prefix of the run. If the effect of a minimal decreasing cycle is $-d$ we say that it is a *minimal d-decreasing cycle*. We say that a node v is *under* a cycle (t, t') if $t' \preceq v$ and *strictly above* if $v \prec t$.

A node t that is under a minimal d -decreasing cycle and strictly over an increasing cycle is called a *mod- d node*; a *mod node* is a mod- d node for some d . Note that any mod node is a mod- d node for exactly one $d \in \mathbb{N}$ due to minimality.

A *reachability witness* for $(q_F, 0)$ is a $(Q \times \mathbb{N})$ -labelled tree with root label $(q_F, 0)$, leaves with label from $I \times \{0\}$, and so that for every internal node t there is a transition $(q', q'', c, q) \in \Delta$ so that

- $q_t = q, q_{tL} = q', q_{tR} = q'',$
- if t is not a mod node, $n_{tL} + n_{tR} + c = n_t,$
- if t is a mod- d node, $n_{tL} + n_{tR} + c \equiv n_t \pmod{d}.$

► **Lemma 18.** *Tfae*

1. *There is a complete run for (q_F, n) .*

2. *There is a reachability witness for (q_F, n) .*

Proof. For $[1 \Rightarrow 2]$, simply observe that a complete run for $(q_F, 0)$ is in particular a reachability witness for $(q_F, 0)$. On the other hand, $[2 \Rightarrow 1]$ might require that minimal decreasing cycles and maximal increasing cycles are ‘pumped’ in order to obtain a complete run. Take a reachability witness and label each \prec -minimal mod node t with ℓ_v^d , where (v, t) is a simple d -decreasing cycle (the only one possible). We say that a witness *excludes* ℓ_v^d if it has no nodes with that label. Note that:

1. All ℓ -labeled nodes are at incomparable positions.
2. Every ℓ_v^d -labelled node t is the target of a d -decreasing simple cycle.
3. Every subtree rooted at a node that is incomparable with all ℓ -labelled nodes is a run.

These properties will remain invariant through the procedure we describe next. Consider a label ℓ_v^d in the tree, so that v is of minimal height (that is, there is no label $\ell_{v'}^d$ for $v' \prec v$). Suppose that ℓ_v^d occurs at a node t . By property 2, consider the node t' so that (t', t) is a d -decreasing simple cycle. We can now replace the sub-witness at t with another sub-witness that excludes ℓ_v^d (and does not include any new labels of course), and with the same value n_t and state q_t . In order to achieve this, we first remove the label ℓ_v^d from t and replace the sub-witness rooted at t with a witness that excludes ℓ_v^d , by iterating the d -decreasing cycle (t', t) as well as all the maximal increasing cycles below t a number of times, and replacing the mod- d nodes with the corresponding value. When iterating, the ℓ -labels possibly present at dangling subtrees are also copied, so we can end up with a sub-witness with possibly more nodes being labelled, but with no label ℓ_v^d . It is easy to see that property 1 and 3 are preserved. The fact that property 2 is preserved is a consequence of v being \prec -minimal: when iterating we are copying complete simple cycles. We do the same for all ℓ_v^d -labelled nodes, until there are no more ℓ_v^d -labelled nodes, ending up with a witness excluding ℓ_v^d . We repeat the procedure until there are no more labels to exclude and, by property 3, we obtain a complete run. ◀

► **Lemma 19.** *Any minimal reachability witness for $(q_F, 0)$ is of size at most exponential.*

Proof. Due to Lemma 16, we can assume that the f-d prefix of the witness is at most of exponential size.

On the other hand, any subrun rooted at a child of a \prec -maximal mod node does not contain increasing cycles,

xxx

child of a mod node does not contain an increasing cycle (otherwise it would be a mod node). Further, it cannot contain d non-overlapping decreasing cycles, as otherwise we could collapse some of them while maintaining the value modulo d , due to Lemma 2. Since $d < |Q| \cdot M$, this means that the size of such subrun is at most of exponential size.

Further, any “middle tree” below a minimal decreasing cycle and not above a maximal increasing cannot contain d disjoint cycles, as otherwise we could collapse them due to Lemma 2. ◀

► **Lemma 20.** *There is a PSpace algorithm to test if a configuration (q_F, n) has a reachability witness of some exponentially-bounded size.*

► **Corollary 21.** *The reachability problem for 1BVASS is in PSpace.*