

# Efficient Inclusion for a Class of XML Types with Interleaving and Counting

D. Colazzo, G. Ghelli, C. Sartiani

1st Codex meeting

- Essential tool to check and enforce safety and correctness of XML applications.

- Essential tool to check and enforce safety and correctness of XML applications.
- Schema inclusion and schema equality are the main ingredients of any kind of static analysis.

- Essential tool to check and enforce safety and correctness of XML applications.
- Schema inclusion and schema equality are the main ingredients of any kind of static analysis.
- Schema inclusion is PSPACE (or EXPTIME for Extended DTDs) complete when only ordered types are adopted (like in DTDs)

- Essential tool to check and enforce safety and correctness of XML applications.
- Schema inclusion and schema equality are the main ingredients of any kind of static analysis.
- Schema inclusion is PSPACE (or EXPTIME for Extended DTDs) complete when only ordered types are adopted (like in DTDs)

# Counting and interleaving

- Type mechanisms considered in Regular Expressions (REs) for XML Schema and Relax-NG

# Counting and interleaving

- Type mechanisms considered in Regular Expressions (REs) for XML Schema and Relax-NG
- The only presence of interleaving makes RE inclusion EXPSPACE complete!

# Counting and interleaving

- Type mechanisms considered in Regular Expressions (REs) for XML Schema and Relax-NG
- The only presence of interleaving makes RE inclusion EXPSPACE complete!
- Mayer and Stockmeyer showed that counting is not necessary for EXPSPACE completeness.



# Counting and interleaving

- Type mechanisms considered in Regular Expressions (REs) for XML Schema and Relax-NG
- The only presence of interleaving makes RE inclusion EXPSPACE complete!
- Mayer and Stockmeyer showed that counting is not necessary for EXPSPACE completeness.
- A recent ICDT paper by Gelade, Martens, and Neven left an open problem “It would therefore be desirable to find *robust subclasses* for which the basic decision problems are in PTIME”.

# Counting and interleaving

- Type mechanisms considered in Regular Expressions (REs) for XML Schema and Relax-NG
- The only presence of interleaving makes RE inclusion EXPSPACE complete!
- Mayer and Stockmeyer showed that counting is not necessary for EXPSPACE completeness.
- A recent ICDT paper by Gelade, Martens, and Neven left an open problem “It would therefore be desirable to find *robust subclasses* for which the basic decision problems are in PTIME”.
- This work: a first answer to this question.

# Counting and interleaving

- Type mechanisms considered in Regular Expressions (REs) for XML Schema and Relax-NG
- The only presence of interleaving makes RE inclusion EXPSPACE complete!
- Mayer and Stockmeyer showed that counting is not necessary for EXPSPACE completeness.
- A recent ICDT paper by Gelade, Martens, and Neven left an open problem “It would therefore be desirable to find *robust subclasses* for which the basic decision problems are in PTIME”.
- This work: a first answer to this question.

# Our robust subclass : Conflict-Free types

- We focus on REs, and prove that inclusion between two *Conflict-Free* REs  $T$  and  $U$  can be checked polynomial time (more precisely in  $O(|T| * |U| + |U|^2)$  time)

# Our robust subclass : Conflict-Free types

- We focus on REs, and prove that inclusion between two *Conflict-Free* REs  $T$  and  $U$  can be checked polynomial time (more precisely in  $O(|T| * |U| + |U|^2)$  time)
- The result (polynomial complexity) directly extends to C-F XML schemas thanks to a recent result by Gelade, Martens, and Neven :

# Our robust subclass : Conflict-Free types

- We focus on REs, and prove that inclusion between two *Conflict-Free* REs  $T$  and  $U$  can be checked polynomial time (more precisely in  $O(|T| * |U| + |U|^2)$  time)
- The result (polynomial complexity) directly extends to C-F XML schemas thanks to a recent result by Gelade, Martens, and Neven :
  - if inclusion for a given class of **REs** with interleaving and numerical constraints is in the complexity class  $\mathcal{C}, \dots$

# Our robust subclass : Conflict-Free types

- We focus on REs, and prove that inclusion between two *Conflict-Free* REs  $T$  and  $U$  can be checked polynomial time (more precisely in  $O(|T| * |U| + |U|^2)$  time)
- The result (polynomial complexity) directly extends to C-F XML schemas thanks to a recent result by Gelade, Martens, and Neven :
  - if inclusion for a given class of **REs** with interleaving and numerical constraints is in the complexity class  $\mathcal{C}$ ,...
  - ..and  $\mathcal{C}$  is *closed under positive reductions* (a property enjoyed by PTIME),..

# Our robust subclass : Conflict-Free types

- We focus on REs, and prove that inclusion between two *Conflict-Free* REs  $T$  and  $U$  can be checked polynomial time (more precisely in  $O(|T| * |U| + |U|^2)$  time)
- The result (polynomial complexity) directly extends to C-F XML schemas thanks to a recent result by Gelade, Martens, and Neven :
  - if inclusion for a given class of **REs** with interleaving and numerical constraints is in the complexity class  $\mathcal{C}$ ,...
  - ..and  $\mathcal{C}$  is *closed under positive reductions* (a property enjoyed by PTIME),...
  - .. then the complexity of inclusion for DTDs and single-type EDTDs that use the same class of REs is in  $\mathcal{C}$  too
- Single-type EDTDs are the theoretical counterpart of XML Schema definitions.



# Our robust subclass : Conflict-Free types

- We focus on REs, and prove that inclusion between two *Conflict-Free* REs  $T$  and  $U$  can be checked polynomial time (more precisely in  $O(|T| * |U| + |U|^2)$  time)
- The result (polynomial complexity) directly extends to C-F XML schemas thanks to a recent result by Gelade, Martens, and Neven :
  - if inclusion for a given class of **REs** with interleaving and numerical constraints is in the complexity class  $\mathcal{C}$ ,...
  - ..and  $\mathcal{C}$  is *closed under positive reductions* (a property enjoyed by PTIME),...
  - .. then the complexity of inclusion for DTDs and single-type EDTDs that use the same class of REs is in  $\mathcal{C}$  too
- Single-type EDTDs are the theoretical counterpart of XML Schema definitions.

# Conflict-Free REs, first restriction

$$T ::= \epsilon \mid a[m..n] \mid T + T \mid T \cdot T \mid T \& T \mid T!$$

# Conflict-Free REs, first restriction

$$T ::= \epsilon \mid a[m..n] \mid T + T \mid T \cdot T \mid T \& T \mid T!$$

$$\llbracket \epsilon \rrbracket = \{\epsilon\}$$

# Conflict-Free REs, first restriction

$$T ::= \epsilon \mid a[m..n] \mid T + T \mid T \cdot T \mid T \& T \mid T!$$

$$\llbracket \epsilon \rrbracket = \{\epsilon\}$$

$$\llbracket a[m..n] \rrbracket = \{w \mid S(w) = \{a\}, m \leq |w| \leq n\}$$

# Conflict-Free REs, first restriction

$$T ::= \epsilon \mid a[m..n] \mid T + T \mid T \cdot T \mid T \& T \mid T!$$

$$\llbracket \epsilon \rrbracket = \{\epsilon\}$$

$$\llbracket a[m..n] \rrbracket = \{w \mid S(w) = \{a\}, m \leq |w| \leq n\}$$

$$\llbracket T_1 + T_2 \rrbracket = \llbracket T_1 \rrbracket \cup \llbracket T_2 \rrbracket$$

# Conflict-Free REs, first restriction

$$T ::= \epsilon \mid a[m..n] \mid T + T \mid T \cdot T \mid T \& T \mid T!$$

$$\llbracket \epsilon \rrbracket = \{\epsilon\}$$

$$\llbracket a[m..n] \rrbracket = \{w \mid S(w) = \{a\}, m \leq |w| \leq n\}$$

$$\llbracket T_1 + T_2 \rrbracket = \llbracket T_1 \rrbracket \cup \llbracket T_2 \rrbracket$$

$$\llbracket T_1 \cdot T_2 \rrbracket = \llbracket T_1 \rrbracket \cdot \llbracket T_2 \rrbracket$$

# Conflict-Free REs, first restriction

$$T ::= \epsilon \mid a[m..n] \mid T + T \mid T \cdot T \mid T \& T \mid T!$$

$$\llbracket \epsilon \rrbracket = \{\epsilon\}$$

$$\llbracket a[m..n] \rrbracket = \{w \mid S(w) = \{a\}, m \leq |w| \leq n\}$$

$$\llbracket T_1 + T_2 \rrbracket = \llbracket T_1 \rrbracket \cup \llbracket T_2 \rrbracket$$

$$\llbracket T_1 \cdot T_2 \rrbracket = \llbracket T_1 \rrbracket \cdot \llbracket T_2 \rrbracket$$

$$\llbracket T! \rrbracket = \llbracket T \rrbracket \setminus \{\epsilon\}$$

# Conflict-Free REs, first restriction

$$T ::= \epsilon \mid a[m..n] \mid T + T \mid T \cdot T \mid T \& T \mid T!$$

$$\llbracket \epsilon \rrbracket = \{\epsilon\}$$

$$\llbracket a[m..n] \rrbracket = \{w \mid S(w) = \{a\}, m \leq |w| \leq n\}$$

$$\llbracket T_1 + T_2 \rrbracket = \llbracket T_1 \rrbracket \cup \llbracket T_2 \rrbracket$$

$$\llbracket T_1 \cdot T_2 \rrbracket = \llbracket T_1 \rrbracket \cdot \llbracket T_2 \rrbracket$$

$$\llbracket T! \rrbracket = \llbracket T \rrbracket \setminus \{\epsilon\}$$

$$\llbracket T_1 \& T_2 \rrbracket = \llbracket T_1 \rrbracket \& \llbracket T_2 \rrbracket$$



# Conflict-Free REs, first restriction

$$T ::= \epsilon \mid a[m..n] \mid T + T \mid T \cdot T \mid T \& T \mid T!$$

$$\llbracket \epsilon \rrbracket = \{\epsilon\}$$

$$\llbracket a[m..n] \rrbracket = \{w \mid S(w) = \{a\}, m \leq |w| \leq n\}$$

$$\llbracket T_1 + T_2 \rrbracket = \llbracket T_1 \rrbracket \cup \llbracket T_2 \rrbracket$$

$$\llbracket T_1 \cdot T_2 \rrbracket = \llbracket T_1 \rrbracket \cdot \llbracket T_2 \rrbracket$$

$$\llbracket T! \rrbracket = \llbracket T \rrbracket \setminus \{\epsilon\}$$

$$\llbracket T_1 \& T_2 \rrbracket = \llbracket T_1 \rrbracket \& \llbracket T_2 \rrbracket$$

Example :

$$\{ab\} \& \{XY\} = \{abXY, aXbY, aXYb, XabY, XaYb, XYab\}$$

permutations must respect order-constraints !  $XbYa \notin \{ab\} \& \{XY\}$

# Conflict-Free REs, second restriction

**[Conflict-free types]** A type  $T$  is *conflict-free* if for any two distinct subterms  $a[m..n]$  and  $a'[m'..n']$  that occur in  $T$ ,  $a$  is different from  $a'$ .

# Conflict-Free REs, second restriction

**[Conflict-free types]** A type  $T$  is *conflict-free* if for any two distinct subterms  $a[m..n]$  and  $a'[m'..n']$  that occur in  $T$ ,  $a$  is different from  $a'$ .

Examples:

- $(a[1..1] \& b[1..1]) + (a[1..1] \& c[1..1])$  is not CF

# Conflict-Free REs, second restriction

**[Conflict-free types]** A type  $T$  is *conflict-free* if for any two distinct subterms  $a[m..n]$  and  $a'[m'..n']$  that occur in  $T$ ,  $a$  is different from  $a'$ .

Examples:

- $(a[1..1] \& b[1..1]) + (a[1..1] \& c[1..1])$  is not CF
- The equivalent type  $a[1..1] \& (b[1..1] + c[1..1])$  is CF.

# Coding most used REs

- As shown in several recent papers, the *single occurrence* property is enjoyed by most XML schemas

# Coding most used REs

- As shown in several recent papers, the *single occurrence* property is enjoyed by most XML schemas
- Repetition types  $T^*$  or  $T^+$  are generalised by counting, which, is, however, restricted to symbols, so that, for example, types like  $(a \cdot b)^*$  cannot be expressed.

# Coding most used REs

- As shown in several recent papers, the *single occurrence* property is enjoyed by most XML schemas
- Repetition types  $T^*$  or  $T^+$  are generalised by counting, which, is, however, restricted to symbols, so that, for example, types like  $(a \cdot b)^*$  cannot be expressed.
- However, it has been found that DTD and XSD schemas use repetition almost exclusively as  $a^{\text{op}}$  or as  $(a + \dots + z)^{\text{op}}$

# Coding most used REs

- As shown in several recent papers, the *single occurrence* property is enjoyed by most XML schemas
- Repetition types  $T^*$  or  $T^+$  are generalised by counting, which, is, however, restricted to symbols, so that, for example, types like  $(a \cdot b)^*$  cannot be expressed.
- However, it has been found that DTD and XSD schemas use repetition almost exclusively as  $a^{\text{op}}$  or as  $(a + \dots + z)^{\text{op}}$
- $(a + \dots + z)^*$  can be expressed as  $(a^* \& \dots \& z^*)$ , where  $a^*$  is a shortcut for  $a[1..*] + \epsilon$



# Coding most used REs

- As shown in several recent papers, the *single occurrence* property is enjoyed by most XML schemas
- Repetition types  $T^*$  or  $T^+$  are generalised by counting, which, is, however, restricted to symbols, so that, for example, types like  $(a \cdot b)^*$  cannot be expressed.
- However, it has been found that DTD and XSD schemas use repetition almost exclusively as  $a^{\text{op}}$  or as  $(a + \dots + z)^{\text{op}}$
- $(a + \dots + z)^*$  can be expressed as  $(a^* \& \dots \& z^*)$ , where  $a^*$  is a shortcut for  $a[1..*] + \epsilon$
- $(a + \dots + z)^+$  can be expressed as  $(a^* \& \dots \& z^*)!$ .

# Coding most used REs

- As shown in several recent papers, the *single occurrence* property is enjoyed by most XML schemas
- Repetition types  $T^*$  or  $T^+$  are generalised by counting, which, is, however, restricted to symbols, so that, for example, types like  $(a \cdot b)^*$  cannot be expressed.
- However, it has been found that DTD and XSD schemas use repetition almost exclusively as  $a^{\text{op}}$  or as  $(a + \dots + z)^{\text{op}}$
- $(a + \dots + z)^*$  can be expressed as  $(a^* \& \dots \& z^*)$ , where  $a^*$  is a shortcut for  $a[1..*] + \epsilon$
- $(a + \dots + z)^+$  can be expressed as  $(a^* \& \dots \& z^*)!$ .

# Coding most used REs

- As shown in several recent papers, the *single occurrence* property is enjoyed by most XML schemas
- Repetition types  $T^*$  or  $T^+$  are generalised by counting, which, is, however, restricted to symbols, so that, for example, types like  $(a \cdot b)^*$  cannot be expressed.
- However, it has been found that DTD and XSD schemas use repetition almost exclusively as  $a^{\text{op}}$  or as  $(a + \dots + z)^{\text{op}}$
- $(a + \dots + z)^*$  can be expressed as  $(a^* \& \dots \& z^*)$ , where  $a^*$  is a shortcut for  $a[1..*] + \epsilon$
- $(a + \dots + z)^+$  can be expressed as  $(a^* \& \dots \& z^*)!$ .

Hence, C-F types cover a wide class of REs used in human-designed XML schema.

# Main ingredient : Types as constraints

We transform each CF type into an equivalent set of constraints.

# Main ingredient : Types as constraints

We transform each CF type into an equivalent set of constraints.

For instance, consider  $T = (a[1..3] \cdot b[2..2]) + c[1..2]$ , and  $w \in \llbracket T \rrbracket$ :

# Main ingredient : Types as constraints

We transform each CF type into an equivalent set of constraints.

For instance, consider  $T = (a[1..3] \cdot b[2..2]) + c[1..2]$ , and  $w \in \llbracket T \rrbracket$ :

- ❶ **lower-bound**: at least one of  $a$ ,  $b$ , and  $c$  appears in  $w$ ;

# Main ingredient : Types as constraints

We transform each CF type into an equivalent set of constraints.

For instance, consider  $T = (a[1..3] \cdot b[2..2]) + c[1..2]$ , and  $w \in \llbracket T \rrbracket$ :

- ❶ **lower-bound**: at least one of  $a$ ,  $b$ , and  $c$  appears in  $w$ ;
- ❷ **cardinality**: if  $a$  is in  $w$ , it appears 1, 2 or 3 times; if  $b$  is there, it appears twice; if  $c$  is there, it appears once or twice;

# Main ingredient : Types as constraints

We transform each CF type into an equivalent set of constraints.

For instance, consider  $T = (a[1..3] \cdot b[2..2]) + c[1..2]$ , and  $w \in \llbracket T \rrbracket$ :

- ❶ **lower-bound**: at least one of  $a$ ,  $b$ , and  $c$  appears in  $w$ ;
- ❷ **cardinality**: if  $a$  is in  $w$ , it appears 1, 2 or 3 times; if  $b$  is there, it appears twice; if  $c$  is there, it appears once or twice;
- ❸ **upper-bound**: no symbol out of  $\{a, b, c\}$  is in  $w$ ;



# Main ingredient : Types as constraints

We transform each CF type into an equivalent set of constraints.

For instance, consider  $T = (a[1..3] \cdot b[2..2]) + c[1..2]$ , and  $w \in \llbracket T \rrbracket$ :

- ① **lower-bound**: at least one of  $a$ ,  $b$ , and  $c$  appears in  $w$ ;
- ② **cardinality**: if  $a$  is in  $w$ , it appears 1, 2 or 3 times; if  $b$  is there, it appears twice; if  $c$  is there, it appears once or twice;
- ③ **upper-bound**: no symbol out of  $\{a, b, c\}$  is in  $w$ ;
- ④ **exclusion**: if one of  $a$ ,  $b$  is in  $w$ , then  $c$  is not, and if  $c$  is in  $w$  then neither of  $a$ ,  $b$  is in  $w$ ;

# Main ingredient : Types as constraints

We transform each CF type into an equivalent set of constraints.

For instance, consider  $T = (a[1..3] \cdot b[2..2]) + c[1..2]$ , and  $w \in \llbracket T \rrbracket$ :

- ❶ **lower-bound**: at least one of  $a$ ,  $b$ , and  $c$  appears in  $w$ ;
- ❷ **cardinality**: if  $a$  is in  $w$ , it appears 1, 2 or 3 times; if  $b$  is there, it appears twice; if  $c$  is there, it appears once or twice;
- ❸ **upper-bound**: no symbol out of  $\{a, b, c\}$  is in  $w$ ;
- ❹ **exclusion**: if one of  $a$ ,  $b$  is in  $w$ , then  $c$  is not, and if  $c$  is in  $w$  then neither of  $a$ ,  $b$  is in  $w$ ;
- ❺ **co-occurrence**: if  $a$  is in  $w$ , then  $b$  is in  $w$ , and vice versa;

# Main ingredient : Types as constraints

We transform each CF type into an equivalent set of constraints.

For instance, consider  $T = (a[1..3] \cdot b[2..2]) + c[1..2]$ , and  $w \in \llbracket T \rrbracket$ :

- ❶ **lower-bound**: at least one of  $a$ ,  $b$ , and  $c$  appears in  $w$ ;
- ❷ **cardinality**: if  $a$  is in  $w$ , it appears 1, 2 or 3 times; if  $b$  is there, it appears twice; if  $c$  is there, it appears once or twice;
- ❸ **upper-bound**: no symbol out of  $\{a, b, c\}$  is in  $w$ ;
- ❹ **exclusion**: if one of  $a$ ,  $b$  is in  $w$ , then  $c$  is not, and if  $c$  is in  $w$  then neither of  $a$ ,  $b$  is in  $w$ ;
- ❺ **co-occurrence**: if  $a$  is in  $w$ , then  $b$  is in  $w$ , and vice versa;
- ❻ **order**: no occurrence of  $a$  may follow an occurrence of  $b$ .

# The constraint language

Constraints are expressed using the following logic, where  $a, b \in \Sigma$  and  $A, B \subseteq \Sigma$ :

$$F ::= A^+ \mid A^+ \Rightarrow B^+ \mid a?[m..n] \mid \text{upper}(A) \\ \mid a \prec b \mid F \wedge F' \mid \mathbf{true}$$

We do not have disjunction, nor negation.

# Constraint semantics

$$w \models A^+ \quad \Leftrightarrow \quad S(w) \cap A \neq \emptyset, \text{ i.e. some } a \in A \text{ appears in } w$$

# Constraint semantics

$$\begin{array}{ll} w \models A^+ & \Leftrightarrow S(w) \cap A \neq \emptyset, \text{ i.e. some } a \in A \text{ appears in } w \\ w \models A^+ \Rightarrow B^+ & \Leftrightarrow w \not\models A^+ \text{ or } w \models B^+ \end{array}$$

# Constraint semantics

$w \models A^+$	$\Leftrightarrow$	$S(w) \cap A \neq \emptyset$ , i.e. some $a \in A$ appears in $w$
$w \models A^+ \Rightarrow B^+$	$\Leftrightarrow$	$w \not\models A^+$ or $w \models B^+$
$w \models a?[m..n] \ (n \neq *)$	$\Leftrightarrow$	if $a$ appears in $w$ , then it appears at least $m$ times and at most $n$ times

# Constraint semantics

$w \models A^+$	$\Leftrightarrow$	$S(w) \cap A \neq \emptyset$ , i.e. some $a \in A$ appears in $w$
$w \models A^+ \Rightarrow B^+$	$\Leftrightarrow$	$w \not\models A^+$ or $w \models B^+$
$w \models a?[m..n] \ (n \neq *)$	$\Leftrightarrow$	if $a$ appears in $w$ , then it appears at least $m$ times and at most $n$ times
$w \models a?[m..*]$	$\Leftrightarrow$	if $a$ appears in $w$ , then it appears at least $m$ times



# Constraint semantics

$w \models A^+$	$\Leftrightarrow$	$S(w) \cap A \neq \emptyset$ , i.e. some $a \in A$ appears in $w$
$w \models A^+ \Rightarrow B^+$	$\Leftrightarrow$	$w \not\models A^+$ or $w \models B^+$
$w \models a?[m..n] \ (n \neq *)$	$\Leftrightarrow$	if $a$ appears in $w$ , then it appears at least $m$ times and at most $n$ times
$w \models a?[m..*]$	$\Leftrightarrow$	if $a$ appears in $w$ , then it appears at least $m$ times
$w \models \text{upper}(A)$	$\Leftrightarrow$	$S(w) \subseteq A$

# Constraint semantics

$w \models A^+$	$\Leftrightarrow$	$S(w) \cap A \neq \emptyset$ , i.e. some $a \in A$ appears in $w$
$w \models A^+ \Rightarrow B^+$	$\Leftrightarrow$	$w \not\models A^+$ or $w \models B^+$
$w \models a?[m..n] \ (n \neq *)$	$\Leftrightarrow$	if $a$ appears in $w$ , then it appears at least $m$ times and at most $n$ times
$w \models a?[m..*]$	$\Leftrightarrow$	if $a$ appears in $w$ , then it appears at least $m$ times
$w \models \text{upper}(A)$	$\Leftrightarrow$	$S(w) \subseteq A$
$w \models a \prec b$	$\Leftrightarrow$	there is no occurrence of $a$ in $w$ that follows an occurrence of $b$ in $w$

# Constraint semantics

$w \models A^+$	$\Leftrightarrow$	$S(w) \cap A \neq \emptyset$ , i.e. some $a \in A$ appears in $w$
$w \models A^+ \Rightarrow B^+$	$\Leftrightarrow$	$w \not\models A^+$ or $w \models B^+$
$w \models a?[m..n] \ (n \neq *)$	$\Leftrightarrow$	if $a$ appears in $w$ , then it appears at least $m$ times and at most $n$ times
$w \models a?[m..*]$	$\Leftrightarrow$	if $a$ appears in $w$ , then it appears at least $m$ times
$w \models \text{upper}(A)$	$\Leftrightarrow$	$S(w) \subseteq A$
$w \models a \prec b$	$\Leftrightarrow$	there is no occurrence of $a$ in $w$ that follows an occurrence of $b$ in $w$
$w \models F_1 \wedge F_2$	$\Leftrightarrow$	$w \models F_1$ and $w \models F_2$

# Constraint semantics

$w \models A^+$	$\Leftrightarrow$	$S(w) \cap A \neq \emptyset$ , i.e. some $a \in A$ appears in $w$
$w \models A^+ \Rightarrow B^+$	$\Leftrightarrow$	$w \not\models A^+$ or $w \models B^+$
$w \models a?[m..n] \ (n \neq *)$	$\Leftrightarrow$	if $a$ appears in $w$ , then it appears at least $m$ times and at most $n$ times
$w \models a?[m..*]$	$\Leftrightarrow$	if $a$ appears in $w$ , then it appears at least $m$ times
$w \models \text{upper}(A)$	$\Leftrightarrow$	$S(w) \subseteq A$
$w \models a \prec b$	$\Leftrightarrow$	there is no occurrence of $a$ in $w$ that follows an occurrence of $b$ in $w$
$w \models F_1 \wedge F_2$	$\Leftrightarrow$	$w \models F_1$ and $w \models F_2$
$w \models \mathbf{true}$	$\Leftrightarrow$	always

$$\epsilon \not\models A^+$$

$$\epsilon \models \text{upper}(A)$$

$$\epsilon \models a?[m..n]$$

$$\epsilon \models a \prec b$$

$$b \models a \prec b$$

$$aba \not\models a \prec b$$

$$w \not\models \emptyset^+$$

$$w \models \emptyset^+ \Rightarrow A^+$$

$$w \models \emptyset^+ \Rightarrow \emptyset^+$$

## some abbreviations

$$\begin{aligned}a^+ &=_{def} \{a\}^+ \\ a \prec\succ b &=_{def} (a \prec b) \wedge (b \prec a) \\ A \prec B &=_{def} \bigwedge_{a \in A, b \in B} a \prec b \\ A \prec\succ B &=_{def} \bigwedge_{a \in A, b \in B} a \prec\succ b\end{aligned}$$

## some abbreviations

$$\begin{aligned}a^+ &=_{def} \{a\}^+ \\ a \prec\succ b &=_{def} (a \prec b) \wedge (b \prec a) \\ A \prec B &=_{def} \bigwedge_{a \in A, b \in B} a \prec b \\ A \prec\succ B &=_{def} \bigwedge_{a \in A, b \in B} a \prec\succ b\end{aligned}$$

Exclusion is expressed in terms of order-constraints!

## some abbreviations

$$\begin{aligned}a^+ &=_{def} \{a\}^+ \\ a \prec\succ b &=_{def} (a \prec b) \wedge (b \prec a) \\ A \prec B &=_{def} \bigwedge_{a \in A, b \in B} a \prec b \\ A \prec\succ B &=_{def} \bigwedge_{a \in A, b \in B} a \prec\succ b\end{aligned}$$

Exclusion is expressed in terms of order-constraints!

Also

$$T \models F \Leftrightarrow \forall w \in \llbracket T \rrbracket. w \models F$$



# Main Theorem

For each CF type  $T$ :

$$w \in \llbracket T \rrbracket \quad \Leftrightarrow \quad w \models \mathcal{FC}(T) \wedge \mathcal{NC}(T)$$

$\mathcal{FC}(T)$  is the conjunction of flat constraints associated to  $T$

$\mathcal{NC}(T)$  is the conjunction of nested constraints associated to  $T$

In  $\mathcal{FC}(T)$  and  $\mathcal{NC}(T)$  construction, a central role is played by the property  $N(T)$ , which holds iff  $\epsilon \in \llbracket T \rrbracket$

$N(T)$  can be checked in linear time

# Flat constraints $\mathcal{FC}(T)$

Lower-bound:	$SIf(T)$	$=_{def}$	$If_T(S^+(T))$
Cardinality:	$ZeroMinMax(T)$	$=_{def}$	$\bigwedge_{a[m..n] \in Atoms(T)} a?[m..n]$
Upper-bound:	$upperS(T)$	$=_{def}$	$upper(S(T))$
Flat constraints:	$\mathcal{FC}(T)$	$=_{def}$	$SIf(T) \wedge ZeroMinMax(T) \wedge$

# Nested Constraints $\mathcal{NC}(T)$

Co-occurrence:

$$\mathcal{CC}(T_1 + T_2) \quad =_{def} \quad \mathcal{CC}(T_1) \wedge \mathcal{CC}(T_2)$$

# Nested Constraints $\mathcal{NC}(T)$

Co-occurrence:

$$\mathcal{CC}(T_1 + T_2)$$

$$\mathcal{CC}(T_1 \otimes T_2)$$

$$=_{def} \mathcal{CC}(T_1) \wedge \mathcal{CC}(T_2)$$

$$=_{def} \text{If}_{T_2}(S^+(T_1) \Rightarrow S^+(T_2))$$

# Nested Constraints $\mathcal{NC}(T)$

Co-occurrence:

$$\mathcal{CC}(T_1 + T_2)$$

$$\mathcal{CC}(T_1 \otimes T_2)$$

$$=_{def} \mathcal{CC}(T_1) \wedge \mathcal{CC}(T_2)$$

$$=_{def} \text{If}_{T_2}(S^+(T_1) \Rightarrow S^+(T_2)) \\ \wedge \text{If}_{T_1}(S^+(T_2) \Rightarrow S^+(T_1)) \\ \wedge \mathcal{CC}(T_1) \wedge \mathcal{CC}(T_2)$$

# Nested Constraints $\mathcal{NC}(T)$

Co-occurrence:

$$\mathcal{CC}(T_1 + T_2)$$

$$=_{def} \mathcal{CC}(T_1) \wedge \mathcal{CC}(T_2)$$

$$\mathcal{CC}(T_1 \otimes T_2)$$

$$\begin{aligned} &=_{def} \text{If}_{T_2}(S^+(T_1) \Rightarrow S^+(T_2)) \\ &\quad \wedge \text{If}_{T_1}(S^+(T_2) \Rightarrow S^+(T_1)) \\ &\quad \wedge \mathcal{CC}(T_1) \wedge \mathcal{CC}(T_2) \end{aligned}$$

$$\mathcal{CC}(T!)$$

$$=_{def} \mathcal{CC}(T)$$

# Nested Constraints $\mathcal{NC}(T)$

Co-occurrence:

$$\begin{aligned} \mathcal{CC}(T_1 + T_2) &=_{\text{def}} \mathcal{CC}(T_1) \wedge \mathcal{CC}(T_2) \\ \mathcal{CC}(T_1 \otimes T_2) &=_{\text{def}} \text{If}_{T_2}(S^+(T_1) \Rightarrow S^+(T_2)) \\ &\quad \wedge \text{If}_{T_1}(S^+(T_2) \Rightarrow S^+(T_1)) \\ &\quad \wedge \mathcal{CC}(T_1) \wedge \mathcal{CC}(T_2) \\ \mathcal{CC}(T!) &=_{\text{def}} \mathcal{CC}(T) \\ \mathcal{CC}(\epsilon) &=_{\text{def}} \mathcal{CC}(a[m..n]) =_{\text{def}} \mathbf{true} \end{aligned}$$

# Nested Constraints $\mathcal{NC}(T)$

Co-occurrence:

$$\begin{aligned}\mathcal{CC}(T_1 + T_2) &=_{def} \mathcal{CC}(T_1) \wedge \mathcal{CC}(T_2) \\ \mathcal{CC}(T_1 \otimes T_2) &=_{def} \text{If}_{T_2}(S^+(T_1) \Rightarrow S^+(T_2)) \\ &\quad \wedge \text{If}_{T_1}(S^+(T_2) \Rightarrow S^+(T_1)) \\ &\quad \wedge \mathcal{CC}(T_1) \wedge \mathcal{CC}(T_2) \\ \mathcal{CC}(T!) &=_{def} \mathcal{CC}(T) \\ \mathcal{CC}(\epsilon) &=_{def} \mathcal{CC}(a[m..n]) =_{def} \mathbf{true}\end{aligned}$$

Order and exclusion:

$$\mathcal{OC}(T_1 + T_2) =_{def} (S(T_1) \prec\triangleright S(T_2)) \wedge \mathcal{OC}(T_1) \wedge \mathcal{OC}(T_2)$$



# Nested Constraints $\mathcal{NC}(T)$

Co-occurrence:

$$\begin{aligned}\mathcal{CC}(T_1 + T_2) &=_{def} \mathcal{CC}(T_1) \wedge \mathcal{CC}(T_2) \\ \mathcal{CC}(T_1 \otimes T_2) &=_{def} \text{If}_{T_2}(S^+(T_1) \Rightarrow S^+(T_2)) \\ &\quad \wedge \text{If}_{T_1}(S^+(T_2) \Rightarrow S^+(T_1)) \\ &\quad \wedge \mathcal{CC}(T_1) \wedge \mathcal{CC}(T_2) \\ \mathcal{CC}(T!) &=_{def} \mathcal{CC}(T) \\ \mathcal{CC}(\epsilon) &=_{def} \mathcal{CC}(a[m..n]) =_{def} \mathbf{true}\end{aligned}$$

Order and exclusion:

$$\begin{aligned}\mathcal{OC}(T_1 + T_2) &=_{def} (S(T_1) \prec\triangleright S(T_2)) \wedge \mathcal{OC}(T_1) \wedge \mathcal{OC}(T_2) \\ \mathcal{OC}(T_1 \& T_2) &=_{def} \mathcal{OC}(T_1) \wedge \mathcal{OC}(T_2)\end{aligned}$$

# Nested Constraints $\mathcal{NC}(T)$

Co-occurrence:

$$\begin{aligned}\mathcal{CC}(T_1 + T_2) &=_{def} \mathcal{CC}(T_1) \wedge \mathcal{CC}(T_2) \\ \mathcal{CC}(T_1 \otimes T_2) &=_{def} \text{If}_{T_2}(S^+(T_1) \Rightarrow S^+(T_2)) \\ &\quad \wedge \text{If}_{T_1}(S^+(T_2) \Rightarrow S^+(T_1)) \\ &\quad \wedge \mathcal{CC}(T_1) \wedge \mathcal{CC}(T_2) \\ \mathcal{CC}(T!) &=_{def} \mathcal{CC}(T) \\ \mathcal{CC}(\epsilon) &=_{def} \mathcal{CC}(a[m..n]) =_{def} \mathbf{true}\end{aligned}$$

Order and exclusion:

$$\begin{aligned}\mathcal{OC}(T_1 + T_2) &=_{def} (S(T_1) \prec\triangleright S(T_2)) \wedge \mathcal{OC}(T_1) \wedge \mathcal{OC}(T_2) \\ \mathcal{OC}(T_1 \& T_2) &=_{def} \mathcal{OC}(T_1) \wedge \mathcal{OC}(T_2) \\ \mathcal{OC}(T_1 \cdot T_2) &=_{def} (S(T_1) \prec S(T_2)) \wedge \mathcal{OC}(T_1) \wedge \mathcal{OC}(T_2)\end{aligned}$$

# Nested Constraints $\mathcal{NC}(T)$

Co-occurrence:

$$\begin{aligned}\mathcal{CC}(T_1 + T_2) &=_{def} \mathcal{CC}(T_1) \wedge \mathcal{CC}(T_2) \\ \mathcal{CC}(T_1 \otimes T_2) &=_{def} \text{If}_{T_2}(S^+(T_1) \Rightarrow S^+(T_2)) \\ &\quad \wedge \text{If}_{T_1}(S^+(T_2) \Rightarrow S^+(T_1)) \\ &\quad \wedge \mathcal{CC}(T_1) \wedge \mathcal{CC}(T_2) \\ \mathcal{CC}(T!) &=_{def} \mathcal{CC}(T) \\ \mathcal{CC}(\epsilon) &=_{def} \mathcal{CC}(a[m..n]) =_{def} \mathbf{true}\end{aligned}$$

Order and exclusion:

$$\begin{aligned}\mathcal{OC}(T_1 + T_2) &=_{def} (S(T_1) \prec\triangleright S(T_2)) \wedge \mathcal{OC}(T_1) \wedge \mathcal{OC}(T_2) \\ \mathcal{OC}(T_1 \& T_2) &=_{def} \mathcal{OC}(T_1) \wedge \mathcal{OC}(T_2) \\ \mathcal{OC}(T_1 \cdot T_2) &=_{def} (S(T_1) \prec S(T_2)) \wedge \mathcal{OC}(T_1) \wedge \mathcal{OC}(T_2) \\ \mathcal{OC}(T!) &=_{def} \mathcal{OC}(T) \\ \mathcal{OC}(\epsilon) &=_{def} \mathcal{OC}(a[m..n]) =_{def} \mathbf{true}\end{aligned}$$

Nested constraints:

$$\mathcal{NC}(T) =_{def} \mathcal{CC}(T) \wedge \mathcal{OC}(T)$$

# Subtyping as constraints satisfaction

From

$$w \in \llbracket T \rrbracket \quad \Leftrightarrow \quad w \models \mathcal{FC}(T) \wedge \mathcal{CC}(T) \wedge \mathcal{OC}(T)$$

# Subtyping as constraints satisfaction

From

$$w \in \llbracket T \rrbracket \quad \Leftrightarrow \quad w \models \mathcal{FC}(T) \wedge \mathcal{CC}(T) \wedge \mathcal{OC}(T)$$

the following property directly follows:

$$\llbracket T \rrbracket \subseteq \llbracket U \rrbracket \quad \Leftrightarrow \quad T \models \mathcal{CC}(U) \quad \wedge \quad T \models \mathcal{OC}(U) \quad \wedge T \models \mathcal{FC}(U)$$

# Subtyping as constraints satisfaction

From

$$w \in \llbracket T \rrbracket \quad \Leftrightarrow \quad w \models \mathcal{FC}(T) \wedge \mathcal{CC}(T) \wedge \mathcal{OC}(T)$$

the following property directly follows:

$$\llbracket T \rrbracket \subseteq \llbracket U \rrbracket \quad \Leftrightarrow \quad T \models \mathcal{CC}(U) \quad \wedge \quad T \models \mathcal{OC}(U) \quad \wedge \quad T \models \mathcal{FC}(U)$$

We provide a polynomial type inclusion algorithm, by providing three polynomial algorithms for checking  $T \models \mathcal{CC}(U)$ ,  $T \models \mathcal{OC}(U)$  and  $T \models \mathcal{FC}(U)$ , respectively.

# Subtyping as constraints satisfaction

From

$$w \in \llbracket T \rrbracket \quad \Leftrightarrow \quad w \models \mathcal{FC}(T) \wedge \mathcal{CC}(T) \wedge \mathcal{OC}(T)$$

the following property directly follows:

$$\llbracket T \rrbracket \subseteq \llbracket U \rrbracket \quad \Leftrightarrow \quad T \models \mathcal{CC}(U) \quad \wedge \quad T \models \mathcal{OC}(U) \quad \wedge \quad T \models \mathcal{FC}(U)$$

We provide a polynomial type inclusion algorithm, by providing three polynomial algorithms for checking  $T \models \mathcal{CC}(U)$ ,  $T \models \mathcal{OC}(U)$  and  $T \models \mathcal{FC}(U)$ , respectively.

We will focus on  $T \models \mathcal{CC}(U)$  (see the paper for details on the other two algorithms)

# Polynomial checking of $T \models \mathcal{CC}(U)$

$\mathcal{CC}(U)$  is a finite conjunction of at most  $2 \times |U|$  constraints of the form  $A^+ \Rightarrow B^+$



# Polynomial checking of $T \models \mathcal{CC}(U)$

$\mathcal{CC}(U)$  is a finite conjunction of at most  $2 \times |U|$  constraints of the form  $A^+ \Rightarrow B^+$

Given  $A^+ \Rightarrow B^+ \in \mathcal{CC}(U)$ , in order to check  $T \models A^+ \Rightarrow B^+$  we first compute the ‘backward closure’

$$\text{BC}(B)_T = \{a \in S(T) \mid T \models a^+ \Rightarrow B^+\}$$

# Polynomial checking of $T \models \mathcal{CC}(U)$

$\mathcal{CC}(U)$  is a finite conjunction of at most  $2 \times |U|$  constraints of the form  $A^+ \Rrightarrow B^+$

Given  $A^+ \Rrightarrow B^+ \in \mathcal{CC}(U)$ , in order to check  $T \models A^+ \Rrightarrow B^+$  we first compute the ‘backward closure’

$$\text{BC}(B)_T = \{a \in S(T) \mid T \models a^+ \Rrightarrow B^+\}$$

and then we are done since it turns out that

$$\begin{aligned} T \models A^+ \Rrightarrow B^+ \\ \Leftrightarrow \forall a \in (A \cap S(T)). T \models a^+ \Rrightarrow B^+ \\ \Leftrightarrow (A \cap S(T)) \subseteq \text{BC}(B)_T \end{aligned}$$

# Computing $\text{BC}(B)_T$

We compute  $B_T^\uparrow$  such that  $T'$  is a subterm of  $T$  and  $T' \in B_T^\uparrow$  entails  $T \models S(T')^+ \Rightarrow B^+$

# Computing $\text{BC}(B)_T$

We compute  $B_T^\uparrow$  such that  $T'$  is a subterm of  $T$  and  $T' \in B_T^\uparrow$  entails  $T \models S(T')^+ \Rightarrow B^+$

And then we show that  $\text{BC}(B)_T = \cup_{T' \in B_T^\uparrow} S(T')$ .

# Computing $BC(B)_T$

We compute  $B_T^\uparrow$  such that  $T'$  is a subterm of  $T$  and  $T' \in B_T^\uparrow$  entails  $T \models S(T')^+ \Rightarrow B^+$

And then we show that  $BC(B)_T = \cup_{T' \in B_T^\uparrow} S(T')$ .

$(\epsilon)$	for any $B, T$	$\epsilon \in B_T^\uparrow$
$(a[m..n])$	$T = C[a[m..n]], a \in B \Rightarrow$	$a[m..n] \in B_T^\uparrow$
$(+)$	$T = C[T_1 + T_2], T_1 \in B_T^\uparrow, T_2 \in B_T^\uparrow \Rightarrow$	$T_1 + T_2 \in B_T^\uparrow$
$(\otimes)$	$T = C[T_1 \otimes T_2], T_1 \in B_T^\uparrow, T_2 \in B_T^\uparrow \Rightarrow$	$T_1 \otimes T_2 \in B_T^\uparrow$
$(\otimes \Rightarrow)$	$T = C[T_1 \otimes T_2], \neg N(T_2), T_2 \in B_T^\uparrow \Rightarrow$	$T_1 \otimes T_2 \in B_T^\uparrow$
$(\otimes \Leftarrow)$	$T = C[T_1 \otimes T_2], \neg N(T_1), T_1 \in B_T^\uparrow \Rightarrow$	$T_1 \otimes T_2 \in B_T^\uparrow$
$(!)$	$T = C[T_1!], T_1 \in B_T^\uparrow \Rightarrow$	$T_1! \in B_T^\uparrow$

$BC(B)_T$  can be computed in  $O(|B| + |T|)$ , hence  $O(|U| + |T|)$ , time.

# Complexity of $T \models \mathcal{CC}(U)$

We have that :

- $\mathcal{CC}(U)$  has at most  $2 \times |U|$  constraints of the form  $A^+ \Rrightarrow B^+$ .

# Complexity of $T \models \mathcal{CC}(U)$

We have that :

- $\mathcal{CC}(U)$  has at most  $2 \times |U|$  constraints of the form  $A^+ \Rrightarrow B^+$ .
- $T \models A^+ \Rrightarrow B^+ \Leftrightarrow (A \cap S(T)) \subseteq \text{BC}(B)_T$

# Complexity of $T \models \mathcal{CC}(U)$

We have that :

- $\mathcal{CC}(U)$  has at most  $2 \times |U|$  constraints of the form  $A^+ \Rrightarrow B^+$ .
- $T \models A^+ \Rrightarrow B^+ \Leftrightarrow (A \cap S(T)) \subseteq \text{BC}(B)_T$
- We can check  $(A \cap S(T)) \subseteq \text{BC}(B)_T$  in  $O(|U| + |T|)$  time.



# Complexity of $T \models \mathcal{CC}(U)$

We have that :

- $\mathcal{CC}(U)$  has at most  $2 \times |U|$  constraints of the form  $A^+ \Rrightarrow B^+$ .
- $T \models A^+ \Rrightarrow B^+ \Leftrightarrow (A \cap S(T)) \subseteq \text{BC}(B)_T$
- We can check  $(A \cap S(T)) \subseteq \text{BC}(B)_T$  in  $O(|U| + |T|)$  time.

So  $T \models \mathcal{CC}(U)$  can be checked in  $O(|U| \times |T| + |U|^2)$  time.

Since  $T \models \mathcal{OC}(U)$  and  $T \models \mathcal{FC}(U)$  have lower complexity, we have that  $T < U$  can be checked in  $O(|U| \times |T| + |U|^2)$  time.

# Conclusion and Future Work

- In the paper, to appear in IS, we also prove that intersection on CF types is NP complete.
- In a recent ICDT paper we have provided a polynomial algorithm to check  $T < U$  where only  $U$  is required to be CF
- We are looking for extensions with intersection admitting polynomial complexity
- We plan to define an hybrid algorithm, that uses the PTIME algorithm whenever possible, and resorts to the full algorithm when needed.