

Logic for Communicating Automata with Parameterized Topology

Benedikt Bollig

Laboratoire Spécification et Vérification

Séminaire Vérification LIAFA
27 janvier 2014

Introduction

Objective

A Büchi-Elgot-Trakhtenbrot theorem for communicating automata with parameterized topology.

Introduction

Objective

A Büchi-Elgot-Trakhtenbrot theorem for communicating automata with parameterized topology.

Bridges the gap between high-level specifications and system models.

Introduction

Objective

A Büchi-Elgot-Trakhtenbrot theorem for communicating automata with parameterized topology.

Bridges the gap between high-level specifications and system models.

Theorem (Büchi-Elgot-Trakhtenbrot '60s)

Every MSO formula is equivalent to some finite automaton, and vice versa.

Introduction


Objective

A Büchi-Elgot-Trakhtenbrot theorem for communicating automata with parameterized topology.

Bridges the gap between high-level specifications and system models.

Theorem (Büchi-Elgot-Trakhtenbrot '60s)

Every MSO formula is equivalent to some finite automaton, and vice versa.



Introduction


Objective

A Büchi-Elgot-Trakhtenbrot theorem for communicating automata with parameterized topology.

Bridges the gap between high-level specifications and system models.


Theorem (Büchi-Elgot-Trakhtenbrot '60s)

Every MSO formula is equivalent to some finite automaton, and vice versa.





Has been extended to trees, graphs, weighted automata, ...


... and communicating automata (CA)




... and communicating automata (CA)



... and communicating automata (CA)




... and communicating automata (CA)



Büchi-Elgot-Trakthenbrot theorems:

- \forall -bounded channels [Henriksen-Mukund-Kumar-Sohoni-Thiagarajan 2000]
- \forall -bounded channels [Kuske 2002]
- \exists -bounded channels [Genest-Kuske-Muscholl 2004]
- unbounded channels (but weaker logic) [B.-Leucker 2004]

... and communicating automata (CA)




Büchi-Elgot-Trakthenbrot theorems:

- \forall -bounded channels [Henriksen-Mukund-Kumar-Sohoni-Thiagarajan 2000]
- \forall -bounded channels [Kuske 2002]
- \exists -bounded channels [Genest-Kuske-Muscholl 2004]
- unbounded channels (but weaker logic) [B.-Leucker 2004]

But ...

... all results require communication topology to be fixed!

... and communicating automata (CA)



Büchi-Elgot-Trakthenbrot theorems:

- \forall -bounded channels [Henriksen-Mukund-Kumar-Sohoni-Thiagarajan 2000]
- \forall -bounded channels [Kuske 2002]
- \exists -bounded channels [Genest-Kuske-Muscholl 2004]
- unbounded channels (but weaker logic) [B.-Leucker 2004]

But ...

... all results require communication topology to be fixed!

Towards a parameterized version

Parameterized realizability

Let φ be a formula and \mathfrak{T} be a class of topologies.

Is there a CA that is equivalent to φ on all topologies $\mathcal{T} \in \mathfrak{T}$?

Towards a parameterized version

Parameterized realizability

Let φ be a formula and \mathfrak{T} be a class of topologies.

Is there a CA that is equivalent to φ on all topologies $\mathcal{T} \in \mathfrak{T}$?

More precisely:

- φ is an MSO formula over MSCs (directed acyclic graphs)
- \mathfrak{T} is a class of topologies of bounded degree
(such as pipelines, trees, grids, and rings)

Towards a parameterized version

Parameterized realizability

Let φ be a formula and \mathfrak{T} be a class of topologies.

Is there a CA that is equivalent to φ on all topologies $\mathcal{T} \in \mathfrak{T}$?

More precisely:

- φ is an MSO formula over MSCs (directed acyclic graphs)
- \mathfrak{T} is a class of topologies of bounded degree (such as pipelines, trees, grids, and rings)

\Rightarrow Need for new notions

- ▶ Topologies (of bounded degree)
- ▶ Parameterized communicating automata (PCA)

Outline

- Topologies and MSCs

Outline

- Topologies and MSCs
- Parameterized communicating automata

Outline

- Topologies and MSCs
- Parameterized communicating automata
- MSO logic

Outline

- Topologies and MSCs
- Parameterized communicating automata
- MSO logic
- Negative results:
There is a formula $\varphi \in \mathcal{C}$ that is not realizable for \mathfrak{T} .

Outline

- Topologies and MSCs
- Parameterized communicating automata
- MSO logic
- Negative results:
There is a formula $\varphi \in \mathcal{C}$ that is not realizable for \mathfrak{T} .
- Positive results:
All formulas $\varphi \in \mathcal{C}$ are realizable for \mathfrak{T} .

Topologies and MSCs

Topologies

Topology




Topologies

Topology




Topologies

Topology




Topologies

Topology




Topologies

Pipeline



Topologies


Pipeline



Fix finite set $\mathcal{N} = \{a, b, c, \dots\}$ of interface names.

Topologies

Pipeline



Fix finite set $\mathcal{N} = \{a, b, c, \dots\}$ of interface names.


Definition

A **topology** over \mathcal{N} is a pair $\mathcal{T} = (P, \vdash)$ where

- P is the nonempty finite set of processes
- $\vdash \subseteq P \times \mathcal{N} \times \mathcal{N} \times P$ is the edge relation

Topologies

Pipeline



Fix finite set $\mathcal{N} = \{a, b, c, \dots\}$ of interface names.

Definition


A **topology** over \mathcal{N} is a pair $\mathcal{T} = (P, \vdash)$ where

- P is the nonempty finite set of processes
- $\vdash \subseteq P \times \mathcal{N} \times \mathcal{N} \times P$ is the edge relation

Whenever $p \xrightarrow{a \ b} q$, the following hold:

Topologies

Pipeline



Fix finite set $\mathcal{N} = \{a, b, c, \dots\}$ of interface names.

Definition

A **topology** over \mathcal{N} is a pair $\mathcal{T} = (P, \mapsto)$ where


- P is the nonempty finite set of processes
- $\mapsto \subseteq P \times \mathcal{N} \times \mathcal{N} \times P$ is the edge relation

Whenever $p \xrightarrow{a \ b} q$, the following hold:

- 1 $p \neq q$

Topologies

Pipeline



Fix finite set $\mathcal{N} = \{a, b, c, \dots\}$ of interface names.

Definition

A **topology** over \mathcal{N} is a pair $\mathcal{T} = (P, \vdash)$ where


- P is the nonempty finite set of processes
- $\vdash \subseteq P \times \mathcal{N} \times \mathcal{N} \times P$ is the edge relation

Whenever $p \xrightarrow{a \ b} q$, the following hold:

- 1 $p \neq q$
- 2 $q \xrightarrow{b \ a} p$

Topologies

Pipeline



Fix finite set $\mathcal{N} = \{a, b, c, \dots\}$ of interface names.

Definition

A **topology** over \mathcal{N} is a pair $\mathcal{T} = (P, \vdash)$ where


- P is the nonempty finite set of processes
- $\vdash \subseteq P \times \mathcal{N} \times \mathcal{N} \times P$ is the edge relation

Whenever $p \xrightarrow{a \ b} q$, the following hold:

- 1 $p \neq q$
- 2 $q \xrightarrow{b \ a} p$
- 3 $p \xrightarrow{a' \ b'} q'$ implies $(a = a' \iff q = q')$

Topologies

Pipeline



Fix finite set $\mathcal{N} = \{a, b, c, \dots\}$ of interface names.

Definition

A **topology** over \mathcal{N} is a pair $\mathcal{T} = (P, \vdash)$ where


- P is the nonempty finite set of processes
- $\vdash \subseteq P \times \mathcal{N} \times \mathcal{N} \times P$ is the edge relation

Whenever $p \xrightarrow{a \ b} q$, the following hold:

- 1 $p \neq q$
- 2 $q \xrightarrow{b \ a} p$
- 3 $p \xrightarrow{a' \ b'} q'$ implies $(a = a' \iff q = q')$


Topologies

Pipeline $\mathcal{T}_{\text{lin}}^5$




Topologies

Pipeline $\mathcal{T}_{\text{lin}}^5$




Tree




Topologies


Pipeline $\mathcal{T}_{\text{lin}}^5$



Grid $\mathcal{T}_{\text{grid}}^{3,4}$




Tree




Topologies


Pipeline $\mathcal{T}_{\text{lin}}^5$




Tree



Grid $\mathcal{T}_{\text{grid}}^{3,4}$




Ring $\mathcal{T}_{\text{ring}}^5$




Message Sequence Charts (MSCs)

MSC



Message Sequence Charts (MSCs)

MSC




Definition

An **MSC** over $\mathcal{T} = (P, \vdash)$ is a triple $M = (E, \triangleleft, \ell)$ where

Message Sequence Charts (MSCs)

MSC




Definition

An **MSC** over $\mathcal{T} = (P, \vdash)$ is a triple $M = (E, \triangleleft, \ell)$ where

- E is the nonempty finite set of events

Message Sequence Charts (MSCs)

MSC




Definition

An **MSC** over $\mathcal{T} = (P, \vdash)$ is a triple $M = (E, \triangleleft, \ell)$ where

- E is the nonempty finite set of events
- $\triangleleft = \triangleleft_{\text{proc}} \uplus \triangleleft_{\text{msg}} \subseteq E \times E$ acyclic

Message Sequence Charts (MSCs)

MSC




Definition

An **MSC** over $\mathcal{T} = (P, \vdash)$ is a triple $M = (E, \triangleleft, \ell)$ where

- E is the nonempty finite set of events
- $\triangleleft = \triangleleft_{\text{proc}} \uplus \triangleleft_{\text{msg}} \subseteq E \times E$ acyclic
- $\ell : E \rightarrow P$

Message Sequence Charts (MSCs)

MSC




Definition

An **MSC** over $\mathcal{T} = (P, \vdash)$ is a triple $M = (E, \triangleleft, \ell)$ where

- E is the nonempty finite set of events
- $\triangleleft = \triangleleft_{\text{proc}} \uplus \triangleleft_{\text{msg}} \subseteq E \times E$ acyclic
- $\ell : E \rightarrow P$

Message Sequence Charts (MSCs)

MSC



Definition

An **MSC** over $\mathcal{T} = (P, \vdash)$ is a triple $M = (E, \triangleleft, \ell)$ where


- E is the nonempty finite set of events
- $\triangleleft = \triangleleft_{\text{proc}} \uplus \triangleleft_{\text{msg}} \subseteq E \times E$ acyclic
- $\ell : E \rightarrow P$

+ some extra conditions

Parameterized Communicating Automata (PCA)


Parameterized communicating automata (PCA)

PCA \mathcal{A} over $\{a, b\}$




Parameterized communicating automata (PCA)

PCA \mathcal{A} over $\{a, b\}$




PCA \mathcal{A} running on $\mathcal{T}_{\text{lin}}^5$




Parameterized communicating automata (PCA)

PCA \mathcal{A} over $\{a, b\}$




PCA \mathcal{A} running on $\mathcal{T}_{\text{lin}}^5$




Parameterized communicating automata (PCA)

PCA \mathcal{A} over $\{a, b\}$




PCA \mathcal{A} running on $\mathcal{T}_{\text{lin}}^5$




Parameterized communicating automata (PCA)

PCA \mathcal{A} over $\{a, b\}$




PCA \mathcal{A} running on $\mathcal{T}_{\text{lin}}^5$




Parameterized communicating automata (PCA)

PCA \mathcal{A} over $\{a, b\}$




PCA \mathcal{A} running on $\mathcal{T}_{\text{lin}}^5$




Parameterized communicating automata (PCA)

PCA \mathcal{A} running on $\mathcal{T}_{\text{lin}}^5$




Parameterized communicating automata (PCA)

PCA \mathcal{A} running on $\mathcal{T}_{\text{lin}}^5$




Parameterized communicating automata (PCA)

PCA \mathcal{A} running on $\mathcal{T}_{\text{lin}}^5$




Parameterized communicating automata (PCA)

PCA \mathcal{A} running on $\mathcal{T}_{\text{lin}}^5$




$$M_{\text{lin}}^5 =$$



$$\in L_{\mathcal{T}_{\text{lin}}^5}(\mathcal{A})$$

Parameterized communicating automata (PCA)

PCA \mathcal{A} running on $\mathcal{T}_{\text{lin}}^5$




Accepted language

$$L_{\mathcal{T}_{\text{lin}}^n}(\mathcal{A}) = \{M_{\text{lin}}^n\}$$

for all $n \geq 2$


$$M_{\text{lin}}^5 =$$



$$\in L_{\mathcal{T}_{\text{lin}}^5}(\mathcal{A})$$


Parameterized communicating automata (PCA)

PCA \mathcal{A} over $\{a, b\}$



Parameterized communicating automata (PCA)

PCA \mathcal{A} over $\{a, b\}$




Definition

A **PCA** over \mathcal{N} is a tuple (S, Msg, Δ, I, F) :

- S finite set of states

Parameterized communicating automata (PCA)

PCA \mathcal{A} over $\{a, b\}$




Definition

A **PCA** over \mathcal{N} is a tuple (S, Msg, Δ, I, F) :

- S finite set of states
- Msg finite set of messages

Parameterized communicating automata (PCA)

PCA \mathcal{A} over $\{a, b\}$




Definition

A **PCA** over \mathcal{N} is a tuple (S, Msg, Δ, I, F) :

- S finite set of states
- Msg finite set of messages
- $I : (2^{\mathcal{N}} \setminus \{\emptyset\}) \rightarrow 2^S$ initial states

Parameterized communicating automata (PCA)

PCA \mathcal{A} over $\{a, b\}$




Definition

A **PCA** over \mathcal{N} is a tuple $(S, \text{Msg}, \Delta, I, F)$:

- S finite set of states
- Msg finite set of messages
- $I : (2^{\mathcal{N}} \setminus \{\emptyset\}) \rightarrow 2^S$ initial states
- Δ the set of transitions

Parameterized communicating automata (PCA)

PCA \mathcal{A} over $\{a, b\}$




Definition

A **PCA** over \mathcal{N} is a tuple (S, Msg, Δ, I, F) :

- S finite set of states
- Msg finite set of messages
- $I : (2^{\mathcal{N}} \setminus \{\emptyset\}) \rightarrow 2^S$ initial states
- Δ the set of transitions
- F a boolean combination of statements $\langle \#(s) \geq k \rangle$ with $s \in S$ and $k \in \mathbb{N}$

Parameterized communicating automata (PCA)

PCA \mathcal{A} over $\{a, b\}$




Definition

A **PCA** over \mathcal{N} is a tuple (S, Msg, Δ, I, F) :

- S finite set of states
- Msg finite set of messages
- $I : (2^{\mathcal{N}} \setminus \{\emptyset\}) \rightarrow 2^S$ initial states
- Δ the set of transitions
- F a boolean combination of statements $\langle \#(s) \geq k \rangle$ with $s \in S$ and $k \in \mathbb{N}$
"s occurs at least k times as the terminal state of an active process"

Parameterized communicating automata (PCA)

PCA \mathcal{A} over $\{a, b\}$



Definition

A **PCA** over \mathcal{N} is a tuple (S, Msg, Δ, I, F) :

- S finite set of states
- Msg finite set of messages
- $I : (2^{\mathcal{N}} \setminus \{\emptyset\}) \rightarrow 2^S$ initial states
- Δ the set of transitions
- F a boolean combination of statements $\langle \#(s) \geq k \rangle$ with $s \in S$ and $k \in \mathbb{N}$
“ s occurs at least k times as the terminal state of an active process”


$$F = \bigwedge_{s \in S \setminus \{s_2, t_4, u_2\}} \neg \langle \#(s) \geq 1 \rangle$$

Parameterized communicating automata (PCA)

X A PCA cannot say “the topology has at least 5 processes”

Parameterized communicating automata (PCA)

 A PCA cannot say “the topology has at least 5 processes”


 A PCA can say “at least 5 processes of type $\{a, b\}$ are active”

Parameterized communicating automata (PCA)

X A PCA cannot say “the topology has at least 5 processes”

✓ A PCA can say “at least 5 processes of type $\{a, b\}$ are active”

X A PCA cannot distinguish between:




Parameterized communicating automata (PCA)

X A PCA cannot say “the topology has at least 5 processes”

✓ A PCA can say “at least 5 processes of type $\{a, b\}$ are active”

X A PCA cannot distinguish between:




Parameterized communicating automata (PCA)

X A PCA cannot say “the topology has at least 5 processes”

✓ A PCA can say “at least 5 processes of type $\{a, b\}$ are active”

X A PCA cannot distinguish between:




Parameterized communicating automata (PCA)

X A PCA cannot say “the topology has at least 5 processes”

✓ A PCA can say “at least 5 processes of type $\{a, b\}$ are active”

X A PCA cannot distinguish between:



MSO Logic

MSO logic

MSO logic

$$\varphi ::= !a(x) \mid ?a(x) \mid a \in \textit{type}(x) \mid$$

$$x \triangleleft_{\text{proc}} y \mid x \triangleleft_{\text{proc}}^* y \mid x \triangleleft_{\text{msg}} y \mid x \triangleleft^* y \mid x \sim y \mid$$

$$x = y \mid x \in X \mid \neg \varphi \mid \varphi \vee \varphi \mid \exists x \varphi \mid \exists X \varphi$$

where $a \in \mathcal{N}$

MSO logic

MSO logic

$$\varphi ::= !a(x) \mid ?a(x) \mid a \in \text{type}(x) \mid$$
$$x \triangleleft_{\text{proc}} y \mid x \triangleleft_{\text{proc}}^* y \mid x \triangleleft_{\text{msg}} y \mid x \triangleleft^* y \mid x \sim y \mid$$
$$x = y \mid x \in X \mid \neg \varphi \mid \varphi \vee \varphi \mid \exists x \varphi \mid \exists X \varphi$$

where $a \in \mathcal{N}$

$x \sim y$ says that x and y are located on the same process.

MSO logic

MSO logic

$$\begin{aligned} \varphi ::= & \ !a(x) \mid ?a(x) \mid a \in \text{type}(x) \mid \\ & x \triangleleft_{\text{proc}} y \mid x \triangleleft_{\text{proc}}^* y \mid x \triangleleft_{\text{msg}} y \mid x \triangleleft^* y \mid x \sim y \mid \\ & x = y \mid x \in X \mid \neg \varphi \mid \varphi \vee \varphi \mid \exists x \varphi \mid \exists X \varphi \end{aligned}$$

where $a \in \mathcal{N}$

$x \sim y$ says that x and y are located on the same process.

Define fragments:

- FO: first-order logic, without $\exists X \varphi$

MSO logic

MSO logic

$$\begin{aligned}\varphi ::= & \ !a(x) \mid ?a(x) \mid a \in \text{type}(x) \mid \\ & x \triangleleft_{\text{proc}} y \mid x \triangleleft_{\text{proc}}^* y \mid x \triangleleft_{\text{msg}} y \mid x \triangleleft^* y \mid x \sim y \mid \\ & x = y \mid x \in X \mid \neg \varphi \mid \varphi \vee \varphi \mid \exists x \varphi \mid \exists X \varphi\end{aligned}$$

where $a \in \mathcal{N}$

$x \sim y$ says that x and y are located on the same process.

Define fragments:

- FO: first-order logic, without $\exists X \varphi$
- EMSO: formulas of the form $\exists X_1 \dots \exists X_n \varphi$ with $\varphi \in \text{FO}$

MSO logic

MSO logic

$$\varphi ::= !a(x) \mid ?a(x) \mid a \in \text{type}(x) \mid$$
$$\sigma \subseteq x \triangleleft_{\text{proc}} y \mid x \triangleleft_{\text{proc}}^* y \mid x \triangleleft_{\text{msg}} y \mid x \triangleleft^* y \mid x \sim y \mid$$
$$x = y \mid x \in X \mid \neg \varphi \mid \varphi \vee \varphi \mid \exists x \varphi \mid \exists X \varphi$$

where $a \in \mathcal{N}$

$x \sim y$ says that x and y are located on the same process.

Define fragments:

- FO: first-order logic, without $\exists X \varphi$
- EMSO: formulas of the form $\exists X_1 \dots \exists X_n \varphi$ with $\varphi \in \text{FO}$
- $\text{FO}[\sigma]$ and $\text{EMSO}[\sigma]$ (e.g., $\text{FO}[\triangleleft_{\text{proc}}, \triangleleft_{\text{msg}}]$)

MSO logic

MSO logic

$$\varphi ::= !a(x) \mid ?a(x) \mid a \in \text{type}(x) \mid$$
$$\sigma \subseteq x \triangleleft_{\text{proc}} y \mid x \triangleleft_{\text{proc}}^* y \mid x \triangleleft_{\text{msg}} y \mid x \triangleleft^* y \mid x \sim y \mid$$
$$x = y \mid x \in X \mid \neg \varphi \mid \varphi \vee \varphi \mid \exists x \varphi \mid \exists X \varphi$$

where $a \in \mathcal{N}$

$x \sim y$ says that x and y are located on the same process.


Define fragments:

- FO: first-order logic, without $\exists X \varphi$
- EMSO: formulas of the form $\exists X_1 \dots \exists X_n \varphi$ with $\varphi \in \text{FO}$
- $\text{FO}[\sigma]$ and $\text{EMSO}[\sigma]$ (e.g., $\text{FO}[\triangleleft_{\text{proc}}, \triangleleft_{\text{msg}}]$)

Let $L_{\mathcal{T}}(\varphi)$ be the set of MSCs over \mathcal{T} that are a model of φ .


MSO logic

MSC M_{lin}^6



MSO logic


MSC M_{lin}^6



- $M_{\text{lin}}^6 \models \forall x(?b(x) \rightarrow \exists y(x \triangleleft_{\text{proc}}^* y \wedge !b(y)))$

MSO logic


MSC M_{lin}^6



- $M_{\text{lin}}^6 \models \forall x(?b(x) \rightarrow \exists y(x \triangleleft_{\text{proc}}^* y \wedge !b(y))) \in \text{FO}[\triangleleft_{\text{proc}}^*]$

MSO logic


MSC M_{lin}^6



- $M_{\text{lin}}^6 \models \forall x(?b(x) \rightarrow \exists y(x \triangleleft_{\text{proc}}^* y \wedge !b(y))) \in \text{FO}[\triangleleft_{\text{proc}}^*]$
- $M_{\text{lin}}^6 \models \forall x \forall y (x \triangleleft^* y \vee y \triangleleft^* x)$

MSO logic


MSC M_{lin}^6



- $M_{\text{lin}}^6 \models \forall x(?b(x) \rightarrow \exists y(x \triangleleft_{\text{proc}}^* y \wedge !b(y))) \in \text{FO}[\triangleleft_{\text{proc}}^*]$
- $M_{\text{lin}}^6 \models \forall x \forall y (x \triangleleft^* y \vee y \triangleleft^* x)$
- $M_{\text{lin}}^6 \not\models \exists x \exists y (b \notin \text{type}(x) \wedge a \notin \text{type}(y) \wedge x \triangleleft_{\text{msg}} y)$

MSO logic


MSC M_{lin}^6



- $M_{\text{lin}}^6 \models \forall x(?b(x) \rightarrow \exists y(x \triangleleft_{\text{proc}}^* y \wedge !b(y))) \in \text{FO}[\triangleleft_{\text{proc}}^*]$
- $M_{\text{lin}}^6 \models \forall x \forall y (x \triangleleft^* y \vee y \triangleleft^* x)$
- $M_{\text{lin}}^6 \not\models \exists x \exists y (b \notin \text{type}(x) \wedge a \notin \text{type}(y) \wedge x \triangleleft_{\text{msg}} y) =: \varphi$

MSO logic

MSC M_{lin}^6



- $M_{\text{lin}}^6 \models \forall x(?b(x) \rightarrow \exists y(x \triangleleft_{\text{proc}}^* y \wedge !b(y))) \in \text{FO}[\triangleleft_{\text{proc}}^*]$
- $M_{\text{lin}}^6 \models \forall x \forall y (x \triangleleft^* y \vee y \triangleleft^* x)$
- $M_{\text{lin}}^6 \not\models \exists x \exists y (b \notin \text{type}(x) \wedge a \notin \text{type}(y) \wedge x \triangleleft_{\text{msg}} y) =: \varphi$
- $M_{\text{lin}}^n \models \varphi$ iff $n = 2$

Positive results

Theorem

For every PCA \mathcal{A} , there is a formula $\varphi \in \text{EMSO}[\triangleleft_{\text{proc}}, \triangleleft_{\text{msg}}]$ that is equivalent to \mathcal{A} on all topologies.

Positive results

Theorem

For every PCA \mathcal{A} , there is a formula $\varphi \in \text{EMSO}[\triangleleft_{\text{proc}}, \triangleleft_{\text{msg}}]$ that is equivalent to \mathcal{A} on all topologies.

Proof

Standard. □

Negative Results

Restrictions on topologies are necessary

Theorem

There exists a sentence $\varphi \in \text{FO}[\triangleleft_{\text{proc}}, \triangleleft_{\text{msg}}]$ over $\{a, b\}$ such that, for all PCA \mathcal{A} , there is a ring forest \mathcal{T} with $L_{\mathcal{T}}(\mathcal{A}) \neq L_{\mathcal{T}}(\varphi)$.


Restrictions on topologies are necessary

Theorem


There exists a sentence $\varphi \in \text{FO}[\triangleleft_{\text{proc}}, \triangleleft_{\text{msg}}]$ over $\{a, b\}$ such that, for all PCA \mathcal{A} , there is a ring forest \mathcal{T} with $L_{\mathcal{T}}(\mathcal{A}) \neq L_{\mathcal{T}}(\varphi)$.

Proof


$$\varphi = \forall x \exists x_1, \dots, x_6 (x \in \{x_1, \dots, x_6\} \wedge \text{cycle}(x_1, \dots, x_6))$$




Restrictions on topologies are necessary




$M =$



Restrictions on topologies are necessary




$M =$




- Suppose there is \mathcal{A} such that $L_{\mathcal{T}}(\mathcal{A}) = L_{\mathcal{T}}(\varphi)$ for all ring forests \mathcal{T} .

Restrictions on topologies are necessary




$M =$




- Suppose there is \mathcal{A} such that $L_{\mathcal{T}}(\mathcal{A}) = L_{\mathcal{T}}(\varphi)$ for all ring forests \mathcal{T} .
- We have $\underbrace{M \uplus \dots \uplus M}_n \in L_{\mathcal{T}_{\text{ring}}^3 \uplus \dots \uplus \mathcal{T}_{\text{ring}}^3}(\mathcal{A})$ for all $n \geq 1$.

Restrictions on topologies are necessary




- Suppose there is \mathcal{A} such that $L_{\mathcal{T}}(\mathcal{A}) = L_{\mathcal{T}}(\varphi)$ for all ring forests \mathcal{T} .
- We have $\underbrace{M \uplus \dots \uplus M}_n \in L_{\mathcal{T}_{\text{ring}}^3 \uplus \dots \uplus \mathcal{T}_{\text{ring}}^3}(\mathcal{A})$ for all $n \geq 1$.
- For large enough n , there is a run of \mathcal{A} that behaves the same on two copies of M .

Restrictions on topologies are necessary



- Suppose there is \mathcal{A} such that $L_{\mathcal{T}}(\mathcal{A}) = L_{\mathcal{T}}(\varphi)$ for all ring forests \mathcal{T} .
- We have $\underbrace{M \uplus \dots \uplus M}_n \in L_{\mathcal{T}_{\text{ring}}^3 \uplus \dots \uplus \mathcal{T}_{\text{ring}}^3}(\mathcal{A})$ for all $n \geq 1$.
- For large enough n , there is a run of \mathcal{A} that behaves the same on two copies of M .
- Replace the two copies with MSC over $\mathcal{T}_{\text{ring}}^6$. Contradiction. □

Restrictions on topologies are necessary



- Suppose there is \mathcal{A} such that $L_{\mathcal{T}}(\mathcal{A}) = L_{\mathcal{T}}(\varphi)$ for all ring forests \mathcal{T} .
- We have $\underbrace{M \uplus \dots \uplus M}_n \in L_{\mathcal{T}_{\text{ring}}^3 \uplus \dots \uplus \mathcal{T}_{\text{ring}}^3}(\mathcal{A})$ for all $n \geq 1$.
- For large enough n , there is a run of \mathcal{A} that behaves the same on two copies of M .
- Replace the two copies with MSC over $\mathcal{T}_{\text{ring}}^6$. Contradiction. □

Lesson learned

PCA have limited ability to “detect” cycles.

Restrictions on logic are necessary

Theorem


There exists a sentence $\varphi \in \text{FO}[\triangleleft_{\text{proc}}^*, \triangleleft_{\text{msg}}, \triangleleft^*]$ over $\{a, b, c, d\}$ such that, for all PCA \mathcal{A} , there is a tree \mathcal{T} with $L_{\mathcal{T}}(\mathcal{A}) \neq L_{\mathcal{T}}(\varphi)$.

Restrictions on logic are necessary

Theorem

There exists a sentence $\varphi \in \text{FO}[\triangleleft_{\text{proc}}^*, \triangleleft_{\text{msg}}, \triangleleft^*]$ over $\{a, b, c, d\}$ such that, for all PCA \mathcal{A} , there is a tree \mathcal{T} with $L_{\mathcal{T}}(\mathcal{A}) \neq L_{\mathcal{T}}(\varphi)$.

Proof (idea goes back to [Thomas 1996])




Restrictions on logic are necessary

Theorem

There exists a sentence $\varphi \in \text{FO}[\triangleleft_{\text{proc}}^*, \triangleleft_{\text{msg}}, \triangleleft^*]$ over $\{a, b, c, d\}$ such that, for all PCA \mathcal{A} , there is a tree \mathcal{T} with $L_{\mathcal{T}}(\mathcal{A}) \neq L_{\mathcal{T}}(\varphi)$.

Proof (idea goes back to [Thomas 1996])



Lesson learned

Look at more “local” logics.

Positive Results

Locality of FO logic


Theorem [Schwentick-Barthelmann 1999]

Every formula $\varphi \in \text{FO}[\sigma]$ is equivalent to a formula of the form $\exists x_1 \dots \exists x_n \forall y \psi \in \text{FO}[\sigma]$ where ψ is **r -local** around y , for some $r \geq 1$ (quantification is restricted to elements of distance $\leq r$ from y).

Locality of FO logic

Theorem [Schwentick-Barthelmann 1999]


Every formula $\varphi \in \text{FO}[\sigma]$ is equivalent to a formula of the form $\exists x_1 \dots \exists x_n \forall y \psi \in \text{FO}[\sigma]$ where ψ is **r-local** around y , for some $r \geq 1$ (quantification is restricted to elements of distance $\leq r$ from y).



Locality of FO logic

Theorem [Schwentick-Barthelmann 1999]


Every formula $\varphi \in \text{FO}[\sigma]$ is equivalent to a formula of the form $\exists x_1 \dots \exists x_n \forall y \psi \in \text{FO}[\sigma]$ where ψ is **r-local** around y , for some $r \geq 1$ (quantification is restricted to elements of distance $\leq r$ from y).



Locality of FO logic

Theorem [Schwentick-Barthelmann 1999]


Every formula $\varphi \in \text{FO}[\sigma]$ is equivalent to a formula of the form $\exists x_1 \dots \exists x_n \forall y \psi \in \text{FO}[\sigma]$ where ψ is **r-local** around y , for some $r \geq 1$ (quantification is restricted to elements of distance $\leq r$ from y).



Locality of FO logic

Theorem [Schwentick-Barthelmann 1999]


Every formula $\varphi \in \text{FO}[\sigma]$ is equivalent to a formula of the form $\exists x_1 \dots \exists x_n \forall y \psi \in \text{FO}[\sigma]$ where ψ is ***r*-local** around y , for some $r \geq 1$ (quantification is restricted to elements of distance $\leq r$ from y).



Locality of FO logic

Theorem [Schwentick-Barthelmann 1999]

Every formula $\varphi \in \text{FO}[\sigma]$ is equivalent to a formula of the form $\exists x_1 \dots \exists x_n \forall y \psi \in \text{FO}[\sigma]$ where ψ is **r-local** around y , for some $r \geq 1$ (quantification is restricted to elements of distance $\leq r$ from y).



Positive results

Theorem

Let $\varphi \in \text{EMSO}[\triangleleft_{\text{proc}}^*, \triangleleft_{\text{msg}}]$, $B \geq 1$, and \mathfrak{T} be any of the following:

Positive results

Theorem

Let $\varphi \in \text{EMSO}[\triangleleft_{\text{proc}}^*, \triangleleft_{\text{msg}}]$, $B \geq 1$, and \mathfrak{T} be any of the following:

- the set of pipeline topologies,
- the set of grid topologies,
- the set of tree topologies,
- the set of ring topologies.

Positive results

Theorem

Let $\varphi \in \text{EMSO}[\triangleleft_{\text{proc}}^*, \triangleleft_{\text{msg}}]$, $B \geq 1$, and \mathfrak{T} be any of the following:

- the set of pipeline topologies,
- the set of grid topologies,
- the set of tree topologies,
- the set of ring topologies.

There is a PCA \mathcal{A} such that, for all $\mathcal{T} \in \mathfrak{T}$, we have $L_{\mathcal{T}}^B(\mathcal{A}) = L_{\mathcal{T}}^B(\varphi)$.

Positive results

Theorem

Let $\varphi \in \text{EMSO}[\triangleleft_{\text{proc}}^*, \triangleleft_{\text{msg}}]$, $B \geq 1$, and \mathfrak{T} be any of the following:

- the set of pipeline topologies,
- the set of grid topologies,
- the set of tree topologies,
- the set of ring topologies.

There is a PCA \mathcal{A} such that, for all $\mathcal{T} \in \mathfrak{T}$, we have $L_{\mathcal{T}}^B(\mathcal{A}) = L_{\mathcal{T}}^B(\varphi)$.

Here, $L_{\mathcal{T}}^B(\mathcal{A})$ is the restriction of $L_{\mathcal{T}}(\mathcal{A})$ to B -bounded MSCs.

Positive results

Corollary

Let $\varphi \in \text{EMSO}[\triangleleft_{\text{proc}}^*, \triangleleft_{\text{msg}}]$, $B \geq 1$, and \mathfrak{T} be any of the following:

- the set of pipeline topologies,
- the set of grid topologies,
- the set of tree topologies,
- the set of ring topologies.

There is a PCA \mathcal{A} such that, for all $\mathcal{T} \in \mathfrak{T}$, we have $L_{\mathcal{T}}^B(\mathcal{A}) = L_{\mathcal{T}}^B(\varphi)$.

Here, $L_{\mathcal{T}}^B(\mathcal{A})$ is the restriction of $L_{\mathcal{T}}(\mathcal{A})$ to B -bounded MSCs.

Positive results

Corollary

Let $\varphi \in \text{EMSO}[\triangleleft_{\text{proc}}^*, \triangleleft_{\text{msg}}]$, $B \geq 1$, and \mathfrak{T} be any of the following:

- the set of pipeline topologies,
- the set of grid topologies,
- the set of tree topologies,
- the set of ring topologies.

There is a PCA \mathcal{A} such that, for all $\mathcal{T} \in \mathfrak{T}$, we have $L_{\mathcal{T}}^B(\mathcal{A}) = L_{\mathcal{T}}^B(\varphi)$.

Here, $L_{\mathcal{T}}^B(\mathcal{A})$ is the restriction of $L_{\mathcal{T}}(\mathcal{A})$ to B -bounded MSCs.

Theorem

Let $\varphi \in \text{EMSO}[\triangleleft_{\text{proc}}^*, \triangleleft_{\text{msg}}]$, $B \geq 1$, and \mathfrak{T} be a $(r_{\varphi} + 2)$ -unambiguous set of topologies. There is a PCA \mathcal{A} such that, for all $\mathcal{T} \in \mathfrak{T}$, we have $L_{\mathcal{T}}^B(\mathcal{A}) = L_{\mathcal{T}}^B(\varphi)$.

Here, r_{φ} is the radius associated with the first-order kernel of φ .

Unambiguous topology classes

Definition

Let $k \in \mathbb{N}$. A class \mathfrak{T} of topologies is **k -unambiguous** if, for all $w \in (\mathcal{N} \times \mathcal{N})^*$ with $|w| \leq k$, all $(P, \vdash), (P', \vdash') \in \mathfrak{T}$, and all processes $p, q \in P$ and $p', q' \in P'$ such that $p \xrightarrow{w} q$ and $p' \xrightarrow{w} q'$, we have $p = q$ iff $p' = q'$.

Unambiguous topology classes

Definition


Let $k \in \mathbb{N}$. A class \mathfrak{T} of topologies is **k -unambiguous** if, for all $w \in (\mathcal{N} \times \mathcal{N})^*$ with $|w| \leq k$, all $(P, \vdash), (P', \vdash') \in \mathfrak{T}$, and all processes $p, q \in P$ and $p', q' \in P'$ such that $p \xrightarrow{w} q$ and $p' \xrightarrow{w} q'$, we have $p = q$ iff $p' = q'$.

In other words:

If w forms a cycle in a topology from \mathfrak{T} , then it forms a cycle anywhere, in any topology of \mathfrak{T} (if it is applicable).


Unambiguous topology classes

Pipelines ✓ k -unambiguous for all $k \in \mathbb{N}$




Unambiguous topology classes

Pipelines ✓ k -unambiguous for all $k \in \mathbb{N}$




Trees ✓ k -unambiguous for all $k \in \mathbb{N}$




Unambiguous topology classes


Pipelines ✓ k -unambiguous for all $k \in \mathbb{N}$



Trees ✓ k -unambiguous for all $k \in \mathbb{N}$




Grids ✓ k -unambiguous for all $k \in \mathbb{N}$




$$w = (a, b)(c, d)(b, a)(d, c)$$

Unambiguous topology classes

Pipelines ✓ k -unambiguous for all $k \in \mathbb{N}$




Grids ✓ k -unambiguous for all $k \in \mathbb{N}$




$$w = (a, b)(c, d)(b, a)(d, c)$$

Trees ✓ k -unambiguous for all $k \in \mathbb{N}$




Rings ✗ not k -unambiguous for all $k \geq 3$




Unambiguous topology classes


Pipelines ✓ k -unambiguous for all $k \in \mathbb{N}$



Trees ✓ k -unambiguous for all $k \in \mathbb{N}$




Grids ✓ k -unambiguous for all $k \in \mathbb{N}$



$w = (a, b)(c, d)(b, a)(d, c)$

Rings ✗ not k -unambiguous for all $k \geq 3$




But:


- The class of rings of size $\geq k + 1$ is k -unambiguous, for all $k \in \mathbb{N}$.

Unambiguous topology classes


Pipelines ✓ k -unambiguous for all $k \in \mathbb{N}$



Trees ✓ k -unambiguous for all $k \in \mathbb{N}$




Grids ✓ k -unambiguous for all $k \in \mathbb{N}$



$$w = (a, b)(c, d)(b, a)(d, c)$$

Rings ✗ not k -unambiguous for all $k \geq 3$



But:

- The class of rings of size $\geq k + 1$ is k -unambiguous, for all $k \in \mathbb{N}$.
- Every single ring is k -unambiguous, for all $k \in \mathbb{N}$.

Unambiguous topology classes

Theorem

Let $\varphi \in \text{EMSO}[\triangleleft_{\text{proc}}^*, \triangleleft_{\text{msg}}]$, $B \geq 1$, and \mathfrak{T} be a $(r_\varphi + 2)$ -unambiguous set of topologies. There is a PCA \mathcal{A} such that, for all $\mathcal{T} \in \mathfrak{T}$, we have $L_{\mathcal{T}}^B(\mathcal{A}) = L_{\mathcal{T}}^B(\varphi)$.

Unambiguous topology classes

Theorem

Let $\varphi \in \text{EMSO}[\triangleleft_{\text{proc}}^*, \triangleleft_{\text{msg}}]$, $B \geq 1$, and \mathfrak{T} be a $(r_\varphi + 2)$ -unambiguous set of topologies. There is a PCA \mathcal{A} such that, for all $\mathcal{T} \in \mathfrak{T}$, we have $L_{\mathcal{T}}^B(\mathcal{A}) = L_{\mathcal{T}}^B(\varphi)$.

Proof

- Translate φ into normal form

$$\exists X_1 \dots \exists X_m \exists x_1 \dots \exists x_n \forall y \psi$$

where ψ is r_φ -local around y .

Unambiguous topology classes

Theorem

Let $\varphi \in \text{EMSO}[\triangleleft_{\text{proc}}^*, \triangleleft_{\text{msg}}]$, $B \geq 1$, and \mathfrak{T} be a $(r_\varphi + 2)$ -unambiguous set of topologies. There is a PCA \mathcal{A} such that, for all $\mathcal{T} \in \mathfrak{T}$, we have $L_{\mathcal{T}}^B(\mathcal{A}) = L_{\mathcal{T}}^B(\varphi)$.

Proof

- Translate φ into normal form

$$\exists X_1 \dots \exists X_m \exists x_1 \dots \exists x_n \forall y \psi$$

where ψ is r_φ -local around y .

- Existential quantification \Rightarrow projection & guessing of truth values for propositions involving only free variables of $\forall y \psi$ [Gastin-Kuske 2010].

Unambiguous topology classes

Theorem

Let $\varphi \in \text{EMSO}[\triangleleft_{\text{proc}}^*, \triangleleft_{\text{msg}}]$, $B \geq 1$, and \mathfrak{T} be a $(r_\varphi + 2)$ -unambiguous set of topologies. There is a PCA \mathcal{A} such that, for all $\mathcal{T} \in \mathfrak{T}$, we have $L_{\mathcal{T}}^B(\mathcal{A}) = L_{\mathcal{T}}^B(\varphi)$.

Proof

- Translate φ into normal form

$$\exists X_1 \dots \exists X_m \exists x_1 \dots \exists x_n \forall y \psi$$

where ψ is r_φ -local around y .

- Existential quantification \Rightarrow projection & guessing of truth values for propositions involving only free variables of $\forall y \psi$ [Gastin-Kuske 2010].
- Construct **fixed-topology** CA \mathcal{A}_θ for formula $\forall y \psi$ over all **topology neighborhoods** θ of radius $\lceil r_\varphi/2 \rceil$ [Genest-Kuske-Muscholl 2004].

Unambiguous topology classes

Theorem

Let $\varphi \in \text{EMSO}[\triangleleft_{\text{proc}}^*, \triangleleft_{\text{msg}}]$, $B \geq 1$, and \mathfrak{T} be a $(r_\varphi + 2)$ -unambiguous set of topologies. There is a PCA \mathcal{A} such that, for all $\mathcal{T} \in \mathfrak{T}$, we have $L_{\mathcal{T}}^B(\mathcal{A}) = L_{\mathcal{T}}^B(\varphi)$.

Proof

- Translate φ into normal form


$$\exists X_1 \dots \exists X_m \exists x_1 \dots \exists x_n \forall y \psi$$

where ψ is r_φ -local around y .

- Existential quantification \Rightarrow projection & guessing of truth values for propositions involving only free variables of $\forall y \psi$ [Gastin-Kuske 2010].
- Construct **fixed-topology** CA \mathcal{A}_θ for formula $\forall y \psi$ over all **topology neighborhoods** θ of radius $\lceil r_\varphi/2 \rceil$ [Genest-Kuske-Muscholl 2004].
- Glue fixed-topology CA together to obtain a PCA for $\forall y \psi$.


Unambiguous topology classes

Proof (cntd.) suppose $r_\varphi = 3$ so that $\lceil r_\varphi/2 \rceil = 2$




Unambiguous topology classes

Proof (cntd.) suppose $r_\varphi = 3$ so that $\lceil r_\varphi/2 \rceil = 2$





Unambiguous topology classes

Proof (cntd.) suppose $r_\varphi = 3$ so that $\lceil r_\varphi/2 \rceil = 2$





Unambiguous topology classes

Proof (cntd.) suppose $r_\varphi = 3$ so that $\lceil r_\varphi/2 \rceil = 2$



Unambiguous topology classes



Proof (cntd.) suppose $r_\varphi = 3$ so that $\lceil r_\varphi/2 \rceil = 2$



- Process $p = (2, 3)$ guesses topology neighborhood θ and simulates local automaton $\mathcal{A}_\theta[2', 3']$.

Unambiguous topology classes



Proof (cntd.) suppose $r_\varphi = 3$ so that $\lceil r_\varphi/2 \rceil = 2$



- Process $p = (2, 3)$ guesses topology neighborhood θ and simulates local automaton $\mathcal{A}_\theta[2', 3']$.
- Process p sends $(\theta, (2', 3'))$ to $(2, 2)$.

Unambiguous topology classes



Proof (cntd.) suppose $r_\varphi = 3$ so that $\lceil r_\varphi/2 \rceil = 2$



- Process $p = (2, 3)$ guesses topology neighborhood θ and simulates local automaton $\mathcal{A}_\theta[2', 3']$.
- Process p sends $(\theta, (2', 3'))$ to $(2, 2)$.
- Process $(2, 2)$ receives $(\theta, (1', 2'))$ from $(1, 2)$ and simulates $\mathcal{A}_\theta[2', 2']$.

Unambiguous topology classes



Proof (cntd.) suppose $r_\varphi = 3$ so that $\lceil r_\varphi/2 \rceil = 2$



- Process $p = (2, 3)$ guesses topology neighborhood θ and simulates local automaton $\mathcal{A}_\theta[2', 3']$.
- Process p sends $(\theta, (2', 3'))$ to $(2, 2)$.
- Process $(2, 2)$ receives $(\theta, (1', 2'))$ from $(1, 2)$ and simulates $\mathcal{A}_\theta[2', 2']$.
- \Rightarrow Topology admits $w = (b, a)(d, c)(a, b)(c, d)$ -path from p .

Unambiguous topology classes



Proof (cntd.) suppose $r_\varphi = 3$ so that $\lceil r_\varphi/2 \rceil = 2$



- Process $p = (2, 3)$ guesses topology neighborhood θ and simulates local automaton $\mathcal{A}_\theta[2', 3']$.
- Process p sends $(\theta, (2', 3'))$ to $(2, 2)$.
- Process $(2, 2)$ receives $(\theta, (1', 2'))$ from $(1, 2)$ and simulates $\mathcal{A}_\theta[2', 2']$.
- \Rightarrow Topology admits $w = (b, a)(d, c)(a, b)(c, d)$ -path from p .
- Since $|w| = 4 \leq r_\varphi + 2$, and \mathfrak{T} is $(r_\varphi + 2)$ -unambiguous, w forms a cycle in the topology as well.

Unambiguous topology classes

Proof (cntd.) suppose $r_\varphi = 3$ so that $\lceil r_\varphi/2 \rceil = 2$



- Process $p = (2, 3)$ guesses topology neighborhood θ and simulates local automaton $\mathcal{A}_\theta[2', 3']$.
- Process p sends $(\theta, (2', 3'))$ to $(2, 2)$.
- Process $(2, 2)$ receives $(\theta, (1', 2'))$ from $(1, 2)$ and simulates $\mathcal{A}_\theta[2', 2']$.
- \Rightarrow Topology admits $w = (b, a)(d, c)(a, b)(c, d)$ -path from p .
- Since $|w| = 4 \leq r_\varphi + 2$, and \mathfrak{T} is $(r_\varphi + 2)$ -unambiguous, w forms a cycle in the topology as well.
- Every process has to simulate several automata.

Unambiguous topology classes

Almost the same proof works for a weaker logic without channel bound:

Theorem

Let $\varphi \in \text{EMSO}[\triangleleft_{\text{proc}}, \triangleleft_{\text{msg}}, \sim]$, and \mathfrak{T} be a $(r_\varphi + 2)$ -unambiguous set of topologies. There is a PCA \mathcal{A} such that, for all $\mathcal{T} \in \mathfrak{T}$, $L_{\mathcal{T}}(\mathcal{A}) = L_{\mathcal{T}}(\varphi)$.

Unambiguous topology classes

Almost the same proof works for a weaker logic without channel bound:

Theorem

Let $\varphi \in \text{EMSO}[\triangleleft_{\text{proc}}, \triangleleft_{\text{msg}}, \sim]$, and \mathfrak{T} be a $(r_\varphi + 2)$ -unambiguous set of topologies. There is a PCA \mathcal{A} such that, for all $\mathcal{T} \in \mathfrak{T}$, $L_{\mathcal{T}}(\mathcal{A}) = L_{\mathcal{T}}(\varphi)$.

Proof

- Translate φ into normal form

$$\exists X_1 \dots \exists X_m \exists x_1 \dots \exists x_n \forall y \psi$$

where ψ is r_φ -local around y .

- Existential quantification \Rightarrow projection & guessing of truth values for propositions involving only free variables of $\forall y \psi$ [Gastin-Kuske 2010].
- Construct **fixed-topology** CA \mathcal{A}_θ for formula $\forall y \psi$ over all **topology neighborhoods** θ of radius $\lceil r_\varphi/2 \rceil$ [Genest-Kuske-Muscholl 2004].
- Glue fixed-topology CA together to obtain a PCA for $\forall y \psi$.

Unambiguous topology classes

Almost the same proof works for a weaker logic without channel bound:

Theorem

Let $\varphi \in \text{EMSO}[\triangleleft_{\text{proc}}, \triangleleft_{\text{msg}}, \sim]$, and \mathfrak{T} be a $(r_\varphi + 2)$ -unambiguous set of topologies. There is a PCA \mathcal{A} such that, for all $\mathcal{T} \in \mathfrak{T}$, $L_{\mathcal{T}}(\mathcal{A}) = L_{\mathcal{T}}(\varphi)$.

Proof

- Translate φ into normal form

$$\exists X_1 \dots \exists X_m \exists x_1 \dots \exists x_n \forall y \psi$$

where ψ is r_φ -local around y .

- Existential quantification \Rightarrow projection & guessing of truth values for propositions involving only free variables of $\forall y \psi$ [Gastin-Kuske 2010].
- Construct **fixed-topology** CA \mathcal{A}_θ for formula $\forall y \psi$ over all **topology neighborhoods** θ of radius $\lceil r_\varphi/2 \rceil$ [B.-Leucker 2004].
- Glue fixed-topology CA together to obtain a PCA for $\forall y \psi$.

An orthogonal approach

Theorem


Let $\varphi \in \text{EMSO}[\triangleleft_{\text{proc}}, \triangleleft_{\text{msg}}]$. There is a PCA \mathcal{A} that is equivalent to φ on all pipelines, trees, and grids.

An orthogonal approach

Theorem

Let $\varphi \in \text{EMSO}[\triangleleft_{\text{proc}}, \triangleleft_{\text{msg}}]$. There is a PCA \mathcal{A} that is equivalent to φ on all pipelines, trees, and grids.

Proof




An orthogonal approach

Theorem

Let $\varphi \in \text{EMSO}[\triangleleft_{\text{proc}}, \triangleleft_{\text{msg}}]$. There is a PCA \mathcal{A} that is equivalent to φ on all pipelines, trees, and grids.

Proof



Exploit sphere automaton from [B.-Leucker] to compute $\{\triangleleft_{\text{proc}}, \triangleleft_{\text{msg}}\}$ -neighborhoods.

Summary of results

Negative results

- There is an $\text{FO}[\triangleleft_{\text{proc}}, \triangleleft_{\text{msg}}]$ -formula that is not realizable for the class of ring forests.
- There is an FO-formula that is not realizable for the class of trees.

Summary of results

Negative results

- There is an $\text{FO}[\triangleleft_{\text{proc}}, \triangleleft_{\text{msg}}]$ -formula that is not realizable for the class of ring forests.
- There is an FO-formula that is not realizable for the class of trees.

Positive results

- Under a channel bound, every $\text{FO}[\triangleleft_{\text{proc}}^*, \triangleleft_{\text{msg}}]$ -formula is realizable for the classes of pipelines, trees, grids, and rings.
- Every $\text{FO}[\triangleleft_{\text{proc}}, \triangleleft_{\text{msg}}, \sim]$ -formula is realizable for the classes of pipelines, trees, grids, and rings.

Summary of results

Negative results

- There is an $\text{FO}[\triangleleft_{\text{proc}}, \triangleleft_{\text{msg}}]$ -formula that is not realizable for the class of ring forests.
- There is an FO-formula that is not realizable for the class of trees.

Positive results

- Under a channel bound, every $\text{FO}[\triangleleft_{\text{proc}}^*, \triangleleft_{\text{msg}}]$ -formula is realizable for the classes of pipelines, trees, grids, and rings.
- Every $\text{FO}[\triangleleft_{\text{proc}}, \triangleleft_{\text{msg}}, \sim]$ -formula is realizable for the classes of pipelines, trees, grids, and rings.

Open problems

- Is every $\text{FO}[\triangleleft_{\text{proc}}^*, \triangleleft_{\text{msg}}]$ -formula realizable without channel bound?
- Is every $\text{FO}[\triangleleft^*]$ -formula realizable (for interesting classes of topologies)?

Related work

- Parameterized synthesis [Jacobs-Bloem 2012]
- Parameterized verification [Browne-Clarke-Grumberg 1989], [Emerson-Namjoshi 2003], [Bouajjani-Habermehl-Vojnar 2008], [Delzanno-Sangnier-Zavattaro 2010]
- Distributed algorithms [Grumbach-Wu 2010], [Chalopin-Das-Kosowski 2010]
- Automata from normal forms [Schwentick-Barthelmann 1999], [Gastin-Kuske 2010]

Conclusion

Contribution

- A notion of communicating automaton that is independent of a concrete topology
- Büchi-Elgot-Trakhtenbrot theorems for PCA

Conclusion

Contribution

- A notion of communicating automaton that is independent of a concrete topology
- Büchi-Elgot-Trakhtenbrot theorems for PCA

Future work

- Topologies of unbounded degree (unranked trees, star architectures)
- Parameterized verification

Thank You!