

# Complexity collapse for unambiguous languages

Henryk Michalewski   Michał Skrzypczak

University of Warsaw


Highlights 2013  
Paris

# Existential quantifier $\rightsquigarrow$ projection

## Existential quantifier $\rightsquigarrow$ projection


$$S = \left\{ x : \exists_y R(x, y) \right\}$$

## Existential quantifier $\rightsquigarrow$ projection



$$S = \left\{ x : \exists_y R(x, y) \right\}$$


# Existential quantifier $\rightsquigarrow$ projection



$$S = \{x : \exists_y R(x, y)\}$$

$$S = \pi(R)$$

# Existential quantifier $\rightsquigarrow$ projection




$$S = \left\{ x : \exists_y R(x, y) \right\}$$

$$S = \pi(R)$$

$F$  uniformizes  $R$

# Existential quantifier $\rightsquigarrow$ projection




$$S = \{x : \exists_y R(x, y)\}$$

$$S = \pi(R)$$

$F$  uniformizes  $R$

$$S = \pi(F)$$

## Existential quantifier $\rightsquigarrow$ projection




Theorem (Lebesgue, Souslin)

Projection of a *Borel* set may **not** be *Borel*.



## Existential quantifier $\rightsquigarrow$ projection



Theorem (Lebesgue, Souslin)

Projection of a *Borel* set may **not** be *Borel*.

Theorem (Lusin, Souslin)

Projection of an *uniformized Borel* set **is** *Borel*.



## Nondeterministic

## Nondeterministic parity

## Nondeterministic parity tree automata

Nondeterministic parity tree automata

Büchi condition:

„infinitely many accepting states on every branch”

Nondeterministic parity tree automata

Büchi condition:

„infinitely many accepting states on every branch”

Logic		Automata
MSO	$\equiv$	parity

## Nondeterministic parity tree automata

Büchi condition:

„infinitely many **accepting states** on every branch”

Logic		Automata
MSO	$\equiv$	parity
<i>existential</i> MSO	$\equiv$	Büchi



## Nondeterministic parity tree automata

Büchi condition:

„infinitely many **accepting states** on every branch”

	Logic		Automata
	MSO	$\equiv$	parity
<i>existential</i>	MSO	$\equiv$	Büchi
<b>weak</b>	MSO	$\equiv$	$\text{Büchi} \cap (\text{Büchi})^c (= \text{weak})$

# Projection nondeterminism

# Projection nondeterminism

$\mathcal{A}$  — **nondeterministic** automaton


$\mathcal{A}$  — **nondeterministic** automaton

$R(t, \rho)$ : „ $\rho$  is an **accepting run** of  $\mathcal{A}$  on  $t$ ”

# Projection $\rightsquigarrow$ nondeterminism

$\mathcal{A}$  — **nondeterministic** automaton


$R(t, \rho)$ : „ $\rho$  is an **accepting run** of  $\mathcal{A}$  on  $t$ ”



# Projection $\rightsquigarrow$ nondeterminism

$\mathcal{A}$  — **nondeterministic** automaton

$R(t, \rho)$ : „ $\rho$  is an **accepting run** of  $\mathcal{A}$  on  $t$ ”




# Projection $\rightsquigarrow$ nondeterminism

$\mathcal{A}$  — **nondeterministic** automaton

$R(t, \rho)$ : „ $\rho$  is an **accepting run** of  $\mathcal{A}$  on  $t$ ”

$\mathcal{A}$  is **unambiguous** if  $\forall_t \exists_{\rho}^{\leq 1} \rho$  is accepting



# Open problems

---



# Open problems

Theorem (Niwiński, Walukiewicz [1996])

$\exists_v b(v)$  is **not** recognised by *any* unambiguous automaton.

# Open problems

Theorem (Niwiński, Walukiewicz [1996])

$\exists_v b(v)$  is **not** recognised by *any* unambiguous automaton.

Characterization of unambiguous languages:

Decide if  $L(\mathcal{A})$  is recognised by *some* unambiguous automaton.

# Open problems

Theorem (Niwiński, Walukiewicz [1996])

$\exists_v b(v)$  is **not** recognised by *any* unambiguous automaton.

## Characterization of unambiguous languages:

Decide if  $L(\mathcal{A})$  is recognised by *some* unambiguous automaton.

## Complexity of unambiguous languages:

Lower / upper bounds for *descriptive complexity* of unambiguous languages.

# Open problems

Theorem (Niwiński, Walukiewicz [1996])

$\exists_v b(v)$  is **not** recognised by *any* unambiguous automaton.

## Characterization of unambiguous languages:

Decide if  $L(\mathcal{A})$  is recognised by *some* unambiguous automaton.

## Complexity of unambiguous languages:

Lower / upper bounds for *descriptive complexity* of unambiguous languages.

$\left( \begin{array}{l} \text{Partial answer by Hummel [2012], [2013]:} \\ \text{There are unambiguous languages above } \Pi_1^1. \end{array} \right)$

# Unambiguous Büchi is Borel

---

# Unambiguous Büchi is Borel

Theorem (Finkel, Simmonet [2009])


*If  $\mathcal{A}$  is **unambiguous** and **Büchi** then  $L(\mathcal{A})$  is **Borel**.*

# Unambiguous Büchi is Borel

Theorem (Finkel, Simmonet [2009])

If  $\mathcal{A}$  is *unambiguous* and *Büchi* then  $L(\mathcal{A})$  is *Borel*.

Proof.




# Unambiguous Büchi is Borel

Theorem (Finkel, Simmonet [2009])

If  $\mathcal{A}$  is *unambiguous* and *Büchi* then  $L(\mathcal{A})$  is *Borel*.

Proof.



But what if:




# Unambiguous Büchi is Borel

Theorem (Finkel, Simmonet [2009])

If  $\mathcal{A}$  is *unambiguous* and *Büchi* then  $L(\mathcal{A})$  is *Borel*.

Proof.



But what if:

Conjecture (Skurczyński [1993])

If  $L(\mathcal{A})$  is *Borel* then  $L(\mathcal{A})$  is *weak MSO-definable*.

# Unambiguous Büchi is weak

---

# Unambiguous Büchi is weak

## Theorem

*If  $\mathcal{A}$  is **unambiguous** and **Büchi** then  $L(\mathcal{A})$  is **weak MSO**-definable.*


# Unambiguous Büchi is weak

## Theorem

If  $\mathcal{A}$  is *unambiguous* and *Büchi* then  $L(\mathcal{A})$  is *weak MSO*-definable.

## Proof.

*Separation* (Rabin [1970], Arnold, Santocanale [2005])

+ *Game* argument 


# Unambiguous Büchi is weak

## Theorem

If  $\mathcal{A}$  is *unambiguous* and *Büchi* then  $L(\mathcal{A})$  is *weak MSO*-definable.

## Proof.

*Separation* (Rabin [1970], Arnold, Santocanale [2005])

+ *Game* argument 

*Syntactic* conditions: one automaton unambiguous **and** Büchi


# Unambiguous Büchi is weak

## Theorem

If  $\mathcal{A}$  is *unambiguous* and *Büchi* then  $L(\mathcal{A})$  is *weak MSO*-definable.

## Proof.

*Separation* (Rabin [1970], Arnold, Santocanale [2005])

+ *Game* argument 

*Syntactic* conditions: one automaton unambiguous **and** Büchi

Example (Hummel [2012])

There exists a language *L* that is:


# Unambiguous Büchi is weak

## Theorem

If  $\mathcal{A}$  is *unambiguous* and *Büchi* then  $L(\mathcal{A})$  is *weak MSO*-definable.

## Proof.

*Separation* (Rabin [1970], Arnold, Santocanale [2005])

+ *Game* argument 

*Syntactic* conditions: one automaton unambiguous **and** Büchi

Example (Hummel [2012])

There exists a language  $L$  that is:

- recognised by an *unambiguous* (but not Büchi) automaton,


# Unambiguous Büchi is weak

## Theorem

If  $\mathcal{A}$  is *unambiguous* and *Büchi* then  $L(\mathcal{A})$  is *weak MSO*-definable.

## Proof.

*Separation* (Rabin [1970], Arnold, Santocanale [2005])

+ *Game* argument 

*Syntactic* conditions: one automaton unambiguous **and** Büchi

Example (Hummel [2012])

There exists a language  $L$  that is:

- recognised by an *unambiguous* (but not Büchi) automaton,
- recognised by a *Büchi* (but not unambiguous) automaton,




# Unambiguous Büchi is weak

## Theorem

If  $\mathcal{A}$  is *unambiguous* and *Büchi* then  $L(\mathcal{A})$  is *weak MSO*-definable.

## Proof.

*Separation* (Rabin [1970], Arnold, Santocanale [2005])

+ *Game* argument 

*Syntactic* conditions: one automaton unambiguous **and** Büchi

## Example (Hummel [2012])

There exists a language  $L$  that is:

- recognised by an *unambiguous* (but not Büchi) automaton,
- recognised by a *Büchi* (but not unambiguous) automaton,
- *non-Borel*.

# If I had more time...

---

## Theorem

*Similar result for higher **parity indices**  $(i, 2n)$ .*

# If I had more time...

## Theorem

*Similar result for higher **parity indices**  $(i, 2n)$ .*

## Theorem

*Extension to **topological** classes defined by **Game Quantifier**  $\mathfrak{G}$ .*

# If I had more time...

## Theorem

*Similar result for higher **parity indices**  $(i, 2n)$ .*

## Theorem

*Extension to **topological** classes defined by **Game Quantifier**  $\mathfrak{G}$ .*

## Conclusions:

The first collapse of the **parity index** exploiting **unambiguity**.

If I had more time...

Theorem

*Similar result for higher **parity indices**  $(i, 2n)$ .*

Theorem

*Extension to **topological** classes defined by **Game Quantifier**  $\mathfrak{G}$ .*

Conclusions:

The first collapse of the **parity index** exploiting **unambiguity**.

Hopefully a step towards **upper bounds** for unambiguous languages.