

UNAMBIGUITY-PRESERVING OPERATION ON TREE LANGUAGES THAT LIFTS TOPOLOGICAL COMPLEXITY

Szczepan Hummel

Institute of Informatics,
University of Warsaw

HIGHLIGHTS 2013

- infinite trees (binary)

- infinite trees (binary)
- parity automata


- infinite trees (binary)
- **unambiguous** parity automata

- infinite trees (binary)
- **unambiguous** parity automata
- topological complexity

- infinite trees (binary)
- **unambiguous** parity automata
- topological complexity \Leftarrow Wadge reducibility

- infinite trees (binary)
- **unambiguous** parity automata
- topological complexity \Leftarrow Wadge reducibility
= reductions by continuous functions


Given language $L \subseteq T_A$, we construct $\varsigma(L)$ of trees like this:



Given language $L \subseteq T_A$, we construct $\varsigma(L)$ of trees like this:

Trees represent formulas:


- countable disjunction
- negation
- $t \in T_A$ as atoms



Given language $L \subseteq T_A$, we construct $\varsigma(L)$ of trees like this:

Trees represent formulas:

- countable
disjunction
- negation
- $t \in T_A$ as atoms
TRUE iff $t \in L$




Given language $L \subseteq T_A$, we construct $\varsigma(L)$ of trees like this:

Trees represent formulas:

- countable disjunction
- negation
- $t \in T_A$ as atoms
TRUE iff $t \in L$

Well-founded

- = no branches with ∞ many turnings right in the “formula part” of a tree




Given language $L \subseteq T_A$, we construct $\varsigma(L)$ of trees like this:

Trees represent formulas:

- countable disjunction
- negation
- $t \in T_A$ as atoms
TRUE iff $t \in L$

Well-founded

- = no branches with ∞ many turnings right in the “formula part” of a tree

$$\varsigma(L) \rightsquigarrow \text{formulas evaluating to TRUE}$$


Automata theoretic:

THEOREM

L and \overline{L} unambiguous $\implies \varsigma(L)$ and $\overline{\varsigma(L)}$ unambiguous.

- $\varsigma(L)$ — rightmost witness of TRUE
- $\overline{\varsigma(L)}$ — rightmost witness of ill-foundedness

PROPERTIES OF SIGMA OPERATION

Automata theoretic:


THEOREM

L and \bar{L} unambiguous $\implies \varsigma(L)$ and $\overline{\varsigma(L)}$ unambiguous.

Topological:

THEOREM

L hard for class \mathcal{K} $\implies \varsigma(L)$ hard for class $\sigma(\mathcal{K})$.



PROPERTIES OF SIGMA OPERATION

Automata theoretic:


THEOREM

L and \bar{L} unambiguous $\implies \varsigma(L)$ and $\overline{\varsigma(L)}$ unambiguous.

Topological:

THEOREM

L hard for class \mathcal{K} $\implies \varsigma(L)$ hard for class $\sigma(\mathcal{K})$.



PROPERTIES OF SIGMA OPERATION

Automata theoretic:

THEOREM

L and \bar{L} unambiguous $\implies \varsigma(L)$ and $\overline{\varsigma(L)}$ unambiguous.

Topological:

THEOREM

L hard for class \mathcal{K} $\implies \varsigma(L)$ hard for class $\sigma(\mathcal{K})$.

THEOREM


L stretchable $\implies \varsigma(L)$ stretchable.

LEMMA (ARNOLD, NIWIŃSKI '07)

L stretchable $\implies \bar{L} \not\leq_W L$.

COROLLARY

L stretchable $\implies \varsigma(L) \notin \sigma(\mathcal{K})$.



PROPERTIES OF SIGMA OPERATION

Automata theoretic:

THEOREM

L and \bar{L} unambiguous $\implies \varsigma(L)$ and $\overline{\varsigma(L)}$ unambiguous.

Topological:

THEOREM

L hard for class \mathcal{K} $\implies \varsigma(L)$ hard for class $\sigma(\mathcal{K})$.

THEOREM


L stretchable $\implies \varsigma(L)$ stretchable.

LEMMA (ARNOLD, NIWIŃSKI '07)

L stretchable $\implies \bar{L} \not\leq_W L$.

COROLLARY

L stretchable $\implies \varsigma(L) \notin \sigma(\mathcal{K})$.



PROPERTIES OF SIGMA OPERATION

Automata theoretic:

THEOREM

L and \bar{L} unambiguous $\implies \varsigma(L)$ and $\overline{\varsigma(L)}$ unambiguous.

Topological:

THEOREM

L hard for class \mathcal{K} $\implies \varsigma(L)$ hard for class $\sigma(\mathcal{K})$.

THEOREM


L stretchable $\implies \varsigma(L)$ stretchable.

LEMMA (ARNOLD, NIWIŃSKI '07)

L stretchable $\implies \bar{L} \not\leq_W L$.

COROLLARY

L stretchable $\implies \varsigma(L) \notin \sigma(\mathcal{K})$.



PROPERTIES OF SIGMA OPERATION

Automata theoretic:

THEOREM

L and \bar{L} unambiguous $\implies \varsigma(L)$ and $\overline{\varsigma(L)}$ unambiguous.

Topological:

THEOREM

L hard for class \mathcal{K} $\implies \varsigma(L)$ hard for class $\sigma(\mathcal{K})$.

THEOREM


L stretchable $\implies \varsigma(L)$ stretchable.

LEMMA (ARNOLD, NIWIŃSKI '07)

L stretchable $\implies \bar{L} \not\leq_W L$.

COROLLARY

L stretchable $\implies \varsigma(L) \notin \sigma(\mathcal{K})$.



PROPERTIES OF SIGMA OPERATION

Automata theoretic:

THEOREM

L and \bar{L} unambiguous $\implies \varsigma(L)$ and $\overline{\varsigma(L)}$ unambiguous.

Topological:

THEOREM

L hard for class \mathcal{K} $\implies \varsigma(L)$ hard for class $\sigma(\mathcal{K})$.

THEOREM


L stretchable $\implies \varsigma(L)$ stretchable.

LEMMA (ARNOLD, NIWIŃSKI '07)

L stretchable $\implies \bar{L} \not\leq_W L$.

COROLLARY

L stretchable $\implies \varsigma(L) \notin \sigma(\mathcal{K})$.



PROPERTIES OF SIGMA OPERATION

Automata theoretic:

THEOREM

L and \bar{L} unambiguous $\implies \varsigma(L)$ and $\overline{\varsigma(L)}$ unambiguous.

Topological:

THEOREM

L hard for class \mathcal{K} $\implies \varsigma(L)$ hard for class $\sigma(\mathcal{K})$.

THEOREM


L stretchable $\implies \varsigma(L)$ stretchable.

LEMMA (ARNOLD, NIWIŃSKI '07)

L stretchable $\implies \bar{L} \not\leq_W L$.

COROLLARY

L stretchable $\implies \varsigma(L) \notin \sigma(\mathcal{K})$.



PROPERTIES OF SIGMA OPERATION

Automata theoretic:

THEOREM

L and \bar{L} unambiguous $\implies \varsigma(L)$ and $\overline{\varsigma(L)}$ unambiguous.

Topological:

THEOREM

L hard for class \mathcal{K} $\implies \varsigma(L)$ hard for class $\sigma(\mathcal{K})$.

THEOREM


L stretchable $\implies \varsigma(L)$ stretchable.

LEMMA (ARNOLD, NIWIŃSKI '07)

L stretchable $\implies \bar{L} \not\leq_W L$.

COROLLARY

L stretchable $\implies \varsigma(L) \notin \sigma(\mathcal{K})$.



PROPERTIES OF SIGMA OPERATION

Automata theoretic:

THEOREM

L and \bar{L} unambiguous $\implies \varsigma(L)$ and $\overline{\varsigma(L)}$ unambiguous.

Topological:

THEOREM

L hard for class \mathcal{K} $\implies \varsigma(L)$ hard for class $\sigma(\mathcal{K})$.

THEOREM


L stretchable $\implies \varsigma(L)$ stretchable.

LEMMA (ARNOLD, NIWIŃSKI '07)

L stretchable $\implies \bar{L} \not\leq_W L$.

COROLLARY

L stretchable $\implies \varsigma(L) \notin \sigma(\mathcal{K})$.



PROPERTIES OF SIGMA OPERATION

Automata theoretic:

THEOREM

L and \bar{L} unambiguous $\implies \varsigma(L)$ and $\overline{\varsigma(L)}$ unambiguous.

Topological:

THEOREM

L hard for class \mathcal{K} $\implies \varsigma(L)$ hard for class $\sigma(\mathcal{K})$.

THEOREM


L stretchable $\implies \varsigma(L)$ stretchable.

LEMMA (ARNOLD, NIWIŃSKI '07)

L stretchable $\implies \bar{L} \not\leq_W L$.

COROLLARY

L stretchable $\implies \varsigma(L) \notin \sigma(\mathcal{K})$.



PROPERTIES OF SIGMA OPERATION

Automata theoretic:

THEOREM

L and \bar{L} unambiguous $\implies \varsigma(L)$ and $\overline{\varsigma(L)}$ unambiguous.

Topological:

THEOREM

L hard for class \mathcal{K} $\implies \varsigma(L)$ hard for class $\sigma(\mathcal{K})$.

THEOREM


L stretchable $\implies \varsigma(L)$ stretchable.

LEMMA (ARNOLD, NIWIŃSKI '07)

L stretchable $\implies \bar{L} \not\leq_W L$.

COROLLARY

L stretchable $\implies \varsigma(L) \notin \sigma(\mathcal{K})$.



TECHNICAL ISSUES:

- limit step:
 - $\{\vee, \neg\}$ -well-foundedness vs $\#$ -well-foundedness
- alphabet extension:
 - $L, T_A \setminus L$ – unambiguous, $A \subseteq B \not\Rightarrow T_B \setminus L$ – unambiguous

TECHNICAL ISSUES:

- limit step:
 - $\{\vee, \neg\}$ -well-foundedness vs $\#$ -well-foundedness
- alphabet extension:
 - $L, T_A \setminus L$ – unambiguous, $A \subseteq B \not\Rightarrow T_B \setminus L$ – unambiguous

REFERENCES:

- André Arnold and Damian Niwiński. *Continuous separation of game languages*. Fundamenta Informaticae 2007.
 - stretching

TECHNICAL ISSUES:

- limit step:
 - $\{\vee, \neg\}$ -well-foundedness vs $\#$ -well-foundedness
- alphabet extension:
 - $L, T_A \setminus L$ – unambiguous, $A \subseteq B \not\Rightarrow T_B \setminus L$ – unambiguous

REFERENCES:

- André Arnold and Damian Niwiński. *Continuous separation of game languages*. Fundamenta Informaticae 2007.
 - stretching
- Szczepan Hummel. *Unambiguous tree languages are topologically harder than deterministic ones*. GandALF 2012.
 - sets G and $\sigma(G)$ — the best lower topological complexity bounds for unambiguous languages known so far

$$\begin{array}{llll} G & \equiv_W & \overline{\varsigma(\emptyset)} & \in \Sigma_1^1\text{-complete (non-Borel)} \\ \sigma(G) & \equiv_W & \varsigma(\varsigma(\emptyset)) & \notin \sigma(\Sigma_1^1) \end{array}$$