


The Complexity of Admissibility in ω -Regular Games

R. Brenguier J.-F. Raskin M. Sassolas




Highlights 2013
September, 19-21


Controller synthesis



Controller synthesis



Controller synthesis




Models of rationality

- Nash equilibria \rightsquigarrow no player has interest in deviating.
- Regret minimization \rightsquigarrow players prefer moves that would induce less regret had they known the other players strategy.
- **Elimination of dominated strategies** \rightsquigarrow players eliminate “bad” strategies

\hookrightarrow In all cases it is assumed everybody knows and uses the model of rationality.


Iterative elimination of dominated strategies

- What is a “bad” strategy? σ is **strictly dominated** by σ' if
 - for all profiles of the other players, if σ wins, so does σ' .
 - for some profile of the other players, σ loses while σ' wins.




Iterative elimination of dominated strategies

- What is a “bad” strategy? σ is **strictly dominated** by σ' if
 - for all profiles of the other players, if σ wins, so does σ' .
 - for some profile of the other players, σ loses while σ' wins.




Iterative elimination of dominated strategies

- What is a “bad” strategy? σ is **strictly dominated** by σ' if
 - ▶ for all **profiles of the other players**, if σ wins, so does σ' .
 - ▶ for some **profile of the other players**, σ loses while σ' wins.
- **Each player** eliminates its dominated strategies.




Iterative elimination of dominated strategies

- What is a “bad” strategy? σ is **strictly dominated** by σ' if
 - ▶ for all profiles of the other players, if σ wins, so does σ' .
 - ▶ for some profile of the other players, σ loses while σ' wins.
- **Each player** eliminates its dominated strategies.



Iterative elimination of dominated strategies

- What is a “bad” strategy? σ is **strictly dominated** by σ' if
 - ▶ for all profiles of the other players, if σ wins, so does σ' .
 - ▶ for some profile of the other players, σ loses while σ' wins.
- **Each player** eliminates its dominated strategies.
- Repeat until stabilized.



Our setting

- Turn based games on graphs.
- Objective of player i : $W_{\text{IN}_i} \subseteq V^\omega$.

Our setting


- Turn based games on graphs.
- Objective of player i : $WIN_i \subseteq V^\omega$.

- Muller objectives:
 $\rho \in WIN_i$ iff $\text{Inf}(\rho) \in \mathcal{F}$.

↪ Generalizes Büchi and parity conditions.

- Weak Muller objectives:
 $\rho \in WIN_i$ iff $\text{Occ}(\rho) \in \mathcal{F}$.

↪ Generalizes safety and reachability conditions.



Admissibility

- **Dominance**: $\sigma'_i \succ_{\mathcal{S}^n} \sigma_i$ if σ'_i strictly dominates σ_i w.r.t \mathcal{S}^n .
- **Iterative admissibility**: $\mathcal{S}_i^0 = \mathcal{S}_i$ and
$$\mathcal{S}_i^{n+1} := \mathcal{S}_i^n \setminus \{\sigma_i \mid \exists \sigma'_i \in \mathcal{S}_i^n, \sigma'_i \succ_{\mathcal{S}^n} \sigma_i\}.$$
- Set of **iteratively admissible** strategies: $\mathcal{S}^* = \bigcap_{n \in \mathbb{N}} \mathcal{S}^n$

Admissibility

- **Dominance**: $\sigma'_i \succ_{\mathcal{S}^n} \sigma_i$ if σ'_i strictly dominates σ_i w.r.t \mathcal{S}^n .

- **Iterative admissibility**: $\mathcal{S}_i^0 = \mathcal{S}_i$ and

$$\mathcal{S}_i^{n+1} := \mathcal{S}_i^n \setminus \{\sigma_i \mid \exists \sigma'_i \in \mathcal{S}_i^n, \sigma'_i \succ_{\mathcal{S}^n} \sigma_i\}.$$

- Set of **iteratively admissible** strategies: $\mathcal{S}^* = \bigcap_{n \in \mathbb{N}} \mathcal{S}^n$

↪ **Goal**: compute \mathcal{S}^* or at least decide properties thereof.

Admissibility

- **Dominance**: $\sigma'_i \succ_{\mathcal{S}^n} \sigma_i$ if σ'_i **strictly dominates** σ_i w.r.t \mathcal{S}^n .
- **Iterative admissibility**: $\mathcal{S}_i^0 = \mathcal{S}_i$ and
$$\mathcal{S}_i^{n+1} := \mathcal{S}_i^n \setminus \{\sigma_i \mid \exists \sigma'_i \in \mathcal{S}_i^n, \sigma'_i \succ_{\mathcal{S}^n} \sigma_i\}.$$
- Set of **iteratively admissible** strategies: $\mathcal{S}^* = \bigcap_{n \in \mathbb{N}} \mathcal{S}^n$

↪ **Goal**: compute \mathcal{S}^* or at least decide properties thereof.

Remark

\mathcal{S}^* is well defined and is reached after a **finite** number of iterations.

“Admissibility in Infinite Games” [Berwanger, STACS'07]

Admissibility

- **Dominance**: $\sigma'_i \succ_{\mathcal{S}^n} \sigma_i$ if σ'_i strictly dominates σ_i w.r.t \mathcal{S}^n .
- **Iterative admissibility**: $\mathcal{S}_i^0 = \mathcal{S}_i$ and
$$\mathcal{S}_i^{n+1} := \mathcal{S}_i^n \setminus \{\sigma_i \mid \exists \sigma'_i \in \mathcal{S}_i^n, \sigma'_i \succ_{\mathcal{S}^n} \sigma_i\}.$$
- Set of **iteratively admissible** strategies: $\mathcal{S}^* = \bigcap_{n \in \mathbb{N}} \mathcal{S}^n$

↪ **Goal**: compute \mathcal{S}^* or at least decide properties thereof.

Remark

\mathcal{S}^* is well defined and is reached after a *finite* number of iterations.

“Admissibility in Infinite Games” [Berwanger, STACS'07]

Decision problems on \mathcal{S}^*


The winning coalition problem: Given $W, L \subseteq P$, does there exists $\sigma_P \in \mathcal{S}^*$ such that all players of W win the game, and all players of L lose.

The model-checking under admissibility problem: Given φ an LTL formula, is it the case that for any profile $\sigma_P \in \mathcal{S}^*$, $Out(\sigma_P) \models \varphi$?

Values

Introduced in [Berwanger, STACS'07]


- If there is a winning strategy
 - ⇒ admissible strategies are the winning ones.
- It is impossible to win
 - ⇒ all strategies are admissible.



Values

Introduced in [Berwanger, STACS'07]


- If there is a winning strategy
 - admissible strategies are the winning ones.
- It is impossible to win
 - all strategies are admissible.
- Otherwise: it is possible to win, but only with the help of others
 - What are the admissible strategies in this case?



Values

Introduced in [Berwanger, STACS'07]


- If there is a winning strategy: **value 1**.
 - admissible strategies are the winning ones.
- It is impossible to win: **value -1**.
 - all strategies are admissible.
- Otherwise: it is possible to win, but only with the help of others: **value 0**.
 - What are the admissible strategies in this case?



Values

Introduced in [Berwanger, STACS'07]

- If there is a winning strategy: **value 1**.
→ admissible strategies are the winning ones.
- It is impossible to win: **value -1**.
→ all strategies are admissible.
- Otherwise: it is possible to win, but only with the help of others: **value 0**.
→ What are the admissible strategies in this case?



Remark

- A player should *never decrease* its own value.
 - The value depends on S^n .
- How to compute those values?

Safety objectives: a local notion of dominance



- Objective: avoid *Bad* states
- Existence of a winning strategy depends only on:
 - ▶ the current state
 - ▶ *Bad* states visited
 - ~> *unfold* the graph to keep this information
 - ~> size: $|V| \times 2^{|P|}$.
- In unfolded safety games the rule to **never decrease one's own value** is **sufficient** for admissibility.
- The structure of the unfolding avoid explosion in complexity.

Theorem

The winning coalition problem is PSPACE-complete for safety.



Prefix-independent objectives

→ In general: the local condition is not sufficient



Prefix-independent objectives

→ In general: the local condition is not sufficient





- In case the value is 0, need to allow other players to help.
- “Help!”-state for i : a state where $j \neq i$ has several choices with value ≥ 0 for i , while not changing the value for j .

→ Admissible strategies should be winning if the other players played fairly in those states.

Prefix-independent objectives

→ In general: the local condition is not sufficient





- In case the value is 0, need to allow other players to help.
- **“Help!”-state** for i : a state where $j \neq i$ has several choices with value ≥ 0 for i , while not changing the value for j .

→ Admissible strategies should be winning if the other players played **fairly** in those states.

→ Give rises to automaton \mathcal{A}_n recognizing $Out(\mathcal{S}^n)$ with circuit winning condition.

Prefix-independent objectives

→ In general: the local condition is not sufficient



- In case the value is 0, need to allow other players to help.
- **“Help!”-state** for i : a state where $j \neq i$ has several choices with value ≥ 0 for i , while not changing the value for j .

→ Admissible strategies should be winning if the other players played **fairly** in those states.

→ Give rises to automaton \mathcal{A}_n recognizing $Out(\mathcal{S}^n)$ with circuit winning condition.

- In turn, \mathcal{A}_n is used to compute the values at the next step.

Complexity for Objectives defined by Circuits

Theorem (Winning coalition problem)

- *The winning coalition problem PSPACE-complete for circuits.*
- *The winning coalition problem with Büchi objectives is in P^{NP}*
- *The winning coalition problem for weak circuit is PSPACE-complete.*

Theorem (Model-checking under admissibility problem)

The model-checking under admissibility problem is PSPACE-complete for games where the winning condition of each player is given by a circuit condition.

Summary

- Automata representing all outcomes of admissible strategies.
- Algorithms with **tight complexity bounds** to compute the set of **all outcomes** of iteratively admissible strategies.
- Application to model-checking of LTL assuming all players follow rationality.

Summary

- Automata representing all outcomes of admissible strategies.
- Algorithms with **tight complexity bounds** to compute the set of **all outcomes** of iteratively admissible strategies.
- Application to model-checking of LTL assuming all players follow rationality.

Future work

- Extension to **quantitative** games.
- Implementation.

Summary

- Automata representing all outcomes of admissible strategies.
- Algorithms with **tight complexity bounds** to compute the set of **all outcomes** of iteratively admissible strategies.
- Application to model-checking of LTL assuming all players follow rationality.

Future work

- Extension to **quantitative** games.
- Implementation.

Thank you