

# Expressiveness modulo bisimilarity: a coalgebraic perspective

Yde Venema

ILLC, UvA, Amsterdam

<http://staff.science.uva.nl/~yde>

Highlights, Paris, 21 September 2013

# Expressiveness modulo bisimilarity

$$M \equiv L / \Leftrightarrow$$

# Expressiveness modulo bisimilarity

$$M \equiv L / \Leftrightarrow$$

► van Benthem:  $ML \equiv FOL / \Leftrightarrow$

# Expressiveness modulo bisimilarity

$$M \equiv L / \Leftrightarrow$$

- ▶ van Benthem:  $ML \equiv FOL / \Leftrightarrow$
- ▶ many variations, generalizations, ...

# Expressiveness modulo bisimilarity

$$M \equiv L / \Leftrightarrow$$

- ▶ van Benthem:  $ML \equiv FOL / \Leftrightarrow$
- ▶ many variations, generalizations, ...
- ▶ Janin & Walukiewicz:  $\mu ML \equiv MSO / \Leftrightarrow$



# Janin & Walukiewicz

**Theorem** (Janin & Walukiewicz)  $\mu\text{ML} \equiv_s \text{MSO} / \Leftrightarrow$

# Janin & Walukiewicz

**Theorem** (Janin & Walukiewicz)  $\mu\text{ML} \equiv_s \text{MSO} / \Leftrightarrow$

That is, there is a translation  $(\cdot)^* : \text{MSO} \rightarrow \mu\text{ML}$  s.t.

$\varphi$  is bisimulation invariant iff  $\varphi \equiv \varphi^*$ .



# Janin & Walukiewicz

**Theorem** (Janin & Walukiewicz)  $\mu\text{ML} \equiv_s \text{MSO} / \Leftrightarrow$

That is, there is a translation  $(\cdot)^* : \text{MSO} \rightarrow \mu\text{ML}$  s.t.

$\varphi$  is bisimulation invariant iff  $\varphi \equiv \varphi^*$ .

**Proof sketch:** J & W use automata:

1.  $\text{MSO} \equiv \text{Aut}(\text{FOE})$  on tree models
2.  $\mu\text{ML} \equiv \text{Aut}(\text{FO})$ .

# Janin & Walukiewicz

**Theorem** (Janin & Walukiewicz)  $\mu\text{ML} \equiv_s \text{MSO} / \Leftrightarrow$

That is, there is a translation  $(\cdot)^* : \text{MSO} \rightarrow \mu\text{ML}$  s.t.

$\varphi$  is bisimulation invariant iff  $\varphi \equiv \varphi^*$ .

**Proof sketch:** J & W use automata:

1.  $\text{MSO} \equiv \text{Aut}(\text{FOE})$  on tree models
2.  $\mu\text{ML} \equiv \text{Aut}(\text{FO})$ .

Hence it suffices to prove that

3.  $\text{Aut}(\text{FO}) \equiv_s \text{Aut}(\text{FOE}) / \Leftrightarrow$

# Janin & Walukiewicz

**Theorem** (Janin & Walukiewicz)  $\mu\text{ML} \equiv_s \text{MSO} / \Leftrightarrow$

That is, there is a translation  $(\cdot)^* : \text{MSO} \rightarrow \mu\text{ML}$  s.t.

$\varphi$  is bisimulation invariant iff  $\varphi \equiv \varphi^*$ .

**Proof sketch:** J & W use automata:

1.  $\text{MSO} \equiv \text{Aut}(\text{FOE})$  on tree models
2.  $\mu\text{ML} \equiv \text{Aut}(\text{FO})$ .

Hence it suffices to prove that

3.  $\text{Aut}(\text{FO}) \equiv_s \text{Aut}(\text{FOE}) / \Leftrightarrow$

**Point of talk:** Item 3 follows from observations on relation FOE/FO

# Preliminaries: Models

Fix a set  $X$  of proposition letters.

A **model** is a structure  $\mathbb{S} = \langle S, R, V \rangle$  with  $R \subseteq S \times S$  and  $V : X \rightarrow \wp S$ .

# Preliminaries: Models

Fix a set  $X$  of proposition letters.

A **model** is a structure  $\mathbb{S} = \langle S, R, V \rangle$  with  $R \subseteq S \times S$  and  $V : X \rightarrow \wp S$ .

- $R \subseteq S \times S$  induces  $R : S \rightarrow \wp S$ , with  
 $R[s] := \{t \in S \mid Rst\}$  is the **successor set** of  $s$

# Preliminaries: Models

Fix a set  $X$  of proposition letters.

A **model** is a structure  $\mathbb{S} = \langle S, R, V \rangle$  with  $R \subseteq S \times S$  and  $V : X \rightarrow \wp S$ .

- ▶  $R \subseteq S \times S$  induces  $R : S \rightarrow \wp S$ , with  
 $R[s] := \{t \in S \mid Rst\}$  is the **successor set** of  $s$
- ▶  $V : X \rightarrow \wp S$  induces  $m_V : S \rightarrow \wp X$ , with  
 $m_V(s) := \{p \in X \mid s \in V(p)\}$  is the **color** of  $s$ .

# Preliminaries: Automata

An **automaton** is a triple  $\mathbb{A} = \langle A, \delta, \Omega \rangle$  with

- ▶  $A$  a finite set of states/ propositional variables/monadic predicates
- ▶  $\Omega : A \rightarrow \mathbb{N}$  a priority map
- ▶  $\delta : A \times \wp X \rightarrow L(A)$ , with  $L(A)$  some set of **one-step formulas** in  $A$ .

# Preliminaries: Automata

An **automaton** is a triple  $\mathbb{A} = \langle A, \delta, \Omega \rangle$  with

- ▶  $A$  a finite set of states/ propositional variables/monadic predicates
- ▶  $\Omega : A \rightarrow \mathbb{N}$  a priority map
- ▶  $\delta : A \times \wp X \rightarrow L(A)$ , with  $L(A)$  some set of **one-step formulas** in  $A$ .

With such  $\delta$ ,  $\mathbb{A}$  belongs to **Aut**( $L$ ).



# Preliminaries: Automata

An **automaton** is a triple  $\mathbb{A} = \langle A, \delta, \Omega \rangle$  with

- ▶  $A$  a finite set of states/ propositional variables/monadic predicates
- ▶  $\Omega : A \rightarrow \mathbb{N}$  a priority map
- ▶  $\delta : A \times \wp X \rightarrow L(A)$ , with  $L(A)$  some set of **one-step formulas** in  $A$ .

With such  $\delta$ ,  $\mathbb{A}$  belongs to **Aut**( $L$ ).

**Initialized** automaton: pair  $(\mathbb{A}, a_I)$  with  $a_I \in A$

# Preliminaries: Automata

An **automaton** is a triple  $\mathbb{A} = \langle A, \delta, \Omega \rangle$  with

- ▶  $A$  a finite set of states/ propositional variables/monadic predicates
- ▶  $\Omega : A \rightarrow \mathbb{N}$  a priority map
- ▶  $\delta : A \times \wp X \rightarrow L(A)$ , with  $L(A)$  some set of **one-step formulas** in  $A$ .

With such  $\delta$ ,  $\mathbb{A}$  belongs to **Aut**( $L$ ).

**Initialized** automaton: pair  $(\mathbb{A}, a_I)$  with  $a_I \in A$

**Acceptance game** of an automaton  $\mathbb{A}$  on a model  $\mathbb{S}$ :

Position	Player	Admissible moves	Priority
$(a, s) \in A \times S$	$\exists$	$\{I : A \rightarrow \wp S \mid \text{"}I \text{ makes } \delta(a, m_V(s)) \text{ true"}\}$	$\Omega(a)$
$I : A \rightarrow \wp S$	$\forall$	$\{(b, t) \in A \times S \mid t \in I(b)\}$	0

# One-step logic

- ▶ fix a finite set  $A$
- ▶ think of  $A$  as a **signature of monadic predicates**
- ▶ **structure** for  $A$ : pair  $\langle D, I \rangle$  with  $I : A \rightarrow \wp D$  an **interpretation**
- ▶ corresponding monadic first-order language:

$$\varphi ::= a(x) \mid x = y \mid \neg \varphi \mid \varphi \vee \varphi \mid \exists x. \varphi$$

# One-step logic

- ▶ fix a finite set  $A$
- ▶ think of  $A$  as a **signature of monadic predicates**
- ▶ **structure** for  $A$ : pair  $\langle D, I \rangle$  with  $I : A \rightarrow \wp D$  an **interpretation**
- ▶ corresponding monadic first-order language:

$$\varphi ::= a(x) \mid x = y \mid \neg\varphi \mid \varphi \vee \varphi \mid \exists x.\varphi$$

- ▶ **FOE(A)**: sentences in language with equality
- ▶ **FO(A)**: sentences in language without equality

# One-step logic

- ▶ fix a finite set  $A$
- ▶ think of  $A$  as a **signature of monadic predicates**
- ▶ **structure** for  $A$ : pair  $\langle D, I \rangle$  with  $I : A \rightarrow \wp D$  an **interpretation**
- ▶ corresponding monadic first-order language:

$$\varphi ::= a(x) \mid x = y \mid \neg \varphi \mid \varphi \vee \varphi \mid \exists x. \varphi$$

- ▶ **FOE(A)**: sentences in language with equality  
**FO(A)**: sentences in language without equality
- ▶ **Aut(FOE)**: automata with  $\delta : A \times \wp X \rightarrow \text{FOE}(A)$   
**Aut(FO)**: automata with  $\delta : A \times \wp X \rightarrow \text{FO}(A)$

# One-step logic

- ▶ fix a finite set  $A$
- ▶ think of  $A$  as a **signature of monadic predicates**
- ▶ **structure** for  $A$ : pair  $\langle D, I \rangle$  with  $I : A \rightarrow \wp D$  an **interpretation**
- ▶ corresponding monadic first-order language:

$$\varphi ::= a(x) \mid x = y \mid \neg\varphi \mid \varphi \vee \varphi \mid \exists x.\varphi$$

- ▶ **FOE(A)**: sentences in language with equality  
**FO(A)**: sentences in language without equality
- ▶ **Aut(FOE)**: automata with  $\delta : A \times \wp X \rightarrow \text{FOE}(A)$   
**Aut(FO)**: automata with  $\delta : A \times \wp X \rightarrow \text{FO}(A)$

Use in acceptance game:

- ▶ at position  $(a, s)$ ,  $\exists$  needs to **find an interpretation**  $I : A \rightarrow \wp R[s]$   
s.t.  $\langle R[s], I \rangle \models \delta(a, m_V(s))$ .

# Acceptance Game

The **acceptance game**  $\mathcal{A}(\mathbb{A}, \mathbb{S})$  of an automaton  $\mathbb{A}$  on a model  $\mathbb{S}$ :

Position	Player	Admissible moves	Priority
$(a, s) \in A \times S$	$\exists$	$\{I : A \rightarrow \wp S \mid \langle R[s], I \rangle \models \delta(a, m_V(s))\}$	$\Omega(a)$
$I : A \rightarrow \wp S$	$\forall$	$\{(b, t) \in A \times S \mid t \in I(b)\}$	0

$(\mathbb{A}, a_I)$  **accepts**  $(\mathbb{S}, s)$  if  $(a_I, s) \in \text{Win}_{\exists}(\mathcal{A}(\mathbb{A}, \mathbb{S}))$ .

# Logic & Automata

**Theorem 1** (Janin & Walukiewicz)

(a)  $\text{MSO} \equiv \text{Aut}(\text{FOE})$  on trees.

(b)  $\mu\text{ML} \equiv \text{Aut}(\text{FO})$ .



# Logic & Automata

**Theorem 1** (Janin & Walukiewicz)

(a)  $\text{MSO} \equiv \text{Aut}(\text{FOE})$  on trees.

(b)  $\mu\text{ML} \equiv \text{Aut}(\text{FO})$ .

The aim is now to prove

$$\text{Aut}(\text{FO}) \equiv_s \text{Aut}(\text{FOE}) / \Leftrightarrow$$

# Logic & Automata

**Theorem 1** (Janin & Walukiewicz)

(a)  $\text{MSO} \equiv \text{Aut}(\text{FOE})$  on trees.

(b)  $\mu\text{ML} \equiv \text{Aut}(\text{FO})$ .

The aim is now to prove

$$\text{Aut}(\text{FO}) \equiv_s \text{Aut}(\text{FOE}) / \Leftrightarrow$$

Focus on relation  $\text{FOE}/\text{FO}$ .

# One-step bisimulation invariance

## Definition

- ▶ Two  $A$ -structures  $(D, I)$  and  $(D', I')$  are **P-similar** if
  - $\forall d \in D \quad \exists d' \in D' \quad m_I(d) = m_{I'}(d')$
  - $\forall d' \in D' \quad \exists d \in D \quad m_I(d) = m_{I'}(d')$

# One-step bisimulation invariance

## Definition

- ▶ Two  $A$ -structures  $(D, I)$  and  $(D', I')$  are **P-similar** if
  - $\forall d \in D \quad \exists d' \in D' \quad m_I(d) = m_{I'}(d')$
  - $\forall d' \in D' \quad \exists d \in D \quad m_I(d) = m_{I'}(d')$
- ▶ A sentence  $\varphi$  is **P-invariant** if  $P$ -similar  $(D, I)$  and  $(D', I')$  satisfy

$$(D, I) \models \varphi \text{ iff } (D', I') \models \varphi$$

# One-step bisimulation invariance

## Definition

- ▶ Two  $A$ -structures  $(D, I)$  and  $(D', I')$  are **P-similar** if
  - $\forall d \in D \quad \exists d' \in D' \quad m_I(d) = m_{I'}(d')$
  - $\forall d' \in D' \quad \exists d \in D \quad m_I(d) = m_{I'}(d')$
- ▶ A sentence  $\varphi$  is **P-invariant** if  $P$ -similar  $(D, I)$  and  $(D', I')$  satisfy

$$(D, I) \models \varphi \text{ iff } (D', I') \models \varphi$$

**Proposition** Let  $\varphi \in \text{FOE}(A)$  be a sentence.

Then  $\varphi$  is P-invariant iff  $\varphi$  is invariant under surjective homomorphisms.

# One-step bisimulation invariance

## Definition

- ▶ Two  $A$ -structures  $(D, I)$  and  $(D', I')$  are **P-similar** if
  - $\forall d \in D \ \exists d' \in D' \ m_I(d) = m_{I'}(d')$
  - $\forall d' \in D' \ \exists d \in D \ m_I(d) = m_{I'}(d')$
- ▶ A sentence  $\varphi$  is **P-invariant** if  $P$ -similar  $(D, I)$  and  $(D', I')$  satisfy

$$(D, I) \models \varphi \text{ iff } (D', I') \models \varphi$$

**Proposition** Let  $\varphi \in \text{FOE}(A)$  be a sentence.

Then  $\varphi$  is P-invariant iff  $\varphi$  is invariant under surjective homomorphisms.

**Theorem**  $\text{FO} \equiv_s \text{FOE/P}$ :

There is a translation  $(\cdot)^* : \text{FOE} \rightarrow \text{FO}$  s.t.

$$\varphi \text{ is P-invariant iff } \varphi \equiv \varphi^*.$$

# Main Theorem

**Theorem** Let  $M, L \subseteq FOE$  be two one-step languages.

If  $M \equiv_s L/P$  then  $\text{Aut}(M) \equiv_s \text{Aut}(L)/\leftrightarrow$ .

# Main Theorem

**Theorem** Let  $M, L \subseteq FOE$  be two one-step languages.

If  $M \equiv_s L/P$  then  $\text{Aut}(M) \equiv_s \text{Aut}(L)/\cong$ .

**Point of talk**

$\mu\text{ML} \equiv_s \text{MSO}/\cong$  because  $\text{FO} \equiv_s \text{FOE}/P$ .



# Proof of Janin-Walukiewicz Theorem

# Proof of Janin-Walukiewicz Theorem

**Theorem** (Janin & Walukiewicz)  $\mu\text{ML} \equiv_s \text{MSO} / \Leftrightarrow$

# Proof of Janin-Walukiewicz Theorem

**Theorem** (Janin & Walukiewicz)  $\mu\text{ML} \equiv_s \text{MSO} / \Leftrightarrow$

That is, there is a translation  $(\cdot)^* : \text{MSO} \rightarrow \mu\text{ML}$  s.t.

$\varphi$  is bisimulation invariant iff  $\varphi \equiv \varphi^*$ .

# Proof of Janin-Walukiewicz Theorem

**Theorem** (Janin & Walukiewicz)  $\mu\text{ML} \equiv_s \text{MSO} / \Leftrightarrow$

That is, there is a translation  $(\cdot)^* : \text{MSO} \rightarrow \mu\text{ML}$  s.t.

$\varphi$  is bisimulation invariant iff  $\varphi \equiv \varphi^*$ .

## Proof

1. (a)  $\text{MSO} \equiv \text{Aut}(\text{FOE})$  on trees.  
(b)  $\mu\text{ML} \equiv \text{Aut}(\text{FO})$ .
2.  $\text{FO} \equiv_s \text{FOE}/P$
3. If  $M = L/P$  then  $\text{Aut}(M) = \text{Aut}(L)/\Leftrightarrow$

# Final Remarks

- ▶ What is **new** here?

# Final Remarks

- ▶ What is **new** here?
- ▶ Main theorem works at **coalgebraic** level of generality:  
If  $M = L/T$  then  $\text{Aut}(M) = \text{Aut}(L)/\Leftrightarrow$ .

# Final Remarks

- ▶ What is **new** here?
- ▶ Main theorem works at **coalgebraic** level of generality:  
If  $M = L/T$  then  $\text{Aut}(M) = \text{Aut}(L)/\Leftrightarrow$ .
- ▶ Main Theorem generalizes to **restricted** classes of models:

# Final Remarks

- ▶ What is **new** here?
- ▶ Main theorem works at **coalgebraic** level of generality:  
If  $M = L/T$  then  $\text{Aut}(M) = \text{Aut}(L)/\Leftrightarrow$ .
- ▶ Main Theorem generalizes to **restricted** classes of models:  
What about an **FMT** version of the Janin-Walukiewicz Theorem?



# Final Remarks

- ▶ What is **new** here?
- ▶ Main theorem works at **coalgebraic** level of generality:  
$$\text{If } M = L/T \text{ then } \text{Aut}(M) = \text{Aut}(L)/\Leftrightarrow.$$
- ▶ Main Theorem generalizes to **restricted** classes of models:  
What about an **FMT** version of the Janin-Walukiewicz Theorem?
- ▶ Approach works for restricted classes of automata:

# Final Remarks

- ▶ What is **new** here?
- ▶ Main theorem works at **coalgebraic** level of generality:  
$$\text{If } M = L/T \text{ then } \text{Aut}(M) = \text{Aut}(L)/\cong.$$
- ▶ Main Theorem generalizes to **restricted** classes of models:  
What about an **FMT** version of the Janin-Walukiewicz Theorem?
- ▶ Approach works for restricted classes of automata:

$$\text{WMSO}/\cong = ?$$

(Carreiro, Facchini, Venema & Zanasi, forthcoming)

# Reference

Y. Venema,

Expressiveness modulo bisimilarity: a coalgebraic perspective,  
to appear in: A. Baltag and S. Smets (eds.), van Benthem,  
Outstanding Contributions to Logic, Springer, 201x.

Downloadable from <http://staff.science.uva.nl/~yde>