

A Note on the Complexity of Comparing Succinctly Represented Integers, with an Application to Maximum Probability Parsing

KOUSHA ETESSAMI and ALISTAIR STEWART, University of Edinburgh
MIHALIS YANNAKAKIS, Columbia University

The following two decision problems capture the complexity of comparing integers or rationals that are succinctly represented in product-of-exponentials notation, or equivalently, via arithmetic circuits using only multiplication and division gates, and integer inputs.

Input instance: Four lists of positive integers:

$$a_1, \dots, a_n \in \mathbb{N}_+^n; \quad b_1, \dots, b_n \in \mathbb{N}_+^n; \quad c_1, \dots, c_m \in \mathbb{N}_+^m; \quad d_1, \dots, d_m \in \mathbb{N}_+^m;$$

where each of the integers is represented in binary.

Problem 1 (equality testing): Decide whether $a_1^{b_1} a_2^{b_2} \dots a_n^{b_n} = c_1^{d_1} c_2^{d_2} \dots c_m^{d_m}$.

Problem 2 (inequality testing): Decide whether $a_1^{b_1} a_2^{b_2} \dots a_n^{b_n} \geq c_1^{d_1} c_2^{d_2} \dots c_m^{d_m}$.

Problem 1 is easily decidable in polynomial time using a simple iterative algorithm. Problem 2 is much harder. We observe that the complexity of Problem 2 is intimately connected to deep conjectures and results in number theory. In particular, if a refined form of the *ABC conjecture* formulated by Baker in 1998 holds, or if the older *Lang-Waldschmidt conjecture* (formulated in 1978) on linear forms in logarithms holds, then Problem 2 is decidable in P-time (in the standard Turing model of computation). Moreover, it follows from the best available quantitative bounds on linear forms in logarithms, namely, by Baker and Wüstholz [1993] or Matveev [2000], that if m and n are fixed universal constants then Problem 2 is decidable in P-time (without relying on any conjectures). This latter fact was observed earlier by Shub [1993].

We describe one application: P-time maximum probability parsing for arbitrary stochastic context-free grammars (where ϵ -rules are allowed).

Categories and Subject Descriptors: F.2.1 [Analysis of Algorithms and Problem Complexity]: Numerical Algorithms and Problems; F.4.2 [Mathematical Logic and Formal Languages]: Grammars and Other Rewriting Systems—Parsing; G.3 [Probability and Statistics]

General Terms: Algorithms, Theory

Additional Key Words and Phrases: Succinct representation of numbers, arithmetic circuits, logarithmic forms, ABC conjecture, Lang-Waldschmidt conjecture, stochastic context-free grammars, probabilistic parsing

This research was partially supported by the Royal Society, and by NSF grants CCF-1017955 and CCF-1320654.

Authors' addresses: K. Etessami and A. Stewart, School of Informatics, University of Edinburgh, Old College, South Bridge, Edinburgh EH8 9YL, United Kingdom; email: kousha@inf.ed.ac.uk, stewart.al@gmail.com; M. Yannakakis, Department of Computer Science, Columbia University, 455 Computer Science Building, 1214 Amsterdam Avenue, Mail Code 0401, New York, NY 10027; email: mihalis@cs.columbia.edu.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

2014 Copyright is held by Owner/Author. Publication rights licensed to ACM. 1942-3454/2014/05-ART9 \$15.00

DOI: <http://dx.doi.org/10.1145/2601327>

ACM Reference Format:

Etessami, K., Stewart, A., and Yannakakis, M. 2014. A note on the complexity of comparing succinctly represented integers, with an application to maximum probability parsing. *ACM Trans. Comput. Theory* 6, 2, Article 9 (May 2014), 23 pages.
DOI: <http://dx.doi.org/10.1145/2601327>

1. INTRODUCTION

For many computations involving large integers, or large/small nonzero rationals, it is convenient to be able to manipulate and compare the numbers without having to compute a standard binary representation of them. Indeed, in many settings, it is intractable to compute such a binary representation. This has motivated compact representations such as classic floating point, but floating point numbers also suffer a loss of information (precision), which one would like to avoid if possible.

There are a number of succinct representations one could consider for such a purpose. One approach is to represent integers via **arithmetic circuits** (straight-line programs), with gates $\{+, -, *\}$, and with integer inputs (represented in binary). However, the problem of deciding whether an integer represented via an arithmetic circuit is \geq another such integer, referred to as **PosSLP** [Allender et al. 2009], captures all of polynomial time in the unit-cost arithmetic RAM model of computation. The best complexity upper bounds we know for PosSLP in the standard Turing model of computation is the 4th level of the *counting hierarchy*, $P^{PPP^{PPP}}$, as established in Allender et al. [2009]. PosSLP subsumes other hard problems whose complexity is open, like the well-known *square-root-sum* problem [Garey et al. 1976], and it appears highly unlikely that one could show that PosSLP is even in NP. On the other hand, as noted in Allender et al. [2009], the problem of testing **equality** of integers represented by two such arithmetic circuits, **EquSLP**, is P-time equivalent to *polynomial identity testing*, and can be decided in **coRP**. However, it remains open whether EquSLP is in NP and showing this would already imply hard circuit lower bounds [Kabanets and Impagliazzo 2003], so it is likely to be difficult. On the other hand, there are no hardness results known for PosSLP with respect to standard complexity classes, beyond P-hardness. In particular, PosSLP is not known to be NP-hard.

Note that if the arithmetic in the computation is confined to only *linear* operations $\{+, -\}$ on registers, and multiplication by constants in the input, then the encoding length of the numbers is linear in the number of arithmetic operations, so we can represent all the numbers exactly, and P-time in the Turing model can simulate polynomial-time unit-cost *linear* arithmetic computation.

Now consider another natural restricted class of arithmetic circuits, which turn out to be useful in a number of settings: arithmetic circuits containing only **gates** $\{*, /\}$. An essentially equivalent representation is the following: For a list of rational numbers $a = \langle a_1, \dots, a_n \rangle$, and a list of integers $b = \langle b_1, \dots, b_n \rangle$, both of dimension n , we use a^b as a shorthand notation for: $a_1^{b_1} a_2^{b_2} \dots a_n^{b_n}$. We shall refer to this succinct representation of integers and rationals as **product of exponentials (PoE) representation**. PoE representation is easily seen to be equivalent to representation via arithmetic circuits with integer inputs given in binary and with multiplication and division gates $\{*, /\}$. The following is shown in the appendix.

PROPOSITION 1.1. *There is a simple P-time translation from a given number represented in PoE to the same number represented as an arithmetic circuit over $\{*, /\}$ with integer inputs (represented in binary). Likewise, there is a simple P-time translation in the other direction.*

Consider the problem of deciding whether one rational number, a^b , given in PoE representation, is greater than (or, respectively, equal to) another rational number c^d , given in PoE. We remark that, again, the inequality testing problem basically captures the power of polynomial time in the unit-cost arithmetic RAM model of computation, where the only arithmetic operations permitted are $\{*, /\}$.

Input instance: Four lists of positive integers:

$$a_1, \dots, a_n \in \mathbb{N}_+^n; \quad b_1, \dots, b_n \in \mathbb{N}_+^n; \quad c_1, \dots, c_m \in \mathbb{N}_+^m; \quad d_1, \dots, d_m \in \mathbb{N}_+^m;$$

where each of the integers is represented, as usual, in binary.

Problem 1 (equality testing): Decide whether or not $a^b = c^d$.

Problem 2 (inequality testing): Decide whether or not $a^b \geq c^d$.

Note that, by rearrangement, these problems are equivalent to the versions allowing bases a_i and c_j to be rationals (encoded in binary), and allowing b_i and d_j to be any integers (in binary).

Let us note that PoE representation is in fact already widely used in practice. Specifically, because iterated multiplication may make numbers very small or very large, practitioners often explicitly recommend using a *logarithmic transformation* to represent numbers such as $a_1^{b_1} \cdots a_n^{b_n}$ by

$$b_1 \log(a_1) + b_2 \log(a_2) + \cdots + b_n \log(a_n).$$

This allows multiplications and divisions to be carried out by using only addition on the coefficients of the log representations. Note that such “log representations” are basically equivalent to PoE, as long as the logarithms are only interpreted *symbolically*. (Of course, one still needs to be able to compare such sums of logs, and we will return to this shortly.) One setting where log transformation is recommended in practice is for the analysis of Hidden Markov Models (HMMs) using the Viterbi algorithm, and for probabilistic parsing. For example, the book by Durbin et al. [1999] (Section 3.6) says the following.

On modern floating point processors we will run into numerical problems when multiplying many probabilities in the Viterbi, forward, or backward algorithms. For DNA, for instance, we might want to model genomic sequences of 100 000 bases or more. Assuming that the product of one emission and one transition probability is 0.1, the probability of the Viterbi path would then be on the order of $10^{-100000}$. Most computers would behave badly with such numbers..... For the Viterbi algorithm we should always use the logarithm of all probabilities. Since the log of a product is the sum of the logs, all the products are turned into sums..... It is more efficient to take the log of all of the model parameters before running the Viterbi algorithm, to avoid calling the logarithm function repeatedly during the dynamic programming iterations [Durbin et al. 1999, pages 78–79].

We justify these comments from a complexity-theoretic viewpoint. In fact, we do so in the more general context of computing a maximum probability parse tree for a given string and given stochastic context-free grammar (SCFG), which generalizes the Viterbi algorithm for finite-state HMMs. We will observe that if deep conjectures in number theory hold then Problem 2 can be solved in polynomial time by employing the PoE (or log) representation, and also that the PoE representation can be used to obtain P-time algorithms for computing a maximum probability parse tree for a given string with a given SCFG, and for solving related problems.

We first show **Problem 1 is decidable in P-time using an easy iterative algorithm.** Problem 2 is much harder. We observe that **if the Lang-Waldschmidt conjecture [Lang 1978] holds, then Problem 2 is decidable in P-time.** Likewise, **if Baker's refinement [Baker 1998] of the ABC conjecture of Masser and Oesterlè holds, then again it implies Problem 2 is decidable in P-time.** The ABC conjecture is considered one of the central conjectures of modern number theory (see, e.g., Granville and Tucker [2002], Baker and Wüstholz [2000, 2007], and Waldschmidt [2004]).

Furthermore, we observe that the best currently known quantitative bound in Baker's theory of linear forms in logarithms, for example, those due to Baker and Wüstholz [1993] or Matveev [1998, 2000], yield that when m and n are fixed universal constants, Problem 2 is decidable in polynomial time. We note that Shub has already observed this fact in Shub [1993, Theorem 6, page 454], namely that for fixed constants m and n , Problem 2 is decidable in P-time.¹ Although Shub stated a correct theorem, and sketched a proof based on the same ideas, the proof in Shub [1993] contains some inaccuracies. In particular, it mis-states the lower bounds for linear forms in logarithms. In fact, the lower bound quoted in Shub [1993] is false, as we shall explain in a footnote to Proposition 3.7. For this reason, in Proposition 3.7, we provide a proof of this result, first observed by Shub [1993], using the best currently available bounds on linear forms in logarithms [Baker and Wüstholz 1993; Matveev 1998, 2000].

It is well known that the ABC conjecture, and related conjectures involving explicit bounds for linear forms in logarithms, have important applications for *effective solvability* of various diophantine equations. However, to our knowledge, it has not been observed previously that these number-theoretic conjectures are also connected to the *polynomial-time solvability* of basic problems such as the comparison of succinctly represented numbers.

We give one application to maximum probability parsing for *stochastic context-free grammars* (SCFG). Computing the maximum probability (most likely) parse of a given string for a SCFG is a basic task in statistical natural language processes (NLP) (see, e.g., Manning and Schütze [1999]). Until now, it was only known to be computable in P-time for particular classes of SCFGs, in particular SCFGs in Chomsky Normal Form, and SCFGs not containing arbitrary ϵ -rules. For general SCFGs, G , the maximum probability of a parse tree for even a fixed string, w , may be as small as $1/2^{2^{|G|}}$, where $|G|$ is the encoding size of the SCFG. Thus, one cannot express such probabilities in P-time in binary representation. However, **the maximum parse tree probabilities can be expressed concisely in PoE, and if we can check inequalities on such encodings of rational numbers efficiently, then we can compute the maximum parse tree probability in P-time.**

Specifically, we show that if Baker's refined ABC conjecture holds, or if the Lang-Waldschmidt conjecture holds, then given an arbitrary SCFG G , and given an arbitrary string $w \in \Sigma^*$, there is a polynomial-time algorithm that: (1) computes a (succinct representation of) a *maximum probability parse tree* for the string w and also computes (a succinct representation of) the exact maximum parse probability $p_{G,w}^{\max}$; and (2) given also a rational probability q given in binary (or in PoE), decides whether the maximum parse probability of w , $p_{G,w}^{\max}$, satisfies $p_{G,w}^{\max} \geq q$; (3) given also another string $w' \in \Sigma^*$, decides whether $p_{G,w}^{\max} \geq p_{G,w'}^{\max}$. Furthermore, when the SCFG has a fixed constant number, m , of distinct probabilities labeling its rules, all of these problems (1)–(3) are in P-time (in the Turing model), without assuming any number theoretic conjectures. Finally, we show that essentially the same algorithm can be used to approximate the

¹We thank one of the anonymous referees for bringing Shub's paper [Shub 1993] to our attention.

Input: 4 lists a, b, c, d , of positive integers, a & c not containing 1, $|a| = |b|$, & $|c| = |d|$.

Task: Decide whether or not $a^b = c^d$.

```

while there is some  $i \in [a]$  and  $j \in [c]$  such that  $GCD(a_i, c_j) > 1$  do
  Let  $i \in [a]$  and  $j \in [c]$  be such that  $g_{i,j} = GCD(a_i, c_j) > 1$ ;
  Let  $a_i \leftarrow a_i / g_{i,j}$ ; Let  $c_j \leftarrow c_j / g_{i,j}$ ;
  if  $a_i = 1$  then
    Remove  $a_i$  from list  $a$ , and remove  $b_i$  from list  $b$ 
  end if
  if  $c_j = 1$  then
    Remove  $c_j$  from list  $c$ , and remove  $d_j$  from list  $d$ 
  end if
  if  $b_i > d_j$  then
    Append integer  $g_{i,j}$  to the end of list  $a$ ;
    Append integer  $b_i - d_j$  to the end of list  $b$ ;
  else if  $b_i < d_j$  then
    Append integer  $g_{i,j}$  to the end of list  $c$ ;
    Append integer  $d_j - b_i$  to the end of list  $d$ ;
  end if
end while
if  $a$  and  $c$  are both the empty list then
  return EQUAL
else
  return NOT-EQUAL
end if

```

Fig. 1. Simple P-time algorithm for Problem 1.

maximum parsing probability and compute (a succinct representation of) an ϵ -optimal parse tree for a string w and a SCFG G in time polynomial in the size of G, w and $\log(1/\epsilon)$, without assuming any conjectures.

2. DECIDING EQUALITY OF SUCCINCT INTEGERS IN P-TIME

We now give a simple iterative P-time algorithm for Problem 1 (equality testing). The algorithm is in Figure 1. It simply repeatedly computes $g_{i,j} = GCD(a_i, c_j)$ for pairs a_i and c_j , and if $g_{i,j} > 1$, then it does the appropriate adjustments on the succinct representations. It terminates when $g_{i,j} = 1$ for all i, j . The two remaining numbers are 1 if and only if the original numbers were equal.

In more detail, at the start of the iterative algorithm, we initialize four lists of positive integers: $a := \langle a_1, \dots, a_n \rangle$, $b := \langle b_1, \dots, b_n \rangle$, $c := \langle c_1, \dots, c_m \rangle$, and $d := \langle d_1, \dots, d_m \rangle$. We can assume wlog that lists a and c do not contain the number 1. For a list g , we use $|g|$ to denote its length. So, initially, $|a| = |b| = n$ and $|c| = |d| = m$. Every iteration of the algorithm will maintain the following invariant: $|a| = |b|$ and $|c| = |d|$. For a list g , we let $[g] = \{1, \dots, |g|\}$. For a list g , and for $i \in [g]$, we use g_i to denote the i th element of the list g . Given two lists of integers, g and f , where $|g| = |f| = r$, we use g^f to denote $g_1^{f_1} \dots g_r^{f_r}$.

PROPOSITION 2.1. *The algorithm in Figure 1 decides Problem 1, and runs in polynomial time.*²

²It is worth noting that a more careful implementation of this simple algorithm, based on existing “factor refinement” procedures [Bach et al. 1993; Bernstein 2005], can be used to solve Problem 1 very efficiently.

PROOF. For the correctness of the algorithm, we first observe that the following invariant is maintained: the equality

$$a^b = c^d \quad (1)$$

holds before an iteration of the while loop if and only if it holds after an iteration of the while loop.

To see why this is the case, suppose that $GCD(a_i, c_j) = g_{i,j} > 1$, and suppose that an iteration of the while loop is conducted using this i and j . Then, it is clear that the new lists a , b , c , and d are obtained by simply factoring $g_{i,j}$ out of a_i and c_j on the left and right side of Eq. (1), and then dividing both sides of the Eq. (1) by $g_{i,j}^{d_j}$ or by $g_{i,j}^{b_i}$, depending, on whether $b_i \geq d_j$, or $d_j \geq b_i$, respectively. Note that when $b_i = d_j$, dividing both sides by $g_{i,j}^{b_i}$ eliminates this power of $g_{i,j}$ from both sides, so we do not need to include a power of $g_{i,j}$ on either side. Since factoring out $g_{i,j}$ and dividing both sides of the equation by a positive value are reversible, we conclude that the invariant is maintained.

Let us now argue that if the algorithm halts, that is, if the while loop terminates, then the output is correct. Indeed, if the while loop terminates, this means for every pair of numbers a_i and c_j in the lists a and c we have $GCD(a_i, c_j) = 1$. Thus, we also have $GCD(a^b, c^d) = 1$. But in that case, if either $a^b \neq 1$ or $c^d \neq 1$, then $a^b \neq c^d$. Thus, if the while loop halts the algorithm correctly returns “EQUAL” or “NOT-EQUAL” depending on whether or not $a^b = c^d$ for the original input lists.

The only thing left to establish is that the algorithm always halts and runs in polynomial time.

For a list of positive integers a , not containing the number 1, let us call another list a' of positive integers a *factored subform* of a , if there is a mapping $\phi : [a'] \rightarrow [a]$ that maps indices $r \in [a']$ to indices $\phi(r) \in [a]$, such that for all $i \in [a]$

$$\left(\prod_{r \in \phi^{-1}(i)} a'_r \right) \mid a_i.$$

In other words, the product of all entries of a' that map to the entry a_i of a should divide a_i .

We shall call a' a *nontrivial* factored subform of a if the list a' does not contain any entries equal to 1 either, and furthermore no permutation of the list a' is identical to the list a .

Next, let us observe that, after each iteration of the While loop, the positive integer lists a and c must each be nontrivial factored subforms of the respective positive integer lists a and c prior to that iteration of the while loop. Thus, by induction on the number of iterations, after any number of iterations of the while loop we must have a and c consisting of nontrivial factored subforms of the original input lists a and c of positive integers.

But the while loop must therefore terminate, because by the fundamental theorem of arithmetic (unique prime factorization) there can not exist an unbounded sequence of lists of positive integers

$$a^0, a^1, a^2, a^3, \dots$$

such that each one does not contain the number 1, and such that for all $i \in \mathbb{N}$ a^{i+1} is a nontrivial factored subform of a^i .

Furthermore, for the same reason, the while loop must terminate after a number of iterations that is polynomial in the encoding size of the original lists a and c . Namely,

the number of iterations can not be greater than the number of prime factors of the integers in the lists a and c .

Furthermore, the encoding size of the lists a , b , c , and d , always remains polynomial in the encoding size of the original input lists. This is so, firstly, because a and c always remain factored subforms of the original lists, respectively, and furthermore because the maximum value of the positive integers in lists b and d (which are always the same size as their corresponding lists a and c), is never more than their maximum value in the original lists b and d , respectively.

It is then clear that each iteration can be carried out in time polynomial in the encoding size of the original lists, because each iteration of the while loop, when the current lists given by a , b , c , and d , requires at most $|a| \cdot |c|$ computations of GCDs on pairs of integers that are no bigger than the maximum integer in the original lists, and as already established at any iteration the lists themselves are only polynomially bigger than the original lists. \square

3. DECIDING INEQUALITIES BETWEEN SUCCINCT INTEGERS

We now consider the much harder Problem 2 (inequality testing). We first recall a deep theorem due to Baker and Wüstholz on explicit quantitative bounds on linear forms in logarithms.³ Let a_1, \dots, a_n be positive integers, none of which are equal to 0 or to 1, let b_1, \dots, b_n be arbitrary integers not all equal to 0. Let e be the base of the natural logarithm, and define $B := \max\{|b_1|, |b_2|, \dots, |b_n|, e\}$. Let $h'(a_i) = \max\{\log a_i, 1\}$, where \log denotes the natural logarithm. Let

$$\Lambda(a, b) := \log(a^b) = b_1 \log a_1 + b_2 \log a_2 + \dots + b_n \log a_n.$$

For any list a of positive integers, and list b of integers, both of length n , let

$$G(a, b) := e^{-C(n)h'(a_1)h'(a_2)\dots h'(a_n)\log B},$$

where $C(n) := 18(n+1)!n^{n+1}32^{n+2}\log(2n)$.

THEOREM 3.1 [BAKER AND WÜSTHOLZ 1993]. *For any list a of positive integers and any list b of nonzero integers,⁴ where both lists have the same length n , if $\Lambda(a, b) \neq 0$, then*

$$|\Lambda(a, b)| \geq G(a, b).$$

³The general theorem regards logarithms of algebraic numbers. We will state it in the special case of logarithms of standard integers, which suffices for our purposes.

⁴Although this will be obvious to experts, let us explain why this theorem is indeed a specialization (to positive integer a_i 's) of Baker-Wüstholz's. The theorem in Baker and Wüstholz [1993] allows a_i 's to be algebraic numbers, and $\log a_i$ is defined to be *any* determination of the log. Clearly, when a_i is a rational positive integer, $\log a_i$ is uniquely determined. Furthermore, if d is the degree of the field extension $\mathbb{Q}(a_1, \dots, a_n)$ over \mathbb{Q} , then in Baker and Wüstholz [1993], the "height" function $h'(a_i)$ is defined instead to be $h'(a_i) = \max\{h(a_i), (1/d)|\log a_i|, 1/d\}$, where $h(a_i)$ is the *absolute logarithmic Weil height* of a_i , which we will discuss next. First note that in the setting of positive integers, a_i , clearly $d = 1$, and thus $h'(a_i) = \max\{h(a_i), \log a_i, 1\}$. Now, one way to define the absolute logarithmic Weil height $h(a_i)$ (see Schinzel [2000]) is this: let $p(x) \in \mathbb{Z}[x]$ be the minimal polynomial for the algebraic number a_i , suppose $p(x)$ has degree d , let f_0 be the leading coefficient of $p(x)$, and let $\alpha_1, \dots, \alpha_d$ be the complex roots of d (with repetition). Then

$$h(a_i) = \log((|f_0| \prod_{i=1}^d \max(1, |\alpha_i|))^{1/d}).$$

Now, in the simple case where a_i is a positive integer, we see immediately that its minimal polynomial is $p(x) \equiv x - a_i$, and thus that $h(a_i) = \log a_i$. Thus, for positive integers a_i , indeed $h'(a_i) = \max\{\log a_i, 1\}$, as given.

A lower bound similar to Baker-Wüstholz's was obtained by Waldschmidt [1993]. A somewhat improved bound was obtained more recently by Matveev [1998, 2000], who showed $|\Lambda(a, b)| \geq H(a, b)$, where $H(a, b) := e^{-C'(n)h'(a_1)h'(a_2)\dots h'(a_n)\log B}$ and $C'(n) := 2.9(2e)^{2n+6}(n+2)^{9/2}$. (See Nesterenko's presentation [Nesterenko 2003].) The improved bound by Matveev does not have any stronger consequences for our complexity theoretic purposes, beyond that of Theorem 3.1.

These results constitute the current state of the art: they are the best known lower bounds for (homogeneous) linear forms in logarithms of rational numbers (and for more general numbers). Next we state an older conjecture of Lang and Waldschmidt, which would significantly strengthen both Theorem 3.1 and Matveev's improved bound.

CONJECTURE 3.2 (LANG-WALDSCHMIDT 1978 (CF. LANG [1978]; WALDSCHMIDT [2004])). *For every $\epsilon > 0$, there is a $C(\epsilon) > 0$, such that for any list of positive integers a and any list of nonzero integers b , where both lists a and b are of length n , if $\Lambda(a, b) \neq 0$, then:*

$$|\Lambda(a, b)| \geq \frac{C(\epsilon)^n B}{(|b_1| \cdots |b_n| |a_1| \cdots |a_n|)^{1+\epsilon}}. \quad (2)$$

We next recall a central conjecture in modern number theory, namely the *ABC conjecture* (due to Masser and Oesterlè), and a more recent refinement of the ABC conjecture, given by Baker. See, for example, Baker and Wüstholz [2000] and Granville and Tucker [2002], for background on the conjecture. For any integer m , let $N(m) := (\prod_{p|m} p)$, denote the product of all distinct prime numbers p that divide m (i.e., without repetition of any prime p).

CONJECTURE 3.3 (ABC CONJECTURE [MASSER 1985; OESTERLÈ 1988]). *For every $\epsilon > 0$, there is a $K(\epsilon) > 0$, such that for any positive integers a, b, c , such that $a + b = c$, and such that a, b, c are relatively prime (i.e., such that $\text{GCD}(a, b) = 1$), we have:*

$$c \leq K(\epsilon) N(abc)^{1+\epsilon}.$$

For any positive integer m , let $\omega(m)$ denote the number of distinct prime numbers that divide m . Baker [1998] put forward several refinements of the ABC conjecture which make the “constants” more explicit. Among them was the following.

CONJECTURE 3.4 (BAKER'S REFINEMENT OF THE ABC CONJECTURE [BAKER 1998]). *There are absolute constants, $K, K' > 0$, such that for any integers a, b, c that are relatively prime, and such that $a + b + c = 0$, for any $\epsilon > 0$, we have⁵:*

$$\max(|a|, |b|, |c|) \leq K' \epsilon^{-K\omega(ab)} N(abc)^{1+\epsilon}.$$

⁵It is not obvious that Conjecture 3.4 is a refinement of (i.e., implies) the standard ABC Conjecture 3.3, but as pointed out in Baker [1998], this is the case, the key reason being that for integers $n > 1$, $\omega(n) \in O(\log(n)/\log(\log(n)))$. Indeed, a little calculation shows that Conjecture 3.4 implies the ABC conjecture with $K(\epsilon) \in 2^{2^{O(1/\epsilon)}}$.

Baker [1998] showed that Conjecture 3.4 implies the following (slightly weakened) variant of the Lang-Waldschmidt conjecture:

Consequence of Conjecture 3.4 (see Baker [1998]). There is some absolute constant K'' such that for any list of positive integers a and any list of nonzero integers b , where both lists a and b are of length n , if $\Lambda(a, b) \neq 0$, then

$$|\Lambda(a, b)| \geq e^{-K''(\log a_1 + \log a_2 + \dots + \log a_n)(\log \max_i |b_i|)}. \quad (3)$$

In fact, Baker [1998] further showed that a more general (p-adic) version of the bound (3) implies the ABC conjecture. Thus, as noted in Granville and Tucker [2002], the ABC conjecture and such improved quantitative bounds on linear forms in logarithms are intimately related questions. It is perhaps worth mentioning that Baker [2007] expresses doubt about the stronger Lang-Waldschmidt Conjecture. However, he then states a conjecture implying bound (3), which is strong enough for our purposes, and he notes that it originates from his refined ABC conjecture in Baker [1998].

Let us now explore the intimate connection between Problem 2, Theorem 3.1, and Conjectures 3.2, 3.3, and 3.4. Suppose we want to decide whether $a^b \geq c^d$. Clearly, we can first check for equality (in P-time). If equality does not hold, then our goal is to decide $a^b > c^d$, knowing $a^b \neq c^d$. Equivalently, our goal is to decide whether $a^b/c^d > 1$, given that $a^b/c^d \neq 1$. Equivalently, we want to decide whether $\log(a^b c^{-d}) > 0$, given that $\log(a^b c^{-d}) \neq 0$.

So, Problem 2 is P-time equivalent to the following problem: Given positive integers $a = \langle a_1, \dots, a_n \rangle$, and integers $b = \langle b_1, \dots, b_n \rangle$, both encoded in binary, decide whether $\Lambda(a, b) > 0$, with the promise that $\Lambda(a, b) \neq 0$.

We can compute an approximation of the logarithmic form $\Lambda(a, b)$, to within any given desired additive error, $\epsilon > 0$, in time polynomial in the encoding size of a and b , and in $\log(1/\epsilon)$. To see this, we first observe the well-known fact that logarithms of integers can be approximated in P-time (in the standard Turing model). This is, of course, classic. Nevertheless, we provide a proof, both for completeness and because most treatments of the numerical computation of logarithms only consider arithmetic complexity, rather than complexity in the Turing model. Recall we use $\log(x)$ to denote the *natural* logarithm of x , and use $\log_2(x)$ to denote the log base 2.

PROPOSITION 3.5. *There is an algorithm that, given a positive integer a , encoded in binary, and given a positive integer j , encoded in unary, computes a rational value v_a , such that*

$$|\log(a) - v_a| < 2^{-j}$$

The algorithm runs in time polynomial in j and $\log_2(a)$ (in the Turing model).

Proposition 3.5 is proved in the appendix. We can use it to easily prove the following.

PROPOSITION 3.6. *Given as input positive integers $a = \langle a_1, \dots, a_n \rangle$ and integers $b = \langle b_1, \dots, b_n \rangle$, both encoded in binary, and given a positive integer j (given in unary), there is an algorithm that runs in P-time (i.e., in time polynomial in j and in the encoding size of lists a and b) and outputs rational value $v_{a,b}$, such that $|\Lambda(a, b) - v_{a,b}| < \frac{1}{2^j}$.*

PROOF. Given $a = \langle a_1, \dots, a_n \rangle$, and given $b = \langle b_1, \dots, b_n \rangle$, for each $i = 1, \dots, n$, we will first compute an approximation v_{a_i} of $\log(a_i)$ such that

$$|\log(a_i) - v_{a_i}| < \frac{1}{2^{j + \log_2(|b_i|) + \log_2(n)}}.$$

By Proposition 3.5, we can compute such a v_a in time polynomial in the encoding size of the input, a and b , and in j .

Then, we let $v_{a,b} := \sum_{i=1}^n b_i v_{a_i}$. Finally, we observe that this yields:

$$\begin{aligned} |\log(\Lambda(a, b)) - v_{a,b}| &= \left| \sum_{i=1}^n (b_i \log(a_i)) - b_i v_{a_i} \right| \\ &\leq \sum_{i=1}^n |b_i| |\log(a_i) - v_{a_i}| \\ &\leq \sum_{i=1}^n |b_i| 2^{-\log |b_i| - j - \log_2(n)} \\ &= \sum_{i=1}^n 2^{-j}/n = 2^{-j}. \end{aligned}$$

Thus, the rational number $v_{a,b}$, which can be computed in time polynomial in j , and in the encoding size of a and b , is the desired additive approximation of $\Lambda(a, b)$. \square

PROPOSITION 3.7

- (1) *If the ABC conjecture, as refined by Baker (Conjecture 3.4), holds, or if the Lang-Waldschmidt conjecture (Conjecture 3.2) holds, then Problem 2 is decidable in P-time.*
- (2) *(cf. [Shub 1993, Theorem 6]) When m and n are fixed constants, Problem 2 is (unconditionally) decidable in P-time.⁶*

PROOF. To prove both (1) and (2), we simply compute a sufficiently good additive approximation to $\Lambda(a, b)$, using Proposition 3.6, and we then apply the ABC conjecture (Conjecture 3.4) and its consequence (3) or the Lang-Waldschmidt Conjecture (Conjecture 3.2). Likewise, to obtain (2), after approximating $\Lambda(a, b)$, we apply the Baker-Wüstholz Theorem (Theorem 3.1).

In more detail, we start by proving (2): we are given lists a and b of length n and lists c and d of length m , with m and n fixed constants. Let $A := \max\{\max_i a_i, \max_j c_j\}$. Let $B := \max\{|b_1|, \dots, |b_n|, |d_1|, \dots, |d_m|, e\}$. First, we check in P-time if $a^b = c^d$. If this is the case, then we are done. So assume that $a^b \neq c^d$. If $a^b c^{-d} \neq 1$, that is, $\log(a^b c^{-d}) \neq 0$, then by Theorem 3.1 we have

$$|\log(a^b c^{-d})| \geq 2^{-K(\prod_{i=1}^n \log(a_i))(\prod_{j=1}^m \log(c_j)) \log B} \geq 2^{-K(\log A)^{m+n} \log B} \quad (4)$$

⁶As mentioned in the introduction, Shub (Theorem 6 in Shub [1993, page 454]) already observed part (2). Shub sketched a proof based on precisely the same ideas as ours, but the sketched proof in Shub [1993] misstates the known lower bounds on linear forms in logarithms. In fact, the lower bound quoted in Shub [1993] is provably false, and violates Dirichlet's approximation theorem. Namely, Shub [1993] states that for any positive integers a_1, \dots, a_m , and nonzero integers n_1, \dots, n_m , if $\sum_{i=1}^m n_i \log(a_i) \neq 0$, then $|\sum_{i=1}^m n_i \log(a_i)| > J(\bar{a}) > 0$, where $J(\bar{a}) = 2^{-K \cdot m \cdot (\log(\max_i a_i))^m \cdot \log \log(\max_i a_i)}$, for some fixed constant K . Note that this stated lower bound $J(\bar{a})$ depends only on $\bar{a} = (a_1, \dots, a_m)$, and is independent of the coefficients n_i . However, this is false already for linear forms in two logarithms. Consider, e.g., $\log(3)$ and $\log(5)$, and let $\alpha := \log(3)/\log(5)$. By Dirichlet's approximation theorem, for any real number α , and for all $\epsilon > 0$, there is a rational number p/q , such that $|\alpha - p/q| < \epsilon/q$, and thus that $|q \log(3) - p \log(5)| < \epsilon \cdot \log(5)$. Thus note that we can choose $\epsilon = \epsilon'/\log(5) > 0$, for an arbitrary $\epsilon' > 0$. Thus, for all $\epsilon' > 0$, there exist integers q and p such that $|q \log(3) - p \log(5)| < \epsilon'$. This contradicts the lower bound on linear forms in logarithms quoted in Shub [1993]. For this reason, we provide a proof here, using the best currently known lower bounds.

for some fixed constant K (that depends on n and m). But by Proposition 3.6, when m and n are fixed constants, we can compute in time polynomial in the encoding size of a, b, c , and d , a rational value $v_{a,b,c,d}$ such that

$$|\log(a^b c^{-d}) - v_{a,b,c,d}| < 2^{-K(\log A)^{m+n} \log B}. \quad (5)$$

Now suppose $v_{a,b,c,d} \geq 0$. Then, if $\log(a^b c^{-d}) \leq 0$, we would have $|\log(a^b c^{-d}) - v_{a,b,c,d}| = v_{a,b,c,d} + |\log(a^b c^{-d})| \geq 2^{-K(\log A)^{m+n} \log B}$, the last inequality following by (4). However, this contradicts the inequality (5) just given. Thus, if $v_{a,b,c,d} \geq 0$, then it follows that $\log(a^b c^{-d}) > 0$, that is, that $a^b > c^d$.

Similarly, suppose $v_{a,b,c,d} < 0$. Then, if $\log(a^b c^{-d}) \geq 0$, we would have $|\log(a^b c^{-d}) - v_{a,b,c,d}| = |\log(a^b c^{-d})| - v_{a,b,c,d} \geq 2^{-K(\log A)^{m+n} \log B}$, by inequality (4). However, again, this contradicts (5). Thus, if $v_{a,b,c,d} < 0$ then $\log(a^b c^{-d}) < 0$, that is, $a^b < c^d$.

To prove (1), for example, in the case, where we use the consequences of Baker's refined ABC conjecture (Conjecture 3.4, and in particular the bound (3)), exactly the same argument goes through if we instead compute an approximation $v_{a,b,c,d}$ such that

$$|\log(a^b c^{-d}) - v_{a,b,c,d}| < 2^{-K'''((\sum_{i=1}^n \log(a_i)) + (\sum_{j=1}^m \log(c_j)))(\log B)},$$

which again, we know we can do in time polynomial in the encoding size of a, b, c , and d . Similarly, exactly the same argument goes through for proving (1) based on the Lang-Waldschmidt conjecture. \square

4. MAXIMUM PROBABILITY PARSING FOR SCFGS

We now describe an application to the problem of computing a *maximum probability parse tree* for a given string on a given arbitrary *stochastic context-free grammar* (SCFG). For particular classes of grammars (e.g., those in Chomsky Normal Form), there are well-known dynamic programming algorithms for this (based on the CKY parsing algorithm), which generalize the well-known Viterbi algorithm for HMMs (see, e.g., Manning and Schütze [1999]). For arbitrary SCFGs with ϵ -rules, the problem is more involved, and there do not exist good complexity bounds in the literature.

4.1. Definitions and Background for SCFGs

An SCFG $G = (V, \Sigma, R, S, p)$ consists of a finite set V of *nonterminals*, a *start* nonterminal $S \in V$, a finite set Σ of *alphabet (terminal)* symbols, and a finite list of *rules*, $R \subset V \times (V \cup \Sigma)^*$, where each rule $r \in R$ is a pair (A, γ) , which we usually denote by $A \rightarrow \gamma$, where $A \in V$ and $\gamma \in (V \cup \Sigma)^*$. Finally $p : R \rightarrow \mathbb{R}^+$ maps each rule $r \in R$ to a positive *probability*, $p(r) > 0$. For computational purposes, we assume as usual that the rule probabilities are rational numbers, given as the ratios of two integers written in binary. We often denote a rule $r = (A \rightarrow \gamma)$ together with its probability by writing $A \xrightarrow{p(r)} \gamma$. Note that we allow $\gamma \in (V \cup \Sigma)^*$ to possibly be the empty string, denoted by ϵ . A rule of the form $A \rightarrow \epsilon$ is called an ϵ -rule. For a rule $r = (A \rightarrow \gamma)$, we let $\text{left}(r) := A$ and $\text{right}(r) := \gamma$. We let $R_A = \{r \in R \mid \text{left}(r) = A\}$. For $A \in V$, let $p(A) = \sum_{r \in R_A} p(r)$. A SCFG must satisfy that $\forall A \in V, p(A) \leq 1$. An SCFG is called *proper* if $\forall A \in V, p(A) = 1$.

For a SCFG, G , strings $\alpha, \beta \in (V \cup \Sigma)^*$, and $\pi = r_1 \cdots r_k \in R^*$, we write $\alpha \xRightarrow{\pi} \beta$ if the leftmost derivation starting from α , and applying the sequence π of rules, derives β . We define the probability $p(\alpha \xRightarrow{\pi} \beta)$ of the derivation to be $p(\alpha \xRightarrow{\pi} \beta) = \prod_{i=1}^k p(r_i)$ if $\alpha \xRightarrow{\pi} \beta$, and let $p(\alpha \xRightarrow{\pi} \beta) = 0$, otherwise. If $A \xRightarrow{\pi} w$ for $A \in V$ and $w \in \Sigma^*$, we say

that π is a *complete* derivation from A and its *yield* is $y(\pi) = w$. There is a natural one-to-one correspondence between the complete (leftmost) derivations of w starting at A and the *parse trees* of w rooted at A , and this correspondence preserves probabilities. Recall that a parse tree is a rooted, ordered finite tree, where every leaf v is labeled with a symbol $l(v) \in \Sigma \cup \{\epsilon\}$, every internal (non-leaf) node v is labeled with a nonterminal $l(v) \in V$ and has an associated rule $r(v) \in R_{l(v)}$ whose right-hand side is the concatenation of the labels of the children of v . The yield of the parse tree is the concatenation of the labels of the leaves. The probability of the parse tree is the product of the probabilities of the rules associated with its internal nodes.

For a nonterminal A and a string w , the *maximum* parse tree probability for w , starting at A , is defined to be $p_{A,w}^{\max} = \max_{\pi \in R^*} p(A \xRightarrow{\pi} w)$. The *total* probability of generating w starting at A is defined by $p_{A,w} = \sum_{\pi \in R^*} p(A \xRightarrow{\pi} w)$. Given an SCFG, $G = (V, \Sigma, R, S, p)$, and given a string $w \in \Sigma^*$, the goal of maximum probability parsing is to compute $p_{S,w}^{\max}$ and also to compute (a representation of) a maximum probability parse tree, that is, $\arg \max_{\pi \in R^*} p(S \xRightarrow{\pi} w)$. In the following, we will also use $p_{G,w}^{\max}$ to denote the maximum probability $p_{S,w}^{\max}$ of a parse tree for w from the start nonterminal S of G .

For general SCFGs, G , that have ϵ -rules, the maximum probability parse tree of a string w (even just the string $w = \epsilon$) may have exponential size in the size of the grammar, and the corresponding maximum probability may need an exponential number of bits when written as the ratio of two integers. The probability can be specified more compactly in PoE notation. For any SCFG G and string w , polynomial size (in $|G|$ and $|w|$) always suffices to represent the maximum parsing probability in PoE notation: the bases of the expression are (a subset of) the given rule probabilities of G and the exponents are the number of occurrences of the rules in the optimal parse tree; the numbers of occurrences are at most exponential and thus can be written in a polynomial number of bits.

The optimal parse tree can be specified more compactly using a DAG representation that identifies isomorphic subtrees. Formally, a *parse DAG* is a rooted, ordered DAG D (i.e., the DAG has a single source, and the children of every node are ordered), where every sink (leaf) node is labeled with a symbol $l(v) \in \Sigma \cup \{\epsilon\}$, every other (non-sink) node v is labeled with a nonterminal $l(v) \in V$ and has an associated rule $r(v) \in R_{l(v)}$ whose right-hand side is the concatenation of the labels of the children of v . For every node v , we can define inductively in a bottom-up order the yield and probability of the subDAG $D[v]$ rooted at v : If v is a leaf, then the yield is $l(v)$ and the probability is 1. If v is an internal node, then the yield of $D[v]$ is the concatenation of the yields of the children of v , and the probability of $D[v]$ is the product of the probability of the rule $r(v)$ and the probabilities of the subDAGs rooted at the children of v . The parse DAG D corresponds to a parse tree T obtained by replicating nodes so that every node other than the root has a unique parent; the yield and probability of the DAG are equal to the yield and probability of the corresponding tree. As we shall see, for every SCFG G and string w in the language $L(G)$ of G (i.e., that has non-zero probability), there is a maximum probability parse DAG for w of size polynomial in $|G|$ and $|w|$.⁷ Our goal is to construct such a maximum probability parse DAG.

⁷The succinctness of the DAG representation is essential only for derivations of ϵ from nonterminals. In particular, for every SCFG G and $w \in L(G)$, there is a maximum probability parse DAG for w , of size polynomial in $|G|$ and $|w|$, which consists of a tree, some of whose leaves are replaced by DAGs with yield ϵ .

We will say that an SCFG, $G = (V, \Sigma, R, S, p)$ is in *Simple Normal Form* (SNF) if every nonterminal $A \in V$ belongs to one of the following three types.

- (1) Type L. Every rule $r \in R_A$, has the form $A \xrightarrow{p(r)} B$, for some $B \in V$.
- (2) Type Q. There is a single rule in R_A : $A \xrightarrow{1} BC$, for some $B, C \in V$.
- (3) Type T. There is a single rule in R_A : either $A \xrightarrow{1} \epsilon$, or $A \xrightarrow{1} a$ for some $a \in \Sigma$.

An SCFG is said to be in *Chomsky Normal Form* (CNF) if it satisfies the following conditions.

- The grammar does not contain any ϵ -rule except possibly for a rule $S \xrightarrow{p} \epsilon$ associated with the start nonterminal S ; if it does contain such a rule, then S does not appear on the right-hand side of any rule in the grammar.
- Every rule, other than $S \xrightarrow{p} \epsilon$, is either of the form $A \xrightarrow{p} BC$, or of the form $A \xrightarrow{p} a$ where A, B , and C are nonterminals in V and $a \in \Sigma$ is a terminal symbol.

We shall show in the following text that every SCFG can be converted efficiently in P-time, to an equivalent SCFG that is in SNF form, where the equivalence also entails a probability-preserving bijection between parse trees of strings in the two grammars.

Unlike SNF form, conversion of even an ordinary context-free grammar to CNF form does not in general preserve a bijection between parse trees of the original grammar and those of the CNF grammar. This is so even when we ignore the additional issue of needing to preserve the probability of corresponding (e.g., maximum probability) parse trees for a given string, in the setting of SCFGs.

Furthermore, as shown in Etessami et al. [2012], it is not possible in general to convert an arbitrary SCFG to one in CNF form which preserves even just the probabilities of generating every terminal string, without having to introduce irrational rule probabilities even when all rule probabilities of the original SCFG were rational. See Etessami et al. [2012] for a considerably involved P-time algorithm that converts an SCFG to an *approximately* equivalent CNF form SCFG. Here *approximately equivalent* only refers to preservation of the probability of generating strings up to a given length, and not to preservation of a correspondence between parse trees (which is not doable in general), and thus such a conversion is not suitable when our goal is to compute, for example, a maximum probability parse tree for a given string on a given SCFG.

LEMMA 4.1 (LEMMA B.5 OF ETSSAMI ET AL. [2012]). *Any SCFG, $G = (V, \Sigma, S, R, p)$, with rational rule probabilities, can be converted in linear time to a SCFG, $G' = (V', \Sigma, S, R', p')$, in SNF form, such that $V \subseteq V'$, such that G' has the same set of rational values as rule probabilities (possibly with some additional rules having probability 1), and such that for every nonterminal $A \in V$ and string $w \in \Sigma^*$, there is a probability preserving bijection between parse trees of w rooted at A in G and parse trees of w rooted at A in G' . Moreover, given a parse tree for w rooted at A in G we can easily recover the corresponding parse tree in G' , and vice-versa.*

The proof is directly analogous to related proofs in Etessami et al. [2012], and simply involves adding new auxiliary nonterminals and new auxiliary rules, each having probability 1, to suitably “abbreviate” the sequences of symbols, γ , that appear on the right-hand side (RHS) of rules $A \xrightarrow{p} \gamma$, whenever $|\gamma| \geq 3$. We do this repeatedly


```

 $D := \Sigma \cup \{\epsilon\};$ 
Initialize:  $p_{G',\max}^A := 0$ , for every nonterminal  $A$ ;
Define  $p_{G',\max}^a := 1$  for all  $a \in D$ .
while ( $F := \{B \mid B \notin D \wedge \exists r = (B \rightarrow X_1 \dots X_m) \text{ where } X_1, \dots, X_m \in D\} \neq \emptyset$ ) do
  for all  $B \in F$  do
     $q(B) := \max_{\{r=(B \rightarrow X_1 \dots X_k) \mid X_1, \dots, X_k \in D\}} p(r) p_{G',\max}^{X_1} \dots p_{G',\max}^{X_k}$ 
     $m(B) := \arg \max_{\{r=(B \rightarrow X_1 \dots X_k) \mid X_1, \dots, X_k \in D\}} p(r) p_{G',\max}^{X_1} \dots p_{G',\max}^{X_k}$ 
  end for
  Let  $C := \arg \max_{C \in F} q(C)$ ;
   $p_{G',\max}^C := q(C)$ ;
   $D := D \cup \{C\}$ ;
   $t_{G',\max}^C := m(C)$ ;
  (where  $m(C)$  only describes the root rule of tree  $t_{G',\max}^C$ , and  $t_{G',\max}^C$  can thus be
   viewed as being encoded succinctly as a straight-line program, i.e., a DAG.)
end while
For every nonterminal  $A$ : output  $p_{G',\max}^A$ , and if  $p_{G',\max}^A > 0$  then also output  $t_{G',\max}^A$ ;

```

Fig. 2. Knuth's variant of Dijkstra's algorithm, for computing a globally maximum probability parse tree starting from every nonterminal A (see Nederhof and Satta [2008]).

until for all such RHSs, γ , we have $|\gamma| \leq 2$. To obtain the normal form, we may then also need to introduce nonterminals that generate a single terminal symbol with probability 1. The resulting SCFG is guaranteed to be at most polynomially larger (in fact, only linearly larger) if we are careful.

We give an efficient algorithm operating in the unit-cost arithmetic RAM model with only multiplication ($\{*\}$) operations and comparisons permitted, for computing the maximum likelihood parse tree of a given string.

THEOREM 4.2. *Given any SCFG, G , in SNF form, with rational rule probabilities,⁸ given a string $w \in \Sigma^*$, there is an algorithm that computes the maximum parse tree probability $p_{G,w}^{\max}$, and if $p_{G,w}^{\max} > 0$, then it also computes a succinct DAG representation of a maximum probability parse tree, t_w^{\max} , for w .*

The algorithm runs in polynomial time in the unit-cost arithmetic RAM model of computation with only multiplication operations (and comparisons) allowed. And thus, it is P-time Turing reducible to Problem 2: inequality comparison of integers in succinct PoE representation.

PROOF. Given the SCFG, G , we first compute, for every nonterminal A , the maximum probability $p_{A,\epsilon}^{\max}$ of any finite parse tree that starts at nonterminal A and generates the empty string ϵ .

We do this using a variant of Dijkstra's shortest path algorithm, due to Knuth [1977], which works not on finite graphs but on weighted context-free grammars, for generating a parse tree with smallest *sum* total weight (as well as other classes of weight functions). See the survey on probabilistic parsing by Nederhof and Satta [2008] (their Figure 5) where they nicely describe Knuth's algorithm applied to the specific problem of computing, for any given SCFG, the maximum probability of any finite parse tree. We follow Nederhof and Satta's description [Nederhof and Satta 2008].

⁸We can even allow irrational rule probabilities, since for this we assume a unit-cost RAM model of computation.

Given the original SCFG, G , and given a nonterminal A , if we are interested in computing $p_{A,\epsilon}^{\max}$, we first remove from G all rules of the form $B \rightarrow \gamma$, for any nonterminal B , and string γ where γ contains at least one terminal symbol $\sigma \in \Sigma$ in it, because such rules can't possibly help us generate the empty string ϵ .

Let us call the resulting SCFG after these removals G' .⁹

Every finite parse tree of the remaining SCFG, G' , must generate the empty string, because no other terminal symbols are left. Moreover, there is a one-to-one probability preserving correspondence between parse trees of G generating ϵ and parse trees of G' , starting at any nonterminal A in the two SCFGs, respectively.

Therefore, computing $p_{A,\epsilon}^{\max}$ is equivalent to computing the maximum probability of any finite parse tree starting at A in G' . Let us denote this probability by $p_{G',\max}^A$.

Knuth's variant of Dijkstra's algorithm is described in Figure 2 which is taken from Nederhof and Satta [2008] (their Figure 5).¹⁰ It computes $p_{G',\max}^B$ for every nonterminal B of a given SCFG G' , until it has computed $p_{G',\max}^A$, or else discovered that $p_{G',\max}^A = 0$. It does so by iteratively finding a non-terminal B for which $p_{G',\max}^B$ has not yet been computed, and such that, among all such nonterminals, B gives rise to the maximum product probability of a rule $B \rightarrow \gamma$ times the maximum parse tree probabilities $p_{G',\max}^{B'}$ for all nonterminal occurrences B' in γ .

It is not difficult to check that this algorithm works correctly, for the same reason that Dijkstra's algorithm works correctly. It computes $p_{G',\max}^A = p_{A,\epsilon}^{\max}$ and furthermore also computes a DAG representation (straight-line program representation), of a maximum probability parse tree $t_{G,\max,\epsilon}^A$ starting at A , for every nonterminal A of both G' and G . (Note that this algorithm does not require the SCFG G to be in SNF form. We will exploit SNF form only later, in the final dynamic programming step of the algorithm.)

Note, furthermore, that the algorithm requires at most a polynomial number of arithmetic operations, specifically, it requires *multiplications only* (and this fact will be important for us later), as well as comparison operations (for allowing us to take the maximum over a finite set of values).

⁹Some nonterminals A_i in G' may now not have a set of rules R_i associated with them whose probabilities sum to 1, because we have removed some rules. This causes no problem in our computations: we are interested in probabilities of parse trees that don't involve the removed rules, and these remain the same as in G .

¹⁰We note, for clarity, that "Dijkstra's algorithm" is usually viewed as a single-source *shortest path* algorithm on a edge-weighted directed graph, that is, an algorithm that finds a path from a given source s to targets t which minimizes the sum of the nonnegative edge weights along the path. And Knuth's variant can also be viewed as computing the minimum sum total weight of all rules in a finite parse tree starting from a given nonterminal. However, a well-known and straightforward transformation shows that Dijkstra's algorithm (and Knuth's algorithm) can also be used to compute a maximum probability path from a source s to a target t (respectively, a maximum probability parse tree starting at a given nonterminal). Namely, maximizing the product of probabilities labeling edges along a path from s to t is equivalent to minimizing the length of a path from s to t , when every edge having probability $p > 0$ in the original graph is assigned the nonnegative weight $-\log p$ in the transformed graph. And the same transformation also works for Knuth's variant of Dijkstra's algorithm for weighted CFGs, given in Figure 2. For establishing the polynomial running time of these algorithm in the *unit-cost (exact) arithmetic* model of computation, it is convenient to view Knuth's (and Dijkstra's) algorithm in their multiplicative form, because this avoids the need to consider approximations of $-\log p$, for given rational rule probabilities p . However, when we operate in the standard Turing model of computation, as in the proof of Corollary 4.4 for approximating in P-time the maximum probability of a parse tree, we indeed use the log-transformed (minimization) variants of these same algorithms, by first approximating the nonnegative edge weights $-\log p$.

Thus, the algorithm clearly runs in polynomial time in the unit-cost arithmetic RAM model of computation.

However, note that the probabilities $p_{A,\epsilon}^{\max}$ can clearly be extremely small positive numbers in the worst case (as small as $1/2^{2^{|G|}}$), and thus we can not encode them in standard binary notation in polynomial size. However, since only multiplications are being used over a set of input rule probabilities, $p(r)$, we can encode these probabilities succinctly in PoE, by specifying (in binary) the nonnegative integer power of each $p(r)$. We can compute these numbers with the same number of arithmetic operations over PoE notation, as long as we can compare PoE numbers efficiently.

Having computed $p_{A,\epsilon}^{\max}$ for every nonterminal A of G , we next want to use these quantities to compute $p_{A,w}^{\max}$ for an arbitrary string $w \in \Sigma^*$.

In the next step, we will use another application of Dijkstra's algorithm, this time on a finite graph, to compute, for every pair of nonterminals A, B , the maximum probability, $p_{\max,B}^A$, that a derivation of G starting at nonterminal A eventually yields the single nonterminal symbol B as its yield. We do this as follows: construct an edge-labeled directed graph, $H = (V, E)$, with edges labeled by probabilities, with the nonterminals V of G as its nodes, and such that, for each rule $A \xrightarrow{p} B$, we have the corresponding edge $(A, p, B) \in E$. For each rule $A \xrightarrow{p(r)} BC$ such that $p_{C,\epsilon}^{\max} > 0$, we place the edge $(A, p', B) \in E$, where $p' = p(r) * p_{C,\epsilon}^{\max}$. Similarly if $p_{B,\epsilon}^{\max} > 0$, then we put $(A, p', C) \in E$ where $p' = p(r) * p_{B,\epsilon}^{\max}$. For every pair of nodes A, B , if there are multiple edges (A, p, B) and (A, p', B) in E , we only keep one edge with the maximum probability.

We then run Dijkstra's algorithm from every node A to compute the maximum probability path from A to every other node B in H , and we let $p_{\max,B}^A$ denote the product of the probabilities along that path. Note that, in this case again, Dijkstra's algorithm only requires polynomially many *multiplication operations* (no additions) and comparisons, and thus runs in P-time in the unit-cost RAM model of computation, whatever the encoding of the probabilities labeling H is. While running Dijkstra's algorithm we can also retain the maximum probability paths themselves, and combine them with the already computed maximum probability parse trees $t_{\max,\epsilon}^B$ encountered along the path, in order to compute a DAG representation of a maximum probability parse tree $t_{A,B}^{\max}$ in G with root A and with "yield" B . The following claim is not difficult to prove.

CLAIM. *This algorithm correctly computes the maximum probability $p_{\max,B}^A$ of a parse tree in G with root A and yield B , and also computes a succinct DAG representation $t_{A,B}^{\max}$ of such a parse tree.*

We are finally ready to iteratively compute the probabilities $p_{A,w}^{\max}$ for an arbitrary string $w \in \Sigma^+$. Let $w = w_1 \cdots w_n$ be the given string, with $w_i \in \Sigma$. For $i \in \{1, \dots, n\}$, and $j \in \{1, \dots, n - i + 1\}$, let us define $p_{\max,i,j}^A$ to be the maximum probability of any parse tree rooted in A which generates the string $w_i \cdots w_{i+j-1}$. We shall now see how to compute these $p_{\max,i,j}^A$'s via dynamic programming.

Recall that we are assuming that G is in SNF form. For $j = 1$, let $q_{\max,i,1}^A := \max_{r=(A \xrightarrow{p(r)} w_i)} p(r)$. In other words, $q_{\max,i,1}^A$ is simply the maximum probability of any rule associated with A that immediately generates the terminal symbol w_i . By default, if there is no such rule then $q_{\max,i,1}^A := 0$. For $j > 1$, let $q_{\max,i,j}^A$ denote the maximum probability of a parse tree rooted in A which generates the string $w_i \cdots w_{i+j-1}$, and

Initialization:

for all nonterminals $A \in V$ and $i \in \{1, \dots, n\}$ **do**

$q_{\max,i,1}^A := \max_{r=(A \rightarrow w_i)} p(r);$

end for

for all nonterminals $A \in V$, and $i \in \{1, \dots, n\}$ **do**

$p_{\max,i,1}^A := \max_{B \in V} p_{\max,B}^A \cdot q_{\max,i,1}^B;$

end for

Main Loop:

for $j := 2, \dots, n$ **do**

for all nonterminals $A \in V$ and $i \in \{1, \dots, n\}$ **do**

if $(i + j - 1 \leq n)$ **then**

$q_{\max,i,j}^A = \max_{\{m \in \{1, \dots, j-1\} \text{ \& rule } r=(A \rightarrow BC)\}} p(r) \cdot p_{\max,i,m}^B \cdot p_{\max,i+m,j-m}^C$

end if

end for

for all nonterminals $A \in V$ and $i \in \{1, \dots, n\}$ **do**

if $(i + j - 1 \leq n)$ **then**

$p_{\max,i,j}^A = \max_{B \in V} p_{\max,B}^A \cdot q_{\max,i,j}^B$

end if

end for

end for

Fig. 3. Dynamic program for computing maximum probability parse of given string.

furthermore where the rule used at the root of the parse tree is of the form $A \rightarrow BC$, where the yield of both the children B and C are not ϵ .

Figure 3 describes a dynamic programming algorithm for computing both $p_{\max,i,j}^A$'s and $q_{\max,i,j}^A$'s for all i and j , based on mutual recurrence relations. The algorithm assumes that for all nonterminals A and B the values $p_{\max,\epsilon}^A$ and $p_{\max,B}^A$ have already been computed, as described in the previous steps.

It is not difficult to show that the algorithm is correct. Note that $p_{\max,1,n}^A = p_{\max,w}^A$, and thus the algorithm computes the maximum probability of a parse tree for a string w .

Note furthermore that the algorithm runs in polynomially many steps, only requiring unit-cost *multiplication* operations and comparison operations. Furthermore, we can easily augment the algorithm so that, in addition to just computing $p_{\max,w}^A$ it also computes a DAG (a straight-line program) representation of a maximum probability parse tree $t_{\max,w}^A$ for w rooted at A , while still requiring only polynomially many operations in total. This completes the proof.

It is worth mentioning that one could alternatively use Knuth's algorithm in a slightly different way in order to compute the maximum probability $p_{G,w}^{\max}$ of a parse tree for a string w , in polynomial time in the unit-cost model. Namely, we can view the string w , where $|w| = n$ as being described by the obvious "linear" deterministic finite automaton, D_w , with $n + 1$ states, start state s_0 , and final state s_n , such that D_w accepts just the single string w , that is, $L(D_w) = \{w\}$. Then, given the SCFG, G , which we can assume wlog is already in SNF form, and given the DFA, D_w , we can use a standard "product/intersection" construction (see, e.g., Nederhof and Satta [2008]) to form a new *weighted* CFG, G' , which has size polynomial in G and D_w . The nonterminals of G' are given by triples of the form (s, A, s') , where s and s' are states of D_w , and A is a

nonterminal of G . The rules of G' are formed as follows: for every rule $A \xrightarrow{p} BC$ in G , we add the following rules to G' : $(s, A, s') \xrightarrow{p} (s, B, s'')(s'', C, s')$, for every state s'' of D_w . For every rule of the form $A \xrightarrow{p} B$, we add the rule $(s, A, s') \xrightarrow{p} (s, B, s')$. For every rule of the form $A \xrightarrow{p} a$ for some terminal symbol a , we add the rule $(s, A, s') \xrightarrow{p} a$ to G' if and only if there is a transition (s, a, s') in D_w . We also need to be careful with handling ϵ -rules. If $A \xrightarrow{p} \epsilon$ is a rule of G , then we make $(s, A, s) \xrightarrow{p} \epsilon$ a rule of G' for every state s of D_w . This standard product construction has the property that, for every nonterminal A of G , there is a easily computable weight-preserving (i.e., probability-preserving) one-to-one correspondence between the finite parse trees of G rooted at A which generate the string w , and all the finite parse trees of G' rooted at (s_0, A, s_n) . Thus, in order to compute $p_{G,w}^{\max}$, we can alternatively apply Knuth's algorithm directly to G' in order to compute the maximum probability of any finite parse tree rooted at (s_0, A, s_n) . \square

COROLLARY 4.3. *Given any SCFG, G , with rational rule probabilities, and given a string, $w \in \Sigma^*$, where Σ is the terminal alphabet of G :*

- (A) *If either the Lang-Waldschmidt Conjecture, Conjecture 3.2, or Baker's version of the ABC conjecture, Conjecture 3.4, hold,*
- (B) *Or else, if the number of distinct probabilities labeling the rules of G is bounded by a fixed constant, c ,*

then the following all hold.

- (1) *There is a P-time algorithm, in the standard Turing model of computation, for computing the exact probability $p_{G,w}^{\max}$ in succinct product of exponentials notation (PoE), and there is a P-time algorithm for computing, if $p_{G,w}^{\max} > 0$, a maximum probability parse tree t_w^{\max} where t_w^{\max} is represented succinctly as a DAG (straight-line program).*
- (2) *Given, additionally, a rational probability $q \in (0, 1]$, encoded in binary,¹¹ there is a P-time algorithm in the standard Turing model of computation that decides whether $p_{G,w}^{\max} \geq q$.*
- (3) *Likewise, given additionally another string $w' \in \Sigma^*$, there is a P-time algorithm (in the Turing model), that decides whether $p_{G,w}^{\max} \geq p_{G,w'}^{\max}$.*

PROOF. The claims follow easily from the proof of Theorem 4.2. Specifically, recall that the unit-cost RAM algorithms in the proof of Theorem 4.2 only involve multiplication of rational numbers starting with base numbers that are rule probabilities of the given SCFG G , as well as taking the maximum over such numbers (which we can carry out by comparisons). We can therefore maintain all the computed numbers in PoE format, and based on the postulated conditions it follows from Proposition 3.7 that we can carry out all the necessary comparisons in P-time, yielding a P-time algorithm overall which computes the relevant probabilities in PoE notation, and which can compare two such probabilities. \square

Furthermore, without any conjectures, essentially the same algorithm can be used to approximate the maximum parsing probability of a string.

¹¹If we are assuming (A), then q can even be given in PoE. If we are instead assuming (B), then q can also be given in PoE by a^b , but with $a = \langle a_1, \dots, a_k \rangle$, where $k \leq c'$, for some fixed constant c' .

COROLLARY 4.4. *Given any SCFG, G , with rational rule probabilities, given a string, $w \in \Sigma^*$, where Σ is the terminal alphabet of G , and given rational $\epsilon > 0$, there is an algorithm (in the standard Turing model) that runs in time polynomial in $|G|$, $|w|$ and $\log(1/\epsilon)$, which determines whether $w \in L(G)$ and if so, computes a value v such that $|\log_2(p_{G,w}^{\max}) - v| \leq \epsilon$ and the DAG representation of a parse tree of w that has probability $\geq (1 - \epsilon)p_{G,w}^{\max}$.*

PROOF. We will use essentially the same algorithm as in the proof of Theorem 4.2, but we will instead use the log-transformed (shortest path) variants of Dijkstra's and Knuth's algorithms (see footnote 10), by first approximating the weights $-\log p$ corresponding to rule probabilities p , to sufficient precision. We will show that approximating the weights $-\log p$ to within additive error 2^{-k} , where k is polynomial in $|G|$, $|w|$ and $\log(1/\epsilon)$, will suffice to allow the algorithm to approximate $p_{G,w}^{\max}$ to within the desired additive error $\epsilon > 0$.

Assume, wlog, that we first put the SCFG in SNF form. Let n be the number of nonterminals of the SNF grammar. Let us first estimate the size of the PoE expressions for the probabilities that are computed by the algorithm of Theorem 4.2. It is easy to show that the maximum probability $p_{A,\epsilon}^{\max}$ of derivation of ϵ from a nonterminal A is given by a PoE expression whose bases are rule probabilities and where the sum of the exponents is less than 2^n . This can be shown by an easy induction on the iterations of Knuth's algorithm in Figure 2, where the inductive claim is that the sum of the exponents for a nonterminal that is added to D in the i th iteration is at most $2^i - 1$.

Then, we construct a directed graph H and use Dijkstra's algorithm to compute probabilities $p_{A,B}^{\max}$. The edges of H have probabilities of the form $p(r) \cdot p_{C,\epsilon}^{\max}$, and the optimal path between any two nodes is simple, thus it has length at most $n - 1$. Therefore, each probability $p_{A,B}^{\max}$ in PoE notation has sum of exponents at most $(n - 1) \cdot 2^n$.

If we consider then the algorithm of Figure 3, it is easy to show by induction on j that a probability $p_{\max,i,j}^A$ in PoE notation has sum of exponents at most $(2j - 1)((n - 1)2^n + 1)$. Thus, the PoE expression for the final probabilities, as well as all the probabilities during the computation, have sum of exponents less than $2n^2 2^n$. Or in other words, the logarithms of the computed probabilities are (positive) linear combinations of the logarithms of the rule probabilities where the sum of the coefficients is less than $2n^2 2^n$.

Our algorithm for the approximate computation of the maximum parsing probability starts by computing approximately the logarithms of the rule probabilities to a precision of $k = \lceil 2n + \log(1/\epsilon) \rceil$ bits, that is, within additive error $2^{-k} < \epsilon/2^{2n} < \epsilon/(4n^2 2^n)$. Then, we apply the Algorithm of Theorem 4.2 using the log-transformed (additive) versions of Knuth's and Dijkstra's algorithms, and doing all the computations (exactly) in logarithms, by using the *approximated* values for the logarithms, $-\log p$, of the rule probabilities p . Note that every computed quantity is then a linear combination of the (approximated) logarithms of rule probabilities.

We now observe that the cumulative additive error that can be introduced into the final result, because of the initial approximation to the logarithms of the rule probabilities, is at most $4n^2 2^n \cdot 2^{-k} < \epsilon$. The reason why this holds is the following:

Consider a solution S , that is, a succinctly represented parse tree (represented as a DAG). Let $v(S)$ denote the logarithm of the value of this solution. In other words, $v(S)$ denotes the log of the PoE expression giving the product of all rule probabilities used in S . Thus, $v(S)$ can be written as $\sum_r n_r \log p(r)$, where the sum is over all rules r . Recall that $p(r)$ denotes the probability of rule r .

Assume that for all the logarithms of rule probabilities, $\log p(r)$, we have computed an approximation, $a(r)$, such that $|(\log p(r)) - a(r)| < 2^{-k}$. Let $v'(S)$ denote the approximate log value of the solution S , that is, $v'(S) = \sum_r n_r \cdot a(r)$.

Let S^* denote the solution (parse tree) that is computed by the algorithm that uses the approximated values $\log p(r)$. Let S^{opt} denote the optimal solution (which would be computed if we instead had used exact arithmetic and comparisons on PoE numbers).

First, note that $v'(S^*) \geq v'(S^{opt})$, because the approximation algorithm is guaranteed to output the optimal (maximum value) solution S^* with respect to the approximated logarithms $a(p(r))$ of the rule probabilities $p(r)$.

Next, note that both $v(S^*)$ and $v(S^{opt})$ are positive linear combinations of the actual logs of rule probabilities, with their coefficients summing to at most $m = 2n^2 2^n$. So $v'(S^*)$ differs from $v(S^*)$ by at most $2^{-k}m$, and likewise $v'(S^{opt})$ differs from $v(S^{opt})$ by at most $2^{-k}m$. Therefore, since we already argued that $v'(S^*) \geq v'(S^{opt})$, it must be the case that $v(S^*) \geq v(S^{opt}) - (2 \times 2^{-k}m)$. Note that we have chosen k such that $2 \times 2^{-k}m = 2^{-k}4n^2 2^n < \epsilon$. This completes the proof.

The algorithm computes at the same time the DAG representation of a parse tree T , whose probability satisfies $\log_2(p(T)) \geq \log_2 p_{G,w}^{\max} - \epsilon$. Thus, $p(T) \geq p_{G,w}^{\max}/2^\epsilon \geq (1 - \epsilon)p_{G,w}^{\max}$. \square

Appendix A

A.1. Proof of Proposition 1.1

PROPOSITION 1.1. *There is a simple P-time translation from a given number represented in PoE to the same number represented as an arithmetic circuit over $\{*, /\}$ with integer inputs (represented in binary). Likewise, there is a simple P-time translation in the other direction.*

PROOF. Given a number in PoE, observe first that, for integers a_i and b_i , we can use Horner's rule to represent $a_i^{b_i}$ by an arithmetic circuit which takes a_i as an input, and performs repeated squaring and multiplication by a_i to obtain a circuit evaluating to $a_i^{b_i}$ whose depth and number of gates is bounded by $\log_2(b_i)$. We can then obviously compute a linear-size circuit yielding the product $a^b = \prod_i a_i^{b_i}$.

In the other direction, given an arithmetic circuit C over $\{*, /\}$, with positive integer inputs a_1, \dots, a_n , we show by induction on the depth of the circuit that the numbers computed by a gate at depth d can be translated to a PoE a^b , where the base numbers are the a_i 's and where the exponents b_i have absolute value at most 2^d , and can thus be computed in linear time, given C as input. The claim is obvious in the base case, for input gates of the circuit C , which are the a_i 's. Inductively, assume that for some gate $g_i = g_j \odot g_k$ we already have PoE representations for g_j and g_k , given by $a^{b(j)}$ and $a^{b(k)}$ respectively, where $\odot \in \{*, /\}$. Assume that $d = \max\{\text{depth}(g_j), \text{depth}(g_k)\}$. By induction, we can assume each component of the lists (vectors) $b(j)$ and $b(k)$ is at most 2^d .

Now if $\odot \equiv *$, then clearly the value computed by gate g_i can be represented by $a^{b(i)}$, where $b(i) = b(j) + b(k)$ denotes component-wise addition of the two vectors of integers $b(j)$ and $b(k)$. Likewise, if $\odot \equiv /$, then clearly g_i can be represented by $a^{b(i)}$ where $b(i) = b(j) - b(k)$. In both cases, for every component $m \in \{1, \dots, n\}$, we have $|b(i)_m| \leq 2^{d+1}$, since we at most double the absolute value by adding or subtracting two numbers with absolute value $\leq 2^d$. Since g_i has depth $d + 1$, we are done. \square

A. 2. Proof of Proposition 3.5

Recall we use $\log(x)$ to denote the *natural* logarithm of x , and use $\log_2(x)$ to denote the log base 2.

PROPOSITION 3.5. *There is an algorithm that, given a positive integer a , encoded in binary, and given a positive integer j , encoded in unary, computes a rational value v_a , such that*

$$|\log(a) - v_a| < 2^{-j}$$

The algorithm runs in time polynomial in j and $\log_2(a)$ (in the Turing model).

PROOF. Recall the standard power series for the natural logarithm of $x + 1$, which holds for any x in the range $-1 < x < 1$:

$$\log(x + 1) = x - x^2/2 + x^3/3 - x^4/4 + \dots = \sum_{i=1}^{\infty} (-1)^{i+1} \frac{x^i}{i} \quad (6)$$

Consider any positive integer a . We can assume $a > 1$, without loss of generality, because otherwise $\log(1) = 0$. By examining the binary encoding of a , we can easily determine a positive integer $m > 0$, such that $2^m \leq a < 2^{m+1}$. Note that

$$\log(a) = \log(a/2^{m+1}) + \log(2) * (m + 1)$$

Thus, to compute $\log(a)$ “to within sufficient accuracy”, it suffices to compute both $\log(a/2^{m+1})$ and $\log(2)$, “to within sufficient accuracy”. But note that since $a \geq 2^m$, we have that $1/2 \leq a/2^{m+1} < 1$. Letting $y := (a/2^{m+1} - 1)$, since $-1/2 \leq y < 0$, we have $y + 1 = a/2^{m+1}$ is in the convergent region of the series (6), so that:

$$\log(a/2^{m+1}) = \sum_{i=1}^{\infty} (-1)^{i+1} \frac{y^i}{i}$$

Now, note that since $-1/2 < y < 0$, we have $|\sum_{i=k+1}^{\infty} (-1)^{i+1} \frac{y^i}{i}| < \sum_{i=k+1}^{\infty} (1/2)^i \leq (1/2^k)$. Thus, to compute an approximant v' for $\log(a/2^{m+1})$ such that $|\log(a/2^{m+1}) - v'| < (1/2^k)$, all we have to do is to compute the first $k + 1$ terms of the series $\sum_{i=1}^{\infty} (-1)^{i+1} \frac{y^i}{i}$. This we can easily do in time polynomial in k and in the encoding size of a , by just carrying out the arithmetic. (The encoding size of the numbers calculated this way will not get more than polynomially large in the encoding size of a and k : roughly each term has encoding size at most $k * \text{size}(a)$, so the encoding size of the sum is at most $\log_2(k) * k * \text{size}(a)$.)

Next, we need to compute an approximation of $\log(2)$. To do this, we use a well-known alternative series derivable from (6): we have $\log(2) = -\log(1/2) = -\log(1 + -(1/2)) = \sum_{i=1}^{\infty} \frac{1}{i2^i}$. Again, we have $\sum_{i=k+1}^{\infty} \frac{1}{i2^i} \leq 1/2^k$. Thus, we can compute an approximant v'' of $\log(2)$, such that $|v'' - \log(2)| < 2^{-j}$, by just computing the first $j + 1$ terms of the series $\sum_{i=1}^{\infty} \frac{1}{i2^i}$.

We would like to combine a suitable approximation v' of $\log(a/2^{m+1})$ and a suitable approximation v'' of $\log(2)$ to get an approximation of $\log(a) = \log(a/2^{m+1}) + \log(2)(m + 1)$, to within a desired additive error 2^{-j} in time polynomial in the encoding size of a and in j .

We only need to observe that if $|\log(a/2^{m+1}) - v'| \leq 2^{-(j+1)}$ and $|\log(2) - v''| < 2^{-(j+1)}/(m+1)$, and if we let $v_a := (v' - v''(m+1))$, then

$$\begin{aligned} |\log(a) - v_a| &= |(\log(a/2^{m+1}) + \log(2)(m+1)) - (v' + v''(m+1))| \\ &= |(\log(a/2^{m+1}) - v') + (m+1)(\log(2) - v'')| \\ &\leq |(\log(a/2^{m+1}) - v')| + (m+1)|\log(2) - v''| \\ &\leq 2^{-(j+1)} + 2^{-(j+1)} = 2^{-j} \end{aligned}$$

Thus, given positive integer a in binary, we can compute a 2^{-j} -approximation, v_a , of $\log(a)$ in time polynomial in the encoding size of a and in j , in the Turing model of computation. \square

ACKNOWLEDGMENTS

Thanks to Howard Karloff and Igor Shparlinski for comments on an earlier draft. In particular, thanks to Igor for pointing out references Bach et al. [1993] and Bernstein [2005] on efficient factor refinement. We also thank an anonymous referee for pointing out Theorem 6 in Shub's paper [Shub 1993] to us.

REFERENCES

- E. Allender, P. Bürgisser, J. Kjeldgaard-Pedersen, and P. B. Miltersen. 2009. On the complexity of numerical analysis. *SIAM J. Comput.* 38, 5, 1987–2006.
- E. Bach, J. R. Driscoll, and J. Shallit. 1993. Factor refinement. *J. Algor.* 15, 2, 199–222.
- A. Baker. 1998. Logarithmic forms and the *abc*-conjecture. In *Number Theory (Eger, 1996)*, de Gruyter, Berlin, 37–44.
- A. Baker. 2007. On an arithmetical function associated with the *abc*-conjecture. In *Diophantine Geometry*, CRM Series, Vol. 4, Ed. Norm., Pisa, 25–33.
- A. Baker and G. Wüstholz. 1993. Logarithmic forms and group varieties. *J. Reine Angew. Math.* 442, 19–62.
- A. Baker and G. Wüstholz. 2000. Number theory, transcendence and Diophantine geometry in the next millennium. In *Mathematics: Frontiers and Perspectives*, American Mathematical Society, Providence, RI, 1–12.
- A. Baker and G. Wüstholz. 2007. *Logarithmic Forms and Diophantine Geometry*. Cambridge University Press.
- D. J. Bernstein. 2005. Factoring into coprimes in essentially linear time. *J. Algor.* 54, 1, 1–30.
- R. Durbin, S. R. Eddy, A. Krogh, and G. Mitchison. 1999. *Biological Sequence Analysis: Probabilistic Models of Proteins and Nucleic Acids*. Cambridge University Press.
- K. Etessami, A. Stewart, and M. Yannakakis. 2012. Polynomial-time algorithms for multi-type branching processes and stochastic context-free grammars. In *Proceedings of the 44th ACM Symposium on Theory of Computing (STOC)*. (Full version on ArXiv:1201.2374).
- M. R. Garey, R. L. Graham, and D. S. Johnson. 1976. Some NP-complete geometric problems. In *Proceedings of the 8th ACM Symposium on Theory of Computing (STOC)*. 10–22.
- A. Granville and T. J. Tucker. 2002. It's as easy as abc. *Notices AMS* 49, 10, 1224–1231.
- V. Kabanets and R. Impagliazzo. 2003. Derandomizing polynomial identity tests means proving circuit lower bounds. In *Proceedings of the 35th ACM Symposium on Theory of Computing (STOC)*. 355–364.
- D. Knuth. 1977. A generalization of Dijkstra's Algorithm. *Inform. Process. Lett.* 6, 1–5.
- S. Lang. 1978. *Elliptic Curves: Diophantine Analysis*. Springer.
- C. Manning and H. Schütze. 1999. *Foundations of Statistical Natural Language Processing*. MIT Press.
- D. Masser. 1985. Open problems. In *Proceedings of the Symposium on Analytic Number Theory*, London Mathematics Society Lecture Notes, Ser. 96, W. W. L. Chen Ed., Cambridge University Press.
- E. M. Matveev. 1998. An explicit lower bound for a homogeneous rational linear form in logarithms of algebraic numbers. I. *Izv. Ross. Akad. Nauk Ser. Mat.* 62, 4, 81–136. (Russian original. English translation in *Izvestiya Math.* 62, 2, (1998), 723–772.)
- E. M. Matveev. 2000. An explicit lower bound for a homogeneous rational linear form in logarithms of algebraic numbers. II. *Izv. Ross. Akad. Nauk Ser. Mat.* 64, 6, 125–180. (Russian original. English translation in *Izv. Math.* 64, 6, (2000), 1217–1269.)
- M.-J. Nederhof and G. Satta. 2008. Probabilistic parsing. *New Devel. Form. Lang. Appl.* 113, 229–258.

- Y. Nesterenko. 2003. Linear forms in logarithms of rational numbers. In *Diophantine Approximation (Cetraro, 2000)*, Lecture Notes in Mathematics, vol. 1819, Springer, Berlin, 53–106.
- J. Oesterlè. 1988. Nouvelles approches du “Theoreme” de Fermat. *Asterisque* 161-2 (1988), 165–186.
- A. Schinzel. 2000. *Polynomials with Special Regard to Reducibility*. Cambridge University Press.
- M. Shub. 1993. Some remarks on Bezout’s theorem and complexity theory. In *From Topology to Computation: Proceedings of the Smalefest*, M. Hirsch, J. Marsden, and M. Shub Eds., Springer-Verlag, 443–455.
- M. Waldschmidt. 1993. Minorations de combinaisons linéaires de logarithmes de nombres algébriques. *Canad. J. Math.* 45, 1, 176–224.
- M. Waldschmidt. 2004. Open Diophantine problems. *Mosc. Math. J.* 4, 1, 245–305, 312.

Received May 2013; revised December 2013; accepted March 2014