

Revealing vs. Concealing: More Simulation Games for Büchi Inclusion

Milka Hutagalung, Martin Lange, Etienne Lozes

Universität Kassel

LATA 2013 - Bilbao, Spain

April 4, 2013

Table of contents

Büchi inclusion

- Büchi automata
- inclusion problem
- fair simulation game

Multi-pebble games

Multi-letter games

- static k -letter
- dynamic k -letter


Experiments

Büchi automata

- ▶ extends a finite automata to accept infinite sequences of letters
- ▶ represents a language over infinite words

Example

(Nondeterministic) Büchi automata \mathcal{A} over $\Sigma = \{a, b, c\}$



$abaaa... \in L(\mathcal{A})$


$aaaaa... \notin L(\mathcal{A})$

The language $L(\mathcal{A}) = a \cdot (b \cup c) \cdot (a \cup b \cup c)^\omega$.

Büchi inclusion problem

- ▶ Given : two Büchi automata \mathcal{A} , \mathcal{B}
Question : Is $L(\mathcal{A}) \subseteq L(\mathcal{B})$?

Example




- ▶ PSPACE-complete

Büchi inclusion problem

- ▶ Given : two Büchi automata \mathcal{A} , \mathcal{B}
Question : Is $L(\mathcal{A}) \subseteq L(\mathcal{B})$?

Example




- ▶ PSPACE-complete
- ▶ fair simulation game approach:
 - ▶ “Refuter” plays against “Verifier”
 - ▶ each control a pebble on \mathcal{A} and \mathcal{B}
 - ▶ Verifier tries to show language inclusion

Büchi inclusion problem

- ▶ Given : two Büchi automata \mathcal{A} , \mathcal{B}
Question : Is $L(\mathcal{A}) \subseteq L(\mathcal{B})$?

Example




- ▶ PSPACE-complete
- ▶ fair simulation game approach:
 - ▶ “Refuter” plays against “Verifier”
 - ▶ each control a pebble on \mathcal{A} and \mathcal{B}
 - ▶ Verifier tries to show language inclusion

Büchi inclusion problem

- ▶ Given : two Büchi automata \mathcal{A} , \mathcal{B}
Question : Is $L(\mathcal{A}) \subseteq L(\mathcal{B})$?

Example




- ▶ PSPACE-complete
- ▶ fair simulation game approach:
 - ▶ “Refuter” plays against “Verifier”
 - ▶ each control a pebble on \mathcal{A} and \mathcal{B}
 - ▶ Verifier tries to show language inclusion

Büchi inclusion problem

- ▶ Given : two Büchi automata \mathcal{A} , \mathcal{B}
Question : Is $L(\mathcal{A}) \subseteq L(\mathcal{B})$?

Example




- ▶ PSPACE-complete
- ▶ fair simulation game approach:
 - ▶ “Refuter” plays against “Verifier”
 - ▶ each control a pebble on \mathcal{A} and \mathcal{B}
 - ▶ Verifier tries to show language inclusion

Büchi inclusion problem

- ▶ Given : two Büchi automata \mathcal{A} , \mathcal{B}
Question : Is $L(\mathcal{A}) \subseteq L(\mathcal{B})$?

Example




- ▶ PSPACE-complete
- ▶ fair simulation game approach:
 - ▶ “Refuter” plays against “Verifier”
 - ▶ each control a pebble on \mathcal{A} and \mathcal{B}
 - ▶ Verifier tries to show language inclusion

Büchi inclusion problem

- ▶ Given : two Büchi automata \mathcal{A} , \mathcal{B}
Question : Is $L(\mathcal{A}) \subseteq L(\mathcal{B})$?

Example




- ▶ PSPACE-complete
- ▶ fair simulation game approach:
 - ▶ “Refuter” plays against “Verifier”
 - ▶ each control a pebble on \mathcal{A} and \mathcal{B}
 - ▶ Verifier tries to show language inclusion

Fair simulation game

- ▶ can be encoded to parity game with priorities: 0, 1, 2



Example




Fair simulation game

- ▶ can be encoded to parity game with priorities: 0, 1, 2

Example





\Rightarrow




Fair simulation game

- can be encoded to parity game with priorities: 0, 1, 2

Example





\Rightarrow




Fair simulation game

- ▶ can be encoded to parity game with priorities: 0, 1, 2
- ▶ Verifier wins \Leftrightarrow Player 0 wins $\Rightarrow L(\mathcal{A}) \subseteq L(\mathcal{B})$
- ▶ parity game size $< |\mathcal{A}| \cdot |\mathcal{B}| \cdot |\Sigma|$

Example




\Rightarrow



Fair simulation game

- ▶ can be encoded to parity game with priorities: 0, 1, 2
- ▶ Verifier wins \Leftrightarrow Player 0 wins $\Rightarrow L(\mathcal{A}) \subseteq L(\mathcal{B})$
- ▶ parity game size $< |\mathcal{A}| \cdot |\mathcal{B}| \cdot |\Sigma|$


Example



Fair simulation game

- ▶ can be encoded to parity game with priorities: 0, 1, 2
- ▶ Verifier wins \Leftrightarrow Player 0 wins $\Rightarrow L(\mathcal{A}) \subseteq L(\mathcal{B})$
- ▶ parity game size $< |\mathcal{A}| \cdot |\mathcal{B}| \cdot |\Sigma|$


Example



Fair simulation game

- ▶ can be encoded to parity game with priorities: 0, 1, 2
- ▶ Verifier wins \Leftrightarrow Player 0 wins $\Rightarrow L(\mathcal{A}) \subseteq L(\mathcal{B})$
- ▶ parity game size $< |\mathcal{A}| \cdot |\mathcal{B}| \cdot |\Sigma|$


Example



Fair simulation game

- ▶ can be encoded to parity game with priorities: 0, 1, 2
- ▶ Verifier wins \Leftrightarrow Player 0 wins $\Rightarrow L(\mathcal{A}) \subseteq L(\mathcal{B})$
- ▶ parity game size $< |\mathcal{A}| \cdot |\mathcal{B}| \cdot |\Sigma|$

Example




$L(\mathcal{A}) \subseteq L(\mathcal{B})$ but Verifier loss

Fair simulation game

- ▶ can be encoded to parity game with priorities: 0, 1, 2
- ▶ Verifier wins \Leftrightarrow Player 0 wins $\Rightarrow L(\mathcal{A}) \subseteq L(\mathcal{B})$
- ▶ parity game size $< |\mathcal{A}| \cdot |\mathcal{B}| \cdot |\Sigma|$


Example




$L(\mathcal{A}) \subseteq L(\mathcal{B})$ but Verifier loss

k -pebble game [Etessami02]

\mathcal{A} (Refuter)




\mathcal{B} (Verifier)




k -pebble game [Etesami02]

- ▶ Verifier controls k pebbles
- ▶ Verifier wins: Refuter forms an accepting run \Rightarrow all infinite runs of Verifier are accepting

\mathcal{A} (Refuter)




\mathcal{B} (Verifier)




k -pebble game [Etesami02]

- ▶ Verifier controls k pebbles
- ▶ Verifier wins: Refuter forms an accepting run \Rightarrow all infinite runs of Verifier are accepting

\mathcal{A} (Refuter)




\mathcal{B} (Verifier)




k -pebble game [Etesami02]

- ▶ Verifier controls k pebbles
- ▶ Verifier wins: Refuter forms an accepting run \Rightarrow all infinite runs of Verifier are accepting

\mathcal{A} (Refuter)




\mathcal{B} (Verifier)




k -pebble game [Etesami02]

- ▶ Verifier controls k pebbles
- ▶ Verifier wins: Refuter forms an accepting run \Rightarrow all infinite runs of Verifier are accepting

\mathcal{A} (Refuter)




\mathcal{B} (Verifier)




k -pebble game [Etesami02]

- ▶ Verifier controls k pebbles
- ▶ Verifier wins: Refuter forms an accepting run \Rightarrow all infinite runs of Verifier are accepting

\mathcal{A} (Refuter)




\mathcal{B} (Verifier)




k -pebble game [Etesami02]

- ▶ Verifier controls k pebbles
- ▶ Verifier wins: Refuter forms an accepting run \Rightarrow all infinite runs of Verifier are accepting

\mathcal{A} (Refuter)



\mathcal{B} (Verifier)




- ▶ forms a hierarchy:

$$\sqsubseteq_{\text{peb}}^1 \subset \sqsubseteq_{\text{peb}}^2 \subset \sqsubseteq_{\text{peb}}^3 \subset \dots \subset \bigcup_{k \geq 1} \sqsubseteq_{\text{peb}}^k \subset \sqsubseteq_{\text{incl}}$$


k -pebble game [Etesami02]

- ▶ Verifier controls k pebbles
- ▶ Verifier wins: Refuter forms an accepting run \Rightarrow all infinite runs of Verifier are accepting

\mathcal{A} (Refuter)



\mathcal{B} (Verifier)



- ▶ forms a hierarchy:

$$\sqsubseteq_{\text{peb}}^1 \subset \sqsubseteq_{\text{peb}}^2 \subset \sqsubseteq_{\text{peb}}^3 \subset \dots \subset \bigcup_{k \geq 1} \sqsubseteq_{\text{peb}}^k \subset \sqsubseteq_{\text{incl}}$$

- ▶ parity game size $< |\mathcal{A}| \cdot (2 \cdot |\mathcal{B}| + 1)^k \cdot (|\Sigma| + 1)$


Static k -letter game

Static k -letter game


- ▶ both players control one pebble
- ▶ move k steps in each round

Example

\mathcal{A} (Refuter)



\mathcal{B} (Verifier)




Static k -letter game


- ▶ both players control one pebble
- ▶ move k steps in each round

Example

\mathcal{A} (Refuter)



\mathcal{B} (Verifier)




- ▶ parity game size $< |\mathcal{A}| \cdot |\mathcal{B}| \cdot (|\Sigma|^k + 1)$

Static k -letter game


- ▶ both players control one pebble
- ▶ move k steps in each round

Example

\mathcal{A} (Refuter)




\mathcal{B} (Verifier)




- ▶ parity game size $< |\mathcal{A}| \cdot |\mathcal{B}| \cdot (|\Sigma|^k + 1)$
- ▶ do not form a linear hierarchy

Example: static k -letter

\mathcal{A} (Refuter)




\mathcal{B} (Verifier)




Example: static k -letter

\mathcal{A} (Refuter)




\mathcal{B} (Verifier)




Example: static k -letter

\mathcal{A} (Refuter)




\mathcal{B} (Verifier)




Example: static k -letter

\mathcal{A} (Refuter)




\mathcal{B} (Verifier)




Example: static k -letter

\mathcal{A} (Refuter)




\mathcal{B} (Verifier)




Example: static k -letter

\mathcal{A} (Refuter)




\mathcal{B} (Verifier)




Example: static k -letter

\mathcal{A} (Refuter)




\mathcal{B} (Verifier)




Example: static k -letter

\mathcal{A} (Refuter)




\mathcal{B} (Verifier)




► $\mathcal{A} \sqsubseteq_{\text{stat}}^2 \mathcal{B}$ but $\mathcal{A} \not\sqsubseteq_{\text{stat}}^3 \mathcal{B}$

Example: static k -letter

\mathcal{A} (Refuter)



\mathcal{B} (Verifier)




► $\mathcal{A} \sqsubseteq_{\text{stat}}^2 \mathcal{B}$ but $\mathcal{A} \not\sqsubseteq_{\text{stat}}^3 \mathcal{B}$

► hierarchy:


$$\sqsubseteq_{\text{stat}}^{\text{gcd}(k,\ell)} \subseteq \sqsubseteq_{\text{stat}}^k, \quad \sqsubseteq_{\text{stat}}^\ell \subseteq \sqsubseteq_{\text{stat}}^{\text{lcm}(k,\ell)}$$

Example: static k -letter

\mathcal{A} (Refuter)



\mathcal{B} (Verifier)



► $\mathcal{A} \sqsubseteq_{\text{stat}}^2 \mathcal{B}$ but $\mathcal{A} \not\sqsubseteq_{\text{stat}}^3 \mathcal{B}$

► hierarchy:

$$\sqsubseteq_{\text{stat}}^{\text{gcd}(k,\ell)} \subseteq \sqsubseteq_{\text{stat}}^k, \quad \sqsubseteq_{\text{stat}}^\ell \subseteq \sqsubseteq_{\text{stat}}^{\text{lcm}(k,\ell)}$$


► hard to determine a search is hopeless already

► can we refine the game?

Dynamic k -letter game

- ▶ verifier may choose how far both players move.
- ▶ both players move h_i steps in round i , $h_i < k$.


Example ($\mathcal{A} \sqsubseteq_{\text{dyn}}^3 \mathcal{B}$)



Dynamic k -letter game

- ▶ verifier may choose how far both players move.
- ▶ both players move h_i steps in round i , $h_i < k$.


Example ($\mathcal{A} \sqsubseteq_{\text{dyn}}^3 \mathcal{B}$)



Dynamic k -letter game

- ▶ verifier may choose how far both players move.
- ▶ both players move h_i steps in round i , $h_i < k$.


Example ($\mathcal{A} \sqsubseteq_{\text{dyn}}^3 \mathcal{B}$)



Dynamic k -letter game

- ▶ verifier may choose how far both players move.
- ▶ both players move h_i steps in round i , $h_i < k$.


Example ($\mathcal{A} \sqsubseteq_{\text{dyn}}^3 \mathcal{B}$)



Dynamic k -letter game

- ▶ verifier may choose how far both players move.
- ▶ both players move h_i steps in round i , $h_i < k$.


Example ($\mathcal{A} \sqsubseteq_{\text{dyn}}^3 \mathcal{B}$)



Dynamic k -letter game

- ▶ verifier may choose how far both players move.
- ▶ both players move h_i steps in round i , $h_i < k$.

Example ($\mathcal{A} \sqsubseteq_{\text{dyn}}^3 \mathcal{B}$)



- ▶ form a hierarchy:


$$\sqsubseteq_{\text{dyn}}^1 \subset \sqsubseteq_{\text{dyn}}^2 \subset \sqsubseteq_{\text{dyn}}^3 \subset \dots \subset \bigcup_{k \geq 1} \sqsubseteq_{\text{dyn}}^k \subset \sqsubseteq_{\text{incl}}$$

- ▶ parity game size $< |\mathcal{A}| \cdot |\mathcal{B}| \cdot (|\Sigma|^{k+1} + k)$

Dynamic k -letter game

- ▶ more powerful than static game
- ▶ less powerful than pebble game

Example



- ▶ upper bound:

$$\mathcal{A} \sqsubseteq_{\text{dyn}}^k \mathcal{B} \Rightarrow \mathcal{A} \sqsubseteq_{\text{dyn}}^{k_0} \mathcal{B}, \quad k_0 := 2(|\mathcal{A}| + |\mathcal{B}|)^3$$

Experiments

Experiments

mutual exclusion protocols							
	multi-letter				multi-pebble		Rabit
	k	dynamic	k	static	k	pebble	
Mcs	1	22.94s	1	23.48s	1	25.41s	39.00s
FischerV2	1	0.07s	1	0.07s	1	0.07s	0.09s
Peterson	1	0.01s	1	0.01s	1	0.01s	0.03s
Bakery	1	7.22s	1	7.16s	1	7.23s	4.43s
Phils	1	0.02s	1	0.02s	1	0.02s	0.11s
Fischer	1	40.80s	1	47.30s	1	47.37s	3.41s
FischerV3	-	>1h	-	>1h	-	>1h	7.63s
FischerV4	-	>1h	-	>1h	-	>1h	2136.70s
BakeryV2	2	36.01s	2	7.06s	-	>1h	>1h

random NBA								
	size = 30, $d_{acc} = 0.1$, $d_{tr} = 2$				size = 50, $d_{acc} = 0.6$, $d_{tr} = 3$			
	dynamic	static	pebble	Rabit	dynamic	static	pebble	Rabit
time	59.12s	52.78s	18.22s	1655.84s	0.55s	0.52s	2.09s	127.53s
success %	80%	82%	86%	58%	100%	100%	100%	100%
average k	3.66	4.33	1.93	-	1.01	1.01	1.01	-







Experiments

mutual exclusion protocols							
	multi-letter				multi-pebble		Rabit
	k	dynamic	k	static	k	pebble	
Mcs	1	22.94s	1	23.48s	1	25.41s	39.00s
FischerV2	1	0.07s	1	0.07s	1	0.07s	0.09s
Peterson	1	0.01s	1	0.01s	1	0.01s	0.03s
Bakery	1	7.22s	1	7.16s	1	7.23s	4.43s
Phils	1	0.02s	1	0.02s	1	0.02s	0.11s
Fischer	1	40.80s	1	47.30s	1	47.37s	3.41s
FischerV3	-	>1h	-	>1h	-	>1h	7.63s
FischerV4	-	>1h	-	>1h	-	>1h	2136.70s
BakeryV2	2	36.01s	2	7.06s	-	>1h	>1h

random NBA								
	size = 30, $d_{acc} = 0.1$, $d_{tr} = 2$				size = 50, $d_{acc} = 0.6$, $d_{tr} = 3$			
	dynamic	static	pebble	Rabit	dynamic	static	pebble	Rabit
time	59.12s	52.78s	18.22s	1655.84s	0.55s	0.52s	2.09s	127.53s
success %	80%	82%	86%	58%	100%	100%	100%	100%
average k	3.66	4.33	1.93	-	1.01	1.01	1.01	-

- ▶ incremental testing
 - ▶ reasonable approach for inclusion problem
 - ▶ when succeed, comparable to the complete method

Literatures

-  Etessami, K. A Hierarchy of Polynomial-Time Computable Simulations for Automata. *CONCUR* 2002.
-  Henzinger et al. Fair Simulation. *Inf. Comput.* 2002.
-  Abdulla et al. Advanced Ramsey-Based Büchi Automata Inclusion Testing. *CONCUR* 2011
-  Jurdzinski, M. Small Progress Measures for Solving Parity Games. *Inf. Comput.* 2000.
-  Friedmann, O. Lange, M. Solving Parity Games in Practice. *ATVA* 2009.
-  Tabakov, D. Vardi, M. Experimental Evaluation of Classical Automata Constructions. *LPAR* 2005.