

# **Automaton semigroups: the two-state case**

Ines Klimann

LIAFA – UMR 7089 CNRS & Université Paris Diderot  
MealyM – ANR JCJC 12 JS02 012 01




# Automata

finite stateset

finite alphabet

$$(A, \Sigma, \delta = (\delta_i : A \rightarrow A)_{i \in \Sigma})$$

transition functions




- ▶ no initial state
- ▶ no final state
- ▶ finite
- ▶ deterministic
- ▶ complete

# Mealy automata

production functions

$$\mathcal{A} = (A, \Sigma, \delta = (\delta_i : A \rightarrow A)_{i \in \Sigma}, \rho = (\rho_x : \Sigma \rightarrow \Sigma)_{a \in A})$$




►  $(A, \Sigma, \delta)$  is an automaton

►  $(\Sigma, A, \rho)$  is an automaton


# Mealy automata

production functions

$$\mathcal{A} = (A, \Sigma, \delta = (\delta_i : A \rightarrow A)_{i \in \Sigma}, \rho = (\rho_x : \Sigma \rightarrow \Sigma)_{a \in A})$$



- $(A, \Sigma, \delta)$  is an automaton
- $(\Sigma, A, \rho)$  is an automaton




# Generated semigroups

$$\mathcal{A} = (A, \Sigma, \delta, \rho)$$

$$\rho_x : \Sigma \rightarrow \Sigma$$

ex :  $\rho_a : 0 \mapsto 1$




# Generated semigroups

$$\mathcal{A} = (A, \Sigma, \delta, \rho)$$

$$\rho_x : \Sigma^* \rightarrow \Sigma^*$$

$$\text{ex} : \rho_a : 00\dots \mapsto 10\dots$$



# Generated semigroups


$$\mathcal{A} = (A, \Sigma, \delta, \rho)$$

$$\rho_x : \Sigma^* \rightarrow \Sigma^*$$

$$\text{ex : } \rho_a : 00\dots \mapsto 10\dots$$

generated semigroup :

$$\langle \mathcal{A} \rangle_+ = \langle \rho_x, x \in A \rangle_+$$



why automaton (semi)groups?








automaton (semi)groups

easy handling

Mealy automata  
automata theory

Tree automorphisms  
geometric (semi)group theory

## Grigorchuk automaton



Burnside : infinite torsion group  
infinite group with only finite order elements

Milnor : intermediate growth group

Atiyah, Day, Gromov, etc.

complex behaviour

automaton (semi)groups

easy handling

Mealy automata  
automata theory

Tree automorphisms  
geometric (semi)group theory

# Burnside problem

## Theorem 1

$\mathcal{A}$  two-state and reversible



$\langle \mathcal{A} \rangle_+$  finite or free of rank 2



# Burnside problem

## Theorem 1

$\mathcal{A}$  two-state and reversible



$\langle \mathcal{A} \rangle_+$  finite or free of rank 2

## Conjecture 1


$\mathcal{A}$  reversible



$\langle \mathcal{A} \rangle_+$  cannot answer to the Burnside problem



# Finiteness problem

 *The finiteness problem for automaton semigroups is undecidable,*  
P. Gillibert.  
arXiv :cs.FL/1304.2295 (2013)


## Theorem 2

The finiteness of a semigroup generated by a two-state bireversible automaton is decidable.

↪ decidability for two-letter bireversible automata



# Finiteness problem

 *The finiteness problem for automaton semigroups is undecidable,*  
P. Gillibert.  
arXiv :cs.FL/1304.2295 (2013)

## Theorem 2

The finiteness of a semigroup generated by a two-state bireversible automaton is decidable.

↪ decidability for two-letter bireversible automata

## Conjecture 2

The finiteness of a semigroup generated by a bireversible automaton is decidable.





L. Bartholdi and P.V. Silva.  
Groups defined by automata.  
arXiv :cs.FL/1012.1531 (2010)



I. Bondarenko, R.I. Grigorchuk, R. Kravchenko,  
Y. Muntyan, V. Nekrashevych, D. Savchuk, and Z. Šunić.  
On classification of groups generated by 3-state  
automata over a 2-letter alphabet.  
*Algebra Discrete Math.*, 1 :1–163, 2008.



R.I. Grigorchuk, V.V. Nekrashevich, and V.I. Sushchanskiĭ.  
Automata, dynamical systems, and groups.  
*Tr. Mat. Inst. Steklova*, 231 :134–214, 2000.



V. Nekrashevych.  
*Self-similar groups*, volume 117 of *Mathematical Surveys  
and Monographs*.  
American Mathematical Society, Providence, RI, 2005.