

# Polynomial Guarded Transformation for the Modal $\mu$ -Calculus Is Still Open

Florian Bruse, Oliver Friedmann and Martin Lange

September 19, 2013

# Guarded Normal Form

Setting: modal  $\mu$ -calculus and extensions

**GNF**: Every fixpoint variable under scope of a modal operator

Example:  $\mu X. \Diamond(P \vee X)$  guarded,  $\mu X. \nu Y. X \vee \Diamond Y$  not guarded

# Guarded Normal Form

Setting: modal  $\mu$ -calculus and extensions

**GNF**: Every fixpoint variable under scope of a modal operator

Example:  $\mu X. \Diamond(P \vee X)$  guarded,  $\mu X. \nu Y. X \vee \Diamond Y$  not guarded

Why GNF?

Synchronizes unfolding of fixpoints in tableaux, helps in constructions, translations to automata, etc.

can effectively transform any formula into guarded equivalent (BB89, Wal00, KVV00, Mat02)

Hence GNF commonly assumed when working with  $\mu$ -calculus

# Failure of Previous Results

Theorem: guarded transformation possible with **no blowup**  
(KVW00)/**quadratic blowup** (Mat02)

# Failure of Previous Results

Theorem: guarded transformation possible with **no blowup** (KVV00)/**quadratic blowup** (Mat02)

Counterexample is

$$\Phi_n = \mu X_n \cdots \mu X_1. (X_n \vee \cdots \vee X_1 \vee \Box (X_n \vee \cdots \vee X_1))$$

Known GT procedures produce formulae of exponential modal depth

Reason: occurrence of variable at modal depth  $d$  will produce formula at modal depth  $2d$  after unfolding

# Vectorial Form and Hierarchical Equation Systems

Vectorial Form: allow formulae of form

$$\sigma \left\{ \begin{array}{c} X_1.\varphi_1 \\ \vdots \\ X_n.\varphi_n \end{array} \right\} \text{ where each } \varphi_i \text{ may refer to all other } X_i.$$

# Vectorial Form and Hierarchical Equation Systems

Vectorial Form: allow formulae of form


$$\sigma \left\{ \begin{array}{c} X_1.\varphi_1 \\ \vdots \\ X_n.\varphi_n \end{array} \right\} \text{ where each } \varphi_i \text{ may refer to all other } X_i.$$

HES: Allow every fixpoint subformula to refer to every variable

Don't gain expressive power, but succinctness (best known algorithm to unfold is at least exponential)

Notion of guardedness can be generalized


# State of the Art





# State of the Art

Our results in blue



# Poly GT for Vect. Formulae $\rightarrow$ Poly PG Solving

1. Given  $\mu$ -calc. formula  $\varphi$  and TS  $\mathcal{T}, s$ , can obtain vectorial  $\varphi'$  and  $\mathcal{T}'$  s.t.  $\varphi'$   $\diamond, \square$ -free,  $\mathcal{T}'$  has only one state, both polynomial size, and

$$\mathcal{T}, s \models \varphi \leftrightarrow \mathcal{T}' \models \varphi'$$

# Poly GT for Vect. Formulae $\rightarrow$ Poly PG Solving

1. Given  $\mu$ -calc. formula  $\varphi$  and TS  $\mathcal{T}, s$ , can obtain vectorial  $\varphi'$  and  $\mathcal{T}'$  s.t.  $\varphi'$   $\diamond, \square$ -free,  $\mathcal{T}'$  has only one state, both polynomial size, and

$$\mathcal{T}, s \models \varphi \leftrightarrow \mathcal{T}' \models \varphi'$$

2. GT for  $\diamond, \square$ -free formula must eliminate all fixpoints

# Poly GT for Vect. Formulae $\rightarrow$ Poly PG Solving

1. Given  $\mu$ -calc. formula  $\varphi$  and TS  $\mathcal{T}, s$ , can obtain vectorial  $\varphi'$  and  $\mathcal{T}'$  s.t.  $\varphi'$   $\diamond, \square$ -free,  $\mathcal{T}'$  has only one state, both polynomial size, and

$$\mathcal{T}, s \models \varphi \leftrightarrow \mathcal{T}' \models \varphi'$$

2. GT for  $\diamond, \square$ -free formula must eliminate all fixpoints
3. model-check resulting formula in linear time

# Poly GT for Vect. Formulae $\rightarrow$ Poly PG Solving

1. Given  $\mu$ -calc. formula  $\varphi$  and TS  $\mathcal{T}, s$ , can obtain vectorial  $\varphi'$  and  $\mathcal{T}'$  s.t.  $\varphi'$   $\Diamond, \Box$ -free,  $\mathcal{T}'$  has only one state, both polynomial size, and

$$\mathcal{T}, s \models \varphi \leftrightarrow \mathcal{T}' \models \varphi'$$

2. GT for  $\Diamond, \Box$ -free formula must eliminate all fixpoints
3. model-check resulting formula in linear time
4. Consider PG, relevant Walukiewicz-formula: apply steps 1-3

Result: Polynomial GT for vectorial  $\mu$ -calculus gives rise to polynomial solution procedure for parity games

Also holds for HES

# Consequences and Outlook

## Consequences

- ▶ Results in KVV00 still hold
- ▶ Some results in other papers only valid for guarded formulae, see our paper (BFL13)

# Consequences and Outlook

## Consequences

- ▶ Results in KVV00 still hold
- ▶ Some results in other papers only valid for guarded formulae, see our paper (BFL13)

## Open Questions:

- ▶ polynomial GT for  $\mu$ -calculus  $\rightarrow$  polynomial parity game solving?
- ▶ polynomial parity game solving  $\rightarrow$  polynomial GT?
- ▶ relation between  $\epsilon$ -transitions in alternating automata and GNF

# The End

## Thanks!



# The End

**Thanks!**

## Literature:

BB99: B. Banieqbal and H. Barringer. Temporal logic with fixed points. In Proc. Coll. on Temporal Logic in Specification, volume 398 of LNCS, pages 62–73. Springer, 1989.

BFL13: F. Bruse, O. Friedmann, and M. Lange. Guarded Transformation for the Modal  $\mu$ -Calculus. ArXiv e-prints, May 2013.

KVW00: O. Kupferman, M. Y. Vardi, and P. Wolper. An automata-theoretic approach to branching-time model checking. Journal of the ACM, 47(2):312–360, 2000.

Mat02: R. Mateescu. Local model-checking of modal  $\mu$ -calculus on acyclic labeled transition systems. In Proc. 8th Int. Conf. on Tools and Algorithms for the Construction and Analysis of Systems, TACAS'02, volume 2280 of LNCS, pages 281–295. Springer, 2002.

NS99: H. Seidl and A. Neumann. On guarding nested fixpoints. In Proc. 8th Ann. Conf. on Computer Science Logic, CSL'99, volume 1683 of LNCS, pages 484–498. Springer, 1999.

Wal00: I. Walukiewicz. Completeness of Kozen's axiomatisation of the propositional  $\mu$ -calculus. Inf. and Comput., 157(1–2):142–182, 2000.