

# Positive logic is not elementary

Daria Walukiewicz-Chrząszcz  
University of Warsaw

(joint work with Aleksy Schubert and Paweł Urzyczyn)

Highlights 2013  
Paris, September 19, 2013

# *First-order intuitionistic logic*

# *First-order intuitionistic logic*

In intuitionistic logic:

# *First-order intuitionistic logic*

In intuitionistic logic:

Truth defined by provability

# *First-order intuitionistic logic*

In intuitionistic logic:

Truth defined by provability

Classical laws like: excluded middle, double negation elimination or De Morgans's laws are not valid

# *First-order intuitionistic logic*

In intuitionistic logic:

Truth defined by provability

Classical laws like: excluded middle, double negation elimination or De Morgans's laws are not valid

There is no **prenex normal form**

# First-order intuitionistic logic

In intuitionistic logic:

Truth defined by provability

Classical laws like: excluded middle, double negation elimination or De Morgans's laws are not valid

There is no **prenex normal form**

In classical logic:

Every formula is classically equivalent to one of the form:

$$Q_1 x_1 Q_2 x_2 \dots Q_k x_k. \textit{Body}(x_1, x_2, \dots, x_k),$$

where *Body* has no quantifiers

# *The language we study*

First-order formulas

- ▶ with  $\forall$  and  $\rightarrow$
- ▶ without function symbols



# *The language we study*

First-order formulas

- ▶ with  $\forall$  and  $\rightarrow$
- ▶ without function symbols

This fragment is known to be undecidable

# *Classification*

In classical logic:

# Classification

In classical logic:

Formulas may be classified according to the quantifier prefix

*“The Classical Decision Problem” by E.Börger , E.Grädel , Y.Gurevich*

# Classification

In classical logic:

Formulas may be classified according to the quantifier prefix

*“The Classical Decision Problem” by E.Börger , E.Grädel , Y.Gurevich*

In intuitionistic logic:

# Classification

In classical logic:

Formulas may be classified according to the quantifier prefix

*“The Classical Decision Problem” by E.Börger , E.Grädel , Y.Gurevich*

In intuitionistic logic:

The prenex fragment is much weaker (Pspace-complete)

# Classification

In classical logic:

Formulas may be classified according to the quantifier prefix

*"The Classical Decision Problem" by E.Börger , E.Grädel , Y.Gurevich*

In intuitionistic logic:

The prenex fragment is much weaker (Pspace-complete)


Mints hierarchy (1968): consider the quantifier prefix  
a formula *would get*, if classically normalized

## *Positive first-order logic*

$\forall$  quantifiers occurring at *positive* positions will remain  $\forall$  in the prefix

## Positive first-order logic


$\forall$  quantifiers occurring at *positive* positions will remain  $\forall$  in the prefix






## Positive first-order logic

$\forall$  quantifiers occurring at *positive* positions will remain  $\forall$  in the prefix



## Positive first-order logic

$\forall$  quantifiers occurring at *positive* positions will remain  $\forall$  in the prefix




Examples:

$$(\forall x P(x)) \rightarrow Q$$

not positive

## Positive first-order logic

$\forall$  quantifiers occurring at *positive* positions will remain  $\forall$  in the prefix



Examples:

$$\begin{array}{ll} (\forall x P(x)) \rightarrow Q & \text{not positive} \\ ((\forall x P(x)) \rightarrow Q) \rightarrow R & \text{positive} \end{array}$$

Positive first-order intuitionistic logic is decidable:  
Mints (1968), Dowek, Jiang (2006), Rummelhoff (2007)

*Proof construction seen as automaton*

## *Proof construction seen as automaton*

$$\Gamma \vdash \varphi$$

where  $\Gamma \rightarrow \varphi$  is positive.

## *Proof construction seen as automaton*

$$\Gamma \vdash \varphi$$

where  $\Gamma \rightarrow \varphi$  is positive.

Proofs  $\approx$  Automaton

## *Proof construction seen as automaton*

$$\Gamma \vdash \varphi$$

where  $\Gamma \rightarrow \varphi$  is positive.

Proofs  $\approx$  Automaton

$\varphi \approx$  state

## *Proof construction seen as automaton*

$$\Gamma \vdash \varphi$$

where  $\Gamma \rightarrow \varphi$  is positive.

Proofs  $\approx$  Automaton

$\varphi$   $\approx$  state

$\Gamma$   $\approx$  memory



## *Proof construction seen as automaton*

$$\Gamma \vdash \varphi$$

where  $\Gamma \rightarrow \varphi$  is positive.

Proofs  $\approx$  Automaton

$\varphi$   $\approx$  state

$\Gamma$   $\approx$  memory

proof-search process  $\approx$  computation

## *Proof construction seen as automaton*

$$\Gamma \vdash \varphi$$

where  $\Gamma \rightarrow \varphi$  is positive.

Proofs  $\approx$  Automaton

$\varphi$   $\approx$  state

$\Gamma$   $\approx$  memory

proof-search process  $\approx$  computation

proof completed  $\approx$  accept

## *Eden automata*

Memory: tree of knowledge:

## *Eden automata*


Memory: tree of knowledge:

- ▶ bounded depth, unbounded width;
- ▶ fixed number of registers in each node;

## Eden automata


Memory: tree of knowledge:

- ▶ bounded depth, unbounded width;
- ▶ fixed number of registers in each node;




## Eden automata

Automata configuration:  $\langle \text{tree}, \text{node}, \text{state} \rangle$




## Eden automata

No input, initially one node  $0000, q_I$




## *Eden automata—instructions*






## *Eden automata—instructions*

Move up to the father




## *Eden automata—instructions*

Move up to the father




## Eden automata—instructions

Move down to a son (chosen nondeterministically)




## *Eden automata—instructions*

Move down to a son (chosen nondeterministically)




## Eden automata—instructions

Write “1” in a given register at a given ancestor




## Eden automata—instructions

Write “1” in a given register at a given ancestor




## Eden automata—instructions

Check if a given register is “1” at a given ancestor



## Eden automata—instructions


Check if a given register is “1” at a given ancestor






## *Eden automata—instructions*

Create a new child and move there



## Eden automata—instructions

Create a new child and move there



## *Eden automata—limitations*

Non-erasing writes:

## *Eden automata—limitations*

Non-erasing writes: one cannot set a register to “0”

## *Eden automata—limitations*

Non-erasing writes: one cannot set a register to “0”

Positive reads:

## *Eden automata—limitations*

Non-erasing writes: one cannot set a register to “0”

Positive reads: one cannot check that a register is “0”

## *Eden automata—limitations*

Non-erasing writes: one cannot set a register to “0”

Positive reads: one cannot check that a register is “0”

Blind-access to children:

## *Eden automata—limitations*

Non-erasing writes: one cannot set a register to “0”

Positive reads: one cannot check that a register is “0”

Blind-access to children: one enters a random child  
(nondeterminism)



## *Eden automata—limitations*

Non-erasing writes: one cannot set a register to “0”

Positive reads: one cannot check that a register is “0”

Blind-access to children: one enters a random child  
(nondeterminism)

Bounded memory:

## *Eden automata—limitations*

**Non-erasing writes:** one cannot set a register to “0”

**Positive reads:** one cannot check that a register is “0”

**Blind-access to children:** one enters a random child  
(nondeterminism)

**Bounded memory:** one can access only bounded memory, even though the tree is unbounded

## *Alternation*


# *Alternation*

Computation is a tree

# Alternation

Computation is a tree


Typical use




# Alternation

Computation is a tree

Typical use



New (for us) use:



# Contributions

**Thm. 1:** *Any deterministic Turing Machine working in elementary time can be simulated by an Eden automaton.*

# Contributions

**Thm. 1:** *Any deterministic Turing Machine working in elementary time can be simulated by an Eden automaton.*

**Thm. 2:** *The halting problem for Eden Automata is logspace-reducible to positive logic.*



# Contributions

**Thm. 1:** *Any deterministic Turing Machine working in elementary time can be simulated by an Eden automaton.*

**Thm. 2:** *The halting problem for Eden Automata is logspace-reducible to positive logic.*

**Moral:** *The positive logic is not elementary.*

## Lessons learned

- ▶ Automata are good in proof theory

# Lessons learned

- ▶ Automata are good in proof theory
- ▶ Universal loops are useful

# Lessons learned

- ▶ Automata are good in proof theory
- ▶ Universal loops are useful
- ▶ Positive logic is extremely strong