

# On properties of logical sentences with arbitrary monadic predicates <sup>1</sup>

Nathanaël Fijalkow and Charles Paperman

LIAFA  
Université Paris Diderot

Highlights of logic, Game and Automata  
September, 2013

---

<sup>1</sup>The authors are supported by the ANR project FREC, the second author is supported by Fondation CFM.

# Introduction

A nice theorem [Barrington, Compton, Straubing and Thérien, 92]:

$$\mathbf{AC}^0 \cap \mathbf{REG} = \text{"almost aperiodic regular languages"}$$

# Introduction

A nice theorem [Barrington, Compton, Straubing and Thérien, 92]:

$$\mathbf{AC}^0 \cap \mathbf{REG} = \text{"almost aperiodic regular languages"}$$

$$\mathbf{FO}[\mathcal{M}] \cap \mathbf{REG} = \mathbf{FO}[\mathcal{REG}]$$

# Introduction

A nice theorem [Barrington, Compton, Straubing and Thérien, 92]:

$$\mathbf{AC}^0 \cap \mathbf{REG} = \text{"almost aperiodic regular languages"}$$

$$\mathbf{FO}[\mathcal{N}] \cap \mathbf{REG} = \mathbf{FO}[\mathcal{REG}]$$

# Introduction

A nice theorem [Barrington, Compton, Straubing and Thérien, 92]:

$$\mathbf{AC}^0 \cap \mathbf{REG} = \text{"almost aperiodic regular languages"}$$

$$\mathbf{FO}[\mathcal{M}] \cap \mathbf{REG} = \mathbf{FO}[\mathcal{REG}]$$

Remarks :

- ▶ Some generalisations are long-standing conjectures.
- ▶ Proofs rely on deep Circuit Complexity lower bounds.

# Introduction

A nice theorem [Barrington, Compton, Straubing and Thérien, 92]:

$$\mathbf{AC}^0 \cap \mathbf{REG} = \text{"almost aperiodic regular languages"}$$

$$\mathbf{FO}[\mathcal{N}] \cap \mathbf{REG} = \mathbf{FO}[\mathcal{REG}]$$

Remarks :

- ▶ Some generalisations are long-standing conjectures.
- ▶ Proofs rely on deep Circuit Complexity lower bounds.

Aim

Investigate the sub-case of *monadic numerical predicates* over **MSO**.

# Monadic Second Order Logic

$$\mathbf{MSO}[P] = \exists x \phi(x) \mid \exists X \phi(X) \mid \neg \phi \mid \psi \wedge \phi \mid x \in X \mid a(x) \mid P(x_1, \dots, x_r)$$

# Monadic Second Order Logic

$$\mathbf{MSO}[P] = \exists x \phi(x) \mid \exists X \phi(X) \mid \neg \phi \mid \psi \wedge \phi \mid x \in X \mid a(x) \mid P(x_1, \dots, x_r)$$

$x, x_1, \dots, x_r$  are positions over a **finite word**



# Monadic Second Order Logic

$$\mathbf{MSO}[P] = \exists x \phi(x) \mid \exists X \phi(X) \mid \neg \phi \mid \psi \wedge \phi \mid x \in X \mid a(x) \mid P(x_1, \dots, x_r)$$

$x, x_1, \dots, x_r$  are positions over a finite word

$X$  is set of positions.

# Monadic Second Order Logic

$$\mathbf{MSO}[P] = \exists x \phi(x) \mid \exists X \phi(X) \mid \neg \phi \mid \psi \wedge \phi \mid x \in X \mid a(x) \mid P(x_1, \dots, x_r)$$

$x, x_1, \dots, x_r$  are positions over a finite word

$X$  is set of positions.

$P$  is a  $r$ -ary numerical predicate. That is:

$$P = (P_n) \text{ with } P_n \subseteq \{0, \dots, n-1\}^r.$$

# Monadic Second Order Logic

$$\mathbf{MSO}[P] = \exists x \phi(x) \mid \exists X \phi(X) \mid \neg \phi \mid \psi \wedge \phi \mid x \in X \mid a(x) \mid P(x_1, \dots, x_r)$$

$x, x_1, \dots, x_r$  are positions over a finite word

$X$  is set of positions.

$P$  is a  $r$ -ary numerical predicate. That is:

$$P = (P_n) \text{ with } P_n \subseteq \{0, \dots, n-1\}^r.$$

$P$  is uniform if there is  $Q \subseteq \mathbb{N}^r$  such that

$$P_n = \{0, \dots, n-1\}^r \cap Q.$$

# Monadic Second Order Logic

$$\mathbf{MSO}[P] = \exists x \phi(x) \mid \exists X \phi(X) \mid \neg \phi \mid \psi \wedge \phi \mid x \in X \mid a(x) \mid P(x_1, \dots, x_r)$$

$x, x_1, \dots, x_r$  are positions over a finite word

$X$  is set of positions.

$P$  is a  $r$ -ary numerical predicate. That is:

$$P = (P_n) \text{ with } P_n \subseteq \{0, \dots, n-1\}^r.$$

$P$  is uniform if there is  $Q \subseteq \mathbb{N}^r$  such that

$$P_n = \{0, \dots, n-1\}^r \cap Q.$$

Notation:

Class of numerical predicates of arity at most  $r$ :  $\mathcal{N}_r$ .

Class of uniform numerical predicates of arity at most  $r$ :  $\mathcal{UN}_r$ .

# Monadic Second Order Logic

$$\mathbf{MSO}[P] = \exists x \phi(x) \mid \exists X \phi(X) \mid \neg \phi \mid \psi \wedge \phi \mid x \in X \mid a(x) \mid P(x_1, \dots, x_r)$$

$x, x_1, \dots, x_r$  are positions over a finite word

$X$  is set of positions.

$P$  is a  $r$ -ary numerical predicate. That is:

$$P = (P_n) \text{ with } P_n \subseteq \{0, \dots, n-1\}^r.$$

$P$  is uniform if there is  $Q \subseteq \mathbb{N}^r$  such that

$$P_n = \{0, \dots, n-1\}^r \cap Q.$$

Notation:

Class of all numerical predicates :  $\mathcal{N}$ .

Class of all uniform numerical predicates :  $\mathcal{UN}$ .

# Monadic Second Order Logic

$$\mathbf{MSO}[P] = \exists x \phi(x) \mid \exists X \phi(X) \mid \neg \phi \mid \psi \wedge \phi \mid x \in X \mid a(x) \mid P(x_1, \dots, x_r)$$

$x, x_1, \dots, x_r$  are positions over a finite word

$X$  is set of positions.

$P$  is a  $r$ -ary numerical predicate. That is:

$$P = (P_n) \text{ with } P_n \subseteq \{0, \dots, n-1\}^r.$$

$P$  is uniform if there is  $Q \subseteq \mathbb{N}^r$  such that

$$P_n = \{0, \dots, n-1\}^r \cap Q.$$

Examples :

Arity 2 non uniform predicate:  $2x + y = \text{max}$ .

Arity 3 uniform predicate:  $x + y = z$ .

# Regular Predicates

A predicate  $P$  is regular if, and only if, its a boolean combination of  $x \leq y, x \equiv r \bmod q, x = y + k$  with  $k$  fixed ,  $min, max$ .

Notation :

The class of regular predicates :  $\mathcal{REG}$ .

Examples :

Arity 1 non uniform predicate:  $x = max - 3$ .

Arity 2 uniform predicate:  $x < y + 3$ .

# Straubing and Crane-Beach Properties

$L \in \mathcal{N}_e\mathcal{L}$  if there is  $e$  such that for all words  $u, v$ :

$$uev \in L \leftrightarrow uv \in L.$$



# Straubing and Crane-Beach Properties

$L \in \mathcal{N}_e\mathcal{L}$  if there is  $e$  such that for all words  $u, v$ :

$$uev \in L \leftrightarrow uv \in L.$$

Let  $\mathcal{F}[<]$  be your favourite fragment of logic and  $\mathcal{P}$  a class of numerical predicates.

# Straubing and Crane-Beach Properties

$L \in \mathcal{N}_e\mathcal{L}$  if there is  $e$  such that for all words  $u, v$ :

$$uev \in L \leftrightarrow uv \in L.$$

Straubing Property

$$\mathcal{F}[<, \mathcal{P}] \cap \mathbf{REG} = \mathcal{F}[<, \mathcal{P} \cap \mathcal{REG}]$$

Crane-Beach Property

$$\mathcal{F}[<, \mathcal{P}] \cap \mathcal{N}_e\mathcal{L} = \mathcal{F}[<] \cap \mathcal{N}_e\mathcal{L}$$

# Straubing and Crane-Beach Properties

$L \in \mathcal{N}_e\mathcal{L}$  if there is  $e$  such that for all words  $u, v$ :

$$uev \in L \leftrightarrow uv \in L.$$

Straubing Property

$$\mathcal{F}[<, \mathcal{P}] \cap \mathbf{REG} = \mathcal{F}[<, \mathcal{P} \cap \mathcal{REG}]$$

► with:  $\mathbf{FO}[\mathcal{M}]$

Crane-Beach Property

$$\mathcal{F}[<, \mathcal{P}] \cap \mathcal{N}_e\mathcal{L} = \mathcal{F}[<] \cap \mathcal{N}_e\mathcal{L}$$

► with:  $\mathbf{FO}[+], \mathbf{FO}[\leq, \mathcal{N}_1]$

# Straubing and Crane-Beach Properties

$L \in \mathcal{N}_e\mathcal{L}$  if there is  $e$  such that for all words  $u, v$ :

$$uev \in L \leftrightarrow uv \in L.$$

Straubing Property

$$\mathcal{F}[<, \mathcal{P}] \cap \mathbf{REG} = \mathcal{F}[<, \mathcal{P} \cap \mathcal{REG}]$$

- ▶ with: **FO**[ $\mathcal{M}$ ]
- ▶ without: ?

Crane-Beach Property

$$\mathcal{F}[<, \mathcal{P}] \cap \mathcal{N}_e\mathcal{L} = \mathcal{F}[<] \cap \mathcal{N}_e\mathcal{L}$$

- ▶ with: **FO**[ $+$ ], **FO**[ $\leq$ ,  $\mathcal{N}_1$ ]
- ▶ without **FO**[ $+$ ,  $\times$ ]

# Crane-Beach for MSO

## Theorem

The languages definable in  $\mathbf{MSO}[<, \mathcal{N}_1]$  are exactly those recognized by *non-uniform advice automata*.

# Crane-Beach for **MSO**

## Theorem

The languages definable in **MSO** $[<, \mathcal{N}_1]$  are exactly those recognized by *non-uniform advice automata*.

## Corollary

**MSO** $[<, \mathcal{N}_1]$  has the Crane-Beach Property:

$$\mathbf{MSO}[<, \mathcal{N}_1] \cap \mathcal{N}_e \mathcal{L} = \mathbf{MSO}[<] \cap \mathcal{N}_e \mathcal{L}$$

# Substitution Property

## Definition

A fragment  $\mathcal{F}[<, \mathcal{P}]$  has the Substitution Property if any regular language defined by  $\varphi(P_1, \dots, P_k) \in \mathcal{F}[<, \mathcal{P}]$  can be defined by  $\varphi(R_1, \dots, R_k)$  such that  $R_i \in \mathcal{P} \cap \mathcal{REG}$  with the **same** formula  $\varphi$ .

# Substitution Property

## Definition

A fragment  $\mathcal{F}[<, \mathcal{P}]$  has the Substitution Property if any regular language defined by  $\varphi(P_1, \dots, P_k) \in \mathcal{F}[<, \mathcal{P}]$  can be defined by  $\varphi(R_1, \dots, R_k)$  such that  $R_i \in \mathcal{P} \cap \mathcal{REG}$  with the **same** formula  $\varphi$ .

## Theorem

**MSO**[<,  $\mathcal{UN}_1$ ] and **MSO**[<,  $\mathcal{N}_1$ ] have the Substitution Property.



# Substitution Property

## Definition

A fragment  $\mathcal{F}[<, \mathcal{P}]$  has the Substitution Property if any regular language defined by  $\varphi(P_1, \dots, P_k) \in \mathcal{F}[<, \mathcal{P}]$  can be defined by  $\varphi(R_1, \dots, R_k)$  such that  $R_i \in \mathcal{P} \cap \mathcal{REG}$  with the **same** formula  $\varphi$ .

## Theorem

**MSO**[<,  $\mathcal{UN}_1$ ] and **MSO**[<,  $\mathcal{N}_1$ ] have the Substitution Property.

## Corollary

1.  $\mathcal{F}[<, \mathcal{N}_1]$  and  $\mathcal{F}[<, \mathcal{UN}_1]$  have the Straubing Property.
2.  $\mathcal{F}[<, \mathcal{N}_1]$  has *almost* the Crane-Beach property:

$$\mathcal{F}[<, \mathcal{N}_1] \cap \mathcal{N}_e\mathcal{L} = \mathcal{F}[<, \mathcal{REG}_1] \cap \mathcal{N}_e\mathcal{L}$$