

Solving Parity Games on Integer Vectors

P.A. Abdulla¹ R. Mayr² **A. Sangnier**³ J. Sproston⁴

¹ *Uppsala University - Sweden*

² *University of Edinburgh - UK*

³ *LIAFA - Univ Paris Diderot - France*


⁴ *University of Turin - Italy*

Highlights - 21st september 2013

Finite-state parity games

Player 0 ○

Player 1 □




- Finite number of control states
- Every state belongs to Player 0 or Player 1
- Colors (in $\{1, \dots, k\}$) associated to each state
- **Parity winning condition:** Player 0 wins iff the highest color seen infinitely often is even

Finite-state parity games

Player 0 ○

Player 1 □




- Finite number of control states
- Every state belongs to Player 0 or Player 1
- Colors (in $\{1, \dots, k\}$) associated to each state
- **Parity winning condition:** Player 0 wins iff the highest color seen infinitely often is even

Finite-state parity games

Player 0 ○

Player 1 □




- Finite number of control states
- Every state belongs to Player 0 or Player 1
- Colors (in $\{1, \dots, k\}$) associated to each state
- **Parity winning condition:** Player 0 wins iff the highest color seen infinitely often is even

Finite-state parity games

Player 0 ○

Player 1 □




- Finite number of control states
- Every state belongs to Player 0 or Player 1
- Colors (in $\{1, \dots, k\}$) associated to each state
- **Parity winning condition:** Player 0 wins iff the highest color seen infinitely often is even

Finite-state parity games

Player 0 ○

Player 1 □




- Finite number of control states
- Every state belongs to Player 0 or Player 1
- Colors (in $\{1, \dots, k\}$) associated to each state
- **Parity winning condition:** Player 0 wins iff the highest color seen infinitely often is even

Integer vector games

Player 0 ○


Player 1 □



- Adding counters C_1, \dots, C_n to the game
- Transitions can decrement and increment the counter values
- Configurations are pairs (q, \mathbf{v}) with:
 - q : control state
 - $\mathbf{v} \in \mathbb{Z}^n$: values for the counters


Which role play the counters in the winning condition and in the enabledness of transitions ?

Energy semantics




- Transitions are always enabled regardless of the counter values
- If the value of one counter drops below 0, Player 1 wins
- Player 0 wins if no counter drops below 0 and if the parity condition is respected
- Higher value of the counters are always better for Player 0

Energy semantics




- Transitions are always enabled regardless of the counter values
- If the value of one counter drops below 0, Player 1 wins
- Player 0 wins if no counter drops below 0 and if the parity condition is respected
- Higher value of the counters are always better for Player 0

Energy semantics




- Transitions are always enabled regardless of the counter values
- If the value of one counter drops below 0, Player 1 wins
- Player 0 wins if no counter drops below 0 and if the parity condition is respected
- Higher value of the counters are always better for Player 0

Energy semantics




- Transitions are always enabled regardless of the counter values
- If the value of one counter drops below 0, Player 1 wins
- Player 0 wins if no counter drops below 0 and if the parity condition is respected
- Higher value of the counters are always better for Player 0

VASS semantics




- Configurations : (q, \mathbf{v}) with $\mathbf{v} \in \mathbb{N}^n$
- Transitions that make a counter drop below 0 are disabled
- Player 0 wins if the parity condition is respected
- **Higher value of the counters are NOT always better for Player 0**

VASS semantics




- Configurations : (q, \mathbf{v}) with $\mathbf{v} \in \mathbb{N}^n$
- Transitions that make a counter drop below 0 are disabled
- Player 0 wins if the parity condition is respected
- **Higher value of the counters are NOT always better for Player 0**

VASS semantics




- Configurations : (q, \mathbf{v}) with $\mathbf{v} \in \mathbb{N}^n$
- Transitions that make a counter drop below 0 are disabled
- Player 0 wins if the parity condition is respected
- **Higher value of the counters are NOT always better for Player 0**

VASS semantics




- Configurations : (q, \mathbf{v}) with $\mathbf{v} \in \mathbb{N}^n$
- Transitions that make a counter drop below 0 are disabled
- Player 0 wins if the parity condition is respected
- **Higher value of the counters are NOT always better for Player 0**

VASS semantics




- Configurations : (q, \mathbf{v}) with $\mathbf{v} \in \mathbb{N}^n$
- Transitions that make a counter drop below 0 are disabled
- Player 0 wins if the parity condition is respected
- **Higher value of the counters are NOT always better for Player 0**

VASS semantics




- Configurations : (q, \mathbf{v}) with $\mathbf{v} \in \mathbb{N}^n$
- Transitions that make a counter drop below 0 are disabled
- Player 0 wins if the parity condition is respected
- **Higher value of the counters are NOT always better for Player 0**

VASS semantics



- Configurations : (q, \mathbf{v}) with $\mathbf{v} \in \mathbb{N}^n$
- Transitions that make a counter drop below 0 are disabled
- Player 0 wins if the parity condition is respected
- **Higher value of the counters are NOT always better for Player 0**

VASS semantics



- Configurations : (q, \mathbf{v}) with $\mathbf{v} \in \mathbb{N}^n$
- Transitions that make a counter drop below 0 are disabled
- Player 0 wins if the parity condition is respected
- **Higher value of the counters are NOT always better for Player 0**

Problems

For $I \in \{\text{Energy}, \text{VASS}\}$ and a game \mathcal{G} :

- $\text{Win}(\mathcal{G}, I) = \{(q, \mathbf{v}) \in Q \times \mathbb{N}^n \mid$
Player 0 has a winning strategy from $(q, \mathbf{v})\}$

Unknown initial credit problem

- **Input:** A game \mathcal{G} and a semantic $I \in \{\text{Energy}, \text{VASS}\}$
- **Output:** Is $\text{Win}(\mathcal{G}, I)$ not empty ?

Fixed initial credit problem

- **Input:** A game \mathcal{G} , a semantic $I \in \{\text{Energy}, \text{VASS}\}$ and a configuration (q, \mathbf{v})
- **Output:** Do we have $(q, \mathbf{v}) \in \text{Win}(\mathcal{G}, I)$?

Computing the winning set

- **Input:** A game \mathcal{G} and a semantic $I \in \{\text{Energy}, \text{VASS}\}$
- **Output:** Can we compute (and represent finitely) $\text{Win}(\mathcal{G}, I)$?

Previous results

Theorem

[Chatterjee et al., Concur'12]

The unknown initial credit problem is coNP -complete for energy games.


Theorem


[Abdulla et al., CSL'03]


The fixed initial credit problem is undecidable for VASS games (even with reachability objectives).

Single sided games

- Player 1 cannot change the counter values only the control states

Player 0 

Player 1 



Theorem

[Raskin et al., AVoCS'04]

The fixed initial credit problem is decidable for single-sided VASS games with reachability objectives.

Upward-closed winning sets

Upward-closed set

A set $S \subseteq Q \times \mathbb{N}^n$ is upward-closed iff for $(q, \mathbf{v}) \in S$ and all $\mathbf{v}' \in \mathbb{N}^n$, $\mathbf{v} \leq \mathbf{v}'$ implies $(q, \mathbf{v}') \in S$.

Dickson's Lemma



Upward-closed set of $Q \times \mathbb{N}^n$ have a finite number of minimal elements.

- To represent an upward-closed set it is hence enough to store its minimal elements

Proposition

For energy games and single-sided VASS games, the winning sets are upward closed.

From energy games to single-sided games



Proposition

Energy games and single-sided VASS games are PTIME inter-reducible.

Results

Theorem

For single-sided VASS games, the minimal elements of the winning sets are computable.

Corollary

For energy games, the minimal elements of the winning sets are computable.

Hence, for single-sided VASS games and energy games we can solve:

- The unknown initial credit problem
- The fixed initial credit problem

Application to μ -calculus model-checking

- μ -calculus model checking translates into solving a parity game on the system (plus a new control graph).

Application to μ -calculus model-checking

- μ -calculus model checking translates into solving a parity game on the system (plus a new control graph).
- In general, this is undecidable for VASS.

Application to μ -calculus model-checking

- μ -calculus model checking translates into solving a parity game on the system (plus a new control graph).
- In general, this is undecidable for VASS.
- Simple modal logics CTL, EF, EG are fragments of modal μ -calculus.
Model checking VASS with them is **still undecidable**.

Application to μ -calculus model-checking

- μ -calculus model checking translates into solving a parity game on the system (plus a new control graph).
- In general, this is undecidable for VASS.
- Simple modal logics CTL, EF, EG are fragments of modal μ -calculus.
Model checking VASS with them is **still undecidable**.
- **But single-sided parity games on VASS are decidable**

Application to μ -calculus model-checking

- μ -calculus model checking translates into solving a parity game on the system (plus a new control graph).
- In general, this is undecidable for VASS.
- Simple modal logics CTL, EF, EG are fragments of modal μ -calculus.
Model checking VASS with them is **still undecidable**.
- **But single-sided parity games on VASS are decidable**
- Is there a fragment of μ -calculus where model checking VASS translates into a **single-sided** VASS parity game?

Application to μ -calculus model-checking

- μ -calculus model checking translates into solving a parity game on the system (plus a new control graph).
- In general, this is undecidable for VASS.
- Simple modal logics CTL, EF, EG are fragments of modal μ -calculus.
Model checking VASS with them is **still undecidable**.
- **But single-sided parity games on VASS are decidable**
- Is there a fragment of μ -calculus where model checking VASS translates into a **single-sided** VASS parity game?
- **Yes!** Intuitively, universal one-step next modalities are guarded s.t. they are applied only at control-states that do not modify counters.
Existential one-step next has no restrictions

Application to μ -calculus model-checking

- μ -calculus model checking translates into solving a parity game on the system (plus a new control graph).
- In general, this is undecidable for VASS.
- Simple modal logics CTL, EF, EG are fragments of modal μ -calculus.
Model checking VASS with them is **still undecidable**.
- **But single-sided parity games on VASS are decidable**
- Is there a fragment of μ -calculus where model checking VASS translates into a **single-sided** VASS parity game?
- **Yes!** Intuitively, universal one-step next modalities are guarded s.t. they are applied only at control-states that do not modify counters.
Existential one-step next has no restrictions
- This fragment of μ -calculus is incomparable with EF,EG,CTL, and can express non-trivial properties.

Conclusion

What have we done ?

- The winning set of single-sided VASS games can be computed
- Energy games and single-sided VASS games are interreducible
- Our decidability result can be used for model-checking VASS

What's next ?

- Use single-sided VASS to verify more complex systems
- Extend our result with other games (imperfect information for instance)
- Extend our result to stochastic games