

Context



Tools and proof techniques for systems equivalence

Methodology:

1. First do it naively
2. Then improve the associated proof method


Deterministic finite automata

The states x and u are language equivalent




Deterministic finite automata

The states x and u are language equivalent




Deterministic finite automata

The states x and u are language equivalent




Deterministic finite automata

The states x and u are language equivalent




Deterministic finite automata

The states x and u are language equivalent





Deterministic finite automata

The states x and u are language equivalent




Deterministic finite automata

x and u are **not** equivalent




Deterministic finite automata

x and u are **not** equivalent




Deterministic finite automata

x and u are **not** equivalent




Deterministic finite automata

x and u are **not** equivalent




Deterministic finite automata

x and u are **not** equivalent





Deterministic finite automata

x and u are **not** equivalent




Deterministic finite automata

Last example, with two letters




Deterministic finite automata

Last example, with two letters




Deterministic finite automata

Last example, with two letters




Deterministic finite automata

Last example, with two letters




Deterministic finite automata

Last example, with two letters




Deterministic finite automata

Last example, with two letters




Deterministic finite automata

Last example, with two letters



Deterministic finite automata

Last example, with two letters



Correctness

- ▶ A relation R is a **proof of equivalence** (bisimulation) if $x R y$ entails
 - ▶ $o(x) = o(y)$;
 - ▶ for all a , $t_a(x) R t_a(y)$.

Correctness

- ▶ A relation R is a **proof of equivalence** (bisimulation) if $x R y$ entails
 - ▶ $o(x) = o(y)$;
 - ▶ for all a , $t_a(x) R t_a(y)$.
- ▶ *Theorem:* $L(x) = L(y)$ iff there exists a bisimulation R with $x R y$


Correctness

- ▶ A relation R is a **proof of equivalence** (bisimulation) if $x R y$ entails
 - ▶ $o(x) = o(y)$;
 - ▶ for all a , $t_a(x) R t_a(y)$.
- ▶ *Theorem:* $L(x) = L(y)$ iff there exists a bisimulation R with $x R y$

The previous algorithm attempts to construct a bisimulation


Complexity

The previous algorithm is **quadratic**



Complexity


The previous algorithm is **quadratic**



0 pairs

Complexity


The previous algorithm is **quadratic**



1 pairs

Complexity


The previous algorithm is **quadratic**



2 pairs

Complexity


The previous algorithm is **quadratic**



3 pairs

Complexity


The previous algorithm is **quadratic**



4 pairs

Complexity


The previous algorithm is **quadratic**



5 pairs

Complexity


The previous algorithm is **quadratic**



6 pairs

Complexity


The previous algorithm is **quadratic**



7 pairs

Complexity


The previous algorithm is **quadratic**



8 pairs

Complexity


The previous algorithm is **quadratic**



9 pairs

Complexity


The previous algorithm is **quadratic**



10 pairs

Complexity


The previous algorithm is **quadratic**



11 pairs

Complexity


The previous algorithm is **quadratic**



12 pairs

Complexity


The previous algorithm is **quadratic**



13 pairs

Complexity


The previous algorithm is **quadratic**



14 pairs

Complexity


The previous algorithm is **quadratic**



15 pairs

Complexity


The previous algorithm is **quadratic**



16 pairs

Complexity


The previous algorithm is **quadratic**



17 pairs

Complexity


The previous algorithm is **quadratic**



18 pairs

Complexity


The previous algorithm is **quadratic**



19 pairs

Complexity


The previous algorithm is **quadratic**



20 pairs

Complexity


The previous algorithm is **quadratic**



21 pairs

Complexity


The previous algorithm is **quadratic**



21 pairs

First improvement


One can stop much earlier



21 pairs

First improvement


One can stop much earlier



21 20 pairs

First improvement


One can stop much earlier



21 19 pairs

First improvement


One can stop much earlier



21 18 pairs

First improvement


One can stop much earlier



21 17 pairs

First improvement


One can stop much earlier



21 16 pairs

First improvement


One can stop much earlier



21 15 pairs

First improvement


One can stop much earlier



21 14 pairs

First improvement


One can stop much earlier



21 13 pairs

First improvement


One can stop much earlier



21 12 pairs

First improvement


One can stop much earlier



~~21~~ 11 pairs

First improvement


One can stop much earlier



21 10 pairs

First improvement


One can stop much earlier



21 9 pairs

First improvement


One can stop much earlier



[Hopcroft and Karp '71]

First improvement

One can stop much earlier



Complexity: almost linear

[Hopcroft and Karp '71]

[Tarjan '75]


Correctness of the improvement

Correctness of HK algorithm, revisited:

- ▶ The previous relation is **not** a bisimulation - proof of equivalence
- ▶ But can be completed to one using equivalence - transitivity
- ▶ Hopcroft and Karp's algorithm ('71) attempts to construct a bisimulation up to equivalence


Non-Deterministic Automata

Use Hopcroft and Karp **on the fly**, through the powerset construction:



Non-Deterministic Automata



Use Hopcroft and Karp **on the fly**, through the powerset construction:



x
|
|
|
 u



Non-Deterministic Automata

Use Hopcroft and Karp **on the fly**, through the powerset construction:





Non-Deterministic Automata

Use Hopcroft and Karp **on the fly**, through the powerset construction:





Non-Deterministic Automata

Use Hopcroft and Karp **on the fly**, through the powerset construction:





Non-Deterministic Automata

Use Hopcroft and Karp **on the fly**, through the powerset construction:





Non-Deterministic Automata

Use Hopcroft and Karp **on the fly**, through the powerset construction:





Non-Deterministic Automata

Use Hopcroft and Karp **on the fly**, through the powerset construction:





Non-Deterministic Automata

Use Hopcroft and Karp **on the fly**, through the powerset construction:




Non-Deterministic Automata

One can do **better**:




Non-Deterministic Automata

One can do **better**:




$$\frac{(x, u) + (y, v+w)}{= (x+y, u+v+w)}$$




Non-Deterministic Automata

One can do **better**:




$$\frac{(x, u) + (y, v+w)}{= (x+y, u+v+w)}$$



using bisimulations **up to union**


Non-Deterministic Automata

One can do **even** better:



Non-Deterministic Automata

One can do **even** better:




$$x+y = u+y \quad (1)$$

$$= y+z+y \quad (2)$$


$$= y+z$$

$$= u \quad (2)$$



Non-Deterministic Automata

One can do **even** better:




$$x+y = u+y \quad (1)$$

$$= y+z+y \quad (2)$$


$$= y+z$$

$$= u \quad (2)$$



Non-Deterministic Automata

One can do **even** better:




$$x+y = u+y \quad (1)$$

$$= y+z+y \quad (2)$$

$$= y+z$$


$$= u \quad (2)$$



using bisimulations **up to congruence**

Non-Deterministic Automata

One can do **even** better:




$$x+y = u+y \quad (1)$$

$$= y+z+y \quad (2)$$

$$= y+z$$

$$= u \quad (2)$$



this yield to the HKC algorithm [Bonchi, Pous'13]