

Approximating Weak Bisimilarity of Basic Parallel Processes

Patrick Totzke¹ Piotrek Hofman²

¹LFCS, University of Edinburgh

²University of Warsaw

September 7, 2012

Basic Parallel Processes (BPP)

Rewriting Rules


$$\{Q \xrightarrow{a} QQ, Q \xrightarrow{b} \varepsilon, Q \xrightarrow{c} Q\}$$

Basic Parallel Processes (BPP)

Rewriting Rules

$$\{Q \xrightarrow{a} QQ, Q \xrightarrow{b} \varepsilon, Q \xrightarrow{c} Q\}$$

Transition System




Basic Parallel Processes (BPP)


Rewriting Rules

$$\{Q \xrightarrow{a} QQ, Q \xrightarrow{b} \varepsilon, Q \xrightarrow{c} Q\}$$

Notation



Transition System




Basic Parallel Processes (BPP)


Rewriting Rules

$$\{Q \xrightarrow{a} QQ, Q \xrightarrow{b} \varepsilon, Q \xrightarrow{c} Q\}$$

Notation



Transition System



Bisimulation Games

...are played in rounds between Spoiler and Duplicator. If a player cannot move the other wins. Infinite plays are won by Duplicator.

Bisimulation Games

...are played in rounds between Spoiler and Duplicator. If a player cannot move the other wins. Infinite plays are won by Duplicator.

In each round


α vs. β

- 1 Spoiler moves \xrightarrow{a} from one process
- 2 Duplicator responds \xrightarrow{a} from the other
- 3 the game continues from α' vs. β' .

Bisimulation Games

...are played in rounds between Spoiler and Duplicator. If a player cannot move the other wins. Infinite plays are won by Duplicator.

In each round




- 1 Spoiler moves \xrightarrow{a} from one process
- 2 Duplicator responds \xrightarrow{a} from the other
- 3 the game continues from α' vs. β' .

Bisimulation Games

...are played in rounds between Spoiler and Duplicator. If a player cannot move the other wins. Infinite plays are won by Duplicator.

In each round




- 1 Spoiler moves \xrightarrow{a} from one process
- 2 Duplicator responds \xrightarrow{a} from the other
- 3 the game continues from α' vs. β' .

Bisimulation Games

...are played in rounds between Spoiler and Duplicator. If a player cannot move the other wins. Infinite plays are won by Duplicator.

In each round




- 1 Spoiler moves \xrightarrow{a} from one process
- 2 Duplicator responds \xrightarrow{a} from the other
- 3 the game continues from α' vs. β' .

Bisimulation Games

...are played in rounds between Spoiler and Duplicator. If a player cannot move the other wins. Infinite plays are won by Duplicator.

In each round



- 1 Spoiler moves \xrightarrow{a} from one process
- 2 Duplicator responds \xrightarrow{a} from the other
- 3 the game continues from α' vs. β' .

Def: Bisimulation (\sim)

$\alpha \sim \beta$ iff Duplicator has a strategy to win the game from α vs. β .

Silent and Weak Steps

silent weak step

$$\Longrightarrow^{\tau} := \longrightarrow^{\tau*}$$


visible weak step ($a \neq \tau$)

$$\Longrightarrow^a := \longrightarrow^{\tau*} \longrightarrow^a \longrightarrow^{\tau*}$$

Bisimulation Games

...are played in rounds between Spoiler and Duplicator. If a player cannot move the other wins. Infinite plays are won by Duplicator.

In each round



- 1 Spoiler moves \xrightarrow{a} from one process
- 2 Duplicator responds \xrightarrow{a} from the other
- 3 the game continues from α' vs. β' .


Bisimulation \sim

$\alpha \sim \beta$ iff Duplicator has a strategy to win the game from α vs. β .

Weak Bisimulation Games

...are played in rounds between Spoiler and Duplicator. If a player cannot move the other wins. Infinite plays are won by Duplicator.

In each round



- 1 Spoiler moves \xRightarrow{a} from one process
- 2 Duplicator responds \xRightarrow{a} from the other
- 3 the game continues from α' vs. β' .

Weak Bisimulation \approx

$\alpha \approx \beta$ iff Duplicator has a strategy to win the game from α vs. β .

Approximants

Idea

$\alpha \sim_i \beta$ iff Duplicator can survive i rounds of the game.

Approximants

Idea

$\alpha \sim_i \beta$ iff Duplicator can survive i rounds of the game.

$$\sim_0 \supseteq \sim_1 \supseteq \sim_2 \dots$$

Approximants

Idea

$\alpha \sim_i \beta$ iff Duplicator can survive i rounds of the game.

$$\sim_0 \supseteq \sim_1 \supseteq \sim_2 \dots \supseteq \sim_\omega = \bigcap_{i \in \mathbb{N}} \sim_i$$

Approximants

Idea

$\alpha \sim_i \beta$ iff Duplicator can survive i rounds of the game.

For image-finite systems:

$$\sim_0 \supseteq \sim_1 \supseteq \sim_2 \dots \supseteq \sim_\omega = \bigcap_{i \in \mathbb{N}} \sim_i = \sim$$

Approximants

Idea

$\alpha \sim_i \beta$ iff Duplicator can survive i rounds of the game.

For image-finite systems:

$$\sim_0 \supseteq \sim_1 \supseteq \sim_2 \dots \supseteq \sim_\omega = \bigcap_{i \in \mathbb{N}} \sim_i = \sim$$

In general:


$$\sim_0 \supseteq \sim_\omega \supseteq \sim_{\omega+\omega} \supseteq \sim_{\omega*\omega} \supseteq \sim_{\omega^\omega} \supseteq \sim$$

A Guessing Game

Pick a number; stepwise decrease by some positive integer; lose when you go below 0.


A Guessing Game

Pick a number; stepwise decrease by some positive integer; lose when you go below 0.




A Guessing Game

Pick a number; stepwise decrease by some positive integer; lose when you go below 0.




A Guessing Game

Pick a number; stepwise decrease by some positive integer; lose when you go below 0.



A Guessing Game

Pick a number; stepwise decrease by some positive integer; lose when you go below 0.






$$X \begin{array}{c} \Downarrow \\ a \\ \Downarrow \\ Z \end{array}$$

$$Y \begin{array}{c} \Downarrow \\ a \\ \Downarrow \\ Q^n \end{array}$$




A Guessing Game

Pick a number; stepwise decrease by some positive integer; lose when you go below 0.






A Guessing Game

Pick a number; stepwise decrease by some positive integer; lose when you go below 0.






A Guessing Game

Pick a number; stepwise decrease by some positive integer; lose when you go below 0.





A Guessing Game

Pick a number; stepwise decrease by some positive integer; lose when you go below 0.





A Guessing Game

Pick a number; stepwise decrease by some positive integer; lose when you go below 0.





A Guessing Game

Pick a number; stepwise decrease by some positive integer; lose when you go below 0.





A Guessing Game

Pick a number; stepwise decrease by some positive integer; lose when you go below 0.





A Guessing Game

Pick a number; stepwise decrease by some positive integer; lose when you go below 0.



A Guessing Game ($X \approx_\omega Y \not\approx X$)

Pick a number; stepwise decrease by some positive integer; lose when you go below 0.



Using Approximants to decide Weak Bisimilarity

Semi-deciding \approx

... can be done (Esparza '97).

Using Approximants to decide Weak Bisimilarity

Semi-deciding \approx

... can be done (Esparza '97).

Semi-deciding $\not\approx$

For every finite approximant level i check if $(\alpha, \beta) \notin \approx_i$

Using Approximants to decide Weak Bisimilarity

Semi-deciding \approx

... can be done (Esparza '97).

Semi-deciding $\not\approx$

For every finite approximant level i check if $(\alpha, \beta) \notin \approx_i$

① needs $\approx = \bigcap_{i \in \mathbb{N}} \approx_i$

Using Approximants to decide Weak Bisimilarity

Semi-deciding \approx

... can be done (Esparza '97).

Semi-deciding $\not\approx$

For every finite approximant level i check if $(\alpha, \beta) \notin \approx_i$

- 1 needs $\approx = \bigcap_{i \in \mathbb{N}} \approx_i$
- 2 needs decidable \approx_i

Using Approximants to decide Weak Bisimilarity

Semi-deciding \approx

... can be done (Esparza '97).

Semi-deciding $\not\approx$

For every finite approximant level i check if $(\alpha, \beta) \notin \approx_i$

- 1 needs $\approx = \bigcap_{i \in \mathbb{N}} \approx_i$
- 2 needs decidable \approx_i ✓

Using Approximants to decide Weak Bisimilarity

Semi-deciding \approx

... can be done (Esparza '97).

Semi-deciding $\not\approx$

For every finite approximant level i check if $(\alpha, \beta) \notin \approx_i$

- 1 needs $\approx = \bigcap_{i \in \mathbb{N}} \approx_i$ ✗
- 2 needs decidable \approx_i ✓

A Conjecture

Conjecture (Jančar, Hirshfeld)

For any BPP process description, $\approx = \approx_{\omega+\omega}$

A Conjecture

Conjecture (Jančar, Hirshfeld)

For any BPP process description, $\approx = \approx_{\omega+\omega}$

- If this holds *and we could decide* \approx_{ω} then we could semi-decide $\not\approx$.


A Conjecture

Conjecture (Jančar, Hirshfeld)

For any BPP process description, $\approx = \approx_{\omega+\omega}$


- If this holds *and we could decide* \approx_{ω} then we could semi-decide $\not\approx$.
- To falsify we look for inequivalent processes $\alpha \approx_{\omega+\omega} \beta$.

Non-convergence of \approx_i at level $\omega + \omega$



$$X \approx_{\omega} Y \not\approx X$$


Non-convergence of \approx_i at level $\omega + \omega$



$$X \approx_{\omega} Y \not\approx X$$


$$W \approx \varepsilon$$

Non-convergence of \approx_i at level $\omega + \omega$



$$\begin{aligned} X &\approx_{\omega} Y \not\approx X \\ W &\approx \varepsilon \end{aligned}$$


Non-convergence of \approx_i at level $\omega + \omega$



$$X \approx_{\omega} Y \not\approx X$$

$$W \approx \epsilon$$

Non-convergence of \approx_i at level $\omega + \omega$



$$X \approx_{\omega} Y \not\approx X$$

$$W \approx \varepsilon$$


$$XB^m \approx_{\omega} YB^n \not\approx XB^m$$

Non-convergence of \approx_i at level $\omega + \omega$

$$XB^m \approx_\omega YB^n \not\approx XB^m$$

 X Y

Non-convergence of \approx_i at level $\omega + \omega$




X

Y

$$X_2 \approx_\omega Y_2 \not\approx X_2$$

$$XB^m \approx_\omega YB^n \not\approx XB^m$$


Non-convergence of \approx_i at level $\omega + \omega$



$$X_2 \approx Y_2 \approx X_2$$


$$XB^m \approx_\omega YB^n \not\approx XB^m$$

Non-convergence of \approx_i at level $\omega + \omega$




$$X_2 \approx_{\omega} Y_2 \not\approx X_2$$
$$XB^m \approx_{\omega} YB^n \not\approx XB^m$$

Non-convergence of \approx_i at level $\omega + \omega$



$$\begin{aligned}
 X_2 &\approx_{\omega} Y_2 \not\approx X_2 \\
 XB^m &\approx_{\omega} YB^n \not\approx XB^m \\
 Z_2 &\approx_{\omega+1} S_2 \not\approx Z_2
 \end{aligned}$$

Non-convergence of \approx_i at level $\omega + \omega$




$$X_2 \approx_{\omega} Y_2 \not\approx X_2$$

$$XB^m \approx_{\omega} YB^n \not\approx XB^m$$

$$Z_2 \approx_{\omega+1} S_2 \not\approx Z_2$$

$$Z_2 \approx_{\omega+2} W_2 \not\approx Z_2$$

Non-convergence of \approx_i at level $\omega + \omega$




$$X_2 \approx_{\omega+\omega} Y_2 \not\approx X_2$$

$$XB^m \approx_{\omega} YB^n \not\approx XB^m$$

$$Z_2 \approx_{\omega+1} S_2 \not\approx Z_2$$

$$Z_2 \approx_{\omega+2} W_2 \not\approx Z_2$$

Non-convergence of \approx_i at level $\omega + \omega$



$$X_2 \approx_{\omega+\omega} Y_2 \not\approx X_2$$

$$XB^m \approx_{\omega} YB^n \not\approx XB^m$$

$$Z_2 \approx_{\omega+1} S_2 \not\approx Z_2$$

$$Z_2 \approx_{\omega+2} W_2 \not\approx Z_2$$

Stacking this k
times yields
processes

$$X_k \approx_{\omega*k} Y_k \not\approx X_k.$$

Norms

The *norm* of process α :

the length of the shortest word $w = a_0 a_1 \cdots a_n$ such that $\alpha \xrightarrow{a_0} \xrightarrow{a_1} \cdots \xrightarrow{a_n} \varepsilon$ and ∞ if no such words exists.

Norms

The *norm* of process α :

the length of the shortest word $w = a_0 a_1 \cdots a_n$ such that $\alpha \xrightarrow{a_0} \xrightarrow{a_1} \cdots \xrightarrow{a_n} \varepsilon$ and ∞ if no such words exists.

Properties

- Norms can be easily computed
- Norm equality is an invariant for \approx


Faster Approximants

Can we define faster converging approximants?

Faster Approximants

Can we define faster converging approximants?


Example: Word Approximants



Faster Approximants

Can we define faster converging approximants?

Example: Word Approximants



Example: Add Invariant P

Let \approx_i^P enforce that Duplicator must preserve P . Then for every i ,

$$\approx_i \supseteq \approx_i^P$$

Jitka's Class

Jitka's Class

(Stribrna '98: $\approx = \approx_{\omega+\omega}$)

- one visible action symbol
- no zero-norm variables (and no trivial deadlocks)

Jitka's Class

Jitka's Class

(Stribrna '98: $\approx = \approx_{\omega+\omega}$)

- one visible action symbol
- no zero-norm variables (and no trivial deadlocks)

Properties

- If $norm(\alpha) = norm(\beta) = \infty$ then $\alpha \approx \beta$
- $Succ_n(\alpha) = \{\alpha' : \alpha \xrightarrow{a} \alpha' \wedge |\alpha'| = n < \infty\}$ is finite

Jitka's Class

Jitka's Class

(Stribrna '98: $\approx = \approx_{\omega+\omega}$)

- one visible action symbol
- no zero-norm variables (and no trivial deadlocks)

Properties

- If $norm(\alpha) = norm(\beta) = \infty$ then $\alpha \approx \beta$
- $Succ_n(\alpha) = \{\alpha' : \alpha \xrightarrow{a} \alpha' \wedge |\alpha'| = n < \infty\}$ is finite

Approximants with Norm test

Check norm equality in each round. Then $\approx_{\omega}^N = \approx$.

Word Approximants (\approx_i^W)

- ① are undecidable already at level 1 for normed BPP

Word Approximants (\approx_i^W)

- ① are undecidable already at level 1 for normed BPP ✗


Word Approximants (\approx_i^W)

- ① are undecidable already at level 1 for normed BPP ✗
- ② do not converge at level ω

Word Approximants (\approx_i^W)

- ① are undecidable already at level 1 for normed BPP **✗**
- ② do not converge at level ω **✗**

Idea: Preserve equality on "contains R " to force short steps




Play L^{n+1} vs. L^n , where n is Duplicator's choice

Word Approximants (\approx_i^W)

- ① are undecidable already at level 1 for normed BPP ✗
- ② do not converge at level ω ✗

Idea: Preserve equality on "contains R " to force short steps



Play L^{n+1} vs. L^n , where n is Duplicator's choice

This is useful!

Any successful approach will define a computable $\not\approx_\omega^W \subsetneq D \subseteq \not\approx$.

Hopeless invariants

Norm Equality

If α and β has different norms then \approx_2^W distinguishes them.

Hopeless invariants

Norm Equality

If α and β has different norms then \approx_2^W distinguishes them.

Ability to perform an infinite sequence a^ω

Captured by \approx_1^W .

Hopeless invariants

Norm Equality

If α and β has different norms then \approx_2^W distinguishes them.

Ability to perform an infinite sequence a^ω

Captured by \approx_1^W .

Distance to disable action a (and higher level DD-functions)

(Distance to) ^{i} disable a is captured by \approx_{i+1}^W .

Conclusion

- Hirshfeld's Conjecture ($\approx = \approx_{\omega+\omega}$) is false

Conclusion

- Hirschfeld's Conjecture ($\approx = \approx_{\omega+\omega}$) is false
- New proofs for decidability of subclasses

Conclusion

- Hirschfeld's Conjecture ($\approx = \approx_{\omega+\omega}$) is false
- New proofs for decidability of subclasses
- Lower bound of $\omega + \omega$ for convergence of "Word Approximants"

Conclusion

- Hirschfeld's Conjecture ($\approx = \approx_{\omega+\omega}$) is false
- New proofs for decidability of subclasses
- Lower bound of $\omega + \omega$ for convergence of "Word Approximants"
- Found a distinguishing property? Make sure it's not captured by \approx_{ω}^W !

Bibliography



Javier Esparza.

Petri nets, commutative context-free grammars, and basic parallel processes.

Fundam. Inform., 31(1):13–25, 1997.



Will Harwood, Faron Moller, and Anton Setzer.

Weak bisimulation approximants.

In *CSL*, pages 365–379, 2006.



Robin Milner.

Communication and concurrency.

PHI Series in computer science. Prentice Hall, 1989.



Colin Stirling.

Decidability of weak bisimilarity for a subset of basic parallel processes.

In *FoSSaCS*, pages 379–393, 2001.



Jitka Stríbrná.

Decidability and complexity of equivalences for simple process algebras.

PhD thesis, School of Informatics, University of Edinburgh, 1998.