

Hardness of Untimed Language Universality

Romain Brenguier Ocan Sankur
Thanks to Stefan Göller

LSV, CNRS & ENS Cachan, France
`{brenguier,sankur}@lsv.ens-cachan.fr`

YR-CONCUR
September 10, 2011

Timed Systems

- Context: Formal verification of systems running in real-time;

Timed Systems

- Context: Formal verification of systems running in real-time;
- Examples: mobile phone, plane, car, train, robot,...



Timed Systems



- Context: Formal verification of systems running in real-time;
- Examples: mobile phone, plane, car, train, robot,...



- Modeled by Timed Automata

Timed Automata (TA) [Alur and Dill 1994]



Finite automata + Analog clocks



- Clocks cannot be stopped, all grow at the same rate.
- An edge is activated when its **clock constraint** holds.
- A clock can be **reset** by a transition.

Timed Automata (TA) [Alur and Dill 1994]

Finite automata + Analog clocks





Runs of a timed automaton

$$\begin{aligned} &(\text{idle}, x = 0) \xrightarrow{23.7} (\text{idle}, x = 23.7) \xrightarrow{\text{click?}} (\ell_1, x = 0) \xrightarrow{10} (\ell_1, x = 10) \\ &\xrightarrow{\text{click?}} (\ell_2, x = 10) \xrightarrow{\text{double_click!}} (\text{idle}, x = 10) \dots \end{aligned}$$

Timed Automata (TA) [Alur and Dill 1994]

Finite automata + Analog clocks



The **untimed language** of a timed automaton

Sequences of **edge labels** along which there is a run.

For instance $(\text{click?} \cdot \text{single_click!})^* \subseteq L(\mathcal{A})$.

Known Results about TA

- Emptiness is **PSPACE**-complete; $L(\mathcal{A}) = \emptyset?$ $L^t(\mathcal{A}) = \emptyset?$
- Timed language universality is **undecidable**;
 $L^t(\mathcal{A}) = \Sigma^*?$ $L^t(\mathcal{A}) = L^t(\mathcal{B})?$ $L^t(\mathcal{A}) \subseteq L^t(\mathcal{B})?$

Known Results about TA

- Emptiness is **PSPACE**-complete; $L(\mathcal{A}) = \emptyset?$ $L^t(\mathcal{A}) = \emptyset?$

- Timed language universality is **undecidable**;
 $L^t(\mathcal{A}) = \Sigma^*?$ $L^t(\mathcal{A}) = L^t(\mathcal{B})?$ $L^t(\mathcal{A}) \subseteq L^t(\mathcal{B})?$

- Untimed language universality and inclusion are **PSPACE**-hard and in **EXSPACE**.

$$L(\mathcal{A}) = \Sigma^*? \quad L(\mathcal{A}) = L(\mathcal{B})? \quad L(\mathcal{A}) \subseteq L(\mathcal{B})?$$

Known Results about TA

- Emptiness is **PSPACE**-complete; $L(\mathcal{A}) = \emptyset?$ $L^t(\mathcal{A}) = \emptyset?$

- Timed language universality is **undecidable**;
 $L^t(\mathcal{A}) = \Sigma^*?$ $L^t(\mathcal{A}) = L^t(\mathcal{B})?$ $L^t(\mathcal{A}) \subseteq L^t(\mathcal{B})?$

- Untimed language universality and inclusion are **PSPACE**-hard and in **EXSPACE**.

$$L(\mathcal{A}) = \Sigma^*? \quad L(\mathcal{A}) = L(\mathcal{B})? \quad L(\mathcal{A}) \subseteq L(\mathcal{B})?$$


- ▶ What is the exact complexity of these problems?

The Region Abstraction

$a, x > 1, y \leftarrow 0$



$b, y \leq 2, x \leftarrow 0$




The Region Abstraction

$a, x > 1, y \leftarrow 0$



$b, y \leq 2, x \leftarrow 0$




- “Compatibility” between regions and **constraints**;

The Region Abstraction

$a, x > 1, y \leftarrow 0$



$b, y \leq 2, x \leftarrow 0$




- “Compatibility” between regions and **constraints**;
- “Compatibility” between regions and **resets**;

The Region Abstraction

$a, x > 1, y \leftarrow 0$



$b, y \leq 2, x \leftarrow 0$




- “Compatibility” between regions and **constraints**;
- “Compatibility” between regions and **resets**;
- “Compatibility” between regions and **time elapsing**;

The Region Abstraction

$a, x > 1, y \leftarrow 0$



$b, y \leq 2, x \leftarrow 0$



- “Compatibility” between regions and **constraints**;
- “Compatibility” between regions and **resets**;
- “Compatibility” between regions and **time elapsing**;


⇒ Bisimulation property.

The Region Abstraction

$a, x > 1, y \leftarrow 0$



$b, y \leq 2, x \leftarrow 0$



- “Compatibility” between regions and **constraints**;
- “Compatibility” between regions and **resets**;
- “Compatibility” between regions and **time elapsing**;

\Rightarrow Bisimulation property.

Main Result

Theorem

*Untimed language inclusion and universality problems for timed automata are **EXPSpace**-complete.*

Main Result

Theorem

*Untimed language inclusion and universality problems for timed automata are **EXSPACE**-complete.*

Algorithm

Given timed automata \mathcal{A} and \mathcal{B}

- construct the corresponding region automata, $R(\mathcal{A})$, $R(\mathcal{B})$;
- use a **PSPACE** algorithm to check language inclusion on the region automata, $R(\mathcal{A}) \subseteq R(\mathcal{B})$.

Encoding an Exponential Space Turing Machine

Given an exponential space Turing machine \mathcal{T} and an input x ,

Encoding an Exponential Space Turing Machine

Given an exponential space Turing machine \mathcal{T} and an input x ,

- Executions are encoded by some words;

Encoding an Exponential Space Turing Machine

Given an exponential space Turing machine \mathcal{T} and an input x ,

- Executions are encoded by some words;
- We construct an automaton that recognizes timed words that are:
 - ▶ either **not correct** executions of \mathcal{T} ,

Encoding an Exponential Space Turing Machine

Given an exponential space Turing machine \mathcal{T} and an input x ,

- Executions are encoded by some words;
- We construct an automaton that recognizes timed words that are:
 - ▶ either **not correct** executions of \mathcal{T} ,
 - ▶ or executions that do **not start** with the input x ,

Encoding an Exponential Space Turing Machine

Given an exponential space Turing machine \mathcal{T} and an input x ,

- Executions are encoded by some words;
- We construct an automaton that recognizes timed words that are:
 - ▶ either **not correct** executions of \mathcal{T} ,
 - ▶ or executions that do **not start** with the input x ,
 - ▶ or executions that are **not accepting**;


Encoding an Exponential Space Turing Machine

Given an exponential space Turing machine \mathcal{T} and an input x ,


- Executions are encoded by some words;
- We construct an automaton that recognizes timed words that are:
 - ▶ either **not correct** executions of \mathcal{T} ,
 - ▶ or executions that do **not start** with the input x ,
 - ▶ or executions that are **not accepting**;

⇒ The automaton is **universal** if and only if the input x is **not accepted** by the Turing machine.


A configuration



A configuration




A configuration



is encoded by the word


$w =$ ▷ 0 0 1 q 0 1 □ □ □



is encoded by the word $w =$ ▷ 0 0 1 q □ □ □

An execution is encoded by






is encoded by the word $w =$ ▷ 0 0 1 q 0 1 □ □ □

An execution is encoded by




The alphabet of the timed automaton is $\Gamma = \Sigma \cup Q \cup \{\$ \}$



Detecting Errors with an Automaton





Detecting Errors with an Automaton






Detecting Errors with an Automaton






Detecting Errors with a Timed Automaton






Detecting Errors with a Timed Automaton






Detecting Errors with a Timed Automaton






Detecting Errors with a Timed Automaton






Detecting Errors with a Timed Automaton






Detecting Errors with a Timed Automaton



Detecting Errors with a Timed Automaton




Detecting Errors with a Timed Automaton




$$L(D(a, m)) = (\Gamma \setminus \{q_{acc}\})^m \cdot (\Gamma \setminus \{a\}) \cdot \Gamma^*$$


Encoding an Instruction



Encoding an Instruction




Encoding an Instruction




$\dots a \ p \ b \ \dots \ \$ \ \dots \ c \ b \ q \ \dots$

$\leftarrow 2^n - 1 \rightarrow$



The Global Construction



Conclusion

- The algorithm is simple and uses the region abstraction ...

Conclusion

- The algorithm is simple and uses the region abstraction ...
- But the problem is hard.

Conclusion

- The algorithm is simple and uses the region abstraction ...
- But the problem is hard.

Thank you for your attention