

Towards regular separability of Petri net languages

L. Clemente, W. Czerwiński, S. Lasota (University of Warsaw)
Ch. Paperman (University of Bordeaux)

Reykjavík, June 2017

At a glance

Problem:	Regular separability.
Model:	Languages recognised by Petri nets and related formalisms.
Results:	Decidability for restricted subclasses. Open for Petri nets.

Main technical ideas


Our results on regular separability are based on the following techniques:

1. Deterministic = nondeterministic.
2. Reduce to separability of bounded languages.

The following problems are inter-reducible:


- Separability of bounded languages.
 - Separability of commutative languages.
 - Separability of sets of vectors.
3. Regular partitioning.

Regular separability in Iceland



Regular separability in Iceland

A = Heimaey



Regular separability in Iceland

A = Heimaey



B = lava from
the volcano
Eldfell
winter 1973

Regular separability in Iceland



A = Heimaey




R = Sea water

B = lava from
the volcano
Eldfell
winter 1973

Regular separability



Regular separability



Motivation

- Separability gives a certificate of disjointness.
 - Verifying that R is a separator is decidable*.
 - The separator yields a “simple reason” for disjointness.

*Under the assumption that the class of languages is closed under intersection with regular languages and has a decidable emptiness problem.

Motivation

- Separability gives a certificate of disjointness.
 - Verifying that R is a separator is decidable*.
 - The separator yields a “simple reason” for disjointness.
- Separability can be used to circumvent undecidability of disjointness:
 - Disjointness of two CFLs is undecidable.
 - Separability by piecewise-testable languages of CFLs is decidable [Czerwiński, Martens, van Rooijen, Zeitoun '15].

*Under the assumption that the class of languages is closed under intersection with regular languages and has a decidable emptiness problem.


Motivation

- Separability gives a certificate of disjointness.
 - Verifying that R is a separator is decidable*.
 - The separator yields a “simple reason” for disjointness.
- Separability can be used to circumvent undecidability of disjointness:
 - Disjointness of two CFLs is undecidable.
 - Separability by piecewise-testable languages of CFLs is decidable [Czerwiński, Martens, van Rooijen, Zeitoun '15].
- For classes closed under complement, regular separability generalises the *regularity problem*.

*Under the assumption that the class of languages is closed under intersection with regular languages and has a decidable emptiness problem.


Regularity

is A regular?




Regularity


is A regular?



=



Regularity vs. Separability



A is regular

iff

A is regular separable from its
complement

Regularity vs. Separability

- For classes closed under complement, regular separability generalises the *regularity problem*.

Regularity vs. Separability

- For classes closed under complement, regular separability generalises the *regularity problem*.
- For classes *not* closed under complement, the two problems behave rather differently:
 - Regularity is very sensitive to determinism (decidable) vs. nondeterminism (undecidable).
 - Separability is insensitive in this respect: it always reduces to the deterministic case.

Regularity w.r.t. nondeterminism

Deterministic

DCFL [Stearns '67]

Petri nets [Valk, Vidal-Niquet '81]

decidable

Regularity w.r.t. nondeterminism

Deterministic

DCFL [Stearns '67]
Petri nets [Valk, Vidal-Niquet '81]

decidable

Nondeterministic


1-counter nets (no zero test),
even reversal bounded

undecidable
(reduction from universality)


Separability w.r.t. nondeterminism

Separability is *insensitive* to nondeterminism:

It reduces to the deterministic case [C., Czerwiński, Lasota, Paperman ICALP'17].



$$p \xrightarrow{a} q$$




$$r \xrightarrow{a} s$$


Separability w.r.t. nondeterminism

Separability is *insensitive* to nondeterminism:

It reduces to the deterministic case [C., Czerwiński, Lasota, Paperman ICALP'17].



$$p \xrightarrow{a} q$$





$$r \xrightarrow{a} s$$

Separability w.r.t. nondeterminism

Separability is *insensitive* to nondeterminism:

It reduces to the deterministic case [C., Czerwiński, Lasota, Paperman ICALP'17].




$$p \xrightarrow{p \xrightarrow{a} q} q$$

$$r \xrightarrow{a} s$$


Separability w.r.t. nondeterminism

Separability is *insensitive* to nondeterminism:

It reduces to the deterministic case [C., Czerwiński, Lasota, Paperman ICALP'17].



$$p \xrightarrow{p \xrightarrow{a} q} q$$





$$r \xrightarrow{p \xrightarrow{a} q} s$$

Separability w.r.t. nondeterminism

Separability is *insensitive* to nondeterminism:

It reduces to the deterministic case [C., Czerwiński, Lasota, Paperman ICALP'17].







$$p \xrightarrow{a} q$$

$$r \xrightarrow{a} s$$

Separability w.r.t. nondeterminism

Separability is *insensitive* to nondeterminism:





It reduces to the deterministic case [C., Czerwiński, Lasota, Paperman ICALP'17].



Separability w.r.t. nondeterminism

Separability is *insensitive* to nondeterminism:





It reduces to the deterministic case [C., Czerwiński, Lasota, Paperman ICALP'17].



Separability w.r.t. nondeterminism

Separability is *insensitive* to nondeterminism:





It reduces to the deterministic case [C., Czerwiński, Lasota, Paperman ICALP'17].



Separability w.r.t. nondeterminism

Separability is *insensitive* to nondeterminism:

It reduces to the deterministic case [C., Czerwiński, Lasota, Paperman ICALP'17].



Separability w.r.t. nondeterminism

Separability is *insensitive* to nondeterminism:

It reduces to the deterministic case [C., Czerwiński, Lasota, Paperman ICALP'17].

Ingredients:


- A is the homomorphic image of a *deterministic* \hat{A} . (The same for B.)
- Separability is invariant w.r.t. inverse homomorphic images.
- Regular languages are closed under inverse homomorphic images.
- A, B belong to a class closed under inverse homomorphic images.

Undecidable separability

CFL

[Szymanski, Williams '76]

Undecidable separability



Undecidable separability

- CFLs are the homomorphic images of deterministic CFLs.
- CFLs are closed under inverse homomorphic images.


CFL
[Szymanski, Williams '76]

VPL
[Kopczyński LICS'16]



Undecidable separability

- CFLs are the homomorphic images of deterministic CFLs.
- CFLs are closed under inverse homomorphic images.



Undecidable separability

- CFLs are the homomorphic images of deterministic CFLs.

- CFLs are closed under inverse homomorphic images.

CFL
[Szymanski, Williams '76]


VPL
[Kopczyński LICS'16]

1CA
[Czerwiński, Lasota LICS'17]

- 1CAs are the homomorphic images of deterministic 1CAs.

- 1CAs are closed under inverse homomorphic images.

Deterministic 1CA
[C., Czerwiński, Lasota,
Paperman ICALP'17]



Decidable separability

1. 1CN [Czerwiński, Lasota LICS'17].

Via the *Regular Overapproximation* technique
→ Wojtek Czerwiński's talk on Tue 4A 2:05pm.

Decidable separability

1. 1CN [Czerwiński, Lasota LICS'17].

Via the *Regular Overapproximation* technique
→ Wojtek Czerwiński's talk on Tue 4A 2:05pm.

2. $\text{PN}(\mathbb{Z})$ [C., Czerwiński, Lasota, Paperman ICALP'17].

Decidable separability

1. 1CN [Czerwiński, Lasota LICS'17].

Via the *Regular Overapproximation* technique
→ Wojtek Czerwiński's talk on Tue 4A 2:05pm.

2. $\text{PN}(\mathbb{Z})$ [C., Czerwiński, Lasota, Paperman ICALP'17].
3. $\mathbb{C}(\text{PN})$: commutative closure of PN languages
[C., Czerwiński, Lasota, Paperman STACS'17].

Decidable separability

1. 1CN [Czerwiński, Lasota LICS'17].

Via the *Regular Overapproximation* technique
→ Wojtek Czerwiński's talk on Tue 4A 2:05pm.

2. $\text{PN}(\mathbb{Z})$ [C., Czerwiński, Lasota, Paperman ICALP'17].

3. $\mathbb{C}(\text{PN})$: commutative closure of PN languages
[C., Czerwiński, Lasota, Paperman STACS'17].

Reduction to the case of *bounded languages* $L \subseteq a^*b^*$.

Commutative ~ bounded ~ Parikh

The following problems are mutually inter-reducible:

1. Regular separability of *commutative* languages $\subseteq \{a, b\}^*$.
2. Regular separability of *bounded* languages $\subseteq a^*b^*$.
3. *Unary* separability of sets of vectors $\subseteq \mathbb{N}^2$.

Commutative ~ bounded ~ Parikh

The following problems are mutually inter-reducible:

1. Regular separability of *commutative* languages $\subseteq \{a, b\}^*$.
2. Regular separability of *bounded* languages $\subseteq a^*b^*$.
3. *Unary* separability of sets of vectors $\subseteq \mathbb{N}^2$.



What are unary sets?

Regular languages vs. Unary sets

Unary sets correspond to finite-memory counting separately in each coordinate.

- Let $i \in \mathbb{N}$. Vectors $u, v \in \mathbb{N}^d$ are *i-unary equivalent* $u \equiv_i v$ if $\forall 1 \leq k \leq d$,
 - Equivalent modulo i : $u[k] \equiv v[k] \pmod{i}$.
 - Either both big, or both small: $u[k] \geq i$ iff $v[k] \geq i$.
- A subset of \mathbb{N}^d is *unary* if it is the union of i -unary classes, for some $i \in \mathbb{N}$.

Regular languages vs. Unary sets

Unary sets correspond to finite-memory counting separately in each coordinate.

- Let $i \in \mathbb{N}$. Vectors $u, v \in \mathbb{N}^d$ are *i-unary equivalent* $u \equiv_i v$ if $\forall 1 \leq k \leq d$,
 - Equivalent modulo i : $u[k] \equiv v[k] \pmod i$.
 - Either both big, or both small: $u[k] \geq i$ iff $v[k] \geq i$.
- A subset of \mathbb{N}^d is *unary* if it is the union of i -unary classes, for some $i \in \mathbb{N}$.

Connections between unary sets and commutative/bounded regular languages:

- The Parikh image of a commutative regular language is unary.
- The Parikh image of a bounded regular language $\subseteq a^*b^*$ is unary.
- The inverse Parikh image of a unary set is a commutative regular language.


Unary sets correspond to commutative/bounded regular languages

Commutative ~ bounded ~ Parikh

The following problems are mutually inter-reducible:

1. Regular separability of *commutative* languages $\subseteq \{a, b\}^*$.
2. Regular separability of *bounded* languages $\subseteq a^*b^*$.
3. *Unary* separability of sets of vectors $\subseteq \mathbb{N}^2$.

1 \rightarrow 2:



Commutative ~ bounded ~ Parikh

The following problems are mutually inter-reducible:

1. Regular separability of *commutative* languages $\subseteq \{a, b\}^*$.
2. Regular separability of *bounded* languages $\subseteq a^*b^*$.
3. *Unary* separability of sets of vectors $\subseteq \mathbb{N}^2$.


1 \rightarrow 2:

Let A, B commutative.

Define:

$$A' = A \cap a^*b^*,$$

$$B' = B \cap a^*b^*.$$



Commutative ~ bounded ~ Parikh

The following problems are mutually inter-reducible:

1. Regular separability of *commutative* languages $\subseteq \{a, b\}^*$.
2. Regular separability of *bounded* languages $\subseteq a^*b^*$.
3. *Unary* separability of sets of vectors $\subseteq \mathbb{N}^2$.


1 \rightarrow 2:

Let A, B commutative.

Define:

$$A' = A \cap a^*b^*,$$

$$B' = B \cap a^*b^*.$$



Commutative ~ bounded ~ Parikh

The following problems are mutually inter-reducible:


1. Regular separability of *commutative* languages $\subseteq \{a, b\}^*$.
2. Regular separability of *bounded* languages $\subseteq a^*b^*$.
3. *Unary* separability of sets of vectors $\subseteq \mathbb{N}^2$.

1 \rightarrow 2:

Let A, B commutative.

$A' = A \cap a^*b^*$, $B' = B \cap a^*b^*$.

(\Rightarrow) If R separates A, B ,
then $R \cap a^*b^*$ separates A', B' .



Commutative ~ bounded ~ Parikh

The following problems are mutually inter-reducible:


1. Regular separability of *commutative* languages $\subseteq \{a, b\}^*$.
2. Regular separability of *bounded* languages $\subseteq a^*b^*$.
3. *Unary* separability of sets of vectors $\subseteq \mathbb{N}^2$.

1 \rightarrow 2:

Let A, B commutative.

$A' = A \cap a^*b^*$, $B' = B \cap a^*b^*$.

(\Leftarrow) Let R separate A', B' .



Commutative ~ bounded ~ Parikh


The following problems are mutually inter-reducible:

1. Regular separability of *commutative* languages $\subseteq \{a, b\}^*$.
2. Regular separability of *bounded* languages $\subseteq a^*b^*$.
3. *Unary* separability of sets of vectors $\subseteq \mathbb{N}^2$.

1 \rightarrow 2:

Let A, B commutative.

$A' = A \cap a^*b^*, B' = B \cap a^*b^*$.



(\Leftarrow) Let R separate A', B' .

Then the commutative closure of $R \cap a^*b^*$ separates A, B .

Hint: A equals the commutative closure of A' .

Commutative ~ bounded ~ Parikh

The following problems are mutually inter-reducible:

1. Regular separability of *commutative* languages $\subseteq \{a, b\}^*$.
2. Regular separability of *bounded* languages $\subseteq a^*b^*$.
3. *Unary* separability of sets of vectors $\subseteq \mathbb{N}^2$.

$1 \rightarrow 2$ ✓□.


Commutative ~ bounded ~ Parikh

The following problems are mutually inter-reducible:

1. Regular separability of *commutative* languages $\subseteq \{a, b\}^*$.
2. Regular separability of *bounded* languages $\subseteq a^*b^*$.
3. *Unary* separability of sets of vectors $\subseteq \mathbb{N}^2$.

1 \rightarrow 2 ✓□. 2 \rightarrow 3:

Let $A, B \subseteq a^*b^*$ bounded.



Commutative ~ bounded ~ Parikh



The following problems are mutually inter-reducible:

1. Regular separability of *commutative* languages $\subseteq \{a, b\}^*$.
2. Regular separability of *bounded* languages $\subseteq a^*b^*$.
3. *Unary* separability of sets of vectors $\subseteq \mathbb{N}^2$.

1 \rightarrow 2 ✓□. 2 \rightarrow 3:

Let $A, B \subseteq a^*b^*$ bounded.

Consider their Parikh images $\Pi(A), \Pi(B)$.



Commutative ~ bounded ~ Parikh

The following problems are mutually inter-reducible:


1. Regular separability of *commutative* languages $\subseteq \{a, b\}^*$.
2. Regular separability of *bounded* languages $\subseteq a^*b^*$.
3. *Unary* separability of sets of vectors $\subseteq \mathbb{N}^2$.

1 \rightarrow 2 ✓□. 2 \rightarrow 3:

Let $A, B \subseteq a^*b^*$ bounded.

Consider their Parikh images $\Pi(A), \Pi(B)$.

(\Rightarrow) If R separates A, B



Commutative ~ bounded ~ Parikh

The following problems are mutually inter-reducible:


1. Regular separability of *commutative* languages $\subseteq \{a, b\}^*$.
2. Regular separability of *bounded* languages $\subseteq a^*b^*$.
3. *Unary* separability of sets of vectors $\subseteq \mathbb{N}^2$.

$1 \rightarrow 2$ ✓□. $2 \rightarrow 3$:

Let $A, B \subseteq a^*b^*$ bounded.

Consider their Parikh images $\Pi(A), \Pi(B)$.

(\Rightarrow) If $R \subseteq a^*b^*$ separates A, B , then $\Pi(R)$ is unary and separates $\Pi(A), \Pi(B)$.



Commutative ~ bounded ~ Parikh

The following problems are mutually inter-reducible:


1. Regular separability of *commutative* languages $\subseteq \{a, b\}^*$.
2. Regular separability of *bounded* languages $\subseteq a^*b^*$.
3. *Unary* separability of sets of vectors $\subseteq \mathbb{N}^2$.

$1 \rightarrow 2$ ✓□. $2 \rightarrow 3$:

Let $A, B \subseteq a^*b^*$ bounded.

Consider their Parikh images $\Pi(A), \Pi(B)$.

(\Leftarrow) If U unary separates $\Pi(A), \Pi(B)$



Commutative ~ bounded ~ Parikh

The following problems are mutually inter-reducible:


1. Regular separability of *commutative* languages $\subseteq \{a, b\}^*$.
2. Regular separability of *bounded* languages $\subseteq a^*b^*$.
3. *Unary* separability of sets of vectors $\subseteq \mathbb{N}^2$.

$1 \rightarrow 2$ ✓□. $2 \rightarrow 3$:

Let $A, B \subseteq a^*b^*$ bounded.

Consider their Parikh images $\Pi(A), \Pi(B)$.

(\Leftarrow) If U unary separates $\Pi(A), \Pi(B)$,
then $\Pi^{-1}(U)$ is regular and separates A, B .



Commutative ~ bounded ~ Parikh

The following problems are mutually inter-reducible:

1. Regular separability of *commutative* languages $\subseteq \{a, b\}^*$.
2. Regular separability of *bounded* languages $\subseteq a^*b^*$.
3. *Unary* separability of sets of vectors $\subseteq \mathbb{N}^2$.

$1 \rightarrow 2$ ✓□. $2 \rightarrow 3$ ✓□.



Commutative ~ bounded ~ Parikh

The following problems are mutually inter-reducible:

1. Regular separability of *commutative* languages $\subseteq \{a, b\}^*$.
2. Regular separability of *bounded* languages $\subseteq a^*b^*$.
3. *Unary* separability of sets of vectors $\subseteq \mathbb{N}^2$.

$1 \rightarrow 2$ ✓□. $2 \rightarrow 3$ ✓□. $3 \rightarrow 1$:

Let $X, Y \subseteq \mathbb{N}^2$



Commutative ~ bounded ~ Parikh


The following problems are mutually inter-reducible:

1. Regular separability of *commutative* languages $\subseteq \{a, b\}^*$.
2. Regular separability of *bounded* languages $\subseteq a^*b^*$.
3. *Unary* separability of sets of vectors $\subseteq \mathbb{N}^2$.

$1 \rightarrow 2$ ✓□. $2 \rightarrow 3$ ✓□. $3 \rightarrow 1$:

Let $X, Y \subseteq \mathbb{N}^2$

Consider $\Pi^{-1}(X)$, $\Pi^{-1}(Y)$.



Commutative ~ bounded ~ Parikh

The following problems are mutually inter-reducible:


1. Regular separability of *commutative* languages $\subseteq \{a, b\}^*$.
2. Regular separability of *bounded* languages $\subseteq a^*b^*$.
3. *Unary* separability of sets of vectors $\subseteq \mathbb{N}^2$.

$1 \rightarrow 2$ ✓□. $2 \rightarrow 3$ ✓□. $3 \rightarrow 1$:

Let $X, Y \subseteq \mathbb{N}^2$

Consider $\Pi^{-1}(X), \Pi^{-1}(Y)$.

(\Rightarrow) If U unary separates X, Y



Commutative ~ bounded ~ Parikh

The following problems are mutually inter-reducible:


1. Regular separability of *commutative* languages $\subseteq \{a, b\}^*$.
2. Regular separability of *bounded* languages $\subseteq a^*b^*$.
3. *Unary* separability of sets of vectors $\subseteq \mathbb{N}^2$.

$1 \rightarrow 2$ ✓□. $2 \rightarrow 3$ ✓□. $3 \rightarrow 1$:

Let $X, Y \subseteq \mathbb{N}^2$


Consider $\Pi^{-1}(X), \Pi^{-1}(Y)$.

(\Rightarrow) If U unary separates X, Y ,
then $\Pi^{-1}(U)$ is regular
and separates $\Pi^{-1}(X), \Pi^{-1}(Y)$.




Commutative ~ bounded ~ Parikh

(\Leftarrow) Let R be a regular separator of $\Pi^{-1}(X)$, $\Pi^{-1}(Y)$.




Commutative ~ bounded ~ Parikh

(\Leftarrow) Let R be a regular separator of $\Pi^{-1}(X)$, $\Pi^{-1}(Y)$.
Then $\Pi(R)$ is unary and separates X , Y .



Commutative ~ bounded ~ Parikh

(\Leftarrow) Let R be a regular separator of $\Pi^{-1}(X)$, $\Pi^{-1}(Y)$.
Then $\Pi(R)$ ~~is unary~~ and separates X , Y .




Commutative ~ bounded ~ Parikh

(\Leftarrow) Let R be a regular separator of $\Pi^{-1}(X)$, $\Pi^{-1}(Y)$.

Then $\Pi(R)$ ~~is unary~~ and separates X , Y .

Let $\omega \in \mathbb{N}$ be the idempotent power of the syntactic monoid of R , i.e.,

(*) $x \cdot y^\omega \cdot z \in R$ iff $x \cdot y^{2\omega} \cdot z \in R$




Commutative ~ bounded ~ Parikh

(\Leftarrow) Let R be a regular separator of $\Pi^{-1}(X)$, $\Pi^{-1}(Y)$.

Then $\Pi(R)$ ~~is unary~~ and separates X , Y .

Let $\omega \in \mathbb{N}$ be the idempotent power of the syntactic monoid of R , i.e.,

$$(*) \quad x \cdot y^{\omega} \cdot z \in R \text{ iff } x \cdot y^{2\omega} \cdot z \in R$$



Then, $U := \{ u \in \mathbb{N}^d \mid \exists x \in X . u \equiv_{\omega} x \}$ is unary and separates X , Y .


Commutative ~ bounded ~ Parikh

(\Leftarrow) Let R be a regular separator of $\Pi^{-1}(X)$, $\Pi^{-1}(Y)$.

Then $\Pi(R)$ ~~is unary~~ and separates X , Y .

Let $\omega \in \mathbb{N}$ be the idempotent power of the syntactic monoid of R , i.e.,

$$(*) \quad x \cdot y^\omega \cdot z \in R \text{ iff } x \cdot y^{2\omega} \cdot z \in R$$



Then, $U := \{ u \in \mathbb{N}^d \mid \exists x \in X . u \equiv_\omega x \}$ is unary and separates X , Y .


Commutative ~ bounded ~ Parikh

(\Leftarrow) Let R be a regular separator of $\Pi^{-1}(X)$, $\Pi^{-1}(Y)$.

Then $\Pi(R)$ ~~is unary~~ and separates X , Y .

Let $\omega \in \mathbb{N}$ be the idempotent power of the syntactic monoid of R , i.e.,

(*) $x \cdot y^\omega \cdot z \in R$ iff $x \cdot y^{2\omega} \cdot z \in R$



Then, $U := \{ u \in \mathbb{N}^d \mid \exists x \in X . u \equiv_\omega x \}$ is unary and separates X , Y .


Commutative ~ bounded ~ Parikh

(\Leftarrow) Let R be a regular separator of $\Pi^{-1}(X)$, $\Pi^{-1}(Y)$.

Then $\Pi(R)$ ~~is unary~~ and separates X , Y .

Let $\omega \in \mathbb{N}$ be the idempotent power of the syntactic monoid of R , i.e.,

(*) $x \cdot y^\omega \cdot z \in R$ iff $x \cdot y^{2\omega} \cdot z \in R$



Then, $U := \{ u \in \mathbb{N}^d \mid \exists x \in X . u \equiv_\omega x \}$ is unary and separates X , Y .


Commutative ~ bounded ~ Parikh

(\Leftarrow) Let R be a regular separator of $\Pi^{-1}(X)$, $\Pi^{-1}(Y)$.

Then $\Pi(R)$ ~~is unary~~ and separates X , Y .

Let $\omega \in \mathbb{N}$ be the idempotent power of the syntactic monoid of R , i.e.,

(*) $x \cdot y^\omega \cdot z \in R$ iff $x \cdot y^{2\omega} \cdot z \in R$.



Then, $U := \{ u \in \mathbb{N}^d \mid \exists x \in X . u \equiv_\omega x \}$ is unary and separates X , Y .

- $X \subseteq U$ is obvious.


Commutative ~ bounded ~ Parikh

(\Leftarrow) Let R be a regular separator of $\Pi^{-1}(X)$, $\Pi^{-1}(Y)$.

Then $\Pi(R)$ ~~is unary~~ and separates X , Y .

Let $\omega \in \mathbb{N}$ be the idempotent power of the syntactic monoid of R , i.e.,

(*) $x \cdot y^\omega \cdot z \in R$ iff $x \cdot y^{2\omega} \cdot z \in R$



Then, $U := \{ u \in \mathbb{N}^d \mid \exists x \in X . u \equiv_\omega x \}$ is unary and separates X , Y .

- $X \subseteq U$ is obvious.
- U is disjoint with Y : If there was a vector y in U and in Y , then there would be a vector x in X s.t. $x \equiv_\omega y$.


Commutative ~ bounded ~ Parikh

(\Leftarrow) Let R be a regular separator of $\Pi^{-1}(X)$, $\Pi^{-1}(Y)$.

Then $\Pi(R)$ ~~is unary~~ and separates X , Y .

Let $\omega \in \mathbb{N}$ be the idempotent power of the syntactic monoid of R , i.e.,

(*) $x \cdot y^\omega \cdot z \in R$ iff $x \cdot y^{2\omega} \cdot z \in R$.



Then, $U := \{ u \in \mathbb{N}^d \mid \exists x \in X . u \equiv_\omega x \}$ is unary and separates X , Y .

- $X \subseteq U$ is obvious.
- U is disjoint with Y : If there was a vector y in U and in Y , then there would be a vector x in X s.t. $x \equiv_\omega y$.


Commutative ~ bounded ~ Parikh

(\Leftarrow) Let R be a regular separator of $\Pi^{-1}(X)$, $\Pi^{-1}(Y)$.

Then $\Pi(R)$ ~~is unary~~ and separates X , Y .

Let $\omega \in \mathbb{N}$ be the idempotent power of the syntactic monoid of R , i.e.,

$$(*) \quad x \cdot y^{\omega} \cdot z \in R \text{ iff } x \cdot y^{2\omega} \cdot z \in R$$



Then, $U := \{ u \in \mathbb{N}^d \mid \exists x \in X . u \equiv_{\omega} x \}$ is unary and separates X , Y .

- $X \subseteq U$ is obvious.
- U is disjoint with Y : If there was a vector y in U and in Y , then there would be a vector x in X s.t. $x \equiv_{\omega} y$. Consider the words

$$\alpha = a^x[0] b^x[1] \in \Pi^{-1}(X) \quad \text{and} \quad \beta = a^y[0] b^y[1] \in \Pi^{-1}(Y).$$


Commutative ~ bounded ~ Parikh

(\Leftarrow) Let R be a regular separator of $\Pi^{-1}(X)$, $\Pi^{-1}(Y)$.

Then $\Pi(R)$ ~~is unary~~ and separates X , Y .

Let $\omega \in \mathbb{N}$ be the idempotent power of the syntactic monoid of R , i.e.,

$$(*) \quad x \cdot y^{\omega} \cdot z \in R \text{ iff } x \cdot y^{2\omega} \cdot z \in R$$



Then, $U := \{ u \in \mathbb{N}^d \mid \exists x \in X . u \equiv_{\omega} x \}$ is unary and separates X , Y .

- $X \subseteq U$ is obvious.
- U is disjoint with Y : If there was a vector y in U and in Y , then there would be a vector x in X s.t. $x \equiv_{\omega} y$. Consider the words

$$\alpha = a^x[0] b^x[1] \in \Pi^{-1}(X) \quad \text{and} \quad \beta = a^y[0] b^y[1] \in \Pi^{-1}(Y).$$

By $(*)$, $\alpha \in R$ iff $\beta \in R$.


Commutative ~ bounded ~ Parikh

(\Leftarrow) Let R be a regular separator of $\Pi^{-1}(X)$, $\Pi^{-1}(Y)$.

Then $\Pi(R)$ ~~is unary~~ and separates X , Y .

Let $\omega \in \mathbb{N}$ be the idempotent power of the syntactic monoid of R , i.e.,

$$(*) \quad x \cdot y^{\omega} \cdot z \in R \text{ iff } x \cdot y^{2\omega} \cdot z \in R$$



Then, $U := \{ u \in \mathbb{N}^d \mid \exists x \in X . u \equiv_{\omega} x \}$ is unary and separates X , Y .

- $X \subseteq U$ is obvious.
- U is disjoint with Y : If there was a vector y in U and in Y , then there would be a vector x in X s.t. $x \equiv_{\omega} y$. Consider the words

$$\alpha = a^x[0] b^x[1] \in \Pi^{-1}(X) \quad \text{and} \quad \beta = a^y[0] b^y[1] \in \Pi^{-1}(Y).$$

By (*), $\alpha \in R$ iff $\beta \in R$. Since $\alpha \in R$, we get $\beta \in R$. Contradiction!


Commutative ~ bounded ~ Parikh

(\Leftarrow) Let R be a regular separator of $\Pi^{-1}(X)$, $\Pi^{-1}(Y)$.

Then $\Pi(R)$ ~~is unary~~ and separates X , Y .

Let $\omega \in \mathbb{N}$ be the idempotent power of the syntactic monoid of R , i.e.,

$$(*) \quad x \cdot y^\omega \cdot z \in R \text{ iff } x \cdot y^{2\omega} \cdot z \in R$$



Then, $U := \{ u \in \mathbb{N}^d \mid \exists x \in X . u \equiv_\omega x \}$ is unary and separates X , Y .

- $X \subseteq U$ is obvious.
- U is disjoint with Y : If there was a vector y in U and in Y , then there would be a vector x in X s.t. $x \equiv_\omega y$. Consider the words

$$\alpha = a^x[0] b^x[1] \in \Pi^{-1}(X) \quad \text{and} \quad \beta = a^y[0] b^y[1] \in \Pi^{-1}(Y).$$

By (*), $\alpha \in R$ iff $\beta \in R$. Since $\alpha \in R$, we get $\beta \in R$. Contradiction!

Commutative ~ bounded ~ Parikh

The following problems are mutually inter-reducible:

1. Regular separability of *commutative* languages $\subseteq \{a, b\}^*$.
2. Regular separability of *bounded* languages $\subseteq a^*b^*$.
3. *Unary* separability of sets of vectors $\subseteq \mathbb{N}^2$.

$1 \rightarrow 2$ ✓□. $2 \rightarrow 3$ ✓□. $3 \rightarrow 1$ ✓□.

Decidable separability

1. $1CN$ [Czerwiński, Lasota LICS'17].

Via the *Regular Overapproximation* technique
→ Wojtek Czerwiński's talk on Tue 4A 2:05pm.

2. $\mathbb{C}(PN)$: commutative closure of PN languages
[C., Czerwiński, Lasota, Paperman STACS'17].


3. $PN(\mathbb{Z})$ [C., Czerwiński, Lasota, Paperman ICALP'17].

Regular separability of $\mathbb{C}(\text{PN})$

Let $A, B \subseteq \Sigma^*$ be PN languages (acceptance by final configuration).

By the previous reduction:

regular separability of the
commutative closures \mathbb{C}
 $(A), \mathbb{C}(B) \subseteq \Sigma^*$

reduces to 


unary separability of
the Parikh images Π
 $(A), \Pi(B) \subseteq \mathbb{N}^d$

Regular separability of $\mathbb{C}(\text{PN})$

Let $A, B \subseteq \Sigma^*$ be PN languages (acceptance by final configuration).

By the previous reduction:

regular separability of the
commutative closures \mathbb{C}
 $(A), \mathbb{C}(B) \subseteq \Sigma^*$

reduces to 

unary separability of
the Parikh images Π
 $(A), \Pi(B) \subseteq \mathbb{N}^d$

(projections of) *PN reachability sets*

- Add d extra components.
- Increment i -th extra component when reading a_i .
- Project away the other components.

Regular separability of $\mathbb{C}(\text{PN})$

Let $A, B \subseteq \Sigma^*$ be PN languages (acceptance by final configuration).

By the previous reduction:

regular separability of the
commutative closures \mathbb{C}
 $(A), \mathbb{C}(B) \subseteq \Sigma^*$

reduces to

unary separability of
the Parikh images Π
 $(A), \Pi(B) \subseteq \mathbb{N}^d$

(projections of) *PN reachability sets*


reduces to

unary separability of
PN reachability sets

- Add d extra components.
- Increment i -th extra component when reading a_i .
- Project away the other components.

Unary separability of PN reach. sets

Positive separability witness: Unary separator.





Unary separability of PN reach. sets

Positive separability witness: Unary separator.

Negative separability witness:

Non-separable *linear* subsets $X \subseteq A$, $Y \subseteq B$.





(Linear set: $b + P^*$, for a base b and a finite set of periods P .)

Unary separability of PN reach. sets

Positive separability witness: Unary separator.

Negative separability witness:

Non-separable *linear* subsets $X \subseteq A$, $Y \subseteq B$.



(Linear set: $b + P^*$, for a base b and a finite set of periods P .)



Unary separability of PN reach. sets

Positive separability witness: Unary separator.

Negative separability witness:

Non-separable *linear* subsets $X \subseteq A$, $Y \subseteq B$.

- Checking unary separability of linear sets is decidable [Choffrut, Grigorieff IPL'06].
- Checking inclusion of a linear set into a PN reachability set is decidable [Leroux LICS'13].



(Linear set: $b + P^*$, for a base b and a finite set of periods P .)



Unary separability of PN reach. sets

Characterisation:

Two sets $A, B \subseteq \mathbb{N}^d$ are *not* unary separable iff
there exists an infinite sequence of pairs (u_i, v_i) s.t. $u \equiv_i v$.

Negative separability witness:

Non-separable *linear* subsets $X \subseteq A, Y \subseteq B$.



(Linear set: $b + P^*$, for a base b and a finite set of periods P .)

Unary separability of PN reach. sets



Characterisation:

Two sets $A, B \subseteq \mathbb{N}^d$ are *not* unary separable iff there exists an infinite sequence of pairs (u_i, v_i) s.t. $u \equiv_i v$.

Negative separability witness:

Non-separable *linear* subsets $X \subseteq A, Y \subseteq B$.

- X is obtained by “folding” the infinite sequence u_i into a linear set.
- Tool: wqo on PN runs to extract base + finitely many periods.



(Linear set: $b + P^*$, for a base b and a finite set of periods P .)

Decidable separability

Theorem. Unary separability of PN reachability sets is decidable [C., Czerwiński, Lasota, Paperman STACS'17].

Decidable separability

Theorem. Unary separability of PN reachability sets is decidable
[C., Czerwiński, Lasota, Paperman STACS'17].

Theorem. Regular separability of commutative closures of PN languages is decidable
[C., Czerwiński, Lasota, Paperman STACS'17].

Theorem. Commutative regular separability of PN languages is decidable
[C., Czerwiński, Lasota, Paperman STACS'17].

Decidable separability

1. 1CN [Czerwiński, Lasota LICS'17].

Via the *Regular Overapproximation* technique
→ Wojtek Czerwiński's talk on Tue 4A 2:05pm.

2. $\mathbb{C}(\text{PN})$: commutative closure of PN languages
[C., Czerwiński, Lasota, Paperman STACS'17]. ✓□

3. $\text{PN}(\mathbb{Z})$ [C., Czerwiński, Lasota, Paperman ICALP'17].

Regular separability of $\text{PN}(\mathbb{Z})$

Regular separability of ~~PN(\mathbb{Z})~~

Regular separability of Parikh autom.

Regular separability of Parikh autom.

Parikh automaton (PA) [Klaedke, Rueß ICALP'03]:

NFA $A = (\Sigma, Q, I, F, \Delta)$ + semilinear acceptance condition $S \subseteq \mathbb{N}^{|\Delta|}$ on transitions.

- $L(A, S) = \pi(\text{Runs}(A) \cap \Pi^{-1}(S))$. (π returns the word labelling a run.)

Regular separability of Parikh autom.

Parikh automaton (PA) [Klaedke, Rueß ICALP'03]:

NFA $A = (\Sigma, Q, I, F, \Delta)$ + semilinear acceptance condition $S \subseteq \mathbb{N}^{|\Delta|}$ on transitions.

- $L(A, S) = \pi(\text{Runs}(A) \cap \Pi^{-1}(S))$. (π returns the word labelling a run.)

Since *separability is insensitive to nondeterminism*, we can assume DFA.

- $L(A, S) = \text{Runs}(A) \cap \Pi^{-1}(S) = \text{Regular} \cap \text{Commutative}$.

Regular separability of Parikh autom.

Parikh automaton (PA) [Klaedke, Rueß ICALP'03]:

NFA $A = (\Sigma, Q, I, F, \Delta)$ + semilinear acceptance condition $S \subseteq \mathbb{N}^{|\Delta|}$ on transitions.

- $L(A, S) = \pi(\text{Runs}(A) \cap \Pi^{-1}(S))$. (π returns the word labelling a run.)

Since *separability is insensitive to nondeterminism*, we can assume DFA.

- $L(A, S) = \text{Runs}(A) \cap \Pi^{-1}(S) = \text{Regular} \cap \text{Commutative}$.

Critical difference w.r.t. regularity:

- Regularity is undecidable for PA.
- Regularity is decidable for deterministic PA [Cadilhac, Finkel, McKenzie DLT'12].

Regular separability of Parikh autom.

Parikh automaton (PA) [Klaedke, Rueß ICALP'03]:

NFA $A = (\Sigma, Q, I, F, \Delta)$ + semilinear acceptance condition $S \subseteq \mathbb{N}^{| \Delta |}$ on transitions.

- $L(A, S) = \pi(\text{Runs}(A) \cap \Pi^{-1}(S))$. (π returns the word labelling a run.)

Since *separability is insensitive to nondeterminism*, we can assume DFA.


- $L(A, S) = \text{Runs}(A) \cap \Pi^{-1}(S) = \text{Regular} \cap \text{Commutative}$.

Critical difference w.r.t. regularity:


- Regularity is undecidable for PA.
- Regularity is decidable for deterministic PA [Cadilhac, Finkel, McKenzie DLT'12].

Theorem. Regular separability is decidable for PA/PN(\mathbb{Z}).


Regular partitioning




Regular partitioning




Regular partitioning




Regular partitioning



Regular partitioning




Regular partitioning




A, B separable iff, for every i , $A \cap R_i$, $B \cap R_i$ separable


Regular partitioning




Regular partitioning




Regular partitioning



Regular partitioning



Regular partitioning



We can assume the *same underlying DFA* for the two PAs.

Regular separability of Parikh autom.

Basic idea: Count simple cycles instead of transitions.

- Once enough states have been visited, cycles can be rearranged in fixed order.
- This gives a bounded language of cycles.

Regular separability of Parikh autom.

Basic idea: Count simple cycles instead of transitions.


- Once enough states have been visited, cycles can be rearranged in fixed order.
- This gives a bounded language of cycles.

regular separability
of PA languages $\xrightarrow{\text{reduces to}}$ regular separability of
bounded PA languages


Regular separability of Parikh autom.

Basic idea: Count simple cycles instead of transitions.

- Once enough states have been visited, cycles can be rearranged in fixed order.
- This gives a bounded language of cycles.



Counting cycles - Example



IDEA

Read a run from left to right
removing simple cycles
visiting only states which appeared so far.


Run: $p \rightarrow q \rightarrow r \rightarrow s \rightarrow r \rightarrow q \rightarrow r \rightarrow s \rightarrow r \rightarrow t$

Skeleton run: ε

Cycles count: $\#[q \rightarrow r \rightarrow q] = 0$

$\#[r \rightarrow s \rightarrow r] = 0$

Counting cycles - Example



IDEA

Read a run from left to right
removing simple cycles
visiting only states which appeared so far.


Run: $\underline{p} \rightarrow q \rightarrow r \rightarrow s \rightarrow r \rightarrow q \rightarrow r \rightarrow s \rightarrow r \rightarrow t$

Skeleton run: p

Cycles count: $\#[q \rightarrow r \rightarrow q] = 0$

$\#[r \rightarrow s \rightarrow r] = 0$

Counting cycles - Example



IDEA

Read a run from left to right
removing simple cycles
visiting only states which appeared so far.


Run: p→q→r→s→r→q→r→s→r→t

Skeleton run: p→q

Cycles count: $\#[q \rightarrow r \rightarrow q] = 0$

$\#[r \rightarrow s \rightarrow r] = 0$

Counting cycles - Example



IDEA

Read a run from left to right
removing simple cycles
visiting only states which appeared so far.


Run: p→q→r→s→r→q→r→s→r→t

Skeleton run: p→q→r

Cycles count: $\#[q \rightarrow r \rightarrow q] = 0$

$\#[r \rightarrow s \rightarrow r] = 0$

Counting cycles - Example



IDEA

Read a run from left to right
removing simple cycles
visiting only states which appeared so far.


Run: p→q→r→s→r→q→r→s→r→t

Skeleton run: p→q→r→s→r

Cycles count: $\#[q \rightarrow r \rightarrow q] = 0$

$\#[r \rightarrow s \rightarrow r] = 0$

Counting cycles - Example



IDEA

Read a run from left to right
removing simple cycles
visiting only states which appeared so far.


Run: p→q→r→s→r→q→r→s→r→t

Skeleton run: p→q→r→s→r (cannot remove since it changes the support)

Cycles count: $\#[q \rightarrow r \rightarrow q] = 0$

$\#[r \rightarrow s \rightarrow r] = 0$

Counting cycles - Example



IDEA

Read a run from left to right
removing simple cycles
visiting only states which appeared so far.


Run: p→q→r→s→r→q→r→s→r→t

Skeleton run: p→q→r→s→r→q

Cycles count: $\#[q \rightarrow r \rightarrow q] = 0$

$\#[r \rightarrow s \rightarrow r] = 0$

Counting cycles - Example



IDEA

Read a run from left to right
removing simple cycles
visiting only states which appeared so far.


Run: p→q→r→s→r→q→r→s→r→t

Skeleton run: p→q→r→s→r→q (cannot remove since it changes the support)

Cycles count: $\#[q \rightarrow r \rightarrow q] = 0$

$\#[r \rightarrow s \rightarrow r] = 0$

Counting cycles - Example



IDEA

Read a run from left to right
removing simple cycles
visiting only states which appeared so far.


Run: p→q→r→s→r→q→r→s→r→t

Skeleton run: p→q→r→s→r→q→r

Cycles count: $\#[q \rightarrow r \rightarrow q] = 0$

$\#[r \rightarrow s \rightarrow r] = 0$

Counting cycles - Example



IDEA

Read a run from left to right
removing simple cycles
visiting only states which appeared so far.


Run: p→q→r→s→r→q→r→s→r→t

Skeleton run: p→q→r→s→r→q→r

Cycles count: $\#[q \rightarrow r \rightarrow q] = 0$

$\#[r \rightarrow s \rightarrow r] = 0$

Counting cycles - Example



IDEA

Read a run from left to right
removing simple cycles
visiting only states which appeared so far.


Run: p→q→r→s→r→q→r→s→r→t

Skeleton run: p→q→r→s→r

Cycles count: $\#[q \rightarrow r \rightarrow q] = 1$

$\#[r \rightarrow s \rightarrow r] = 0$

Counting cycles - Example



IDEA

Read a run from left to right
removing simple cycles
visiting only states which appeared so far.


Run: p→q→r→s→r→q→r→s→r→t

Skeleton run: p→q→r→s→r→s

Cycles count: $\#[q \rightarrow r \rightarrow q] = 1$

$\#[r \rightarrow s \rightarrow r] = 0$

Counting cycles - Example



IDEA

Read a run from left to right
removing simple cycles
visiting only states which appeared so far.


Run: $p \rightarrow q \rightarrow r \rightarrow s \rightarrow r \rightarrow q \rightarrow r \rightarrow s \rightarrow r$ $\rightarrow t$

Skeleton run: $p \rightarrow q \rightarrow r \rightarrow s \rightarrow r \rightarrow s \rightarrow r$

Cycles count: $\#[q \rightarrow r \rightarrow q] = 1$

$\#[r \rightarrow s \rightarrow r] = 0$

Counting cycles - Example



IDEA

Read a run from left to right
removing simple cycles
visiting only states which appeared so far.


Run: p → q → r → s → r → q → r → s → r → t

Skeleton run: p → q → r → s → r → s → r

Cycles count: $\#[q \rightarrow r \rightarrow q] = 1$

$\#[r \rightarrow s \rightarrow r] = 0$

Counting cycles - Example



IDEA

Read a run from left to right
removing simple cycles
visiting only states which appeared so far.


Run: $p \rightarrow q \rightarrow r \rightarrow s \rightarrow r \rightarrow q \rightarrow r \rightarrow s \rightarrow r$ $\rightarrow t$

Skeleton run: $p \rightarrow q \rightarrow r \rightarrow s \rightarrow r$

Cycles count: $\#[q \rightarrow r \rightarrow q] = 1$

$\#[r \rightarrow s \rightarrow r] = 1$

Counting cycles - Example



IDEA

Read a run from left to right
removing simple cycles
visiting only states which appeared so far.


Run: $p \rightarrow q \rightarrow r \rightarrow s \rightarrow r \rightarrow q \rightarrow r \rightarrow s \rightarrow r \rightarrow t$

Skeleton run: $p \rightarrow q \rightarrow r \rightarrow s \rightarrow r \rightarrow t$

Cycles count: $\#[q \rightarrow r \rightarrow q] = 1$

$\#[r \rightarrow s \rightarrow r] = 1$

Counting cycles - Example



$$\alpha(\rho) := (\rho_0, (i, j))$$

Canonical run (cycles appear in a fixed order):

$$p \rightarrow q (\rightarrow r \rightarrow q)^i \rightarrow r \rightarrow s \rightarrow r (\rightarrow s \rightarrow r)^j \rightarrow t$$



Run: $p \rightarrow q \rightarrow r \rightarrow s \rightarrow r \rightarrow q \rightarrow r \rightarrow s \rightarrow r \rightarrow \dots \rightarrow t =: \rho$

Skeleton run: $p \rightarrow q \rightarrow r \rightarrow s \rightarrow r \rightarrow t =: \rho_0$

Cycles count: $\#[q \rightarrow r \rightarrow q] = i$


$$\#[r \rightarrow s \rightarrow r] = j$$

Regular partitioning




Three skeleton runs ρ_0 , ρ_1 , ρ_2 .

Regular partitioning




Three skeleton runs ρ_0, ρ_1, ρ_2 .

Regular partitioning




Three skeleton runs ρ_0, ρ_1, ρ_2 .

Regular partitioning



Three skeleton runs ρ_0, ρ_1, ρ_2 .


Regular partitioning



Fix a skeleton run ρ_0 . Restrict to canonical runs $C := p \rightarrow c_0^* \rightarrow r \rightarrow s \rightarrow c_1^* \rightarrow t$.

$A, B \subseteq \Sigma^*$ are regular separable iff $A \cap C, B \cap C \subseteq \Sigma^*$ are regular separable

Regular partitioning



Fix a skeleton run ρ_0 . Restrict to canonical runs $C := p \rightarrow c_0^* \rightarrow r \rightarrow s \rightarrow c_1^* \rightarrow t$.

$A, B \subseteq \Sigma^*$ are regular separable iff $A \cap C, B \cap C \subseteq \Sigma^*$ are regular separable

→ **Reduction to regular separability of *bounded* PA languages.**

(→ Unary separability of semilinear sets.)

Decidable separability

1. 1CN [Czerwiński, Lasota LICS'17].

Via the *Regular Overapproximation* technique
→ Wojtek Czerwiński's talk on Tue 4A 2:05pm.

2. $\mathbb{C}(\text{PN})$: commutative closure of PN languages
[C., Czerwiński, Lasota, Paperman STACS'17]. ✓□

3. PA/PN(\mathbb{Z}) [C., Czerwiński, Lasota, Paperman ICALP'17]. ✓□

Decidable separability

1. 1CN [Czerwiński, Lasota LICS'17].

Via the *Regular Overapproximation* technique
→ Wojtek Czerwiński's talk on Tue 4A 2:05pm.

2. $\mathbb{C}(\text{PN})$: commutative closure of PN languages
[C., Czerwiński, Lasota, Paperman STACS'17]. ✓□

3. $\text{PA/PN}(\mathbb{Z})$ [C., Czerwiński, Lasota, Paperman ICALP'17]. ✓□

4. [Conjecture] Separability of PN languages is decidable.

Towards separability of Petri nets

Possible techniques:

- Regular over-approximations of Petri net languages?
- Reduction to bounded Petri net languages?


Towards separability of Petri nets

Possible techniques:

- Regular over-approximations of Petri net languages?
- Reduction to bounded Petri net languages?

Other interesting directions

- Promise problems:
 - Given two CFGs for L and its complement, decide whether L is regular.
 - Cf. undecidability of regularity for CFLs.



DISCARDED SLIDES

Undecidable separability for 1CA

Technique: (polynomial) reduction from *every* decidable problem.

- Decidable problem (up to computable encoding):
 $L \subseteq \mathbb{N}$ recognised by deterministic, total 2CA (2 counters with zero test).
- If regular separability has time complexity $f(n)$,
then every decidable problem has time complexity $f(p(n))$.
- This contradicts the time hierarchy theorem.

Reduction: From a 2CA and input k build two 1CA A, B s.t.

2CA accepts k iff A, B are regular separable.

- Each 1CA simulates 1 counter.
- If 2CA rejects, let n be the length of the rejecting computation.
- We can separate A, B by looking only at prefixes of length n :

$$L(A) \cap \Sigma(<n) \cup \{ xy \mid x \in \text{Prefix}(L(A), n), y \in \Sigma^* \}$$

Separability for $\mathbb{C}(\text{PN})$

By reduction to (1) *unary separability* in \mathbb{N}^d of *reachability sets* of PNs

$\mathbb{C}(A), \mathbb{C}(B) \subseteq \Sigma^*$ are separable by a regular language

(2) iff

$\mathbb{C}(A), \mathbb{C}(B) \subseteq \Sigma^*$ are separable by a *commutative* regular language

(3) iff

$\Pi(A), \Pi(B) \subseteq \mathbb{N}^d$ are separable by a *unary set* \rightarrow union of *i*-unary equivalence classes

Vectors $u, v \in \mathbb{N}^d$ are *i-unary equivalent* $u \equiv_i v$ if $\forall 1 \leq k \leq d,$

- Equivalent modulo n : $u[k] \equiv v[k] \pmod i$.
- Either both big, or both small: $u[k] \geq i$ iff $v[k] \geq i$.


For two words $u, v \in \Sigma^*$, let $u \equiv_i v$ if $\Pi(u) \equiv_i \Pi(v)$.

Separability for $\mathbb{C}(\text{PN})$ - Step (2)

Let $\omega \in \mathbb{N}$ be the idempotent power of the syntactic monoid of R , i.e.,

$$(*) \quad \forall x, y, z \in \Sigma^* . x \cdot y^{\omega} \cdot z \in R \text{ iff } x \cdot y^{2\omega} \cdot z \in R$$

- $S := \{ u \in \Sigma^* \mid \exists v \in \mathbb{C}(A) . u \equiv_{\omega} v \}$ separates $\mathbb{C}(A)$, $\mathbb{C}(B)$:




Separability for $\mathbb{C}(\text{PN})$ - Step (2)

Let $\omega \in \mathbb{N}$ be the idempotent power of the syntactic monoid of R , i.e.,

$$(*) \quad \forall x, y, z \in \Sigma^* . x \cdot y^\omega \cdot z \in R \text{ iff } x \cdot y^{2\omega} \cdot z \in R$$



- $S := \{ u \in \Sigma^* \mid \exists v \in \mathbb{C}(A) . u \equiv_\omega v \}$ separates $\mathbb{C}(A)$, $\mathbb{C}(B)$.
- S is commutative regular since $\Pi(S)$ is ω -unary.



Separability for $\mathbb{C}(\text{PN})$ - Step (3)

$\mathbb{C}(A), \mathbb{C}(B) \subseteq \Sigma^*$ are separable by a *commutative* regular language S
(3) iff



$\Pi(A), \Pi(B) \subseteq \mathbb{N}^d$ are separable by a *unary set* $U = \Pi(S)$



Separability for $\mathbb{C}(\text{PN})$ - Step (3)

$\mathbb{C}(A), \mathbb{C}(B) \subseteq \Sigma^*$ are separable by a *commutative* regular language S
(3) iff

$\Pi(A), \Pi(B) \subseteq \mathbb{N}^d$ are separable by a *unary set* $U = \Pi(S)$



Separability for $\mathbb{C}(\text{PN})$ - Step (1)

$\mathbb{C}(A), \mathbb{C}(B) \subseteq \Sigma^*$ are separable by a *commutative* regular language S
(3) iff

$\Pi(A), \Pi(B) \subseteq \mathbb{N}^d$ are separable by a *unary set* $U = \Pi(S)$



(projections of) PN reachability sets

- Add d extra components.
- Increment i -th extra component when reading a_i .
- Project away the other components.

(1) Reduction to *unary separability* in \mathbb{N}^d of *projections of PN reachability sets*

Regular separability of Parikh autom.

NFA with transitions labelled by vectors in \mathbb{Z}^d .

Acceptance by reaching a final state with value $0 \in \mathbb{Z}^d$.

Since *separability is insensitive to nondeterminism*, we can assume DFA.

A deterministic $\text{PN}(\mathbb{Z})$ language is the intersection of:

- A regular language (the one recognised by the underlying DFA),
- The inverse Parikh image of a semilinear set.

Critical difference w.r.t. regularity:

- Regularity is undecidable for $\text{PN}(\mathbb{Z})$.
- Regularity is decidable for deterministic $\text{PN}(\mathbb{Z})$
[Cadilhac, Finkel, McKenzie DLT'12].

Theorem. Regular separability is decidable for $\text{PN}(\mathbb{Z})$.

Counting cycles

- Simple cycle: sequence transitions starting and ending in the same state, where no other state repeats.
- Two cycles are *equivalent* if one is a cyclic permutation of the other.
- Fix an enumeration of equivalence classes of simple cycles $[c_1], \dots, [c_d]$.
- In order to freely reorder simple cycles, adding or removing a cycle must not change the set of visited states \rightarrow need to visit enough states before cycles can be reordered independently.

IDEA

Read a run from left to right
removing simple cycles visiting only states which appeared so far.