

EQUIPMENT TECHNICAL SPECIFICATION SHEET

2025 Caterpillar 330 GC Hydraulic Excavator

GENERAL INFORMATION

Manufacturer	Caterpillar Inc.
Model	330 GC
Year	2025
Serial Number	CAT0330GC2NR01847
Configuration	Standard Boom — 10' 10" Stick
Condition	New — 0 Hours

ENGINE

Specification	Value
Engine Model	Cat C7.1 ACERT
Gross Power	268 hp (200 kW) @ 1,800 rpm
Net Power	252 hp (188 kW) @ 1,800 rpm
Displacement	7.01 L (427.8 cu in)
Aspiration	Turbocharged, Aftercooled
Emissions	EPA Tier 4 Final / EU Stage V
Fuel Tank Capacity	145 gal (549 L)
DEF Tank Capacity	13.5 gal (51 L)

HYDRAULIC SYSTEM

Specification	Value
Main Pump Flow	2 x 71.3 gpm (2 x 270 L/min)
Maximum Pressure	5,076 psi (350 bar)
Hydraulic System Type	Load-sensing, electronically controlled
Auxiliary Circuit	High-flow capable — 79.2 gpm (300 L/min)

DIMENSIONS & WEIGHTS

Dimension	Measurement
Operating Weight	73,600 lb (33,385 kg)
Max Dig Depth	23' 10" (7.26 m)
Max Reach at Ground	35' 5" (10.8 m)
Max Dump Height	23' 5" (7.13 m)

Dimension	Measurement
Tail Swing Radius	11' 0" (3.35 m)
Track Gauge	8' 6" (2.59 m)
Overall Width — Tracks	10' 10" (3.30 m)
Transport Height	10' 9" (3.28 m)
Transport Length	34' 9" (10.60 m)
Ground Pressure	8.0 psi (55 kPa)

STANDARD FEATURES

Cat GRADE with 2D system, Product Link Elite telematics, 10" LCD touchscreen monitor, rearview camera, auto-idle shutdown, pattern changer (ISO/SAE), heavy-duty air filtration, ROPS/FOPS Level II cab, automatic climate control, Bluetooth radio, 120V AC outlet, LED work lights (8), ground-level service access, secondary emergency engine shutoff.

Specifications based on manufacturer published data. Caterpillar, Cat, and the Cat logo are trademarks of Caterpillar Inc.