

1 Symbolica for Typst

symbolica exposes Symbolica's exact algebra engine to Typst through a WebAssembly plugin. Expressions and matrices are passed around as opaque byte payloads; use `to-typst` for document output and `to-symbolica` for portable text.

1.1 Setup

```
#import "@local/symbolica:0.1.0": *
```

```
#let expr = math($(x + 1)^2$)
#to-typst(expand(expr))
```

For a source checkout, import the local library directly:

```
#import "lib.typ": *
```

1.2 Worked API Examples

Each example shows the Typst code first, then the rendered output produced by the current plugin.

1.2.1 Engine, Parsing, and Symbols

```
#let sym = init(namespace: "physics")
#let smath = sym.math
#let svar = sym.var

#let x = var("x")
#let y = symbol("y")
#let a-wild = wild("a")
#let rhs-only = dummy("fresh")
#let expr = math($(x + 1)^2 + y$)
#let same = from-math($(x + 1)^2 + y$)
#let literal = atom("z")
#let namespaced = add(svar("x"), x)
```

```
expr: #to-typst(expr)
same: #to-typst(same)
literal: #to-typst(literal)
wildcards: #raw(to-symbolica(a-wild)) and #raw(to-symbolica(rhs-only))
namespaces: #raw(to-symbolica(namespaced, namespaces: true))
```

```
expr:  $y + (1 + x)^2$ 
same:  $y + (1 + x)^2$ 
literal:  $z$ 
wildcards:  $a\_$  and  $fresh\_$ 
namespaces:  $typst::x+physics::x$ 
```

1.2.2 Parse Tree Inspection

```
#array-tree($(x + 1)^2$)
```

```
(
  strong(body: raw(text: "pow")),
  (
    styled(child: raw(text: "base"), ..),
    (
      strong(body: raw(text: "()")),
      (
        styled(child: raw(text: "expr"), ..),
        (
          strong(body: raw(text: "add")),

```

```

        equation(body: [x]),
        equation(body: [1]),
      ),
    ),
  ),
),
(
  styled(child: raw(text: "exp"), ..),
  equation(body: [2]),
),
)

```

1.2.3 Rendering

```
#let expr = math($(x + 1)^2 + y$)
```

```

canonical: #raw(canonical(expr))
to-symbolica: #raw(to-symbolica(expr))
to-typst-source: #raw(to-typst-source(expr))
to-typst: #to-typst(expr)
to-latex: #raw(to-latex(expr))

```

```

canonical: y+(1+x)^2
to-symbolica: y+(1+x)^2
to-typst-source: y+(1+x)^2
to-typst:  $y + (1 + x)^2$ 
to-latex: y+\left(1+x\right)^{2}

```

1.2.4 Algebra and Calculus

```

#let p = math($x^2 + 2 x + 1$)
#let q = math($(x + 1) (y + 2)$)

```

```

simplify: #to-typst(simplify(p))
expand: #to-typst(expand(q))
factor: #to-typst(factor(p))
derivative: #to-typst(derivative(q, x))
series: #builtin.to-typst(builtin.series(builtin.math($cos(x)/(x + 1)$), builtin.var("x"), 0, 3))

```

```

simplify:  $1 + 2x + x^2$ 
expand:  $2 + 2x + xy + y$ 
factor:  $(1 + x)^2$ 
derivative:  $2 + y$ 
series:  $1 - x + \frac{1}{2}x^2 - \frac{1}{2}x^3$ 

```

1.2.5 Scalar Constructors and Arithmetic

```

#let arith = add(
  mul(2, x, y),
  neg(z),
  sub(x, y),
  div(1, x),
  pow(x, 3),
)
#to-typst(arith)

```

```
 $x + 2xy - y - z + x^3 + \frac{1}{x}$ 
```

1.2.6 Replacement

```
#let src = math($f(x, y) + x$)
#let swapped = replace(src, math($f("a_", "b_")$), math($g("b_", "a_")$))
#let r1 = rule(math($f("a_")$), math($h("a_")$))
#let r2 = rule(x, z)
#let multiple = replace-multiple(math($f(x) + x$), (r1, r2))
#let wild-replaced = replace-wildcards(math($k("a_")$), ((wild("a"), math($x + 1$)),))
#let all = replace-all(math($x + y$), y, z)
```

```
replace: #to-typst(swapped)
replace-multiple: #to-typst(multiple)
replace-wildcards: #to-typst(wild-replaced)
replace-all: #to-typst(all)
```

```
replace:  $x + g(y, x)$ 
replace-multiple:  $z + h(x)$ 
replace-wildcards:  $k(1 + x)$ 
replace-all:  $x + z$ 
```

1.2.7 Evaluation and Solving

```
#let value = evaluate(math($x^2 + y$), values: ((x, 2.0), (y, 3.0)))
#let complex = evaluate(math($x^2$), values: ((x, (re: 2.0, im: 1.0)),))
#let exact = solve-linear((math($2 x + y - 5$), math($x - y - 1$)), (x, y))
#let root = nsolve(math($x^2 - 2$), x, 1.0)
#let roots = nsolve-system((math($x^2 + y - 3$), math($x - y$)), (x, y), (1.0, 1.0))
```

```
value: #repr(value)
complex: #repr(complex)
solve-linear: #exact.map(to-typst).join[, ]
nsolve: #repr(root)
nsolve-system: #repr(roots)
```

```
value: (re: 7.0, im: 0.0)
complex: (re: 3.0, im: 4.0)
solve-linear: 2, 1
nsolve: 1.4142135623746899
nsolve-system: (1.3027756377319948, 1.3027756377319948)
```

1.2.8 Matrix Construction and Rendering

```
#let A = matrix($mat(2, 1; 1, -1)$)
#let B = matrix(((1, 2), (3, 4)))
#let b = vec((5, 1))
#let I = identity(2)
#let D = eye((1, 2))
```

```
A: #to-typst(A)
B: #to-typst(B)
b: #to-typst(b)
I: #to-typst(I)
D: #to-typst(D)
```

```
A:  $\begin{pmatrix} 2 & 1 \\ 1 & -1 \end{pmatrix}$ 
B:  $\begin{pmatrix} 1 & 2 \\ 3 & 4 \end{pmatrix}$ 
b:  $\begin{pmatrix} 5 \\ 1 \end{pmatrix}$ 
```

$$I: \begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix}$$

$$D: \begin{pmatrix} 1 & 0 \\ 0 & 2 \end{pmatrix}$$

1.2.9 Matrix Operations

```
#let solved = matrix-solve(A, b)
#let any = matrix-solve-any(A, b)
#let reduced = row-reduce(B)
#let aug = augment(A, B)
#let parts = split-col(aug, 2)

add: #to-typst(matrix-add(A, B))
sub: #to-typst(matrix-sub(B, A))
mul: #to-typst(matrix-mul(A, I))
scalar mul: #to-typst(matrix-mul(A, 3))
scalar div: #to-typst(matrix-div-scalar(B, 2))
transpose: #to-typst(transpose(A))
det: #to-typst(det(A))
inv: #to-typst(inv(A))
solve: #to-typst(solved)
solve-any: #to-typst(any)
row-reduce: rank #reduced.rank, #to-typst(reduced.matrix)
augment: #to-typst(aug)
split-col: #to-typst(parts.at(0)) | #to-typst(parts.at(1))
```

```
add:  $\begin{pmatrix} 3 & 3 \\ 4 & 3 \end{pmatrix}$ 
sub:  $\begin{pmatrix} -1 & 1 \\ 2 & 5 \end{pmatrix}$ 
mul:  $\begin{pmatrix} 2 & 5 \\ 2 & 1 \end{pmatrix}$ 
mul:  $\begin{pmatrix} 1 & -1 \end{pmatrix}$ 
scalar mul:  $\begin{pmatrix} 6 & 3 \\ 3 & -3 \end{pmatrix}$ 
scalar div:  $\begin{pmatrix} \frac{1}{2} & 1 \\ \frac{3}{2} & 2 \end{pmatrix}$ 
transpose:  $\begin{pmatrix} 2 & 1 \\ 1 & -1 \end{pmatrix}$ 
det:  $-3$ 
inv:  $\begin{pmatrix} \frac{1}{3} & \frac{1}{3} \\ \frac{1}{3} & -\frac{2}{3} \end{pmatrix}$ 
solve:  $\begin{pmatrix} 2 \\ 1 \end{pmatrix}$ 
solve-any:  $\begin{pmatrix} 2 \\ 1 \end{pmatrix}$ 
row-reduce: rank 2,  $\begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix}$ 
augment:  $\begin{pmatrix} 2 & 1 & 1 & 2 \\ 1 & -1 & 3 & 4 \end{pmatrix}$ 
split-col:  $\begin{pmatrix} 2 & 1 \\ 1 & -1 \end{pmatrix} \mid \begin{pmatrix} 1 & 2 \\ 3 & 4 \end{pmatrix}$ 
```

1.2.10 Matrix Entries and Polynomial Content

```
#let P = matrix(((mul(2, x), mul(4, x)), (mul(6, x), mul(8, x))))

primitive-part: #to-typst(primitive-part(P))
content: #to-typst(content(P))
matrix-at: #to-typst(matrix-at(A, 0, 1))
matrix-shape: #repr(matrix-shape(A))
```

```
primitive-part:  $\begin{pmatrix} 1 & 2 \\ 3 & 4 \end{pmatrix}$ 
content:  $2x$ 
matrix-at: 1
matrix-shape: (2, 2)
```

1.3 API Reference

The reference below is generated from the doc comments in `lib.typ` with `tidy`. Its examples use a preamble equivalent to importing the package with `: *`.

1.4 symbolica

- `add()`
- `array-tree()`
- `atom()`
- `augment()`
- `canonical()`
- `content()`
- `derivative()`
- `det()`
- `div()`
- `dummy()`
- `evaluate()`
- `expand()`
- `eye()`
- `factor()`
- `from-math()`
- `identity()`
- `init()`
- `inv()`
- `math()`
- `matrix()`
- `matrix-add()`
- `matrix-at()`
- `matrix-div-scalar()`
- `matrix-mul()`
- `matrix-shape()`
- `matrix-solve()`
- `matrix-solve-any()`
- `matrix-sub()`
- `mul()`
- `neg()`
- `nsolve()`
- `nsolve-system()`
- `pow()`
- `primitive-part()`
- `replace()`
- `replace-all()`
- `replace-multiple()`
- `replace-wildcards()`
- `row-reduce()`
- `rule()`
- `series()`
- `simplify()`
- `solve-linear()`
- `split-col()`
- `sub()`
- `symbol()`
- `to-latex()`

- to-symbolica()
- to-typst()
- to-typst-source()
- transpose()
- var()
- vec()
- wild()

1.4.1 add

Add one or more expression payloads or Typst values.

```
#to-typst(add("x", 1, "y"))
```

 $1 + x + y$

1.4.1.1 Parameters

`add(...terms)` -> `bytes`

1.4.2 array-tree

Render the Parsely tree used for parsing a math expression.

```
#array-tree($(x + 1)^2$)
```

```
(
  strong(body: raw(text: "pow")),
  (
    styled(child: raw(text: "base"), ..),
    (
      strong(body: raw(text: "()")),
      (
        styled(child: raw(text: "expr"), ..),
        (
          strong(body: raw(text: "add")),
          equation(body: [x]),
          equation(body: [1]),
        ),
      ),
    ),
  ),
),
(
  styled(child: raw(text: "exp"), ..),
  equation(body: [2]),
),
)
```

1.4.2.1 Parameters

`array-tree(`
 `eqn,`
 `grammar`
`)` -> `content`

1.4.3 atom

Convert a Typst value or math expression into an atom payload.

```
#to-typst(atom("x"))
```

x

1.4.3.1 Parameters

```
atom(value) -> bytes
```

1.4.4 augment

Horizontally augment two matrices.

```
#to-tyrst(augment(identity(2), matrix(((1,
2), (3, 4))))))
```

$$\begin{pmatrix} 1 & 0 & 1 & 2 \\ 0 & 1 & 3 & 4 \end{pmatrix}$$

1.4.4.1 Parameters

```
augment(
  lhs,
  rhs
) -> bytes
```

1.4.5 canonical

Render an atom or matrix payload as Symbolica text.

```
#raw(canonical(math($x + 1$)))
```

1+x

1.4.5.1 Parameters

```
canonical(
  expr,
  namespaces
) -> str
```

1.4.6 content

Compute the content of a matrix as an atom payload.

```
#let x = var("x")
#let P = matrix((mul(2, x), mul(4, x)),
(mul(6, x), mul(8, x)))
#to-tyrst(content(P))
```

$2x$

1.4.6.1 Parameters

```
content(matrix) -> bytes
```

1.4.7 derivative

Differentiate expr with respect to var.

```
#let x = var("x")
```

```
#to-typst(derivative(math$(x + 1)^2$, x))
```

$2(1 + x)$

1.4.7.1 Parameters

```
derivative(  
  expr,  
  var  
) -> bytes
```

1.4.8 det

Compute the determinant of a matrix as an atom payload.

```
#to-typst(det(matrix(((1, 2), (3, 4)))))
```

-2

1.4.8.1 Parameters

```
det(matrix) -> bytes
```

1.4.9 div

Divide two expression payloads or Typst values.

```
#to-typst(div(1, "x"))
```

$\frac{1}{x}$

1.4.9.1 Parameters

```
div(  
  lhs,  
  rhs  
) -> bytes
```

1.4.10 dummy

Construct an RHS-only wildcard marker. This is wildcard syntax, not a fresh symbol generator.

```
#raw(to-symbolica(dummy("fresh")))
```

fresh_

1.4.10.1 Parameters

```
dummy(  
  name,  
  level,  
  namespace  
) -> bytes
```

1.4.11 evaluate

Evaluate an expression with optional real or complex values.

```
#let x = var("x")
#let y = var("y")
#repr(evaluate(math($x^2 + y$), values: ((x,
2.0), (y, 3.0))))
```

```
(re: 7.0, im: 0.0)
```

1.4.11.1 Parameters

```
evaluate(
  expr,
  values
) -> dictionary
```

1.4.12 expand

Expand products and powers through Symbolica's polynomial expansion.

```
#to-tyrst(expand(math($(x + 1)^2$)))
```

$$1 + 2x + x^2$$

1.4.12.1 Parameters

```
expand(expr) -> bytes
```

1.4.13 eye

Create a diagonal matrix payload from diagonal entries.

```
#to-tyrst(eye((1, 2)))
```

$$\begin{pmatrix} 1 & 0 \\ 0 & 2 \end{pmatrix}$$

1.4.13.1 Parameters

```
eye(diag) -> bytes
```

1.4.14 factor

Factor an expression payload.

```
#to-tyrst(factor(math($(x^2 + 2 x + 1$)))
```

$$(1 + x)^2$$

1.4.14.1 Parameters

```
factor(expr) -> bytes
```

1.4.15 from-math

Parse Tyrst math content with an optional grammar and namespace override.

```
#to-tyrst(from-math($(x + 1)^2$))
```

$$(1 + x)^2$$

1.4.15.1 Parameters

```
from-math(  
  eqn,  
  grammar,  
  namespace  
) -> bytes
```

1.4.16 identity

Create an n by n identity matrix payload.

```
#to-typst(identity(2))
```

$$\begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix}$$

1.4.16.1 Parameters

```
identity(n) -> bytes
```

1.4.17 init

Create a Symbolica engine record backed by the WebAssembly plugin.

The returned dictionary contains the full API. The top-level functions below are convenience wrappers around `init()` with default settings.

```
#let sym = init(namespace: "physics")  
#let v = sym.var  
#let render = sym.to-symbolica  
#raw(render(v("x"), namespaces: true))
```

physics::x

1.4.17.1 Parameters

```
init(  
  namespace: str,  
  source: str,  
  grammar: dictionary  
) -> dictionary
```

1.4.17.1.1 namespace `str`

Default namespace used for symbols parsed from Typst math or strings.

Default: `"typst"`

1.4.17.1.2 source `str`

WebAssembly plugin path passed to Typst's plugin constructor.

Default: `"symbolica.wasm"`

1.4.17.1.3 grammar `dictionary`

Parsely grammar used by math and from-math.

Default: `_default_grammar`

1.4.18 inv

Compute the inverse of a matrix payload.

```
#to-typst(inv(matrix(((1, 2), (3, 4)))))
```

$$\begin{pmatrix} -2 & 1 \\ \frac{3}{2} & -\frac{1}{2} \end{pmatrix}$$

1.4.18.1 Parameters

`inv(matrix)` -> bytes

1.4.19 math

Parse Typst math content into an opaque Symbolica atom payload.

```
#let expr = math($x + 1$)
#to-typst(expr)
```

$$1 + x$$

1.4.19.1 Parameters

```
math(
  eqn: content,
  grammar: dictionary none,
  namespace: str none
) -> bytes
```

1.4.19.1.1 eqn content

Math content, normally written as `$...$`.

1.4.19.1.2 grammar dictionary or none

Optional Parsely grammar override.

Default: none

1.4.19.1.3 namespace str or none

Optional namespace override for parsed symbols.

Default: none

1.4.20 matrix

Convert Typst math `mat(...)`, `vec(...)`, or nested arrays into a matrix payload.

```
#to-typst(matrix($mat(1, 2; 3, 4)$))
```

$$\begin{pmatrix} 1 & 2 \\ 3 & 4 \end{pmatrix}$$

1.4.20.1 Parameters

`matrix(value)` -> bytes

1.4.21 matrix-add

Add two matrix payloads.

```
#to-typst(matrix-add(matrix(((1, 2), (3, 4))), identity(2)))
```

$$\begin{pmatrix} 2 & 2 \\ 3 & 5 \end{pmatrix}$$

1.4.21.1 Parameters

```
matrix-add(  
  lhs,  
  rhs  
) -> bytes
```

1.4.22 matrix-at

Read a matrix entry as an atom payload using zero-based indices.

```
#let A = matrix(((1, 2), (3, 4)))  
#to-typst(matrix-at(A, 0, 1))
```

2

1.4.22.1 Parameters

```
matrix-at(  
  matrix,  
  row,  
  col  
) -> bytes
```

1.4.23 matrix-div-scalar

Divide a matrix by a scalar expression.

```
#to-typst(matrix-div-scalar(matrix(((2, 4), (6, 8))), 2))
```

$$\begin{pmatrix} 1 & 2 \\ 3 & 4 \end{pmatrix}$$

1.4.23.1 Parameters

```
matrix-div-scalar(  
  lhs,  
  rhs  
) -> bytes
```

1.4.24 matrix-mul

Multiply matrices, or multiply a matrix by a scalar expression.

```
#to-typst(matrix-mul(matrix(((1, 2), (3, 4))), identity(2)))
```

$$\begin{pmatrix} 1 & 2 \\ 3 & 4 \end{pmatrix}$$

1.4.24.1 Parameters

```
matrix-mul(  
  lhs,  
  rhs  
) -> bytes
```

1.4.25 matrix-shape

Return the matrix shape as (rows, columns).

```
#repr(matrix-shape(matrix(((1, 2), (3, 4)))))
```

(2, 2)

1.4.25.1 Parameters

`matrix-shape(matrix)` -> array

1.4.26 matrix-solve

Solve $A \times b$ exactly.

```
#let A = matrix($mat(2, 1; 1, -1)$)
#let b = vec((5, 1))
#to-tyrst(matrix-solve(A, b))
```

$\begin{pmatrix} 2 \\ 1 \end{pmatrix}$

1.4.26.1 Parameters

`matrix-solve(`
 A,
 b
)
-> bytes

1.4.27 matrix-solve-any

Solve $A \times b$ exactly, allowing any solution for underdetermined systems.

```
#let A = matrix($mat(2, 1; 1, -1)$)
#let b = vec((5, 1))
#to-tyrst(matrix-solve-any(A, b))
```

$\begin{pmatrix} 2 \\ 1 \end{pmatrix}$

1.4.27.1 Parameters

`matrix-solve-any(`
 A,
 b
)
-> bytes

1.4.28 matrix-sub

Subtract two matrix payloads.

```
#to-tyrst(matrix-sub(matrix(((1, 2), (3, 4))), identity(2)))
```

$\begin{pmatrix} 0 & 2 \\ 3 & 3 \end{pmatrix}$

1.4.28.1 Parameters

`matrix-sub(`
 lhs,
 rhs
)
-> bytes

1.4.29 mul

Multiply one or more expression payloads or Typst values.

```
#to-typst(mul(2, "x", "y"))
```

$2xy$

1.4.29.1 Parameters

```
mul(..factors) -> bytes
```

1.4.30 neg

Negate an expression payload.

```
#to-typst(neg("x"))
```

$-x$

1.4.30.1 Parameters

```
neg(expr) -> bytes
```

1.4.31 nsolve

Numerically solve a univariate expression near init.

```
#let x = var("x")
#repr(nsolve(math($x^2 - 2$), x, 1.0))
```

1.4142135623746899

1.4.31.1 Parameters

```
nsolve(
  expr,
  var,
  init,
  prec,
  max-iterations
) -> float
```

1.4.32 nsolve-system

Numerically solve a system of expressions near init.

```
#let x = var("x")
#let y = var("y")
#repr(nsolve-system((math($x^2 + y - 3$),
math($x - y$)), (x, y), (1.0, 1.0)))
```

(1.3027756377319948, 1.3027756377319948)

1.4.32.1 Parameters

```
nsolve-system(
  system,
  variables,
  init,
  prec,
  max-iterations
) -> array
```

1.4.33 pow

Raise base to exp.

```
#to-typst(pow("x", 3))
```

 x^3

1.4.33.1 Parameters

```
pow(  
  base,  
  exp  
) -> bytes
```

1.4.34 primitive-part

Compute the primitive part of a matrix payload.

```
#let x = var("x")  
#let P = matrix((mul(2, x), mul(4, x)),  
  (mul(6, x), mul(8, x)))  
#to-typst(primitive-part(P))
```

$$\begin{pmatrix} 1 & 2 \\ 3 & 4 \end{pmatrix}$$

1.4.34.1 Parameters

```
primitive-part(matrix) -> bytes
```

1.4.35 replace

Replace subexpressions matching pattern with rhs.

```
#to-typst(replace(math($f(x, y)$),  
  math($f("a_", "b_")$), math($g("b_",  
  "a_")$)))
```

 $g(y, x)$

1.4.35.1 Parameters

```
replace(  
  expr,  
  pattern,  
  rhs,  
  repeat,  
  once,  
  bottom-up,  
  nested,  
  non-greedy-wildcards,  
  min-level,  
  max-level,  
  level-range,  
  level-is-tree-depth,  
  partial,  
  allow-new-wildcards-on-rhs,  
  rhs-cache-size  
) -> bytes
```

1.4.36 replace-all

Compatibility alias for replace with default replacement settings.

```
#to-typst(replace-all(math($x + y$),  
var("y"), var("z")))
```

$$x + z$$

1.4.36.1 Parameters

```
replace-all(  
  expr,  
  pattern,  
  replacement  
) -> bytes
```

1.4.37 replace-multiple

Apply multiple replacement rules in one pass.

```
#let r1 = rule(math($f("a_")$),  
math($h("a_")$))  
#let r2 = rule(var("x"), var("z"))  
#to-typst(replace-multiple(math($f(x) + x$),  
(r1, r2)))
```

$$z + h(x)$$

1.4.37.1 Parameters

```
replace-multiple(  
  expr,  
  rules,  
  repeat,  
  once,  
  bottom-up,  
  nested  
) -> bytes
```

1.4.38 replace-wildcards

Replace wildcard placeholders inside a pattern.

```
#to-typst(replace-wildcards(math($k("a_")$),  
((wild("a"), math($x + 1$)),))
```

$$k(1 + x)$$

1.4.38.1 Parameters

```
replace-wildcards(  
  pattern,  
  replacements  
) -> bytes
```

1.4.39 row-reduce

Row-reduce a matrix and return (matrix: ..., rank: ...).

```
#let rr = row-reduce(matrix(((1, 2), (3,  
4))))
```

```
rank #rr.rank: #to-typst(rr.matrix)
```

rank 2: $\begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix}$

1.4.39.1 Parameters

```
row-reduce(  
  matrix,  
  max-col  
) -> dictionary
```

1.4.40 rule

Build a reusable replacement rule for replace-multiple.

```
#let r = rule(math($f("a_")$),  
math($g("a_")$))  
#to-typst(replace-multiple(math($f(x)$),  
(r,)))
```

$g(x)$

1.4.40.1 Parameters

```
rule(  
  pattern,  
  rhs,  
  non-greedy-wildcards,  
  min-level,  
  max-level,  
  level-range,  
  level-is-tree-depth,  
  partial,  
  allow-new-wildcards-on-rhs,  
  rhs-cache-size  
) -> dictionary
```

1.4.41 series

Compute a series expansion around expansion-point.

```
#let sym = init(namespace: "symbolica")  
#let m = sym.math  
#let v = sym.var  
#let ser = sym.series  
#let render = sym.to-typst  
#render(ser(m($cos(x)/(x + 1)$), v("x"), 0,  
3))
```

$1 - x + \frac{1}{2}x^2 - \frac{1}{2}x^3$

1.4.41.1 Parameters

```
series(  
  expr,  
  var,  
  expansion-point,  
  depth,  
  depth-denom,  
  depth-is-absolute  
) -> bytes
```

1.4.42 simplify

Normalize an expression payload without changing its mathematical value.

```
#to-typst(simplify(math($x + 0$)))
```

 x

1.4.42.1 Parameters

```
simplify(expr) -> bytes
```

1.4.43 solve-linear

Solve a linear system exactly for variables.

```
#let x = var("x")
#let y = var("y")
#let sol = solve-linear((math($2 x + y - 5$),
math($x - y - 1$)), (x, y))
#sol.map(to-typst).join[, ]
```

 $2, 1$

1.4.43.1 Parameters

```
solve-linear(
  system,
  variables
) -> array
```

1.4.44 split-col

Split a matrix at a column index.

```
#let aug = augment(identity(2), matrix(((1,
2), (3, 4))))
#let parts = split-col(aug, 2)
#to-typst(parts.at(0)) | #to-
typst(parts.at(1))
```

$$\begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix} \mid \begin{pmatrix} 1 & 2 \\ 3 & 4 \end{pmatrix}$$

1.4.44.1 Parameters

```
split-col(
  matrix,
  index
) -> array
```

1.4.45 sub

Subtract two expression payloads or Typst values.

```
#to-typst(sub("x", "y"))
```

 $x - y$

1.4.45.1 Parameters

```
sub(  
  lhs,  
  rhs  
) -> bytes
```

1.4.46 symbol

Construct a symbol atom with an optional namespace override.

```
#to-typst(symbol("x"))
```

x

1.4.46.1 Parameters

```
symbol(  
  name,  
  namespace  
) -> bytes
```

1.4.47 to-latex

Render an atom or matrix payload as LaTeX source.

```
#raw(to-latex(math($x^2 + 1$)))
```

$1+x^2$

1.4.47.1 Parameters

```
to-latex(expr) -> str
```

1.4.48 to-symbolica

Alias for canonical.

```
#raw(to-symbolica(math($x + 1$)))
```

$1+x$

1.4.48.1 Parameters

```
to-symbolica(  
  expr,  
  namespaces  
) -> str
```

1.4.49 to-typst

Render an atom or matrix payload as Typst math content.

```
#to-typst(math($x + 1$))
```

$1 + x$

1.4.49.1 Parameters

```
to-typst(  
  expr,  
  block  
) -> content
```

1.4.50 to-typst-source

Render an atom or matrix payload as Typst math source.

```
#raw(to-typst-source(math($x + 1$)))
```

$1+x$

1.4.50.1 Parameters

```
to-typst-source(expr) -> str
```

1.4.51 transpose

Transpose a matrix payload.

```
#to-typst(transpose(matrix(((1, 2), (3,  
4)))))
```

$\begin{pmatrix} 1 & 3 \\ 2 & 4 \end{pmatrix}$

1.4.51.1 Parameters

```
transpose(matrix) -> bytes
```

1.4.52 var

Alias for symbol for variables used in expressions, solves, and derivatives.

```
#to-typst(var("x"))
```

x

1.4.52.1 Parameters

```
var(  
  name,  
  namespace  
) -> bytes
```

1.4.53 vec

Convert values or Typst math `vec(...)` into a column-vector matrix payload.

```
#to-typst(vec((1, 2)))
```

$\begin{pmatrix} 1 \\ 2 \end{pmatrix}$

1.4.53.1 Parameters

```
vec(values) -> bytes
```

1.4.54 wild

Construct a wildcard symbol by appending underscore levels to name.

```
#raw(to-symbolica(wild("a")))
```

```
a_
```

1.4.54.1 Parameters

```
wild(  
  name,  
  level,  
  namespace  
) -> bytes
```