

Tymbolica

Exact symbolic computation inside Typst

User manual · version 0.1.0

Parse Typst mathematics, transform it with Symbolica's exact algebra engine,
and place the result directly back into a document.

[Repository](#) · [MIT license](#) · [Symbolica guide](#) · [Symbolica license](#)

Contents

1	Start here	3
1.1	Installation	3
1.2	Where to begin	3
2	A few ideas before the examples	3
2.1	Keep expressions symbolic until you display them	3
2.2	Variables and wildcards have different jobs	4
2.3	Built-in functions such as sine and cosine	4
2.4	Write equations as expressions equal to zero	4
3	Worked mathematical guides	4
3.1	Calibrate a pendulum model	5
3.2	Rewrite a repeated identity with wildcards	6
3.3	Integrate a polynomial and verify it	6
3.4	Solve a nonlinear system exactly and numerically	7
3.5	Recover an interpolating polynomial with matrices	8
3.6	Map a gradient across a grid	8
4	What to expect	9
4.1	When something looks wrong	9
5	API reference	10
5.1	Parsing, symbols, and rendering	10
5.2	Algebra and calculus	14
5.3	Rewriting	17
5.4	Evaluation and solving	22
5.5	Matrices	28
5.6	Scalar constructors	36
5.7	Advanced configuration	38
6	Compatibility and licensing	38
7	Acknowledgements	39

1 Start here

Tymbolica keeps symbolic calculation beside the mathematics it belongs to. You can write a formula in Typst, factor or differentiate it, and place the answer straight back into the page—without copying expressions to another program.

Here is the whole pattern: read some mathematics with `math`, do the algebra, and display the result with `to-typst`.

```
#import "@local/tymbolica:0.1.0": *

#let p = math($(x + y)^3 - (x^3 + y^3)$)
#to-typst(factor(expand(p)))
```

$$3xy(x + y)$$

Tymbolica finds $3xy(x + y)$ exactly. The same three-step pattern—read, calculate, display—runs through the rest of this manual.

1.1 Installation

Until Tymbolica is published in Typst Universe, install it from a checkout. On Linux, place or symlink the repository root at:

```
~/local/share/typst/packages/local/tymbolica/0.1.0
```

Use the corresponding Typst data directory on macOS or Windows. The package root must contain `typst.toml`; its `typst` directory contains `lib.typ` and `tymbolica.wasm`. Then import:

```
#import "@local/tymbolica:0.1.0": *
```

From a source checkout, a document can instead import the library by relative path:

```
#import "path/to/tymbolica/typst/lib.typ": *
```

No build step is needed to use the package: everything required is already included in the checkout.

Why @local? The examples use `@local` because this version is installed from the repository. A future Typst Universe release will use its published namespace instead.

1.2 Where to begin

If you want to...	Start with...
Turn Typst mathematics into a symbolic expression	<code>math</code> , <code>var</code> , and <code>atom</code>
Put an answer back into the document	<code>to-typst</code>
Factor, expand, differentiate, integrate, or take a series	<code>expand</code> , <code>factor</code> , <code>derivative</code> , <code>integrate</code> , <code>series</code>
Replace a recurring symbolic pattern	<code>wild</code> , <code>rule</code> , <code>replace</code>
Evaluate a formula at many points	<code>evaluate-many</code> , <code>evaluate-grid</code>
Solve equations exactly or numerically	<code>solve-linear</code> , <code>solve-system</code> , <code>nsolve-system</code>
Work with exact matrices	<code>matrix</code> , <code>matrix-solve</code> , <code>row-reduce</code>

2 A few ideas before the examples

2.1 Keep expressions symbolic until you display them

The value returned by `math` is a symbolic expression, not something Typst can typeset on its own. Pass it through as many algebraic operations as you like, then call `to-typst` where you want the answer to appear.

Typst math $\rightarrow$ math $\rightarrow$ symbolic expression $\rightarrow$ transform $\rightarrow$ to-typst $\rightarrow$ document

```
#let expression = math($(x + 1)^4$)
#let transformed = expand(expression)

original: $ #to-typst(expression) $\
expanded: $ #to-typst(transformed) $
```

original:

$$(1 + x)^4$$

expanded:

$$1 + 4x + 6x^2 + 4x^3 + x^4$$

For ordinary documents, to-typst is usually all you need. to-latex is handy when exporting to another system, while canonical shows Symbolica's plain text form when you are diagnosing a difficult expression.

2.2 Variables and wildcards have different jobs

Function	Typical input	Use
math	<code>\$x^2 + 1\$</code>	Read a Typst formula.
atom	a number, string, formula, or expression	Turn a general value into an expression.
var	<code>"x"</code>	Create a variable that belongs to the mathematics.
wild	<code>"a"</code>	Create a placeholder used only while matching a pattern.

The distinction that matters A variable is part of the formula. A wildcard is a blank in a pattern. Use `var("x")` for the x in $x^2 + 1$; use `wild("a")` when a replacement rule should accept any expression in place of a .

Repeated occurrences of the same wildcard in one pattern must capture the same expression. Different matches can bind it differently; the rewriting guide below turns that rule into a concrete example.

2.3 Built-in functions such as sine and cosine

Polynomials work with the imported top-level functions. For analytic functions such as `sin`, `cos`, and `exp`, create a Symbolica-flavoured set of functions so that differentiation and numerical evaluation recognize them:

```
#let sym = init(namespace: "symbolica")
#let parse = sym.math
#let x = sym.var("x")
#let derivative = sym.derivative

#sym.to-typst(derivative(parse($sin(x)$), x))
```

The worked pendulum example binds these functions to short local names so that the calculation remains readable.

2.4 Write equations as expressions equal to zero

Solver inputs are expressions understood to equal zero. For example, `math($x + y - 3$)` represents $x + y = 3$.

For several variables, each solution row follows the variable order you give the solver. Exact solving finds all supported algebraic branches; numerical solving looks for one branch near your initial guess.

3 Worked mathematical guides

The quickest way to learn the package is to follow a calculation from question to answer. Each example below ends with a check, because a plausible-looking formula is not yet a convincing result.

3.1 Calibrate a pendulum model

A pendulum gives us a small but complete modelling problem. Begin with the potential $V(\theta) = \kappa(1 - \cos \theta)$, derive the restoring torque, and take a cubic small-angle approximation. Two torque readings are then enough to recover both the unknown scale κ and a sensor offset τ_0 .

The calculation is adapted from Symbolica's [pendulum calibration example](#). We create the symbolica set of functions because `cos` must be understood as the analytic cosine rather than as an arbitrary function name.

3.1.1 Derive the model

```
#let sym = init(namespace: "symbolica")
#let (
  math: m, var: v, to-typtst: render,
  derivative, series, neg, add,
) = sym

#let potential = m($kappa (1 - cos(theta)))$
#let q = v("θ")
#let k = v("κ")
#let b = v("τ₀")

#let torque = neg(derivative(potential, q))
#let small-angle = series(torque, q, 0, 3)
#let model = add(small-angle, b)

$ V(theta) = #render(potential) $\
$ tau(theta) = -(partial V)/(partial theta) = #render(torque) $\
$ tau_small(theta) + tau_0 = #render(model) $
```

$$V(\theta) = \kappa(1 - \cos(\theta))$$

$$\tau(\theta) = -\frac{\partial V}{\partial \theta} = -\kappa \sin(\theta)$$

$$\tau_{\text{small}}(\theta) + \tau_0 = -\kappa\theta + \frac{1}{6}\kappa\theta^3 + \tau_0$$

The derivative gives the restoring torque, while the cubic series keeps the first nonlinear correction to the familiar small-angle law. Adding τ_0 leaves a model that is linear in the two unknown parameters.

3.1.2 Fit two readings exactly

```
#let q1 = v("θ₁")
#let q2 = v("θ₂")
#let t1 = v("τ₁")
#let t2 = v("τ₂")

#let fit = solve-linear((
  sub(replace(model, q, q1), t1),
  sub(replace(model, q, q2), t2),
), (k, b))

$ kappa = #render(fit.at(0)) $\
$ tau_0 = #render(fit.at(1)) $
```

$$\kappa = \frac{6 \tau_1 - 6 \tau_2}{-6 \theta_1 + 6 \theta_2 + \theta_1^3 - \theta_2^3}$$

$$\tau_0 = \frac{-6 \theta_1 \tau_2 + 6 \theta_2 \tau_1 + \theta_1^3 \tau_2 - \theta_2^3 \tau_1}{-6 \theta_1 + 6 \theta_2 + \theta_1^3 - \theta_2^3}$$

Nothing has been rounded: both fitted parameters are still formulas in the angles and measured torques. Now insert two observations, $(\theta_1, \tau_1) = (0.10, -0.4697)$ and $(\theta_2, \tau_2) = (0.20, -0.9545)$.

3.1.3 Insert the measurements and check the fit

```
#let fitted = evaluate-many(
  fit,
  (q1, q2, t1, t2),
  ((0.10, 0.20, -0.4697, -0.9545)),
).first()
#let predictions = evaluate-many(
  model,
  (q, k, b),
  (
    (0.10, fitted.at(0).re, fitted.at(1).re),
    (0.20, fitted.at(0).re, fitted.at(1).re),
  ),
)

$ kappa approx #calc.round(fitted.at(0).re, digits: 6), quad
tau_0 approx #calc.round(fitted.at(1).re, digits: 6) $
predicted torques:
#predictions.map(row => str(calc.round(row.first().re, digits: 4))).join(", ")
```

$$\kappa \approx 4.905228, \quad \tau_0 \approx 0.020005$$

predicted torques: -0.4697, -0.9545

The formula for κ remains exact until the measured values are inserted. Substituting the fitted parameters back into the model reproduces both torque readings, so the final line checks the entire chain from potential to fit.

3.2 Rewrite a repeated identity with wildcards

This is where a wildcard earns its keep. Suppose an expression contains several copies of $\sin^2(a) + \cos^2(a)$, but the argument a is different each time. The pattern should insist that the two functions share an argument without fixing what that argument is.

```
#let source = math(
  $3 (sin(x)^2 + cos(x)^2
    + sin(x + y)^2 + cos(x + y)^2$
)
#let identity = math(
  $sin("a_")^2 + cos("a_")^2$
)

#let one-pass = replace(source, identity, 1)
#let reduced = replace(source, identity, 1, repeat: true)

source: #to-tyrst(source)\
one pass: #to-tyrst(one-pass)\
repeat to a fixed point: #to-tyrst(reduced)
```

source: $3(\sin(x)^2 + \cos(x)^2) + \sin(x + y)^2 + \cos(x + y)^2$
 one pass: $1 + 3(\sin(x)^2 + \cos(x)^2)$
 repeat to a fixed point: 4

Within one match, both occurrences of `a_` capture the same expression. Across matches it first captures one argument and then another. This is the practical difference between an ordinary `var("a")` and `wild("a")`.

Repeating rules `repeat: true` keeps applying the rule until the expression stops changing. Use it only for rules that settle: $a \rightarrow a + 1$, for example, would never reach a fixed point.

3.3 Integrate a polynomial and verify it

The next polynomial is compact while factored and rather less friendly after expansion. We integrate its expanded terms one by one, add the contributions, and differentiate the answer as a check.

```
#let x = var("x")
#let p = math($(x + 1)^3 (2 x^2 - 3 x + 5)$)
#let integration = integrate-with-steps(p, x)
#let residual = expand(
  sub(derivative(integration.result, x), p)
)
```

```

$ p(x) = #to-tyrst(p) $ \
term contributions: \
#for (index, term) in integration.steps.enumerate() [
  #(index + 1). #to-tyrst(term) #linebreak()
]
$ integral p(x) dif x = #to-tyrst(integration.result) + C $ \
verification: $ (partial I)/(partial x) - p(x) = #to-tyrst(residual) $

```

$$p(x) = (1+x)^3(5-3x+2x^2)$$

term contributions:

1. $5x$
2. $6x^2$
3. $\frac{8}{3}x^3$
4. $\frac{1}{2}x^4$
5. $\frac{3}{5}x^5$
6. $\frac{1}{3}x^6$

$$\int p(x) dx = 5x + 6x^2 + \frac{8}{3}x^3 + \frac{1}{2}x^4 + \frac{3}{5}x^5 + \frac{1}{3}x^6 + C$$

verification:

$$\frac{\partial I}{\partial x} - p(x) = 0$$

Each numbered line is the antiderivative of one term after expansion. Their sum is one antiderivative of p ; the displayed equation adds the customary $+C$. Differentiating the sum leaves a zero residual.

Integration boundary At present, integration is limited to polynomials. An integral such as $\int \frac{1}{1+x^2} dx$ is outside Tymbolica's current scope.

3.4 Solve a nonlinear system exactly and numerically

The circle $x^2 + y^2 = 25$ and the line $x - y = 1$ meet twice. The exact solver should find both intersections; the numerical solver should find the one nearest its starting point.

```

#let x = var("x")
#let y = var("y")
#let system = (
  math($x^2 + y^2 - 25$),
  math($x - y - 1$),
)

#let exact = solve-system(system, (x, y))
#let positive = nsolve-system(
  system, (x, y), (3.0, 3.0), prec: 1e-10,
)
#let negative = nsolve-system(
  system, (x, y), (-3.0, -3.0), prec: 1e-10,
)
#let checks = evaluate-many(
  system, (x, y), (positive, negative),
)

```

exact branches:

1. $x = 4, y = 3$
 2. $x = -3, y = -4$
- seed (3,3) $\rightarrow$ (4, 3); maximum residual 0.0
 seed (-3,-3) $\rightarrow$ (-3, -4); maximum residual 3.552713678800501e-15

The exact calculation finds both branches. Starting near either intersection selects that numerical branch, and the small residual confirms that the point lies on both curves. A poor starting point may still converge elsewhere—or not at all.

3.5 Recover an interpolating polynomial with matrices

Find the quadratic through $(0, 1)$, $(1, 3)$, and $(2, 8)$. Writing $p(t) = a_0 + a_1 t + a_2 t^2$ turns interpolation into the exact matrix equation $Aa = b$.

```
#let t = var("t")
#let A = matrix((
  (1, 0, 0),
  (1, 1, 1),
  (1, 2, 4),
))
#let b = vec((1, 3, 8))
#let coefficients = matrix-solve(A, b)
#let check = matrix-mul(A, coefficients)
#let polynomial = add(
  matrix-at(coefficients, 0, 0),
  mul(matrix-at(coefficients, 1, 0), t),
  mul(matrix-at(coefficients, 2, 0), pow(t, 2)),
)

$ A = #to-tyrst(A), quad b = #to-tyrst(b) $ \
$ op("det")(A) = #to-tyrst(det(A)) $ \
$ a = #to-tyrst(coefficients) $ \
$ p(t) = #to-tyrst(polynomial) $ \
$ A a = #to-tyrst(check) $
```

$$A = \begin{pmatrix} 1 & 0 & 0 \\ 1 & 1 & 1 \\ 1 & 2 & 4 \end{pmatrix}, \quad b = \begin{pmatrix} 1 \\ 3 \\ 8 \end{pmatrix}$$

$$\det(A) = 2$$

$$a = \begin{pmatrix} 1 \\ \frac{1}{2} \\ \frac{3}{2} \end{pmatrix}$$

$$p(t) = 1 + \frac{1}{2}t + \frac{3}{2}t^2$$

$$Aa = \begin{pmatrix} 1 \\ 3 \\ 8 \end{pmatrix}$$

The nonzero determinant tells us the coefficients are unique. Reading them back gives the polynomial, and multiplying Aa recovers the three original measurements.

3.6 Map a gradient across a grid

Consider the quadratic surface $f(x, y) = x^2 + xy + y^2$. We first derive its two gradient components, then sample the height and gradient together on a small Cartesian grid.

```
#let x = var("x")
#let y = var("y")
#let f = math($x^2 + x y + y^2$)
#let fx = derivative(f, x)
#let fy = derivative(f, y)
#let grid = evaluate-grid(
  (f, fx, fy),
  (x, y),
  (
    domain(-1, 1, samples: 3),
    domain(-1, 1, samples: 3),
  ),
)

$ f = #to-tyrst(f) $ \
$ partial_x f = #to-tyrst(fx), quad partial_y f = #to-tyrst(fy) $
```


$$f = xy + x^2 + y^2$$

$$\partial_x f = 2x + y, \quad \partial_y f = x + 2y$$

x	y	f	$\partial_x f$	$\partial_y f$
-1	-1	3	-3	-3
-1	0	1	-2	-1
-1	1	1	-1	1
0	-1	1	-1	-2
0	0	0	0	0
0	1	1	1	2
1	-1	1	1	-1
1	0	1	2	1
1	1	3	3	3

The table makes the geometry visible: the gradient vanishes at the origin and points uphill everywhere else. `evaluate-grid` pairs each point with one value for every requested expression; use `evaluate-many` when your sample points do not form a Cartesian product.

4 What to expect

Tymbolica deliberately presents a smaller surface than Symbolica itself. The parts covered in this manual work well for exact algebra in documents, but a few boundaries are worth knowing before you choose an approach:

- Integration is polynomial-only. The term-by-term form expands the input first and does not add $+C$ automatically.
- Exact system solving is intended for linear and polynomial equations. Numerical solving depends on a starting point and gives an approximate answer rather than a derivation of convergence.
- Matrix entries must be rational-polynomial expressions, and their dimensions must agree for the requested operation.
- Algebraic transformations do not keep a separate list of assumptions. If a manipulation is valid only under a condition such as $x \neq 1$, preserve that condition in the surrounding document.
- Some unusual Typst math structures may not parse. `array-tree` can help show what the parser received.

For operations beyond this scope—general integration, arbitrary precision, or deeper polynomial algorithms—use Symbolica directly.

4.1 When something looks wrong

Symptom	Likely cause	What to try
expected content, found bytes	A symbolic result was inserted directly into <code>...</code> .	Display it with <code>to-typst</code> .
A derivative or series leaves a function unchanged	<code>sin</code> , <code>cos</code> , or another analytic function was read as an ordinary name.	Use <code>init(namespace: "symbolica")</code> for Symbolica built-ins.
A replacement does not match	Repeated wildcards would have to capture different expressions.	Check that every occurrence of the wildcard should match the same value.
An exact solver errors	An equation was not rearranged to zero, or the system is outside the supported polynomial scope.	Move every term to the left; try <code>nsolve-system</code> for a numerical branch.

Symptom	Likely cause	What to try
A numerical solver errors or finds an unwanted root	The starting point leads to a different root or no root.	Try another physically meaningful initial guess and check residuals.
A matrix operation errors	Shapes differ, a matrix is singular, or an entry is unsupported.	Inspect <code>matrix-shape</code> , <code>det</code> , and the coefficient expressions.

5 API reference

The worked chapters are meant for reading; this section is meant for looking things up. Functions are grouped by the kind of calculation they perform.

5.1 Parsing, symbols, and rendering

5.1.1 math

Parse Typst math content into an opaque Symbolica atom payload.

Arithmetic, fractions, powers, roots, absolute values, calls, and common Typst math structures are translated through the configured grammar. Matrix-valued `mat(...)` and `vec(...)` content must instead be passed to `matrix` or `vec`. Keep the returned bytes opaque and use this module's functions to inspect or transform them.

```
#let expr = math($x + 1$)
#to-typst(expr)
```

 $1 + x$

Parameters

```
math(
  eqn: content,
  grammar: dictionary | none,
  namespace: str | none
) -> bytes
```

eqn `content`

Math content, normally written as `$...$`.

grammar `dictionary` or `none`

Parser grammar override. `none` uses the default engine grammar.

Default: `none`

namespace `str` or `none`

Namespace for parsed symbols. `none` uses the engine namespace ("`typst`" for the top-level function).

Default: `none`

5.1.2 atom

Convert a supported Typst value or math expression into an atom payload.

Existing atom bytes pass through unchanged. Content is parsed like `math`; integers and floats become numbers. Strings are parsed as leaf values: numeric strings become numbers and other strings become symbols in the engine's namespace. Matrix payloads are not atom payloads and should not be passed to atom-only algebra functions.

```
#to-tpst(atom("x"))
```

 x

Parameters

```
atom(value: bytes content int float str) -> bytes
```

value bytes or content or int or float or str

Value to convert.

5.1.3 var

Construct a named Symbolica variable.

Unlike wild, this is an ordinary mathematical symbol and therefore does not capture subexpressions during pattern matching.

```
#to-tpst(var("x"))
```

 x

Parameters

```
var(
  name: str,
  namespace: str none
) -> bytes
```

name str

Symbol name without a namespace prefix or wildcard suffix.

namespace str or none

Namespace override. none uses the engine namespace.

Default: none

5.1.4 wild

Construct a Symbolica pattern wildcard.

This creates the symbol name followed by level underscores. A wildcard is a pattern placeholder used by rule, replace, and replace-wildcards; it is not an ordinary unknown for algebra or solving. Use var for a mathematical variable.

```
#raw(canonical(wild("a")))
```

 $a_$

Parameters

```
wild(
  name: str,
  level: int,
  namespace: str none
) -> bytes
```

name `str`

Base name of the wildcard, without trailing underscores.

level `int`Number of underscore levels to append. 1 creates a conventional single wildcard such as `a_`; 0 appends no underscore and therefore creates an ordinary symbol instead.Default: `1`**namespace** `str` or `none`Namespace override. `none` uses the engine namespace.Default: `none`

5.1.5 array-tree

Render the parse tree for a Typst math expression.

This is a diagnostic view of the tree consumed by `math`; it does not create a Symbolica atom.`#array-tree($(x + 1)^2$)`

```
(
  strong(body: raw(text: "pow")),
  (
    styled(child: raw(text: "base"), ..),
    (
      strong(body: raw(text: "()")),
      (
        styled(child: raw(text: "expr"), ..),
        (
          strong(body: raw(text: "add")),
          equation(body: [x]),
          equation(body: [1]),
        ),
      ),
    ),
  ),
),
(
  styled(child: raw(text: "exp"), ..),
  equation(body: [2]),
),
)
```

Parameters

```
array-tree(
  eqn: content,
  grammar: dictionary none
) -> content
```

eqn `content`

Math content to inspect.

grammar dictionary or none

Parser grammar override. none uses the engine grammar.

Default: none

5.1.6 canonical

Render an atom or matrix payload as Symbolica source text.

```
#raw(canonical(math($x + 1$)))
```

1+x

Parameters

```
canonical(
  expr: bytes content int float str,
  namespaces: bool
) -> str
```

expr bytes or content or int or float or str

Atom or matrix payload. Other supported expression values are first converted as by atom.

namespaces bool

Include symbol namespaces in the output.

Default: false

5.1.7 to-typst-source

Render an atom or matrix payload as Typst math source.

```
#raw(to-typst-source(math($x + 1$)))
```

1+x

Parameters

```
to-typst-source(expr: bytes content int float str) -> str
```

expr bytes or content or int or float or str

Atom or matrix payload, or a supported expression value.

5.1.8 to-typst

Render an atom or matrix payload as evaluated Typst math content.

The payload is first printed as Typst math source and then evaluated in math mode. Use to-typst-source when you need the source string instead.

```
#to-typst(math($x + 1$))
```

$$1 + x$$

Parameters

```
to-typst(
  expr: bytes content int float str,
  block: bool
) -> content
```

expr bytes or content or int or float or str

Atom or matrix payload, or a supported expression value.

block bool

Render as a block equation instead of inline math.

Default: `false`

5.1.9 to-latex

Render an atom or matrix payload as LaTeX source.

```
#raw(to-latex(math($x^2 + 1$)))
```

$$1+x^{\{2\}}$$

Parameters

```
to-latex(expr: bytes content int float str) -> str
```

expr bytes or content or int or float or str

Atom or matrix payload, or a supported expression value.

5.2 Algebra and calculus

5.2.1 simplify

Re-import and re-export an atom in Symbolica's canonical internal form.

This operation does not perform algebraic simplification; it currently acts as a normalization and validation round-trip for atom payloads.

```
#to-typst(simplify(math($x + 0$)))
```

$$x$$

Parameters

```
simplify(expr: bytes content int float str) -> bytes
```

expr bytes or content or int or float or str

Atom payload or supported expression value to normalize.

5.2.2 expand

Expand an expression through Symbolica's polynomial expansion.

```
#to-typst(expand(math($(x + 1)^2$)))
```

$$1 + 2x + x^2$$

Parameters

```
expand(expr: bytes content int float str) -> bytes
```

expr bytes or content or int or float or str

Atom payload or supported expression value to expand.

5.2.3 factor

Factor an expression with Symbolica's exact factorization routine.

```
#to-typst(factor(math($x^2 + 2 x + 1$)))
```

$$(1 + x)^2$$

Parameters

```
factor(expr: bytes content int float str) -> bytes
```

expr bytes or content or int or float or str

Atom payload or supported expression value to factor.

5.2.4 derivative

Differentiate an expression exactly with respect to an indeterminate.

```
#let x = var("x")
#to-typst(derivative(math($(x + 1)^2$), x))
```

$$2(1 + x)$$

Parameters

```
derivative(
  expr: bytes content int float str,
  var: bytes content str
) -> bytes
```

expr bytes or content or int or float or str

Expression to differentiate.

var bytes or content or str

Symbolica indeterminate, normally created with var.

5.2.5 integrate

Integrate a polynomial exactly with respect to a variable.

The expression must be polynomial in `var`; rational functions with a non-constant denominator and general transcendental integrands are rejected. No arbitrary integration constant is added.

```
#let x = var("x")
#to-tyrst(integrate(math($3 x^2 - 4 x + 7$),
x))
```

$$7x - 2x^2 + x^3$$

Parameters

```
integrate(
  expr: bytes content int float str,
  var: bytes content str
) -> bytes
```

expr bytes or content or int or float or str

Polynomial expression to integrate.

var bytes or content or str

Integration variable, normally created with `var`.

5.2.6 integrate-with-steps

Integrate a polynomial and expose one contribution per expanded term.

This has the same polynomial-only restriction as `integrate`. It returns `(result: bytes, steps: array)`, where `result` is the complete antiderivative and every atom payload in `steps` is the antiderivative of one top-level term after Symbolica expands and canonically normalizes the input. A non-sum has one step; source terms may combine or cancel during expansion. Thus `steps` is a deterministic term-by-term decomposition, not a general pedagogical derivation trace. No integration constant is added.

```
#let x = var("x")
#let out = integrate-with-steps(math($3 x^2 - 4
x + 7$), x)
#to-tyrst(out.result)
#out.steps.map(to-tyrst).join[, ]
```

$$7x - 2x^2 + x^3 \quad 7x, \quad -2x^2, \quad x^3$$

Parameters

```
integrate-with-steps(
  expr: bytes content int float str,
  var: bytes content str
) -> dictionary
```

expr bytes or content or int or float or str

Polynomial expression to integrate.

var bytes or content or str

Integration variable, normally created with `var`.

5.2.7 series

Compute a univariate series expansion around expansion-point.

The truncation depth is the rational number depth / depth-denom. With an absolute depth it is measured directly in var; with a relative depth it is measured from the lowest order encountered in the expression.

```
#let sym = init(namespace: "symbolica")
#let m = sym.math
#let v = sym.var
#let ser = sym.series
#let render = sym.to-tyrst
#render(ser(m($cos(x)/(x + 1)$), v("x"), 0, 3))
```

$$1 - x + \frac{1}{2}x^2 - \frac{1}{2}x^3$$

Parameters

```
series(
  expr: bytes content int float str,
  var: bytes content str,
  expansion-point: bytes content int float str,
  depth: int,
  depth-denom: int,
  depth-is-absolute: bool
) -> bytes
```

expr bytes or content or int or float or str

Expression to expand.

var bytes or content or str

Expansion variable, normally created with var.

expansion-point bytes or content or int or float or str

Point about which to expand.

depth int

Numerator of the requested truncation depth.

depth-denom int

Denominator of the truncation depth.

Default: 1

depth-is-absolute bool

Use an absolute depth when true, or a depth relative to the lowest order in the expression when false.

Default: true

5.3 Rewriting

5.3.1 rule

Build a reusable replacement rule for replace-multiple.

pattern and rhs may contain symbols created with wild. The returned dictionary contains opaque atom payloads plus the matching options; pass it to replace-multiple rather than editing it manually.

```
#let r = rule(math($f("a_")$), math($g("a_")$))
#to-tyrst(replace-multiple(math($f(x)$), (r,)))
```

 $g(x)$

Parameters

```
rule(
  pattern: bytes content int float str,
  rhs: bytes content int float str,
  non-greedy-wildcards: array,
  min-level: int,
  max-level: int none,
  level-range: array none,
  level-is-tree-depth: bool,
  partial: bool,
  allow-new-wildcards-on-rhs: bool,
  rhs-cache-size: int
) -> dictionary
```

pattern bytes or content or int or float or str

Pattern to match.

rhs bytes or content or int or float or str

Expression substituted for each match. Wildcards captured by pattern are substituted in this expression.

non-greedy-wildcards array

Wildcards that should prefer the smallest possible match.

Default: ()

min-level int

Lowest expression level at which matching is allowed; the root is level zero.

Default: 0

max-level int or none

Highest allowed matching level, or none for no upper bound.

Default: none

level-range array or none

Optional (minimum, maximum) pair overriding min-level and max-level; the maximum may be none.

Default: none

level-is-tree-depth bool

Count full expression-tree depth when true; otherwise levels increase when entering functions.

Default: `false`

partial `bool`

Allow a pattern to match part of a sum, product, or other term instead of requiring the whole term.

Default: `true`

allow-new-wildcards-on-rhs `bool`

Permit wildcards on rhs that do not occur in pattern. When false, such rules are rejected.

Default: `false`

rhs-cache-size `int`

Maximum number of substituted right-hand sides cached; use zero to disable this cache.

Default: `100`

5.3.2 replace

Replace subexpressions matching pattern with rhs.

By default all non-overlapping outermost matches are replaced once. `repeat: true` reapplies the rule until the expression stops changing; rules that cycle therefore do not terminate. Use rule plus `replace-multiple` when several patterns must be considered together.

```
#to-tyrst(replace(math($f(x, y)$),
  math($f("a_", "b_")$), math($g("b_", "a_")$)))
```

$$g(y, x)$$

Parameters

```
replace(
  expr: bytes content int float str,
  pattern: bytes content int float str,
  rhs: bytes content int float str,
  repeat: bool,
  once: bool,
  bottom-up: bool,
  nested: bool,
  non-greedy-wildcards: array,
  min-level: int,
  max-level: int none,
  level-range: array none,
  level-is-tree-depth: bool,
  partial: bool,
  allow-new-wildcards-on-rhs: bool,
  rhs-cache-size: int
) -> bytes
```

expr bytes or content or int or float or str

Expression in which to replace matches.

pattern bytes or content or int or float or str

Pattern to match.

rhs bytes or content or int or float or str

Replacement expression.

repeat bool

Reapply the rule until it makes no further change.

Default: false

once bool

Replace only the first match found during a pass.

Default: false

bottom-up bool

Visit deepest matches before outer matches.

Default: false

nested bool

Replace nested matches from the deepest outward, acting on the result of each inner replacement.

Default: false

non-greedy-wildcards array

Wildcards that should prefer the smallest possible match.

Default: ()

min-level int

Lowest allowed matching level; the root is level zero.

Default: 0

max-level int or none

Highest allowed matching level, or none for no upper bound.

Default: none

level-range array or none

Optional (minimum, maximum) pair overriding min-level and max-level.

Default: none

level-is-tree-depth `bool`

Count full tree depth instead of function-entry depth.

Default: `false`

partial `bool`

Allow matching a part of a term rather than the entire term.

Default: `true`

allow-new-wildcards-on-rhs `bool`

Permit rhs wildcards that are absent from pattern.

Default: `false`

rhs-cache-size `int`

Maximum number of substituted right-hand sides cached; zero disables the cache.

Default: `100`

5.3.3 replace-multiple

Apply several reusable replacement rules together.

The traversal options apply to the combined rule set. With `repeat: true`, the complete set is reapplied until no rule changes the expression; cyclic rule sets do not terminate.

```
#let r1 = rule(math($f("a_")$),
math($h("a_")$))
#let r2 = rule(var("x"), var("z"))
#to-tyrst(replace-multiple(math($f(x) + x$),
(r1, r2)))
```

$$z + h(x)$$

Parameters

```
replace-multiple(
  expr: bytes content int float str,
  rules: array,
  repeat: bool,
  once: bool,
  bottom-up: bool,
  nested: bool
) -> bytes
```

expr bytes or content or int or float or str

Expression in which to replace matches.

rules array

Array of dictionaries returned by rule.

repeat bool

Reapply the rule set until it makes no further change.

Default: `false`

once bool

Replace only the first match found during a pass.

Default: `false`

bottom-up bool

Visit deepest matches before outer matches.

Default: `false`

nested bool

Replace nested matches from deepest to outermost, acting on intermediate results.

Default: `false`

5.3.4 replace-wildcards

Substitute explicit values for wildcard placeholders in a pattern.

This does not search another expression. It transforms pattern itself and requires each key in replacements to be a wildcard symbol.

```
#to-tyrst(replace-wildcards(math($k("a_")$),
((wild("a"), math($x + 1$))),))
```

$$k(1 + x)$$

Parameters

```
replace-wildcards(
  pattern: bytes content int float str,
  replacements: array
) -> bytes
```

pattern bytes or content or int or float or str

Pattern containing wildcards to substitute.

replacements array

Array of (wildcard, replacement) pairs.

5.4 Evaluation and solving

5.4.1 evaluate

Evaluate one expression numerically with optional substitutions.

values maps atom keys to real numbers or complex dictionaries of the form (re: number, im: number). Evaluation must eliminate every unsupported symbolic quantity. The result always has the exact shape (re: float, im: float), even when it is real.

```
#let x = var("x")
#let y = var("y")
#repr(evaluate(math($x^2 + y$), values: ((x,
2.0), (y, 3.0))))
```

```
(re: 7.0, im: 0.0)
```

Parameters

```
evaluate(
  expr: bytes content int float str,
  values: array
) -> dictionary
```

expr bytes or content or int or float or str

Expression to evaluate.

values array

Array of (expression, value) substitution pairs. Values may be real numbers or (re: ..., im: ...) dictionaries.

Default: ()

5.4.2 domain

Describe one real sampling axis for evaluate-grid.

Both endpoints are included when samples is greater than one. A single-sample domain evaluates only at min. The returned dictionary has the exact shape (min: float, max: float, samples: int).

```
#repr(domain(-1, 1, samples: 3))
```

```
(min: -1.0, max: 1.0, samples: 3)
```

Parameters

```
domain(
  min: int float,
  max: int float,
  samples: int
) -> dictionary
```

min int or float

Finite lower endpoint; it must be less than max.

max int or float

Finite upper endpoint.

samples int

Number of evenly spaced points. Must be positive.

Default: 200

5.4.3 evaluate-many

Evaluate one or more expressions at explicit points in one batch.

A single expression or variable may be passed directly; otherwise use an array. Every point must supply one real or complex value per variable. The result has one row per point in input order and one (re: float, im: float) dictionary per expression in expression order.

```
#let x = var("x")
#let y = var("y")
#let rows = evaluate-many((math($x + y$),
math($x y$)), (x, y), ((1, 2), (3, 4)))
#repr(rows)
```

```
(
  ((re: 3.0, im: 0.0), (re: 2.0, im: 0.0)),
  ((re: 7.0, im: 0.0), (re: 12.0, im: 0.0)),
)
```

Parameters

```
evaluate-many(
  expressions: bytes content array int float str,
  variables: bytes content array str,
  points: array
) -> array
```

expressions bytes or content or array or int or float or str

One expression or a non-empty array of expressions to evaluate.

variables bytes or content or array or str

One variable or an array defining input-column order.

points array

Array of input rows. Each row is an array ordered like variables; for one variable, a scalar point is also accepted.

5.4.4 evaluate-grid

Evaluate expressions over a Cartesian product of real domains in one batch.

The result is (shape: array, points: array, values: array). shape lists the sample count of every domain. The grid axes are flattened into rows with the last domain varying fastest: each points row contains real coordinates in variable order, while the corresponding values row contains one (re: float, im: float) dictionary per expression.

```
#let x = var("x")
#let y = var("y")
#let grid = evaluate-grid(math($x^2 + y$), (x,
y), (domain(-1, 1, samples: 3), domain(0, 1,
samples: 2)))
shape: #repr(grid.shape); values:
#repr(grid.values)
```



```
shape: (3, 2) values: (
  ((re: 1.0, im: 0.0),),
  ((re: 2.0, im: 0.0),),
  ((re: 0.0, im: 0.0),),
  ((re: 1.0, im: 0.0),),
  ((re: 1.0, im: 0.0),),
  ((re: 2.0, im: 0.0),),
)
```

Parameters

```
evaluate-grid(
  expressions: bytes content array int float str,
  variables: bytes content array str,
  domains: array
) -> dictionary
```

expressions bytes or content or array or int or float or str

One expression or a non-empty array of expressions.

variables bytes or content or array or str

One variable or an array defining grid-axis order.

domains array

One domain dictionary per variable, in the same order.

5.4.5 solve-linear

Solve a linear system exactly for variables.

Each item in system is interpreted as an expression equal to zero. A vector matrix may be supplied instead of an array. The returned array contains one atom payload per item in variables, in the same order. For an underdetermined system, bound variables may be expressed using free variables; Symbolica chooses the highest-indexed variables as free. Inconsistent or nonlinear systems produce an error.

```
#let x = var("x")
#let y = var("y")
#let sol = solve-linear((math($2 x + y - 5$),
math($x - y - 1$)), (x, y))
#sol.map(to-tpst).join[, ]
```

```
2, 1
```

Parameters

```
solve-linear(
  system: array bytes content int float str,
  variables: array content str
) -> array
```

system array or bytes or content or int or float or str

Linear expressions understood to equal zero, as an array or vector matrix.

variables array or content or str

Variables to solve for, in result order.

5.4.6 solve-system

Solve a linear or supported polynomial nonlinear system exactly.

Each expression in system is understood to equal zero. Polynomial systems are solved exactly through Symbolica's Gröbner-basis and algebraic-root machinery; coefficients may contain symbolic parameters when Symbolica can treat them rationally. The result is an array of solution rows. Every row contains one atom payload per requested variable, in variables order; an empty array means there are no solutions.

```
#let x = var("x")
#let y = var("y")
#let solutions = solve-system((math($x^2 - 1$),
math($y - x$)), (x, y))
#repr(solutions.map(row => row.map(canonical)))
```

```
(("-1", "-1"), ("1", "1"))
```

Parameters

```
solve-system(
  system: array content int float str,
  variables: array content str
) -> array
```

system array or content or int or float or str

Expressions understood to equal zero.

variables array or content or str

Variables to eliminate and return, in result-column order.

5.4.7 nsolve

Find a real root of a univariate expression with Newton's method.

The expression is interpreted as equal to zero and evaluated with f64 arithmetic. Convergence is local and depends on init; failure to converge within max-iterations produces an error.

```
#let x = var("x")
#repr(nsolve(math($x^2 - 2$), x, 1.0))
```

```
1.4142135623746899
```

Parameters

```
nsolve(
  expr: bytes content int float str,
  var: bytes content str,
  init: int float,
  prec: int float,
```

```
max-iterations: int
) -> float
```

expr bytes or content or int or float or str

Expression understood to equal zero.

var bytes or content or str

Real solve variable, normally created with var.

init int or float

Initial real guess.

prec int or float

Numerical tolerance for the Newton iteration.

Default: $1e-4$

max-iterations int

Maximum number of Newton iterations.

Default: 1000

5.4.8 nsolve-system

Find a common real root of a system with multivariate Newton iteration.

Every expression is interpreted as equal to zero. variables and init must have matching lengths, and the returned floats follow that same order. Convergence is local and is not guaranteed for an arbitrary initial guess.

```
#let x = var("x")
#let y = var("y")
#repr(nsolve-system((math($x^2 + y - 3$),
math($x - y$)), (x, y), (1.0, 1.0)))
```

```
(1.3027756377319948, 1.3027756377319948)
```

Parameters

```
nsolve-system(
  system: array content int float str,
  variables: array content str,
  init: array,
  prec: int float,
  max-iterations: int
) -> array
```

system array or content or int or float or str

Expressions understood to equal zero.

variables array or content or str

Variables to solve for, in result order.

init `array`

Initial real value for every variable.

prec `int` or `float`

Numerical tolerance for the Newton iteration.

Default: `1e-4`

max-iterations `int`

Maximum number of Newton iterations.

Default: `1000`

5.5 Matrices

5.5.1 matrix

Convert Typst values into an opaque Symbolica matrix payload.

Accepted forms are Typst math `mat(...)` or `vec(...)`, a non-empty rectangular nested array, a flat array interpreted as a column vector, a scalar interpreted as a one-by-one matrix, or an existing payload. Every entry must be convertible to a rational polynomial; general transcendental expressions are not valid matrix entries.

```
#to-typst(matrix($mat(1, 2; 3, 4)$))
```

$$\begin{pmatrix} 1 & 2 \\ 3 & 4 \end{pmatrix}$$

Parameters

`matrix(value: bytes | content | array | int | float | str) -> bytes`

value `bytes` or `content` or `array` or `int` or `float` or `str`

Matrix source value.

5.5.2 vec

Convert a non-empty sequence into a column-vector matrix payload.

Array entries must be rational-polynomial compatible. Typst math `vec(...)` is accepted directly; existing matrix bytes pass through unchanged.

```
#to-typst(vec((1, 2)))
```

$$\begin{pmatrix} 1 \\ 2 \end{pmatrix}$$

Parameters

`vec(values: array | content | bytes) -> bytes`

values `array` or `content` or `bytes`

Vector entries, Typst `vec(...)` content, or an existing matrix payload.

5.5.3 identity

Create an n by n identity matrix payload.

```
#to-tpst(identity(2))
```

$$\begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix}$$

Parameters

```
identity(n: int) -> bytes
```

n int

Positive matrix dimension.

5.5.4 eye

Create a square diagonal matrix from a non-empty entry array.

Every entry must be rational-polynomial compatible.

```
#to-tpst(eye((1, 2)))
```

$$\begin{pmatrix} 1 & 0 \\ 0 & 2 \end{pmatrix}$$

Parameters

```
eye(diag: array) -> bytes
```

diag array

Diagonal entries in top-left to bottom-right order.

5.5.5 matrix-add

Add two matrices entry by entry.

The matrices must have equal shapes. Matrix source values accepted by matrix may be supplied directly.

```
#to-tpst(matrix-add(matrix(((1, 2), (3, 4))),  
identity(2)))
```

$$\begin{pmatrix} 2 & 2 \\ 3 & 5 \end{pmatrix}$$

Parameters

```
matrix-add(  
  lhs: bytes content array int float str,  
  rhs: bytes content array int float str  
) -> bytes
```

lhs bytes or content or array or int or float or str

Left matrix.

rhs bytes or content or array or int or float or str

Right matrix of the same shape.

5.5.6 matrix-sub

Subtract two matrices entry by entry.

The matrices must have equal shapes. Matrix source values accepted by `matrix` may be supplied directly.

```
#to-typst(matrix-sub(matrix(((1, 2), (3, 4))),
identity(2)))
```

$$\begin{pmatrix} 0 & 2 \\ 3 & 3 \end{pmatrix}$$

Parameters

```
matrix-sub(
  lhs: bytes content array int float str,
  rhs: bytes content array int float str
) -> bytes
```

lhs bytes or content or array or int or float or str

Left matrix.

rhs bytes or content or array or int or float or str

Right matrix of the same shape.

5.5.7 matrix-mul

Multiply two matrices, or multiply a matrix by a scalar expression.

Matrix multiplication requires compatible inner dimensions. A scalar must be rational-polynomial compatible. Because opaque bytes are interpreted as matrix payloads in the right-hand position, pass scalar atoms as ordinary values or math content rather than as preconstructed atom bytes.

```
#to-typst(matrix-mul(matrix(((1, 2), (3, 4))),
identity(2)))
```

$$\begin{pmatrix} 1 & 2 \\ 3 & 4 \end{pmatrix}$$

Parameters

```
matrix-mul(
  lhs: bytes content array int float str,
  rhs: bytes content array int float str
) -> bytes
```

lhs bytes or content or array or int or float or str

Left matrix.

rhs bytes or content or array or int or float or str

Right matrix, or scalar Typst value/math content.

5.5.8 matrix-div-scalar

Divide every matrix entry by a nonzero scalar expression.

The scalar must be rational-polynomial compatible.

```
#to-tyrst(matrix-div-scalar(matrix(((2, 4), (6, 8))), 2))
```

$$\begin{pmatrix} 1 & 2 \\ 3 & 4 \end{pmatrix}$$

Parameters

```
matrix-div-scalar(
  lhs: bytes content array int float str,
  rhs: bytes content int float str
) -> bytes
```

lhs bytes or content or array or int or float or str

Matrix dividend.

rhs bytes or content or int or float or str

Nonzero scalar divisor.

5.5.9 transpose

Transpose a matrix, exchanging rows and columns.

```
#to-tyrst(transpose(matrix(((1, 2), (3, 4)))))
```

$$\begin{pmatrix} 1 & 3 \\ 2 & 4 \end{pmatrix}$$

Parameters

```
transpose(matrix: bytes content array int float str) -> bytes
```

matrix bytes or content or array or int or float or str

Matrix to transpose.

5.5.10 det

Compute the exact determinant of a square matrix.

The result is an atom payload rather than a matrix payload.

```
#to-tyrst(det(matrix(((1, 2), (3, 4)))))
```

−2

Parameters

```
det(matrix: bytes content array int float str) -> bytes
```

matrix bytes or content or array or int or float or str

Square matrix.

5.5.11 inv

Compute the exact inverse of an invertible square matrix.

Singular and non-square matrices produce an error.

```
#to-typst(inv(matrix(((1, 2), (3, 4)))))
```

$$\begin{pmatrix} -2 & 1 \\ \frac{3}{2} & -\frac{1}{2} \end{pmatrix}$$

Parameters

```
inv(matrix: bytes | content | array | int | float | str) -> bytes
```

matrix bytes or content or array or int or float or str

Invertible square matrix.

5.5.12 matrix-solve

Solve the matrix equation $A \cdot x = b$ exactly.

The row counts of A and b must agree. This strict solver reports an error when the system does not have the required unique solution; use `matrix-solve-any` for underdetermined systems.

```
#let A = matrix($mat(2, 1; 1, -1)$)
#let b = vec((5, 1))
#to-typst(matrix-solve(A, b))
```

$$\begin{pmatrix} 2 \\ 1 \end{pmatrix}$$

Parameters

```
matrix-solve(
  A: bytes | content | array | int | float | str,
  b: bytes | content | array | int | float | str
) -> bytes
```

A bytes or content or array or int or float or str

Coefficient matrix.

b bytes or content or array or int or float or str

Right-hand-side matrix or column vector.

5.5.13 matrix-solve-any

Solve $A \cdot x = b$ exactly, choosing one solution if underdetermined.

The row counts of A and b must agree. An inconsistent system still produces an error.

```
#let A = matrix($mat(2, 1; 1, -1)$)
#let b = vec((5, 1))
#to-typst(matrix-solve-any(A, b))
```

$$\begin{pmatrix} 2 \\ 1 \end{pmatrix}$$

Parameters

```
matrix-solve-any(
  A: bytes | content | array | int | float | str,
  b: bytes | content | array | int | float | str
) -> bytes
```


A bytes or content or array or int or float or str

Coefficient matrix.

b bytes or content or array or int or float or str

Right-hand-side matrix or column vector.

5.5.14 row-reduce

Row-reduce a matrix exactly using Gaussian elimination.

Returns (matrix: bytes, rank: int). By default every column may contain a pivot. Set max-col to limit pivot search to the first max-col columns, which is useful for an augmented matrix whose trailing columns are right-hand sides; all columns are still transformed by the row operations.

```
#let rr = row-reduce(matrix(((1, 2), (3, 4))))
rank #rr.rank: #to-tyrst(rr.matrix)
```

rank 2: $\begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix}$

Parameters

```
row-reduce(
  matrix: bytes content array int float str,
  max-col: int none
) -> dictionary
```

matrix bytes or content or array or int or float or str

Matrix to reduce.

max-col int or none

Number of leading columns eligible for pivots. none uses every column. An explicit value must be between zero and the column count.

Default: none

5.5.15 augment

Horizontally concatenate two matrices as [lhs rhs].

Both matrices must have the same number of rows.

```
#to-tyrst(augment(identity(2), matrix(((1, 2),
(3, 4)))))
```

$\begin{pmatrix} 1 & 0 & 1 & 2 \\ 0 & 1 & 3 & 4 \end{pmatrix}$

Parameters

```
augment(
  lhs: bytes content array int float str,
  rhs: bytes content array int float str
) -> bytes
```

lhs bytes or content or array or int or float or str

Left block.

rhs bytes or content or array or int or float or str

Right block with the same row count.

5.5.16 split-col

Split a matrix into left and right column blocks.

Returns exactly (left, right), both as matrix payloads. The current matrix backend requires $\text{index} > 0$ and $\text{index} < \text{columns} - 1$.

```
#let aug = augment(identity(2), matrix(((1, 2),
(3, 4))))
#let parts = split-col(aug, 2)
#to-tyrst(parts.at(0)) | #to-tyrst(parts.at(1))
```

$$\begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix} \mid \begin{pmatrix} 1 & 2 \\ 3 & 4 \end{pmatrix}$$

Parameters

```
split-col(
  matrix: bytes content array int float str,
  index: int
) -> array
```

matrix bytes or content or array or int or float or str

Matrix to split.

index int

Zero-based first column of the right block.

5.5.17 primitive-part

Divide a rational-polynomial matrix by its content.

The result is the primitive matrix whose coefficient GCD has been removed.

```
#let x = var("x")
#let P = matrix(((mul(2, x), mul(4, x)),
(mul(6, x), mul(8, x))))
#to-tyrst(primitive-part(P))
```

$$\begin{pmatrix} 1 & 2 \\ 3 & 4 \end{pmatrix}$$

Parameters

```
primitive-part(matrix: bytes content array int float str) -> bytes
```

matrix bytes or content or array or int or float or str

Matrix whose entries are rational polynomials.

5.5.18 content

Compute the coefficient content of a rational-polynomial matrix.

The content is the common coefficient GCD and is returned as an atom payload.

```
#let x = var("x")
#let P = matrix(((mul(2, x), mul(4, x)),
(mul(6, x), mul(8, x))))
#to-tyrst(content(P))
```

$2x$

Parameters

`content(matrix: bytes content array int float str) -> bytes`

matrix bytes or content or array or int or float or str

Matrix whose entries are rational polynomials.

5.5.19 matrix-at

Read one matrix entry as an atom payload using zero-based indices.

```
#let A = matrix(((1, 2), (3, 4)))
#to-tyrst(matrix-at(A, 0, 1))
```

2

Parameters

```
matrix-at(
  matrix: bytes content array int float str,
  row: int,
  col: int
) -> bytes
```

matrix bytes or content or array or int or float or str

Matrix to index.

row int

Zero-based row index. Must be within the matrix bounds.

col int

Zero-based column index. Must be within the matrix bounds.

5.5.20 matrix-shape

Return the matrix shape as the two-element array (rows, columns).

```
#repr(matrix-shape(matrix(((1, 2), (3, 4)))))
```

(2, 2)

Parameters

`matrix-shape(matrix: bytes content array int float str) -> array`

matrix bytes or **content** or array or **int** or **float** or **str**

Matrix to inspect.

5.6 Scalar constructors

5.6.1 add

Construct an exact sum from expression values.

Arguments are converted as by atom. With no arguments, the result is the additive identity zero.

```
#to-tyrst(add("x", 1, "y"))
```

 $1 + x + y$

Parameters

`add(..terms: arguments) -> bytes`

..terms arguments

Positional terms to add.

5.6.2 mul

Construct an exact product from expression values.

Arguments are converted as by atom. With no arguments, the result is the multiplicative identity one.

```
#to-tyrst(mul(2, "x", "y"))
```

 $2xy$

Parameters

`mul(..factors: arguments) -> bytes`

..factors arguments

Positional factors to multiply.

5.6.3 neg

Negate an expression exactly.

```
#to-tyrst(neg("x"))
```

 $-x$

Parameters

`neg(expr: bytes content int float str) -> bytes`

expr bytes or **content** or **int** or **float** or **str**

Expression to negate.

5.6.4 sub

Subtract rhs from lhs exactly.

```
#to-tyrst(sub("x", "y"))
```

$$x - y$$

Parameters

```
sub(
  lhs: bytes content int float str,
  rhs: bytes content int float str
) -> bytes
```

lhs bytes or content or int or float or str

Minuend.

rhs bytes or content or int or float or str

Subtrahend.

5.6.5 div

Construct the exact quotient lhs / rhs.

```
#to-tyrst(div(1, "x"))
```

$$\frac{1}{x}$$

Parameters

```
div(
  lhs: bytes content int float str,
  rhs: bytes content int float str
) -> bytes
```

lhs bytes or content or int or float or str

Numerator.

rhs bytes or content or int or float or str

Denominator.

5.6.6 pow

Construct the exact power base ^ exp.

```
#to-tyrst(pow("x", 3))
```

$$x^3$$

Parameters

```
pow(
  base: bytes content int float str,
```

```
exp: bytes content int float str
) -> bytes
```

base bytes or content or int or float or str

Base expression.

exp bytes or content or int or float or str

Exponent expression.

5.7 Advanced configuration

5.7.1 init

Create an independent set of Tymbolica functions.

The returned dictionary exposes the same parsing, algebra, evaluation, solving, and matrix operations as the top-level API. Use it when you need a different symbol namespace, plugin location, or parser grammar; ordinary calculations can use the imported top-level functions directly.

```
#let sym = init(namespace: "physics")
#let v = sym.var
#let render = sym.canonical
#raw(render(v("x"), namespaces: true))
```

```
physics::x
```

Parameters

```
init(
  namespace: str,
  source: str,
  grammar: dictionary
) -> dictionary
```

namespace str

Default namespace for symbols parsed from Typst math or strings. A per-call namespace passed to math or var takes precedence.

Default: "typst"

source str

WebAssembly plugin path passed to Typst's plugin constructor. Relative paths are resolved by Typst from this source file.

Default: "tymbolica.wasm"

grammar dictionary

Parser grammar used by math and array-tree unless they receive an explicit override.

Default: _default_grammar

6 Compatibility and licensing

This manual describes Tymbolica 0.1.0. The package is tested with Typst 0.14 or newer.

Tymbolica's original source code is released under the [MIT License](#). Symbolica is developed by the Symbolica contributors and is distributed under its own [license terms](#). The MIT License does not relicense Symbolica or the bundled WebAssembly artifact; Symbolica's terms still apply to their use.

For source, issues, and release history, visit github.com/lcnbr/tymbolica.

7 Acknowledgements

Tymbolica would not exist without [Symbolica](#). Thank you to its contributors for building and sharing the algebra engine at the heart of this package.

Thanks also to [Parsely](#), which makes it possible to work with mathematics written directly in Typst, and to [Tidy](#), which powers this manual's examples and reference pages.