

Single Page Applications

Mendel Rosenblum

Web Apps and Browsers

- Web apps run in browsers (by definition)
- Users are use to browsing in browsers
 - Browser maintains a history of URLs visited
 - Back button - Go back in history to previous URL
 - Forward button - Go forward in history to next URL
 - Can move to a different page
 - Typing into location bar or forward/back buttons
 - Selecting a bookmarked URL
 - Page refresh operation
- Browser tosses the current JavaScript environment when navigating to a different page
 - Problematic for JavaScript frameworks: URL (and cookies) are the only information preserved


Problem with some web apps

- Initial: pages served from web server
 - Each page had a URL and app switched between pages served by web server
- Early JavaScript apps: Website a single page/URL with the JavaScript

Problem: Restart web app on navigation (Can lose a lot of work!)

```
window.onbeforeunload = function(e) { return 'All will be lost!'; }
```

- Users expect app in browser to do the right thing:
 - Navigate with forward and back buttons, browser page history
 - Navigate away and come back to the app
 - Bookmark a place in the app
 - Copy the URL from the location bar and share it with someone
 - Push the page refresh button on the browser



Changing URL without page refresh

- Can change hash fragment in URL without reload

`http://example.com`

`http://example.com#fragment`

`http://example.com?id=3535`

`http://example.com?id=3535#fragment`

- HTML5 give JavaScript control of page reload
 - Browser History API - `window.history` - Change URL without reloading page

Deep linking

- Concept: the URL should capture the web app's context so that directing the browser to the URL will result the app's execution to that context
 - Bookmarks
 - Sharing

- Context is defined by the user interface designer!

Consider: Viewing information of entity and have an edit dialog open

Should the link point to the entity view or to the entity & dialog?

Does it matter if I'm bookmarking for self or sharing with others?

How about navigating away and back or browser refresh?

Deep linking in Single Page Apps

Two approaches:

1. Maintain the app's context state in the URL
 - + Works for browser navigation and refresh
 - + User can copy URL from location bar
2. Provide a share button to generate deep linking URL
 - + Allows user to explicitly fetch a URL based on need
 - + Can keep URL in location bar pretty

Either way web app needs to be able to initialize self from deep linked URL

Ugly URLs

`http://www.example.org/dirmod?sid=789AB8&type=gen&mod=Core+Pages&gid=A6CD4967199`

versus

`http://www.example.org/show/A6CD4967199`

What is that ugly thing in the location bar above my beautiful web application?

`https://www.flickr.com/photos/jarnasen/24593000826/in/explore-2016-01-26/`

ReactJS support for SPA

- ReactJS has no opinion! Need 3rd party module.
- Example: React Router <https://reacttraining.com/react-router/>
 - Idea: Use URL to control conditional rendering
- Various ways of encoding information in URL
 - In fragment part of the URL: [HashRouter](#)
 - Use HTML5 URL handler: [BrowserRouter](#)
- Import as a module:

```
import {HashRouter, Route, Link, Redirect} from 'react-router-dom';
```


Example React Router

```
<HashRouter>
  <div>
    ...
    <Route path="/states" component={States} />
    ...
    <Link to="/states">States</Link>
    ...
  </div>
</HashRouter>
```

- JSX block controlled by URL enclosed in HashRouter
- Route will render the component if URL matches.
- Use Link component to generated hyperlink:

 States

Passing parameters with React Router

- Parameter passing in URL

```
<Route  
  path="/Book/:book/ch/:chapter"  
  component={BookChapterComponent}  
>
```

- Parameters put in prop.match of the component

```
function BookChapterComponent({ match }) {  
  return ( <div>  
    <h3>Book: {match.params.book}</h3>  
    <h3>Chapter: {match.params.chapter}</h3>  
  </div> );  
}
```

```
<Link to="/Book/Moby/ch/1">  
  Moby  
</Link>
```

Book: Moby

Chapter: 1

Route: `component=`, `render=`, `children=`

- `component={BookChapterComponent}`
 - Mounts components on match (unmounts on URL change)
 - Passes match object with: `params`, `url`, `history`
- `render={props => <BookChapterComponent book={props.match.params.book} chapter={props.match.params.chapter} />}`
 - Calls function with props having match object from above.
 - Doesn't mount/unmount component (does update it)
- `children=` - Like `render=` except is called regardless of the match
 - `match` will be `null` if URL doesn't match
 - Useful if you want to have something always render but only active on matching URL.

Multiple route matches have precedence order: `component`, `render`, `children`

`Switch` is useful with multiple `Route` - Renders the first matching one

Example

SortTab - no ResponsiveSortTab - ResponsiveSortTab - Responsive with Scroll

All Columns

Records 110 of 49

reset

ID	Name	Phone	Email	Birthdate	Last Access	Rating	Time	Salary	Score
24	Alexandra Nixon	(422) 644-3488	nixon.alex@coria.com	12/01/1981	February 25, 2001	-1	41%	\$46,672	7.5
17	Aisa Monroe	(859) 974-4442	aisa.lla@aram.edu	02/14/1990	April 30, 2003	6	95%	\$103,999	5.9
10	Baker Osborn	(378) 371-0559	turns.baker@ec.edu	03/29/1970	July 23, 2005	-7	61%	\$2,868	0.1
9	Caldwell Larson	(850) 562-3177	alt@idolor.com	07/20/1983	June 22, 2004	-3	81%	\$63,736	7.5
25	Charissa Manning	(438) 395-9392	nb.vuata@necon.org	07/01/1980	April 02, 2005	-8	11%	\$32,199	3.5
48	Charly Hahn	(395) 200-9188	ac@Quous.edu	06/04/1976	January 17, 2009	-2	88%	\$3,246	5.5
30	Donan Hodge	(304) 536-8850	selous@lanest.org	06/16/1978	February 21, 2007	6	6%	\$28,057	0.1
1	Ezekiel Hart	(627) 536-4760	torlor@est.ca	12/02/1962	March 26, 2009	-7	7%	\$73,229	6.9
12	Fletcher Briggs	(992) 962-9419	amet.anta@lenore.edu	06/12/1971	December 12, 2006	7	23%	\$142,448	8.9
40	Fritz Benton	(525) 353-2984	a@damnuc.com	10/02/1957	June 16, 2002	-5	2%	\$75,654	8.9
								\$3,442,036	
						0.8	44.1%	\$70,246	5.19

1

view all

10

Entries Per Page

Page 1 of 5

What to keep in URL: table length, viewport in table, search box, sort column, etc.
Is it different for bookmark or share? Nav away and back?

Example: Not everything goes in URL









Angular JS Crud Grid

This is a running demo of the Angular JS CRUD Grid I describe in my blog:

Angular JS CRUD Grid
softwarejuancarlos.com

Delete 'Eggs'

Are you sure you want to remove this item?

		Name	Expire Date
		Milk	Sunday, October 5, 2014
		Eggs	Sunday, October 5, 2014
		Steak	2x 400g Saturday, September 20, 2014
		Oranges	