

Interactive / complex / 1

IC 1

IC 2

IC 3

IC 4

IC 5

IC 6

IC 7

IC 8

IC 9

IC 10

IC 11

IC 12

IC 13

IC 14v1

IC 14v2

query	Interactive / complex / 1																																																																					
title	Transitive friends with a certain name																																																																					
pattern																																																																						
description	Given a start Person with ID \$personId, find Persons with a given first name (\$firstName) that the start Person is connected to (excluding start Person) by at most 3 steps via the knows relationships. Return Persons, including the distance (1..3), summaries of the Persons workplaces and places of study.																																																																					
params	<table><tr><td>1</td><td>\$personId</td><td>ID</td><td></td></tr><tr><td>2</td><td>\$firstName</td><td>String</td><td></td></tr></table>					1	\$personId	ID		2	\$firstName	String																																																										
1	\$personId	ID																																																																				
2	\$firstName	String																																																																				
result	<table><tr><td>1</td><td>otherPerson.id</td><td>ID</td><td>R</td><td></td></tr><tr><td>2</td><td>otherPerson.lastName</td><td>String</td><td>R</td><td></td></tr><tr><td>3</td><td>distanceFromPerson</td><td>32-bit Integer</td><td>C</td><td></td></tr><tr><td>4</td><td>otherPerson.birthday</td><td>Date</td><td>R</td><td></td></tr><tr><td>5</td><td>otherPerson.creationDate</td><td>DateTime</td><td>R</td><td></td></tr><tr><td>6</td><td>otherPerson.gender</td><td>String</td><td>R</td><td></td></tr><tr><td>7</td><td>otherPerson.browserUsed</td><td>String</td><td>R</td><td></td></tr><tr><td>8</td><td>otherPerson.locationIP</td><td>String</td><td>R</td><td></td></tr><tr><td>9</td><td>otherPerson.email</td><td>{Long String}</td><td>R</td><td></td></tr><tr><td>10</td><td>otherPerson.speaks</td><td>{String}</td><td>R</td><td></td></tr><tr><td>11</td><td>locationCity.name</td><td>String</td><td>R</td><td></td></tr><tr><td>12</td><td>universities</td><td>{<String, 32-bit Integer, String>}</td><td>A</td><td>{<university.name, studyAt.classYear, universityCity.name>}</td></tr><tr><td>13</td><td>companies</td><td>{<String, 32-bit Integer, String>}</td><td>A</td><td>{<company.name, workAt.workFrom, companyCountry.name>}</td></tr></table>					1	otherPerson.id	ID	R		2	otherPerson.lastName	String	R		3	distanceFromPerson	32-bit Integer	C		4	otherPerson.birthday	Date	R		5	otherPerson.creationDate	DateTime	R		6	otherPerson.gender	String	R		7	otherPerson.browserUsed	String	R		8	otherPerson.locationIP	String	R		9	otherPerson.email	{Long String}	R		10	otherPerson.speaks	{String}	R		11	locationCity.name	String	R		12	universities	{<String, 32-bit Integer, String>}	A	{<university.name, studyAt.classYear, universityCity.name>}	13	companies	{<String, 32-bit Integer, String>}	A	{<company.name, workAt.workFrom, companyCountry.name>}
1	otherPerson.id	ID	R																																																																			
2	otherPerson.lastName	String	R																																																																			
3	distanceFromPerson	32-bit Integer	C																																																																			
4	otherPerson.birthday	Date	R																																																																			
5	otherPerson.creationDate	DateTime	R																																																																			
6	otherPerson.gender	String	R																																																																			
7	otherPerson.browserUsed	String	R																																																																			
8	otherPerson.locationIP	String	R																																																																			
9	otherPerson.email	{Long String}	R																																																																			
10	otherPerson.speaks	{String}	R																																																																			
11	locationCity.name	String	R																																																																			
12	universities	{<String, 32-bit Integer, String>}	A	{<university.name, studyAt.classYear, universityCity.name>}																																																																		
13	companies	{<String, 32-bit Integer, String>}	A	{<company.name, workAt.workFrom, companyCountry.name>}																																																																		
sort	<table><tr><td>1</td><td>distanceFromPerson</td><td>↑</td><td></td></tr><tr><td>2</td><td>otherPerson.lastName</td><td>↑</td><td></td></tr><tr><td>3</td><td>otherPerson.id</td><td>↑</td><td></td></tr></table>					1	distanceFromPerson	↑		2	otherPerson.lastName	↑		3	otherPerson.id	↑																																																						
1	distanceFromPerson	↑																																																																				
2	otherPerson.lastName	↑																																																																				
3	otherPerson.id	↑																																																																				
limit	20																																																																					
CPs	2.1, 5.3, 8.2																																																																					
relevance	This query is a representative of a simple navigational query. It is interesting for several aspects. (1) It requires for a complex aggregation for returning the concatenation of universities, companies, languages and email information of the Person. (2) It tests the ability of the optimizer to move the evaluation of sub-queries functionally dependant on the Person, after the evaluation of the top-k. (3) Its performance is highly sensitive to properly estimating the cardinalities in each transitive path, and paying attention not to explore already visited Persons.																																																																					