Technical parameters of small bore well drilling machine

Bore diameter(hammer)	90-350mm
Bore depth	260m
Air consumption	17-35m³/min
Air pressure	1.7-3.0Mpa
Pipe diameter	76mm/89mm
Pipe length	3m
Push force	4T
Lifting force	15T
Lifting speed	2.5m/min
feeding speed	0.5-5m/min
Fast lifting speed	24m/min
Fast feeding speed	35m/min
Max torque of the rotary	4000-5300Nm
Rotary speed	45-70r/min
Mud Pump flow	200L/min (option)
High hydraulic leg	1.5m
Feeding efficiency	10-35m/h
Travel speed	2.5Km/h
Climb ability	30°
Dimension(L*W*H)	4×1.85×2.3M
Weight	6500Kg
Diesel engine	70KW FAW engine

ກວດລະບົບເດືອນລະເທື່ອ

ເວລາເລີ່ມເຮັດວຽກ

ແຈ້ງເຕືອນກວດເຊັກລະບົບ3ເດືອນ 6ເດືອນ ປີ1

ວັນທີໃສ່ນ້ຳມັນເຄື່ອງ

Basic Info.

Model NO.	RCF260C	Certification	CE, ISO 9001:2008
Condition	New	Motor	AC Motor
Drill Hole Diameter	90-350mm	Drill Hole Depth	260m
Bit Type	Cone Bit	Drilling Way	Rotary
Type	Crawler	Engine	70kw
Drilling Rig Weight	6500kgs	Rotary Torque	4000-5300n.M
Drilling Pipe Length	3m	Transport Package	FCL
Specification	4000*1850*2300mm	Trademark	Rancheng
Origin	China	Production Capacity	100

ສາງ - ລາຍການເຄື່ອງຈັກເຈາະເອົາມາແຕ່ຊຽງຂວາງ ໄປສະຫວັນນະເຂດ 9/1/2025			
ລ/ດ	ລາຍການເຄື່ອງອຸປະກອນ	ຈຳນວນ	ໝາຍເຫດ
1	ກ້ານເຈາະ HQ	150ກ້ານ	
2	ກ້ານເຈາະ PQ	70 ກ້ານ	
3	ຄໍບາເລວ HQ	2 ອັນ	
4	ໂອຊັອດ HQ	1 ອັນ	
5	ຈຸບ HQ	2 ອັນ	
6	ເບັກເອັນ HQ	2 ອັນ	
7	ເບັກເອັນ PQ	2 ອັນ	
8	ລິບມົ້ງ HQ	4 ອັນ	

9	ຊັບ HQ	4 ອັນ	
10	ສາຍນ້ຳ	4 ມັດ	
11	ກະແຈຫັນກ້ານ	1 ອັນ	
12	ກະແຈຫັນຈຸບ	2 ອັນ	
13	ເປົ້ານ້ຳຍາ	22 ເປົ້າ	
14	ຈັກປັ້ານ້ຳ	2	ເຜ
15	ຈັກເຈາະ(ຈັກໃຫຍ່)	1	gr
16	ຈັກໄຟ	1	ເຜ