

Red File: /libs/hihgui/cvHighgui.reds
Source: C_Functions/highgui_c.h
Fonctions: 23

Function	
cvInitSystem	This function is used to set some external parameters in case of X Window
cvStartWindowThread	Start a separated window thread that will manage mouse events
cvNamedWindow	Create window
cvSetWindowProperty	Set and Get Property of the window
cvGetWindowProperty	Set and Get Property of the window
cvShowImage	Show image
cvResizeWindow	Resize window
cvMoveWindow	Move window
cvDestroyWindow	Destroy window and all the trackers associated with it
cvDestroyAllWindows	Destroy all windows and all the trackers associated
cvGetWindowHandle	Get native window handle (HWND in case of Win32 and Widget in case of X Window)
cvGetWindowName	Get name of highgui window given its native handle
cvCreateTrackbar	Create trackbar and display it on top of given window, set callback
cvCreateTrackbar2	new
cvGetTrackbarPos	Retrieve trackbar position
cvSetTrackbarPos	Set trackbar position
cvSetTrackbarMax	Set trackbar max value
cvSetMouseCallback	Assign callback for mouse events
cvWaitKey	Wait for key event infinitely (delay<=0) or for "delay" milliseconds
cvSetOpenGLDrawCallback	OpenGL support
cvSetOpenGLContext	OpenGL support
cvUpdateWindow	OpenGL support