

[illegible]

NOTES:

1. CLEAN ALL THREADS AND SEAL BORES BEFORE ASSEMBLY.

2. APPLY ANTI-SEIZE COMPOUND TO ALL TOOL JOINT CONNECTIONS UNLESS OTHERWISE NOTED.

3. PRESSURE TEST SEAL SECTION TO 1,500 PSI FOR 10 MINUTES WITH NO VISIBLE LEAKAGE. RECORD THE RESULT ON THE ASSEMBLY TRAVELER.

4. STAMP ASSEMBLY SERIAL NUMBER ON ITEM 20 WITHIN 2.0" OF THE SHOULDER.

REV A

INITIAL RELEASE, ECO 1042

11-20-25

AR

MO

REV B

ADDED ALT. HOUSINGS, ECO 1107

03-12-26

AR

MO

68.4"

OAL

22.5"

BOX TO SPRING STACK

BOX END (UPHOLE)

PIN END (DOWNHOLE)

ASSEMBLY OVERVIEW

SCALE 1:12

19

17

21

18

22

20

25 ± 5 FT-LBS
PIPE SEALANT

Ø6.50 OD

API 4-1/2 IF PIN

2,000 ± 100 FT-LBS
LEFT HAND
THREAD LOCKER, MEDIUM STRENGTH

18,000 ± 1,000 FT-LBS
ANTI-SEIZE COMPOUND

SECTION A-A

SCALE 1:4

ITEM	PART NO.	DESCRIPTION	QTY	NOTES
17	TDT-650-1701	SPLINE SLEEVE, 6-1/2	1	
18	TDT-650-1801	LOCK NUT, 4-1/2 UN, LEFT HAND	1	
19	TDT-650-1901	SEAL CARRIER, LOWER	1	
20	TDT-650-2001	BOTTOM SUB, 6-1/2	1	API 4-1/2 IF PIN
21	TDT-00-0121	GREASE FITTING, 1/8 NPT	2	
22	TDT-00-0122	PIPE PLUG, 1/8 NPT, SOCKET HEAD	2	

HEAT TREAT:

N/A

MATERIAL:

SEE BOM

DRAWN	AR	11-20-25
CHECKED	MO	11-24-25
ENG APPR.	AR	11-26-25

PROPRIETARY NOTICE

THIS FICTIONAL DRAWING WAS PREPARED FOR THE PDF-TRANSLATE-ZH PROJECT AS A DEMONSTRATION. IT DOES NOT DESCRIBE A REAL PRODUCT AND MUST NOT BE USED FOR MANUFACTURE.

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
FINISH: $\sqrt[12]{}$ MAX.; $\sqrt[32]{}$ ON ALL
THREADS & RELIEF SURFACES.
BREAK ALL SHARP CORNERS.
REMOVE ALL BURRS.
TOLERANCES:
ANGULAR: ±1°-0'
DECIMAL: .XXX ±.005
 .XX ±.010
 .X ±.030
FRACTIONAL: ±1/32
ALL UNSPECIFIED DIAMETERS TO
BE WITHIN .003 TIR.

tethys

TETHYS DOWNHOLE TOOLS
HARBOR POINT ASSEMBLY SHOP
FICTIONAL DEMONSTRATION ONLY

6-1/2" SHOCK SUB ASSEMBLY,
DUAL SPRING STACK

PART NO.
TDT-650-0100

DWG. NO.
TDT-650-0100B

SCALE: 1:4

WEIGHT: 640 LBS

SHEET 1 OF 3

[illegible]



