

Package ‘jointVIP’

December 20, 2022

Title Prioritize Variables with Joint Variable Importance Plot in
Observational Study Design

Version 0.1.0

Description In the observational study design stage, matching/weighting methods are conducted. However, when many background variables are present, the decision as to which variables to prioritize for matching/weighting is not trivial. Thus, the joint treatment-outcome variable importance plots are created to guide variable selection. The joint variable importance plots enhance variable comparisons via bias curves, derived using the classical omitted variable bias framework. The joint variable importance plots translate variable importance into recommended values for tuning parameters in existing methods. Post-matching and/or weighting plots can also be used to visualize and assess the quality of the observational study design.

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.1

Depends R (>= 3.3)

Suggests causaldata, devtools (>= 2.4.5), knitr, MatchIt, WeightIt,
optmatch, optweight (>= 0.2.4), rmarkdown (>= 2.18), testthat
(>= 3.0.0)

Config/testthat/edition 3

Collate 'measures.R' 'general.R'

Imports ggrepel (>= 0.9.2), ggplot2 (>= 3.4.0)

VignetteBuilder knitr

URL <https://github.com/ldliao/jointVIP>

BugReports <https://github.com/ldliao/jointVIP/issues>

NeedsCompilation no

Author Lauren D. Liao [aut, cre] (<<https://orcid.org/0000-0003-4697-6909>>),
Samuel D. Pimentel [aut] (<<https://orcid.org/0000-0002-0409-6586>>)

Maintainer Lauren D. Liao <ldliao@berkeley.edu>

R topics documented:

add_OVB_curves	2
add_variable_labels	3
bootstrap.plot	3
ceiling_dec	4
check_measures	5
create_jointVIP	5
create_post_jointVIP	6
floor_dec	7
get_boot_measures	8
get_measures	8
get_post_measures	9
plot.jointVIP	9
plot.post_jointVIP	10
print.jointVIP	11
print.post_jointVIP	12
summary.jointVIP	13
summary.post_jointVIP	14
Index	17

add_OVB_curves	<i>support function to plot bias curves</i>
----------------	---

Description

support function to plot bias curves

Usage

add_OVB_curves(p, ...)

Arguments

- p plot made with jointVIP object
- ... encompasses other variables needed

Value

a joint variable importance plot of class ggplot with curves

add_variable_labels	<i>support function to plot variable text labels</i>
---------------------	--

Description

support function to plot variable text labels

Usage

```
add_variable_labels(p, ...)
```

Arguments

p	plot made with jointVIP object
...	encompasses other variables needed

Value

a joint variable importance plot of class ggplot with curves

bootstrap.plot	<i>plot the bootstrap version of the jointVIP object</i>
----------------	--

Description

plot the bootstrap version of the jointVIP object

Usage

```
bootstrap.plot(
  x,
  ...,
  smd = "OVB-based",
  use_abs = TRUE,
  plot_title = "Joint Variable Importance Plot",
  B = 100
)
```

Arguments

x	a jointVIP object
...	custom options: bias_curve_cutoffs, text_size, max.overlaps, label_cut_std_md, label_cut_outcome_cor, label_cut_bias, OVB_curves, add_var_labs
smd	specify the standardized mean difference is OVB-based or standard
use_abs	TRUE (default) for absolute measures
plot_title	optional string for plot title
B	100 (default) for the number of times the bootstrap step wished to run

Value

a joint variable importance plot of class ggplot

Examples

```
data <- data.frame(year = rnorm(50, 200, 5),
                  pop = rnorm(50, 1000, 500),
                  gdpPerCap = runif(50, 100, 1000),
                  trt = rbinom(50, 1, 0.5),
                  out = rnorm(50, 1, 0.2))
# random 20 percent of control as pilot data
pilot_sample_num = sample(which(data$trt == 0),
                          length(which(data$trt == 0)) *
                          0.2)
pilot_df = data[pilot_sample_num, ]
analysis_df = data[-pilot_sample_num, ]
treatment = "trt"
outcome = "out"
covariates = names(analysis_df)[!names(analysis_df)
                              %in% c(treatment, outcome)]
new_jointVIP = create_jointVIP(treatment = treatment,
                              outcome = outcome,
                              covariates = covariates,
                              pilot_df = pilot_df,
                              analysis_df = analysis_df)
# more bootstrap number B would be typically used in real settings
# this is just a small example
set.seed(1234567891)
bootstrap.plot(new_jointVIP, B = 15)
```

ceiling_dec

support function for ceiling function with decimals

Description

support function for ceiling function with decimals

Usage

```
ceiling_dec(num, dec_place = 1)
```

Arguments

num	numeric
dec_place	decimal place that is desired ceiling for

Value

numeric number desired

check_measures	<i>Check measures Check to see if there is any missing values or variables without any variation or identical rows (only unique rows will be used)</i>
----------------	--

Description

Check measures Check to see if there is any missing values or variables without any variation or identical rows (only unique rows will be used)

Usage

```
check_measures(measures)
```

Arguments

measures measures needed for jointVIP

Value

measures needed for jointVIP

create_jointVIP	<i>create jointVIP object</i>
-----------------	-------------------------------

Description

This is creates the jointVIP object & check inputs

Usage

```
create_jointVIP(treatment, outcome, covariates, pilot_df, analysis_df)
```

Arguments

treatment	string denoting the name of the treatment variable
outcome	string denoting the name of the outcome variable
covariates	vector of strings or list denoting column names of interest
pilot_df	data.frame of the pilot data
analysis_df	data.frame of the analysis data

Value

a jointVIP object

Examples

```

data <- data.frame(year = rnorm(50, 200, 5),
                  pop = rnorm(50, 1000, 500),
                  gdpPercap = runif(50, 100, 1000),
                  trt = rbinom(50, 1, 0.5),
                  out = rnorm(50, 1, 0.2))
# random 20 percent of control as pilot data
pilot_sample_num = sample(which(data$trt == 0),
                          length(which(data$trt == 0)) *
                          0.2)
pilot_df = data[pilot_sample_num, ]
analysis_df = data[-pilot_sample_num, ]
treatment = "trt"
outcome = "out"
covariates = names(analysis_df)[!names(analysis_df)
                              %in% c(treatment, outcome)]
new_jointVIP = create_jointVIP(treatment = treatment,
                              outcome = outcome,
                              covariates = covariates,
                              pilot_df = pilot_df,
                              analysis_df = analysis_df)

```

create_post_jointVIP *create jointVIP object*

Description

This is creates the post_jointVIP object & check inputs

Usage

```
create_post_jointVIP(object, post_analysis_df)
```

Arguments

object a jointVIP object
post_analysis_df
 post matched or weighted data.frame

Value

a post_jointVIP object (subclass of jointVIP)

Examples

```

data <- data.frame(year = rnorm(50, 200, 5),
                  pop = rnorm(50, 1000, 500),
                  gdpPercap = runif(50, 100, 1000),
                  trt = rbinom(50, 1, 0.5),
                  out = rnorm(50, 1, 0.2))
# random 20 percent of control as pilot data

```

```

pilot_sample_num = sample(which(data$trt == 0),
                           length(which(data$trt == 0)) *
                           0.2)
pilot_df = data[pilot_sample_num, ]
analysis_df = data[-pilot_sample_num, ]
treatment = "trt"
outcome = "out"
covariates = names(analysis_df)[!names(analysis_df)
                               %in% c(treatment, outcome)]
new_jointVIP = create_jointVIP(treatment = treatment,
                               outcome = outcome,
                               covariates = covariates,
                               pilot_df = pilot_df,
                               analysis_df = analysis_df)

## at this step typically you may wish to do matching or weighting
## the results after can be stored as a post_data
## the post_data here is not matched or weighted, only for illustrative purposes
post_data <- data.frame(year = rnorm(50, 200, 5),
                        pop = rnorm(50, 1000, 500),
                        gdpPercap = runif(50, 100, 1000),
                        trt = rbinom(50, 1, 0.5),
                        out = rnorm(50, 1, 0.2))
post_dat_jointVIP = create_post_jointVIP(new_jointVIP, post_data)

```

floor_dec

support function for floor function with decimals

Description

support function for floor function with decimals

Usage

```
floor_dec(num, dec_place = 1)
```

Arguments

num	numeric
dec_place	decimal place that is desired floor for

Value

numeric number desired

get_boot_measures	<i>Calculate bootstrapped variation additional tool to help calculate the uncertainty of each variable's bias</i>
-------------------	---

Description

Calculate bootstrapped variation additional tool to help calculate the uncertainty of each variable's bias

Usage

```
get_boot_measures(object, smd = "OVB-based", use_abs = TRUE, B = 100)
```

Arguments

object	jointVIP object
smd	calculate standardized mean difference either using OVB-based or standard
use_abs	TRUE (default) for absolute measures
B	100 (default) for the number of times the bootstrap step wished to run

Value

bootstrapped measures needed for bootstrap-jointVIP

get_measures	<i>Prepare data frame to plot standardized omitted variable bias Marginal standardized mean differences and outcome correlation</i>
--------------	---

Description

Prepare data frame to plot standardized omitted variable bias Marginal standardized mean differences and outcome correlation

Usage

```
get_measures(object, smd = "OVB-based")
```

Arguments

object	jointVIP object
smd	calculate standardized mean difference either using OVB-based or standard

Value

measures needed for jointVIP

get_post_measures	<i>Post-measures data frame to plot post-standardized omitted variable bias</i>
-------------------	---

Description

Post-measures data frame to plot post-standardized omitted variable bias

Usage

```
get_post_measures(object, smd = "OVB-based")
```

Arguments

object	post_jointVIP object
smd	calculate standardized mean difference either using OVB-based or standard

Value

measures needed for jointVIP

plot_jointVIP	<i>plot the jointVIP object</i>
---------------	---------------------------------

Description

plot the jointVIP object

Usage

```
## S3 method for class 'jointVIP'
plot(
  x,
  ...,
  smd = "OVB-based",
  use_abs = TRUE,
  plot_title = "Joint Variable Importance Plot"
)
```

Arguments

x	a jointVIP object
...	custom options: bias_curve_cutoffs, text_size, max.overlaps, label_cut_std_md, label_cut_outcome_cor, label_cut_bias, OVB_curves, add_var_labs, expanded_y_curve_label
smd	specify the standardized mean difference is OVB-based or standard
use_abs	TRUE (default) for absolute measures
plot_title	optional string for plot title

Value

a joint variable importance plot of class ggplot

Examples

```
data <- data.frame(year = rnorm(50, 200, 5),
                  pop = rnorm(50, 1000, 500),
                  gdpPercap = runif(50, 100, 1000),
                  trt = rbinom(50, 1, 0.5),
                  out = rnorm(50, 1, 0.2))
# random 20 percent of control as pilot data
pilot_sample_num = sample(which(data$trt == 0),
                          length(which(data$trt == 0)) *
                          0.2)
pilot_df = data[pilot_sample_num, ]
analysis_df = data[-pilot_sample_num, ]
treatment = "trt"
outcome = "out"
covariates = names(analysis_df)[!names(analysis_df)
                             %in% c(treatment, outcome)]
new_jointVIP = create_jointVIP(treatment = treatment,
                              outcome = outcome,
                              covariates = covariates,
                              pilot_df = pilot_df,
                              analysis_df = analysis_df)

plot(new_jointVIP)
```

plot.post_jointVIP	<i>plot the post_jointVIP object this plot uses the same custom options as the jointVIP object</i>
--------------------	--

Description

plot the post_jointVIP object this plot uses the same custom options as the jointVIP object

Usage

```
## S3 method for class 'post_jointVIP'
plot(
  x,
  ...,
  smd = "OVB-based",
  use_abs = TRUE,
  plot_title = "Joint Variable Importance Plot",
  add_post_labs = TRUE,
  post_label_cut_bias = 0.005
)
```

Arguments

x	a post_jointVIP object
...	custom options: bias_curve_cutoffs, text_size, max.overlaps, label_cut_std_md, label_cut_outcome_cor, label_cut_bias, OVB_curves, add_var_labs, expanded_y_curvelab

smd	specify the standardized mean difference is OVB-based or standard
use_abs	TRUE (default) for absolute measures
plot_title	optional string for plot title
add_post_labs	TRUE (default) show post-measure labels
post_label_cut_bias	0.005 (default) show cutoff above this number; suppressed if show_post_labs is FALSE

Value

a post-analysis joint variable importance plot of class ggplot

Examples

```
data <- data.frame(year = rnorm(50, 200, 5),
                  pop = rnorm(50, 1000, 500),
                  gdpPercap = runif(50, 100, 1000),
                  trt = rbinom(50, 1, 0.5),
                  out = rnorm(50, 1, 0.2))
# random 20 percent of control as pilot data
pilot_sample_num = sample(which(data$trt == 0),
                          length(which(data$trt == 0)) *
                          0.2)
pilot_df = data[pilot_sample_num, ]
analysis_df = data[-pilot_sample_num, ]
treatment = "trt"
outcome = "out"
covariates = names(analysis_df)[!names(analysis_df)
                             %in% c(treatment, outcome)]
new_jointVIP = create_jointVIP(treatment = treatment,
                              outcome = outcome,
                              covariates = covariates,
                              pilot_df = pilot_df,
                              analysis_df = analysis_df)

## at this step typically you may wish to do matching or weighting
## the results after can be stored as a post_data
## the post_data here is not matched or weighted, only for illustrative purposes
post_data <- data.frame(year = rnorm(50, 200, 5),
                      pop = rnorm(50, 1000, 500),
                      gdpPercap = runif(50, 100, 1000),
                      trt = rbinom(50, 1, 0.5),
                      out = rnorm(50, 1, 0.2))
post_dat_jointVIP = create_post_jointVIP(new_jointVIP, post_data)
plot(post_dat_jointVIP)
```

print.jointVIP

Obtains a print for jointVIP object

Description

Obtains a print for jointVIP object

Usage

```
## S3 method for class 'jointVIP'
print(x, ..., smd = "OVb-based", use_abs = TRUE, bias_tol = 0.01)
```

Arguments

x	a jointVIP object
...	not used
smd	specify the standardized mean difference is OVb-based or standard
use_abs	TRUE (default) for absolute measures
bias_tol	numeric 0.01 (default) any bias above the absolute bias_tol will be printed

Value

measures used to create the plot of jointVIP

Examples

```
data <- data.frame(year = rnorm(50, 200, 5),
                  pop = rnorm(50, 1000, 500),
                  gdpPercap = runif(50, 100, 1000),
                  trt = rbinom(50, 1, 0.5),
                  out = rnorm(50, 1, 0.2))
# random 20 percent of control as pilot data
pilot_sample_num = sample(which(data$trt == 0),
                          length(which(data$trt == 0)) *
                          0.2)
pilot_df = data[pilot_sample_num, ]
analysis_df = data[-pilot_sample_num, ]
treatment = "trt"
outcome = "out"
covariates = names(analysis_df)[!names(analysis_df)
                              %in% c(treatment, outcome)]
new_jointVIP = create_jointVIP(treatment = treatment,
                              outcome = outcome,
                              covariates = covariates,
                              pilot_df = pilot_df,
                              analysis_df = analysis_df)

print(new_jointVIP)
```

print.post_jointVIP	<i>Obtains a print for post_jointVIP object</i>
---------------------	---

Description

Obtains a print for post_jointVIP object

Usage

```
## S3 method for class 'post_jointVIP'
print(x, ..., smd = "OVb-based", use_abs = TRUE, bias_tol = 0.01)
```

Arguments

x	a post_jointVIP object
...	not used
smd	specify the standardized mean difference is OVB-based or standard
use_abs	TRUE (default) for absolute measures
bias_tol	numeric 0.01 (default) any bias above the absolute bias_tol will be printed

Value

measures used to create the plot of jointVIP

Examples

```
data <- data.frame(year = rnorm(50, 200, 5),
                  pop = rnorm(50, 1000, 500),
                  gdpPercap = runif(50, 100, 1000),
                  trt = rbinom(50, 1, 0.5),
                  out = rnorm(50, 1, 0.2))
# random 20 percent of control as pilot data
pilot_sample_num = sample(which(data$trt == 0),
                          length(which(data$trt == 0)) *
                          0.2)
pilot_df = data[pilot_sample_num, ]
analysis_df = data[-pilot_sample_num, ]
treatment = "trt"
outcome = "out"
covariates = names(analysis_df)[!names(analysis_df)
                             %in% c(treatment, outcome)]
new_jointVIP = create_jointVIP(treatment = treatment,
                              outcome = outcome,
                              covariates = covariates,
                              pilot_df = pilot_df,
                              analysis_df = analysis_df)

## at this step typically you may wish to do matching or weighting
## the results after can be stored as a post_data
## the post_data here is not matched or weighted, only for illustrative purposes
post_data <- data.frame(year = rnorm(50, 200, 5),
                      pop = rnorm(50, 1000, 500),
                      gdpPercap = runif(50, 100, 1000),
                      trt = rbinom(50, 1, 0.5),
                      out = rnorm(50, 1, 0.2))
post_dat_jointVIP = create_post_jointVIP(new_jointVIP, post_data)
print(post_dat_jointVIP)
```

summary.jointVIP

Obtains a summary jointVIP object

Description

Obtains a summary jointVIP object

Usage

```
## S3 method for class 'jointVIP'
summary(object, ..., smd = "OVB-based", use_abs = TRUE, bias_tol = 0.01)
```

Arguments

object	a jointVIP object
...	not used
smd	specify the standardized mean difference is OVB-based or standard
use_abs	TRUE (default) for absolute measures
bias_tol	numeric 0.01 (default) any bias above the absolute bias_tol will be summarized

Value

no return value

Examples

```
data <- data.frame(year = rnorm(50, 200, 5),
                  pop = rnorm(50, 1000, 500),
                  gdpPercap = runif(50, 100, 1000),
                  trt = rbinom(50, 1, 0.5),
                  out = rnorm(50, 1, 0.2))
# random 20 percent of control as pilot data
pilot_sample_num = sample(which(data$trt == 0),
                          length(which(data$trt == 0)) *
                          0.2)
pilot_df = data[pilot_sample_num, ]
analysis_df = data[-pilot_sample_num, ]
treatment = "trt"
outcome = "out"
covariates = names(analysis_df)[!names(analysis_df)
                        %in% c(treatment, outcome)]
new_jointVIP = create_jointVIP(treatment = treatment,
                              outcome = outcome,
                              covariates = covariates,
                              pilot_df = pilot_df,
                              analysis_df = analysis_df)

summary(new_jointVIP)
```

summary.post_jointVIP *Obtains a summary post_jointVIP object*

Description

Obtains a summary post_jointVIP object

Usage

```
## S3 method for class 'post_jointVIP'
summary(
  object,
  ...,
  smd = "OVB-based",
  use_abs = TRUE,
  bias_tol = 0.01,
  post_bias_tol = 0.005
)
```

Arguments

object	a post_jointVIP object
...	not used
smd	specify the standardized mean difference is OVB-based or standard
use_abs	TRUE (default) for absolute measures
bias_tol	numeric 0.01 (default) any bias above the absolute bias_tol will be summarized
post_bias_tol	numeric 0.005 (default) any bias above the absolute bias_tol will be summarized

Value

no return value

Examples

```
data <- data.frame(year = rnorm(50, 200, 5),
  pop = rnorm(50, 1000, 500),
  gdpPercap = runif(50, 100, 1000),
  trt = rbinom(50, 1, 0.5),
  out = rnorm(50, 1, 0.2))
# random 20 percent of control as pilot data
pilot_sample_num = sample(which(data$trt == 0),
  length(which(data$trt == 0)) *
  0.2)
pilot_df = data[pilot_sample_num, ]
analysis_df = data[-pilot_sample_num, ]
treatment = "trt"
outcome = "out"
covariates = names(analysis_df)[!names(analysis_df)
  %in% c(treatment, outcome)]
new_jointVIP = create_jointVIP(treatment = treatment,
  outcome = outcome,
  covariates = covariates,
  pilot_df = pilot_df,
  analysis_df = analysis_df)

## at this step typically you may wish to do matching or weighting
## the results after can be stored as a post_data
## the post_data here is not matched or weighted, only for illustrative purposes
post_data <- data.frame(year = rnorm(50, 200, 5),
  pop = rnorm(50, 1000, 500),
  gdpPercap = runif(50, 100, 1000),
```

```
      trt = rbinom(50, 1, 0.5),  
      out = rnorm(50, 1, 0.2))  
post_dat_jointVIP = create_post_jointVIP(new_jointVIP, post_data)  
summary(post_dat_jointVIP)
```


Index

`add_OVB_curves`, [2](#)
`add_variable_labels`, [3](#)

`bootstrap.plot`, [3](#)

`ceiling_dec`, [4](#)
`check_measures`, [5](#)
`create_jointVIP`, [5](#)
`create_post_jointVIP`, [6](#)

`floor_dec`, [7](#)

`get_boot_measures`, [8](#)
`get_measures`, [8](#)
`get_post_measures`, [9](#)

`plot.jointVIP`, [9](#)
`plot.post_jointVIP`, [10](#)
`print.jointVIP`, [11](#)
`print.post_jointVIP`, [12](#)

`summary.jointVIP`, [13](#)
`summary.post_jointVIP`, [14](#)