

Операционные системы

Анализ файловой структуры UNIX. Команды для работы с файлами и каталогами

Валерия Лиджиева

21 июня 2025

Российский университет дружбы народов, Москва, Россия

Цели и задачи работы

Ознакомление с файловой системой Linux, её структурой, именами и содержанием каталогов. Приобретение практических навыков по применению команд для работы с файлами и каталогами, по управлению процессами, по проверке использования диска и обслуживанию файловой системы.

- 1 Выполнить приимеры
- 2 Выполнить дествия по работе с каталогами и файлами
- 3 Выполнить действия с правами доступа
- 4 Получить дополнительные сведения при помощи справки по командам.

Процесс выполнения лабораторной работы

```
ldlīdzhieva@ldlīdzhieva:~$  
ldlīdzhieva@ldlīdzhieva:~$ cd  
ldlīdzhieva@ldlīdzhieva:~$ touch abc1  
ldlīdzhieva@ldlīdzhieva:~$ cp abc1 april  
ldlīdzhieva@ldlīdzhieva:~$ cp abc1 may  
ldlīdzhieva@ldlīdzhieva:~$ mkdir monthly  
ldlīdzhieva@ldlīdzhieva:~$ cp april may monthly  
ldlīdzhieva@ldlīdzhieva:~$ cp monthly/may monthly/june  
ldlīdzhieva@ldlīdzhieva:~$ ls monthly  
april  june  may  
ldlīdzhieva@ldlīdzhieva:~$ mkdir monthly.00  
ldlīdzhieva@ldlīdzhieva:~$ cp -r monthly monthly.00  
ldlīdzhieva@ldlīdzhieva:~$ cp -r monthly.00 /tmp  
ldlīdzhieva@ldlīdzhieva:~$
```

Рис. 1: Выполнение примеров

```
ldlidzhieva@ldlidzhieva:~$ cd
ldlidzhieva@ldlidzhieva:~$ mv april july
ldlidzhieva@ldlidzhieva:~$ mv july monthly.00
ldlidzhieva@ldlidzhieva:~$ ls monthly.00
july  monthly
ldlidzhieva@ldlidzhieva:~$ mv monthly.00 monthly.01
ldlidzhieva@ldlidzhieva:~$ mkdir reports
ldlidzhieva@ldlidzhieva:~$ mv monthly.01 reports
ldlidzhieva@ldlidzhieva:~$ mv reports/monthly.01 reports/monthly
ldlidzhieva@ldlidzhieva:~$
```

Рис. 2: Выполнение примеров

```
ldlidzhieva@ldlidzhieva:~$ touch may
ldlidzhieva@ldlidzhieva:~$ ls -l may
-rw-r--r--. 1 ldlidzhieva ldlidzhieva 0 июн 21 11:09 may
ldlidzhieva@ldlidzhieva:~$ chmod u+x may
ldlidzhieva@ldlidzhieva:~$ ls -l may
-rwxr--r--. 1 ldlidzhieva ldlidzhieva 0 июн 21 11:09 may
ldlidzhieva@ldlidzhieva:~$ chmod u-x may
ldlidzhieva@ldlidzhieva:~$ ls -l may
-rw-r--r--. 1 ldlidzhieva ldlidzhieva 0 июн 21 11:09 may
ldlidzhieva@ldlidzhieva:~$ chmod g-r,o-r monthly
ldlidzhieva@ldlidzhieva:~$ chmod g+w abc1
ldlidzhieva@ldlidzhieva:~$
```

Рис. 3: Выполнение примеров

Создание директорий и копирование файлов

```
ldlidzhieva@ldlidzhieva:~$  
ldlidzhieva@ldlidzhieva:~$ cp /usr/include/linux/sysinfo.h ~  
ldlidzhieva@ldlidzhieva:~$ mv sysinfo.h equipment  
ldlidzhieva@ldlidzhieva:~$ mkdir ski.plases  
ldlidzhieva@ldlidzhieva:~$ mv equipment ski.plases/  
ldlidzhieva@ldlidzhieva:~$ mv ski.plases/equipment ski.plases/equiplist  
ldlidzhieva@ldlidzhieva:~$ touch abc1  
ldlidzhieva@ldlidzhieva:~$ cp abc1 ski.plases/equiplist2  
ldlidzhieva@ldlidzhieva:~$ cd ski.plases/  
ldlidzhieva@ldlidzhieva:~/ski.plases$ mkdir equipment  
ldlidzhieva@ldlidzhieva:~/ski.plases$ mv equiplist equipment/  
ldlidzhieva@ldlidzhieva:~/ski.plases$ mv equiplist2 equipment/  
ldlidzhieva@ldlidzhieva:~/ski.plases$ cd  
ldlidzhieva@ldlidzhieva:~$ mkdir newdir  
ldlidzhieva@ldlidzhieva:~$ mv newdir ski.plases/  
ldlidzhieva@ldlidzhieva:~$ mv ski.plases/newdir/ ski.plases/plans  
ldlidzhieva@ldlidzhieva:~$
```

Рис. 4: Работа с каталогами

Работа с командой chmod

```
ldlidzhieva@ldlidzhieva:~$  
ldlidzhieva@ldlidzhieva:~$ mkdir australia play  
ldlidzhieva@ldlidzhieva:~$ touch my_os feathers  
ldlidzhieva@ldlidzhieva:~$ chmod 744 australia/  
ldlidzhieva@ldlidzhieva:~$ chmod 711 play/  
ldlidzhieva@ldlidzhieva:~$ chmod 544 my_os  
ldlidzhieva@ldlidzhieva:~$ chmod 664 feathers  
ldlidzhieva@ldlidzhieva:~$ ls -l  
итого 0  
-rw-rw-r--. 1 ldlidzhieva ldlidzhieva 0 июн 21 11:11 abc1  
drwxr--r--. 1 ldlidzhieva ldlidzhieva 0 июн 21 11:12 australia  
-rw-rw-r--. 1 ldlidzhieva ldlidzhieva 0 июн 21 11:12 feathers  
drwxr-xr-x. 1 ldlidzhieva ldlidzhieva 74 июн 21 10:45 git-extended  
-rw-r--r--. 1 ldlidzhieva ldlidzhieva 0 июн 21 11:09 may  
drwx--x--x. 1 ldlidzhieva ldlidzhieva 24 июн 21 11:06 monthly  
-r-xr--r--. 1 ldlidzhieva ldlidzhieva 0 июн 21 11:12 my_os  
drwx--x--x. 1 ldlidzhieva ldlidzhieva 0 июн 21 11:12 play  
drwxr-xr-x. 1 ldlidzhieva ldlidzhieva 14 июн 21 11:07 reports  
drwxr-xr-x. 1 ldlidzhieva ldlidzhieva 28 июн 21 11:12 ski.plases  
drwxr-xr-x. 1 ldlidzhieva ldlidzhieva 10 июн 21 10:15 work  
drwxr-xr-x. 1 ldlidzhieva ldlidzhieva 0 июн 21 10:06 Видео  
drwxr-xr-x. 1 ldlidzhieva ldlidzhieva 0 июн 21 10:06 Документы  
drwxr-xr-x. 1 ldlidzhieva ldlidzhieva 26 июн 21 10:23 Загрузки  
drwxr-xr-x. 1 ldlidzhieva ldlidzhieva 0 июн 21 10:06 Изображения  
drwxr-xr-x. 1 ldlidzhieva ldlidzhieva 0 июн 21 10:06 Музыка  
drwxr-xr-x. 1 ldlidzhieva ldlidzhieva 0 июн 21 10:06 Общедоступные  
drwxr-xr-x. 1 ldlidzhieva ldlidzhieva 0 июн 21 10:06 'Рабочий стол'  
drwxr-xr-x. 1 ldlidzhieva ldlidzhieva 0 июн 21 10:06 Шаблоны  
ldlidzhieva@ldlidzhieva:~$
```



```
root:x:0:0:Super User:/root:/bin/bash
bin:x:1:1:bin:/bin:/usr/sbin/nologin
daemon:x:2:2:daemon:/sbin:/usr/sbin/nologin
adm:x:3:4:adm:/var/adm:/usr/sbin/nologin
lp:x:4:7:lp:/var/spool/lpd:/usr/sbin/nologin
sync:x:5:0:sync:/sbin:/bin/sync
shutdown:x:6:0:shutdown:/sbin:/sbin/shutdown
halt:x:7:0:halt:/sbin:/sbin/halt
mail:x:8:12:mail:/var/spool/mail:/usr/sbin/nologin
operator:x:11:0:operator:/root:/usr/sbin/nologin
games:x:12:100:games:/usr/games:/usr/sbin/nologin
ftp:x:14:50:FTP User:/var/ftp:/usr/sbin/nologin
nobody:x:65534:65534:Kernel Overflow User:/:/usr/sbin/nologin
dbus:x:81:81:System Message Bus:/:/usr/sbin/nologin
apache:x:48:48:Apache:/usr/share/httpd:/sbin/nologin
tss:x:59:59:Account used for TPM access:/:/usr/sbin/nologin
avahi:x:70:70:Avahi mDNS/DNS-SD Stack:/var/run/avahi-daemon:/sbin/nologin
geoclue:x:999:999>User for geoclue:/var/lib/geoclue:/sbin/nologin
usbmuxd:x:113:113:usbmuxd user:/:/sbin/nologin
systemd-oom:x:998:998:systemd Userspace OOM Killer:/:/usr/sbin/nologin
qemu:x:107:107:qemu user:/:/sbin/nologin
polkitd:x:114:114>User for polkitd:/:/sbin/nologin
rtkit:x:172:172:RealtimeKit:/:/sbin/nologin
chrony:x:997:994:chrony system user:/var/lib/chrony:/sbin/nologin
dnsmasq:x:996:993:Dnsmasq DHCP and DNS server:/var/lib/dnsmasq:/usr/sbin/nologin
gluster:x:995:992:GlusterFS daemons:/run/gluster:/sbin/nologin
rpc:x:32:32:Rpcbind Daemon:/var/lib/rpcbind:/sbin/nologin
pipewire:x:994:991:PipeWire System Daemon:/run/pipewire:/usr/sbin/nologin
unbound:x:993:990:Unbound DNS resolver:/var/lib/unbound:/sbin/nologin
nm-openconnect:x:992:989:NetworkManager user for OpenConnect:/:/sbin/nologin
rpcuser:x:29:29:RPC Service User:/var/lib/nfs:/sbin/nologin
wsdd:x:991:988:Web Services Dynamic Discovery host daemon:/:/sbin/nologin
sssd:x:990:986>User for sssd:/run/sss:/sbin/nologin
/etc/passwd
```

```
ldlīdzhieva@ldlīdzhieva:~$  
ldlīdzhieva@ldlīdzhieva:~$ cp feathers file.old  
ldlīdzhieva@ldlīdzhieva:~$ mv file.old play/  
ldlīdzhieva@ldlīdzhieva:~$ mkdir fun  
ldlīdzhieva@ldlīdzhieva:~$ cp -R play/ fun/  
ldlīdzhieva@ldlīdzhieva:~$ mv fun/ play/games  
ldlīdzhieva@ldlīdzhieva:~$
```

Рис. 7: Работа с файлами и правами доступа

```
ldlidzhieva@ldlidzhieva:~ — man mount
MOUNT(8) System Administration MOUNT(8)

NAME
    mount - mount a filesystem

SYNOPSIS
    mount [-h|-V]

    mount [-l] [-t fstype]

    mount -a [-fFnrsvw] [-t fstype] [-O optlist]

    mount [-fnrsvw] [-o options] device mountpoint

    mount [-fnrsvw] [-t fstype] [-o options] device mountpoint

    mount --bind|--rbind|--move olddir newdir

    mount --make-[shared|slave|private|unbindable|rshared|rslave|rprivate|runbindable] mountpoint

DESCRIPTION
    All files accessible in a Unix system are arranged in one big tree, the file hierarchy, rooted at /. These files can be spread out over several devices. The mount command serves to attach the filesystem found on some device to the big file tree. Conversely, the umount(8) command will detach it again. The filesystem is used to control how data is stored on the device or provided in a virtual way by network or other services.

    The standard form of the mount command is:

        mount -t type device dir

    This tells the kernel to attach the filesystem found on device (which is of type type) at the directory dir. The option -t type is optional. The mount command is usually able to detect a

Manual page mount(8) line 1 (press h for help or q to quit)
```

```
ldlidzhieva@ldlidzhieva:~ — man fsck
FSCK(8)                                     System Administration      FSCK(8)

NAME
    fsck - check and repair a Linux filesystem

SYNOPSIS
    fsck [-lsAVRTMNP] [-r [fd]] [-C [fd]] [-t fstype] [filesystem...] [--] [fs-specific-options]

DESCRIPTION
    fsck is used to check and optionally repair one or more Linux filesystems. filesystem can be a
    device name (e.g., /dev/hdc1, /dev/sdb2), a mount point (e.g., /, /usr, /home), or a filesystem
    label or UUID specifier (e.g., UUID=8868abf6-88c5-4a83-98b8-bfc24057f7bd or LABEL=root).
    Normally, the fsck program will try to handle filesystems on different physical disk drives in
    parallel to reduce the total amount of time needed to check all of them.

    If no filesystems are specified on the command line, and the -A option is not specified, fsck
    will default to checking filesystems in /etc/fstab serially. This is equivalent to the -As
    options.

    The exit status returned by fsck is the sum of the following conditions:

    0
        No errors

    1
        Filesystem errors corrected

    2
        System should be rebooted

    4
        Filesystem errors left uncorrected

Manual page fsck(8) line 1 (press h for help or q to quit)
```

```
ldlidzhieva@ldlidzhieva:~ -- man mkfs
MKFS(8)                                     System Administration                                     MKFS(8)

NAME
    mkfs - build a Linux filesystem

SYNOPSIS
    mkfs [options] [-t type] [fs-options] device [size]

DESCRIPTION
    This mkfs frontend is deprecated in favour of filesystem specific mkfs.<type> utils.

    mkfs is used to build a Linux filesystem on a device, usually a hard disk partition. The device argument is either the device name (e.g., /dev/hda1, /dev/sdb2), or a regular file that shall contain the filesystem. The size argument is the number of blocks to be used for the filesystem.

    The exit status returned by mkfs is 0 on success and 1 on failure.

    In actuality, mkfs is simply a front-end for the various filesystem builders (mkfs.fstype) available under Linux. The filesystem-specific builder is searched for via your PATH environment setting only. Please see the filesystem-specific builder manual pages for further details.

OPTIONS
    -t, --type type
        Specify the type of filesystem to be built. If not specified, the default filesystem type (currently ext2) is used.

    fs-options
        Filesystem-specific options to be passed to the real filesystem builder.

    -V, --verbose
        Produce verbose output, including all filesystem-specific commands that are executed. Specifying this option more than once inhibits execution of any filesystem-specific commands. This is really only useful for testing.

Manual page mkfs(8) line 1 (press h for help or q to quit)
```

```
ldlidzhieva@ldlidzhieva:~ — man kill
KILL(1) User Commands KILL(1)

NAME
  kill - terminate a process

SYNOPSIS
  kill [-signal|-s signal|-p] [-q value] [-a] [--timeout milliseconds signal] [--] pid|name...

  kill -l [number] | -L

DESCRIPTION
  The command kill sends the specified signal to the specified processes or process groups.

  If no signal is specified, the TERM signal is sent. The default action for this signal is to
  terminate the process. This signal should be used in preference to the KILL signal (number 9),
  since a process may install a handler for the TERM signal in order to perform clean-up steps
  before terminating in an orderly fashion. If a process does not terminate after a TERM signal has
  been sent, then the KILL signal may be used; be aware that the latter signal cannot be caught,
  and so does not give the target process the opportunity to perform any clean-up before
  terminating.

  Most modern shells have a builtin kill command, with a usage rather similar to that of the
  command described here. The --all, --pid, and --queue options, and the possibility to specify
  processes by command name, are local extensions.

  If signal is 0, then no actual signal is sent, but error checking is still performed.

ARGUMENTS
  The list of processes to be signaled can be a mixture of names and PIDs.

  pid
    Each pid can be expressed in one of the following ways:

Manual page kill(1) line 1 (press h for help or q to quit)
```


Выводы по проделанной работе

В ходе данной работы мы ознакомились с файловой системой Linux, её структурой, именами и содержанием каталогов. Научились совершать базовые операции с файлами, управлять правами их доступа для пользователя и групп. Ознакомились с Анализом файловой системы. А также получили базовые навыки по проверке использования диска и обслуживанию файловой системы.