

isban

Center for Open Middleware / Ontology Engineering Group

Universidad Politécnica de Madrid,
Spain.

Building interoperable read-write Linked Data applications with the W3C Linked Data Platform and the LDP4j framework

ESWC 2015 - May 31st , 2015 - Portoroz (Slovenia)

Building interoperable read-write Linked Data applications with the W3C Linked Data Platform and the LDP4j framework

LDP4j 101

LDP4j to the rescue

- Java-based framework for the development of read-write Linked Data applications
 - **Motto:** Focus on your business logic, we will take care of the rest
 - **License:** Apache License, v2.0
- Features:
 - **Simplified business object handling:**
 - Lifting from and lowering to an intermediate representation that can be automatically unmarshalled from or marshalled to RDF, respectively.
 - **LDP support**
 - Protocol conversation control
 - Transparent metadata management
 - **REST aware**
 - Transparent publication of RDF URIRefs.
 - **HTTP compliant**
 - The framework takes care of fulfilling the requirements prescribed by the HTTP related RFCs (i.e., conditional requests processing, content negotiation, entity tag handling,...)

www.ldap4j.org



contact@ldap4j.org

<https://github.com/ldap4j/ldap4j>



[@LDP4j](https://twitter.com/LDP4j)

High level architecture



R+W LD
App. Provider



Application API

- Templating annotations
- Application configuration
- Handler API
- Handler extensibility APIs
- Data manipulation API
- State manipulation API

- LDP protocol handling
- RDF transformation
- Application management
- Resource management
- Endpoint management

Application Engine

Server Frontend

Client Frontend

Server side
HTTP
handling


Client side
HTTP
handling




R+W LD
App. Consumer



What's an LDP4j Application?



Application model in detail



Applications

- The *glue* that allow the LDP4j framework know about
 - how to publish **resources** for each of the entities defined by the application, and
 - how to interact with the application whenever a client requests the interaction with any of the published **resources**
- **Resources** represent entities of the application's domain model that the LDP4j framework knows about...
- ... which are published via **endpoints** that implement the LDP specification.

Templates

- Specify the type of resources used by the application and their (hierarchical) organization

Resource	Basic Container	Direct Container	Indirect Container	Attachment
id	id	id	id	id
name	name	name	name	name
description	description	description	description	description
handler	handler	handler	handler	handler
attachments	attachments	attachments	attachments	path
	memberHandler	memberHandler	memberHandler	predicate
	memberPath	memberPath	memberPath	
		membershipPredicate	membershipPredicate	
		membershipRelation	membershipRelation	
			insertedContentRelation	

Mandatory

Optional



Informational



Organization



Behaviour



Vocabulary

Handlers (I)

- Implement the behaviour, *a.k.a.*, *business logic*, of the resources defined by the templates
- Minimum required behaviour:
 - `org.ldap4j.application.ext.ResourceHandler`
 - Common operations for RDF sources (*i.e.*, retrieval)
 - `org.ldap4j.application.ext.ContainerHandler`
 - Common operations for Containers (*e.g.*, creation of new resources)
- Behaviour can be extended as needed:
 - `org.ldap4j.application.ext.Modifiable`
 - Support for resource updates
 - `org.ldap4j.application.ext.Deleteable`
 - Support for resource deletion

Handlers (II)

- Responsibilities:
 - **Management of the life-cycle of the resources,**
 - To let the LDP4j framework
 - manage of the **endpoints** required for publishing the resources, and
 - control protocol specific metadata required by the LDP specification (*e.g.*, entity tags)
 - Carried out via **Sessions** and **Snapshots**
 - **Data manipulation:**
 - Consume data provided by a request (*i.e.*, POST, PUT)
 - Map the data provided in a request defined in terms of the application's vocabulary to objects of the application's domain model
 - Provide data to send in a response (*i.e.*, GET)
 - Map objects of the application's domain model to data that can be marshalled in the response in terms of the application's vocabulary
 - Carried out using **DataSets**, **Individuals**, **Properties**, and **Literals**

Resource life-cycle management (I)

Actors

- **Snapshots:** act as surrogates of the resources during the execution of a handler operation
 - `org.ldap4j.application.session.ResourceSnapshot`
 - Manage attachments
 - `org.ldap4j.application.session.ContainerSnapshot:`
 - Manage containment relations between resource
 - `org.ldap4j.application.session.AttachmentSnapshot:`
 - Manage parent-child relation between resources
- **Sessions:** coordinates the management process
 - `org.ldap4j.application.session.ReadSession:`
 - Available on resource retrieval operations
 - `org.ldap4j.application.session.WriteSession:`
 - Available on resource modification operations

Snapshot management (I)

Operations (I)

- **Snapshot creation:**

- How:

- Attachment creation (on write operations)
 - Member creation (on write operations)
 - Root resource creation (on application startup)

Constrained by the
templates defined
by the application

- Side-effects:

- Create new resources, create endpoints for publishing the new resources, and update the entity tags and last modified dates for resources whose description must be modified as a result of the creation of the resources (e.g., resources that have attached membership aware containers upon new member creation)

- **Snapshot update:**

- How:

- Via session (on write operations)

- Side-effects:


- Update the entity tag and last modified date of the affected resource.

Resource life-cycle management (III)

Operations (II)


- **Snapshot deletion:**
 - How:
 - Attachment deletion (on write operations)
 - Member deletion (on write operations)
 - Via session (on write operations)
 - Side-effects:
 - Delete existing resources, remove the endpoints used for publishing them, and update the entity tags and last modified dates of resources whose description must be modified as a result of the deletion of the resources (e.g., containers upon deletion of a member)
 - Hierarchy aware
- **Save changes:**
 - Make changes permanent
- **Discard changes**

Data manipulation (I)




Data manipulation (II)

Literal boxing/unboxing




Data manipulation (II)

Literal boxing/unboxing




Data manipulation (II)

Literal boxing/unboxing




Data manipulation (II)

Literal boxing/unboxing




Data manipulation (II)

Literal boxing/unboxing




Data manipulation (II)

Literal boxing/unboxing




Data manipulation (II)

Literal boxing/unboxing




Data manipulation (II)

Literal boxing/unboxing




Data manipulation (II)

Literal boxing/unboxing




Data manipulation (II)

Literal boxing/unboxing




Data manipulation (II)

Literal boxing/unboxing




Data manipulation (II)

Literal boxing/unboxing




Data manipulation (II)


Literal boxing/unboxing



Dealing with failures (I)





Dealing with failures (II)



Dealing with failures (III)


Expressing constraint failures

- Rely on the Shape Constraint Language (SHACL) [1] to define constraints on data set:
 - “[...] an vocabulary for describing RDF graph structures. Some of these graph structures are captured as "shapes", which group together constraints about the same RDF nodes. Shapes provide a high-level vocabulary to identify predicates and their associated cardinalities, datatypes and other constraints.”




[1] <http://www.w3.org/TR/shacl/>


Dealing with failures (III)




Application API in detail




Application bootstrap process




Application execution process




Application execution process




Application execution process




Application execution process




Application execution process




Application execution process




Application execution process




Application execution process



Application shutdown process



Questions?



Miguel Esteban Gutiérrez,
Nandana Mihindukulasooriya,
Raúl García Castro,
Asunción Gómez Pérez
Center for Open Middleware / Ontology Engineering Group
Universidad Politécnica de Madrid,
Spain.