8.2. Description of Level 1 Command

8.2.1. NOP (00h)

00h	NOP (No Operation)												
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	0	0	0	0	0	0	00h
Parameter	No Parameter.												
Description	This command is an empty command; it does not have any effect on the display module. However it can be used to terminate Frame Memory Write or Read as described in RAMWR (Memory Write) and RAMRD (Memory Read) Commands. X = Don't care.												
Restriction	None												
Register Availability	<table><tr><td>Status</td><td>Availability</td></tr><tr><td>Normal Mode On, Idle Mode Off, Sleep Out</td><td>Yes</td></tr><tr><td>Normal Mode On, Idle Mode On, Sleep Out</td><td>Yes</td></tr><tr><td>Partial Mode On, Idle Mode Off, Sleep Out</td><td>Yes</td></tr><tr><td>Partial Mode On, Idle Mode On, Sleep Out</td><td>Yes</td></tr><tr><td>Sleep In</td><td>Yes</td></tr></table>												
Default	<table><tr><td>Status</td><td>Default Value</td></tr><tr><td>Power On Sequence</td><td>N/A</td></tr><tr><td>SW Reset</td><td>N/A</td></tr><tr><td>HW Reset</td><td>N/A</td></tr></table>												
Flow Chart	None												

8.2.2. Software Reset (01h)

01h	SWRESET												
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	0	0	0	0	0	1	01h
Parameter	No Parameter.												
Description	When the Software Reset command is written, it causes a software reset. It resets the commands and parameters to their S/W Reset default values. (See default tables in each command description.) Note: The Frame Memory contents are unaffected by this command X = Don't care.												
Restriction	It will be necessary to wait 5msec before sending new command following software reset. The display module loads all display supplier factory default values to the registers during this 5msec. If Software Reset is applied during Sleep Out mode, it will be necessary to wait 120msec before sending Sleep out command. Software Reset Command cannot be sent during Sleep Out sequence.												

Register Availability				
	Status	Availability		
	Normal Mode On, Idle Mode Off, Sleep Out	Yes		
	Normal Mode On, Idle Mode On, Sleep Out	Yes		
	Partial Mode On, Idle Mode Off, Sleep Out	Yes		
	Partial Mode On, Idle Mode On, Sleep Out	Yes		
	Sleep In	Yes		

Default		
	Status	Default Value
	Power On Sequence	N/A
	SW Reset	N/A
	HW Reset	N/A

Flow Chart

SWRESET(01h)

Display whole blank screen

Set Commands to S/W Default Values

Sleep In Mode

Legend

Command

Parameter

Display

Action

Mode

Sequential transfer

8.2.3. Read display identification information (04h)

04h				RDDIDIF (Read Display Identification Information)									
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	0	0	0	1	0	0	04h
1st Parameter	1	↑	1	XX	X	X	X	X	X	X	X	X	X
2nd Parameter	1	↑	1	XX	ID1 [7:0]								XX
3rd Parameter	1	↑	1	XX	ID2 [7:0]								XX
4th Parameter	1	↑	1	XX	ID3 [7:0]								XX

Description	This read byte returns 24 bits display identification information. The 1st parameter is dummy data. The 2nd parameter (ID1 [7:0]): LCD module's manufacturer ID. The 3rd parameter (ID2 [7:0]): LCD module/driver version ID. The 4th parameter (ID3 [7:0]): LCD module/driver ID.
Restriction	
Register Availability	<table><tr><td>Status</td><td>Availability</td></tr><tr><td>Normal Mode On, Idle Mode Off, Sleep Out</td><td>Yes</td></tr><tr><td>Normal Mode On, Idle Mode On, Sleep Out</td><td>Yes</td></tr><tr><td>Partial Mode On, Idle Mode Off, Sleep Out</td><td>Yes</td></tr><tr><td>Partial Mode On, Idle Mode On, Sleep Out</td><td>Yes</td></tr><tr><td>Sleep In</td><td>Yes</td></tr></table>
Default	<table><tr><td>Status</td><td>Default Value</td></tr><tr><td>Power On Sequence</td><td>See description</td></tr><tr><td>SW Reset</td><td>See description</td></tr><tr><td>HW Reset</td><td>See description</td></tr></table>
Flow Chart	

8.2.4. Read Display Status (09h)

09h				RDDST (Read Display Status)										
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	0	0	1	0	0	1	09h
1st Parameter	1	↑	1	XX	X	X	X	X	X	X	X	X	X
2nd Parameter	1	↑	1	XX	D [31:25]							0	00
3rd Parameter	1	↑	1	XX	0	D [22:20]			D [19:16]				61
4th Parameter	1	↑	1	XX	0	0	0	0	0	D [10:8]			00
5th Parameter	1	↑	1	XX	D [7:5]			0	0	0	0	0	00

This command indicates the current status of the display as described in the table below:

Bit	Description	Value	Status
D31	Booster voltage status	0	Booster OFF
		1	Booster ON
D30	Row address order	0	Top to Bottom (When MADCTL B7='0')
		1	Bottom to Top (When MADCTL B7='1')
D29	Column address order	0	Left to Right (When MADCTL B6='0').
		1	Right to Left (When MADCTL B6='1').
D28	Row/column exchange	0	Normal Mode (When MADCTL B5='0').
		1	Reverse Mode (When MADCTL B5='1').
D27	Vertical refresh	0	LCD Refresh Top to Bottom (When MADCTL B4='0')
		1	LCD Refresh Bottom to Top (When MADCTL B4='1').
D26	RGB/BGR order	0	RGB (When MADCTL B3='0')
		1	BGR (When MADCTL B3='1')
D25	Horizontal refresh order	0	LCD Refresh Left to Right (When MADCTL B2='0')
		1	LCD Refresh Right to Left (When MADCTL B2='1')
D24	Not used	0	---
D23	Not used	0	---
D22	Interface color pixel format definition	101	16-bit/pixel
D21			
D20		110	18-bit/pixel
D19	Idle mode ON/OFF	0	Idle Mode OFF
		1	Idle Mode ON
D18	Partial mode ON/OFF	0	Partial Mode OFF
		1	Partial Mode ON.
D17	Sleep IN/OUT	0	Sleep IN Mode
		1	Sleep OUT Mode.
D16	Display normal mode ON/OFF	0	Display Normal Mode OFF.
		1	Display Normal Mode ON.
D15	Vertical scrolling status	0	Scroll OFF
D14	Not used	0	---
D13	Inversion status	0	Not defined
D12	All pixel ON	0	Not defined
D11	All pixel OFF	0	Not defined
D10	Display ON/OFF	0	Display is OFF
		1	Display is ON
D9	Tearing effect line ON/OFF	0	Tearing Effect Line OFF
		1	Tearing Effect ON
D[8:6]	Gamma curve selection	000	GC0
		001	---
		010	---
		011	---
		other	Not defined

Description

			0	Mode 1, V-Blanking only
	D5	Tearing effect line mode	1	Mode 2, both H-Blanking and V-Blanking.
	D4	Not used	0	---
	D3	Not used	0	---
	D2	Not used	0	---
	D1	Not used	0	---
	D0	Not used	0	---

X = Don't care

Restriction

Register Availability

Status	Availability
Normal Mode On, Idle Mode Off, Sleep Out	Yes
Normal Mode On, Idle Mode On, Sleep Out	Yes
Partial Mode On, Idle Mode Off, Sleep Out	Yes
Partial Mode On, Idle Mode On, Sleep Out	Yes
Sleep In	Yes

Default

Status	Default Value
Power On Sequence	32'h00610000h
SW Reset	32'h00610000h
HW Reset	32'h00610000h

Flow Chart

RDDST(09h)

Host
- -
Driver

1st Parameter: Dummy Read
2nd Parameter: Send D[31:25] display status
3rd Parameter: Send D[19:16] display status
4th Parameter: Send D[10:8] display status
5th Parameter: Send D[7:5] display status

Legend

Command

Parameter

Display

Action

Mode

Sequential transfer

8.2.5. Read Display Power Mode (0Ah)

0Ah				RDDPM (Read Display Power Mode)									
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	0	0	1	0	1	0	0Ah
1st Parameter	1	↑	1	XX	X	X	X	X	X	X	X	X	X
2nd Parameter	1	↑	1	XX	D7	D6	D5	D4	D3	D2	D1	D0	08

Description	This command indicates the current status of the display as described in the table below::

Bit	Value	Description	Comment
D7	0	Booster Off or has a fault.	---
	1	Booster On and working OK	---
D6	0	Idle Mode Off.	---
	1	Idle Mode On.	---
D5	0	Partial Mode Off.	---
	1	Partial Mode On.	---
D4	0	Sleep In Mode	---
	1	Sleep Out Mode	---
D3	0	Display Normal Mode Off.	---
	1	Display Normal Mode On	---
D2	0	Display is Off.	---
	1	Display is On	---
D1	--	Not Defined	Set to '0'
D0	--	Not Defined	Set to '0'

X = Don't care

Restriction	

Register Availability	

Status	Availability
Normal Mode On, Idle Mode Off, Sleep Out	Yes
Normal Mode On, Idle Mode On, Sleep Out	Yes
Partial Mode On, Idle Mode Off, Sleep Out	Yes
Partial Mode On, Idle Mode On, Sleep Out	Yes
Sleep In	Yes

Default	

Status	Default Value
Power On Sequence	8'h08h
SW Reset	8'h08h
HW Reset	8'h08h

Flow Chart	

RDDPM(0Ah)

Host
Driver

1st Parameter: Dummy Read
2nd Parameter: Send D[7:2] display power mode status

Legend
Command
Parameter
Display
Action
Mode
Sequential transfer

8.2.6. Read Display MADCTL (0Bh)

0Bh	RDDMADCTL (Read Display MADCTL)												
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	0	0	1	0	1	1	0Bh
1st Parameter	1	↑	1	XX	X	X	X	X	X	X	X	X	X
2nd Parameter	1	↑	1	XX	D7	D6	D5	D4	D3	D2	D1	D0	00

Description

This command indicates the current status of the display as described in the table below:

Bit	Value	Description	Comment
D7	0	Top to Bottom (When MADCTL B7='0').	---
	1	Bottom to Top (When MADCTL B7='1').	---
D6	0	Left to Right (When MADCTL B6='0')	---
	1	Right to Left (When MADCTL B6='1')	---
D5	0	Normal Mode (When MADCTL B5='0').	---
	1	Reverse Mode (When MADCTL B5='1')	---
D4	0	LCD Refresh Top to Bottom (When MADCTL B4='0')	---
	1	LCD Refresh Bottom to Top (When MADCTL B4='1').	---
D3	0	RGB (When MADCTL B3='0')	---
	1	BGR (When MADCTL B3='1').	---
D2	0	LCD Refresh Left to Right (When MADCTL B2='0').	---
	1	LCD Refresh Right to Left (When MADCTL B2='1').	---
D1	--	Switching between Segment outputs and RAM	Set to '0'
D0	--	Switching between Segment outputs and RAM	Set to '0'

X = Don't care

Restriction

Register Availability

Status	Availability
Normal Mode On, Idle Mode Off, Sleep Out	Yes
Normal Mode On, Idle Mode On, Sleep Out	Yes
Partial Mode On, Idle Mode Off, Sleep Out	Yes
Partial Mode On, Idle Mode On, Sleep Out	Yes
Sleep In	Yes

Default

Status	Default Value
Power On Sequence	8'h00h
SW Reset	No Change
HW Reset	8'h00h

Flow Chart

RDDMADCTL(0Bh)

Host

Driver

1st Parameter: Dummy Read
2nd Parameter: Send D[7:2] display power mode status

Legend

Command
Parameter
Display
Action
Mode
Sequential transfer

8.2.7. Read Display Pixel Format (0Ch)

0Ch	RDDCOLMOD (Read Display Pixel Format)											
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	0	0	1	1	0	0	0Ch
1st Parameter	1	↑	1	XX	X	X	X	X	X	X	X	X	X
2nd Parameter	1	↑	1	XX	RIM	DPI [2:0]			0	DBI [2:0]			06

Description

This command indicates the current status of the display as described in the table below:

RIM	DPI [2:0]			RGB Interface Format	DBI [2:0]			MCU Interface Format
0	0	0	0	Reserved	0	0	0	Reserved
0	0	0	1	Reserved	0	0	1	Reserved
0	0	1	0	Reserved	0	1	0	Reserved
0	0	1	1	Reserved	0	1	1	Reserved
0	1	0	0	Reserved	1	0	0	Reserved
0	1	0	1	16 bits / pixel	1	0	1	16 bits / pixel
0	1	1	0	18 bits / pixel	1	1	0	18 bits / pixel
0	1	1	1	Reserved	1	1	1	Reserved
1	1	0	1	16 bits / pixel (6-bit 3 times data transfer)				
1	1	1	0	18 bits / pixel (6-bit 3 times data transfer)				

X = Don't care

Restriction

Register Availability

Status	Availability
Normal Mode On, Idle Mode Off, Sleep Out	Yes
Normal Mode On, Idle Mode On, Sleep Out	Yes
Partial Mode On, Idle Mode Off, Sleep Out	Yes
Partial Mode On, Idle Mode On, Sleep Out	Yes
Sleep In	Yes

Default

Status	Default Value		
	RIM	DPI [2:0]	DBI [2:0]
Power On Sequence	1'b0	3'b000	3'b110
SW Reset	No Chang	No Chang	No Chang
HW Reset	1'b0	3'b000	3'b110

Flow Chart

RDDCOLMOD(0Ch)

Host
Driver

1st Parameter: Dummy Read
2nd Parameter: Send D[7:2] display pixel format status

Legend
Command
Parameter
Display
Action
Mode
Sequential transfer

8.2.8. Read Display Image Format (0Dh)

0Dh				RDDIM (Read Display Image Mode)									
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	0	0	1	1	0	1	0Dh
1st Parameter	1	↑	1	XX	X	X	X	X	X	X	X	X	X
2nd Parameter	1	↑	1	XX	0	0	0	0	0		D [2:0]		00

Description	This command indicates the current status of the display as described in the table below:

D [2:0]	Description
000	Gamma curve 1 (G2.2)
001	---
010	---
011	---
Other	Not defined

X = Don't care

Restriction	

Register Availability	

Status	Availability
Normal Mode On, Idle Mode Off, Sleep Out	Yes
Normal Mode On, Idle Mode On, Sleep Out	Yes
Partial Mode On, Idle Mode Off, Sleep Out	Yes
Partial Mode On, Idle Mode On, Sleep Out	Yes
Sleep In	Yes

Default	

Status	Default Value
Power On Sequence	3'b000
SW Reset	3'b000
HW Reset	3'b000

Flow Chart

RDDIM(0Dh)

Host
Driver

1st Parameter: Dummy Read
2nd Parameter: Send D[7:0] display image mode status

Legend
Command
Parameter
Display
Action
Mode
Sequential transfer

8.2.9. Read Display Signal Mode (0Eh)

| 0Eh				RDDSM (Read Display Signal Mode)									
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	0	0	1	1	1	0	0Eh
1stParameter	1	↑	1	XX	X	X	X	X	X	X	X	X	X
2ndParameter	1	↑	1	XX	D7	D6	D5	D4	D3	D2	D1	D0	00
Description	This command indicates the current status of the display as described in the table below: 	Bit	Value	Description
---	---	---
D7	0	Tearing effect line OFF
	1	Tearing effect line ON
D6	0	Tearing effect line mode 1
	1	Tearing effect line mode 2
D5	0	Horizontal sync. (RGB interface) OFF
	1	Horizontal sync. (RGB interface) ON
D4	0	Vertical sync. (RGB interface) OFF
	1	Vertical sync. (RGB interface) ON
D3	0	Pixel clock (DOTCLK, RGB interface) OFF
	1	Pixel clock (DOTCLK, RGB interface) ON
D2	0	Data enable (DE, RGB interface) OFF
	1	Data enable (DE, RGB interface) ON
D1	0	Reserved
D0	0	Reserved | X = Don't care													
Restriction													
Register Availability		Status	Availability
---	---
Normal Mode On, Idle Mode Off, Sleep Out	Yes
Normal Mode On, Idle Mode On, Sleep Out	Yes
Partial Mode On, Idle Mode Off, Sleep Out	Yes
Partial Mode On, Idle Mode On, Sleep Out	Yes
Sleep In	Yes													
Default		Status	Default Value
---	---
Power On Sequence	8'h00h
SW Reset	8'h00h
HW Reset	8'h00h													
Flow Chart	RDDSM(0Eh) Host Driver 1st Parameter: Dummy Read 2nd Parameter: Send D[7:0] display signal mode status Legend Command Parameter Display Action Mode Sequential transfer													

8.2.10. Read Display Self-Diagnostic Result (0Fh)

0Fh				RDDSDR (Read Display Self-Diagnostic Result)									
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	0	0	1	1	1	1	0Fh
1st Parameter	1	↑	1	XX	X	X	X	X	X	X	X	X	X
2nd Parameter	1	↑	1	XX	D7	D6	0	0	0	0	0	0	00

	Bit	Description	Action
	D7	Register Loading Detection	Invert the D7 bit if register values loading work properly.
	D6	Functionality Detection	Invert the D6 bit if the display is functionality
	D5	Not Used	'0'
Description	D4	Not Used	'0'
	D3	Not Used	'0'
	D2	Not Used	'0'
	D1	Not Used	'0'
	D0	Not Used	'0'

Restriction

Register Availability

Status	Availability
Normal Mode On, Idle Mode Off, Sleep Out	Yes
Normal Mode On, Idle Mode On, Sleep Out	Yes
Partial Mode On, Idle Mode Off, Sleep Out	Yes
Partial Mode On, Idle Mode On, Sleep Out	Yes
Sleep In	Yes

Default

Status	Default Value
Power On Sequence	8'h00h
SW Reset	8'h00h
HW Reset	8'h00h

Flow Chart

RDDSDR(0Fh)

Host

Driver

1st Parameter: Dummy Read
2nd Parameter: Send D[7:6] display self-diagnostic status

Legend

Command
Parameter
Display
Action
Mode
Sequential transfer

8.2.11. Enter Sleep Mode (10h)

10h	SPLIN (Enter Sleep Mode)											
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	0	1	0	0	0	0	10h
Parameter	No Parameter											
Description	This command causes the LCD module to enter the minimum power consumption mode. In this mode e.g. the DC/DC converter is stopped, Internal oscillator is stopped, and panel scanning is stopped. MCU interface and memory are still working and the memory keeps its contents. X = Don't care											
Restriction	This command has no effect when module is already in sleep in mode. Sleep In Mode can only be left by the Sleep Out Command (11h). It will be necessary to wait 5msec before sending next to command, this is to allow time for the supply voltages and clock circuits to stabilize. It will be necessary to wait 120msec after sending Sleep Out command (when in Sleep In Mode) before Sleep In command can be sent.											
Register Availability	<table><tr><td>Status</td><td>Availability</td></tr><tr><td>Normal Mode On, Idle Mode Off, Sleep Out</td><td>Yes</td></tr><tr><td>Normal Mode On, Idle Mode On, Sleep Out</td><td>Yes</td></tr><tr><td>Partial Mode On, Idle Mode Off, Sleep Out</td><td>Yes</td></tr><tr><td>Partial Mode On, Idle Mode On, Sleep Out</td><td>Yes</td></tr><tr><td>Sleep In</td><td>Yes</td></tr></table>											
Default	<table><tr><td>Status</td><td>Default Value</td></tr><tr><td>Power On Sequence</td><td>Sleep IN Mode</td></tr><tr><td>SW Reset</td><td>Sleep IN Mode</td></tr><tr><td>HW Reset</td><td>Sleep IN Mode</td></tr></table>											
Flow Chart	It takes 120msec to get into Sleep In mode after SLPIN command issued. 											

8.2.12. Sleep Out (11h)

11h	SLPOUT (Sleep Out)												
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	0	1	0	0	0	1	11h
Parameter	No Parameter												
Description	This command turns off sleep mode. In this mode e.g. the DC/DC converter is enabled, Internal oscillator is started, and panel scanning is started. X = Don't care												
Restriction	This command has no effect when module is already in sleep out mode. Sleep Out Mode can only be left by the Sleep In Command (10h). It will be necessary to wait 5msec before sending next command, this is to allow time for the supply voltages and clock circuits stabilize. The display module loads all display supplier's factory default values to the registers during this 5msec and there cannot be any abnormal visual effect on the display image if factory default and register values are same when this load is done and when the display module is already Sleep Out –mode. The display module is doing self-diagnostic functions during this 5msec. It will be necessary to wait 120msec after sending Sleep In command (when in Sleep Out mode) before Sleep Out command can be sent.												
Register Availability	<table><tr><td>Status</td><td>Availability</td></tr><tr><td>Normal Mode On, Idle Mode Off, Sleep Out</td><td>Yes</td></tr><tr><td>Normal Mode On, Idle Mode On, Sleep Out</td><td>Yes</td></tr><tr><td>Partial Mode On, Idle Mode Off, Sleep Out</td><td>Yes</td></tr><tr><td>Partial Mode On, Idle Mode On, Sleep Out</td><td>Yes</td></tr><tr><td>Sleep In</td><td>Yes</td></tr></table>												
Default	<table><tr><td>Status</td><td>Default Value</td></tr><tr><td>Power On Sequence</td><td>Sleep IN Mode</td></tr><tr><td>SW Reset</td><td>Sleep IN Mode</td></tr><tr><td>HW Reset</td><td>Sleep IN Mode</td></tr></table>												
Flow Chart	It takes 120msec to become Sleep Out mode after SLPOUT command issued.												

SPLOUT (11h)

Start Internal Oscillator

Start up DC-DC Converter

Charge Offset voltage for LCD Panel

Display whole blank screen for 2 frames (Automatic No effect to DISP ON/OFF Commands)

Display Memory contents in accordance with the current command table settings

Sleep Out Mode

Legend

Command

Parameter

Display

Action

Mode

Sequential transfer

8.2.13. Partial Mode ON (12h)

12h	PTLON (Partial Mode On)											
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	0	1	0	0	1	0	12h
Parameter	No Parameter											
Description	This command turns on partial mode The partial mode window is described by the Partial Area command (30H). To leave Partial mode, the Normal Display Mode On command (13H) should be written. X = Don't care											
Restriction	This command has no effect when Partial mode is active.											

Register Availability		Status	Availability
		Normal Mode On, Idle Mode Off, Sleep Out	Yes
		Normal Mode On, Idle Mode On, Sleep Out	Yes
		Partial Mode On, Idle Mode Off, Sleep Out	Yes
		Partial Mode On, Idle Mode On, Sleep Out	Yes
		Sleep In	Yes

Default		Status	Default Value
		Power On Sequence	Normal Display Mode ON
		SW Reset	Normal Display Mode ON
		HW Reset	Normal Display Mode ON

Flow Chart	See Partial Area (30h)

8.2.14. Normal Display Mode ON (13h)

13h					NORON (Normal Display Mode On)								
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	0	1	0	0	1	1	13h
Parameter	No Parameter												
Description	This command returns the display to normal mode. Normal display mode on means Partial mode off. Exit from NORON by the Partial mode On command (12h) X = Don't care												
Restriction	This command has no effect when Normal Display mode is active.												
Register Availability													
Default													
Flow Chart	See Partial Area (30h)												

Register Availability:

Status	Availability
Normal Mode On, Idle Mode Off, Sleep Out	Yes
Normal Mode On, Idle Mode On, Sleep Out	Yes
Partial Mode On, Idle Mode Off, Sleep Out	Yes
Partial Mode On, Idle Mode On, Sleep Out	Yes
Sleep In	Yes

Default:

Status	Default Value
Power On Sequence	Normal Display Mode ON
SW Reset	Normal Display Mode ON
HW Reset	Normal Display Mode ON

8.2.15. Display Inversion OFF (20h)

20h	DINVOFF (Display Inversion OFF)											
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	1	0	0	0	0	0	20h
Parameter	No Parameter											

Description	This command is used to recover from display inversion mode. This command makes no change of the content of frame memory. This command doesn't change any other status. Memory Display Panel X = Don't care

Restriction	This command has no effect when module already is inversion OFF mode.

Register Availability

Status	Availability
Normal Mode On, Idle Mode Off, Sleep Out	Yes
Normal Mode On, Idle Mode On, Sleep Out	Yes
Partial Mode On, Idle Mode Off, Sleep Out	Yes
Partial Mode On, Idle Mode On, Sleep Out	Yes
Sleep In	Yes

Default

Status	Default Value
Power On Sequence	Display Inversion OFF
SW Reset	Display Inversion OFF
HW Reset	Display Inversion OFF

Flow Chart

Display Inversion On Mode

INVOFF(20h)

Display Inversion Off Mode

Legend
Command
Parameter
Display
Action
Mode
Sequential transfer

8.2.16. Display Inversion ON (21h)

21h							DINVON (Display Inversion ON)						
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	1	0	0	0	0	1	21h
Parameter	No Parameter												
Description	This command is used to enter into display inversion mode. This command makes no change of the content of frame memory. Every bit is inverted from the frame memory to the display. This command doesn't change any other status. To exit Display inversion mode, the Display inversion OFF command (20h) should be written. X = Don't care
Restriction	This command has no effect when module already is inversion ON mode.

Register Availability

Status	Availability
Normal Mode On, Idle Mode Off, Sleep Out	Yes
Normal Mode On, Idle Mode On, Sleep Out	Yes
Partial Mode On, Idle Mode Off, Sleep Out	Yes
Partial Mode On, Idle Mode On, Sleep Out	Yes
Sleep In	Yes

Default

Status	Default Value
Power On Sequence	Display Inversion OFF
SW Reset	Display Inversion OFF
HW Reset	Display Inversion OFF

Flow Chart

8.2.17. Gamma Set (26h)

26h	GAMSET (Gamma Set)												
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	1	0	0	1	1	0	26h
Parameter	1	1	↑	XX	GC [7:0]								01

Description	This command is used to select the desired Gamma curve for the current display. A maximum of 4 fixed gamma curves can be selected. The curve is selected by setting the appropriate bit in the parameter as described in the Table: <table><tr><td>GC [7:0]</td><td>Curve Selected</td></tr><tr><td>01h</td><td>Gamma curve 1 (G2.2)</td></tr><tr><td>02h</td><td>---</td></tr><tr><td>04h</td><td>---</td></tr><tr><td>08h</td><td>---</td></tr></table> Note: All other values are undefined. X = Don't care
Restriction	Values of GC [7:0] not shown in table above are invalid and will not change the current selected Gamma curve until valid value is received.
Register Availability	<table><tr><td>Status</td><td>Availability</td></tr><tr><td>Normal Mode On, Idle Mode Off, Sleep Out</td><td>Yes</td></tr><tr><td>Normal Mode On, Idle Mode On, Sleep Out</td><td>Yes</td></tr><tr><td>Partial Mode On, Idle Mode Off, Sleep Out</td><td>Yes</td></tr><tr><td>Partial Mode On, Idle Mode On, Sleep Out</td><td>Yes</td></tr><tr><td>Sleep In</td><td>Yes</td></tr></table>
Default	<table><tr><td>Status</td><td>Default Value</td></tr><tr><td>Power On Sequence</td><td>8'h01h</td></tr><tr><td>SW Reset</td><td>8'h01h</td></tr><tr><td>HW Reset</td><td>8'h01h</td></tr></table>
Flow Chart	

8.2.18. Display OFF (28h)

28h				DISPOFF (Display OFF)									
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	1	0	1	0	0	0	28h
Parameter	No Parameter												

Description	This command is used to enter into DISPLAY OFF mode. In this mode, the output from Frame Memory is disabled and blank page inserted. This command makes no change of contents of frame memory. This command does not change any other status. There will be no abnormal visible effect on the display.

Memory → Display Panel

X = Don't care.

Restriction	This command has no effect when module is already in display off mode.

Register Availability		

Status	Availability
Normal Mode On, Idle Mode Off, Sleep Out	Yes
Normal Mode On, Idle Mode On, Sleep Out	Yes
Partial Mode On, Idle Mode Off, Sleep Out	Yes
Partial Mode On, Idle Mode On, Sleep Out	Yes
Sleep In	Yes

Default		

Status	Default Value
Power On Sequence	Display OFF
SW Reset	Display OFF
HW Reset	Display OFF

Flow Chart

Display On Mode → DISPOFF (28h) → Display Off Mode

Legend
- Command
- Parameter
- Display
- Action
- Mode
- Sequential transfer

8.2.19. Display ON (29h)

29h				DISPON (Display ON)									
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	1	0	1	0	0	1	29h
Parameter	No Parameter												
Description	This command is used to recover from DISPLAY OFF mode. Output from the Frame Memory is enabled. This command makes no change of contents of frame memory. This command does not change any other status Memory ⟹ Display Panel X = Don't care.												
Restriction	This command has no effect when module is already in display on mode.												
Register Availability				Status			Availability						
				Normal Mode On, Idle Mode Off, Sleep Out			Yes						
				Normal Mode On, Idle Mode On, Sleep Out			Yes						
				Partial Mode On, Idle Mode Off, Sleep Out			Yes						
				Partial Mode On, Idle Mode On, Sleep Out			Yes						
				Sleep In			Yes						
Default				Status	Default Value								
				Power On Sequence	Display OFF								
				SW Reset	Display OFF								
				HW Reset	Display OFF								
Flow Chart	Display Off Mode → DISPON(29h) → Display On Mode Legend: Command, Parameter, Display, Action, Mode, Sequential transfer												

8.2.20. Column Address Set (2Ah)

2Ah				CASET (Column Address Set)									
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	1	0	1	0	1	0	2Ah
1st Parameter	1	1	↑	XX	SC15	SC14	SC13	SC12	SC11	SC10	SC9	SC8	Note1
2nd Parameter	1	1	↑	XX	SC7	SC6	SC5	SC4	SC3	SC2	SC1	SC0	
3rd Parameter	1	1	↑	XX	EC15	EC14	EC13	EC12	EC11	EC10	EC9	EC8	Note1
4th Parameter	1	1	↑	XX	EC7	EC6	EC5	EC4	EC3	EC2	EC1	EC0	

Description

This command is used to define area of frame memory where MCU can access. This command makes no change on the other driver status. The values of SC [15:0] and EC [15:0] are referred when RAMWR command comes. Each value represents one column line in the Frame Memory.

X = Don't care

Restriction

SC [15:0] always must be equal to or less than EC [15:0].

Note 1: When SC [15:0] or EC [15:0] is greater than 00EFh (When MADCTL's B5 = 0) or 013Fh (When MADCTL's B5 = 1), data of out of range will be ignored

Register Availability

Status	Availability
Normal Mode On, Idle Mode Off, Sleep Out	Yes
Normal Mode On, Idle Mode On, Sleep Out	Yes
Partial Mode On, Idle Mode Off, Sleep Out	Yes
Partial Mode On, Idle Mode On, Sleep Out	Yes
Sleep In	Yes

Default

Status	Default Value	
Power On Sequence	SC [15:0]=0000h	EC [15:0]=00EFh
SW Reset	SC [15:0]=0000h	If MADCTL's B5 = 0: EC [15:0]=00EFh If MADCTL's B5 = 1: EC [15:0]=013Fh
HW Reset	SC [15:0]=0000h	EC [15:0]=00EFh

Flow Chart

CASET (2Ah)

1st Parameter: SC[15:8]
2nd Parameter: SC[7:0]
3rd Parameter: EC[15:8]
4th Parmeter EC[7:0]

If
Needed

PASET (2Bh)

1st Parameter: SP[15:8]
2nd Parameter: SP[7:0]
3rd Parameter: EP[15:8]
4th Parameter: EP[7:0]

RAMWR(2Ch)

Image Data
D1[17:0],D2[17:0]..Dn[17:0]

If
Needed

Any Commend

Legend

Command

Parameter

Display

Action

Mode

Sequential transfer

8.2.21. Page Address Set (2Bh)

2Bh	PASET (Page Address Set)												
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	1	0	1	0	1	1	2Bh
1st Parameter	1	1	↑	XX	SP15	SP14	SP13	SP12	SP11	SP10	SP9	SP8	Note1
2nd Parameter	1	1	↑	XX	SP7	SP6	SP5	SP4	SP3	SP2	SP1	SP0	Note1
3rd Parameter	1	1	↑	XX	EP15	EP14	EP13	EP12	EP11	EP10	EP9	EP8	Note1
4th Parameter	1	1	↑	XX	EP7	EP6	EP5	EP4	EP3	EP2	EP1	EP0	Note1
Description	This command is used to define area of frame memory where MCU can access. This command makes no change on the other driver status. The values of SP [15:0] and EP [15:0] are referred when RAMWR command comes. Each value represents one Page line in the Frame Memory. X = Don't care												
Restriction	SP [15:0] always must be equal to or less than EP [15:0] Note 1: When SP [15:0] or EP [15:0] is greater than 013Fh (When MADCTL's B5 = 0) or 00EFh (When MADCTL's B5 = 1), data of out of range will be ignored.												

Status	Availability
Normal Mode On, Idle Mode Off, Sleep Out	Yes
Normal Mode On, Idle Mode On, Sleep Out	Yes
Partial Mode On, Idle Mode Off, Sleep Out	Yes
Partial Mode On, Idle Mode On, Sleep Out	Yes
Sleep In	Yes

Register Availability

Status	Default Value	
Power On Sequence	SP [15:0]=0000h	EP [15:0]=013Fh
SW Reset	SP [15:0]=0000h	If MADCTL's B5 = 0: EP [15:0]=013Fh If MADCTL's B5 = 1: EP [15:0]=00EFh
HW Reset	SP [15:0]=0000h	EP [15:0]=013Fh

Default

Flow Chart	

CASET (2Ah)

1st Parameter: SC[15:8]
2nd Parameter: SC[7:0]
3rd Parameter: EC[15:8]
4th Parmeter EC[7:0]

If Needed

PASET (2Bh)

1st Parameter: SP[15:8]
2nd Parameter: SP[7:0]
3rd Parameter: EP[15:8]
4th Parameter: EP[7:0]

RAMWR(2Ch)

If Needed

Image Data
D1[17:0],D2[17:0]..Dn[17:0]

Any Commend

Legend

Command

Parameter

Display

Action

Mode

Sequential transfer

8.2.22. Memory Write (2Ch)

2Ch	RAMWR (Memory Write)												
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	1	0	1	1	0	0	2Ch
1st Parameter	1	1	↑	D1 [17:0]									XX
:	1	1	↑	Dx [17:0]									XX
Nth Parameter	1	1	↑	Dn [17:0]									XX

Description	This command is used to transfer data from MCU to frame memory. This command makes no change to the other driver status. When this command is accepted, the column register and the page register are reset to the Start Column/Start Page positions. The Start Column/Start Page positions are different in accordance with MADCTL setting.) Then D [17:0] is stored in frame memory and the column register and the page register incremented. Sending any other command can stop frame Write. X = Don't care.
Restriction	In all color modes, there is no restriction on length of parameters.

Register Availability

Status	Availability
Normal Mode On, Idle Mode Off, Sleep Out	Yes
Normal Mode On, Idle Mode On, Sleep Out	Yes
Partial Mode On, Idle Mode Off, Sleep Out	Yes
Partial Mode On, Idle Mode On, Sleep Out	Yes
Sleep In	Yes

Default

Status	Default Value
Power On Sequence	Contents of memory is set randomly
SW Reset	Contents of memory is not cleared
HW Reset	Contents of memory is not cleared

Flow Chart

8.2.23. Color Set (2Dh)

2Dh	RGBSET (Color Set)												
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	1	0	1	1	0	1	2Dh
1st Parameter	1	1	↑	XX	0	0	R00 [5:0]						XX
nth Parameter	1	1	↑	XX	0	0	Rnn [5:0]						XX
32nd Parameter	1	1	↑	XX	0	0	R31 [5:0]						XX
33rd Parameter	1	1	↑	XX	0	0	G00 [5:0]						XX
nth Parameter	1	1	↑	XX	0	0	Gnn [5:0]						XX
96th Parameter	1	1	↑	XX	0	0	G64 [5:0]						XX
97th Parameter	1	1	↑	XX	0	0	B00 [5:0]						XX
nth Parameter	1	1	↑	XX	0	0	Bnn [5:0]						XX
128th Parameter	1	1	↑	XX	0	0	B31 [5:0]						XX

Description	This command is used to define the LUT for 16-bit to 18-bit color depth conversion. 128 bytes must be written to the LUT regardless of the color mode. Only the values in Section 7.4 are referred. This command has no effect on other commands, parameter and contents of frame memory. Visible change takes effect next time the frame memory is written to.
Restriction	

Register Availability

Status	Availability
Normal Mode On, Idle Mode Off, Sleep Out	Yes
Normal Mode On, Idle Mode On, Sleep Out	Yes
Partial Mode On, Idle Mode Off, Sleep Out	Yes
Partial Mode On, Idle Mode On, Sleep Out	Yes
Sleep In	Yes

Default

Status	Default Value
Power On Sequence	Random values
SW Reset	Contents of LUT protected
HW Reset	Random values

Flow Chart

RGBSET (2Dh)

1st Parameter: R00[5:0]
:
32nd Parameter: R31[5:0]
33rd Parameter: G00[5:0]
:
96th Parameter: G63[5:0]
97th Parameter: B00[5:0]
:
128th Parameter: B31[5:0]

Legend

Command
Parameter
Display
Action
Mode
Sequential transfer

8.2.24. Memory Read (2Eh)

2Eh				RAMRD (Memory Read)									
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	1	0	1	1	1	0	2Eh
1stParameter	1	1	↑	XX	X	X	X	X	X	X	X	X	X
2ndParameter	1	1	↑	D1 [17:0]									XX
:	1	1	↑	Dx [17:0]									XX
(N+1)th Parameter	1	1	↑	Dn [17:0]									XX

Description	This command transfers image data from ILI9341's frame memory to the host processor starting at the pixel location specified by preceding set_column_address and set_page_address commands. If Memory Access control B5 = 0: The column and page registers are reset to the Start Column (SC) and Start Page (SP), respectively. Pixels are read from frame memory at (SC, SP). The column register is then incremented and pixels read from the frame memory until the column register equals the End Column (EC) value. The column register is then reset to SC and the page register is incremented. Pixels are read from the frame memory until the page register equals the End Page (EP) value or the host processor sends another command. If Memory Access Control B5 = 1: The column and page registers are reset to the Start Column (SC) and Start Page (SP), respectively. Pixels are read from frame memory at (SC, SP). The page register is then incremented and pixels read from the frame memory until the page register equals the End Page (EP) value. The page register is then reset to SP and the column register is incremented. Pixels are read from the frame memory until the column register equals the End Column (EC) value or the host processor sends another command.
Restriction	There is no restriction on length of parameters.

Register Availability	Status	Availability
	Normal Mode On, Idle Mode Off, Sleep Out	Yes
	Normal Mode On, Idle Mode On, Sleep Out	Yes
	Partial Mode On, Idle Mode Off, Sleep Out	Yes
	Partial Mode On, Idle Mode On, Sleep Out	Yes
	Sleep In	Yes

Default	Status	Default Value
	Power On Sequence	Contents of memory is set randomly
	SW Reset	Contents of memory is set randomly
	HW Reset	Contents of memory is set randomly

Flow Chart	

RAMRD (2Eh)

Dummy Read

Image Data
D1[17:0],D2[17:0]..Dn[17:0]

Any Command

Legend

Command

Parameter

Display

Action

Mode

Sequential transfer

8.2.25. Partial Area (30h)

30h							PLTAR (Partial Area)						
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	1	1	0	0	0	0	30h
1st Parameter	1	1	↑	XX	SR15	SR14	SR13	SR12	SR11	SR10	SR9	SR8	00
2nd Parameter	1	1	↑	XX	SR7	SR6	SR5	SR4	SR3	SR2	SR1	SR0	00
3rd Parameter	1	1	↑	XX	ER15	ER14	ER13	ER12	ER11	ER10	ER9	ER8	01
4th Parameter	1	1	↑	XX	ER7	ER6	ER5	ER4	ER3	ER2	ER1	ER0	3F
Description	This command defines the partial mode's display area. There are 2 parameters associated with this command, the first defines the Start Row (SR) and the second the End Row (ER), as illustrated in the figures below. SR and ER refer to the Frame Memory Line Pointer. If End Row>Start Row when MADCTL B4=0:- If End Row>Start Row when MADCTL B4=1:- If End Row<Start Row when MADCTL B4=0:- If End Row = Start Row then the Partial Area will be one row deep. X = Don't care.												
Restriction	SR [15…0] and ER [15…0] cannot be 0000h nor exceed 013Fh.												

Status	Availability
Normal Mode On, Idle Mode Off, Sleep Out	Yes
Normal Mode On, Idle Mode On, Sleep Out	Yes
Partial Mode On, Idle Mode Off, Sleep Out	Yes
Partial Mode On, Idle Mode On, Sleep Out	Yes
Sleep In	Yes

Register Availability

Status	Default Value	
	SR [15:0]	ER [15:0]
Power On Sequence	16'h0000h	16'h013Fh
SW Reset	16'h 0000h	16'h 013Fh
HW Reset	16'h 0000h	16'h 013Fh

Default

Flow Chart

1. To Enter Partial Mode

2. To Leave Partial Mode

8.2.26. Vertical Scrolling Definition (33h)

33h	VSCRDEF (Vertical Scrolling Definition)												
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	1	1	0	0	1	1	33h
1st Parameter	1	↑	1	XX	TFA [15:8]								00
2nd Parameter	1	↑	1	XX	TFA [7:0]								00
3rd Parameter	1	↑	1	XX	VSA [15:8]								01
4th Parameter	1	↑	1	XX	VSA [7:0]								40
5th Parameter	1	↑	1	XX	BFA [15:8]								00
6th Parameter	1	↑	1	XX	BFA [7:0]								00
Description	This command defines the Vertical Scrolling Area of the display. When MADCTL B4=0 The 1st & 2nd parameter TFA [15...0] describes the Top Fixed Area (in No. of lines from Top of the Frame Memory and Display). The 3rd & 4th parameter VSA [15...0] describes the height of the Vertical Scrolling Area (in No. of lines of the Frame Memory [not the display] from the Vertical Scrolling Start Address). The first line read from Frame Memory appears immediately after the bottom most line of the Top Fixed Area. The 5th & 6th parameter BFA [15...0] describes the Bottom Fixed Area (in No. of lines from Bottom of the Frame Memory and Display). TFA, VSA and BFA refer to the Frame Memory Line Pointer. When MADCTL B4=1 The 1st & 2nd parameter TFA [15...0] describes the Top Fixed Area (in No. of lines from Bottom of the Frame Memory and Display). The 3rd & 4th parameter VSA [15...0] describes the height of the Vertical Scrolling Area (in No. of lines of the Frame Memory [not the display] from the Vertical Scrolling Start Address). The first line read from Frame Memory appears immediately after the top most line of the Top Fixed Area. The 5th & 6th parameter BFA [15...0] describes the Bottom Fixed Area (in No. of lines from Top of the Frame Memory and Display).

X = Don't care

Restriction	

Register Availability

Status	Availability
Normal Mode On, Idle Mode Off, Sleep Out	Yes
Normal Mode On, Idle Mode On, Sleep Out	Yes
Partial Mode On, Idle Mode Off, Sleep Out	Yes
Partial Mode On, Idle Mode On, Sleep Out	Yes
Sleep In	Yes

Default

Status	Default Value		
	TFA [15:0]	VSA [15:0]	BFA [15:0]
Power On Sequence	16'h0000h	16'h0140h	16'h0000h
SW Reset	16'h0000h	16'h0140h	16'h0000h
HW Reset	16'h0000h	16'h0140h	16'h0000h

Flow Chart	1. To enter Vertical Scroll Mode :

1. To enter Vertical Scroll Mode :

Normal Mode

VSCRDEF (33h)

1st & 2nd parameter :
TFA[15:0]

3rd & 4th Parameter
VSA[15:0]

5th & 6th Parameter
BFA[15:0]

CASET(2Ah)

1st & 2nd parameter :
SC[15:0]

3rd & 4th Parameter
EC[15:0]

PASET(2Bh)

1st & 2nd parameter :
SP[15:0]

3rd & 4th Parameter
EP[15:0]

MADCTL

Parameter

RAMRW(2Ch)

Scroll Image Data

VSCRSADD(37h)

1st & 2nd parameter :
VSP[15:0]

Normal Mode

Only required for non-rolling scrolling

Only required for non-rolling scrolling

Optional : It may be necessary to redefine the Frame Memory Write Direction

Legend

Command

Parameter

Display

Action

Mode

Sequential transfer

Note : The Frame Memory Window size ,must be defined correctly otherwise undesirable image will be displayed.

2. Continuous Scroll :

```
┌─────────────────┐
│   Scroll Mode   │
└─────────────────┘
         │
         ▼
   ┌──────────────┐
   │ CASET (2Ah)  │◄──────┐
   └──────────────┘       │
         │                │
         ▼                │
 ┌──────────────────┐     │
 │ 1st & 2nd param: │     │
 │    SC[15:0]      │     │
 └──────────────────┘     │
         │                │
         ▼                │
 ┌──────────────────┐     │
 │ 3rd & 4th Param  │     │
 │    EC[15:0]      │     │
 └──────────────────┘     │
         │                │
         ▼                │
   ┌──────────────┐       │
   │ PASET (2Bh)  │       │
   └──────────────┘       │
         │                │
         ▼                │
 ┌──────────────────┐     │
 │ 1st & 2nd param: │     │
 │    SP[15:0]      │     │
 └──────────────────┘     │
         │                │
         ▼                │
 ┌──────────────────┐     │
 │ 3rd & 4th Param  │     │
 │    EP[15:0]      │     │
 └──────────────────┘     │
         │                │
         ▼                │
   ┌──────────────┐       │
   │    RAMRW     │       │
   └──────────────┘       │
         │                │
         ▼                │
  ╭───────────────╮       │
  │ Scroll Image  │       │
  │     Data      │       │
  ╰───────────────╯       │
         │                │
         ▼                │
 ┌──────────────────┐     │
 │ VSCRSADD(37h)    │─────┘
 └──────────────────┘
```

Legend

- Command
- Parameter
- Display
- Action
- Mode
- Sequential transfer

3.To Leave Vertical Scroll Mode:

```
┌─────────────────┐
│   Scroll Mode   │
└─────────────────┘
         │
         ▼
   ┌──────────────┐
   │ DISOFF(28h)  │◄──── (Optional )
   └──────────────┘      To prevent Tearing Effect Image
         │               Display
         ▼
 ┌──────────────────────┐
 │ MORON(12h)/PTLON(12h)│
 └──────────────────────┘
         │
         ▼
 ┌─────────────────┐
 │ Scroll Mode Off │
 └─────────────────┘
         │
         ▼
   ┌──────────────┐
   │ RAMRW(2Ch)   │
   └──────────────┘
         │
         ▼
  ╭────────────────────────────╮
  │       Image Data           │
  │ D1[17:0],D2[17:0]...Dn[17:0]│
  ╰────────────────────────────╯
         │
         ▼
   ┌──────────────┐
   │ DISON(29h)   │
   └──────────────┘
```

Note: Scroll Mode can be left by both the Normal Display Mode ON (13h) and Partial Mode ON (12h) commands.

8.2.27. Tearing Effect Line OFF (34h)

34h													
	TEOFF (Tearing Effect Line OFF)												
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	1	1	0	1	0	0	34h
Parameter	No Parameter												
Description	This command is used to turn OFF (Active Low) the Tearing Effect output signal from the TE signal line. X = Don't care.												
Restriction	This command has no effect when Tearing Effect output is already OFF.												
Register Availability													
Default													
Flow Chart													

Register Availability

Status	Availability
Normal Mode On, Idle Mode Off, Sleep Out	Yes
Normal Mode On, Idle Mode On, Sleep Out	Yes
Partial Mode On, Idle Mode Off, Sleep Out	Yes
Partial Mode On, Idle Mode On, Sleep Out	Yes
Sleep In	Yes

Default

Status	Default Value
Power On Sequence	OFF
SW Reset	OFF
HW Reset	OFF

Flow Chart

TE Line Output ON

TEOFF(34h)

TE Line Output OFF

Legend

Command

Parameter

Display

Action

Mode

Sequential transfer

8.2.28. Tearing Effect Line ON (35h)

35h	TEON (Tearing Effect Line ON)												
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	1	1	0	1	0	1	35h
Parameter	1	1	↑	XX	0	0	0	0	0	0	0	M	00
Description	This command is used to turn ON the Tearing Effect output signal from the TE signal line. This output is not affected by changing MADCTL bit B4. The Tearing Effect Line On has one parameter which describes the mode of the Tearing Effect Output Line. When **M=0**: The Tearing Effect Output line consists of V-Blanking information only: When **M=1**: The Tearing Effect Output Line consists of both V-Blanking and H-Blanking information: Note: During Sleep In Mode with Tearing Effect Line On, Tearing Effect Output pin will be active Low. X = Don't care.
Restriction	This command has no effect when Tearing Effect output is already ON
Register Availability	<table><tr><th>Status</th><th>Availability</th></tr><tr><td>Normal Mode On, Idle Mode Off, Sleep Out</td><td>Yes</td></tr><tr><td>Normal Mode On, Idle Mode On, Sleep Out</td><td>Yes</td></tr><tr><td>Partial Mode On, Idle Mode Off, Sleep Out</td><td>Yes</td></tr><tr><td>Partial Mode On, Idle Mode On, Sleep Out</td><td>Yes</td></tr><tr><td>Sleep In</td><td>Yes</td></tr></table>
Default	<table><tr><th>Status</th><th>Default Value</th></tr><tr><td>Power On Sequence</td><td>OFF</td></tr><tr><td>SW Reset</td><td>OFF</td></tr><tr><td>HW Reset</td><td>OFF</td></tr></table>

Flow Chart	

TE Line Output OFF

TEON(35h)

1st Parameter: M bit

TE Line Output ON

Legend

Command

Parameter

Display

Action

Mode

Sequential transfer

8.2.29. Memory Access Control (36h)

36h				MADCTL (Memory Access Control)									
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	1	1	0	1	1	0	36h
Parameter	1	1	↑	XX	MY	MX	MV	ML	BGR	MH	0	0	00

Description	This command defines read/write scanning direction of frame memory.
	This command makes no change on the other driver status.

Bit	Name	Description
MY	Row Address Order	These 3 bits control MCU to memory write/read direction.
MX	Column Address Order	
MV	Row / Column Exchange	
ML	Vertical Refresh Order	LCD vertical refresh direction control.
BGR	RGB-BGR Order	Color selector switch control (0=RGB color filter panel, 1=BGR color filter panel)
MH	Horizontal Refresh ORDER	LCD horizontal refreshing direction control.

Note: When BGR bit is changed, the new setting is active immediately without update the content in Frame Memory again.

X = Don't care.

The information contained herein is the exclusive property of ILI Technology Corp. and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of ILI Technology Corp.

Page 127 of 245

MH(Horizontal refresh order control bit)="0"	MH(Horizontal refresh order control bit)="1"

Note: Top-Left (0,0) means a physical memory location.

Restriction

Register Availability

Status	Availability
Normal Mode On, Idle Mode Off, Sleep Out	Yes
Normal Mode On, Idle Mode On, Sleep Out	Yes
Partial Mode On, Idle Mode Off, Sleep Out	Yes
Partial Mode On, Idle Mode On, Sleep Out	Yes
Sleep In	Yes

Default

Status	Default Value
Power On Sequence	8'h00h
SW Reset	No change
HW Reset	8'h00h

Flow Chart

MADCTR(36h)

1st Parameter: MY, MX, MV, ML, RGB, MH

Legend

Command

Parameter

Display

Action

Mode

Sequential transfer

8.2.30. Vertical Scrolling Start Address (37h)

37h				VSCRSADD (Vertical Scrolling Start Address)									
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	1	1	0	1	1	1	37h
1st Parameter	1	↑	1	XX	VSP [15:8]								00
2nd Parameter	1	↑	1	XX	VSP [7:0]								00

| Description | This command is used together with Vertical Scrolling Definition (33h). These two commands describe the scrolling area and the scrolling mode. The Vertical Scrolling Start Address command has one parameter which describes the address of the line in the Frame Memory that will be written as the first line after the last line of the Top Fixed Area on the display as illustrated below:-

When MADCTL B4=0

Example:

When Top Fixed Area = Bottom Fixed Area = 00, Vertical Scrolling Area = 320 and VSP='3'.

When MADCTL B4=1

Example:

When Top Fixed Area = Bottom Fixed Area = 00, Vertical Scrolling Area = 320 and VSP='3'.

Note: (1) When new Pointer position and Picture Data are sent, the result on the display will happen at the next Panel Scan to avoid tearing effect. VSP refers to the Frame Memory line Pointer.

(2) This command is ignored when the ILI9341 enters Partial mode.

X = Don't care |

Restriction	
Register Availability	<table><tr><td>Status</td><td>Availability</td></tr><tr><td>Normal Mode On, Idle Mode Off, Sleep Out</td><td>Yes</td></tr><tr><td>Normal Mode On, Idle Mode On, Sleep Out</td><td>Yes</td></tr><tr><td>Partial Mode On, Idle Mode Off, Sleep Out</td><td>No</td></tr><tr><td>Partial Mode On, Idle Mode On, Sleep Out</td><td>No</td></tr><tr><td>Sleep In</td><td>Yes</td></tr></table>
Default	<table><tr><td rowspan="2">Status</td><td>Default Value</td></tr><tr><td>VSP [15:0]</td></tr><tr><td>Power On Sequence</td><td>16'h0000h</td></tr><tr><td>SW Reset</td><td>16'h0000h</td></tr><tr><td>HW Reset</td><td>16'h0000h</td></tr></table>
Flow Chart	See Vertical Scrolling Definition (33h) description.

8.2.31. Idle Mode OFF (38h)

38h	IDMOFF (Idle Mode OFF)											
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	1	1	1	0	0	0	38h
Parameter	No Parameter											

Description	This command is used to recover from Idle mode on. In the idle off mode, LCD can display maximum 262,144 colors. X = Don't care.
Restriction	This command has no effect when module is already in idle off mode.

Register Availability

Status	Availability
Normal Mode On, Idle Mode Off, Sleep Out	Yes
Normal Mode On, Idle Mode On, Sleep Out	Yes
Partial Mode On, Idle Mode Off, Sleep Out	Yes
Partial Mode On, Idle Mode On, Sleep Out	Yes
Sleep In	Yes

Default

Status	Default Value
Power On Sequence	Idle mode OFF
SW Reset	Idle mode OFF
HW Reset	Idle mode OFF

Flow Chart

Idle mode on

IDMOFF(38h)

Idle mode off

Legend
Command
Parameter
Display
Action
Mode
Sequential transfer

8.2.32. Idle Mode ON (39h)

39h	IDMON (Idle Mode ON)											
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	1	1	1	0	0	1	39h
Parameter	No Parameter											

Description	This command is used to enter into Idle mode on.

This command is used to enter into Idle mode on.

In the idle on mode, color expression is reduced. The primary and the secondary colors using MSB of each R, G and B in the Frame Memory, 8 color depth data is displayed.

Memory   Panel Display

Memory Contents vs. Display Color			
	$R_5 R_4 R_3 R_2 R_1 R_0$	$G_5 G_4 G_3 G_2 G_1 G_0$	$B_5 B_4 B_3 B_2 B_1 B_0$
Black	0XXXXX	0XXXXX	0XXXXX
Blue	0XXXXX	0XXXXX	1XXXXX
Red	1XXXXX	0XXXXX	0XXXXX
Magenta	1XXXXX	0XXXXX	1XXXXX
Green	0XXXXX	1XXXXX	0XXXXX
Cyan	0XXXXX	1XXXXX	1XXXXX
Yellow	1XXXXX	1XXXXX	0XXXXX
White	1XXXXX	1XXXXX	1XXXXX

X = Don't care.

Restriction	This command has no effect when module is already in idle off mode.

Register Availability	

Status	Availability
Normal Mode On, Idle Mode Off, Sleep Out	Yes
Normal Mode On, Idle Mode On, Sleep Out	Yes
Partial Mode On, Idle Mode Off, Sleep Out	Yes
Partial Mode On, Idle Mode On, Sleep Out	Yes
Sleep In	Yes

Default	

Status	Default Value
Power On Sequence	Idle mode OFF
SW Reset	Idle mode OFF
HW Reset	Idle mode OFF

Flow Chart	

Idle mode off

IDMON(39h)

Idle mode on

Legend

Command

Parameter

Display

Action

Mode

Sequential transfer

8.2.33. COLMOD: Pixel Format Set (3Ah)

3Ah	PIXSET (Pixel Format Set)											
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	1	1	1	0	1	0	3Ah
Parameter	1	1	↑	XX	0	DPI [2:0]			0	DBI [2:0]			66
Description	This command sets the pixel format for the RGB image data used by the interface. DPI [2:0] is the pixel format select of RGB interface and DBI [2:0] is the pixel format of MCU interface. If a particular interface, either RGB interface or MCU interface, is not used then the corresponding bits in the parameter are ignored. The pixel format is shown in the table below. If using RGB Interface must selection serial interface. X = Don't care												
Restriction													
Register Availability													
Default													
Flow Chart													

DPI [2:0]			RGB Interface Format
0	0	0	Reserved
0	0	1	Reserved
0	1	0	Reserved
0	1	1	Reserved
1	0	0	Reserved
1	0	1	16 bits / pixel
1	1	0	18 bits / pixel
1	1	1	Reserved

DBI [2:0]			MCU Interface Format
0	0	0	Reserved
0	0	1	Reserved
0	1	0	Reserved
0	1	1	Reserved
1	0	0	Reserved
1	0	1	16 bits / pixel
1	1	0	18 bits / pixel
1	1	1	Reserved

Register Availability:

Status	Availability
Normal Mode On, Idle Mode Off, Sleep Out	Yes
Normal Mode On, Idle Mode On, Sleep Out	Yes
Partial Mode On, Idle Mode Off, Sleep Out	Yes
Partial Mode On, Idle Mode On, Sleep Out	Yes
Sleep In	Yes

Default:

Status	Default Value	
	DPI [2:0]	DBI [2:0]
Power On Sequence	3'b110	3'b110
SW Reset	No Change	No Change
HW Reset	3'b110	3'b110

Flow Chart:

COLMOD (3Ah)

DPI[2:0] RGB pixel format
DBI[2:0] MCU pixel format

Any Command

Legend

Command
Parameter
Display
Action
Mode
Sequential transfer

8.2.34. Write_Memory_Continue (3Ch)

3Ch				Write_Memory_Continue								
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	1	1	1	1	0	0	3Ch
1st Parameter	1	1	↑	D1 [17..8]	D1 [7]	D1 [6]	D1 [5]	D1 [4]	D1 [3]	D1 [2]	D1 [1]	D1 [0]	000 3FF
Xth Parameter	1	1	↑	Dx [17..8]	Dx [7]	Dx [6]	Dx [5]	Dx [4]	Dx [3]	Dx [2]	Dx [1]	Dx [0]	000 3FF
Nth Parameter	1	1	↑	Dn [17..8]	Dn [7]	Dn [6]	Dn [5]	Dn [4]	Dn [3]	Dn [2]	Dn [1]	Dn [0]	000 3FF

Description	This command transfers image data from the host processor to the display module's frame memory continuing from the pixel location following the previous write_memory_continue or write_memory_start command. **If set_address_mode B5 = 0:** Data is written continuing from the pixel location after the write range of the previous write_memory_start or write_memory_continue. The column register is then incremented and pixels are written to the frame memory until the column register equals the End Column (EC) value. The column register is then reset to SC and the page register is incremented. Pixels are written to the frame memory until the page register equals the End Page (EP) value and the column register equals the EC value, or the host processor sends another command. If the number of pixels exceeds (EC – SC + 1) * (EP – SP + 1) the extra pixels are ignored. **If set_address_mode B5 = 1:** Data is written continuing from the pixel location after the write range of the previous write_memory_start or write_memory_continue. The page register is then incremented and pixels are written to the frame memory until the page register equals the End Page (EP) value. The page register is then reset to SP and the column register is incremented. Pixels are written to the frame memory until the column register equals the End column (EC) value and the page register equals the EP value, or the host processor sends another command. If the number of pixels exceeds (EC – SC + 1) * (EP – SP + 1) the extra pixels are ignored. Sending any other command can stop frame Write. Frame Memory Access and Interface setting (B3h), WEMODE=0 When the transfer number of data exceeds (EC-SC+1)*(EP-SP+1), the exceeding data will be ignored. Frame Memory Access and Interface setting (B3h), WEMODE=1 When the transfer number of data exceeds (EC-SC+1)*(EP-SP+1), the column and page number will be reset, and the exceeding data will be written into the following column and page.
Restriction	A write_memory_start should follow a set_column_address, set_page_address or set_address_mode to define the write address. Otherwise, data written with write_memory_continue is written to undefined addresses.

		Status	Availability
Register Availability		Normal Mode On, Idle Mode Off, Sleep Out	Yes
		Normal Mode On, Idle Mode On, Sleep Out	Yes
		Partial Mode On, Idle Mode Off, Sleep Out	Yes
		Partial Mode On, Idle Mode On, Sleep Out	Yes
		Sleep In	No
Default		Status	Default Value
		Power On Sequence	Random value
		SW Reset	No change
		HW Reset	No change
Flow Chart			

8.2.35. Read_Memory_Continue (3Eh)

3Eh	Read_Memory_Continue												
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	0	1	1	1	1	1	0	3Eh
1st Parameter	1	↑	1	XX	X	X	X	X	X	X	X	X	X
2nd Parameter	1	↑	1	D1 [17..8]	D1 [7]	D1 [6]	D1 [5]	D1 [4]	D1 [3]	D1 [2]	D1 [1]	D1 [0]	000 3FF
xst Parameter	1	↑	1	Dx [17..8]	Dx [7]	Dx [6]	Dx [5]	Dx [4]	Dx [3]	Dx [2]	Dx [1]	Dx [0]	000 3FF
Nst Parameter	1	↑	1	Dn [17..8]	Dn [7]	Dn [6]	Dn [5]	Dn [4]	Dn [3]	Dn [2]	Dn [1]	Dn [0]	000 3FF

Description	This command transfers image data from the display module's frame memory to the host processor continuing from the location following the previous read_memory_continue (3Eh) or read_memory_start (2Eh) command. If set_address_mode B5 = 0: Pixels are read continuing from the pixel location after the read range of the previous read_memory_start or read_memory_continue. The column register is then incremented and pixels are read from the frame memory until the column register equals the End Column (EC) value. The column register is then reset to SC and the page register is incremented. Pixels are read from the frame memory until the page register equals the End Page (EP) value and the column register equals the EC value, or the host processor sends another command. If set_address_mode B5 = 1: Pixels are read continuing from the pixel location after the read range of the previous read_memory_start or read_memory_continue. The page register is then incremented and pixels are read from the frame memory until the page register equals the End Page (EP) value. The page register is then reset to SP and the column register is incremented. Pixels are read from the frame memory until the column register equals the End Column (EC) value and the page register equals the EP value, or the host processor sends another command. This command makes no change to the other driver status.
Restriction	A read_memory_start should follow a set_column_address, set_page_address or set_address_mode to define the read location. Otherwise, data read with read_memory_continue is undefined.
Register Availability	Status	Availability
	Normal Mode On, Idle Mode Off, Sleep Out	Yes
	Normal Mode On, Idle Mode On, Sleep Out	Yes
	Partial Mode On, Idle Mode Off, Sleep Out	Yes
	Partial Mode On, Idle Mode On, Sleep Out	Yes
	Sleep In	Yes
Default	Status	Default Value
	Power On Sequence	Random data
	SW Reset	No change
	HW Reset	No change

Flow Chart

Read_memory_start

Dummy Read

Image Data
D1[17:0],D2[17:0]
....,Dn[17:0]

Next Command

Legend

Command

Parameter

Display

Action

Mode

Sequential
transfer

8.2.36. Set_Tear_Scanline (44h)

44h				Set_Tear_Scanline									
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	1	0	0	0	1	0	0	44h
1st Parameter	1	1	↑	XX	0	0	0	0	0	0	0	STS [8]	00
2nd Parameter	1	1	↑	XX	STS [7]	STS [6]	STS [5]	STS [4]	STS [3]	STS [2]	STS [1]	STS [0]	00

Description	This command turns on the display Tearing Effect output signal on the TE signal line when the display reaches line STS. The TE signal is not affected by changing set_address_mode bit B4. The Tearing Effect Line On has one parameter that describes the Tearing Effect Output Line mode. Vertical Time Scale — tvdl — tvdh Note that set_tear_scanline with STS=0 is equivalent to set_tear_on with M=0. The Tearing Effect Output line shall be active low when the display module is in Sleep mode.
Restriction	-

Register Availability		
	Status	Availability
	Normal Mode On, Idle Mode Off, Sleep Out	Yes
	Normal Mode On, Idle Mode On, Sleep Out	Yes
	Partial Mode On, Idle Mode Off, Sleep Out	Yes
	Partial Mode On, Idle Mode On, Sleep Out	Yes
	Sleep In	Yes

Default		
	Status	Default Value
	Power On Sequence	STS [8:0]=0000h
	SW Reset	STS [8:0]=0000h
	HW Reset	STS [8:0]=0000h

Flow Chart	

8.2.37. Get_Scanline (45h)

45h				Get_Scanline									
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	1	0	0	0	1	0	1	45h
1st Parameter	1	↑	1	XX	X	X	X	X	X	X	X	X	X
2nd Parameter	1	↑	1	XX	0	0	0	0	0	0	GTS [9]	GTS [8]	00
3rd Parameter	1	↑	1	XX	GTS [7]	GTS [6]	GTS [5]	GTS [4]	GTS [3]	GTS [2]	GTS [1]	GTS [0]	00
Description	The display returns the current scan line, GTS, used to update the display device. The total number of scan lines on a display device is defined as VSYNC + VBP + VACT + VFP. The first scan line is defined as the first line of V-Sync and is denoted as Line 0. When in Sleep Mode, the value returned by get_scanline is undefined.												
Restriction	None												

Register Availability		
	Status	Availability
	Normal Mode On, Idle Mode Off, Sleep Out	Yes
	Normal Mode On, Idle Mode On, Sleep Out	Yes
	Partial Mode On, Idle Mode Off, Sleep Out	Yes
	Partial Mode On, Idle Mode On, Sleep Out	Yes
	Sleep In	Yes

Default		
	Status	Default Value GTS [9:0]
	Power On Sequence	GTS [9:0]=0000h
	SW Reset	GTS [9:0]=0000h
	HW Reset	GTS [9:0]=0000h

Flow Chart

8.2.38. Write Display Brightness (51h)

51h	WRDISBV (Write Display Brightness)												
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	1	0	1	0	0	0	1	51h
Parameter	1	1	↑	XX	DBV[7]	DBV[6]	DBV[5]	DBV[4]	DBV[3]	DBV[2]	DBV[1]	DBV[0]	00

Description	This command is used to adjust the brightness value of the display. It should be checked what is the relationship between this written value and output brightness of the display. This relationship is defined on the display module specification. In principle relationship is that 00h value means the lowest brightness and FFh value means the highest brightness.
Restriction	None
Register Availability	<table><tr><td>Status</td><td>Availability</td></tr><tr><td>Normal Mode On, Idle Mode Off, Sleep Out</td><td>Yes</td></tr><tr><td>Normal Mode On, Idle Mode On, Sleep Out</td><td>Yes</td></tr><tr><td>Partial Mode On, Idle Mode Off, Sleep Out</td><td>Yes</td></tr><tr><td>Partial Mode On, Idle Mode On, Sleep Out</td><td>Yes</td></tr><tr><td>Sleep In</td><td>Yes</td></tr></table>
Default	<table><tr><td rowspan="2">Status</td><td>Default Value</td></tr><tr><td>DBV [7:0]</td></tr><tr><td>Power On Sequence</td><td>8'h00h</td></tr><tr><td>SW Reset</td><td>8'h00h</td></tr><tr><td>HW Reset</td><td>8'h00h</td></tr></table>
Flow Chart	

8.2.39. Read Display Brightness (52h)

52h	RDDISBV (Read Display Brightness Value)												
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	1	0	1	0	0	1	0	52h
1st Parameter	1	↑	1	XX	X	X	X	X	X	X	X	X	X
2nd Parameter	1	↑	1	XX	DBV[7]	DBV[6]	DBV[5]	DBV[4]	DBV[3]	DBV[2]	DBV[1]	DBV[0]	00

Description	This command returns the brightness value of the display. It should be checked what the relationship between this returned value and output brightness of the display. This relationship is defined on the display module specification. In principle the relationship is that 00h value means the lowest brightness and FFh value means the highest brightness.
Restriction	The display module is sending 2nd parameter value on the data lines if the MCU wants to read more than one parameter (= more than 2 RDX cycle) on DBI Mode. Only 2nd parameter is sent on DSI (The 1st parameter is not sent).

Register Availability

Status	Availability
Normal Mode On, Idle Mode Off, Sleep Out	Yes
Normal Mode On, Idle Mode On, Sleep Out	Yes
Partial Mode On, Idle Mode Off, Sleep Out	Yes
Partial Mode On, Idle Mode On, Sleep Out	Yes
Sleep In	Yes

Default

Status	Default Value
	DBV [7:0]
Power On Sequence	8'h00h
SW Reset	8'h00h
HW Reset	8'h00h

Flow Chart

8.2.40. Write CTRL Display (53h)

53h	WRCTRLD (Write Control Display)												
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	1	0	1	0	0	1	1	53h
Parameter	1	1	↑	XX	0	0	BCTRL	0	DD	BL	0	0	00
Description	This command is used to control display brightness. **BCTRL**: Brightness Control Block On/Off, This bit is always used to switch brightness for display. 0 = Off (Brightness registers are 00h, DBV[7..0]) 1 = On (Brightness registers are active, according to the other parameters.) **DD**: Display Dimming, only for manual brightness setting DD = 0: Display Dimming is off DD = 1: Display Dimming is on **BL**: Backlight Control On/Off 0 = Off (Completely turn off backlight circuit. Control lines must be low.) 1 = On Dimming function is adapted to the brightness registers for display when bit BCTRL is changed at DD=1, e.g. BCTRL: 0 → 1 or 1→ 0. When BL bit change from "On" to "Off", backlight is turned off without gradual dimming, even if dimming-on (DD=1) are selected.												
Restriction	None												
Register Availability	<table><tr><th>Status</th><th>Availability</th></tr><tr><td>Normal Mode On, Idle Mode Off, Sleep Out</td><td>Yes</td></tr><tr><td>Normal Mode On, Idle Mode On, Sleep Out</td><td>Yes</td></tr><tr><td>Partial Mode On, Idle Mode Off, Sleep Out</td><td>Yes</td></tr><tr><td>Partial Mode On, Idle Mode On, Sleep Out</td><td>Yes</td></tr><tr><td>Sleep In</td><td>Yes</td></tr></table>												
Default	<table><tr><th rowspan="2">Status</th><th colspan="3">Default Value</th></tr><tr><th>BCTRL</th><th>DD</th><th>BL</th></tr><tr><td>Power On Sequence</td><td>1'b0</td><td>1'b0</td><td>1'b0</td></tr><tr><td>SW Reset</td><td>1'b0</td><td>1'b0</td><td>1'b0</td></tr><tr><td>HW Reset</td><td>1'b0</td><td>1'b0</td><td>1'b0</td></tr></table>												

Flow Chart	

Legend:
- Command
- Parameter
- Display
- Action
- Mode
- Sequential transfer

Flow chart:
- WRCTRLD
- BCTRL,DD,BL
- New Control Value Loaded

8.2.41. Read CTRL Display (54h)

54h	RDCTRLD (Read Control Display)											
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	1	0	1	0	1	0	0	54h
1st Parameter	1	↑	1	XX	X	X	X	X	X	X	X	X	XX
2nd Parameter	1	↑	1	XX	0	0	BCTRL	0	DD	BL	0	0	00

Description	This command is used to return brightness setting. **BCTRL**: Brightness Control Block On/Off, '0' = Off (Brightness registers are 00h) '1' = On (Brightness registers are active, according to the DBV[7..0] parameters.) **DD**: Display Dimming '0' = Display Dimming is off '1' = Display Dimming is on **BL**: Backlight On/Off '0' = Off (Completely turn off backlight circuit. Control lines must be low.) '1' = On
Restriction	The display module is sending 2nd parameter value on the data lines if the MCU wants to read more than one parameter (= more than 2 RDX cycle) on DBI. Only 2nd parameter is sent on DSI (The 1st parameter is not sent).
Register Availability	<table><tr><td>Status</td><td>Availability</td></tr><tr><td>Normal Mode On, Idle Mode Off, Sleep Out</td><td>Yes</td></tr><tr><td>Normal Mode On, Idle Mode On, Sleep Out</td><td>Yes</td></tr><tr><td>Partial Mode On, Idle Mode Off, Sleep Out</td><td>Yes</td></tr><tr><td>Partial Mode On, Idle Mode On, Sleep Out</td><td>Yes</td></tr><tr><td>Sleep In</td><td>Yes</td></tr></table>
Default	<table><tr><td rowspan="2">Status</td><td colspan="3">Default Value</td></tr><tr><td>BCTRL</td><td>DD</td><td>BL</td></tr><tr><td>Power On Sequence</td><td>1'b0</td><td>1'b0</td><td>1'b0</td></tr><tr><td>SW Reset</td><td>1'b0</td><td>1'b0</td><td>1'b0</td></tr><tr><td>HW Reset</td><td>1'b0</td><td>1'b0</td><td>1'b0</td></tr></table>

Flow Chart

8.2.42. Write Content Adaptive Brightness Control (55h)

55h	WRCABC (Write Content Adaptive Brightness Control)												
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	1	0	1	0	1	0	1	55h
Parameter	1	1	↑	XX	0	0	0	0	0	0	C [1]	C [0]	00

Description	This command is used to set parameters for image content based adaptive brightness control functionality. There is possible to use 4 different modes for content adaptive image functionality, which are defined on a table below.

C [1:0]	Default Value
2'b00	Off
2'b01	User Interface Image
2'b10	Still Picture
2'b11	Moving Image

Restriction	None

Register Availability		

Status	Availability
Normal Mode On, Idle Mode Off, Sleep Out	Yes
Normal Mode On, Idle Mode On, Sleep Out	Yes
Partial Mode On, Idle Mode Off, Sleep Out	Yes
Partial Mode On, Idle Mode On, Sleep Out	Yes
Sleep In	Yes

Default		

Status	Default Value
Power On Sequence	C [1:0]=00h
SW Reset	C [1:0]=00h
HW Reset	C [1:0]=00h

Flow Chart

8.2.43. Read Content Adaptive Brightness Control (56h)

56h	RDCABC (Read Content Adaptive Brightness Control)												
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	1	0	1	0	1	1	0	56h
1st Parameter	1	↑	1	XX	X	X	X	X	X	X	X	X	XX
2nd Parameter	1	↑	1	XX	0	0	0	0	0	0	C [1]	C [0]	00

Description	This command is used to read the settings for image content based adaptive brightness control functionality. It is possible to use 4 different modes for content adaptive image functionality, which are defined on a table below. <table><tr><td>C [1:0]</td><td>Default Value</td></tr><tr><td>2'b00</td><td>Off</td></tr><tr><td>2'b01</td><td>User Interface Image</td></tr><tr><td>2'b10</td><td>Still Picture</td></tr><tr><td>2'b11</td><td>Moving Image</td></tr></table>
Restriction	The display module is sending 2nd parameter value on the data lines if the MCU wants to read more than one parameter (= more than 2 RDX cycle) on DBI. Only 2nd parameter is sent on DSI (The 1st parameter is not sent).
Register Availability	<table><tr><td>Status</td><td>Availability</td></tr><tr><td>Normal Mode On, Idle Mode Off, Sleep Out</td><td>Yes</td></tr><tr><td>Normal Mode On, Idle Mode On, Sleep Out</td><td>Yes</td></tr><tr><td>Partial Mode On, Idle Mode Off, Sleep Out</td><td>Yes</td></tr><tr><td>Partial Mode On, Idle Mode On, Sleep Out</td><td>Yes</td></tr><tr><td>Sleep In</td><td>Yes</td></tr></table>
Default	<table><tr><td>Status</td><td>Default Value</td></tr><tr><td>Power On Sequence</td><td>C [1:0]=00h</td></tr><tr><td>SW Reset</td><td>C [1:0]=00h</td></tr><tr><td>HW Reset</td><td>C [1:0]=00h</td></tr></table>
Flow Chart	

8.2.44. Write CABC Minimum Brightness (5Eh)

5Eh				Backlight Control 1								
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	1	0	1	1	1	1	0	5Eh
Parameter	1	1	↑	XX	CMB [7]	CMB [6]	CMB [5]	CMB [4]	CMB [3]	CMB [2]	CMB [1]	CMB [0]	00

Description	This command is used to set the minimum brightness value of the display for CABC function. CMB[7:0]: CABC minimum brightness control, this parameter is used to avoid too much brightness reduction. When CABC is active, CABC cannot reduce the display brightness to less than CABC minimum brightness setting. Image processing function is worked as normal, even if the brightness cannot be changed. This function does not affect to the other function, manual brightness setting. Manual brightness can be set the display brightness to less than CABC minimum brightness. Smooth transition and dimming function can be worked as normal. When display brightness is turned off (BCTRL=0 of "Write CTRL Display (53h)"), CABC minimum brightness setting is ignored. In principle relationship is that 00h value means the lowest brightness for CABC and FFh value means the highest brightness for CABC.

Register Availability	Status	Availability
	Normal Mode On, Idle Mode Off, Sleep Out	Yes
	Normal Mode On, Idle Mode On, Sleep Out	Yes
	Partial Mode On, Idle Mode Off, Sleep Out	Yes
	Partial Mode On, Idle Mode On, Sleep Out	Yes
	Sleep In	Yes

Default	Status	Default Value CMB [7:0]
	Power On Sequence	8'h00h
	SW Reset	No Change
	HW Reset	8'h00h

8.2.45. Read CABC Minimum Brightness (5Fh)

5Fh				**Backlight Control 1**								
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	0	1	0	1	1	1	1	1	5Fh
1st Parameter	1	↑	1	XX	X	X	X	X	X	X	X	X	X
2nd Parameter	1	↑	1	XX	CMB [7]	CMB [6]	CMB [5]	CMB [4]	CMB [3]	CMB [2]	CMB [1]	CMB [0]	00

Description	This command returns the minimum brightness value of CABC function.
	In principle the relationship is that 00h value means the lowest brightness and FFh value means the highest brightness.
	CMB[7:0] is CABC minimum brightness specified with "Write CABC minimum brightness (5Eh)" command. In principle relationship is that 00h value means the lowest brightness for CABC and FFh value means the highest brightness for CABC.

Register Availability	Status	Availability
	Normal Mode On, Idle Mode Off, Sleep Out	Yes
	Normal Mode On, Idle Mode On, Sleep Out	Yes
	Partial Mode On, Idle Mode Off, Sleep Out	Yes
	Partial Mode On, Idle Mode On, Sleep Out	Yes
	Sleep In	Yes

Default	Status	Default Value CMB [7:0]
	Power On Sequence	8'h00h
	SW Reset	No Change
	HW Reset	8'h00h

8.2.46. Read ID1 (DAh)

DAh	RDID1 (Read ID1)											
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	1	0	1	1	0	1	0	DAh
1stParameter	1	↑	1	XX	X	X	X	X	X	X	X	X	X
2ndParameter	1	↑	1	XX	ID1 [7:0]								00

Description	This read byte identifies the LCD module's manufacturer ID and it is specified by User
	The 1st parameter is dummy data.
	The 2nd parameter is LCD module's manufacturer ID.
	X = Don't care

Restriction	

Register Availability		
	Status	Availability
	Normal Mode On, Idle Mode Off, Sleep Out	Yes
	Normal Mode On, Idle Mode On, Sleep Out	Yes
	Partial Mode On, Idle Mode Off, Sleep Out	Yes
	Partial Mode On, Idle Mode On, Sleep Out	Yes
	Sleep In	Yes

Default			
	Status	Default Value (Before MTP program)	Default Value (After MTP program)
	Power On Sequence	8'h00h	MTP value
	SW Reset	8'h00h	MTP value
	HW Reset	8'h00h	MTP value

Flow Chart	

RDID1(DAh)

Host

Driver

1st Parameter: Dummy Read
2nd Parameter: Send ID1[7:0]

Legend

Command

Parameter

Display

Action

Mode

Sequential transfer

8.2.47. Read ID2 (DBh)

DBh	RDID2 (Read ID2)												
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	1	0	1	1	0	1	1	DBh
1st Parameter	1	↑	1	XX	X	X	X	X	X	X	X	X	X
2nd Parameter	1	↑	1	XX	ID2 [7:0]								00

Description	This read byte is used to track the LCD module/driver version. It is defined by display supplier (with User's agreement) and changes each time a revision is made to the display, material or construction specifications. The 1st parameter is dummy data. The 2nd parameter is LCD module/driver version ID and the ID parameter range is from 80h to FFh. The ID2 can be programmed by MTP function. X = Don't care
Restriction	
Register Availability	<table><tr><th>Status</th><th>Availability</th></tr><tr><td>Normal Mode On, Idle Mode Off, Sleep Out</td><td>Yes</td></tr><tr><td>Normal Mode On, Idle Mode On, Sleep Out</td><td>Yes</td></tr><tr><td>Partial Mode On, Idle Mode Off, Sleep Out</td><td>Yes</td></tr><tr><td>Partial Mode On, Idle Mode On, Sleep Out</td><td>Yes</td></tr><tr><td>Sleep In</td><td>Yes</td></tr></table>
Default	<table><tr><th>Status</th><th>Default Value (Before MTP program)</th><th>Default Value (After MTP program)</th></tr><tr><td>Power On Sequence</td><td>8'h80h</td><td>MTP value</td></tr><tr><td>SW Reset</td><td>8'h80h</td><td>MTP value</td></tr><tr><td>HW Reset</td><td>8'h80h</td><td>MTP value</td></tr></table>
Flow Chart	RDID2(DBh) Host Driver 1st Parameter: Dummy Read 2nd Parameter: Send ID2[7:0] Legend Command Parameter Display Action Mode Sequential transfer

8.2.48. Read ID3 (DCh)

DCh							RDID3 (Read ID3)						
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	1	0	1	1	1	0	0	DCh
1stParameter	1	↑	1	XX	X	X	X	X	X	X	X	X	X
2ndParameter	1	↑	1	XX	ID3 [7:0]								00

Description	This read byte identifies the LCD module/driver and It is specified by User. The 1st parameter is dummy data. The 2nd parameter is LCD module/driver ID. The ID3 can be programmed by MTP function. X = Don't care
Restriction	

Register Availability		
	Status	Availability
	Normal Mode On, Idle Mode Off, Sleep Out	Yes
	Normal Mode On, Idle Mode On, Sleep Out	Yes
	Partial Mode On, Idle Mode Off, Sleep Out	Yes
	Partial Mode On, Idle Mode On, Sleep Out	Yes
	Sleep In	Yes

Default			
	Status	Default Value (Before MTP program)	Default Value (After MTP program)
	Power On Sequence	8'h00h	MTP value
	SW Reset	8'h00h	MTP value
	HW Reset	8'h00h	MTP value

Flow Chart	

RDID3(DCh)

Host
Driver

1st Parameter: Dummy Read
2nd Parameter: Send ID3[7:0]

Legend

Command
Parameter
Display
Action
Mode
Sequential transfer

8.3. Description of Level 2 Command

8.3.1. RGB Interface Signal Control (B0h)

B0h	\multicolumn IFMODE (Interface Mode Control)											
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	0	1	1	0	0	0	0	B0h
Parameter	1	1	↑	XX	ByPass_MODE	RCM [1]	RCM [0]	0	VSPL	HSPL	DPL	EPL	40

Description	Sets the operation status of the display interface. The setting becomes effective as soon as the command is received.
	EPL: DE polarity ("0"= High enable for RGB interface, "1"= Low enable for RGB interface)
	DPL: DOTCLK polarity set ("0"= data fetched at the rising time, "1"= data fetched at the falling time)
	HSPL: HSYNC polarity ("0"= Low level sync clock, "1"= High level sync clock)
	VSPL: VSYNC polarity ("0"= Low level sync clock, "1"= High level sync clock)
	RCM [1:0]: RGB interface selection (refer to the RGB interface section).
	ByPass_MODE: Select display data path whether Memory or Direct to Shift register when RGB Interface is used.

ByPass_MODE	Display Data Path
0	Direct to Shift Register (**default**)
1	Memory

Restriction	EXTC should be high to enable this command

Register Availability		
	Status	Availability
	Normal Mode ON, Idle Mode OFF, Sleep OUT	Yes
	Normal Mode ON, Idle Mode ON, Sleep OUT	Yes
	Partial Mode ON, Idle Mode OFF, Sleep OUT	Yes
	Partial Mode ON, Idle Mode ON, Sleep OUT	Yes
	Sleep IN	Yes

Default						
	Status	Default Value				
		ByPass_MODE	RCM [1:0]	VSPL	HSPL	DPL	EPL
	Power ON Sequence	1'b0	2'b10	1'b0	1'b0	1'b0	1'b1
	SW Reset	1'b0	2'b10	1'b0	1'b0	1'b0	1'b1
	HW Reset	1'b0	2'b10	1'b0	1'b0	1'b0	1'b1

8.3.2. Frame Rate Control (In Normal Mode/Full Colors) (B1h)

B1h				FRMCTR1 (Frame Rate Control (In Normal Mode / Full colors))								
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	0	1	1	0	0	0	1	B1h
1ˢᵗ Parameter	1	1	↑	XX	0	0	0	0	0	0	DIVA [1:0]		00
2ⁿᵈ Parameter	1	1	↑	XX	0	0	0	RTNA [4:0]					1B

Description

Formula to calculate frame frequency:

$$\text{Frame Rate} = \frac{fosc}{\text{Clocks per line} \times \text{Division ratio} \times (\text{Lines} + \text{VBP} + \text{VFP})}$$

Sets the division ratio for internal clocks of Normal mode at MCU interface.

fosc : internal oscillator frequency

Clocks per line : RTNA setting

Division ratio : DIVA setting

Lines : total driving line number

VBP : back porch line number

VFP : front porch line number

RTNA [4:0]					Frame Rate (Hz)
1	0	0	0	0	119
1	0	0	0	1	112
1	0	0	1	0	106
1	0	0	1	1	100
1	0	1	0	0	95
1	0	1	0	1	90
1	0	1	1	0	86
1	0	1	1	1	83

RTNA [4:0]					Frame Rate (Hz)
1	1	0	0	0	79
1	1	0	0	1	76
1	1	0	1	0	73
1	1	0	1	1	70(default)
1	1	1	0	0	68
1	1	1	0	1	65
1	1	1	1	0	63
1	1	1	1	1	61

DIVA [1:0] : division ratio for internal clocks when Normal mode.

DIVA [1:0]		Division Ratio
0	0	fosc
0	1	fosc / 2
1	0	fosc / 4
1	1	fosc / 8

RTNA [4:0] : RTNA[4:0] is used to set 1H (line) period of Normal mode at MCU interface.

RTNA [4:0]					Clock per Line
0	0	0	0	0	Setting prohibited
0	0	0	0	1	Setting prohibited
0	0	0	1	0	Setting prohibited
0	0	0	1	1	Setting prohibited
0	0	1	0	0	Setting prohibited
0	0	1	0	1	Setting prohibited
0	0	1	1	0	Setting prohibited
0	0	1	1	1	Setting prohibited
0	1	0	0	0	Setting prohibited
0	1	0	0	1	Setting prohibited
0	1	0	1	0	Setting prohibited

RTNA [4:0]					Clock per Line
0	1	0	1	1	Setting prohibited
0	1	1	0	0	Setting prohibited
0	1	1	0	1	Setting prohibited
0	1	1	1	0	Setting prohibited
0	1	1	1	1	Setting prohibited
1	0	0	0	0	16 clocks
1	0	0	0	1	17 clocks
1	0	0	1	0	18 clocks
1	0	0	1	1	19 clocks
1	0	1	0	0	20 clocks
1	0	1	0	1	21 clocks

RTNA [4:0]					Clock per Line
1	0	1	1	0	22 clocks
1	0	1	1	1	23 clocks
1	1	0	0	0	24 clocks
1	1	0	0	1	25 clocks
1	1	0	1	0	26 clocks
1	1	0	1	1	27 clocks
1	1	1	0	0	28 clocks
1	1	1	0	1	29 clocks
1	1	1	1	0	30 clocks
1	1	1	1	1	31 clocks

Restriction	EXTC should be high to enable this command

Register Availability		
	Status	Availability
	Normal Mode ON, Idle Mode OFF, Sleep OUT	Yes
	Normal Mode ON, Idle Mode ON, Sleep OUT	Yes
	Partial Mode ON, Idle Mode OFF, Sleep OUT	Yes
	Partial Mode ON, Idle Mode ON, Sleep OUT	Yes
	Sleep IN	Yes

Default			
	Status	Default Value	
		DIVA [1:0]	RTNA [4:0]
	Power ON Sequence	2'b00	5'h1Bh
	SW Reset	2'b00	5'h1Bh
	HW Reset	2'b00	5'h1Bh

8.3.3. Frame Rate Control (In Idle Mode/8 colors) (B2h)

B2h				FRMCTR2 (Frame Rate Control (In Idle Mode / 8I colors))									
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	0	1	1	0	0	1	0	B2h
1st Parameter	1	1	↑	XX	0	0	0	0	0	0	DIVB [1:0]		00
2nd Parameter	1	1	↑	XX	0	0	0	RTNB [4:0]					1B

Formula to calculate frame frequency

$$\text{Frame Rate} = \frac{fosc}{\text{Clocks per line } \times \text{ Division ratio} \times (\text{Lines} + \text{VBP} + \text{VFP})}$$

Sets the division ratio for internal clocks of Idle mode at MCU interface.

fosc : internal oscillator frequency

Clocks per line : RTNB setting

Division ratio : DIVB setting

Lines : total driving line number

VBP : back porch line number

VFP : front porch line number

RTNB [4:0]					Frame Rate (Hz)
1	0	0	0	0	119
1	0	0	0	1	112
1	0	0	1	0	106
1	0	0	1	1	100
1	0	1	0	0	95
1	0	1	0	1	90
1	0	1	1	0	86
1	0	1	1	1	83

RTNB [4:0]					Frame Rate (Hz)
1	1	0	0	0	79
1	1	0	0	1	76
1	1	0	1	0	73
1	1	0	1	1	70(default)
1	1	1	0	0	68
1	1	1	0	1	65
1	1	1	0	1	63
1	1	1	1	1	61

DIVB [1:0]: division ratio for internal clocks when Idle mode.

DIVB [1:0]		Division Ratio
0	0	fosc
0	1	fosc / 2
1	0	fosc / 4
1	1	fosc / 8

RTNB [4:0]: RTNB[4:0] is used to set 1H (line) period of Idle mode at MCU interface.

RTNB [4:0]					Clock per Line
0	0	0	0	0	Setting prohibited
0	0	0	0	1	Setting prohibited
0	0	0	1	0	Setting prohibited
0	0	0	1	1	Setting prohibited
0	0	1	0	0	Setting prohibited
0	0	1	0	1	Setting prohibited
0	0	1	1	0	Setting prohibited
0	0	1	1	1	Setting prohibited
0	1	0	0	0	Setting prohibited
0	1	0	0	1	Setting prohibited
0	1	0	1	0	Setting prohibited

RTNB [4:0]					Clock per Line
0	1	0	1	1	Setting prohibited
0	1	1	0	0	Setting prohibited
0	1	1	0	1	Setting prohibited
0	1	1	1	0	Setting prohibited
0	1	1	1	1	Setting prohibited
1	0	0	0	0	16 clocks
1	0	0	0	1	17 clocks
1	0	0	1	0	18 clocks
1	0	0	1	1	19 clocks
1	0	1	0	0	20 clocks
1	0	1	0	1	21 clocks

RTNB [4:0]					Clock per Line
1	0	1	1	0	22 clocks
1	0	1	1	1	23 clocks
1	1	0	0	0	24 clocks
1	1	0	0	1	25 clocks
1	1	0	1	0	26 clocks
1	1	0	1	1	27 clocks
1	1	1	0	0	28 clocks
1	1	1	0	1	29 clocks
1	1	1	1	0	30 clocks
1	1	1	1	1	31 clocks

Description (row label)

Restriction	EXTC should be high to enable this command	
Register Availability		

Status	Availability
Normal Mode ON, Idle Mode OFF, Sleep OUT	Yes
Normal Mode ON, Idle Mode ON, Sleep OUT	Yes
Partial Mode ON, Idle Mode OFF, Sleep OUT	Yes
Partial Mode ON, Idle Mode ON, Sleep OUT	Yes
Sleep IN	Yes

Default

Status	Default Value	
	DIVB [1:0]	RTNB [4:0]
Power ON Sequence	2'b00	5'h1Bh
SW Reset	2'b00	5'h1Bh
HW Reset	2'b00	5'h1Bh

8.3.4. Frame Rate control (In Partial Mode/Full Colors) (B3h)

B3h	\multicolumn											
				FRMCTR3 (Frame Rate Control (In Partial Mode / Full colors))								
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	0	1	1	0	0	1	1	B3h
1st Parameter	1	1	↑	XX	0	0	0	0	0	0	DIVC [1:0]		00
2nd Parameter	1	1	↑	XX	0	0	0	RTNC [4:0]					1B

Description

Formula to calculate frame frequency:

$$\text{Frame Rate} = \frac{fosc}{\text{Clocks per line} \times \text{Division ratio} \times (\text{Lines} + \text{VBP} + \text{VFP})}$$

Sets the division ratio for internal clocks of Partial mode (Idle mode off) at MCU interface.

fosc : internal oscillator frequency

Clocks per line : RTNC setting

Division ratio : DIVC setting

Lines : total driving line number

VBP : back porch line number

VFP : front porch line number

RTNC [4:0]					Frame Rate (Hz)	RTNC [4:0]					Frame Rate (Hz)
1	0	0	0	0	119	1	1	0	0	0	79
1	0	0	0	1	112	1	1	0	0	1	76
1	0	0	1	0	106	1	1	0	1	0	73
1	0	0	1	1	100	1	1	0	1	1	70(default)
1	0	1	0	0	95	1	1	1	0	0	68
1	0	1	0	1	90	1	1	1	0	1	65
1	0	1	1	0	86	1	1	1	0	1	63
1	0	1	1	1	83	1	1	1	1	1	61

DIVC [1:0]: division ratio for internal clocks when Partial mode.

DIVC [1:0]		Division Ratio
0	0	fosc
0	1	fosc / 2
1	0	fosc / 4
1	1	fosc / 8

Note: 1clock unit=1.625u sec

RTNC [4:0]: RTNC [4:0] is used to set 1H (line) period of Partial mode at MCU interface.

RTNC [4:0]					Clock per Line	RTNC [4:0]					Clock per Line	RTNC [4:0]					Clock per Line
0	0	0	0	0	Setting prohibited	0	1	0	1	1	Setting prohibited	1	0	1	1	0	22 clocks
0	0	0	0	1	Setting prohibited	0	1	1	0	0	Setting prohibited	1	0	1	1	1	23 clocks
0	0	0	1	0	Setting prohibited	0	1	1	0	1	Setting prohibited	1	1	0	0	0	24 clocks
0	0	0	1	1	Setting prohibited	0	1	1	1	0	Setting prohibited	1	1	0	0	1	25 clocks
0	0	1	0	0	Setting prohibited	0	1	1	1	1	Setting prohibited	1	1	0	1	0	26 clocks
0	0	1	0	1	Setting prohibited	1	0	0	0	0	16 clocks	1	1	0	1	1	27 clocks
0	0	1	1	0	Setting prohibited	1	0	0	0	1	17 clocks	1	1	1	0	0	28 clocks
0	0	1	1	1	Setting prohibited	1	0	0	1	0	18 clocks	1	1	1	0	1	29 clocks
0	1	0	0	0	Setting prohibited	1	0	0	1	1	19 clocks	1	1	1	1	0	30 clocks
0	1	0	0	1	Setting prohibited	1	0	1	0	0	20 clocks	1	1	1	1	1	31 clocks
0	1	0	1	0	Setting prohibited	1	0	1	0	1	21 clocks						

Restriction	EXTC should be high to enable this command

Register Availability		Status	Availability
		Normal Mode ON, Idle Mode OFF, Sleep OUT	Yes
		Normal Mode ON, Idle Mode ON, Sleep OUT	Yes
		Partial Mode ON, Idle Mode OFF, Sleep OUT	Yes
		Partial Mode ON, Idle Mode ON, Sleep OUT	Yes
		Sleep IN	Yes

Default		Status	Default Value	
			DIVC [1:0]	RTNC [4:0]
		Power ON Sequence	2'b00	5'h1Bh
		SW Reset	2'b00	5'h1Bh
		HW Reset	2'b00	5'h1Bh

8.3.5. Display Inversion Control (B4h)

B4h	INVTR (Display Inversion Control)											
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	0	1	1	0	1	0	0	B4h
1st Parameter	1	1	↑	XX	0	0	0	0	0	NLA	NLB	NLC	02

Description	Display inversion mode set **NLA**: Inversion setting in full colors normal mode (Normal mode on) **NLB**: Inversion setting in Idle mode (Idle mode on) **NLC**: Inversion setting in full colors partial mode (Partial mode on / Idle mode off) <table><tr><td>NLA / NLB / NLC</td><td>Inversion</td></tr><tr><td>0</td><td>Line inversion</td></tr><tr><td>1</td><td>Frame inversion</td></tr></table>
Restriction	EXTC should be high to enable this command

Register Availability		
	Status	Availability
	Normal Mode ON, Idle Mode OFF, Sleep OUT	Yes
	Normal Mode ON, Idle Mode ON, Sleep OUT	Yes
	Partial Mode ON, Idle Mode OFF, Sleep OUT	Yes
	Partial Mode ON, Idle Mode ON, Sleep OUT	Yes
	Sleep IN	Yes

Default	Status	Default Value		
		NLA	NLB	NLC
	Power ON Sequence	1'b0	1'b1	1'b0
	SW Reset	1'b0	1'b1	1'b0
	H/W Reset	1'b0	1'b1	1'b0

8.3.6. Blanking Porch Control (B5h)

B5h				PRCTR (Blanking Porch)								
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	0	1	1	0	1	0	1	B5h
1st Parameter	1	1	↑	XX	0	VFP [6:0]							02
2nd Parameter	1	1	↑	XX	0	VBP [6:0]							02
3rd Parameter	1	1	↑	XX	0	0	0	HFP [4:0]					0A
4th Parameter	1	1	↑	XX	0	0	0	HBP [4:0]					14

VFP [6:0] / **VBP [6:0]:** The VFP [6:0] and VBP [6:0] bits specify the line number of vertical front and back porch period

respectively.

VFP [6:0] VBP [6:0]	Number of HSYNC of front/back porch	VFP [6:0] VBP [6:0]	Number of HSYNC of front/back porch
0000000	Setting inhibited	1000000	64
0000001	Setting inhibited	1000001	65
0000010	2	1000010	66
0000011	3	1000011	67
0000100	4	1000100	68
0000101	5	1000101	69
0000110	6	1000110	70
0000111	7	1000111	71
0001000	8	1001000	72
0001001	9	1001001	73
0001010	10	1001010	74
0001011	11	1001011	75
0001100	12	1001100	76
0001101	13	1001101	77
: :	: :	: :	: :
0111101	61	1111101	125
0111110	62	1111110	126
0111111	63	1111111	127

Note: VFP + VBP ≦ 254 HSYNC signals

HFP [4:0] / **HBP [4:0]:** The HFP [4:0] and HBP [4:0] bits specify the line number of horizontal front and back porch period

respectively.

HFP [4:0] HBP [4:0]	Number of DOTCLK of the front/back porch	HFP [4:0] HBP [4:0]	Number of DOTCLK of front/back porch
00000	Setting prohibited	10000	16
00001	Setting prohibited	10001	17
00010	2	10010	18
00011	3	10011	19
00100	4	10100	20
00101	5	10101	21
00110	6	10110	22
00111	7	10111	23
01000	8	11000	24
01001	9	11001	25
01010	10	11010	26
01011	11	11011	27
01100	12	11100	28
01101	13	11101	29
01110	14	11110	30
01111	15	11111	31

Description column label appears on the left side.

Restriction	EXTC should be high to enable this command			

Register Availability			
	Status	**Availability**	
	Normal Mode ON, Idle Mode OFF, Sleep OUT	Yes	
	Normal Mode ON, Idle Mode ON, Sleep OUT	Yes	
	Partial Mode ON, Idle Mode OFF, Sleep OUT	Yes	
	Partial Mode ON, Idle Mode ON, Sleep OUT	Yes	
	Sleep IN	Yes	

Default	Status	Default Value			
		VFP [6:0]	VBP [6:0]	HFP [4:0]	HBP [4:0]
	Power ON Sequence	7'h02h	7'h02h	5'h0Ah	5'h14h
	SW Reset	7'h02h	7'h02h	5'h0Ah	5'h14h
	HW Reset	7'h02h	7'h02h	5'h0Ah	5'h14h

8.3.7. Display Function Control (B6h)

B6h	DISCTRL (Display Function Control)												
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	0	1	1	0	1	1	0	B6h
1st Parameter	1	1	↑	XX	0	0	0	0	PTG [1:0]		PT [1:0]		0A
2nd Parameter	1	1	↑	XX	REV	GS	SS	SM	ISC [3:0]				82
3rd Parameter	1	1	↑	XX	0	0	NL [5:0]						27
4th Parameter	1	1	↑	XX	0	0	PCDIV [5:0]						XX

PTG [1:0]: Set the scan mode in non-display area.

PTG1	PTG0	Gate outputs in non-display area	Source outputs in non-display area	VCOM output
0	0	Normal scan	Set with the PT [2:0] bits	VCOMH/VCOML
0	1	Setting prohibited	---	---
1	0	Interval scan	Set with the PT [2:0] bits	
1	1	Setting prohibited	---	---

PT [1:0]: Determine source/VCOM output in a non-display area in the partial display mode.

PT [1:0]		Source output on non-display area		VCOM output on non-display area	
		Positive polarity	Negative polarity	Positive polarity	Negative polarity
0	0	V63	V0	VCOML	VCOMH
0	1	V0	V63	VCOML	VCOMH
1	0	AGND	AGND	AGND	AGND
1	1	Hi-Z	Hi-Z	AGND	AGND

SS: Select the shift direction of outputs from the source driver.

SS	Source Output Scan Direction
0	S1 → S720
1	S720 → S1

In addition to the shift direction, the settings for both SS and BGR bits are required to change the assignment of R, G, and B dots to the source driver pins.

To assign R, G, B dots to the source driver pins from S1 to S720, set SS = 0.

To assign R, G, B dots to the source driver pins from S720 to S1, set SS = 1.

REV: Select whether the liquid crystal type is normally white type or normally black type.

REV	Liquid crystal type
0	Normally black
1	Normally white

ISC [3:0]: Specify the scan cycle interval of gate driver in non-display area when PTG [1:0] ="10" to select interval scan.

Then scan cycle is set as odd number from 0~29 frame periods. The polarity is inverted every scan cycle.

ISC [3:0]	Scan Cycle	f_{FLM} = 60Hz
0000	1 frame	17ms
0001	3 frames	51ms
0010	5 frames	85ms
0011	7 frames	119ms
0100	9 frames	153ms
0101	11 frames	187ms
0110	13 frames	221ms
0111	15 frames	255ms

1000	17 frames	289ms
1001	19 frames	323ms
1010	21 frames	357ms
1011	23 frames	391ms
1100	25 frames	425ms
1101	27 frames	459ms
1110	29 frames	493ms
1111	31 frames	527ms

GS: Sets the direction of scan by the gate driver in the range determined by SCN [4:0] and NL [4:0]. The scan direction determined by GS = 0 can be reversed by setting GS = 1.

GS	Gate Output Scan Direction
0	G1 → G320
1	G320 → G1

SM: Sets the gate driver pin arrangement in combination with the GS bit to select the optimal scan mode for the module.

SM	GS	Scan Direction	Gate Output Sequence
0	0		G1→G2→G3→G4→ ……………… ….→G317→G318→G319→G320
0	1		G320→G319->G318→G317→…… …. →G4→G3→G2→G1

1	0	G1 ⋮ G319 / TFT Panel / Odd-number / G1 to G319 / Even-number / G2 ⋮ G320 / G2 to G320 / ILI9341	G1→G3→………..→G317→G319→ G2→G4→…………→G318→G320
1	1	G1 ⋮ G319 / TFT Panel / Odd-number / G1 to G319 / Even-number / G2 ⋮ G320 / G2 to G320 / ILI9341	G320→G318→………...→G4→G2→ G319→G317→…………→G3→G1

NL [5:0]: Sets the number of lines to drive the LCD at an interval of 8 lines. The GRAM address mapping is not affected by the number of lines set by NL [5:0]. The number of lines must be the same or more than the number of lines necessary for the size of the liquid crystal panel.

NL [5:0]						LCD Drive Line	NL [5:0]						LCD Driver Line
0	0	0	0	0	0	Setting prohibited	0	1	0	1	0	1	176 lines
0	0	0	0	0	1	16 lines	0	1	0	1	1	0	184 lines
0	0	0	0	1	0	24 lines	0	1	0	1	1	1	192 lines
0	0	0	0	1	1	32 lines	0	1	1	0	0	0	200 lines
0	0	0	1	0	0	40 lines	0	1	1	0	0	1	208 lines
0	0	0	1	0	1	48 lines	0	1	1	0	1	0	216 lines
0	0	0	1	1	0	56 lines	0	1	1	0	1	1	224 lines
0	0	0	1	1	1	64 lines	0	1	1	1	0	0	232 lines
0	0	1	0	0	0	72 lines	0	1	1	1	0	1	240 lines
0	0	1	0	0	1	80 lines	0	1	1	1	1	0	248 lines
0	0	1	0	1	0	88 lines	0	1	1	1	1	1	256 lines
0	0	1	0	1	1	96 lines	1	0	0	0	0	0	264 lines
0	0	1	1	0	0	104 lines	1	0	0	0	0	1	272 lines
0	0	1	1	0	1	112 lines	1	0	0	0	1	0	280 lines
0	0	1	1	1	0	120 lines	1	0	0	0	1	1	288 lines
0	0	1	1	1	1	128 lines	1	0	0	1	0	0	296 lines
0	1	0	0	0	0	136 lines	1	0	0	1	0	1	304 lines
0	1	0	0	0	1	144 lines	1	0	0	1	1	0	312 lines
0	1	0	0	1	0	152 lines	1	0	0	1	1	1	320 lines
0	1	0	0	1	1	160 lines	Others						Setting inhibited
0	1	0	1	0	0	168 lines							

PCDIV [5:0]:

$$\text{external fosc} = \frac{\text{DOTCLK}}{2 \ (\text{PCDIV} + 1)}$$

Restriction	EXTC should be high to enable this command

Register Availability

Status	Availability
Normal Mode ON, Idle Mode OFF, Sleep OUT	Yes
Normal Mode ON, Idle Mode ON, Sleep OUT	Yes
Partial Mode ON, Idle Mode OFF, Sleep OUT	Yes
Partial Mode ON, Idle Mode ON, Sleep OUT	Yes
Sleep IN	Yes

Default

Status	Default Value							
	PTG [1:0]	PT [1:0]	REV	GS	SS	SM	ISC [3:0]	NL [5:0]
Power ON Sequence	2'b10	2'b10	1'b1	1'b0	1'b0	1'b0	4'b0010	6'h27h
SW Reset	2'b10	2'b10	1'b1	1'b0	1'b0	1'b0	4'b0010	6'h27h
HW Reset	2'b10	2'b10	1'b1	1'b0	1'b0	1'b0	4'b0010	6'h27h

8.3.8. Entry Mode Set (B7h)

B7h				ETMOD (Entry Mode Set)									
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	0	1	1	0	1	1	1	B7h
Parameter	1	1	↑	XX	0	0	0	0	0	GON	DTE	GAS	06

Description

GAS: Low voltage detection control.

GAS	Low voltage detection
0	Enable
1	Disable

GON/DTE: Set the output level of gate driver G1 ~ G320 as follows

GON	DTE	G1~G320 Gate Output
0	0	VGH
0	1	VGH
1	0	VGL
1	1	Normal display

Restriction

EXTC should be high to enable this command

Register Availability

Status	Availability
Normal Mode ON, Idle Mode OFF, Sleep OUT	Yes
Normal Mode ON, Idle Mode ON, Sleep OUT	Yes
Partial Mode ON, Idle Mode OFF, Sleep OUT	Yes
Partial Mode ON, Idle Mode ON, Sleep OUT	Yes
Sleep IN	Yes

Default

Status	Default Value		
	GON	DTE	GAS
Power ON Sequence	1'b1	1'b1	1'b0
SW Reset	1'b1	1'b1	1'b0
HW Reset	1'b1	1'b1	1'b0

8.3.9. Backlight Control 1 (B8h)

B8h	Backlight Control 1											
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	0	1	1	1	0	0	0	B8h
Parameter		1	↑	XX	0	0	0	0	TH_UI [3]	TH_UI [2]	TH_UI [1]	TH_UI [0]	0C

Description	**TH_UI [3:0]**: These bits are used to set the percentage of grayscale data accumulate histogram value in the user interface (UI) mode. This ratio of maximum number of pixels that makes display image white (=data "255") to the total of pixels by image processing.

TH_UI [3:0]	Description
4'0h	99%
4'1h	98%
4'2h	96%
4'3h	94%
4'4h	92%
4'5h	90%
4'6h	88%
4'7h	86%

TH_UI [3:0]	Description
4'8h	84%
4'9h	82%
4'Ah	80%
4'Bh	78%
4'Ch	76%
4'Dh	74%
4'Eh	72%
4'Fh	70%

Register Availability

Status	Availability
Normal Mode On, Idle Mode Off, Sleep Out	Yes
Normal Mode On, Idle Mode On, Sleep Out	Yes
Partial Mode On, Idle Mode Off, Sleep Out	Yes
Partial Mode On, Idle Mode On, Sleep Out	Yes
Sleep In	Yes

Default

Status	Default Value
	TH_UI [3:0]
Power On Sequence	4'b0110
SW Reset	No change
HW Reset	4'b0110

8.3.10. Backlight Control 2 (B9h)

B9h					Backlight Control 2								
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	0	1	1	1	0	0	1	B9h
Parameter	1	1	↑	XX	TH_MV [3]	TH_MV [2]	TH_MV [1]	TH_MV [0]	TH_ST [3]	TH_ST [2]	TH_ST [1]	TH_ST [0]	CC

Description	**TH_ST [3:0]**: These bits are used to set the percentage of grayscale data accumulate histogram value in the still picture mode. This ratio of maximum number of pixels that makes display image white (=data "255") to the total of pixels by image processing.

TH_ST [3:0]	Description		TH_ST [3:0]	Description
4'0h	99%		4'8h	84%
4'1h	98%		4'9h	82%
4'2h	96%		4'Ah	80%
4'3h	94%		4'Bh	78%
4'4h	92%		4'Ch	76%
4'5h	90%		4'Dh	74%
4'6h	88%		4'Eh	72%
4'7h	86%		4'Fh	70%

TH_MV [3:0]: These bits are used to set the percentage of grayscale data accumulate histogram value in the moving image mode. This ratio of maximum number of pixels that makes display image white (=data "255") to the total of pixels by image processing.

TH_MV [3:0]	Description		TH_MV [3:0]	Description
4'0h	99%		4'8h	84%
4'1h	98%		4'9h	82%
4'2h	96%		4'Ah	80%
4'3h	94%		4'Bh	78%
4'4h	92%		4'Ch	76%
4'5h	90%		4'Dh	74%
4'6h	88%		4'Eh	72%
4'7h	86%		4'Fh	70%

Status	Availability
Normal Mode On, Idle Mode Off, Sleep Out	Yes
Normal Mode On, Idle Mode On, Sleep Out	Yes
Partial Mode On, Idle Mode Off, Sleep Out	Yes
Partial Mode On, Idle Mode On, Sleep Out	Yes
Sleep In	Yes

Register Availability

Status	Default Value	
	TH_MV [3:0]	TH_ST [3:0]
Power On Sequence	4'b1100	4'b1100
SW Reset	No change	No change
HW Reset	4'b1100	4'b1100

Default

8.3.11. Backlight Control 3 (BAh)

BAh				Backlight Control 3								
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	0	1	1	1	0	1	0	BAh
Parameter	1	1	↑	XX	0	0	0	0	DTH_UI [3]	DTH_UI [2]	DTH_UI [1]	DTH_UI [0]	04

Description	**DTH_UI [3:0]**: This parameter is used set the minimum limitation of grayscale threshold value in User Icon (UI) image mode. This register setting will limit the minimum Dth value to prevent the display image from being too white and the display quality is not acceptable. | DTH_UI [3:0]	Description		DTH_UI [3:0]	Description | |---|---|---|---|---| | 4'0h | 252 | | 4'8h | 220 | | 4'1h | 248 | | 4'9h | 216 | | 4'2h | 244 | | 4'Ah | 212 | | 4'3h | 240 | | 4'Bh | 208 | | 4'4h | 236 | | 4'Ch | 204 | | 4'5h | 232 | | 4'Dh | 200 | | 4'6h | 228 | | 4'Eh | 196 | | 4'7h | 224 | | 4'Fh | 192 |

The description table rendered cleanly:

DTH_UI [3:0]	Description		DTH_UI [3:0]	Description
4'0h	252		4'8h	220
4'1h	248		4'9h	216
4'2h	244		4'Ah	212
4'3h	240		4'Bh	208
4'4h	236		4'Ch	204
4'5h	232		4'Dh	200
4'6h	228		4'Eh	196
4'7h	224		4'Fh	192

Register Availability

Status	Availability
Normal Mode On, Idle Mode Off, Sleep Out	Yes
Normal Mode On, Idle Mode On, Sleep Out	Yes
Partial Mode On, Idle Mode Off, Sleep Out	Yes
Partial Mode On, Idle Mode On, Sleep Out	Yes
Sleep In	Yes

Default

Status	Default Value
	DTH_UI [3:0]
Power On Sequence	4'b0100
SW Reset	No change
HW Reset	4'b0100

8.3.12. Backlight Control 4 (BBh)

BBh	Backlight Control 4												
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	0	1	1	1	0	1	1	BBh
Parameter	1	1	↑	XX	DTH_MV [3]	DTH_MV [2]	DTH_MV [1]	DTH_MV [0]	DTH_ST [3]	DTH_ST [2]	DTH_ST [1]	DTH_ST [0]	65

DTH_ST [3:0]/DTH_MV [3:0]: This parameter is used set the minimum limitation of grayscale threshold value. This register setting will limit the minimum Dth value to prevent the display image from being too white and the display quality is not acceptable.

DTH_ST [3:0]	Description
4'0h	224
4'1h	220
4'2h	216
4'3h	212
4'4h	208
4'5h	204
4'6h	200
4'7h	196

DTH_ST [3:0]	Description
4'8h	192
4'9h	188
4'Ah	184
4'Bh	180
4'Ch	176
4'Dh	172
4'Eh	168
4'Fh	164

DTH_MV [3:0]	Description
4'0h	224
4'1h	220
4'2h	216
4'3h	212
4'4h	208
4'5h	204
4'6h	200
4'7h	196

DTH_MV [3:0]	Description
4'8h	192
4'9h	188
4'Ah	184
4'Bh	180
4'Ch	176
4'Dh	172
4'Eh	168
4'Fh	164

Description

Status	Availability
Normal Mode On, Idle Mode Off, Sleep Out	Yes
Normal Mode On, Idle Mode On, Sleep Out	Yes
Partial Mode On, Idle Mode Off, Sleep Out	Yes
Partial Mode On, Idle Mode On, Sleep Out	Yes
Sleep In	Yes

Register Availability

Default			
		Status	**Default Value**
			DTH_MV [3:0]	DTH_ST [3:0]
		Power On Sequence	4'b0110	4'b0101
		SW Reset	No change	No change
		HW Reset	4'b0110	4'b0101

8.3.13. Backlight Control 5 (BCh)

BCh				Backlight Control 5								
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	0	1	1	1	1	0	0	BCh
Parameter	1	1	↑	XX	DIM2 [3]	DIM2 [2]	DIM2 [1]	DIM2 [0]	0	DIM1 [2]	DIM1 [1]	DIM1 [0]	44

Description

DIM1 [2:0]: This parameter is used to set the transition time of brightness level to avoid the sharp brightness transition on vision.

DIM1 [2:0]	Description
3'0h	1 frame
3'1h	1 frame
3'2h	2 frames
3'3h	4 frames
3'4h	8 frames
3'5h	16 frames
3'6h	32 frames
3'7h	64 frames

DIM2 [3:0]: This parameter is used to set the threshold of brightness change.

When the brightness transition difference is smaller than DIM2 [3:0], the brightness transition will be ignored.

For example:

If | brightness B – brightness A| < DIM2 [2:0], the brightness transition will be ignored and keep the brightness A.

Register Availability

Status	Availability
Normal Mode On, Idle Mode Off, Sleep Out	Yes
Normal Mode On, Idle Mode On, Sleep Out	Yes
Partial Mode On, Idle Mode Off, Sleep Out	Yes
Partial Mode On, Idle Mode On, Sleep Out	Yes
Sleep In	Yes

Default

Status	Default Value	
	DIM2 [3:0]	DIM1 [2:0]
Power On Sequence	4'b0100	4'b0100
SW Reset	No change	No change
HW Reset	4'b0100	4'b0100

8.3.14. Backlight Control 7 (BEh)

BEh					Backlight Control 7								
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	0	1	1	1	1	1	0	BEh
Parameter	1	1	↑	XX	PWM_DIV[7]	PWM_DIV[6]	PWM_DIV[5]	PWM_DIV[4]	PWM_DIV[3]	PWM_DIV[2]	PWM_DIV[1]	PWM_DIV[0]	0F

Description

PWM_DIV [7:0]: PWM_OUT output frequency control. This command is used to adjust the PWM waveform frequency of PWM_OUT. The PWM frequency can be calculated by using the following equation.

$$f_{PWM\_OUT} = \frac{16MHz}{(PWM\_DIV[7:0]+1) \quad 255}$$

PWM_DIV [7:0]	f_{PWM_OUT}
8'h0	62.74 KHz
8'h1	31.38 KHz
8'h2	20.915KHz
8'h3	15.686KHz
8'h4	12.549 KHz
…	…
8'hFB	249Hz
8'hFC	248Hz
8'hFD	247Hz
8'hFE	246Hz
8'hFF	245Hz

Note: The output frequency tolerance of internal frequency divider in CABC is ±10%

Register Availability

Status	Availability
Normal Mode On, Idle Mode Off, Sleep Out	Yes
Normal Mode On, Idle Mode On, Sleep Out	Yes
Partial Mode On, Idle Mode Off, Sleep Out	Yes
Partial Mode On, Idle Mode On, Sleep Out	Yes
Sleep In	Yes

Default

Status	Default Value
Power On Sequence	PWM_DIV [7:0]=0Fh
SW Reset	No change
HW Reset	PWM_DIV [7:0]=0Fh

8.3.15. Backlight Control 8 (BFh)

BFh								Backlight Control 2					
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	0	1	1	1	1	1	1	BFh
Parameter	1	1	↑	XX	0	0	0	0	0	LEDONR	LEDONPOL	LEDPWMPOL	00

Description	**LEDPWMPOL:** The bit is used to define polarity of LEDPWM signal.

BL	LEDPWMPOL	LEDPWM pin
0	0	0
0	1	1
1	0	Original polarity of PWM signal
1	1	Inversed polarity of PWM signal

LEDONPOL: This bit is used to control LEDON pin.

BL	LEDONPOL	LEDON pin
0	0	0
0	1	1
1	0	LEDONR
1	1	Inversed LEDONR

LEDONR: This bit is used to control LEDON pin.

LEDONR	Description
0	Low
1	High

Register Availability	Status	Availability
	Normal Mode On, Idle Mode Off, Sleep Out	Yes
	Normal Mode On, Idle Mode On, Sleep Out	Yes
	Partial Mode On, Idle Mode Off, Sleep Out	Yes
	Partial Mode On, Idle Mode On, Sleep Out	Yes
	Sleep In	Yes

Default	Status	Default Value		
		LEDONR	LEDONPOL	LEDPWMPOL
	Power On Sequence	1'b0	1'b0	1'b0
	SW Reset	No change	No change	No change
	HW Reset	1'b0	1'b0	1'b0

8.3.16. Power Control 1 (C0h)

C0h															
							PWCTRL 1 (Power Control 1)								
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX		
Command	0	1	↑	XX	1	1	0	0	0	0	0	0	C0h		
1stParameter	1	1	↑	XX	0	0	VRH [5:0]						21		

Description

VRH [5:0]: Set the GVDD level, which is a reference level for the VCOM level and the grayscale voltage level.

VRH [5:0]						GVDD	VRH [5:0]						GVDD
0	0	0	0	0	0	Setting prohibited	1	0	0	0	0	0	4.45 V
0	0	0	0	0	1	Setting prohibited	1	0	0	0	0	1	4.50 V
0	0	0	0	1	0	Setting prohibited	1	0	0	0	1	0	4.55 V
0	0	0	0	1	1	3.00 V	1	0	0	0	1	1	4.60 V
0	0	0	1	0	0	3.05 V	1	0	0	1	0	0	4.65 V
0	0	0	1	0	1	3.10 V	1	0	0	1	0	1	4.70 V
0	0	0	1	1	0	3.15 V	1	0	0	1	1	0	4.75 V
0	0	0	1	1	1	3.20 V	1	0	0	1	1	1	4.80 V
0	0	1	0	0	0	3.25 V	1	0	1	0	0	0	4.85 V
0	0	1	0	0	1	3.30 V	1	0	1	0	0	1	4.90 V
0	0	1	0	1	0	3.35 V	1	0	1	0	1	0	4.95 V
0	0	1	0	1	1	3.40 V	1	0	1	0	1	1	5.00 V
0	0	1	1	0	0	3.45 V	1	0	1	1	0	0	5.05 V
0	0	1	1	0	1	3.50 V	1	0	1	1	0	1	5.10 V
0	0	1	1	1	0	3.55 V	1	0	1	1	1	0	5.15 V
0	0	1	1	1	1	3.60 V	1	0	1	1	1	1	5.20 V
0	1	0	0	0	0	3.65 V	1	1	0	0	0	0	5.25 V
0	1	0	0	0	1	3.70 V	1	1	0	0	0	1	5.30 V
0	1	0	0	1	0	3.75 V	1	1	0	0	1	0	5.35 V
0	1	0	0	1	1	3.80 V	1	1	0	0	1	1	5.40 V
0	1	0	1	0	0	3.85 V	1	1	0	1	0	0	5.45 V
0	1	0	1	0	1	3.90 V	1	1	0	1	0	1	5.50 V
0	1	0	1	1	0	3.95 V	1	1	0	1	1	0	5.55 V
0	1	0	1	1	1	4.00 V	1	1	0	1	1	1	5.60 V
0	1	1	0	0	0	4.05 V	1	1	1	0	0	0	5.65 V
0	1	1	0	0	1	4.10 V	1	1	1	0	0	1	5.70 V
0	1	1	0	1	0	4.15 V	1	1	1	0	1	0	5.75 V
0	1	1	0	1	1	4.20 V	1	1	1	0	1	1	5.80 V
0	1	1	1	0	0	4.25 V	1	1	1	1	0	0	5.85 V
0	1	1	1	0	1	4.30 V	1	1	1	1	0	1	5.90 V
0	1	1	1	1	0	4.35 V	1	1	1	1	1	0	5.95 V
0	1	1	1	1	1	4.40 V	1	1	1	1	1	1	6.00 V

Note1: Make sure that VC and VRH setting restriction: GVDD ≦ (DDVDH - 0.2) V.

Restriction

EXTC should be high to enable this command

Register Availability

Status	Availability
Normal Mode ON, Idle Mode OFF, Sleep OUT	Yes
Normal Mode ON, Idle Mode ON, Sleep OUT	Yes
Partial Mode ON, Idle Mode OFF, Sleep OUT	Yes
Partial Mode ON, Idle Mode ON, Sleep OUT	Yes
Sleep IN	Yes

Default

Status	Default Value
	VRH [5:0]
Power ON Sequence	6'h21h
SW Reset	6'h21h
HW Reset	6'h21h

8.3.17. Power Control 2 (C1h)

C1h	PWCTRL 2 (Power Control 2)											
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	1	0	0	0	0	0	1	C1h
Parameter	1	1	↑	XX	0	0	0	0	0		BT [2:0]		10

Description	**BT [2:0]:** Sets the factor used in the step-up circuits. Select the optimal step-up factor for the operating voltage. To reduce power consumption, set a smaller factor.

BT [2:0]			DDVDH	VGH	VGL
0	0	0	VCI x 2	VCI x 7	-VCI x 4
0	0	1			-VCI x 3
0	1	0		VCI x 6	-VCI x 4
0	1	1			-VCI x 3

Note1: Make sure that DDVDH setting restriction: DDVDH ≦ 5.8 V.

    2: Make sure that VGH and VGL setting restriction: VGH -VGL≦ 28 V.

Restriction	EXTC should be high to enable this command

Register Availability		

Status	Availability
Normal Mode ON, Idle Mode OFF, Sleep OUT	Yes
Normal Mode ON, Idle Mode ON, Sleep OUT	Yes
Partial Mode ON, Idle Mode OFF, Sleep OUT	Yes
Partial Mode ON, Idle Mode ON, Sleep OUT	Yes
Sleep IN	Yes

Default		

Status	Default Value
	BT [2:0]
Power ON Sequence	3'b000
SW Reset	3'b000
HW Reset	3'b000

8.3.18. VCOM Control 1(C5h)

C5h				VMCTRL1 (VCOM Control 1)								
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	1	0	0	0	1	0	1	C5h
1st Parameter	1	1	↑	XX	0	VMH [6:0]							31
2nd Parameter	1	1	↑	XX	0	VML [6:0]							3C

Description

VMH [6:0] : Set the VCOMH voltage.

VMH [6:0]	VCOMH(V)	VMH [6:0]	VCOMH(V)	VMH [6:0]	VCOMH(V)	VMH [6:0]	VCOMH(V)
0000000	2.700	0100000	3.500	1000000	4.300	1100000	5.100
0000001	2.725	0100001	3.525	1000001	4.325	1100001	5.125
0000010	2.750	0100010	3.550	1000010	4.350	1100010	5.150
0000011	2.775	0100011	3.575	1000011	4.375	1100011	5.175
0000100	2.800	0100100	3.600	1000100	4.400	1100100	5.200
0000101	2.825	0100101	3.625	1000101	4.425	1100101	5.225
0000110	2.850	0100110	3.650	1000110	4.450	1100110	5.250
0000111	2.875	0100111	3.675	1000111	4.475	1100111	5.275
0001000	2.900	0101000	3.700	1001000	4.500	1101000	5.300
0001001	2.925	0101001	3.725	1001001	4.525	1101001	5.325
0001010	2.950	0101010	3.750	1001010	4.550	1101010	5.350
0001011	2.975	0101011	3.775	1001011	4.575	1101011	5.375
0001100	3.000	0101100	3.800	1001100	4.600	1101100	5.400
0001101	3.025	0101101	3.825	1001101	4.625	1101101	5.425
0001110	3.050	0101110	3.850	1001110	4.650	1101110	5.450
0001111	3.075	0101111	3.875	1001111	4.675	1101111	5.475
0010000	3.100	0110000	3.900	1010000	4.700	1110000	5.500
0010001	3.125	0110001	3.925	1010001	4.725	1110001	5.525
0010010	3.150	0110010	3.950	1010010	4.750	1110010	5.550
0010011	3.175	0110011	3.975	1010011	4.775	1110011	5.575
0010100	3.200	0110100	4.000	1010100	4.800	1110100	5.600
0010101	3.225	0110101	4.025	1010101	4.825	1110101	5.625
0010110	3.250	0110110	4.050	1010110	4.850	1110110	5.650
0010111	3.275	0110111	4.075	1010111	4.875	1110111	5.675
0011000	3.300	0111000	4.100	1011000	4.900	1111000	5.700
0011001	3.325	0111001	4.125	1011001	4.925	1111001	5.725
0011010	3.350	0111010	4.150	1011010	4.950	1111010	5.750
0011011	3.375	0111011	4.175	1011011	4.975	1111011	5.775
0011100	3.400	0111100	4.200	1011100	5.000	1111100	5.800
0011101	3.425	0111101	4.225	1011101	5.025	1111101	5.825
0011110	3.450	0111110	4.250	1011110	5.050	1111110	5.850
0011111	3.475	0111111	4.275	1011111	5.075	1111111	5.875

VML [6:0] : Set the VCOML voltage

VML [6:0]	VCOML(V)	VML [6:0]	VCOML(V)	VML [6:0]	VCOML(V)	VML [6:0]	VCOML(V)
0000000	-2.500	0100000	-1.700	1000000	-0.900	1100000	-0.100
0000001	-2.475	0100001	-1.675	1000001	-0.875	1100001	-0.075
0000010	-2.450	0100010	-1.650	1000010	-0.850	1100010	-0.050
0000011	-2.425	0100011	-1.625	1000011	-0.825	1100011	-0.025
0000100	-2.400	0100100	-1.600	1000100	-0.800	1100100	0
0000101	-2.375	0100101	-1.575	1000101	-0.775	1100101	Reserved
0000110	-2.350	0100110	-1.550	1000110	-0.750	1100110	Reserved
0000111	-2.325	0100111	-1.525	1000111	-0.725	1100111	Reserved
0001000	-2.300	0101000	-1.500	1001000	-0.700	1101000	Reserved
0001001	-2.275	0101001	-1.475	1001001	-0.675	1101001	Reserved
0001010	-2.250	0101010	-1.450	1001010	-0.650	1101010	Reserved
0001011	-2.225	0101011	-1.425	1001011	-0.625	1101011	Reserved
0001100	-2.200	0101100	-1.400	1001100	-0.600	1101100	Reserved
0001101	-2.175	0101101	-1.375	1001101	-0.575	1101101	Reserved
0001110	-2.150	0101110	-1.350	1001110	-0.550	1101110	Reserved
0001111	-2.125	0101111	-1.325	1001111	-0.525	1101111	Reserved
0010000	-2.100	0110000	-1.300	1010000	-0.500	1110000	Reserved
0010001	-2.075	0110001	-1.275	1010001	-0.475	1110001	Reserved
0010010	-2.050	0110010	-1.250	1010010	-0.450	1110010	Reserved
0010011	-2.025	0110011	-1.225	1010011	-0.425	1110011	Reserved

0010100	-2.000	0110100	-1.200	1010100	-0.400	1110100	Reserved
0010101	-1.975	0110101	-1.175	1010101	-0.375	1110101	Reserved
0010110	-1.950	0110110	-1.150	1010110	-0.350	1110110	Reserved
0010111	-1.925	0110111	-1.125	1010111	-0.325	1110111	Reserved
0011000	-1.900	0111000	-1.100	1011000	-0.300	1111000	Reserved
0011001	-1.875	0111001	-1.075	1011001	-0.275	1111001	Reserved
0011010	-1.850	0111010	-1.050	1011010	-0.250	1111010	Reserved
0011011	-1.825	0111011	-1.025	1011011	-0.225	1111011	Reserved
0011100	-1.800	0111100	-1.000	1011100	-0.200	1111100	Reserved
0011101	-1.775	0111101	-0.975	1011101	-0.175	1111101	Reserved
0011110	-1.750	0111110	-0.950	1011110	-0.150	1111110	Reserved
0011111	-1.725	0111111	-0.925	1011111	-0.125	1111111	Reserved

Restriction	EXTC should be high to enable this command

Register Availability

Status	Availability
Normal Mode ON, Idle Mode OFF, Sleep OUT	Yes
Normal Mode ON, Idle Mode ON, Sleep OUT	Yes
Partial Mode ON, Idle Mode OFF, Sleep OUT	Yes
Partial Mode ON, Idle Mode ON, Sleep OUT	Yes
Sleep IN	Yes

Default

Status	Default Value	
	VMH [6:0]	VML [6:0]
Power ON Sequence	7'h31	7'h3C
SW Reset	7'h31	7'h3C
HW Rest	7'h31	7'h3C

8.3.19. VCOM Control 2(C7h)

C7h					VMCTRL1 (VCOM Control 1)							
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	1	0	0	0	1	1	1	C7h
Parameter	1	1	↑	XX	nVM	VMF [6:0]							C0

Description	**nVM:** nVM equals to "0" after power on reset and VCOM offset equals to program MTP value. When nVM set to "1", setting of VMF [6:0] becomes valid and VCOMH/VCOML can be adjusted. **VMF [6:0]:** Set the VCOM offset voltage.

VMF[6:0]	VCOMH	VCOML		VMF[6:0]	VCOMH	VCOML
0000000	VMH	VML		1000000	VMH	VML
0000001	VMH – 63	VML – 63		1000001	VMH + 1	VML + 1
0000010	VMH – 62	VML – 62		1000010	VMH + 2	VML + 2
0000011	VMH – 61	VML – 61		1000011	VMH + 3	VML + 3
0000100	VMH – 60	VML – 60		1000100	VMH + 4	VML + 4
0000101	VMH – 58	VML – 58		1000101	VMH + 5	VML + 5
0000110	VMH – 58	VML – 58		1000110	VMH + 6	VML + 6
0000111	VMH – 57	VML – 57		1000111	VMH + 7	VML + 7
0001000	VMH – 56	VML – 56		1001000	VMH + 8	VML + 8
0001001	VMH – 55	VML – 55		1001001	VMH + 9	VML + 9
0001010	VMH – 54	VML – 54		1001010	VMH + 10	VML + 10
0001011	VMH – 53	VML – 53		1001011	VMH + 11	VML + 11
0001100	VMH – 52	VML – 52		1001100	VMH + 12	VML + 12
0001101	VMH – 51	VML -51		1001101	VMH + 13	VML + 13
0001110	VMH – 50	VML – 50		1001110	VMH + 14	VML + 14
0001111	VMH – 49	VML – 49		1001111	VMH + 15	VML + 15
0010000	VMH – 48	VML – 48		1010000	VMH + 16	VML + 16
0010001	VMH – 47	VML – 47		1010001	VMH + 17	VML + 17
0010010	VMH – 46	VML – 46		1010010	VMH + 18	VML + 18
0010011	VMH – 45	VML – 45		1010011	VMH + 19	VML + 19
0010100	VMH – 44	VML – 44		1010100	VMH + 20	VML + 20
0010101	VMH – 43	VML – 43		1010101	VMH + 21	VML + 21
0010110	VMH – 42	VML – 42		1010110	VMH + 22	VML + 22
0010111	VMH – 41	VML – 41		1010111	VMH + 23	VML + 23
0011000	VMH – 40	VML – 40		1011000	VMH + 24	VML + 24
0011001	VMH – 39	VML – 39		1011001	VMH + 25	VML + 25
0011010	VMH – 38	VML – 38		1011010	VMH + 26	VML + 26
0011011	VMH – 37	VML – 37		1011011	VMH + 27	VML + 27
0011100	VMH – 36	VML – 36		1011100	VMH + 28	VML + 28
0011101	VMH – 35	VML – 35		1011101	VMH + 29	VML + 29
0011110	VMH – 34	VML – 34		1011110	VMH + 30	VML + 30
0011111	VMH – 33	VML – 33		1011111	VMH + 31	VML + 31
0100000	VMH – 32	VML – 32		1100000	VMH + 32	VML + 32
0100001	VMH – 31	VML – 31		1100001	VMH + 33	VML + 33
0100010	VMH – 30	VML – 30		1100010	VMH + 34	VML + 34
0100011	VMH – 29	VML – 29		1100011	VMH + 35	VML + 35
0100100	VMH – 28	VML – 28		1100100	VMH + 36	VML + 36
0100101	VMH – 27	VML – 27		1100101	VMH + 37	VML + 37
0100110	VMH – 26	VML – 26		1100110	VMH + 38	VML + 38
0100111	VMH – 25	VML – 25		1100111	VMH + 39	VML + 39
0101000	VMH – 24	VML – 24		1101000	VMH + 40	VML + 40
0101001	VMH – 23	VML – 23		1101001	VMH + 41	VML + 41
0101010	VMH – 22	VML – 22		1101010	VMH + 42	VML + 42
0101011	VMH – 21	VML – 21		1101011	VMH + 43	VML + 43
0101100	VMH – 20	VML – 20		1101100	VMH + 44	VML + 44
0101101	VMH – 19	VML – 19		1101101	VMH + 45	VML + 45
0101110	VMH – 18	VML – 18		1101110	VMH + 46	VML + 46
0101111	VMH – 17	VML – 17		1101111	VMH + 47	VML + 47
0110000	VMH – 16	VML – 16		1110000	VMH + 48	VML + 48
0110001	VMH – 15	VML – 15		1110001	VMH + 49	VML + 49
0110010	VMH – 14	VML – 14		1110010	VMH + 50	VML + 50
0110011	VMH – 13	VML – 13		1110011	VMH + 51	VML + 51
0110100	VMH – 12	VML – 12		1110100	VMH + 52	VML + 52

0110101	VMH – 11	VML – 11		1110101	VMH + 53	VML + 53
0110110	VMH – 10	VML – 10		1110110	VMH + 54	VML + 54
0110111	VMH – 9	VML – 9		1110111	VMH + 55	VML + 55
0111000	VMH – 8	VML – 8		1111000	VMH + 56	VML + 56
0111001	VMH – 7	VML – 7		1111001	VMH + 57	VML + 57
0111010	VMH – 6	VML – 6		1111010	VMH + 58	VML + 58
0111011	VMH – 5	VML – 5		1111011	VMH + 59	VML + 59
0111100	VMH – 4	VML – 4		1111100	VMH + 60	VML + 60
0111101	VMH – 3	VML – 3		1111101	VMH + 61	VML + 61
0111110	VMH – 2	VML – 2		1111110	VMH + 62	VML + 62
0111111	VMH – 1	VML – 1		1111111	VMH + 63	VML + 63

Restriction

EXTC should be high to enable this command

Register Availability

Status	Availability
Normal Mode ON, Idle Mode OFF, Sleep OUT	Yes
Normal Mode ON, Idle Mode ON, Sleep OUT	Yes
Partial Mode ON, Idle Mode OFF, Sleep OUT	Yes
Partial Mode ON, Idle Mode ON, Sleep OUT	Yes
Sleep IN	Yes

Default

Status	Default Value	
	nVM	VMF [6:0]
Power ON Sequence	1'b1	7'h40h
SW Reset	1'b1	7'h40h
HW Reset	1'b1	7'h40h

8.3.20. NV Memory Write (D0h)

D0h	NVMWR (NV Memory Write)												
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	1	0	1	0	0	0	0	D0h
1st Parameter	1	1	↑	XX	0	0	0	0	0	PGM_ADR [2:0]			00
2nd Parameter	1	1	↑	XX	PGM_DATA [7:0]								XX

Description	This command is used to program the NV memory data. After a successful MTP operation, the information of PGM_DATA [7:0] will programmed to NV memory. **PGM_ADR [2:0]**: The select bits of ID1, ID2, ID3 and VMF [6:0] programming can be OTP x 3 times. See table below. **PGM_DATA [7:0]**: The programmed data.

PGM_ADR [2:0]			Programmed NV Memory Selection
0	0	0	ID1 programming
0	0	1	ID2 programming
0	1	0	ID3 programming
1	0	0	VMF [6:0] programming
Others			Reserved

Restriction	EXTC should be high to enable this command

Register Availability		
	Status	Availability
	Normal Mode ON, Idle Mode OFF, Sleep OUT	Yes
	Normal Mode ON, Idle Mode ON, Sleep OUT	Yes
	Partial Mode ON, Idle Mode OFF, Sleep OUT	Yes
	Partial Mode ON, Idle Mode ON, Sleep OUT	Yes
	Sleep IN	Yes

Default			
	Status	Default Value	
		PGM_ADR [2:0]	PGM_DATA [7:0]
	Power ON Sequence	3'b000	MTP value
	SW Reset	3'b000	MTP value
	HW Reset	3'b000	MTP value

8.3.21. NV Memory Protection Key (D1h)

D1h	NVMPKEY (NV Memory Protection Key)												
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	1	0	1	0	0	0	1	D1h
1st Parameter	1	1	↑	XX	KEY [23:16]								55h
2nd Parameter	1	1	↑	XX	KEY [15:8]								AAh
3rd Parameter	1	1	↑	XX	KEY [7:0]								66h

Description	**KEY [23:0]:** NV memory programming protection key. When writing MTP data to D1h, this register must be set to 0x55AA66h to enable MTP programming. If D1h register is not written with 0x55AA66h, then NV memory programming will be aborted.
Restriction	EXTC should be high to enable this command

Register Availability		
	Status	Availability
	Normal Mode ON, Idle Mode OFF, Sleep OUT	Yes
	Normal Mode ON, Idle Mode ON, Sleep OUT	Yes
	Partial Mode ON, Idle Mode OFF, Sleep OUT	Yes
	Partial Mode ON, Idle Mode ON, Sleep OUT	Yes
	Sleep IN	Yes

Default		
	Status	Default Value
	Power ON Sequence	KEY [23:0]=55AA66h
	SW Reset	KEY [23:0]=55AA66h
	HW Reset	KEY [23:0]=55AA66h

8.3.22.   NV Memory Status Read (D2h)

D2h	RDNVM (NV Memory Status Read)											
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	1	0	1	0	0	1	0	D2h
1st Parameter	1	↑	1	XX	X	X	X	X	X	X	X	X	X
2nd Parameter	1	↑	1	XX	0	ID2_CNT [2:0]			0	ID1_CNT [2:0]			XX
3rd Parameter	1	↑	1	XX	BUSY	VMF_CNT [2:0]			0	ID3_CNT [2:0]			XX

| Description | **ID1_CNT [2:0] / ID2_CNT [2:0] / ID3_CNT [2:0] / VMF_CNT [2:0]: ID and VMF all can be OPT x 3 times,** NV memory program record. The bits will increase "+1" automatically after writing the PGM_DATA [7:0] to NV memory. |

ID1_CNT [2:0] / ID2_CNT [2:0] ID3_CNT [2:0] / VMF_CNT [2:0]			Description
Status			Availability
0	0	0	No Programmed
0	0	1	Programmed 1 time
0	1	1	Programmed 2 times
1	1	1	Programmed 3 times

BUSY: The status bit of NV memory programming.

BUSY	The Status of NV Memory
0	Idle
1	Busy

Restriction	EXTC should be high to enable this command

Register Availability		
Status	Availability
Normal Mode ON, Idle Mode OFF, Sleep OUT	Yes
Normal Mode ON, Idle Mode ON, Sleep OUT	Yes
Partial Mode ON, Idle Mode OFF, Sleep OUT	Yes
Partial Mode ON, Idle Mode ON, Sleep OUT	Yes
Sleep IN	Yes

Default

Status	Default Value				
	ID3_CNT	ID2_CNT	ID1_CNT	VMF_CNT	BUSY
Power ON Sequence	X	X	X	X	X
SW Reset	X	X	X	X	X
HW Reset	X	X	X	X	X

8.3.23. Read ID4 (D3h)

D3h	RDID4 (Read ID4)											
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	1	0	1	0	0	1	1	D3h
1st Parameter	1	↑	1	XX	X	X	X	X	X	X	X	X	X
2nd Parameter	1	↑	1	XX	0	0	0	0	0	0	0	0	00h
3rd Parameter	1	↑	1	XX	1	0	0	1	0	0	1	1	93h
4th Parameter	1	↑	1	XX	0	1	0	0	0	0	0	1	41h

Description	Read IC device code. The 1st parameter is dummy read period. The 2nd parameter means the IC version. The 3rd and 4th parameter mean the IC model name.
Restriction	EXTC should be high to enable this command

Register Availability		
	Status	Availability
	Normal Mode ON, Idle Mode OFF, Sleep OUT	Yes
	Normal Mode ON, Idle Mode ON, Sleep OUT	Yes
	Partial Mode ON, Idle Mode OFF, Sleep OUT	Yes
	Partial Mode ON, Idle Mode ON, Sleep OUT	Yes
	Sleep IN	Yes

Default		
	Status	Default Value
	Power ON Sequence	24'h009341h
	SW Reset	24'h009341h
	HW Reset	24'h009341h

8.3.24. Positive Gamma Correction (E0h)

E0h	PGAMCTRL (Positive Gamma Control)												
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	1	1	0	0	0	0	0	E0h
1st Parameter	1	1	↑	XX	0	0	0	0	VP63 [3:0]				08
2nd Parameter	1	1	↑	XX	0	0	VP62 [5:0]						
3rd Parameter	1	1	↑	XX	0	0	VP61 [5:0]						
4th Parameter	1	1	↑	X	0	0	0	0	VP59 [3:0]				05
5th Parameter	1	1	↑	XX	0	0	0	VP57 [4:0]					
6th Parameter	1	1	↑	XX	0	0	0	0	VP50 [3:0]				09
7th Parameter	1	1	↑	XX	0	VP43 [6:0]							
8th Parameter	1	1	↑	XX	VP27 [3:0]				VP36 [3:0]				
9th Parameter	1	1	↑	XX	0	VP20 [6:0]							
10th Parameter	1	1	↑	XX	0	0	0	0	VP13 [3:0]				0B
11th Parameter	1	1	↑	XX	0	0	0	VP6 [4:0]					
12th Parameter	1	1	↑	XX	0	0	0	0	VP4 [3:0]				00
13th Parameter	1	1	↑	XX	0	0	VP2 [5:0]						
14th Parameter	1	1	↑	XX	0	0	VP1 [5:0]						
15th Parameter	1	1	↑	XX	0	0	0	0	VP0 [3:0]				00

Description	Set the gray scale voltage to adjust the gamma characteristics of the TFT panel.
Restriction	EXTC should be high to enable this command

Register Availability		
	Status	Availability
	Normal Mode ON, Idle Mode OFF, Sleep OUT	Yes
	Normal Mode ON, Idle Mode ON, Sleep OUT	Yes
	Partial Mode ON, Idle Mode OFF, Sleep OUT	Yes
	Partial Mode ON, Idle Mode ON, Sleep OUT	Yes
	Sleep IN	Yes

Default	

8.3.25. Negative Gamma Correction (E1h)

E1h				NGAMCTRL (Negative Gamma Correction)									
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	1	1	0	0	0	0	1	E1h
1st Parameter	1	1	↑	XX	0	0	0	0	VN63 [3:0]				08
2nd Parameter	1	1	↑	XX	0	0	VN62 [5:0]						
3rd Parameter	1	1	↑	XX	0	0	VN61 [5:0]						
4th Parameter	1	1	↑	XX	0	0	0	0	VN59 [3:0]				07
5th Parameter	1	1	↑	XX	0	0	0	VN57 [4:0]					
6th Parameter	1	1	↑	XX	0	0	0	0	VN50 [3:0]				05
7th Parameter	1	1	↑	XX	0	VN43 [6:0]							
8th Parameter	1	1	↑	XX	VN36 [3:0]				VN27 [3:0]				
9th Parameter	1	1	↑	XX	0	VN20 [6:0]							
10th Parameter	1	1	↑	XX	0	0	0	0	VN13 [3:0]				04
11th Parameter	1	1	↑	XX	0	0	0	VN6 [4:0]					
12th Parameter	1	1	↑	XX	0	0	0	0	VN4 [3:0]				0F
13th Parameter	1	1	↑	XX	0	0	VN2 [5:0]						
14th Parameter	1	1	↑	XX	0	0	VN1 [5:0]						
15th Parameter	1	1	↑	XX	0	0	0	0	VN0 [3:0]				0F
Description	Set the gray scale voltage to adjust the gamma characteristics of the TFT panel.												
Restriction	EXTC should be high to enable this command												

Status	Availability
Normal Mode ON, Idle Mode OFF, Sleep OUT	Yes
Normal Mode ON, Idle Mode ON, Sleep OUT	Yes
Partial Mode ON, Idle Mode OFF, Sleep OUT	Yes
Partial Mode ON, Idle Mode ON, Sleep OUT	Yes
Sleep IN	Yes

Register Availability

Default

8.3.26. Digital Gamma Control 1 (E2h)

E2h				DGAMCTRL (Digital Gamma Control 1)									
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	1	1	0	0	0	1	0	E2h
1st Parameter	1	1	↑	XX	RCA0 [3:0]				BCA0 [3:0]				XX
:	1	1	↑	XX	RCAx [3:0]				BCAx [3:0]				XX
16th Parameter	1	1	↑	XX	RCA15 [3:0]				BCA15 [3:0]				XX

Description	**RCAx [3:0]:** Gamma Macro-adjustment registers for red gamma curve. **BCAx [3:0]:** Gamma Macro-adjustment registers for blue gamma curve.
Restriction	EXTC should be high to enable this command

Register Availability	

Status	Availability
Normal Mode ON, Idle Mode OFF, Sleep OUT	Yes
Normal Mode ON, Idle Mode ON, Sleep OUT	Yes
Partial Mode ON, Idle Mode OFF, Sleep OUT	Yes
Partial Mode ON, Idle Mode ON, Sleep OUT	Yes
Sleep IN	Yes

Default	

Status	Default Value	
	RCAx [3:0]	BCAx [3:0]
Power ON Sequence	TBD	TBD
SW Reset	TBD	TBD
HW Reset	TBD	TBD

8.3.27. Digital Gamma Control 2(E3h)

E3h					DGAMCTRL (Digital Gamma Control 2)								
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	1	1	0	0	0	1	1	E3h
1st Parameter	1	1	↑	XX	RFA0 [3:0]				BFA0 [3:0]				XX
:	1	1	↑	XX	RFAx [3:0]				BFAx [3:0]				XX
64rdParameter	1	1	↑	XX	RFA63 [3:0]				BFA63 [3:0]				XX

Description	**RFAx [3:0]:** Gamma Micro-adjustment register for red gamma curve. **BFAx [3:0]:** Gamma Micro-adjustment register for blue gamma curve.
Restriction	EXTC should be high to enable this command

Register Availability		
	Status	Availability
	Normal Mode ON, Idle Mode OFF, Sleep OUT	Yes
	Normal Mode ON, Idle Mode ON, Sleep OUT	Yes
	Partial Mode ON, Idle Mode OFF, Sleep OUT	Yes
	Partial Mode ON, Idle Mode ON, Sleep OUT	Yes
	Sleep IN	Yes

Default			
	Status	Default Value	
		RFAx [3:0]	BFAx [3:0]
	Power ON Sequence	TBD	TBD
	SW Reset	TBD	TBD
	HW Reset	TBD	TBD

8.3.28. Interface Control (F6h)

F6h						IFCTL (16bits Data Format Selection)						
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	1	1	1	0	1	1	0	F6h
1stParameter	1	1	↑	XX	MY_EOR	MX_EOR	MV_EOR	0	BGR_EOR	0	0	WE MODE	01
2ndParameter	1	1	↑	XX	0	0	EPF [1]	EPF [0]	0	0	MDT [1]	MDT [0]	00
3rdParameter	1	1	↑	XX	0	0	ENDIAN	0	DM [1]	DM [0]	RM	RIM	00

Description

MY_EOR / MX_EOR / MV_EOR / BGR_EOR:

The set value of MADCTL is used in the IC is derived as exclusive OR between 1st Parameter of IFCTL and MADCTL Parameter.

MDT [1:0]: Select the method of display data transferring.

WEMODE: Memory write control

WEMODE=0: When the transfer number of data exceeds (EC-SC+1)*(EP-SP+1), the exceeding data will be ignored.

WEMODE=1: When the transfer number of data exceeds (EC-SC+1)*(EP-SP+1), the column and page number will be reset, and the exceeding data will be written into the following column and page.

ENDIAN: Select Little Endian Interface bit. At Little Endian mode, the host sends LSB data first.

ENDIAN	Data transfer Mode
0	Normal (MSB first, default)
1	Little Endian (LSB first)

Note: Little Endian is valid on only 65K 8-bit and 9-bit MCU interface mode.

DM [1:0]: Select the display operation mode.

DM [1]	DM [0]	Display Operation Mode
0	0	Internal clock operation
0	1	RGB Interface Mode
1	0	VSYNC interface mode
1	1	Setting disabled

The DM [1:0] setting allows switching between internal clock operation mode and external display interface operation mode.

However, switching between the RGB interface operation mode and the VSYNC interface operation mode is prohibited.

RM: Select the interface to access the GRAM.

Set RM to "1" when writing display data by the RGB interface.

RM	Interface for RAM Access
0	System interface/VSYNC interface
1	RGB interface

RIM: Specify the RGB interface mode when the RGB interface is used. These bits should be set before display operation through the RGB interface and should not be set during operation.

RIM	COLMOD [6:4]	RGB Interface Mode
0	110 (262K color)	18- bit RGB interface (1 transfer/pixel)
	101 (65K color)	16- bit RGB interface (1 transfer/pixel)
1	110 (262K color)	6- bit RGB interface (3 transfer/pixel)
	101 (65K color)	6- bit RGB interface (3 transfer/pixel)

EPF [1:0]: 65K color mode data format.

The information contained herein is the exclusive property of ILI Technology Corp. and shall not be distributed,
reproduced, or disclosed in whole or in part without prior written permission of ILI Technology Corp.

Page 193 of 245

EPF [1:0]	Expand 16 bbp (R,G,B) to 18bbp (R,G,B)
00	MSB is inputted to LSB r [5:0] = {R [4:0], R [4]} g [5:0] = {G [5:0]} b [5:0] = {B [4:0], B [4]}
01	"0" is inputted to LSB r [5:0] = {R [4:0], 0} g [5:0] = {G [5:0]} b [5:0] = {B [4:0], 0} Exception: R [4:0], B[4:0] = 5'h1F → r [5:0], b[5:0] = 6'h3F
10	"1" is inputted to LSB r [5:0] = {R [4:0], 1} g [5:0] = {G [5:0]} b [5:0] = {B [4:0], 1} Exception: R [4:0], B[4:0] = 5'h00 → r [5:0], b[5:0] = 6'h00
11	Compare R [4:0], G [5:1], B [4:0] case: Case 1: R=G=B → r [5:0] = {R [4:0], G [0]}, g [5:0] = {G [5:0]}, b [5:0] = {B [4:0], G [0]} Case 2: R=B≠G → r [5:0] = {R [4:0], R [4]}, g [5:0] = {G [5:0]}, b [5:0] = {B [4:0], B [0]} Case 3: R=G≠B → r [5:0] = {R [4:0], G [0]}, g [5:0] = {G [5:0]}, b [5:0] = {B [4:0], B [0]} Case 4: B=G≠R → r [5:0] = {R [4:0], R [4]}, g [5:0] = {G [5:0]}, b [5:0] = {B [4:0], G [0]}

Restriction	EXTC should be high to enable this command

Register Availability

Status	Availability
Normal Mode ON, Idle Mode OFF, Sleep OUT	Yes
Normal Mode ON, Idle Mode ON, Sleep OUT	Yes
Partial Mode ON, Idle Mode OFF, Sleep OUT	Yes
Partial Mode ON, Idle Mode ON, Sleep OUT	Yes
Sleep IN	Yes

Default

Status	Default Value						
	EPF [1:0]	MDT [1:0]	ENDIAN	WEMODE	DM [1:0]	RM	RIM
Power ON Sequence	2'b00	2'b00	1'b0	1'b1	2'b00	1'b0	1'b0
SW Reset	2'b00	2'b00	1'b0	1'b1	2'b00	1'b0	1'b0
HW Reset	2'b00	2'b00	1'b0	1'b1	2'b00	1'b0	1'b0

8.4 Description of Extend register command
8.4.1 Power control A (CBh)

CBh							Power control A						
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	1	1	1	0	1	1	0	CBh
1st Parameter	1	1	↑	XX	0	0	1	1	1	0	0	1	39
2nd Parameter	1	1	↑	XX	0	0	1	0	1	1	0	0	2C
3rd Parameter	1	1	↑	XX	0	0	0	0	0	0	0	0	00
4rd Parameter	1	1	↑	XX	0	0	1	1	0	REG_VD[2:0]			34
5rd Parameter	1	1	↑	XX	0	0	0	0	0	VBC[2:0]			02

Description	REG_VD[2:0]: vcore control REG_VD[2:0] / Vcore(V) 000 / 1.55 001 / 1.4 010 / 1.5 011 / 1.65 100 / 1.6 101 / 1.7 110 / reserved 111 / reserved VBC[2:0]: ddvdh control VBC[2:0] / DDVDH(V) 000 / 5.8 001 / 5.7 010 / 5.6 011 / 5.5 100 / 5.4 101 / 5.3 110 / 5.2 111 / Reserved
Restriction	EXTC should be high to enable this command

Register Availability	Status	Availability
	Normal Mode ON, Idle Mode OFF, Sleep OUT	Yes
	Normal Mode ON, Idle Mode ON, Sleep OUT	Yes
	Partial Mode ON, Idle Mode OFF, Sleep OUT	Yes
	Partial Mode ON, Idle Mode ON, Sleep OUT	Yes
	Sleep IN	Yes

Default	Status	Default Value				
		Parameter1	Parameter2	Parameter3	Parameter4	Parameter5
	Power ON Sequence	39	2C	00	34	02
	SW Reset	39	2C	00	34	02
	HW Reset	39	2C	00	34	02

8.4.2 Power control B (CFh)

CFh							Power control B						
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	1	0	0	1	1	1	1	CFh
1st Parameter	1	1	↑	XX	0	0	0	0	0	0	0	0	00
2nd Parameter	1	1	↑	XX	1	PCEQ	DRV_ena	Power control[1:0]		0	0	1	81
3rd Parameter	1	1	↑	XX	DRV_vml[2:1]		1	DC_ena	DRV_vml[0]	DRV_vmh[2:0]			30

Description	2nd parameter: power control[1:0]
	
	 Only setting power control [1:0]=11, the VGH and VGL voltage level follow the table below.
	
	 <table><tr><td colspan="3">BT [2:0]</td><td>DDVDH</td><td>VGH</td><td>VGL</td></tr><tr><td>0</td><td>0</td><td>0</td><td rowspan="4">VCI x 2</td><td rowspan="2">VCI x 7</td><td>-VCI x 4</td></tr><tr><td>0</td><td>0</td><td>1</td><td>-VCI x 3</td></tr><tr><td>0</td><td>1</td><td>0</td><td rowspan="2">VCI x 6</td><td>-VCI x 4</td></tr><tr><td>0</td><td>1</td><td>1</td><td>-VCI x 3</td></tr></table>
	 bit[5]: DRV_ena : For VCOM driving ability enhancement, DRV_ena = 1: Enable, and vice versa
	
	 bit[6]: PCEQ: PC and EQ operation for power saving
	
	       0:disable this function
	
	       1:enable this function
	
	 3rd parameter: default: 30h
	
	 bit[2:0]: DRV_vmh[2:0] 3'b000 adjust over drive width for VMH(000: 1 op_clk ~111: 8 op_clk)
	
	 bit[3]: DRV_vml[0] 1'b0
	
	 bit[4]: DC_ena: Discharge path enable. Enable high for ESD protection, 1: enable and vice versa
	
	 bit[7:6] : DRV_vml[2:1] 2'b00

Restriction	EXTC should be high to enable this command
Register Availability	<table><tr><td>Status</td><td>Availability</td></tr><tr><td>Normal Mode ON, Idle Mode OFF, Sleep OUT</td><td>Yes</td></tr><tr><td>Normal Mode ON, Idle Mode ON, Sleep OUT</td><td>Yes</td></tr><tr><td>Partial Mode ON, Idle Mode OFF, Sleep OUT</td><td>Yes</td></tr><tr><td>Partial Mode ON, Idle Mode ON, Sleep OUT</td><td>Yes</td></tr><tr><td>Sleep IN</td><td>Yes</td></tr></table>
Default	<table><tr><td rowspan="2">Status</td><td colspan="3">Default Value</td></tr><tr><td>Parameter1</td><td>Parameter2</td><td>Parameter3</td></tr><tr><td>Power ON Sequence</td><td>00</td><td>A2</td><td>F0</td></tr><tr><td>SW Reset</td><td>00</td><td>A2</td><td>F0</td></tr><tr><td>HW Reset</td><td>00</td><td>A2</td><td>F0</td></tr></table>

8.4.3 Driver timing control A (E8h)

F6h					Driver timing control A								
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	1	1	0	1	0	0	0	E8h
1stParameter	1	1	↑	XX	1	0	0	0	0	1	0	NOW	84
2ndParameter	1	1	↑	XX	0	0	0	EQ	0	0	0	CR	11
3rdParameter	1	1	↑	XX	0	1	1	1	1	0	PC[1:0]		7A

Description	EQ timing for Internal clock 1st parameter:gate driver non-overlap timing control 0:default non-overlap time 1:default + 1unit 2nd parameter:EQ timing control 0: default – 1unit 1:default EQ timing parameter:CR timing control 0: default – 1unit 1:default CR timing 3rd parameter:pre-charge timing control 11: reserved 10: default pre-charge timing 01:default – 1unit 00:default – 2unit
Restriction	EXTC should be high to enable this command

Register Availability		
	Status	Availability
	Normal Mode ON, Idle Mode OFF, Sleep OUT	Yes
	Normal Mode ON, Idle Mode ON, Sleep OUT	Yes
	Partial Mode ON, Idle Mode OFF, Sleep OUT	Yes
	Partial Mode ON, Idle Mode ON, Sleep OUT	Yes
	Sleep IN	Yes

Default	Status	Default Value		
		Parameter1	Parameter2	Parameter3
	Power ON Sequence	84	11	7A
	SW Reset	84	11	7A
	HW Reset	84	11	7A

8.4.4 Driver timing control A (E9h)

F6h							Driver timing control A					
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	1	1	0	1	0	0	0	E8h
1stParameter	1	1	↑	XX	1	0	0	0	0	1	0	NOWE	84
2ndParameter	1	1	↑	XX	0	0	0	EQE	0	0	0	CRE	11
3rdParameter	1	1	↑	XX	0	1	1	1	1	0	PCE[1:0]		7A

Description	EQE timing for External clock
	1st parameter:gate driver non-overlap timing control
	0:default non-overlap time
	1:default + 1unit
	2nd parameter:EQE timing control
	0: default – 1unit
	1:default EQE timing
	parameter:CRE timing control
	0: default – 1unit
	1:default CRE timing
	3rd parameter:pre-charge timing control
	11: reserved
	10: default pre-charge timing
	01:default – 1unit
	00:default – 2unit

Restriction	EXTC should be high to enable this command

	Status	Availability
Register Availability	Normal Mode ON, Idle Mode OFF, Sleep OUT	Yes
	Normal Mode ON, Idle Mode ON, Sleep OUT	Yes
	Partial Mode ON, Idle Mode OFF, Sleep OUT	Yes
	Partial Mode ON, Idle Mode ON, Sleep OUT	Yes
	Sleep IN	Yes

	Status	Default Value		
		Parameter1	Parameter2	Parameter3
Default	Power ON Sequence	84	11	7A
	SW Reset	84	11	7A
	HW Reset	84	11	7A

8.4.5 Driver timing control B (EAh)

F6h	Driver timing control B											
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	1	1	0	1	0	1	0	EAh
1st Parameter	1	1	↑	XX	VG_SW_T4		VG_SW_T3		VG_SW_T2		VG_SW_T1		66
2nd Parameter	1	1	↑	XX	X	X	X	X	X	X	0	0	00

Description

1st parameter:gate driver timing control

VG_SW_T1[1:0]:EQ to GND

VG_SW_T2[1:0]:EQ to DDVDH

VG_SW_T3[1:0]:EQ to DDVDH

VG_SW_T4[1:0]:EQ to GND

00: 0 unit

01: 1 unit

10: 2 unit

11: 3 unit

Restriction EXTC should be high to enable this command

Register Availability

Status	Availability
Normal Mode ON, Idle Mode OFF, Sleep OUT	Yes
Normal Mode ON, Idle Mode ON, Sleep OUT	Yes
Partial Mode ON, Idle Mode OFF, Sleep OUT	Yes
Partial Mode ON, Idle Mode ON, Sleep OUT	Yes
Sleep IN	Yes

Default

Status	Default Value	
	Parameter1	Parameter2
Power ON Sequence	66	00
SW Reset	66	00
HW Reset	66	00

8.4.6 Power on sequence control (EDh)

F6h					Power on sequence control								
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	1	1	0	1	1	0	1	EDh
1st Parameter	1	1	↑	XX	X	1	CP1 soft start		X	1	CP23 soft start		55
2nd Parameter	1	1	↑	XX	X	0	En_vcl		X	0	En_ddvdh		01
3rd Parameter	1	1	↑	XX	X	0	En_vgh		X	0	En_vgl		23
4th Parameter	1	1	↑	XX	DDVDH_ENH	0	0	0	0	0	0	1	1

Description	1st parameter:soft start control
	00:soft start keep 3 frame
	01:soft start keep 2 frame
	01:soft start keep 1 frame
	11:disable
	2nd/ 3rd parameter:power on sequence control
	00:1st frame enable
	01:2nd frame enable
	10:3rd frame enable
	11:4th frame enable
	4th parameter:DDVDH enhance mode(only for 8 external capacitors)
	0: disable
	1: enable

Restriction	EXTC should be high to enable this command

Register Availability	Status	Availability
	Normal Mode ON, Idle Mode OFF, Sleep OUT	Yes
	Normal Mode ON, Idle Mode ON, Sleep OUT	Yes
	Partial Mode ON, Idle Mode OFF, Sleep OUT	Yes
	Partial Mode ON, Idle Mode ON, Sleep OUT	Yes
	Sleep IN	Yes

Default	Status	Default Value			
		Parameter1	Parameter2	Parameter3	Parameter4
	Power ON Sequence	55	01	23	01
	SW Reset	55	01	23	01
	HW Reset	55	01	23	01

8.4.7 Enable 3G (F2h)

F6h					Enable_3G							
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	1	1	1	0	0	1	0	F2h
1st Parameter	1	1	↑	XX	0	0	0	0	0	0	1	3G_enb	02

Description	1st Parameter: Enable 3 gamma control 3G_enb high for 3 gamma control enable
Restriction	EXTC should be high to enable this command

Register Availability		
	Status	Availability
	Normal Mode ON, Idle Mode OFF, Sleep OUT	Yes
	Normal Mode ON, Idle Mode ON, Sleep OUT	Yes
	Partial Mode ON, Idle Mode OFF, Sleep OUT	Yes
	Partial Mode ON, Idle Mode ON, Sleep OUT	Yes
	Sleep IN	Yes

Default		
	Status	Default Value Parameter1
	Power ON Sequence	02
	SW Reset	02
	HW Reset	02

8.4.8 Pump ratio control (F7h)

F6h	\multicolumn											
						Pump ratio control						
	D/CX	RDX	WRX	D17-8	D7	D6	D5	D4	D3	D2	D1	D0	HEX
Command	0	1	↑	XX	1	1	1	1	0	1	1	0	F7h
1stParameter	1	1	↑	XX	X	X	Ratio[1:0]		0	0	0	0	10

Description	1st parameter:ratio control 00:reserved 01:reserved 10:DDVDH=2xVCI 11:DDVDH=3xVCI
Restriction	EXTC should be high to enable this command
Register Availability	<table><tr><td>Status</td><td>Availability</td></tr><tr><td>Normal Mode ON, Idle Mode OFF, Sleep OUT</td><td>Yes</td></tr><tr><td>Normal Mode ON, Idle Mode ON, Sleep OUT</td><td>Yes</td></tr><tr><td>Partial Mode ON, Idle Mode OFF, Sleep OUT</td><td>Yes</td></tr><tr><td>Partial Mode ON, Idle Mode ON, Sleep OUT</td><td>Yes</td></tr><tr><td>Sleep IN</td><td>Yes</td></tr></table>
Default	<table><tr><td rowspan="2">Status</td><td>Default Value</td></tr><tr><td>Parameter1</td></tr><tr><td>Power ON Sequence</td><td>10</td></tr><tr><td>SW Reset</td><td>10</td></tr><tr><td>HW Reset</td><td>10</td></tr></table>