

1) Install Python 3.10

```
root@dlp:~# pkg install -y python310
root@dlp:~# python3.10 -V
Python 3.10.13
```

verify to create a test script

```
root@dlp:~# echo -e "import sys\nprint(sys.version)" > python_test.py
root@dlp:~# python3.10 python_test.py
3.10.13 (main, Jan 6 2024, 01:52:42) [Clang 16.0.6 (https://github.com/llvm/llvm-project.git llvmorg-16.0.6-0-g7cbf1a
```

2) Install SQLite3 library

```
root@dlp:~# pkg install -y py310-sqlite3
```

3) Install Django in a Python venv environment with any user you like to setup it

```
freebsd@dlp:~ $ python3.10 -m venv --system-site-packages ~/django5
```

```
freebsd@dlp:~ $ . ~/django5/bin/activate
```

```
(django5) freebsd@dlp:~ $ pip install 'Django>=5'
```

```
Collecting Django>=5
  Downloading Django-5.0.1-py3-none-any.whl (8.1 MB)
    8.1/8.1 MB 27.2 MB/s eta 0:00:00
Collecting asgiref<4,>=3.7.0
  Using cached asgiref-3.7.2-py3-none-any.whl (24 kB)
Collecting sqlparse>=0.3.1
  Using cached sqlparse-0.4.4-py3-none-any.whl (41 kB)
Collecting typing-extensions>=4
  Using cached typing_extensions-4.9.0-py3-none-any.whl (32 kB)
Installing collected packages: typing-extensions, sqlparse, asgiref, Django
Successfully installed Django-5.0.1 asgiref-3.7.2 sqlparse-0.4.4 typing-extensions-4.9.0
```

```
(django5) freebsd@dlp:~ $ django-admin --version
5.0.1
```

to exit from venv, run like follows

```
(django5) freebsd@dlp:~ $ deactivate
```

4) Create a test project

```
freebsd@dlp:~ $ . ~/django5/bin/activate
```

create testproject

```
(django5) freebsd@dlp:~ $ django-admin startproject testproject2
```

```
(django5) freebsd@dlp:~ $ cd testproject2
```

configure database (default is SQLite)

```
(django5) freebsd@dlp:~/testproject2 $ python manage.py migrate
```

create admin user

```
(django5) freebsd@dlp:~/testproject2 $ python manage.py createsuperuser
```

```
Username (leave blank to use 'freebsd'): freebsd
```

```
Email address: freebsd@dlp.srv.world
```

```
Password:
```

```
Password (again):
```

```
Superuser created successfully.
```

```
(django5) freebsd@dlp:~/testproject2 $ vi testproject2/settings.py
```

```
# line 28 : set if you allow to access to Django from other Hosts
# specify Hosts with comma separated
# if allow all, specify like follows
ALLOWED_HOSTS = ['*']
```

start server

```
(django5) freebsd@dlp:~/testproject2 $ python manage.py runserver 0.0.0.0:8000
```

```
Watching for file changes with StatReloader
```

```
Performing system checks...
```

```
System check identified no issues (0 silenced).
```

```
February 01, 2024 - 01:59:55
```

```
Django version 5.0.1, using settings 'testproject2.settings'
```

```
Starting development server at http://0.0.0.0:8000/
```

```
Quit the server with CONTROL-C.
```

<http://bla:8000>

<http://bla:8000/admin>

5) Create a test application to try to use Django

```
freebsd@dlp:~ $ . ~/django5/bin/activate
(django5) freebsd@dlp:~ $ cd testproject2
(django5) freebsd@dlp:~/testproject2 $ python manage.py startapp test_app
(django5) freebsd@dlp:~/testproject2 $ vi test_app/views.py
# add to last line
from django.http import HttpResponse
def main(request):
    html = '<html>\n' \
          '<body>\n' \
          '<div style="width: 100%; font-size: 40px; font-weight: bold; text-align: center;">\n' \
          'Django Test Page\n' \
          '</div>\n' \
          '</body>\n' \
          '</html>\n'
    return HttpResponse(html)
```

```
(django5) freebsd@dlp:~/testproject2 $ vi testproject2/urls.py
# line 18, 22 : add like follows
from django.contrib import admin
from django.urls import path, include

urlpatterns = [
    path('admin/', admin.site.urls),
    path('test_app/', include('test_app.urls')),
]
```

```
(django5) freebsd@dlp:~/testproject2 $ vi test_app/urls.py
# create new
from django.urls import path
from .views import main

urlpatterns = [
    path('', main, name='home')
]
```

```
(django5) freebsd@dlp:~/testproject2 $ vi testproject2/settings.py
# line 33 : add test application in [INSTALLED_APPS] section
INSTALLED_APPS = (
    'django.contrib.admin',
    'django.contrib.auth',
    'django.contrib.contenttypes',
    'django.contrib.sessions',
    'django.contrib.messages',
    'django.contrib.staticfiles',
    'test_app',
)
```

```
(django5) freebsd@dlp:~/testproject2 $ python manage.py runserver 0.0.0.0:8000
```

http://bla:8000/test_app