CERTIFIED ZEROTH-ORDER EXACT PENALIZATION FOR BLACK-BOX SPARSITY-CONSTRAINED OPTIMIZATION

Dongxu Liu[1,*], *Dongyang Liu*[2], *Wenjia Shi*[3], *Keming Fan*[3], *Linhao Wang*[3]
[1]School of Artificial Intelligence, Jilin University, Changchun, China
[2]Yingcai Honors College, University of Electronic Science and Technology of China, Chengdu, China
[3]College of Computer Science and Technology, Jilin University, Changchun, China

E-mail: liudx9924@mails.jlu.edu.cn, 2024310102018@std.uestc.edu.cn, shiwj2126@mails.jlu.edu.cn, fankm2124@mails.jlu.edu.cn, lhwang2124@mails.jlu.edu.cn

ABSTRACT

Exact-penalty methods reformulate sparsity into continuous objectives, but existing trimmed-ℓ_1 algorithms rely on first-order proximal updates and do not directly apply to function-value-only black-box problems. We propose ZO-IDEP, a zeroth-order realization of this exact-penalty route using coordinate finite differences and the closed-form trimmed-ℓ_1 proximal map. To our knowledge, it is the first ZO treatment of this route that certifies when inactive coordinate queries become permanently redundant. The key analysis propagates estimator error through convergence and identification. We prove convergence to a sparse proximal fixed point, finite support identification, and, under convexity of the restricted objective plus a valid localization radius, trajectory-preserving support restriction, after which the restricted and hypothetical full-coordinate trajectories coincide, reducing per-step queries from $2d$ to $2k$. Experiments verify exact post-switch step preservation, 58.3–62.5% finite-budget savings, and the failure of heuristic early freezing. Code is available at `https://github.com/ldx825/ZO-IDEP_ICASSP-2027`.

***Index Terms*—** zeroth-order optimization, exact penalty, sparse optimization, support identification, black-box optimization

1. INTRODUCTION

Consider the cardinality-constrained problem

$$\min_{x\in\mathbb{R}^d} f(x) \quad \text{s.t.} \quad \|x\|_0 \le k. \tag{1}$$

Sparse optimization is classically approached through convex and nonconvex regularization [1, 2, 3] or explicit subset selection [4]. Zhao *et al.* recently developed an exact-penalty route based on

$$\Phi_\lambda(x) = f(x) + \lambda h_k(x), \qquad h_k(x) = \|x\|_1 - \|x\|_{[k]}, \tag{2}$$

where $\|x\|_{[k]}$ sums the k largest magnitudes [5]. Under their error-bound premise (e.g., globally K-Lipschitz f and $\lambda > K$), the penalized and constrained solution sets coincide; related Ky-Fan/DC exact penalties appear in [6, 7].

The missing piece is a black-box realization. Function-value-only problems arise in score APIs, auditing, and simulation [8, 9]. Zeroth-order (ZO) methods replace ∇f by query-based estimators [10, 11, 12, 13], but coordinate differences cost $2d$ queries per iteration. Our question is whether the sparsity structure created by the exact penalty can itself reduce this black-box cost: ZO-IDEP solves the problem with full coordinate queries first, then removes inactive queries after a verifiable support certificate.

The contribution is not a new finite-difference estimator or a new sparse projection: to our knowledge, ZO-IDEP is the first ZO treatment of the trimmed-ℓ_1 exact-penalty dynamics that *certifies when inactive coordinate queries become permanently redundant*. The proof chain is: finite-difference error ⇒ global inexact-proximal convergence ⇒ finite support identification ⇒ an invariant-support certificate. After certification, the k-coordinate trajectory is exactly the hypothetical full-coordinate proximal trajectory, reducing each future step from $2d$ to $2k$ queries.

*Corresponding author.

2. RELATION TO PRIOR WORK

2.1. Exact penalization and a black-box oracle

The error-bound analysis of [5] gives equivalence of the original and penalized minimizers when f is globally K-Lipschitz and $\lambda > K$; this premise is separate from (A1)–(A4) and the local conditions used by our theorems. Related Ky-Fan/DC penalties were studied in [6], and exactness at stronger stationarity notions in [7]. Derivative-free penalty methods for cardinality- and mixed-integer-constrained black-box problems follow trust-region, decomposition, or active-set routes [14, 15, 16], without a query-redundancy certificate.

Definition 1 (Black-box oracle)**.** *A zeroth-order oracle returns $\mathcal{O}_0(x) = f(x)$ for a requested x but does not expose $\nabla f(x)$ or an unbiased gradient estimator.*

This model includes score-only neural-network access [8, 9] and hidden-feature sparse learning [17].

2.2. What is different from sparse ZO and safe screening

Hard-thresholding methods impose sparsity at every iteration; IHT is a classical first-order example [18], while SZOHT studies its interaction with ZO gradient error and may obtain weak dimension dependence [19]; compositional stochastic thresholding targets nonlinear sparse AUC [20]. ZORO instead exploits sparsity of the *gradient* [21], and block-coordinate ZO reduces per-step cost by querying blocks rather than an identified support [22]. ZO-SCHT recently combines ZO estimation with compositional hard thresholding for black-box sparse AUC optimization [17]. Generic ZO proximal methods treat broader nonsmooth black-box composites [23, 24].

Gap-Safe screening rules eliminate variables using convex dual regions [25], and derivative-free methods identify active constraints of explicit constrained problems [26, 27]. Support/activity identification is also known for forward–backward and inexact proximal-gradient methods [28, 29], but without the black-box oracle-restriction certificate studied here. A concurrent preprint searches directly on sparse manifolds with support stabilization [30]. ZO-IDEP instead certifies a *latent Top-k support generated by a nonconvex exact penalty* and proves equality between the support-restricted and hypothetical full-coordinate proximal trajectories.

Algorithm 1 ZO-IDEP

Input: $x_0, k, \lambda, \eta, \{\mu_t\}$; valid certificate data $L, D_t, \{\varepsilon_{t+s}\}_{s\ge 0}$; $S \leftarrow \emptyset$
for $t = 0, 1, \dots$ **do**
  if $S = \emptyset$ **then**
    query all coordinates of $\widehat{g}_t$ by (5)
    if $|\operatorname{supp}(x_t)| = k$ and (16) holds at $x = x_t$ **then**
      $S \leftarrow \operatorname{supp}(x_t)$; $x_{t+1,S} = x_{t,S} - \eta \widehat{g}_{t,S}$; $x_{t+1,S^c} = 0$
    else
      $x_{t+1} \in \mathcal{P}_\eta(x_t - \eta \widehat{g}_t)$
    end if
  else
    update on S as in the certified branch, querying only $\widehat{g}_{t,S}$
  end if
end for

3. ZO-IDEP FROM FUNCTION VALUES

For $z \in \mathbb{R}^d$, let

$$\mathcal{P}_\eta(z) \in \arg\min_u \left\{ \lambda h_k(u) + \frac{1}{2\eta}\|u - z\|_2^2 \right\}. \tag{3}$$

If I indexes any k largest magnitudes of z, every global solution has the closed form [5]

$$[\mathcal{P}_\eta(z)]_i = \begin{cases} z_i, & i \in I, \\ \operatorname{sgn}(z_i)(|z_i| - \eta\lambda)_+, & i \notin I. \end{cases} \tag{4}$$

Strict margins below remove tie ambiguity.

Given only $f(\cdot)$, ZO-IDEP uses coordinate central differences

$$\widehat{g}_{t,i} = \frac{f(x_t + \mu_t e_i) - f(x_t - \mu_t e_i)}{2\mu_t}, \qquad \xi_t := \widehat{g}_t - \nabla f(x_t). \tag{5}$$

This estimator-error viewpoint is standard in ZO/derivative-free analysis [13, 11].

Lemma 1 (Coordinate finite-difference error)**.** *If f has an L-Lipschitz gradient, then*

$$\|\xi_t\|_\infty \le \frac{L\mu_t}{2}, \qquad \|\xi_t\|_2 \le \frac{\sqrt{d}\, L\mu_t}{2}. \tag{6}$$

The full phase performs

$$x_{t+1} \in \mathcal{P}_\eta(x_t - \eta \widehat{g}_t), \tag{7}$$

using $2d$ queries. Once a support S is certified, ZO-IDEP queries only S and uses

$$x_{t+1,S} = x_{t,S} - \eta \widehat{g}_{t,S}, \qquad x_{t+1,S^c} = 0, \tag{8}$$

using $2k$ queries. The full estimator available at the switching iteration is also used to test the certificate below, so switching requires no additional oracle call; Algorithm 1 summarizes the method.

4. THEORY

4.1. Global convergence and identification

Let a bounded level set contain the iterates. Assume (A1) $f \in C^1$ has L-Lipschitz gradient; (A2) $\Psi(x, r) := \Phi_\lambda(x) + r^2/2$ is lower bounded and satisfies the KL property; (A3) $0 < \eta < 1/L$, $\{\mu_t\}$ is nonincreasing, $\sum_t (\sum_{j\ge t} \mu_j^2)^{1/2} < \infty$, and (3) is solved globally; (A4) $\sup \|\nabla f(x)\|_\infty < \lambda$ on the level set, used only to conclude k-sparsity. KL-based inexact descent analyses of this type are standard for forward–backward schemes [31, 32], while explicit gradient-error conditions in convex proximal methods appear in [33].

Theorem 1 (Full-phase convergence)**.** *Under (A1)–(A4), the full-coordinate sequence has finite length and converges to $x^\star$ satisfying*

$$x^\star \in \mathcal{P}_\eta(x^\star - \eta \nabla f(x^\star)), \qquad \|x^\star\|_0 \le k. \tag{9}$$

Moreover, with $a = (1 - \eta L)/(2\eta)$, $c_\eta = L + \eta^{-1}$, $E_T = \sum_{t<T} \|\xi_t\|_2^2$, and $\Delta_0 = \Phi_\lambda(x_0) - \inf \Phi_\lambda$,

$$\frac{1}{T}\sum_{t<T} \operatorname{dist}^2(0, \partial\Phi_\lambda(x_{t+1})) \le \frac{4c_\eta^2 \Delta_0}{aT} + \left(2 + \frac{2c_\eta^2}{a^2}\right)\frac{E_T}{T}. \tag{10}$$

Hence $E_\infty < \infty$ gives an ε-stationary iterate in $\mathcal{O}(\varepsilon^{-2})$ iterations and $\mathcal{O}(d\varepsilon^{-2})$ function evaluations.

For exact k-sparsity, let $S^\star = \operatorname{supp}(x^\star)$ and

$$\gamma_\star = \min_{i\in S^\star} |x_i^\star| - \eta \max_{j\notin S^\star} |\nabla_j f(x^\star)|,$$

$$\tau_\star = \eta\left(\lambda - \max_{j\notin S^\star} |\nabla_j f(x^\star)|\right), \quad \delta_\star = \min\{\gamma_\star/2, \tau_\star\}. \tag{11}$$

Theorem 2 (Finite support identification)**.** *Under (A1)–(A4), if $|S^\star| = k$, $\gamma_\star > 0$, $\tau_\star > 0$, and*

$$(1 + \eta L)\|x_t - x^\star\|_2 + \frac{\eta L \mu_t}{2} < \delta_\star, \tag{12}$$

then $\operatorname{supp}(x_{t+1}) = S^\star$. Consequently, a finite T_{id} exists after which the full method keeps $S^\star$. If, for some $q_x, q_\mu \in (0, 1)$ and every $t \ge t_0$, $\|x_t - x^\star\|_2 \le C_x q_x^{t-t_0}$ and $\mu_t \le C_\mu q_\mu^{t-t_0}$, then

$$T_{\mathrm{id}} \le t_0 + 2 + \left\lceil \max\left\{0, \max\left\{ \frac{\log \frac{2(1+\eta L)C_x}{\delta_\star}}{\log(1/q_x)}, \frac{\log \frac{\eta L C_\mu}{\delta_\star}}{\log(1/q_\mu)} \right\}\right\}\right\rceil. \tag{13}$$

Unlike forward–backward activity identification [28, 29], safe screening [25], and derivative-free active-set rules [26, 27], the identified set here is the latent Top-k support of the exact-penalty prox, with the ZO perturbation shown explicitly.

4.2. Certified support restriction

At a candidate switching iteration t, let $x = x_t$, $S = \operatorname{supp}(x)$, and $|S| = k$. Define $f_S(u_S) = f(u_S, 0_{S^c})$ and let $X_S^\star = \arg\min f_S$.

Theorem 3 (Invariant-support certificate)**.** *Assume f_S is convex and L-smooth, $X_S^\star \neq \emptyset$, and $0 < \eta \le 1/L$. Suppose valid numbers D_t and $\{\varepsilon_{t+s}\}_{s\ge 0}$ satisfy*

$$\operatorname{dist}(x, X_S^\star) \le D_t, \qquad \|\widehat{g}_{t+s} - \nabla f(x_{t+s})\|_\infty \le \varepsilon_{t+s}, \tag{14}$$

with $B_t := \sum_{s\ge 0} \varepsilon_{t+s} < \infty$ and $\bar{\varepsilon}_t := \sup_{s\ge 0} \varepsilon_{t+s}$. Set

$$\begin{aligned} R_t &= D_t + \eta\sqrt{k}\, B_t, \\ H_t &= \|\widehat{g}_{S^c}(x)\|_\infty + \varepsilon_t + 2LR_t, \\ A_t &= \min_{i\in S} |x_i| - 2R_t - \eta(LR_t + \bar{\varepsilon}_t). \end{aligned} \tag{15}$$

If

$$H_t + \bar{\varepsilon}_t < \lambda, \qquad A_t > \eta(H_t + \bar{\varepsilon}_t), \tag{16}$$

then every subsequent support-restricted iterate remains on S, and at each such iterate the hypothetical full-coordinate ZO proximal step (7) *selects the same S and returns exactly the same next point as* (8)*. Thus inactive coordinate queries are redundant.*

Remark 1 (Localization radius)**.** *The certificate takes a valid radius D_t as data. It can come from a compact level set, a problem-specific bound, or, when curvature information is available, the estimate $D_t \le (\|\widehat{g}_S(x)\|_2 + \sqrt{k}\varepsilon_t)/m$.*

Table 1. $n = 128, d = 256, k = 16$; means over 30 trials. Error: ℓ_2 recovery error; Ov.: planted-support overlap; Qry.: function evaluations.

Method	Obj.↓	Error↓	Ov.↑	Qry.↓
PG-EP [5]	.0053	.255	.971	FO
SZOHT-RD [19]	.0451	1.526	.573	30,300
Coord-ZO-IHT	.0182	.857	.783	153,600
Full-ZO-EP	.0053	.255	.971	153,600
ZO-IDEP	**.0053**	**.255**	**.971**	**59,568**

Corollary 1 (Post-switch rate and query ratio)**.** *Under Theorem 3, let $x_S^\star \in X_S^\star$ attain the bound $\|x - x_S^\star\| \le D_t$ and define $\bar{x}_N = N^{-1}\sum_{s=1}^{N} x_{t+s}$. Then*

$$f_S(\bar{x}_N) - f_S^\star \le \frac{D_t^2}{2\eta N} + \frac{R_t\sqrt{k}}{N}\sum_{s=0}^{N-1}\varepsilon_{t+s} \le \frac{D_t^2/(2\eta) + R_t\sqrt{k}B_t}{N}. \tag{17}$$

Thus the post-switch function-value complexity is $\mathcal{O}(k/\varepsilon)$; when the restricted objective is strongly convex, Proposition 1 gives the geometric rate $\mathcal{O}(k\log(1/\varepsilon))$. More generally, the restricted and hypothetical full trajectories are identical, so for a common post-switch hitting time N_{tar},

$$\frac{Q_{\mathrm{IDEP}}}{Q_{\mathrm{full}}} = \frac{dT_{\mathrm{sw}} + kN_{\mathrm{tar}}}{d(T_{\mathrm{sw}} + N_{\mathrm{tar}})} \longrightarrow \frac{k}{d} \quad \text{as } N_{\mathrm{tar}} \to \infty. \tag{18}$$

Proposition 1 (Strong-convexity specialization)**.** *Under Theorem 3, suppose f_S is m-strongly convex with $m > 0$ and $\mu_{t+s} \le \mu_t$, so Lemma 1 gives $\varepsilon_{t+s} \le \varepsilon_t = L\mu_t/2$ uniformly. Take the gradient-generated radius $D_t = (\|\widehat{g}_S(x)\|_2 + \sqrt{k}\varepsilon_t)/m$ and set*

$$q = \sqrt{1 - \tfrac{2\eta mL}{m+L}}, \qquad H_t = \|\widehat{g}_{S^c}(x)\|_\infty + \varepsilon_t + 2LR,$$
$$R = D_t, \qquad A_t = \min_{i\in S}|x_i| - 2R - \eta(LR + \varepsilon_t). \tag{19}$$

If $qR + \eta\sqrt{k}\varepsilon_t \le R$, $H_t + \varepsilon_t < \lambda$, and $A_t > \eta(H_t + \varepsilon_t)$, then the conclusions of Theorem 3 hold and the restricted trajectory contracts: with $r_s = \|x_{t+s} - x_S^\star\|_2$, $r_s \le q^s R + \eta\sqrt{k}\sum_{j=0}^{s-1} q^{s-1-j}\varepsilon_{t+j}$, so if $\varepsilon_{t+j} \le c\beta^j$, then $r_s = \mathcal{O}(\rho^s)$ with $\rho = \max\{q, \beta\} < 1$, and for fixed $\mu_t = \mu$, $\limsup_{s\to\infty} r_s \le \eta\sqrt{k}L\mu/(2(1-q))$.

5. NUMERICAL RESULTS

We follow the sparse-regression protocol of [5] with 30 fixed seeds and 300 steps. PG-EP is the first-order reference; Full-ZO-EP uses the same exact-penalty objective/prox without restriction; Coord-ZO-IHT and SZOHT-RD are hard-thresholding baselines [18, 19]. All penalties use $\lambda_t = (\lambda/40)40^{\min\{1,(t+1)/C\}}$ and certification is tested only at terminal λ. Regression/scaling use $(\lambda, C, \eta, \mu_t) = (.025, 100, .9/L, 10^{-3})$; ridge logistic uses $\lambda = .02$, $\eta = .1/L$, and a swept fixed or geometric μ_t (stress: $C = 200$); phase retrieval uses $\lambda = .10$ with $\eta = .8/L$. Least-squares central differences are exact ($\varepsilon_t = 0$); the logistic runs exercise $\varepsilon_t = L\mu_t/2$ in (15). The radius D_t of Theorem 3 uses restricted curvature, $D_t = (\|\widehat{g}_S(x)\|_2 + \sqrt{k}\varepsilon_t)/m$ with $m = \lambda_{\min}(A_S^\top A_S/n)$ for the n-sample least-squares model and $m = .02$, the ridge coefficient, for ridge logistic.

For valid-bound regression and geometrically smoothed logistic runs, the maximum endpoint gap and post-switch shadow-step mismatch (restricted versus hypothetical full-coordinate step) are zero, and at fixed $k/d = 1/16$ savings remain 58.3–62.5% as d grows (Table 2), covering pre-switch cost and the switching iteration's full-coordinate estimate. The scaling sweep uses different seeds, explaining the small $(256, 16)$ discrepancy with Table 1. In a harder regression sweep, $31/150$ runs do not certify within 300 steps; the certificate is sufficient, not guaranteed.

The diagnostics (Figure 1) agree with the theory. For $\mu \le 10^{-2}$, all 30 logistic runs certify, while at 3×10^{-2} none switches; the measured identification margin correlates negatively with switch time ($r = -0.695$). Fixed-μ runs track the Proposition 1 neighborhood; the restricted-optimum distance rises from 1.9×10^{-10} to 2.3×10^{-5} over the sweep. Under geometric smoothing, the empirical restricted contraction is 0.9820 ± 0.0001 for $\beta = .99$ versus the conservative $\rho = .99$ of Proposition 1, and $Q_{\mathrm{IDEP}}/Q_{\mathrm{full}}$ decreases from .990 at target 10^{-2} to .715 at 10^{-3}. Heuristic stability rules freeze a wrong local support in 40–46.7% of stress-test runs (Table 3). Phase-retrieval local-basin runs (120/120) satisfy the implemented certificate-form inequalities and save 48.5% on average, as an empirical diagnostic with pointwise curvature surrogates.

6. CONCLUSION

ZO-IDEP makes the trimmed-ℓ_1 exact-penalty route function-value only and propagates the ZO estimation error through convergence, identification, and certified query restriction. Once certified, inactive coordinate evaluations are provably redundant and the restricted trajectory exactly matches Full-ZO-EP. The certificate relies on a valid localization radius (Remark 1); when the restricted objective is strongly convex, the geometric rates of Proposition 1 apply.

7. APPENDIX: PROOFS

The main proofs are collected here.

Proof of Lemma 1. For each coordinate i, the fundamental theorem of calculus gives

$$\widehat{g}_{t,i} - \nabla_i f(x_t) = \frac{1}{2\mu_t}\int_{-\mu_t}^{\mu_t}\big(\nabla_i f(x_t + se_i) - \nabla_i f(x_t)\big)\,ds. \tag{20}$$

By L-smoothness, the integrand is bounded in magnitude by $L|s|$, hence $|\widehat{g}_{t,i} - \nabla_i f(x_t)| \le L\mu_t/2$. Taking the maximum and Euclidean norms yields (6). □

Proof of Theorem 1. Let $s_t = x_{t+1} - x_t$ and $a = (1 - \eta L)/(2\eta) > 0$. Global optimality of the proximal subproblem, using x_t as a competitor, yields

$$\lambda h_k(x_{t+1}) + \langle \widehat{g}_t, s_t\rangle + \frac{\|s_t\|^2}{2\eta} \le \lambda h_k(x_t). \tag{21}$$

Combining (21) with L-smoothness of f, writing $\widehat{g}_t = \nabla f(x_t) + \xi_t$, and applying Young's inequality gives

$$\Phi_\lambda(x_{t+1}) \le \Phi_\lambda(x_t) - \frac{a}{2}\|s_t\|^2 + \frac{\|\xi_t\|^2}{2a}. \tag{22}$$

Fermat's rule for the globally solved proximal subproblem provides $v_{t+1} \in \lambda\partial h_k(x_{t+1})$ such that $\widehat{g}_t + s_t/\eta + v_{t+1} = 0$. Therefore

$$w_{t+1} := \nabla f(x_{t+1}) + v_{t+1} \in \partial\Phi_\lambda(x_{t+1}),$$
$$\|w_{t+1}\| \le c_\eta\|s_t\| + \|\xi_t\|. \tag{23}$$


With $\delta_t = \|\xi_t\|^2/(2a)$ and $r_t = \sum_{j\ge t}\delta_j$, set $\rho_t = \sqrt{2r_t}$ and lift to $\Psi(x, r) = \Phi_\lambda(x) + r^2/2$. Then (22) gives $\Psi(x_{t+1}, \rho_{t+1}) +$

Table 2. Fixed-ratio scaling; every row certifies in 30/30 runs.

(d, k)	Mean T_{sw}	ZO-IDEP / Full	Saving
$(128, 8)$	99.0	28,800 / 76,800	62.5%
$(256, 16)$	103.2	59,616 / 153,600	61.2%
$(512, 32)$	104.2	120,192 / 307,200	60.9%
$(1024, 64)$	112.5	256,320 / 614,400	58.3%

Table 3. Low-margin logistic stress test, $(n, d, k) = (512, 128, 8)$, 800 iterations; Wrong freeze: endpoint differs from Full-ZO-EP.

Rule	Mean switch	Wrong	Saving
Stable-3	3.0	14/30	93.3%
Stable-5	5.0	14/30	93.0%
Stable-10	10.4	12/30	92.4%
Certified ZO-IDEP	no switch	0/30	0%
Oracle-EndSupport	119.3	0/30	79.6%



(a) (b) (c)

Fig. 1. Theory-aligned diagnostics: (a) ZO error can delay/prevent certification; (b) a larger identification margin switches earlier; (c) the query ratio decreases as the target accuracy tightens.

$(a/2)\|s_t\|^2 \le \Psi(x_t, \rho_t)$. Lemma 1 and (A3) imply $\sum_t(\|\xi_t\| + \rho_t) < \infty$, while (23) bounds $\mathrm{dist}(0, \partial\Psi(x_{t+1}, \rho_{t+1}))$ by $c_\eta\|s_t\| + \|\xi_t\| + \rho_{t+1}$. These verify hypotheses H1–H4 of the abstract inexact forward–backward framework [32] with $F_{\mathrm{abs}} = \Psi$, descent constant $a/2$, $b = c_\eta$, and $\zeta_{t+1} = \|\xi_t\| + \rho_{t+1}$; the KL property of Ψ from (A2) supplies H5–H6 [31], hence $\sum_t \|s_t\| < \infty$ and $x_t \to x^\star$. Setting $z_t = x_t - \eta\widehat{g}_t$ and $z^\star = x^\star - \eta\nabla f(x^\star)$, global optimality of (3) with arbitrary competitor u gives $\lambda h_k(x_{t+1}) + \frac{\|x_{t+1}-z_t\|^2}{2\eta} \le \lambda h_k(u) + \frac{\|u-z_t\|^2}{2\eta}$; passing to the limit proves (9). A nonzero soft-thresholded tail coordinate would force $|\nabla_j f(x^\star)| = \lambda$, contradicting (A4). Summing (22) yields $\sum_{t<T}\|s_t\|^2 \le 2\Delta_0/a + E_T/a^2$; combining with (23) proves (10). □

Proof of Theorem 2. Let $z^\star = x^\star - \eta\nabla f(x^\star)$ and $\widehat{z}_t = x_t - \eta\widehat{g}_t$. From smoothness and Lemma 1,

$$\|\widehat{z}_t - z^\star\|_\infty \le (1 + \eta L)\|x_t - x^\star\|_2 + \eta L\mu_t/2. \tag{24}$$

At the fixed point, $z_i^\star = x_i^\star$ for $i \in S^\star$ and $z_j^\star = -\eta\nabla_j f(x^\star)$ for $j \notin S^\star$. Condition (12) is strictly smaller than half the active/inactive ranking gap and smaller than the inactive soft-threshold gap. Hence the Top-k set in (4) is exactly $S^\star$, while every $j \notin S^\star$ remains below $\eta\lambda$. Thus $\mathrm{supp}(x_{t+1}) = S^\star$. Since $x_t \to x^\star$ and $\mu_t \to 0$, the condition holds after a finite index; substituting the stated local geometric bounds into (12) gives the explicit bound (13). □

Proof of Theorem 3. Choose $x_S^\star \in X_S^\star$ with $\|x - x_S^\star\| \le D_t$. For convex L-smooth f_S and $0 < \eta \le 1/L$, the exact gradient map $G = I - \eta\nabla f_S$ is nonexpansive. Writing the restricted ZO step as $x^+ = G(x) - \eta\xi_S$, induction gives

$$\|x_{t+s} - x_S^\star\|_2 \le D_t + \eta\sqrt{k}\sum_{j=0}^{s-1}\varepsilon_{t+j} \le R_t. \tag{25}$$

Thus any future restricted iterate y obeys $\|y - x\| \le 2R_t$. Smoothness then implies

$$\|\nabla_{S^c} f(y)\|_\infty \le \|\widehat{g}_{S^c}(x)\|_\infty + \varepsilon_t + 2LR_t = H_t, \tag{26}$$

$$\|\nabla_S f(y)\|_2 \le L\|y - x_S^\star\|_2 \le LR_t. \tag{27}$$

For the hypothetical full ZO input $z = y - \eta\widehat{g}(y)$, every inactive coordinate therefore satisfies $|z_j| \le \eta(H_t + \bar{\varepsilon}_t) < \eta\lambda$, while each active coordinate satisfies $|z_i| \ge A_t > \eta(H_t + \bar{\varepsilon}_t)$. Hence the unique Top-$k$ set is S, inactive coordinates are soft-thresholded to zero, and the full proximal step equals the restricted update; (25) closes the induction. □

Proof of Corollary 1. Let $y = x_{t+s}$ and $y^+ = x_{t+s+1}$. Convexity, L-smoothness, and $\eta \le 1/L$ imply

$$f_S(y^+) - f_S^\star \le \frac{\|y - x_S^\star\|^2 - \|y^+ - x_S^\star\|^2}{2\eta} + \sqrt{k}\varepsilon_{t+s}\|y^+ - x_S^\star\|. \tag{28}$$

Theorem 3 bounds the last norm by R_t. Summing over $s = 0, \ldots, N-1$, dividing by N, and using convexity at the average iterate gives (17); (18) follows since the two post-switch trajectories share hitting times and cost $2k$ vs $2d$ per step. □

Proof of Proposition 1. Strong convexity gives $\|x - x_S^\star\|_2 \le R$. The exact gradient map $G = I - \eta\nabla f_S$ is q-Lipschitz on S, and the restricted ZO step is $x^+ = G(x) - \eta\xi_S$, so $r_{s+1} \le q\,r_s + \eta\|\xi_S\|_2 \le q\,r_s + \eta\sqrt{k}\varepsilon_{t+s}$, which unrolls to the stated bound. The condition $qR + \eta\sqrt{k}\varepsilon_t \le R$ keeps the radius-R ball invariant, and the remaining two reproduce the active/inactive separation of the proof of Theorem 3, so every full ZO step equals the restricted one. □

8. REFERENCES

[1] Robert Tibshirani, "Regression shrinkage and selection via the lasso," *J. Roy. Statist. Soc. Ser. B*, vol. 58, no. 1, pp. 267–288, 1996.

[2] Jianqing Fan and Runze Li, "Variable selection via nonconcave penalized likelihood and its oracle properties," *J. Amer. Statist. Assoc.*, vol. 96, no. 456, pp. 1348–1360, 2001.

[3] Cun-Hui Zhang, "Nearly unbiased variable selection under minimax concave penalty," *Ann. Statist.*, vol. 38, no. 2, pp. 894–942, 2010.

[4] Dimitris Bertsimas, Angela King, and Rahul Mazumder, "Best subset selection via a modern optimization lens," *Ann. Statist.*, vol. 44, no. 2, pp. 813–852, 2016.

[5] Jianing Zhao, Junbin Liu, Anthony Man-Cho So, and Wing-Kin Ma, "An exact penalty method for sparsity-constrained optimization," in *Proc. IEEE ICASSP*, 2026.

[6] Jun ya Gotoh, Akiko Takeda, and Katsuya Tono, "Dc formulations and algorithms for sparse optimization problems," *Math. Program.*, vol. 169, no. 1, pp. 141–176, 2018.

[7] Shotaro Yagishita and Jun ya Gotoh, "Exact penalization at d-stationary points of cardinality- or rank-constrained problem," *Optimization*, vol. 75, no. 10, pp. 2701–2735, 2026.

[8] Pin-Yu Chen, Huan Zhang, Yash Sharma, Jinfeng Yi, and Cho-Jui Hsieh, "Zoo: Zeroth order optimization based black-box attacks to deep neural networks without training substitute models," in *Proc. ACM AISec*, 2017, pp. 15–26.

[9] Viet Quoc Vo, Ehsan Abbasnejad, and Damith C. Ranasinghe, "Brusleattack: A query-efficient score-based black-box sparse adversarial attack," in *Proc. ICLR*, 2024.

[10] Yurii Nesterov and Vladimir Spokoiny, "Random gradient-free minimization of convex functions," *Found. Comput. Math.*, vol. 17, no. 2, pp. 527–566, 2017.

[11] Saeed Ghadimi and Guanghui Lan, "Stochastic first- and zeroth-order methods for nonconvex stochastic programming," *SIAM J. Optim.*, vol. 23, no. 4, pp. 2341–2368, 2013.

[12] John C. Duchi, Michael I. Jordan, Martin J. Wainwright, and Andre Wibisono, "Optimal rates for zero-order convex optimization: The power of two function evaluations," *IEEE Trans. Inf. Theory*, vol. 61, no. 5, pp. 2788–2806, 2015.

[13] Albert S. Berahas, Liyuan Cao, Krzysztof Choromanski, and Katya Scheinberg, "A theoretical and empirical comparison of gradient approximations in derivative-free optimization," *Found. Comput. Math.*, vol. 22, no. 2, pp. 507–560, 2022.

[14] Matteo Lapucci, Tommaso Levato, and Marco Sciandrone, "Convergent inexact penalty decomposition methods for cardinality-constrained problems," *J. Optim. Theory Appl.*, vol. 188, no. 2, pp. 473–496, 2021.

[15] Caio Merlini Giuliani, Eduardo Camponogara, and Andrew R. Conn, "A derivative-free exact penalty algorithm: Basic ideas, convergence theory and computational studies," *Comput. Appl. Math.*, vol. 41, no. 1, pp. 56, 2022.

[16] Tommaso Giovannelli, Giampaolo Liuzzi, Stefano Lucidi, and Francesco Rinaldi, "Derivative-free methods for mixed-integer nonsmooth constrained optimization," *Comput. Optim. Appl.*, vol. 82, pp. 293–327, 2022.

[17] Wenkang Wang, Dongxu Liu, and Bin Gu, "Zeroth-order stochastic compositional gradient descent: Towards black-box sparse auc maximization," in *Proc. AISTATS*, 2026, vol. 300 of *Proceedings of Machine Learning Research*, pp. 3268–3276.

[18] Thomas Blumensath, Mehrdad Yaghoobi, and Mike E. Davies, "Iterative hard thresholding and l0 regularisation," in *Proc. IEEE ICASSP*, 2007, vol. 3, pp. III–877–III–880.

[19] William de Vazelhes, Hualin Zhang, Huimin Wu, Xiaotong Yuan, and Bin Gu, "Zeroth-order hard-thresholding: Gradient error vs. expansivity," in *Adv. Neural Inf. Process. Syst.*, 2022, vol. 35, pp. 22589–22601.

[20] Wenkang Wang, Dongxu Liu, and Bin Gu, "Towards nonlinear sparse auc maximization via compositional stochastic hard thresholding," in *Proc. AAAI*, 2026, vol. 40 of *Proceedings of the AAAI Conference on Artificial Intelligence*, pp. 26489–26497.

[21] HanQin Cai, Daniel McKenzie, Wotao Yin, and Zhenliang Zhang, "Zeroth-order regularized optimization (ZORO): Approximately sparse gradients and adaptive sampling," *SIAM J. Optim.*, vol. 32, no. 2, pp. 687–714, 2022.

[22] HanQin Cai, Yuchen Lou, Daniel McKenzie, and Wotao Yin, "A zeroth-order block coordinate descent algorithm for huge-scale black-box optimization," in *Proc. ICML*, 2021, vol. 139 of *Proceedings of Machine Learning Research*, pp. 1193–1203.

[23] Ehsan Kazemi and Liqiang Wang, "Efficient zeroth-order proximal stochastic method for nonconvex nonsmooth black-box problems," *Mach. Learn.*, vol. 113, no. 1, pp. 97–120, 2024.

[24] Vyacheslav Kungurtsev and Francesco Rinaldi, "A zeroth order method for stochastic weakly convex optimization," *Comput. Optim. Appl.*, vol. 80, no. 3, pp. 731–753, 2021.

[25] Eugene Ndiaye, Olivier Fercoq, Alexandre Gramfort, and Joseph Salmon, "Gap safe screening rules for sparsity enforcing penalties," *J. Mach. Learn. Res.*, vol. 18, no. 128, pp. 1–33, 2017.

[26] Robert Michael Lewis and Virginia Torczon, "Active set identification for linearly constrained minimization without explicit derivatives," *SIAM J. Optim.*, vol. 20, no. 3, pp. 1378–1405, 2009.

[27] Andrea Brilli, Andrea Cristofari, Giampaolo Liuzzi, and Stefano Lucidi, "Complexity results and active-set identification of a derivative-free method for bound-constrained problems," *J. Optim. Theory Appl.*, vol. 209, no. 1, 2026, Art. no. 3.

[28] Jingwei Liang, Jalal Fadili, and Gabriel Peyré, "Activity identification and local linear convergence of forward–backward-type methods," *SIAM J. Optim.*, vol. 27, no. 1, pp. 408–437, 2017.

[29] Yutong Dai and Daniel P. Robinson, "Inexact proximal-gradient methods with support identification," *arXiv preprint arXiv:2211.02214*, 2022.

[30] Morteza Kimiaei, Shima Shabani, and Michael Breuss, "Reservoir zero-coordinatewise projected subspace search for minimization over sparse symmetric sets in machine learning," *arXiv preprint arXiv:2606.28124*, 2026.

[31] Hédy Attouch, Jérôme Bolte, and Benar Fux Svaiter, "Convergence of descent methods for semi-algebraic and tame problems: Proximal algorithms, forward–backward splitting, and regularized gauss–seidel methods," *Math. Program.*, vol. 137, no. 1–2, pp. 91–129, 2013.

[32] Silvia Bonettini, Peter Ochs, Marco Prato, and Simone Rebegoldi, "An abstract convergence framework with application to inertial inexact forward–backward methods," *Comput. Optim. Appl.*, vol. 84, no. 2, pp. 319–362, 2023.

[33] Mark Schmidt, Nicolas Le Roux, and Francis Bach, "Convergence rates of inexact proximal-gradient methods for convex optimization," in *Adv. Neural Inf. Process. Syst.*, 2011, vol. 24.