

Beginner tree algorithms

 William Fiset 




Rooting a tree

 William Fiset 

Rooting a tree

Sometimes it's useful to root an undirected tree to add structure to the problem you're trying to solve.




Undirected graph
adjacency list:

```
0 -> [2, 1, 5]
1 -> [0]
2 -> [3, 0]
3 -> [2]
4 -> [5]
5 -> [4, 6, 0]
6 -> [5]
```


Rooting a tree

Sometimes it's useful to root an undirected tree to add structure to the problem you're trying to solve.




Rooting a tree

Conceptually this is like "picking up" the tree by a specific node and having all the edges point downwards.




Rooting a tree


You can root a tree using any of its nodes.




In some situations it's also useful to keep have a reference to the parent node in order to walk up the tree.




Rooting a tree is easily done depth first.





Rooting a tree is easily done depth first.





Rooting a tree is easily done depth first.





Rooting a tree is easily done depth first.





Rooting a tree is easily done depth first.





Rooting a tree is easily done depth first.





Rooting a tree is easily done depth first.





Rooting a tree is easily done depth first.





Rooting a tree is easily done depth first.





Rooting a tree is easily done depth first.





Rooting a tree is easily done depth first.





Rooting a tree is easily done depth first.





Rooting a tree is easily done depth first.





Rooting a tree is easily done depth first.





Rooting a tree is easily done depth first.





Rooting a tree is easily done depth first.





Rooting a tree is easily done depth first.





Rooting a tree is easily done depth first.





Rooting a tree is easily done depth first.



Rooting a tree is easily done depth first.



Rooting a tree is easily done depth first.



Rooting tree pseudocode

```
# TreeNode object structure.
```

```
class TreeNode:
```

```
    # Unique integer id to identify this node.
```

```
    int id;
```

```
    # Pointer to parent TreeNode reference. Only the  
    # root node has a null parent TreeNode reference.
```

```
    TreeNode parent;
```

```
    # List of pointers to child TreeNodes.
```

```
    TreeNode[] children;
```

Rooting tree pseudocode

```
# TreeNode object structure.
```

```
class TreeNode:
```

```
    # Unique integer id to identify this node.
```

```
    int id;
```

```
    # Pointer to parent TreeNode reference. Only the  
    # root node has a null parent TreeNode reference.
```

```
    TreeNode parent;
```

```
    # List of pointers to child TreeNodes.
```

```
    TreeNode[] children;
```

Rooting tree pseudocode

TreeNode object structure.

class **TreeNode**:

Unique integer id to identify this node.

int id;

Pointer to parent TreeNode reference. Only the
root node has a null parent TreeNode reference.

TreeNode parent;

List of pointers to child TreeNodes.

TreeNode[] children;

Rooting tree pseudocode

TreeNode object structure.

class TreeNode:

Unique integer id to identify this node.

int id;

Pointer to parent TreeNode reference. Only the
root node has a null parent TreeNode reference.
TreeNode parent;

List of pointers to child TreeNodes.

TreeNode[] children;

Rooting tree pseudocode

TreeNode object structure.

class TreeNode:

Unique integer id to identify this node.

int id;

Pointer to parent TreeNode reference. Only the
root node has a null parent TreeNode reference.

TreeNode parent;

List of pointers to child TreeNodes.

TreeNode[] children;

Rooting tree pseudocode

```
# g is the graph/tree represented as an adjacency
# list with undirected edges. If there's an edge between
# (u, v) there's also an edge between (v, u).
# rootId is the id of the node to root the tree from.
function rootTree(g, rootId = 0):
    root = TreeNode(rootId, null, [])
    return buildTree(g, root, null)

# Build tree recursively depth first.
function buildTree(g, node, parent):
    for childId in g[node.id]:
        # Avoid adding an edge pointing back to the parent.
        if parent != null and childId == parent.id:
            continue
        child = TreeNode(childId, node, [])
        node.children.add(child)
        buildTree(g, child, node)
    return node
```

Rooting tree pseudocode

```
# g is the graph/tree represented as an adjacency
# list with undirected edges. If there's an edge between
# (u, v) there's also an edge between (v, u).
# rootId is the id of the node to root the tree from.
function rootTree(g, rootId = 0):
    root = TreeNode(rootId, null, [])
    return buildTree(g, root, null)

# Build tree recursively depth first.
function buildTree(g, node, parent):
    for childId in g[node.id]:
        # Avoid adding an edge pointing back to the parent.
        if parent != null and childId == parent.id:
            continue
        child = TreeNode(childId, node, [])
        node.children.add(child)
        buildTree(g, child, node)
    return node
```

Rooting tree pseudocode

```
# g is the graph/tree represented as an adjacency
# list with undirected edges. If there's an edge between
# (u, v) there's also an edge between (v, u).
# rootId is the id of the node to root the tree from.
function rootTree(g, rootId = 0):
    root = TreeNode(rootId, null, [])
    return buildTree(g, root, null)

# Build tree recursively depth first.
function buildTree(g, node, parent):
    for childId in g[node.id]:
        # Avoid adding an edge pointing back to the parent.
        if parent != null and childId == parent.id:
            continue
        child = TreeNode(childId, node, [])
        node.children.add(child)
        buildTree(g, child, node)
    return node
```

Rooting tree pseudocode

```
# g is the graph/tree represented as an adjacency  
# list with undirected edges. If there's an edge between  
# (u, v) there's also an edge between (v, u).  
# rootId is the id of the node to root the tree from.
```

```
function rootTree(g, rootId = 0):  
    root = TreeNode(rootId, null, [])  
    return buildTree(g, root, null)
```

```
# Build tree recursively depth first.
```

```
function buildTree(g, node, parent):  
    for childId in g[node.id]:  
        # Avoid adding an edge pointing back to the parent.  
        if parent != null and childId == parent.id:  
            continue  
        child = TreeNode(childId, node, [])  
        node.children.add(child)  
        buildTree(g, child, node)  
    return node
```

Rooting tree pseudocode

```
# g is the graph/tree represented as an adjacency
# list with undirected edges. If there's an edge between
# (u, v) there's also an edge between (v, u).
# rootId is the id of the node to root the tree from.
function rootTree(g, rootId = 0):
    root = TreeNode(rootId, null, [])
    return buildTree(g, root, null)

# Build tree recursively depth first.
function buildTree(g, node, parent):
    for childId in g[node.id]:
        # Avoid adding an edge pointing back to the parent.
        if parent != null and childId == parent.id:
            continue
        child = TreeNode(childId, node, [])
        node.children.add(child)
        buildTree(g, child, node)
    return node
```

Rooting tree pseudocode

```
# g is the graph/tree represented as an adjacency
# list with undirected edges. If there's an edge between
# (u, v) there's also an edge between (v, u).
# rootId is the id of the node to root the tree from.
function rootTree(g, rootId = 0):
    root = TreeNode(rootId, null, [])
    return buildTree(g, root, null)

# Build tree recursively depth first.
function buildTree(g, node, parent):
    for childId in g[node.id]:
        # Avoid adding an edge pointing back to the parent.
        if parent != null and childId == parent.id:
            continue
        child = TreeNode(childId, node, [])
        node.children.add(child)
        buildTree(g, child, node)
    return node
```

Rooting tree pseudocode

```
# g is the graph/tree represented as an adjacency
# list with undirected edges. If there's an edge between
# (u, v) there's also an edge between (v, u).
# rootId is the id of the node to root the tree from.
function rootTree(g, rootId = 0):
    root = TreeNode(rootId, null, [])
    return buildTree(g, root, null) ← root node has
                                     no parent!

# Build tree recursively depth first.
function buildTree(g, node, parent):
    for childId in g[node.id]:
        # Avoid adding an edge pointing back to the parent.
        if parent != null and childId == parent.id:
            continue
        child = TreeNode(childId, node, [])
        node.children.add(child)
        buildTree(g, child, node)
    return node
```


Rooting tree pseudocode

```
# g is the graph/tree represented as an adjacency
# list with undirected edges. If there's an edge between
# (u, v) there's also an edge between (v, u).
# rootId is the id of the node to root the tree from.
function rootTree(g, rootId = 0):
    root = TreeNode(rootId, null, [])
    return buildTree(g, root, null)

# Build tree recursively depth first.
function buildTree(g, node, parent):
    for childId in g[node.id]:
        # Avoid adding an edge pointing back to the parent.
        if parent != null and childId == parent.id:
            continue
        child = TreeNode(childId, node, [])
        node.children.add(child)
        buildTree(g, child, node)
    return node
```

Rooting tree pseudocode

```
# g is the graph/tree represented as an adjacency
# list with undirected edges. If there's an edge between
# (u, v) there's also an edge between (v, u).
# rootId is the id of the node to root the tree from.
function rootTree(g, rootId = 0):
    root = TreeNode(rootId, null, [])
    return buildTree(g, root, null)

# Build tree recursively depth first.
function buildTree(g, node, parent):
    for childId in g[node.id]:
        # Avoid adding an edge pointing back to the parent.
        if parent != null and childId == parent.id:
            continue
        child = TreeNode(childId, node, [])
        node.children.add(child)
        buildTree(g, child, node)
    return node
```

Rooting tree pseudocode

```
# g is the graph/tree represented as an adjacency
# list with undirected edges. If there's an edge between
# (u, v) there's also an edge between (v, u).
# rootId is the id of the node to root the tree from.
function rootTree(g, rootId = 0):
    root = TreeNode(rootId, null, [])
    return buildTree(g, root, null)

# Build tree recursively depth first.
function buildTree(g, node, parent):
    for childId in g[node.id]:
        # Avoid adding an edge pointing back to the parent.
        if parent != null and childId == parent.id:
            continue
        child = TreeNode(childId, node, [])
        node.children.add(child)
        buildTree(g, child, node)
    return node
```

Rooting tree pseudocode

```
# g is the graph/tree represented as an adjacency
# list with undirected edges. If there's an edge between
# (u, v) there's also an edge between (v, u).
# rootId is the id of the node to root the tree from.
function rootTree(g, rootId = 0):
    root = TreeNode(rootId, null, [])
    return buildTree(g, root, null)

# Build tree recursively depth first.
function buildTree(g, node, parent):
    for childId in g[node.id]:
        # Avoid adding an edge pointing back to the parent.
        if parent != null and childId == parent.id:
            continue
        child = TreeNode(childId, node, [])
        node.children.add(child)
        buildTree(g, child, node)
    return node
```

Rooting tree pseudocode

```
# g is the graph/tree represented as an adjacency
# list with undirected edges. If there's an edge between
# (u, v) there's also an edge between (v, u).
# rootId is the id of the node to root the tree from.
function rootTree(g, rootId = 0):
    root = TreeNode(rootId, null, [])
    return buildTree(g, root, null)

# Build tree recursively depth first.
function buildTree(g, node, parent):
    for childId in g[node.id]:
        # Avoid adding an edge pointing back to the parent.
        if parent != null and childId == parent.id:
            continue
        child = TreeNode(childId, node, [])
        node.children.add(child)
        buildTree(g, child, node)
    return node
```


Rooting a Tree

