


```
src/Algorithms/PartB_SMAStar.java
```

```

27      *
28      * @param@returnprivatestaticancestors(Node node)newArrayListwhilenull
return/**
29      * Identifies the node with the worst (highest) f-cost that is a leaf
node in
30      * the frontier.
31      *
32      * @param@returnprivatestaticgetWorstLeafNode(PriorityQueue<Node>
frontier)returnnull/**
33      * Prints the nodes currently in the frontier along with their f-
costs, sorted
34      * by f-cost, angle, and distance.
35      *
36      * @paramprivatestaticvoidprintFrontier(PriorityQueue<Node> frontier)
newNode0if0Stringresult="%.3f","[""/**
37      * Constructs the path from the goal node back to the start node
using the
38      * parent map.
39      *
40      * @param@param@returnprivatestaticconstructPath(Node goal, Map<Node,
Node> parentMap)newArrayListNodecurrent=whilenullreturn Algorithms;
41
42  General.Node;
43  General.Utility;
44
45  java.util.ArrayList;
46  java.util.Arrays;
47  java.util.Collections;
48  java.util.Comparator;
49  java.util.HashMap;
50  java.util.List;
51  java.util.Map;
52  java.util.PriorityQueue;
53  java.util.stream.Collectors;
54
55
56  {
57      start      The starting node of the search.
58      * goal      The goal node to find.
59      * planetSize The size of the planet, which may influence the maximum
60      *              search bounds.
61      * memorySize The maximum size of the frontier, limiting the number
of
62      *              nodes stored in memory at one time.
63      * A list of nodes representing the path from the start to the goal
if
64      *              found; null if no path exists.
65      */</span>
66      List<Node> planetSize, memorySize)</span> {
67          PriorityQueue<Node> frontier = <>(
68              Comparator.comparingDouble(Node::getfCost)
69                  .thenComparingInt(Node::getD)
70                  .thenComparingInt(Node::getAngle));
71          Map<Node, Node> parentMap = <>();
72          Map<Node, Double> costSoFar = <>();
73          ;
74
75          frontier.add(start);
76          parentMap.put(start, );
77          costSoFar.put(start, );
78

```

```

79         (!frontier.isEmpty()) {
80             visitedCount++;
81             printFrontier(frontier);
82             frontier.poll();
83
84             (current.getfCost() >= || current.getDepth() >= memorySize)
{
85                 ;
86             }
87
88             (current.equals(goal)) {
89                 List<Node> path = constructPath(current, parentMap);
90                 Utility.printPath(path, visitedCount);
91                 path;
92             }
93
94             updateFrontier(frontier, current, goal, planetSize,
memorySize, parentMap);
95         }
96         Utility.algorithmFails(visitedCount);
97         ;
98     }
99
100     frontier    The priority queue used to store nodes during the search.
101     * current    The current node being expanded.
102     * goal        The goal node of the search.
103     * planetSize The size of the planet influencing node expansions.
104     * memorySize The maximum number of nodes allowed in the frontier.
105     * parentMap  A map linking each node to its parent, used to
reconstruct
106     *            paths.
107     */</span>
108     planetSize,
109     memorySize, Map<Node, Node> parentMap)</span> {
110         List<Node> successors = <>{
111             current.getForgotten().size() == ?
current.getSuccessors(planetSize, goal) : current.getForgotten());
112
113
114
115         List<Node> toAdd = <>();
116         (Node successor : successors) {
117             (!successor.equals(goal) && successor.getDepth() >=
memorySize) {
118                 successor.setfCost();
119             }
120             successor.setLeaf();
121             (successor.getParent() != ) {
122                 successor.getParent().setLeaf();
123             }
124             toAdd.add(successor);
125         }
126
127
128         frontier.addAll(toAdd);
129
130         (frontier.size() > memorySize) {
131             shrinkFrontier(frontier, parentMap, goal, memorySize);
132         }
133     }
134

```

```

135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164 frontier    The priority queue of nodes.
165 * parentMap A map of nodes to their parents, used to maintain the
166 *             search tree's structure.
167 * goal       The goal node, used for recalculating heuristic values
168 if
169 *             needed.
170 * memorySize The maximum size of the frontier allowed.
171 */</span>
172 memorySize)</span> {
173     (frontier.size() > memorySize) {
174         getWorstLeafNode(frontier);
175         (worstNode != ) {
176             frontier.remove(worstNode);
177             worstNode.setLeaf();
178             worstNode.getForgotten().add(worstNode.getParent());
179             worstNode.getParent();
180             (parent != ) {
181                 parent.getForgotten().add(worstNode);
182 parent.getForgotten().stream().mapToDouble(Node::getfCost).min().orElse();
183                 parent.setfCost(minFCost);
184                 (!
185 existsInFrontierWhereWorstParentInAncestors(worstNode, frontier)) {
186                     parent.setLeaf();
187                     frontier.add(parent);
188                 }
189             }
190         }
191     }
192 }

```

```

193 worstNode The node considered the worst based on its f-cost.
194 * frontier The current frontier.
195 * true if the worst parent is found among the ancestors of any node
196 in
197 * the frontier, false otherwise.
198 */</span>
199 {
200     (Node node : frontier) {
201         (ancestors(node).contains(worstNode.getParent())) {
202             ;
203         }
204     };
205 }
206
207 node The node whose ancestors are to be found.
208 * A list of nodes representing the ancestors of the given node.
209 */</span>
210 List<Node> {
211     List<Node> ancestors = <Node>();
212     (node.getParent() != ) {
213         ancestors.add(node.getParent());
214         node = node.getParent();
215     }
216     ancestors;
217 }
218
219 frontier The current frontier.
220 * The node with the highest f-cost that does not have any children
221 in
222 * the search tree.
223 */</span>
224 Node {
225     frontier.stream()
226         .filter(node -> node.getLeaf())
227         .max(Comparator.comparingDouble(Node::getfCost))
228         .orElse();
229 }
230
231 frontier The priority queue containing the nodes.
232 */</span>
233 {
234     Node[] frontierArray = frontier.toArray( []);
235     Arrays.sort(frontierArray,
236         Comparator.comparingDouble(Node::getfCost)
237             .thenComparingInt(Node::getAngle)
238             .thenComparingInt(Node::getD));
239     (frontierArray.length != ) {
240         Arrays.stream(frontierArray)
241             .map(node -> node.toString() + String.format(,
242 node.getfCost()))
243             .collect(Collectors.joining());
244         System.out.println( + result + );
245     }
246 }
247
248 goal The goal node where the path ends.
249 * parentMap A map of child nodes to their parent nodes as discovered
250 * during the search.
251 * A list of nodes representing the path from the goal to the start.
252 */</span>

```

```
251     List<Node> {
252         List<Node> path = <>();
253         goal;
254         (current != ) {
255             path.add(current);
256             current = current.getParent();
257         }
258         Collections.reverse(path);
259         path;
260     }
261 }
262
```