Simultaneous state and parameter estimation



- You have now learned how to use Kalman filters to perform state estimation and parameter estimation independently
 - □ How about both at the same time?
- There are two approaches to doing so: joint estimation and dual estimation
- These are discussed generically in this lesson, then more specifically in the remaining lessons this week

Dr. Gregory L. Plett | University of Colorado Colorado Springs

Battery State-of-Health (SOH) Estimation | A Kalman-filter approach to total capacity estimation

Generic joint estimation



In joint estimation, state and parameter vectors are combined, KF simultaneously estimates this augmented state vector

$$\begin{bmatrix} x_k \\ \theta_k \end{bmatrix} = \begin{bmatrix} f(x_{k-1}, u_{k-1}, \theta_{k-1}, w_{k-1}) \\ \theta_{k-1} + r_{k-1} \end{bmatrix}$$
$$y_k = h(x_k, u_k, \theta_k, v_k).$$

■ To simplify notation, let X_k be the augmented state, W_k be the augmented noise, and \mathcal{F} be the augmented state equations:

$$X_k = \mathcal{F}(X_{k-1}, u_{k-1}, W_{k-1})$$

$$y_k = h(X_k, u_k, v_k).$$

Evaluating generic joint estimation



- Advantage:
 - Quite straightforward to implement: with augmented model of system state dynamics and parameter dynamics defined, we simply apply a nonlinear KF method
- Disadvantages:
 - Large matrix operations due to the high dimensionality of the resulting augmented model
 - Potentially poor numeric conditioning due to the vastly different time scales of the states/parameters in augmented state vector

Generic dual estimation: state evolution



- In <u>dual estimation</u>, separate KFs are used for state and parameter estimation
- Computational complexity lower, matrices may be numerically better conditioned
- However, by decoupling state from parameters, any cross-correlations between changes are lost, leading to potentially poorer accuracy
- Model of state dynamics again explicitly includes parameters as vector θ_k

$$x_k = f(x_{k-1}, u_{k-1}, w_{k-1}, \theta_{k-1})$$

$$y_k = h(x_k, u_k, v_k, \theta_{k-1})$$

■ Non-time-varying numeric values required by the model may be embedded within $f(\cdot)$ and $h(\cdot)$, and are not included in θ_k

Dr. Gregory L. Plett

Iniversity of Colorado Colorado Springs

Battery State-of-Health (SOH) Estimation | A Kalman-filter approach to total capacity estimation

4 of 6

I.5.3: How to estimate states and parameters at the same time

Generic dual estimation: parameter evolution



Update KF,

 Also slightly revise model of parameter dynamics to include effect of state equation explicitly

$$\theta_k = \theta_{k-1} + r_{k-1}$$

$$d_k = h(f(x_{k-1}, u_{k-1}, \bar{w}_{k-1}, \theta_{k-1}), u_k, e_k, \theta_{k-1})$$

- The dual filters can be viewed by drawing a block diagram
 - □ The interactions will be made clearer later
- The process essentially comprises two KFs running in parallel—one adapting state and one adapting parameters—with some information exchange

Iniversity of Colorado Colorado Spring

Battery State-of-Health (SOH) Estimation | A Kalman-filter approach to total capacity estimation

5 of

4.5.3: How to estimate states and parameters at the same time

Summary



- Two approaches to adapting a model's states and parameters at same time
- Joint estimation augments both in large state vector, uses single standard nonlinear KF with this augmented system
- Dual estimation uses separate nonlinear KFs for state and parameter estimation
- Joint estimation easier conceptually but can be slower due to large matrix operations and possibly poorer matrix conditioning
- Dual estimation generally faster, but ignores any correlation between state and parameter estimation in its updates