



Explosion-Proof Mining Rail Robot — KRXG32C

SevnceRobotics

Product Overview

Purpose-built for coal-mine underground environments, the KRXG32C uses a composite explosion-proof structure engineered for gas and dust hazards, paired with flexible rail-following technology that adapts to curves and slopes throughout mine tunnels. Integrated multi-dimensional sensing, edge computing, and 5G transmission deliver real-time monitoring and fast data return, improving mine safety management and operating efficiency.

Features and Capabilities

Dimensions	≤ 1400 × 420 × 480 mm (L×W×H)	Min. Passable Width	600 mm (incl. rail)
Weight	≤ 120 kg (subject to actual product)	Min. Passable Height	600 mm (incl. rail)
Explosion-Proof Rating	Ex I Mb (mining gas group)	Climbing Ability	≤ 25°
Protection Rating	IP66	Operating Temperature	-20°C to +60°C
Drive Method	Single-Rail, Dual-Drive	Charging Time	≤ 3 h
Top Speed	≤ 2 m/s	Range	8 km (level track)
Braking Distance	≤ 0.5 m	Positioning Accuracy	≤ ±5 cm

Standard Features

Autonomous Obstacle Avoidance	Emergency Stop	Auto-Charging
Auxiliary Lighting	Audio-Visual Alarm	Edge Computing
Autonomous Inspection	Voice Intercom	Voice Broadcast
Live Monitoring	Video Surveillance	Self-Check

One-Key Return

Offline Patrol

Monitoring Backend

Fault Diagnosis