

FE8828 Programming Web Applications in Finance

- Session 2 -

Intermediate R Programming Shiny/2: R Web Framework Data Manipulation and EDA/I

Dr. Yang Ye yy@runchee.com

Sep 12, 2019

Lecture 4: Intermediate R Programming

Let's review some R basics and bring us to intermediate level of R programming. There are following topics:

- Vector/Matrix/String/Date/Time
- Data Frame
- List
- Load/Save
- Anonymous function ...



3 of 106

FE8828 Programming Web Applications in Finance - Session 2 - (1)

4 of 106

R: Vector

```
# Create a vector from number
v <- c(1, 3)
v[1] <- 3
v
## [1] 3 3
```

```
# repeat 100 for 10 times.
rep(100, 10)
## [1] 100 100 100 100 100 100 100 100 100 100
```

4 of 106

R: Matrix

```
# create matrix of 3x4
mat <- matrix(2, 3, 4)
mat
##      [,1] [,2] [,3] [,4]
## [1,]    2    2    2    2
## [2,]    2    2    2    2
## [3,]    2    2    2    2
# set first row to 4
mat[1, ] <- 4
# set element (2, 2) to 6
mat[2, 2] <- 6
```

Find element(s) in Vector

- `which()`
- `match()`
- `%in%`

```
data <- 10:1
match(c(1, 3), data)
## [1] 10  8
data[match(c(1, 3), data)]
## [1] 1 3
# Equivalently, ...
which(1 == data | 3 == data)
## [1]  8 10
data[which(1 == data | 3 == data)]
## [1] 3 1
```

Check whether element exists

- FALSE case when element doesn't exist

```
match(c(11, 31), 10:1)
## [1] NA NA
which(11 == 10:1 | 31 == 10:1)
## integer(0)
```

- any() and all()

```
if (all(c(1, 33) %in% 1:3)) {
  cat("Found all\n")
}

if (any(c(1, 33) %in% 1:3)) {
  cat("Found one/some.\n")
}
## Found one/some.
```

Random

```
# Normal distribution random number
rnorm(3, mean = 10, sd = 3)
## [1] 9.457757 12.104269 12.481584
```

```
# Uniform distribution random number
runif(3)
## [1] 0.4210065 0.4148565 0.5943060
```

```
# Sample
sample(1:10, 10, replace = FALSE)
## [1] 4 7 5 3 10 1 6 8 2 9
# To Be/Not to Be
sample(c(T, F), 10, replace = TRUE)
## [1] FALSE TRUE FALSE TRUE TRUE TRUE TRUE TRUE TRUE FALSE
# Throw a dice
sample(1:6, 10, replace = TRUE)
## [1] 6 3 6 3 4 3 6 5 4 4
```

Print

- There is `print()` but I use `cat(paste0(..., "\n"))` most.
- `"\n"` is appended to the end to create a line break.
- `paste0()/paste()` can use to create new strings from any data types.
- `paste0()` combines any thing without space. `paste()` uses space, by default.
- `paste0/paste` with `collapse` helps with vector to print them in one line.
- `paste0/paste` works with all types of data.

```
x <- c(Sys.Date(), Sys.Date(), Sys.Date())
cat(paste0("Current dates is ", x, "\n"))
## Current dates is 2019-09-01.
## Current dates is 2019-09-01.
## Current dates is 2019-09-01.
cat(paste0("Current dates is ", paste0(x, collapse = ", "), "\n"))
## Current dates is 2019-09-01, 2019-09-01, 2019-09-01.
```

9 of 106

FE8828 Programming Web Applications in Finance - Session 2 - (1)

10 of 106

String

```
# sub-string
# substr(x, start, stop)
substr("The fox jumps.", 6, 6 + 5 - 1)
## [1] "ox ju"
```

```
# paste0/paste to concatenate string/convert to string
new_string <- paste0("This is ", "cat")
new_string <- paste0("This is ", "cat", sep = "a")
new_string <- paste0(1:3, sep = "a")
```

```
# toupper/tolower
toupper("big")
## [1] "BIG"
tolower("LOWER")
## [1] "lower"
```

Find/Replace in String

```
# grepl: Find, returns T or F
grepl("A", "ABC", fixed = TRUE)
## [1] TRUE
grepl("D", "ABC", fixed = TRUE)
## [1] FALSE
```

```
# sub: replace for one time
# sub(pattern, replace, string,...)
# fixed = TRUE means use fixed string. Not regular expression
sub("D", "ABC", "DDD", fixed = TRUE)
## [1] "ABCDD"
# gsub: replace for all
gsub("D", "ABC", "DDD", fixed = TRUE)
## [1] "ABCABCABC"
```

Find/Replace String with Regular Expression (RE)

If you start to use *regular expression*, sub/grepl becomes super powerful. They are default with RE turned on with default value for `fixed = FALSE`.

```
# If we need to find `Start` appearing the beginning of the string
grepl("^Start", "Start with me")
## [1] TRUE
grepl("^Start", "me Start")
## [1] FALSE
```

```
# To find something in the end
sub("X$", "Z", "XYZ ends with X")
## [1] "XYZ ends with Z"
```

Match/Extraction with Regular Expression (RE)

Match with RE

```
sub("[^\\_]+\\_.*", "", "USDCNY_M1")
## [1] ""
```

- `[^_]`: Character not containing `_`. Because `_` is a special character, we quote it with two backslashes.
- `+`: One or more
- `.`: Any character
- `*`: none or more.

13 of 106

FE8828 Programming Web Applications in Finance - Session 2 - (1)

14 of 106

Match/Extraction with Regular Expression (RE)

Extraction with RE

```
# Rough cut
sub("([^\\_]+)\\_.*", "\\1", "USDCNY_M1")
## [1] "USDCNY"
```

```
# Nice cut
sub("([^\\_]+)\\_(.*)", "\\1 \\2", "USDCNY_M1")
## [1] "USDCNY M1"
```

```
# Wonderful cut
sub("([^\\_]+)\\_([[:alpha:]])([[:digit:]])", "\\1 \\2 \\3", "USDCNY_M1")
## [1] "USDCNY M 1"
```

Regular Expression's Cheatsheet is available at <https://www.rstudio.com/resources/cheatsheets/>

14 of 106

Date

```
# Create date
dt1 <- as.Date("2019-11-03")
dt1
## [1] "2019-11-03"
dt2 <- Sys.Date()
dt2
## [1] "2019-09-01"
```

```
library(lubridate)
```

```
# Date is such a central role in finance.
# More function about date can be found in package `lubridate`
# Create date with lubridate, a package which provides lots of date functions.
ymd(20190910)
## [1] "2019-09-10"
ymd("20190910")
## [1] "2019-09-10"
```

Date: format code

We can use codes for convert date from/to string.

- %Y/%y: four-digit year/two-digit year
- %m: month in number
- %b/%B: month in abbreviation/full, i.e. Jan/January.
- %d: day

```
format(Sys.Date(), format = "%Y/%m/%d")
## [1] "2019/09/01"
```

```
as.Date("2019-11-03", format = "%Y-%m-%d") # %m for number month
## [1] "2019-11-03"
as.Date("2019-Nov-03", format = "%Y-%b-%d") # %b for the 3-letter month
## [1] "2019-11-03"
as.Date("03Nov2019", format = "%d%b%Y")
## [1] "2019-11-03"
```


Other functions from lubridate

```
library(lubridate)
# Change a date
x <- as.Date("2019-10-10")
month(x) <- 1
x
## [1] "2019-01-10"
```

```
# Set to the end of the month
day(x) <- days_in_month(x)
```

17 of 106

FE8828 Programming Web Applications in Finance - Session 2 - (1)

18 of 106

Business days

Use package bizdays

```
# install.packages("bizdays")
library(bizdays)
```

```
# 'weekends' is a calendar of weekdays
bizdays("2019-10-01", "2019-10-31", "weekends")
## [1] 22

# add bizdays
add.bizdays("2019-10-01", 5, "weekends")
## [1] "2019-10-08"

# Generate all business days between two dates.
# You will find this useful for financial application.
bizseq("2019-10-01", "2019-10-31", cal = "weekends")
## [1] "2019-10-01" "2019-10-02" "2019-10-03" "2019-10-04" "2019-10-07"
## [6] "2019-10-08" "2019-10-09" "2019-10-10" "2019-10-11" "2019-10-14"
## [11] "2019-10-15" "2019-10-16" "2019-10-17" "2019-10-18" "2019-10-21"
## [16] "2019-10-22" "2019-10-23" "2019-10-24" "2019-10-25" "2019-10-28"
## [21] "2019-10-29" "2019-10-30" "2019-10-31"
# bizdays excludes starting day, so one day less than bizseq.
length(bizseq("2019-10-01", "2019-10-31", cal = "weekends"))
## [1] 23
```

18 of 106

Calendar

If not provided, `start.date` is by default the first holiday and `end.date` is the last holiday, so we provide them here.

```
# Create a holiday calendar for this mini term.  
create.calendar(name="MFE_Mini_2", holidays = c(as.Date("2019-10-28")),  
               start.date = as.Date("2019-09-10"), end.date =  
                 as.Date("2019-10-31"),  
               weekdays = c("saturday", "sunday"))  
  
bizdays("2019-10-01", "2019-10-31", cal = "weekends")  
## [1] 22  
# One day less  
bizdays("2019-10-01", "2019-10-31", cal = "MFE_Mini_2")  
## [1] 21
```

Time

Convert time to character/string

- %H: hour
- %M: minute
- %S: second

```
format(Sys.time(), format = "%H%M")
## [1] "1513"
format(Sys.time(), format = "%H:%M:%S")
## [1] "15:13:05"
format(Sys.time(), format = "%H:%M:%S")
## [1] "15:13:05"
library(lubridate)
ymd_hms("2011-12-31 12:59:59")
## [1] "2011-12-31 12:59:59 UTC"
```

21 of 106

FE8828 Programming Web Applications in Finance - Session 2 - (1)

22 of 106

Time

Change time, lubridate provides hour, minute

```
x <- Sys.time()
x
## [1] "2019-09-01 15:13:05 +08"
hour(x) <- 12
x
## [1] "2019-09-01 12:13:05 +08"
minute(x) <- 3
x
## [1] "2019-09-01 12:03:05 +08"
minute(x) <- 123 # what will happen?
x
## [1] "2019-09-01 14:03:05 +08"
```

22 of 106

List - Basic

```
# Create a list with list() function
# Nameless list
# list[_n_] => item by order
a <- list(3, 4)
a[[1]]
## [1] 3
a[[2]]
## [1] 4

# Named list, you can use $ and [ operators
# list[[]]: gives back a value
# list$name => list[["name"]]
a <- list(a = 3, b = 4)
a[[1]]
## [1] 3
a[[2]]
## [1] 4
a[["a"]]
## [1] 3
a$a
## [1] 3
```

23 of 106

List - Create

```
# When you want to use a number as key, use backtick
list_of_strikes <- list()
list_of_strikes$`65` <- 3
list_of_strikes$`60` <- 4

# if a name doesn't exist in the list
a$c
## NULL
# Use `is.null()` to check
if (is.null(a$c)) {
  cat("c doesn't exist in list a\n")
}
## c doesn't exist in list a
```

List - Create

```
ll <- list(elem = 1, c1 = "a", c2 = "b")

# access the list
ll[[1]]
ll$elem

# add new member to the list
ll$new_elem <- 3
# update member in the list
ll$c1 <- 3

# set c1 to NULL would delete c1 from the list
ll$c1 <- NULL

ll
## $elem
## [1] 1
##
## $c2
## [1] "b"
##
## $new_elem
## [1] 3
```

25 of 106

List - Usage I

```
# List can be used as map/dictionary.
# Map
basket <- sample(c("Apple", "Orange", "Pear"), 100, replace = TRUE)
fruit_count <- list()
for (b in basket) {
  if (is.null(fruit_count[[b]])) {
    fruit_count[[b]] <- 1
  } else {
    fruit_count[[b]] <- fruit_count[[b]] + 1
  }
}
fruit_count
## $Pear
## [1] 38
##
## $Apple
## [1] 36
##
## $Orange
## [1] 26
```

26 of 106

List - Usage 2

```
# Let's write a generic function to do this
add_to_map <- function(map, key, value) {
  if (is.null(map[[key]])) {
    map[[key]] <- value
  } else {
    map[[key]] <- map[[key]] + value
  }
  map
}

# You may copy function add_to_map to every file that you want to use this kind
  of dictionary
fruit_count <- add_to_map(fruit_count, "Pomelo", 12)
fruit_count
## $Pear
## [1] 38
##
## $Apple
## [1] 36
##
## $Orange
## [1] 26
##
## $Pomelo
## [1] 12
```

List - Usage 3

```
# Use case 1: Use list to pass data in or out.
# pass in
do_lots_of_work <- function(lst) {
  lst$a + lst$b
}
# pass out
ret_lots_of_work <- function() {
  return(list(a = a, b = b))
}

res <- ret_lots_of_work()
res$a
## $a
## [1] 3
##
## $b
## [1] 4
res$b
## [1] "Apple"

# Case 2: configuration
app_config <- list(MAX = 10, MIN = 10, DISPLAY_RESULT = TRUE)

do_lots_of_work <- function(app_config) {
  app_config$MAX
}
```

R: data frame

Common functions for data frame

```
View()
head()
tail()
str()
nrow()
ncol()
dim() # returns both nrow and ncol
colnames()/rownames()
```

31 of 106

FE8828 Programming Web Applications in Finance - Session 2 - (1)

32 of 106

R: data frame

The basic structure of a data frame:

- There is one observation per row and
- Each column represents a variable, a measure, feature, or characteristic of that observation.
- In summary, **2D table**

```
df <- data_frame(
  date = seq(as.Date("2019-01-01"), as.Date("2019-01-10"), by = "day"),
  stock = replicate(10, paste0(sample(LETTERS, 3, replace = TRUE), collapse =
    "")),
  quantity = round(runif(10) * 10000, 0))
## Warning: `data_frame()` is deprecated, use `tibble()`.
## This warning is displayed once per session.
# df["date"]: gives a data frame
# df[["date"]]: gives value
# df$date: same as df[["date"]]

# Get three rows
df[c(3, 6, 9), , drop = F]
```

32 of 106

Data frame extraction with drop =

```
# Get three columns
df[, 1, drop = FALSE]
# This would return a vector
df[, 1, drop = TRUE]

# Use column names
df[, c("date", "quantity"), drop = FALSE]
```

33 of 106

FE8828 Programming Web Applications in Finance - Session 2 - (1)

34 of 106

Functions

Input parameters

```
func1 <- function() { }

func2 <- function(input1, input2) { }

# Param input1 is default to 1
func3 <- function(input1 = 1, input2) { }

func4 <- function(input1, input_type = c("int", "char")) {
  # This would check whether input_type is set to one of the pre-set values.
  input_type = match.arg(input_type)
}

func5 <- function(in1, in2) {
  if (in1 < 0) {
    return(0)
  } else {
    return(in1 + in2)
  }
}
```

34 of 106

Functions

```
# The last value before function finishes will be returned automatically. No
# need to use return.
func5 <- function(in1, in2) {
  if (in1 < 0) {
    0
  } else {
    in1 + in2
  }
}

# Unless there is extra steps before
func6 <- function(in1, in2) {
  if (in1 < 0) {
    return(0) # if we have 0 here, it's not the last step before function exits.
  } else {
    res <- in1 + in2
  }

  res <- res * 3
  res
}
```

Exercise

Write functions to do

- Determine leap year?
- Print the list of month names in abbreviation or full
- Write a function to count how many working days in a year, given 1) the year 2) list of holidays?

Anonymous Function

```
# Function that's defined in-place, which doesn't need to have a name.
(function(x) { print(x) }) (3)
## [1] 3
# if there is only one line, you can skip { }
(function(x) print(x)) (3)
## [1] 3

# For longer functions, you can make it multi-lines.
(function(x) {
  if (x > 3) {
    print(x)
  } else {
    print(x - 3)
  }
}) (3)
## [1] 0
```

37 of 106

purrr::map and sapply() Function

```
library(purrr) # install.packages("purrr")

# These two are equivalent.
res1 <- purrr::map(1:10, function(x) { rnorm(x, n = 10) })
# function(x) func(x) can be simplified as func.
res2 <- purrr::map(1:10, rnorm, n = 10)
head(res1, n = 1)
## [[1]]
## [1] 0.3572592 2.0830855 0.1349641 0.7002837 0.4030648 1.8801055 0.5504936
## [8] 0.3071205 0.5539132 2.4709504
# purrr::map returns a list()
```

```
# This is what we really want to do. Generate ten normal distribution and get
their mean.
# rnorm(n, mean = 0, sd = 1). Where does the input go to?
res <- purrr::map(1:10, rnorm, n = 1000)
map_dbl(res, mean)
## [1] 0.9320273 1.9948344 3.0312639 4.0065534 5.0389796 6.0183644 6.9727675
## [8] 7.9720216 9.0063688 9.9685941

# sapply achieves the same as purrr::map, a bit slower.
# Package purrr succeeds original R base.
sapply(1:10, function(x) x ^ 2)
## [1] 1 4 9 16 25 36 49 64 81 100
sapply(1:10, function(x) x ^ (x, 2))
## [1] 1 4 9 16 25 36 49 64 81 100
sapply(1:10, function(x) x ^ (2, x))
```

38 of 106

##	[1]	2	4	8	16	32	64	128	256	512	1024
----	-----	---	---	---	----	----	----	-----	-----	-----	------

Object

S3 Object System in R

```
# Object
# Define class with attributes.
vanilla_option <- setClass("vanilla_option",
                           slots = c(type = "character",
                                     strike = "numeric",
                                     underlying = "numeric"))

# Create object, either way
opt1 <- new("vanilla_option", type = "c", strike = 100, underlying = 100)
opt2 <- vanilla_option(type = "c", strike = 100, underlying = 100)

# Use @ to visit member. or,
opt1@type
## [1] "c"
slot(opt1, "strike")
## [1] 100
```

Work with objects

```
# Generate a vector of options
opts <- sapply(1:10000, function(x) {
  vanilla_option(type = sample(c("c", "p"), 1),
    strike = round(runif(1) * 100, 0),
    underlying = round(runif(1) * 100, 0))
})

# install.packages("fOptions")
library(fOptions)

start <- Sys.time()
# GBSOption also returns an object. We just need its price attribute.
res1 <- sapply(opts, function(o) {
  obj <- GBSOption(o@type, o@underlying, o@strike, Time = 1,
    r = 0.01, b = 0, sigma = 0.3)
  obj@price
})
cat(as.numeric(Sys.time() - start))
## 2.060005
head(res1, n = 4)
## [1] 0.000000 10.575406 36.659607 8.661286

# Alternatively to sapply, we can use map* functions from purrr package
# map is a generic function that returns a list
# map_dbl is for result of double, it would return a vector
library(purrr)
```

41 of 106

FE8828 Programming Web Applications in Finance - Session 2 - (1)

42 of 106

```
res2 <- purrr::map_dbl(opts, function(o) {
  (GBSOption(o@type, o@underlying, o@strike, Time = 1,
    r = 0.01, b = 0, sigma = 0.3))@price
})
head(res2, n = 4)
## [1] 0.000000 10.575406 36.659607 8.661286
```

Read/Write data

```
# set working directory
setwd("C:/TEMP")
# Save this_is_var1 to a file
saveRDS(this_is_var1, file = "C:/TEMP/DATA/data.Rds")
# Load a variable from a file. `new_loaded` is the name given to it.
new_loaded <- readRDS(file = "C:/TEMP/DATA/data.Rds")
```

- On Windows, use double slashes `\\` or single backslash `/`. e.g. `C:\\TEMP\\DATA`,
`C:/TEMP/DATA`
- On Mac, use backslash `/Users/.../`


43 of 106

FE8828 Programming Web Applications in Finance - Session 2 - (1)

44 of 106

Exercise I: Fastest Fish Problem


We have ten fishes releases in a very long lane at fixed time interval. They swim at different speed. The fish surpassing the previous fish would eat it. How many fishes would survive on average?



44 of 106

Histogram of Fishes Alive

```
## res_sim: 2.9333
## res_ana: 2.92896825396825
```



45 of 106

FE8828 Programming Web Applications in Finance - Session 2 - (1)

46 of 106

Exercise 2: How far to make a choice?

- Secretary Problem (https://en.wikipedia.org/wiki/Secretary_problem)
- If we have 100 secretaries ranked from best to worst, coming to interview at random order, what's the probability that our picked is the best in the group?
- Our selection strategy, use a small group to establish our selection criteria, for the subsequent ones, we pick the first that's better than our selection criteria. What's the split?

Step 1: `make_choice <- function(N, split_number)`

1. Generate a list `input_list` of `N` long with integer 1 to `N` at random position
2. Split the list `input_list` into two: evaluation group and selection group.
3. Remember the best number from evaluation group and match the first number in selection group, `>=` than best. Return it.

Run this function for a few (hundred) times and find the probability of getting `N`.

Step 2: `find_optimal()`, calls Step 1 a few (hundred) times for each of the split number from 1 to `N/2`. So we can find the optimal value for the split for the `N`.

46 of 106

Hint: Find the solution for $N = 3$, and $N = 10$, then move on to $N = 100$.

Lecture 5: Shiny/2: R Web Framework

Minimalist

```
library(shiny)
ui <- fluidPage("Hello World")
server <- function(input, output, session) { }
shinyApp(ui = ui, server = server)
```

Think around Input and Outputs

```
ui <- fluidPage(
  titlePanel("Hello World with a Histogram"),
  # Input() functions
  numericInput("num", "Number of Sample", value = 30),
  # Output() functions
  plotOutput("hist")
)
```

Input

All input functions follow such function signature except for input-specific parameters.

```
inputXXX(inputId = "input name", label = "label to display", ...)
```

- numericInput
- textInput
- passwordInput
- slideInput
- selectInput
- dateInput

Reference: <https://shiny.rstudio.com/reference/shiny/1.1.0/>

Output

All output functions follow such pattern.

```
yyyOutput(outputId = "output name")
```

- textOutput("text")
- verbatimTextOutput("text_orignal")
- tableOutput("t1")
- dataTableOutput("t2")
- plotOutput(outputId = "hist", width = "400px", height = "400px")
- uiOutput("uiX")

For plotOutput, I suggest to set width and height to fixed size so we need extra parameters.
For other kinds of outputs, only outputId is good enough.

Server

Sever is to fill the content of output

```
server <- function(input, output, session) {
  # Enable either one of two
  output$hist <- renderPlot({ hist(rnorm(100)) })

  if (FALSE) {
    output$hist <- renderPlot({
      title("a normal random number histogram")
      hist(rnorm(input$num))
    })
  }
}
```

shinyApp = UI + Server

- UI and Server combine to be a ShinyApp.
- UI is to run the same for each browser/client.
- Server is separate between different users.

```
shinyApp(ui, server)
```

Reactivity Kicks In

- **Reactivity:** `input$num -----> output$p1`
- Reactivity links input to the output like a data flow.

Reactive values work together with reactive functions.

1. Reactive function responds. `input$x => output$y`
2. Reactive value notifies. `input$x => expression() => output$y`

55 of 106

FE8828 Programming Web Applications in Finance - Session 2 - (1)

56 of 106

Reactivity - I

Reactivity is enabled by placing input `inputXXX` inside `renderXXX` function. (shiny-21.R)

```
library(shiny)

ui <- fluidPage(
  numericInput("num", "Num", 100),
  # numericInput("mean", "Mean", 5),
  # numericInput("sd", "SD", 3),
  numericInput("lambda", "Lambda", 1),
  plotOutput("p1")
)

server <- function(input, output, session) {
  output$p1 <- renderPlot({
    # hist(rnorm(input$num, mean = input$mean, sd = input$sd))
    hist(rpois(n = input$num, lambda = input$lambda))
  })
}

shinyApp(ui, server)
```

56 of 106

Reactivity - 2

- Button represents a manual trigger of the action.
- We use `observeEvent` to observe button action, and `isolate` to cut down the link of `inputXXX` in `renderXXX`, so button can work.
- If we remove `isolate`? (shiny-22.R)

```
library(shiny)

ui <- fluidPage(
  numericInput("num", "Num", 10),
  actionButton("go", "Go"),
  plotOutput("p1")
)

server <- function(input, output, session) {
  observeEvent(input$go, {
    output$p1 <- renderPlot({
      # hist(rnorm(isolate(input$num)))
      # To make code in good clarity, I re-write above one line into below two lines
      # with additional variable input_num to hold the value from input$num.
      input_num <- isolate(input$num)
      hist(rnorm(input_num))
    })
  })
}

shinyApp(ui, server)
```

57 of 106

Reactivity - 3

We can add a reactiveValue with `eventReactive`. (shiny-23.R)

```
library(shiny)

ui <- fluidPage(
  numericInput("num", "Num", 10),
  actionButton("go", "Go"),
  plotOutput("p1")
)

server <- function(input, output, session) {
  data <- eventReactive(input$go, {
    hist(rnorm(input$num))
  })
  # Variable data becomes a reactive variable.
  # What changes to it will trigger the output.
  output$p1 <- renderPlot({ data() })
}

shinyApp(ui, server)
```

Output

For tableOutput

```
output$t1 <- renderTable(iris)

output$t1 <- renderTable({
  some input..
  output is a data frame.
})
```

For dataTableOutput (Dynamic table)

```
output$t2 <- renderDataTable(iris)
```

For plotOutput

```
output$p2 <- renderPlot({ plot(runif(1000), runif(1000)) })
```

For textOutput and verbatimTextOutput

```
output$t3 <- renderText({ "foo" })
output$t4 <- renderPrint({
  print("foo")
  print("bar")
})
```

Example: (Shiny-24.R)

```
library(shiny)
library(DT)

ui <- fluidPage(
  h3("t1"),
  tableOutput("t1"),
  hr(),
  fluidRow(
    column(9, h3("dt1"),
      dataTableOutput("dt1")),
    column(3, h3("x4"),
      verbatimTextOutput("x4"))),
  hr(),
  fluidRow(
    column(8, h3("dt2"),
      dataTableOutput("dt2")),
    column(4, h3("p5"),
      plotOutput("p5")))
)

options(error = function() traceback(2))

server <- function(input, output, session) {
  output$t1 <- renderTable(iris[1:10,], striped = TRUE, hover = TRUE)
  output$dt1 <- renderDataTable(iris, options = list( pageLength = 5))
  output$x4 <- renderPrint({
    s = input$dt1_rows_selected
    if (length(s)) {
      cat('These rows were selected:\n\n')
      cat(s, sep = ', ')
    }
  })

  output$dt2 <- renderDataTable(iris,
                                options = list(pageLength = 5),
                                server = FALSE)

  output$p5 <- renderPlot({
```

61 of 106

```
    s <- input$dt2_rows_selected
    plot(iris$Sepal.Length, iris$Sepal.Width)
    if (length(s)) {
      points(iris[s, c("Sepal.Length", "Sepal.Width"), drop = F],
             pch = 19, cex = 1, col = "red")
    }
  })
}

shinyApp(ui, server)
```

Debug Shiny

- Debug in R Studio
- Clear all variable to run Shiny in R Studio
- `debugSource`, if you use other source code

Shiny Summary

- Reactive is about wiring input and output
- Connect from receiver: `plot/tabulate` for data
- Connect from trigger: button, isolate to create a Chinese wall

Shiny Assignment

- I. For Shiny-24.R, add a selectInput for different color names, returned from `colors()`.

```
plot(1:10, pch = 19, cex = 1, col = "skyblue1")
```

2. Create a Bond Schedule

- Inputs: start date, tenor, coupon rate, coupon frequency, and yield to maturity.
- Output: coupon schedule (ignore public holidays), amount in table and plot. NPV

$$NPV = \frac{Cashflow_1}{(1+yield)^1} + \frac{Cashflow_2}{(1+yield)^2} + \dots + \frac{LastCashflow}{(1+yield)^n}$$


For a Bond with fixed coupon

$$BondPrice = Coupon * \frac{1 - (\frac{1}{(1+yield)^n})}{yield} + \left[MaturityValue * \frac{1}{(1+yield)^n} \right]$$

Lecture 6: Data Manipulation and EDA (Exploratory Data Analysis)/I

Tidyverse

`install.packages("tidyverse")`



SQL

- It was invented by Edgar Codd
- It first appeared in 1974, which is 45 years ago.

Edgar F. Codd

From Wikipedia, the free encyclopedia

Edgar Frank "Ted" Codd (19 August 1923 – 19 April 2003) was an English computer scientist who, while working for IBM, invented the **relational model** for database management, the theoretical basis for relational databases and relational database management systems. He made other valuable contributions to computer science, but the relational model, a very influential general theory of data management, remains his most mentioned, analyzed and celebrated achievement.^[607]

Contents [hide]

- Biography
- Work
- Publications
- See also
- References
- Further reading
- External links

Biography [edit]

Edgar Frank Codd was born in Fortuneswell, on the Isle of Portland in Dorset, England. After attending Poole Grammar School, he studied mathematics and chemistry at Exeter College, Oxford, before serving as a pilot in the RAF Coastal Command during the Second World War, flying Sunderlands.^[6] In 1948, he moved to New York to work for IBM as a mathematical programmer. In 1953, angered by Senator Joseph McCarthy, Codd moved to Ottawa, Ontario, Canada. In 1957 he returned to the US working for IBM and from 1961–1965 pursuing his doctorate in computer science at the

Edgar "Ted" Codd



Born Edgar Frank Codd
19 August 1923^[602]
Fortuneswell, Dorset, England

Died 19 April 2003 (aged 79)
Williams Island, Aventura, Florida, USA

Alma mater Exeter College, Oxford
University of Michigan

Known for OLAP
Relational model^[6]
Codd's cellular automaton
Codd's 12 rules

CRUD: Create | Read | Update | Delete

Data engineering was born around 70s with SQL.



SQL does CRUD

```
# Select everything from Shops.
SELECT * FROM Shops;

# Select with a filter
SELECT * FROM Shops WHERE size = "Big";

# Select with a filter and order
SELECT * FROM Shops WHERE size = "Big" ORDER BY Name;

# Select with a filter, order, group and summary function `sum`
SELECT Region, sum(Sales) FROM Shops WHERE size = "Medium" GROUP BY Region;

# Insert a new record to Shops.
INSERT into Shops (Name, Region, Sales) VALUES ("Costco", "North", 123456, ...);

# Update a field
UPDATE Shops SET Sales = Sales + 1000 WHERE Name = "Costco";

# Delete from Shops with a filter
DELETE from Shops WHERE Sales < 1000
```

Data frame does CRUD

```
df <- data.frame(a = 1:10, b = 10:1)
# Select (aka Filter)
df[which(df$a == 3 | df$b == 3), , drop = T]
df[match(3, df$a), , drop = T]
df[, match("b", colnames(df)), drop = T]

# Insert
rbind(df, df)

# Delete
df[-(which(df$a == 3 | df$b == 3)), , drop = T]

# Update
df[which(df$a == 3 | df$b == 3), 2] <- 3
```

71 of 106

FE8828 Programming Web Applications in Finance - Session 2 - (1)

72 of 106

dplyr

dplyr package from tidyverse is a high-performance package to manipulate data in data frame.

```
# tidyverse is a bundle of packages.
# I usually load them all with library(tidyverse, instead of library(dplyr)
# individually.
library(tidyverse)
# -- Attaching packages ----- tidyverse 1.2.1
--
# v ggplot2 3.2.1      v purrr   0.3.2
# v tibble  2.1.3      v dplyr  0.8.3
# v tidyr   0.8.3      v stringr 1.4.0
# v readr   1.3.1      v forcats 0.4.0
# -- Conflicts ----- tidyverse_conflicts()
--
# x dplyr::filter() masks stats::filter()
# x dplyr::lag()    masks stats::lag()
```

Use `dplyr::lag` and `dplyr::filter` when it doesn't work.

72 of 106

How dplyr works

`dplyr` provides functions in “verbs”, which is functions that does one thing only. We will learn to use the following.

■ Key

- *select*: return a subset of the columns of a data frame
- *filter*: extract a subset of rows based on logical conditions
- *arrange*: reorder rows
- *rename*: rename variables
- *mutate*: add new variables/columns or transform existing variables

■ Group

- *group_by* / *rowwise* / *ungroup*: stratify the data
- *summarise* / *summarize*: generate summary statistics of different variables in the data frame, possibly within strata
- *do*: process data within the strata

■ Combine

- *left_join* / *right_join* / *anti_join* / *full_join*
- *bind_rows* / *bind_cols*

73 of 106

■ Helpers

- *%>%*: the “pipe” operator is used to connect multiple verb actions together into a pipeline
- *ifelse* / *case_when*
- *lag/distinct*
- *n*


Sample dataset

A data-driven approach to predict the success of telemarketing

Author: Sérgio Moroa; Paulo Cortezb; Paulo Ritaa

<http://dx.doi.org/10.1016/j.dss.2014.03.001>

I chose this data set of a Portuguese retail bank clients profile. - Real data collected from a Portuguese retailbank, from May 2008 to June 2013, in a total of 52,944 phone contacts.



Sample dataset columns

variable = column = field

Personal profile

- 1 - age (numeric)
- 2 - job : type of job (categorical: “admin.”, “unknown”, “unemployed”, “management”, “housemaid”, “entrepreneur”, “student”, “blue-collar”, “self-employed”, “retired”, “technician”, “services”)
- 3 - marital : marital status (categorical: “married”, “divorced”, “single”; note: “divorced” means divorced or widowed)
- 4 - education (categorical: “unknown”, “secondary”, “primary”, “tertiary”)
- 5 - default: has credit in default? (binary: “yes”, “no”)
- 6 - balance: average yearly balance, in euros (numeric)
- 7 - housing: has housing loan? (binary: “yes”, “no”)
- 8 - loan: has personal loan? (binary: “yes”, “no”)

Related with the last contact of the current campaign:

- 9 - contact: contact communication type (categorical: “unknown”, “telephone”, “cellular”)
- 10 - day: last contact day of the month (numeric)
- 11 - month: last contact month of year (categorical: “jan”, “feb”, “mar”, ..., “nov”, “dec”)
- 12 - duration: last contact duration, in seconds (numeric)

Other attributes:

- 13 - campaign: number of contacts performed during this campaign and for this client (numeric, includes last contact)
- 14 - pdays: number of days that passed by after the client was last contacted from a previous campaign (numeric, -1 means client was not previously contacted)
- 15 - previous: number of contacts performed before this campaign and for this client (numeric)
- 16 - poutcome: outcome of the previous marketing campaign (categorical: “unknown”, “other”, “failure”, “success”)

Output variable (desired target):

- 17 - y - has the client subscribed a term deposit? (binary: “yes”, “no”)

Read data

Use RStudio's File -> Import Dataset, you may choose either "From Text (base)" or "From Text (readr)". Either way loads the data.

`base` comes with R. `readr` is a package from tidyverse that provides more options and functionality. Copy the generated code to your script file.

I place it at <https://goo.gl/PBQnBt> (for direct use), <https://goo.gl/fFQAAM> (for Download).

You may download it and save it to local.

```
# Use base
bank <- read.csv("example/data-bank/bank.csv", sep=";") # or,
bank <- read.csv("https://goo.gl/PBQnBt", sep = ";")

# use readr
library(readr)
bank <- read_delim("example/data-bank/bank.csv",
                  ";", escape_double = FALSE, trim_ws = TRUE)

## Parsed with column specification:
## cols(
##   age = col_double(),
##   job = col_character(),
##   marital = col_character(),
##   education = col_character(),
##   default = col_character(),
##   balance = col_double(),
```

79 of 106

FE8828 Programming Web Applications in Finance - Session 2 - (1)

80 of 106

```
##   housing = col_character(),
##   loan = col_character(),
##   contact = col_character(),
##   day = col_double(),
##   month = col_character(),
##   duration = col_double(),
##   campaign = col_double(),
##   pdays = col_double(),
##   previous = col_double(),
##   poutcome = col_character(),
##   y = col_character()
## )
```

View (bank)

select

`select(df, ...)`, ... can be

- variable name
- numeric to indicate nth column (– means exclude)
- a range
- a function

81 of 106

FE8828 Programming Web Applications in Finance - Session 2 - (1)

82 of 106

select - Examples

```
subset <- select(bank, marital)
subset <- select(bank, 1)
subset <- select(bank, -1)
subset <- select(bank, -job)
subset <- select(bank, -(job:education))
subset <- select(bank, starts_with("p"))
subset <- select(bank, ends_with("p"))
subset <- select(bank, contains("p"))
```

82 of 106

select as a re-arrangement of columns.

```
job_first <- select(bank, job, everything())
```

83 of 106

FE8828 Programming Web Applications in Finance - Session 2 - (1)

84 of 106

filter


```
colnames(bank)
## [1] "age"      "job"      "marital"  "education" "default"
## [6] "balance"  "housing"  "loan"     "contact"   "day"
## [11] "month"    "duration" "campaign" "pdays"    "previous"
## [16] "poutcome" "y"

young <- dplyr::filter(bank, age < 40)
another_young <- dplyr::filter(bank, age < 20 & marital == "married")
just_young <- dplyr::filter(bank, age < 20 & marital == "single")

young2 <- dplyr::filter(bank, age >= 20 & age < 30)
another_young2 <- dplyr::filter(bank, age >= 20 & age < 30 & marital ==
                                "married")
just_young2 <- dplyr::filter(bank, age >= 20 & age < 30 & marital == "single")
```

84 of 106

filter - logic operators



85 of 106

FE8828 Programming Web Applications in Finance - Session 2 - (1)

86 of 106

filter - string operations

```
# %in% to match multiple
second_upper <- dplyr::filter(bank, education %in% c("tertiary", "secondary"))

# filter out NA value.
no_na <- dplyr::filter(bank, !is.na(balance) & balance > 0)
```

86 of 106

Exercise

- How many bank client have a loan while doesn't have a housing?
- How many bank client have a job between 20 to 40?

87 of 106

FE8828 Programming Web Applications in Finance - Session 2 - (1)

88 of 106

rename

```
# rename(new name = old)
# Use tick to quote special strings.
df <- rename(bank, young_age = age)
df <- rename(bank, `Age in Bank` = age)
```

88 of 106

arrange

```
# arrange is sort
arrange(bank, job)
arrange(bank, default, job)

# descending for day
arrange(bank, desc(day))
arrange(bank, desc(as.Date(day, format="%d", origin = Sys.Date())))
```

NB: Missing values are always sorted at the end.

89 of 106

FE8828 Programming Web Applications in Finance - Session 2 - (1)

90 of 106

Exercise

- How could you use `arrange()` to sort all missing values to the start? (Hint: use `is.na()`).

```
arrange(bank, !is.na(a), a)
```

- Find the longest duration?
- Find the eldest?

mutate

```
# Replace existing
# ifelse is to check condition.
df1 <- mutate(bank, y = ifelse(y == "yes", T, F))

# Add a new column.
df2 <- mutate(bank, duration_diff = duration - mean(duration, na.rm = TRUE))

# case_when is a function to deal multiple choices.
df2_age_group <- mutate(bank, age_group = case_when(
  age < 20 ~ "youth",
  age < 40 ~ "middle-age",
  age < 50 ~ "senior",
  TRUE ~ "happy"
))

df2_age_group_res <-
  group_by(df2_age_group, age_group) %>%
  summarise(mean_age = mean(age)) %>%
  transmute(mean_age_diff = mean_age - lag(mean_age))
```

91 of 106

mutate 2

```
firstup <- function(x) {
  substr(x, 1, 1) <- toupper(substr(x, 1, 1))
  x
}

# month.abb is a built-in array of month names.
df3 <- mutate(bank, month_name = factor(firstup(as.character(month)), levels =
  month.abb))

# transmute would remove all other columns after mutation, only keeping the new
  variable.
df5 <- transmute(bank,
  duration_trend = duration - mean(duration, na.rm = TRUE),
  balance_trend = balance - mean(balance, na.rm = TRUE))
```

What you can do with mutate

- $+$, $-$, $*$, $/$: ordinary arithmetic operator
- $\%/\%$ (integer division) and $\%\%$ (remainder), where $x == y * (x \%/\% y) + (x \% \% y)$
- $x / \text{sum}(x)$: compute the proportion of all things
- $y - \text{mean}(y)$: computes the difference from the mean.
- $\log2()$, $\log()$, $\log10()$:
- $\text{lead}()$, $\text{lag}()$: compute running differences (e.g. $x - \text{lag}(x)$) or find when values change ($x \neq \text{lag}(x)$)
- rolling sum, prod, min, max: $\text{cumsum}()$, $\text{cumprod}()$, $\text{cummin}()$, $\text{cummax}()$; and dplyr provides $\text{cummean}()$
- $\text{row_number}()$ / $\text{min_rank}()$ / $\text{ntile}(n)$

```
y <- c(1, 2, 2, NA, 3, 4)
row_number(y)
## [1] 1 2 3 NA 4 5
min_rank(y)
## [1] 1 2 2 NA 4 5
ntile(y, 2)
## [1] 1 1 1 NA 2 2
```

Summary

- We learned the key “verbs” from dplyr. Let’s pick up the rest next week.

95 of 106

FE8828 Programming Web Applications in Finance - Session 2 - (1)

96 of 106

Pipe: %>%

We may write such code.

```
df <- select(df, x)
df <- mutate(df, a = 1)
df <- rename(df, a = b)
df <- arrange(df, x)

# This is effectively,
arrange(rename(mutate(select(df, x), a = 1), a = b), x)

third(second(first(x)))
```

How about this?

```
df %>% select %>% mutate %>% rename %>% arrange
```

96 of 106

%>% Benefits

%>% operator allows you to transform the flow from nesting to left-to-right fashion, i.e.

```
first(x) %>% second() %>% third()

x %>% first() %>% second() %>% third() # this could also do.

x %>% first(.) %>% second(.) %>% third(.) # . represents the input
```

What's the output of below?

```
c(1, 3, 7, 9) %>% {
  print(.)
  mean(.)
} %>% { . * 3 } %>% {
  print(.)
  sample(round(., 0))
}
## [1] 1 3 7 9
## [1] 15
## [1] 15 3 6 4 7 8 1 13 5 12 11 2 14 10 9
```

Work with Pipe

%>% ... %>%

```
# Feed the data for multiple processing
{
  v <- .
  cn <- colnames(v)

  v <- select(v, u, z)
  colnames(v) <- cn[1:3]
  v
}

# How to return multiple value

%>% {
  assign("new_data", filter(., group == "1"), envir = parent.env(environment()))
  filter(., group == "2")
} %>% {
  select(., z < 0.4) # on group 2
  select(new_data, z > 0.4) # on group 1
}

# or, we use list
%>% {
  a <- filter(., group == "1")
  b <- filter(., group == "2")
}
```

```
list(a, b)
} %>% {
  v <- .
  v$a
  v$b
}
```

Code pattern with Pipe

```
df %>%
... %>%
... %>%
... %>%
{
  v <- .
  ggplot(data = v) +
    # full data is used here
    geom_line(data = v) +
    # partial data needs to be highlighted.
    geom_line(data = filter(., some condition), color = "red")
}
```

Use of Caution for Pipe (%>%)

Pros:

- We don't need to keep intermediate result, saves memory and also variable names.

Cons:

- Difficult to debug, to find something in the middle of the chain.
- Use `{ print(.); filter(., ...) }` to print intermediate results.
- Separate the long pipes into shorter pipes, adding more intermediate variables.
- Your pipes are longer than (say) ten steps. In that case, create intermediate objects with meaningful names. That will make debugging easier, because you can more easily check the intermediate results, and it makes it easier to understand your code, because the variable names can help communicate intent.
- You have multiple inputs or outputs. If two or more objects being combined together, don't use the pipe.
- Pipes are fundamentally linear and expressing complex relationships with them will typically yield confusing code.

Environment

Environment is where your data resides. Use `local()` to isolate.

```
# local stores the data wihtin the boundary of {}
x <- 3
local({
  print(x)
  x <- 1
  print(x)
})
## [1] 3
## [1] 1
print(x)
## [1] 3
```

```
# local stores the nearest environment
x <- 3
{
  print(x)
  x <- 1
  print(x)
}
## [1] 3
## [1] 1
x
## [1] 1
```

103 of 106

FE8828 Programming Web Applications in Finance - Session 2 - (1)

104 of 106

```
get_sum <- function(i) {
  v <- 0
  for (i in 1:10) {
    v <- v + i
  }
  v
}

get_sum(10)
## [1] 55

# object 'v' not found
v
## [1] 3 3
```

Environment

Use `assign()` to do space-jump.

```
# assign data to global environment
x <- 1
pass_out_global <- function() {
  assign("x", 3, envir = .GlobalEnv)
}

# assign data to just one level up
pass_out <- function(env) {
  print(env)
  assign("x", 2, envir = env)
}
```

```
x <- 1
pass_out(environment())
## <environment: R_GlobalEnv>
x
## [1] 2

# assign data to pass it out of function
extra_layer <- function(env) {
  pass_out(env)
}

x <- 1
extra_layer(env = environment())
```

105 of 106

FE8828 Programming Web Applications in Finance - Session 2 - (1)

106 of 106

```
## <environment: R_GlobalEnv>
x
## [1] 2

extra_layer_g <- function() {
  pass_out_global()
}

x <- 1
extra_layer_g()
x
## [1] 3
```