leanSeal: A Committee-Free Encrypted Mempool from Hashes Alone

Vitalik Buterin[1] Quang Dao[2] Justin Drake[1]

[1]Ethereum Foundation
vitalik@ethereum.org, justin.drake@ethereum.org
[2]Carnegie Mellon University
qvd@andrew.cmu.edu

October 2026

Abstract

We present leanSeal, a simple encrypted mempool construction that needs neither a committee nor a trusted setup, relying only on a hash function such as SHA-256. Encrypted mempools let block builders order transactions before reading them, which prevents front-running and sandwich attacks based on their contents. Existing designs either trust a committee to open the transactions afterwards, or let each sender open its own, in which case the sender can withhold its key when the ordering is unfavorable.

In leanSeal, the sender opens its own transaction but also attaches the chained-hash time-lock puzzle of Mahmoody, Moran and Vadhan (CRYPTO 2011), which anyone can solve to recover the key after a fixed amount of sequential computation. Withholding the key therefore cannot keep the transaction hidden, provided that it was sealed correctly.

For our exact encoding, we prove in the random-oracle model that parallel hashing does not shorten the puzzle: a classical attacker with about the hash rate of the whole Bitcoin network recovers the key of a 30-second puzzle early with probability at most about 2^{-117}. The time itself rests on one hardware estimate, the latency of one chained SHA-256, which we set at 3.5 ns for the fastest attacker. Such a puzzle takes about 21 s to build on a laptop, ahead of time, and adds 152 to 512 bytes to a transaction.

leanSeal also combines with a threshold committee that releases keys for included transactions. If reading a transaction needs both the committee's key and the puzzle's, transactions that are never included stay private while the committee is honest. If either key suffices, the committee opens transactions at once, so withholding a key can no longer delay or cancel execution. We also add a bond that charges a sender for a puzzle sealed incorrectly on purpose, and apply leanSeal to sealed-bid batch auctions.

Contents

1 Introduction **3**
- 1.1 Our results . . . 4

2 Sealing Transactions with leanSeal **5**
- 2.1 The flow . . . 5
- 2.2 The timing condition . . . 7
- 2.3 Choosing the delay . . . 7
- 2.4 A proof of concept . . . 7

3 The Puzzle **8**
- 3.1 Notation and model . . . 8
- 3.2 Building and opening . . . 9

4 Security **10**
- 4.1 Assumptions . . . 10
- 4.2 The delay theorem . . . 10
- 4.3 The hardware assumption . . . 12
- 4.4 Attacks and link width . . . 12

5 Implementation and Costs **13**
- 5.1 Measurements . . . 14
- 5.2 What a delay costs . . . 14
- 5.3 The number of chains . . . 14

6 Trade-offs and Mitigations **15**
- 6.1 Excluded transactions are also disclosed . . . 15
- 6.2 Withholding: disclosure is forced, execution is not . . . 16
- 6.3 A bond for malformed puzzles . . . 17
- 6.4 A complete application: sealed-bid batch auctions . . . 18
- 6.5 Other requirements . . . 18

7 Comparison with Other Encrypted-Mempool Designs **20**
- 7.1 The design space . . . 20
- 7.2 Composing leanSeal with a threshold committee . . . 22
- 7.3 Settings where leanSeal is practical . . . 22

8 Related Work and Open Questions **23**
- 8.1 Lower bounds for hash-only puzzles . . . 23
- 8.2 Related work . . . 23
- 8.3 Open questions . . . 24

Acknowledgments **24**

AI Assistance **24**

A Proof of the Delay Theorem **27**

B Proof of the Hiding Theorem **29**

C Estimating the Hardware Speed **30**

D The Bond and the Auction in Detail **32**
- D.1 The verification game and solver pay . . . 32
- D.2 The auction rules . . . 33

1 Introduction

In an encrypted mempool [PP26], block builders order transactions before they can read them, which removes their ability to front-run or sandwich a transaction based on its contents. The central question is who opens the transactions afterwards. Current designs give three answers, each at a cost.

- **A committee** holds a threshold decryption key and opens what was ordered, as in Shutter [Shu]. Privacy then rests on no threshold of its members colluding, and liveness on enough of them being online.
- **A trusted execution environment** opens transactions inside hardware whose vendor and side channels must be trusted.
- **The sender** opens its own transaction after the ordering, as in sealed transactions and the self-decryption path of LUCID [EFM26]. No other party is trusted, but the sender sees the ordering first and can withhold its key when the ordering is unfavorable, which gives it a free option.

Hybrid designs [WM25] let either the sender or a committee open, which removes the free option while the committee is online and the committee's liveness problem while the sender is honest. Their failure case remains a dishonest sender while the committee is offline.

We present leanSeal, a fallback for self-decryption that needs no committee: no designated party has to be online or trusted for a withheld transaction to be disclosed. The sender opens its own transaction in the normal case, but it attaches a time-lock puzzle that anyone can solve to recover the key after a fixed amount of sequential computation, about 30 seconds on Ethereum.

If the puzzle is well formed and the transaction is encrypted under its key, a sender that withholds its key can still delay or cancel the transaction's execution, but cannot keep the transaction hidden. Unlike a timed commitment [BN00], the puzzle carries no proof that it opens to the committed key; instead, a sender whose puzzle fails to open forfeits a bond. The puzzle uses only a hash function such as SHA-256: it needs no trusted setup and no hardware trust, and its idealized form provably keeps its delay against quantum attackers in the quantum random-oracle model [ACH+23].

The puzzle is the chained-hash puzzle of Mahmoody, Moran and Vadhan [MMV11], in which the sender computes as many hashes as an opener, but in parallel (Figure 1). They also proved that no puzzle built only from hashes can make the sender's work grow more slowly than the delay, so the cost of leanSeal falls on the sender. This paper examines whether that cost is acceptable for sealing transactions (Table 1), and what an encrypted mempool built on the puzzle can and cannot provide.

Table 1: The reference puzzle at a glance: a 30-second lock of $n = 16$ chains of 2^{29} SHA-256 steps with 24-byte links. Times are on an Apple M4 MacBook Air (Section 5); building and forced opening are half our measurements of the one-minute puzzle ($m = 2^{30}$, run with 32-byte links and the same chain work), since both are linear in the delay.

	Value	Basis
Earliest opening by an attacker	30 s	ASSUMED: 3.5 ns per chained hash
Opening when the sender reveals the key, the normal case	12.0 ms	MEASURED: command line, end to end
Forced opening without the sender, one laptop core	3 min 21 s	MEASURED, halved
Building the puzzle, before the transaction exists	21 s	MEASURED, halved: all CPU cores
Added to a transaction, on-demand or stockpiled puzzle	512 or 152 B	exact




Figure 1: The same n chains, arranged two ways in time (drawn for $n = 4$). The sender knows every link and runs the chains side by side. An opener must run them one after another, because each chain's starting link is hidden under the end of the previous chain. The puzzle consists of the n links, so its size grows with n and not with the delay.

1.1 Our results

1. **A design.** We describe how leanSeal serves as the decryption path of an encrypted mempool (Section 2). It uses the same data as LUCID and the hybrid design, a ciphertext bound to a commitment to its key, so its puzzle fits them as a fallback that needs no third party.

2. **A concrete security proof.** In the random-oracle model, a classical attacker derives the key even one oracle round early with probability at most about 2^{-117} for a 30-second lock against about the hash rate of the whole Bitcoin network (Section 4). A second theorem gives a corresponding hiding bound for sealed transactions against attackers whose other computation is bounded, with terms for repeated nonces and for HMAC-SHA256 as a pseudorandom function. Turning rounds into seconds needs one hardware parameter, the fastest time for one chained SHA-256, which we set at 3.5 ns, 3.7 times faster than the fastest published design that we know of. This parameter, not the bound, limits the reference puzzle: an attacker at 1.3 ns per step, 2.7 times faster than assumed, reads it in 11.2 s, before a 12-second ordering deadline.

3. **Practical costs.** A 30-second puzzle, enough when the order is fixed within a slot, takes about 21 s to build on a laptop CPU and can be built before the transaction exists (Section 2.3 chooses the delay per use case). A sender that keeps a stock can use single-chain puzzles, which add 152 bytes to a transaction (Section 5).

4. **An analysis of the trade-offs.** The puzzle guarantees eventual disclosure, not timely execution. Withholding can still delay or cancel execution, so a deposit forfeited on a missed reveal, which the reveal deadline makes observable, must deter it. No efficient check of puzzles is known, and a malformed puzzle is cheaper than a well-formed one, so a strategic sender keeps its option unless malformation is penalized. We add a bond, forfeited when a forced opening is shown on chain to fail, if necessary by a bisection game (Section 6.3). A time lock also reveals transactions that are never included; we argue that this holds for every design whose fallback opening is input-free, and show how validity windows, private submission and a committee limit it (Section 6). We compare leanSeal with threshold, TEE, hybrid and delay-encryption designs (Section 7).

5. **A complete application.** In a sealed-bid batch auction, settlement can wait for forced openings. We specify one, with admission limits, deposits, bonds, paid solvers, deadlines and a clearing rule, and compare it with commit–reveal under the same rules. A valid, escrowed bid with a well-formed puzzle remains binding after a missed reveal, and withholding a malformed




Figure 2: Commit–reveal with a time-lock fallback. When senders reveal their keys, no puzzle is solved. For a well-formed puzzle, withholding the key cannot prevent disclosure, but it can still delay or cancel execution.

bid costs the bond as well as the deposit, while an offline bidder forfeits only the deposit; commit–reveal can charge the larger penalty only to every bidder that misses a reveal. The cost is bytes, the bidder's work and settlement delay after a missed reveal (Section 6.4).

6. **An implementation**: a specified format with a Rust implementation, a second implementation in Python, test vectors and benchmarks, and a prototype encrypted mempool on an EVM chain (Section 2.4) [lea26]. In the prototype, a sandwich attack costs a plaintext swap 9.25%, while the same swap, sealed, executes at the fair price. This comes from the pool, which refuses direct trades from the swap's submission until its batch executes, and would hold equally under commit–reveal without puzzles. Separately, a withheld key is forced open from an honestly built puzzle.

Neither the chained-hash puzzle nor the use of timed commitments against front-running is new (Section 8). We are not aware of a prior design that uses a hash-only time-lock puzzle, bound to a key commitment, as the fallback for self-decryption, without a committee. Beyond the design, our contributions are a concrete bound for an exact encoding, measured costs against an explicit attacker, an analysis of what such a fallback can and cannot provide in an encrypted mempool, and an application compared with commit–reveal under the same rules.

2 Sealing Transactions with leanSeal

This section treats the puzzle as a black box and describes how it supports an encrypted mempool. The sender runs Build to obtain a puzzle Z, which contains a commitment C, and a key K. Anyone can check a claimed key against C with one hash. Anyone can also recover K from Z, without the sender, with N sequential hashes, which takes at least $T = N\ell$ seconds on the fastest hardware. Sections 3 and 4 construct the puzzle and prove this. Table 2 lists the properties an encrypted mempool may want and what leanSeal provides; no known design provides all of them, and Section 7 compares the alternatives.

2.1 The flow

leanSeal is used like a timed commitment [BN00], but without its proof that a forced opening recovers the committed key; Figure 2 shows the flow.

1. **Submit.** The sender takes a puzzle from its stock and encrypts its signed transaction under K. It sends the sealed transaction together with a plaintext envelope: the account that pays, a nonce, a gas limit, a fee and a deposit (Section 6.5).

Table 2: Properties of an encrypted mempool, and what leanSeal provides.

Property	**leanSeal**
Contents hidden until the order is fixed	yes, for T after exposure, under the hardware assumption
Every included transaction opens	yes, without the sender or anyone else, if the puzzle is well formed; this is not checked, but a failed opening can forfeit a bond (Section 6.3)
No free cancellation after seeing the order	no: withholding still delays or, with expiry, cancels execution; a deposit must deter it (Section 6.2)
Excluded transactions stay private	no: they open after T like any other (Section 6.1)
Sender, fee and size hidden	no; the envelope is public and the size can be padded
Trusted parties or setup	none
Post-quantum	plausibly; proved for the idealized puzzle only (Section 4.4)
Cost	152 to 512 bytes per transaction, sender work proportional to T paid in advance, no puzzle solving in the normal case (Section 5)

2. **Order.** The builder orders sealed transactions without reading them. The ordering commits to the hash of each whole sealed transaction, not only to C: once K is known, anyone could seal a different transaction under the same puzzle.
3. **Reveal.** Once the ordering is fixed, the sender publishes K. Nodes check it against C, decrypt in milliseconds and execute the transaction in its committed position. No puzzle is solved.
4. **Fallback.** If the sender has not revealed K by the reveal deadline, its deposit is forfeited, and anyone can solve the puzzle and publish K. We call a puzzle *well formed* if its chains lead to the key committed in C and its transaction is encrypted under that key. A well-formed puzzle therefore opens without its sender, but its transaction can only run late or not at all. A protocol can also hold a bond that the sender forfeits if the forced opening fails (Section 6.3).

A ciphertext bound to a commitment to its key is the structure that recent Ethereum designs already use. In LUCID (EIP-8184) [EFM26], a sealed transaction's ticket goes on chain and carries a commitment $\mathsf{keccak256}(k_{\text{dem}})$ to the key and a hash of the ciphertext envelope, which itself travels off chain. The key is released by a key publisher of the sender's choice, possibly the sender itself, and the publication fee is paid only when decryption succeeds. In the hybrid design of Wagner and Ma [WM25], the sender puts $\text{Enc}_k(tx)$ and $\mathsf{H}(k)$ on chain and gives a committee a threshold encryption of k, so that either the sender or the committee can open. leanSeal fits both as a fallback that needs no third party: the sender is its own key publisher, and the puzzle replaces the committee as the party that discloses the key when the sender does not.

Inside LUCID, only the puzzle is used. It travels in the envelope's opaque header with K as k_{dem}; its SHA-256 commitment C is separate from the ticket's keccak commitment, and the cipher stays ChaCha20-Poly1305. The puzzle provides eventual disclosure only: executing a transaction whose key is disclosed minutes late needs an additional protocol rule, which LUCID does not have.

The reveal should be due as soon as the ordering is fixed. In LUCID, the builder's bid commits to the tickets of slot n, keys are released once the beacon block carrying the bid is attested and must be seen before the payload-timeliness committee votes, and the decrypted transactions execute at the top of block $n + 1$, before any ordinary transaction. A short window shortens the delay the puzzle must provide and limits what a sender learns before deciding whether to reveal (Section 6.2).

2.2 The timing condition

The attacker's clock starts at *exposure*, t_{exp}, the first moment anyone but the sender holds the puzzle. The deadline t_{order} is the moment the transaction's position can no longer change. The contents stay hidden until the deadline if

$$t_{\text{order}} - t_{\text{exp}} < N \cdot \ell_{\text{attacker}},$$

with a margin for propagation. A forced opening finishes $N \cdot \ell_{\text{solver}}$ after a solver starts, which on a laptop core is minutes after the deadline.

If the attacker is k times faster than assumed, the delay shrinks k-fold. Once it falls below $t_{\text{order}} - t_{\text{exp}}$, the contents can be read before the order is fixed: privacy before ordering is lost, and content-dependent MEV becomes possible again for any party that can solve the puzzle in time.

2.3 Choosing the delay

The delay should be the smallest that covers the time from exposure to the fixed order, $t_{\text{order}} - t_{\text{exp}}$. Building, forced opening, the solvers' load and the window in which a withholding sender holds an option all grow linearly with T; only the size does not. The attacker speed already carries a margin of about 3.7 over the fastest published design (Section 4.3), so we take T about twice the time to fix the order, with a floor of 15 s and rounded up. Table 3 applies this to the settings of Section 7.3. We use $T = 30$ s as the reference: it covers a puzzle that is sent only to the slot's builder, or published after a commitment, and ordered within one 12-second slot.

The last row shows why leanSeal needs an order that is fixed early. Waiting for today's finality makes every cost sixty times larger than in the reference setting, so a protocol either accepts that a reorganization exposes revealed transactions (Section 6.5) or relies on fast finality, which brings the delay back to the reference range. Public gossip remains affordable for a wait of one or two slots but not longer, so the puzzle should not wait in a public mempool.

2.4 A proof of concept

We implemented this flow as an EVM contract, using EIP-7702 and transient storage, with off-chain sender, keeper and solver roles [lea26]. Each block's sealed transactions form a batch, and batches execute strictly in order from one queue. On submission, the contract checks each envelope's structure against the specification and caps the gas per transaction and per batch. The sender reveals its key within two blocks; anyone then executes the batch in order. The contract checks each key against its commitment, decrypts the envelope with SHA-256 only and calls the sender's account. Only accounts delegated to the contract's own account code may submit, and the delegation is checked again before the call, so the call that runs is the committed one. The queue advances past a transaction only if the executor supplied its full gas, and a failing or redelegated account cannot block it.

Two further rules make the committed order binding for a market. First, a guarded pool refuses direct trades from the submission of a sealed transaction until its batch has executed. A key is public as soon as its reveal is pending, before the reveal executes, so a lock that started at the reveal would let whoever reads the pending key trade ahead of it. While sealed transactions keep arriving, the pool therefore trades only through them. Second, sealed calls are restricted to the pool, so a sealed transaction ordered ahead of another has parameters fixed before any reveal. Otherwise it could read state that the attacker wrote after the reveals and adapt to the victim's plaintext. General programmable transactions need execution immediately after key release with nothing in between, which only a protocol such as LUCID provides.

A missed reveal burns most of the deposit: the solver who posts the key receives a smaller bounty, which the sender, who knows its key, could claim itself, so the net penalty is the deposit minus the bounty. The deposit prices only the missed reveal: a sender that reveals on time

Table 3: The delay per setting. Building uses all cores of the M4 Air (0.70 s per second of delay); forced opening uses one of its cores (6.7 times the delay).

Setting	Time to fix the order	Delay T	Building	Forced opening
Rollup with a sequencer	1–2 s	15 s	11 s	1.7 min
Ethereum with enshrined PBS; puzzle sent to the builder, or published after a commitment	up to one slot, 12 s	**30 s**	21 s	3.3 min
Sealed-bid auction with fast finality; bid sent to the builders of its slot	about one slot	30 s	21 s	3.3 min
Public gossip, waiting w slots	$12(w+1)$ s	$24(w+1)$ s	$17(w+1)$ s	$2.7(w+1)$ min
Order fixed only at finality, Ethereum today	about 13 min	30 min	21 min	3.3 h

and then revokes its approval or moves its funds makes its own trade fail without penalty, a cancellation that also only immediate execution removes. A forced opening publishes the key and pays the bounty, but the transaction does not run. Its key may already have been public: a builder that reads a pending reveal and keeps it out of the two blocks makes the ticket miss while holding the key, and could trade around the transaction if it ran later. Such a builder can still make an honest sender forfeit its deposit, so the window must exceed the number of consecutive blocks that one builder controls.

On a local chain with 2-second blocks, a searcher watching the mempool sandwiched a plaintext swap, which lost 9.25% against the fair price. The same swap, sealed, executed at the fair price: the searcher read the key from the pending reveal, decrypted the swap and placed a trade ahead of the reveal in the same block, and the pool rejected it. The puzzle plays no part in this result: no puzzle is solved on that path, and the same contract with plain commit–reveal would reject the trade as well. The second experiment shows that an honestly built puzzle opens without its sender. With its key withheld, a demonstration puzzle of 2^{29} steps, 1/16 of the reference work, was solved on one core in 13 s; the key was published, and the swap did not run. The prototype does not implement the bond of Section 6.3, so a sender that attaches a malformed puzzle loses only its deposit.

The keeper splits a batch into transactions within the gas cap of EIP-7825. In the contract's unit tests, with a 128-byte test puzzle and 256-byte swaps, submitting costs 194,000 to 270,000 gas, revealing about 74,500, executing a batch of two swaps about 357,000, and a forced opening about 67,000. These are contract-call costs; calldata and intrinsic costs come on top and grow with the envelope.

3 The Puzzle

A *hash chain* starts from a value and hashes it many times in a row. Each step needs the previous output, so even unlimited parallel hardware must compute the steps one after another. A single chain of N steps would serve as a lock, except that its builder also needs N sequential steps. The construction of Mahmoody, Moran and Vadhan [MMV11] avoids this: the sender builds n short chains of m steps at the same time and links them so that an opener can only run them in order. The opener's delay is $N = nm$ steps; the sender's wall time is m steps on n cores.

3.1 Notation and model

The notation follows the specification (`SPEC.md` in the repository [lea26]). Integers are encoded big-endian, $a \parallel b$ is concatenation, $[v]_b$ is the first b bytes of v, and $\oplus$ is bytewise XOR. A *labelled*

Algorithm 1 Build(n, m, b), run by the sender

1: $salt \leftarrow$ 16 random bytes; $x_1, \ldots, x_n \leftarrow b$ random bytes each
2: $ctx \leftarrow (1, b, n, m, salt)$
3: **for** $i = 1, \ldots, n$ **in parallel do**
4: $\quad s_i \leftarrow \mathsf{H}_{\mathsf{start}}(ctx, i, x_i)$
5: $\quad y_i \leftarrow F_i^m(s_i)$ ▷ *m sequential steps*
6: **for** $i = 1, \ldots, n-1$ **do**
7: $\quad z_i \leftarrow [\mathsf{H}_{\mathsf{mask}}(ctx, y_i)]_b \oplus x_{i+1}$ ▷ *hide the next link*
8: $a \leftarrow ctx$
9: **for** $i = 1, \ldots, n$ **do** $a \leftarrow \mathsf{H}_{\mathsf{acc}}(a, y_i)$
10: $K \leftarrow \mathsf{H}_{\mathsf{key}}(ctx, a)$; $C \leftarrow \mathsf{H}_{\mathsf{commit}}(ctx, K)$
11: **return** puzzle $Z = (ctx, C, x_1, z_1, \ldots, z_{n-1})$ and key K

Algorithm 2 Open(Z), run by anyone

1: parse Z as $(ctx, C, x_1, z_1, \ldots, z_{n-1})$
2: $x \leftarrow x_1$; $a \leftarrow ctx$
3: **for** $i = 1, \ldots, n$ **do** ▷ *in sequence*
4: $\quad y \leftarrow F_i^m(\mathsf{H}_{\mathsf{start}}(ctx, i, x))$ ▷ *m sequential steps*
5: $\quad a \leftarrow \mathsf{H}_{\mathsf{acc}}(a, y)$ ▷ *lines 5 and 6 share one oracle round*
6: $\quad$ **if** $i < n$ **then** $x \leftarrow [\mathsf{H}_{\mathsf{mask}}(ctx, y)]_b \oplus z_i$ ▷ *unhide x_{i+1}*
7: $K \leftarrow \mathsf{H}_{\mathsf{key}}(ctx, a)$
8: **if** $\mathsf{H}_{\mathsf{commit}}(ctx, K) \neq C$ **then return** $\perp$ ▷ *malformed puzzle*
9: **return** K

hash is $\mathsf{TH}(label, x) = \mathsf{SHA256}(\mathsf{u8}(|label|) \parallel label \parallel x)$, and we write $\mathsf{H}_{\mathsf{start}}, \mathsf{H}_{\mathsf{mask}}, \mathsf{H}_{\mathsf{acc}}, \mathsf{H}_{\mathsf{key}}, \mathsf{H}_{\mathsf{commit}}$ for labelled hashes with the labels `leanseal/v1/start`, `leanseal/v1/mask` and so on. The *chain step* for chain i is

$$F_i(s) = \mathsf{SHA256}\big(s \parallel salt \parallel \mathsf{be32}(i)\big),$$

where *salt* is 16 random bytes drawn for each puzzle. Its input is exactly 52 bytes, so one step is one SHA-256 compression, and no other hash in the format has an input of that length.

A puzzle has n chains of m steps and b-byte links; the specification bounds the parameters, in particular $m \leq 2^{48}$. The reference parameters are $n = 16$, $m = 2^{29}$ and $b = 24$: $N = 2^{33}$ steps, a 30-second delay at 3.5 ns per step, and a 452-byte puzzle. The measurements of Section 5 use the one-minute puzzle, with $m = 2^{30}$.

We prove the delay in the random-oracle model [MMV11]: each chain step and each labelled hash is an independent random function that anyone can query, and an attacker is charged only for its queries. Time after publication is counted in *oracle rounds*: all queries in a round are chosen before any answer from that round arrives. A bound in rounds therefore holds however much parallel hardware the attacker has; turning rounds into seconds takes the hardware assumption of Section 4.

3.2 Building and opening

Algorithms 1 and 2 give the two algorithms, following Sections 4 and 5 of the specification with the byte encodings left out. The context ctx is a 32-byte encoding of the version, b, n, m and the salt. Start hashes include the context and the chain index, and chain steps the salt and the index. Mask, key and commitment hashes include the context; the accumulator begins at the context and absorbs the chain ends in order.

The sender knows every link, so it runs the n chains of Algorithm 1 in parallel. Each link after the first is published only masked, under a hash of the end of the chain before it. The key is a hash of all chain ends in order, and the commitment C lets anyone check a claimed key with one hash. An opener without the key has only x_1: it runs chain 1, uses its end to unhide x_2, runs chain 2, and so on, nm steps in sequence (Figure 1). The only way to start a chain early is to guess its link. The sender encrypts the transaction under K with HMAC-SHA256 (Section 5) and keeps the puzzle and key until it needs them.

Four choices in the encoding matter for security. Every hash depends on its puzzle's context or salt, and chain starts and steps also name their chain, so work on another puzzle does not help. Masks are hashes of chain ends, not the ends themselves, so learning a link says nothing about the chain before it. The key depends on every chain's end, so a guessed link cannot be confirmed until the opener's own chains reach it. Finally, the puzzle has $68 + nb$ bytes regardless of the delay, which depends only on N.

4 Security

Secrecy until the deadline rests on two assumptions about SHA-256 and two about the attacker's hardware. This section states them, proves the delay in the random-oracle model, and estimates the one hardware parameter that the proof cannot supply.

4.1 Assumptions

A1. No shortcut. The chain step and each labelled hash behave like independent random oracles on their whole inputs. We instantiate them heuristically with SHA-256; a chain step is a single compression. If this fails, the delay is lost and the hash must be replaced, which the versioned format allows.

A2. Speed. During the delay, no party computes one chain step in less than ℓ. An error here shrinks the delay in proportion.

A3. Budget. The attacker computes at most R hashes per second in total. An error here multiplies the bound of Theorem 1 by the same factor; for the reference puzzle, any factor up to 2^{52} keeps it below 2^{-64}.

A4. Encryption. HMAC-SHA256 is a pseudorandom function (Definition 2).

4.2 The delay theorem

Model. The chain steps $F_1, \ldots, F_n$ and the labelled hashes of Algorithms 1 and 2 are independent random oracles (Section 3.1). The attacker is a classical randomized algorithm $\mathcal{A} = (\mathcal{A}_0, \mathcal{A}_1)$ with unbounded computation. $\mathcal{A}_0$ runs before the puzzle exists and makes Q_{pre} queries; its whole state passes to $\mathcal{A}_1$, which receives the puzzle and makes Q_{on} queries. Let $Q = Q_{\text{pre}} + Q_{\text{on}}$. Time after publication is counted in oracle rounds: all queries in a round are chosen before any answer from that round arrives.

Honest schedule. Computing each chain's mask and accumulator in the same round, Open derives K in oracle round

$$T_{\text{key}} = n(m + 2) + 1$$

and returns it, checked against C, one round later. Build takes $m + n + 3$ rounds: one for the starts, m for the chains, n for the accumulator, with the masks alongside, and one each for K and C. Let $P = n(m + 3) + 1$, the number of oracle answers Open uses, C included.

Theorem 1 (Classical attackers, random-oracle model). *Let* $(Z, K) \leftarrow \mathsf{Build}(n, m, b)$, *with randomness independent of the oracles. For every attacker* $\mathcal{A} = (\mathcal{A}_0, \mathcal{A}_1)$ *as above,*

$$\Pr\left[\mathcal{A}_1 \text{ outputs } K \text{ within fewer than } T_{\text{key}} \text{ oracle rounds}\right] \;\le\; \frac{Q_{\text{on}}}{2^{8b}} + \frac{Q_{\text{pre}}}{2^{128+8b}} + \frac{QP + P^2 + 1}{2^{256}},$$

and the first term is absent when $n = 1$.

The bound in seconds. Assumptions A2 and A3 turn oracle rounds and queries into time. Write $T = nm\ell$, and let the attacker make $Q_{\text{on}} = R \cdot T$ queries after publication. Against $R = 10^{21}$ queries per second, about the hash rate of the whole Bitcoin network (Section 4.3), the bound is about 2^{-117} for a 30-second lock and 2^{-97} for a one-year lock. Precomputation changes this only slightly: a full year of queries at the same rate before a 30-second puzzle is published adds about 2^{-128}. With 24-byte links the first term, the chance of guessing a link, dominates; for a 30-second lock the full-width terms are smaller by a factor of about 2^{31}. At a fixed delay the bound depends on the number of chains only weakly, through $P \approx N$, except that the first term is absent when $n = 1$. The bound covers every speed-up, however small: except with this probability, the attacker does not derive the key even one oracle round before the honest opener.

Scope. The threshold is the round in which K is derived, not the round in which Open returns: an attacker that skips the check against C finishes one round before Open does, with certainty. The precomputation term is needed even when $n = 1$, where the only link is public: an attacker that guesses the salt and the link in advance and computes the key opens the puzzle in zero rounds with probability $2^{-(128+8b)}$. The theorem concerns recovery of the key; Theorem 2 below extends it to the contents. The bounds are classical; extending them to this instantiation against quantum attackers is outside the scope of this paper.

Appendix A gives the proof. It follows the structure of Pietrzak and Reyzin's soundness proof for proofs of sequential work [PR26].

Hiding the contents. An attacker in an encrypted mempool also sees the envelopes sealed under K, and may only need to tell two candidate transactions apart. The labelled hashes H_{enc} and H_{mac} that derive an envelope's subkeys are random oracles like the others, but HMAC is computed outside the oracles. This theorem, unlike Theorem 1, therefore needs the attacker's other computation to be bounded, since an unbounded attacker could evaluate HMAC under every key. We let $\mathcal{A}$ make at most Q_{pre} and Q_{on} oracle queries, as before, and at most t further computation steps.

Definition 1 (Encryption game). For $\beta \in \{0, 1\}$, the game Hide_β and its envelope oracle Enc are given in Figure 3. $\mathcal{A}_0$ makes at most Q_{pre} oracle queries; $\mathcal{A}_1$ makes at most Q_{on} and stops within fewer than T_{key} oracle rounds. The advantage of $\mathcal{A}$ is

$$\mathrm{Adv}^{\text{hide}}(\mathcal{A}) = \left|\Pr[\mathsf{Hide}_1(\mathcal{A}) = 1] - \Pr[\mathsf{Hide}_0(\mathcal{A}) = 1]\right|.$$

Definition 2 (Pseudorandomness of HMAC). For $\beta \in \{0, 1\}$ and u keys, the game PRF_β is given in Figure 3. The advantage of an algorithm $\mathcal{B}$ is

$$\mathrm{Adv}^{\text{prf}}_u(\mathcal{B}) = \left|\Pr[\mathsf{PRF}_1(\mathcal{B}) = 1] - \Pr[\mathsf{PRF}_0(\mathcal{B}) = 1]\right|,$$

and $\mathrm{Adv}^{\text{prf}}_u(t')$ is the largest advantage of an algorithm running in time t'.

Theorem 2 (Hiding). *For every attacker as above,*

$$\mathrm{Adv}^{\text{hide}}(\mathcal{A}) \;\le\; 2\left(\frac{Q_{\text{on}}}{2^{8b}} + \frac{Q_{\text{pre}}}{2^{128+8b}} + \frac{QP' + P'^2}{2^{256}} + \frac{Q_{\text{enc}}^2}{2^{129}} + \mathrm{Adv}^{\text{prf}}_{2Q_{\text{enc}}}\left(t + O(Q + P')\right)\right),$$

where $P' = P + 2Q_{\text{enc}}$, *and the first term is absent when* $n = 1$.




Figure 3: The games of Definitions 1 and 2. H denotes all the oracles, and $\mathsf{Seal}(K, \eta, M)$ is the envelope of M under K with nonce η (Section 5). $\mathcal{F}$ is the set of functions from byte strings to 32-byte values, and $\xleftarrow{\$}$ samples uniformly.

The first three terms come from Theorem 1, with P' path values in place of P: each envelope adds two subkeys derived from K. The fourth is the chance that two nonces repeat, and the last is the cost of replacing HMAC under the $2Q_{\text{enc}}$ subkeys by random functions. For the reference puzzle and few envelopes, the doubled link-guessing term is about 2^{-116}; the nonce term can dominate when many envelopes share a puzzle. The theorem says nothing from round T_{key} on, when the key can be derived and every envelope under it opens. Appendix B gives the proof.

4.3 The hardware assumption

The attacker's total hash rate can be estimated from deployed hardware: the Bitcoin network computes about 10^{21} hashes per second (October 2026), and we take $R = 10^{21}$. A query is one compression, while a Bitcoin hash costs two, since it hashes twice and the first block of the header is computed once; counted in compressions, the network makes about $2 \cdot 10^{21}$ queries per second, which costs one bit: 2^{-116} instead of 2^{-117} for a 30-second lock. Mining hardware computes many independent hashes at once, of block headers rather than salted chains, and says little about how fast one hash can follow another, so it bounds R, not ℓ (Appendix C).

The speed ℓ is the assumption that most needs hardware evidence. Table 4 collects what is known. Relative to the fastest published design that we know of, a synthesized 7 nm core at 13.0 ns per hash [BCF+20], we assume an *advantage* of $A \approx 3.7$, that is, $\ell = 3.5$ ns: 6.6 times faster than one core of the M4 laptop we measured. Some advantage over the published core is certain, since it is a general-purpose design that registers every round and does not exploit the constant part of a chain step's input; Appendix C gives a circuit model for a chip built for chains. We do not claim 3.5 ns is a lower bound. The theorem holds for any value of ℓ the reader adopts, and every cost in Section 5 scales linearly with $1/\ell$.

Sensitivity. Only A1 fails abruptly. An attacker k times faster than assumed opens a 30-second puzzle in $30/k$ seconds; restoring the margin costs k times more sender work and no extra bytes. An attacker with k times the budget multiplies the bound by k, which for the reference puzzle stays below 2^{-64} unless k exceeds 2^{52}. Slower honest hardware costs time, never secrecy. For the reference setting the margin is a factor of about 2.5: a 30-second puzzle covers a 12-second window only while one step takes more than $12\,\text{s}/2^{33} \approx 1.4$ ns. At 1.3 ns, the advantage $A = 10$ that Appendix C does not rule out, it opens in 11.2 s, before the deadline. The bound of Theorem 1 is negligible next to this; the hardware estimate is what limits the reference parameters. The secrecy is also temporary: a sealed transaction becomes public in any case, so only hardware that exists during its delay matters, and ℓ can be repriced as hardware improves.

4.4 Attacks and link width

- **Link guessing.** An attacker can guess a hidden link x_k and run chains $k, k+1, \ldots$ while its own earlier chains are still running. This is the first term of the theorem; with 24-byte links

Table 4: Time per chained SHA-256 hash, from measurements to models.

Source	Time per hash	Basis
Apple M4, one core	23.2 ns	MEASURED: leanSeal benchmark
AMD EPYC 9554P (Zen 4), one core	37.4 ns	MEASURED: leanSeal benchmark, SHA-NI
Published SHA-256 core, 7 nm [BCF+20]	13.0 ns	SYNTHESIS: 67 cycles at 5.15 GHz; not a fabricated chip
Custom round circuit, 3–5 nm	2.9–9.7 ns	MODEL: Appendix C; no such chip has been built
Assumed attacker	**3.5 ns**	the design point of this paper ($A \approx 3.7$)

each guess is right with probability 2^{-192}. Because the key needs every chain's end, a guess cannot be checked against C until the attacker's own chains reach link k.

- **Precomputation.** Every hash on the honest path depends on the puzzle's fresh salt and a fresh link, so work done before publication or on another puzzle does not help, except as counted by the theorem's second and third terms.
- **Quantum attackers.** Afshar et al. [ACH+23] prove that the idealized chained puzzle keeps its delay against quantum openers in the quantum random-oracle model. Carrying this over to leanSeal's exact encoding has not been done; our bound is classical.
- **Early access.** The attacker's clock starts when it first holds the puzzle. Puzzles built in advance must stay private until use.
- **Message substitution.** A claimed key is checked against C with one hash and the tag then authenticates the transaction. But once K is known, anyone can seal a different transaction under the same puzzle, so an ordering must bind the hash of the whole sealed transaction (Section 2.1).

The link width b enters the online guessing term $Q_{\text{on}}/2^{8b}$ and the preprocessing term. With $n = 16$ and the attacker budget above, 16-byte links (324-byte puzzle) give 2^{-53} for a 30-second lock, 24-byte links (452 bytes) give 2^{-117}, and 32-byte links (580 bytes) give 2^{-148}; for a one-year lock, which needs at least 33 chains to respect the format's limit $m \le 2^{48}$, the three give about 2^{-33}, 2^{-97} and 2^{-108}. We use 24 bytes, which keeps the bound near 2^{-96} or below for delays up to a year. With $n = 1$ there is no hidden link, so the online guessing term vanishes; the preprocessing term still depends on the salt and link entropy.

5 Implementation and Costs

leanSeal implements Section 3 as a versioned format with a written specification, a Rust implementation and command-line tool, and an independent Python implementation that agrees with it on every test vector [lea26]. The solver saves its progress, so an interrupted solve can be resumed, and it can solve several puzzles at once, one per core. The Rust code depends only on `getrandom` and `signal-hook`, uses the ARMv8 and x86 SHA-256 instructions when present, and is tested with known answers, round trips, property tests over 480,000 mutated encodings and fuzzing of every decoder. The specification and an earlier C implementation were reviewed over several rounds by an AI model; no human cryptographer has reviewed the code or the format.

Encryption. Encryption uses only SHA-256. For a fresh 16-byte nonce, subkeys k_{enc} and k_{mac} are labelled hashes of K and the nonce; the keystream is $\mathsf{HMAC}(k_{\text{enc}}, \mathsf{be64}(j))$ for block j, and an HMAC tag under k_{mac} covers every preceding byte. A sealed transaction of L bytes takes $128 + nb + L$ bytes: the $68 + nb$-byte puzzle, 8 bytes of framing, the nonce and length (20 bytes)

and the tag (32 bytes). One puzzle can seal several messages under different nonces; they all open together.

5.1 Measurements

Table 5 gives the measurements on two Apple laptops: a fanless MacBook Air with an M4 (10 CPU cores) and a MacBook Pro with an M4 Max (16 CPU cores). GPU figures come from a separate Metal benchmark of the chain step; the tool does not yet build puzzles on a GPU.

5.2 What a delay costs

Four formulas describe the scheme. The delay is $T = N\ell$. Building takes about N/R_s, where R_s is the sender's total hash rate. The puzzle takes $68 + nb$ bytes. Opening without the key takes N times the opener's own time per step: 3.3 minutes on one laptop core for a 30-second puzzle.

The sender's cost is therefore proportional to the delay: about 0.70 seconds of a laptop's time, with all its cores busy, per second of delay (0.097 on the M4 Max GPU, amortized over a batch that takes hours). For constructions from a random oracle, this work cannot be reduced asymptotically [MMV11] (Section 8.1). Two observations make this cost acceptable. First, a puzzle does not depend on the transaction it will seal, so a wallet can keep a stock and build more while idle or charging; the building time is then a cost, not a delay. A laptop CPU running all day builds about 2,800 30-second puzzles (Section 5.3). Second, the delay only needs to cover the time until the ordering is fixed (Section 2.2); halving the delay halves all the work and leaves the puzzle size unchanged.

Precomputation removes the latency, not the cost. Building is spent on every sealed transaction, including those revealed on time, unlike the solvers' work, which arises only on a missed reveal (Section 6.5). At the 265 transactions per slot of our mainnet sample (Section 6.5), one fresh 30-second puzzle each keeps about 460 M4 Air laptops fully busy at 21 s per puzzle, or about 680 at the stock rate below. At about 20 W per laptop under load, an estimate we have not measured, this is 0.1 to 0.2 Wh per transaction and 9 to 14 kW in total. We have not measured phones; a wallet on a phone would build its stock while charging, or outsource building (Section 6.5).

5.3 The number of chains

The delay depends only on N; the number of chains n sets how many cores can work on one puzzle at once, and the size. A sender that builds a puzzle when its transaction is ready needs one chain per core it wants to use: $n = 16$ builds a 30-second puzzle in about 21 s on the M4 Air and 15 s on the M4 Max, half the measured times for a one-minute puzzle. A sender that builds a stock obtains its parallelism from building many puzzles at once instead (five one-minute 16-chain puzzles built together on the M4 Air finished in 187.6 s, or 37.5 s amortized per puzzle, about 19 s per 30-second puzzle), so it can use a single chain per puzzle. Table 6 compares the options.

With $n = 1$, sealing a 110-byte transfer gives 262 bytes rather than 622, and the guessing term of Theorem 1 vanishes. The daily figure above is projected from a single run, which was not archived and was made on a machine that was not idle: ten single-chain puzzles built at once on the M4 Air, one per core, took 75 s for 2^{31} steps each. A stock builder could interleave two single-chain puzzles per core, as the builder already does with chains, to keep the 1.5-fold gain of two SHA-256 pipelines per core.

Table 5: Measurements. The measured puzzle is a one-minute lock with $n = 16$, $m = 2^{30}$ and 24-byte links; the 30-second reference puzzle ($m = 2^{29}$) takes half these times to build and to open without the key. The M4 Air building and opening runs used 32-byte links, with the same chain work. Opening with the key is the command-line tool's end-to-end time, including process start and file input and output.

Measured	M4 Air	M4 Max
One chain step, one CPU core	23.2 ns	24.1 ns
Total CPU hash rate, independent chains	461 M/s	867 M/s
Total GPU hash rate, many chains in flight	0.71 G/s	2.96 G/s
Building the one-minute puzzle on the CPU	42.1 s	30.1 s
Opening it without the key, one core	6 min 42 s	–
Opening a sealed 110-byte transaction with the key	12.0 ms	–

Table 6: 30-second puzzles ($N = 2^{33}$, 24-byte links) for different numbers of chains. The times are half those measured for one-minute puzzles, except for $n = 4$, which is projected from the measured time per step.

Chains n	Puzzle	Added to a transaction	Building on a 10-core laptop
16	452 B	512 B	on demand, about 21 s
4	164 B	224 B	on demand, about 50 s
1	92 B	152 B	from a stock: one per 30 s, about 2,800 a day

6 Trade-offs and Mitigations

6.1 Excluded transactions are also disclosed

A time lock opens whether or not its transaction is included. If a builder receives a sealed transaction and leaves it out, the builder, or anyone else holding it, can read it after the delay. A threshold committee that decrypts only included transactions keeps excluded ones private, which matters because an excluded transaction can still reveal an intent to trade. The secrecy leanSeal gives is temporary in every case: it suits protection against front-running, not the lasting confidentiality that shielded transfers need.

This is not specific to leanSeal. Call a fallback opening *input-free* if it takes only the sealed transaction and auxiliary data that is available whether or not the transaction is included, with no later input or secret release that depends on inclusion.

Claim 1 (informal)**.** *In any scheme whose fallback opening is input-free, whoever can open an included sealed transaction without the sender can open it equally well when it is not included.*

Since inclusion is not an input to the opening, the opening cannot depend on it. Revealing a transaction if and only if it is included therefore needs either a party that can refuse to open, such as a committee, a TEE or the sender, or an opening that takes a later inclusion witness as input, as witness encryption with a blockchain clock does [LJKW18]. The second class is outside the claim; we know of no practical construction in it, and the later input must come from some party or from consensus. Naraghi draws the same three-way distinction among the inputs of a forced opening [Nar26]. This disclosure is inherent in the guarantee: a puzzle protects against a withholding sender only because the sender has released it before the ordering is fixed. Four measures delay the disclosure, narrow its audience and reduce its value.

- **Delay.** An excluded transaction opens a delay after exposure, not at exposure as in today's public mempool; by then, most opportunities to front-run it have passed.
- **Expiry.** A short validity window in the signed transaction means that by the time an excluded transaction can be read, it can no longer be executed. What leaks is the intent. The sender

can also cancel early by spending the nonce.

- **Fewer holders.** Sent only to the parties that can include it in the current slot, the builder or the inclusion-list committee, rather than gossiped, an excluded transaction is readable only by them, and exposure starts close to t_{order}. Broadcasting only a hash of the sealed transaction and publishing the rest once its slot is reserved [Her26, Nar26] also starts exposure close to t_{order}, and a transaction whose commitment is never included is never exposed; but the sender can then decline to publish, which the deposit must also cover (Section 6.2).
- **A committee.** Encrypting under a key derived from both a leanSeal key and a committee's key keeps excluded transactions private while the committee is honest (Section 7.2).

6.2 Withholding: disclosure is forced, execution is not

With plain commit–reveal, the sender holds a free option: it reveals its key if the ordering is favorable and withholds it otherwise. The time lock turns withholding into delay, so withholding cannot keep a well-formed puzzle's transaction hidden. Execution, however, cannot wait at the committed position for minutes of solving without stalling every later transaction. A late-opened transaction must therefore execute later or be dropped, and with a tight deadline, a late execution that reverts amounts to a cancellation. Executing it later is safe only if no one could read its key earlier: a builder that keeps a pending reveal out until the deadline holds the key, and could trade around the late execution, so our prototype drops it (Section 2.4). Withholding thus still lets the sender delay or cancel execution, and a deposit must deter that choice. The reveal deadline makes a missed reveal observable; the time lock separately guarantees disclosure.

- **A deposit forfeited on a missed reveal.** A missed reveal is visible on chain. The deposit is a plaintext field, since the protocol cannot see the transaction's value; LUCID's partly refunded top-of-block fee [EFM26] is one such rule. The penalty must be irrecoverable: the sender knows its own key, so any part of the deposit paid to whoever publishes the key is a part the sender can claim back. A forfeitable fee is also much weaker against an attacker with two or more commitments ahead of its victim (fee inversion [Nar26], Section 7). Capping at one the commitments that may execute ahead of a transaction, or making release decisions blind (below), avoids this.
- **The value of the option.** During the reveal window the sender sees the ordering and the market, but not the other sealed transactions. Its option is roughly an at-the-money option over the window, worth about $0.4\,\sigma\sqrt{\Delta t}$ of the traded value: about 0.015%, or \$1.50 on a \$10,000 trade, for an asset with 60% annual volatility and a 12-second window. If a late-opened transaction may still execute, the option lasts until the forced opening instead: about 0.02% if fast solvers open the reference puzzle in 30 seconds and 0.06% for the 3.3 minutes one laptop core takes.
- **Sizing the deposit.** These are values of an unpenalized option in a volatility-only model, not sufficient deposits. A deposit charged only when the option is exercised raises the exercise threshold but leaves a residual option: a deposit equal to the option's value still leaves more than half of it. The ordering itself also carries information that the model omits. Sizing the deposit therefore needs a target exercise probability or a bound on the gain from withholding [Nar26], over the whole window in which the option lasts.
- **The last revealer.** A sender that sees the others' reveals before its own deadline decides with more information. Releasing reveals simultaneously is an additional protocol requirement; a party that merely collects plaintext keys could leak them early. Blind simultaneous release [Nar26] is one mechanism: right after ordering, each releaser, here each sender, escrows its key under a timed pad that outlasts a window of one or two seconds, so every decision to reveal is fixed before any key is public. It needs a committee to fix the set of timely

escrows, funded fast solvers and a slashable deposit, and escrows by end users remain an open problem (Section 7).

Applications in which order within a batch does not matter avoid this problem, since settlement can wait for every forced opening; Section 6.4 specifies one.

What the puzzle adds to commit–reveal. With the same deposit and deadline, plain commit–reveal already makes a missed reveal observable and penalized, so in a general mempool the deposit, not the puzzle, deters withholding. The puzzle adds two things, each conditional on a well-formed puzzle. First, a withheld transaction becomes public, so withholding no longer keeps the sender's intent private: a sender cannot submit several sealed orders and reveal only the profitable ones without disclosing the others. Second, a sender that goes offline after submitting, or whose key publisher fails, does not lose its transaction: anyone can recover it, and a protocol that executes late openings, such as the auction of Section 6.4, can still run it.

Strategic senders. A sender could build a puzzle whose key matches C but whose chains lead elsewhere, or encrypt its transaction under a key other than the committed one; either way, the solved key does not open the transaction. No efficient check of puzzles at submission is known (Section 8.3). A malformed puzzle costs nothing to make, while a well-formed one costs about 21 s of a laptop and removes the option to withhold privately. Without a penalty for malformation, a sender that values the option therefore never builds a well-formed puzzle, and the two additions above cover only senders whose software builds puzzles honestly: senders that go offline or whose key publisher fails, not senders that withhold by strategy. Against strategic senders the deposit alone then deters withholding, exactly as in commit–reveal. Section 6.3 adds the missing penalty.

6.3 A bond for malformed puzzles

A missed reveal is observable at once; a malformed puzzle only after a forced opening fails. A protocol can charge the two separately: the deposit d on a missed reveal, and a bond B when malformation is established. The bond is returned when the sender's reveal is accepted or when any key matching C opens the transaction, and is forfeited if malformation is established first.

Proving a failed opening. Given a key matching C, a contract checks the envelope's authentication tag directly, so a failing tag establishes malformation at once. Chains that do not lead to the committed key need an optimistic verification game, as in TrueBit [TR17] and Arbitrum [KGC+18]. A claimant posts the final state of Open, anyone may challenge it, and bisection over the $N + O(n)$ steps narrows each dispute to one step, which the contract recomputes; for the reference puzzle a game takes 34 rounds of two moves. A forced opening is assigned to a solver drawn from a staked registry and paid from the forfeited deposit, so that a sender cannot collect the reward by posting its own key late. Appendix D gives the rules; a deployment needs a full specification and its gas costs (Section 8.3).

What the bond changes. Table 7 lists what each choice forfeits. A sender that withholds by strategy now either discloses its transaction or, to keep it private, forfeits $d + B$, while one that goes offline with a well-formed puzzle forfeits only d. Since B is charged only when malformation is established, it can be much larger than d without raising the cost of an honest failure. Commit–reveal cannot make this distinction, since an accidental missed reveal and a strategic one look the same; it can raise the price of the option only by raising the price of going offline. In a general mempool where late openings do not run, as in our prototype, the bond makes concealed withholding cost $d + B$, but withholding still cancels the transaction for d; in an auction, a valid bid from a well-formed puzzle settles anyway (Section 6.4).

Table 7: What a sender forfeits for each choice, with a deposit d forfeited on a missed reveal and a bond B forfeited when malformation is established, before subtracting payments the sender can recover. Building and locked capital are costs too, and are not shown.

Sender	Commit–reveal, deposit d	leanSeal, deposit d and bond B
Reveals on time	nothing	nothing
Goes offline	d; the transaction is lost	d; the transaction is disclosed, and runs where late openings run
Withholds, well-formed puzzle	d; the transaction stays private	d; the transaction is disclosed
Withholds, malformed puzzle	n/a	$d + B$ if it stays private; d if the sender later posts a key that opens it

The bond gives no assurance when a transaction is accepted: it prices malformation but does not rule it out, so a protocol still cannot know at submission that a puzzle will open, and a sender that values its option above $d + B$ still buys it. Nor does the bond bound the work a sender can induce: with malformed chains but a valid key, it can let the solvers nearly finish and then open the transaction itself, which returns the bond. The net deposit must therefore pay for a solve at the admission limits, about 3.3 core-minutes for the reference puzzle (Appendix D).

6.4 A complete application: sealed-bid batch auctions

In a sealed-bid batch auction, order within a batch does not matter, so settlement can wait until every bid is open, and a forced opening still settles a bid at its committed terms. This is the classical use of timed commitments [BN00], and the setting where the puzzle adds most. We specify a frequent batch auction with a uniform price and compare it with the same auction under commit–reveal; Section D.2 gives its full rules.

Each batch k sells a quantity Q_k that the seller deposits in advance. A bid (k, p, x), a unit price and a quantity, is sealed with fixed puzzle parameters and admitted only in the block of slot k, together with its escrow, d and B. Bidders reveal once that block is final, so no key is published before the set of bids is fixed, and a bid still sealed after the reveal window goes to a solver as in Section 6.3. Once every bid is open or excluded, the valid bids clear at a uniform price. The auction assumes the fast finality planned for lean consensus, under which the set of bids is fixed within the reference $T = 30$ s of exposure; under today's finality the delay would have to cover about 13 minutes (Table 3).

Table 8 compares this auction with commit–reveal under the same rules. In the auction, a valid, adequately escrowed bid with a well-formed puzzle remains binding after a missed reveal, including that of the last revealer, who sees the others' bids before its deadline. Withholding a malformed bid incurs an additional bond penalty, and an honest offline bidder still forfeits the reveal deposit. Commit–reveal can impose the same $d + B$ penalty on every missed reveal, but then an offline bidder pays it too. Against this, leanSeal costs bytes, the bidder's work, solver work and settlement delay after a missed reveal. Bids are private only for the delay: a bid that the builder leaves out of slot k is not counted and opens anyway (Section 6.1).

6.5 Other requirements

Finality. The deadline t_{order} is when the position can no longer change. Today an Ethereum block can be reorganized until it is finalized, about 13 minutes later, far beyond a 30-second lock; after a reorganization, a revealed transaction can be front-run in the replacement block. A protocol can accept this once a block has its attestations, so that a reorganization degrades only the affected transactions to today's exposure. With the faster finality planned for lean consensus, t_{order} shrinks to seconds and a 30-second lock covers it with a wide margin.

Table 8: The auction under commit–reveal and under leanSeal, with the same escrow, admission slot and reveal window. Settlement times assume an honest, live first solver whose moves are included in time, and the deadlines of Section D.2.

	Commit–reveal, deposit d	**Commit–reveal, deposit $d + B$**	**leanSeal, deposit d and bond B**
Bidder goes offline	bid lost; forfeits d	bid lost; forfeits $d + B$	a valid bid settles; forfeits d, which pays the solver
Bidder withholds after seeing the market or others' bids	cancels for d	cancels for $d + B$	well-formed puzzle: a valid bid settles anyway; malformed: cancels for $d + B$
Added per bid	a 32-byte commitment	a 32-byte commitment	152 to 512 bytes; about 21 s of a laptop, ahead of time
Solver work	none	none	3.3 core-minutes per missed reveal
Settlement	after W slots	after W slots	after the reveal window if all bids reveal; otherwise, from the first solver assignment, at most 10 minutes for an opening or failing tag, 20 for an unchallenged claim, and 158 for a disputed claim

Admission. A sealed transaction cannot be checked before it is opened, so, as in other encrypted mempools, its plaintext envelope is signed and checked as usual and its fee is charged whether or not the opened transaction is valid. The number of open puzzles per sender should be capped.

Solvers. Opening a withholding sender's transaction within about the delay needs a chip as fast as the assumed attacker; a laptop core takes 3.3 minutes for the reference puzzle. If every one of the roughly 265 transactions per slot in our mainnet sample had to be forced open, this would occupy about 660 attacker-speed circuits or 4,400 laptop cores; at a forced-opening rate of 1%, about 44 cores, before redundancy and failed solves. With deposits in place, withholding should be rare.

A published key can be copied, and a withholding sender can publish its own key after the deadline, so a reward for the first matching key would go to copiers or to the sender; designated solvers paid per assignment avoid the first, and the second unless the sender controls the solver (Section 6.3). Whatever payment the sender or its coalition can recover reduces its penalty, so the cost of withholding is the forfeited deposit minus every such payment, and it is this difference that must deter withholding (Section 6.2).

Size and gas. Sealing adds 152 bytes with stockpiled single-chain puzzles and 512 with the reference puzzle. In 20 consecutive mainnet blocks (22 October 2026; 5,300 transactions; reproducible with `bench/eth-sample.py`), the median transaction was 179 bytes, so sealing makes it 1.8 or 3.9 times larger. As calldata at 16 gas per nonzero byte the added bytes cost about 2,400 or 8,200 gas, against 21,000 for a plain transfer, and about 6,100 or 20,500 for a transaction that pays the calldata floor of EIP-7623, 40 gas per nonzero byte. The ordering needs only the 32-byte hash of each sealed transaction; the rest need only remain available until it is opened, for which a blob, retained for about 18 days, suffices.

Sharing puzzles. One puzzle can cover all of a sender's transactions that should open together. It cannot be shared with unrelated senders: everyone who encrypts under a key knows it. Sharing the cost of opening across senders is delay encryption, which hashes cannot provide when the setup is cheap (Section 8.1). A sender without sufficient hardware can instead outsource building to several services, and encrypt under a hash of all their keys, which stays secret if any one service is honest. Opening, however, needs every service's puzzle to be well formed, and the transaction carries all of them, so its size and the solvers' work grow with the number of services.

7 Comparison with Other Encrypted-Mempool Designs

7.1 The design space

Every encrypted mempool must answer who opens a transaction once it is ordered. Table 9 compares the answers; the survey of Passerat-Palmbach [PP26] and the critique of Garimidi, Bonneau and Heimbach [GBH25] discuss them at length.

The table exhibits a trade-off. Every design in the table that keeps excluded transactions private has a party that can refuse to open, and that party is also the one that can fail to open; Claim 1 says this is forced for input-free fallbacks. Among the designs compared here with an input-free fallback, leanSeal is the only one with no setup and a plausible post-quantum argument. Relative to the other designs, it has three costs: bytes (152 to 512 per transaction, against a 32-byte commitment), the sender's computation, and minutes rather than seconds for a forced opening.

Post-quantum security is a further constraint on the committee designs, not a reason to rule them out, but none of them meets it in practice today. Batched threshold encryption, which lets a committee open a batch with communication independent of its size while excluded transactions stay private, is built from pairings [CGPW24]. The lattice-based threshold batch IBE of Boneh, Laufer and Tas [BLT25] is a post-quantum candidate, without reported sizes. Tree-BTE [ADG+26] can be instantiated from ring LWE; its partial implementation of that version uses about 0.89 MB per ciphertext for a batch of 1,024, against 152 to 512 bytes for leanSeal. Without batching, lattice threshold decryption needs a share from each member for each transaction. A post-quantum committee can still back up leanSeal in the compositions of Section 7.2, where it carries only a fallback key.

DecryptChain [AK26] also removes the fixed committee. It keeps a decryption committee but opens its membership through public proof-of-work in each epoch, so that a compromised committee can be replaced and committed transactions are eventually decrypted. In leanSeal, no committee is involved: the fallback is the sender's own puzzle, which anyone can solve.

The closest work is Naraghi's analysis of reveal optionality [Nar26], which appeared while this paper was being written. Three of its results bear on leanSeal.

- **A timing bound.** Its Theorem 2 covers every forced opening whose inputs are public at broadcast: privacy until the order is fixed and opening by the execution deadline are compatible only if the attacker is at most an explicit ratio of protocol times faster than the honest solvers, a ratio below two once a ciphertext waits a slot in a public mempool and must execute in the next. leanSeal is consistent with this because the sender's reveal is the timely path; the forced opening may finish minutes later, at the cost of late or no execution (Section 6.2). With 200 s from the fixed order to the execution deadline, about one laptop core's time for the reference puzzle, a 4-second ordering delay and a 12-second wait, the bound allows an attacker 13.5 times faster than honest solvers starting at broadcast, or 12.5 if they start once the order is fixed; our assumed attacker is 6.6 times faster than a laptop core.
- **Fee inversion.** Pricing a missed reveal with a forfeitable fee, as LUCID does, is much weaker when two commitments may execute ahead of the victim: the attacker can arrange to forfeit

Table 9: Who opens a sealed transaction, and what each answer rests on. "Excluded" says whether a transaction that is never included stays private.

Design	Privacy before ordering rests on	Opening guaranteed if	Excluded	Setup, PQ
Private order flow	the builder or relay	the builder includes it	if trusted	none; n/a
Commit–reveal, LUCID self-decryption [EFM26]	nothing	the sender chooses to	private	none; yes
Threshold committee: Shutter [Shu], Aptos [Apt26], batched schemes [CGPW24]	no threshold of members colluding	a threshold is online	private with per-transaction keys [CGPP24]	DKG or setup; no
Hybrid [WM25]	no threshold colluding	the sender *or* a threshold is online	private	as threshold
TEE builder	the vendor and physical security [TEE25]	the operator is online	private	attestation; n/a
RSA time lock with proofs [Rad22]	the hardware estimate	always; proofs check the puzzle	opens after T	RSA modulus; no
Delay encryption [BD21]	the hardware estimate	one solve per round	opens after T	trusted setup; no
Blind simultaneous release [Nar26], a layer on the above	the underlying scheme	the releaser escrows in time, and the attacker is at most 3 (2-s window) or 7 (1-s window) times faster than funded solvers	as the underlying scheme	as the underlying scheme; pads plausibly
leanSeal	the hardware estimate	the sender reveals *or* the puzzle is well formed	opens after T	none; plausibly
leanSeal OR committee	both	the sender, a threshold *or* the puzzle	opens after T	as threshold

the large fee only when its guess about the victim is right, so once its best guess has probability above $2/(F+1)$, where $1/F$ is the share of the fee a revealed transaction pays, deterrence needs a fee of at least half its gain. This applies to leanSeal's deposit as well (Section 6.2). Under BSR, below, the single-commitment fee suffices again, because every reveal decision is fixed before any key is public.

- **Blind simultaneous release (BSR).** BSR confines a time lock to the decision window. Right after the order is fixed, each releaser (a key publisher, a committee member, or a sender holding a fallback key) escrows its release value under a timed pad, a precomputed iterated hash, within a window of one or two seconds. After the window, values are revealed or forced open in time for the batch to execute at the top of the next payload, and a releaser whose escrow does not open its commitment is slashed. Privacy before ordering comes from the underlying scheme, not from the pad. On a ticket-first design with twelve-second slots, forced opening in time needs funded solvers within a factor of 3 to 3.5 of the attacker, or 7 to 8 with a one-second window.

BSR and leanSeal solve different problems. leanSeal keeps a transaction private before ordering without a committee or key publisher and guarantees that it is eventually disclosed; BSR makes release decisions simultaneous, which removes the option to decide after seeing others' reveals. They could compose if a leanSeal sender acted as its own releaser and escrowed K in the BSR window, which would supply the simultaneous release that leanSeal leaves open (Section 6.2); Naraghi lists such end-user escrows as open, because of the deposit's capital cost and the pad's precomputation. A leanSeal puzzle could serve as the pad: one that covers a 2-second

window against our assumed attacker builds in about 1.4 s on the M4 Air, which bears on the precomputation barrier, but opens in about 13 s on one laptop core, so it still needs BSR's funded solvers.

Our analysis also supplies concrete figures that Naraghi's leaves open. His pad is a single hash chain whose sequentiality is taken from the random-oracle model, without a concrete bound; a leanSeal puzzle with $n = 1$ has this form, and Theorem 1 gives it one. Our hardware model (Section 4.3) bears on the hardware gap that he lists as open: against our assumed attacker, a factor of 3 to 3.5 requires honest solvers at 10 to 12 ns per hash, faster than one Apple M4 core (23.2 ns) or the Xeon core Naraghi measures (70 ns) and close to the fastest published design (13.0 ns); a factor of 7 to 8 admits a laptop core. These figures rest on our estimate, not on a measurement.

7.2 Composing leanSeal with a threshold committee

A time lock and a committee fail in different ways: the time lock relies on a hardware estimate and leaks excluded transactions, and the committee relies on no threshold of its members colluding and on enough of them being online. The two can be combined in two ways. Let K_{tl} be a leanSeal key and K_{th} a key that a threshold committee releases for included transactions.

- **AND.** Encrypt under $\mathsf{H}(K_{\mathrm{tl}}, K_{\mathrm{th}})$. Reading the transaction needs both keys, so the contents stay hidden while the committee is honest *or* the delay has not passed. With an honest committee, excluded transactions are never revealed. With a colluding committee, the puzzle still keeps the contents hidden for the delay, so the committee cannot read transactions before ordering them. Opening needs both the committee and the puzzle (or the sender's reveal), so a committee that goes offline blocks it.
- **OR.** Encrypt the transaction's key twice, once under each. Either key opens the transaction, so opening needs the committee *or* the puzzle: a committee that withholds keys or goes offline cannot block the opening. Privacy needs the committee to be honest *and* the delay not to have passed.

Table 10 summarizes this. In both, the sender's own reveal remains the fast path. The OR form has the structure of the hybrid designs of Section 7.1, with leanSeal as a fallback that requires no trusted party; the AND form uses leanSeal as a floor for privacy under a committee.

7.3 Settings where leanSeal is practical

leanSeal is practical where three conditions hold: the order is fixed within seconds of exposure, a deposit is acceptable, and a delay of minutes is tolerable for a withholding sender's transaction. Three settings satisfy them.

- **The self-decryption path of LUCID or a hybrid.** Here leanSeal serves as a fallback that requires no trusted party. In the OR form it removes the hybrid design's failure case, a withholding sender while the committee is offline, at the cost of 92 to 452 bytes of puzzle per transaction. Inside LUCID it uses only the puzzle, in the envelope's header; executing a transaction disclosed late needs a protocol rule LUCID does not have.
- **Sealed-bid and batch auctions.** Settlement can wait for every bid to open, so a withheld bid is forced open and still binds its bidder. With escrowed bids and the bond of Section 6.3, leanSeal suffices on its own (Section 6.4).
- **Rollups and chains with fast finality**, where a sequencer or a fast-finality protocol fixes the order within seconds, so a lock of 15 to 30 seconds leaves a wide margin.

It is impractical for transactions that wait several slots in a public mempool. The clock starts at exposure, so a two-slot wait exhausts a 30-second lock; broadcasting only a commitment and

Table 10: Composing leanSeal (time lock, TL) with a threshold committee (TH).

	Contents hidden while	**Opening guaranteed if**	**Excluded transactions**
TL alone	delay not passed	puzzle well formed	revealed after the delay
TH alone	committee honest	committee online	private, if the committee opens only included ones
TL AND TH	committee honest *or* delay not passed	committee online *and* puzzle well formed	private while the committee is honest
TL OR TH	committee honest *and* delay not passed	committee online *or* puzzle well formed	revealed after the delay

publishing the puzzle once the slot is reserved [Nar26], or sending it only to the slot's builder, removes the wait. It is also impractical wherever excluded transactions must stay private and no committee is acceptable: an input-free fallback cannot do both (Claim 1), and openings that take later inclusion witnesses, which are outside this claim, are not practical today.

8 Related Work and Open Questions

8.1 Lower bounds for hash-only puzzles

The delay is limited by the sender's work. Mahmoody, Moran and Vadhan [MMV11] proved that if building a puzzle takes N hash calls, an attacker with unlimited parallelism can open it in about N oracle rounds. The chained puzzle needs about N rounds, so it is asymptotically optimal among random-oracle constructions: no hash-only puzzle can make the sender's work grow more slowly than the delay. The attack makes an enormous number of queries, so the result limits what a proof can promise rather than giving a cheap way to open puzzles.

Delay encryption. Suppose a public setup costs S hash calls, after which senders encrypt to a slot with E calls each and one long computation per slot opens everything. Then running the setup and encrypting is itself a puzzle that costs $S + E$ calls, so by the result above it opens in about $S + E$ rounds: with a cheap setup, the delay is limited by the cost of one encryption. A long setup is not covered by this argument, but if each slot then has a unique, quickly checkable key, computing it is a verifiable delay function, which no hash-only construction can give [MSW20, GRY25, AAK+26]. No method is known that opens independent puzzles for less than one full solve each.

8.2 Related work

Rivest, Shamir and Wagner [RSW96] introduced time-lock puzzles from repeated squaring in RSA groups, which need a trusted setup or class groups and are broken by quantum computers. Later algebraic constructions trade one of these drawbacks for another. Post-quantum time-lock puzzles from lattices [AMZ24] build in time logarithmic in the delay after preprocessing, but rest on circular small-secret LWE and have not been engineered for practical use. Delay encryption from isogenies [BD21] opens a whole slot with one computation but needs a trusted setup and is broken by quantum computers. Batch-solvable puzzles [DGM24] use pairings, and `tlock` [GMR23] encrypts to a future round of a threshold beacon.

Hash-only puzzles avoid these assumptions. Mahmoody, Moran and Vadhan [MMV11] gave the chained-hash puzzle, and Afshar et al. [ACH+23] showed that it keeps its delay against quantum openers in the quantum random-oracle model. Proofs of sequential work [MMV13, CP18] and verifiable delay functions [BBBF18] are related notions with different requirements.

The chained-hash idea has been implemented several times, by Branwen [Bra11], Johnson [Joh13], Todd [Tod14] and EtherDream [Eth24], without a concrete bound or an explicit attacker model.

leanSeal follows the pattern of timed commitments [BN00], without their proof that a forced opening recovers the committed value, and their use against front-running is not new. Time-Capsule [DE20] gives multi-party timed commitments based on discrete logarithms, with puzzle difficulty set by a proof-of-work blockchain, so that operators cannot front-run committed transactions; Ambrona, Beunardeau and Toledo [ABT23] list front-running among the applications of their timed commitments. Multiparty delay encryption [KAJF23] keeps Ethereum transactions encrypted until execution using time-lock puzzles, assuming one honest attestation aggregator per slot. In leanSeal, the fallback is the sender's own puzzle and needs only a hash function. Encrypted-mempool designs are compared in Section 7.

8.3 Open questions

1. **The speed of chained SHA-256.** Every parameter is set relative to ℓ. A circuit-level estimate by hardware designers would give the assumed advantage of 3.7 an empirical basis.
2. **Checking puzzles at submission.** The bond of Section 6.3 prices a malformed puzzle once a forced opening fails, but a protocol still cannot know at submission that a puzzle will open, which is what the proofs of a timed commitment [BN00] provide. A proof over all nm chain steps would cost far more than building the puzzle, and it is not known whether a cheaper check, such as spot-checking the chains or the links between them, can suffice.
3. **Smaller puzzles.** Each chain the sender runs in parallel needs its own hidden link, so a chained puzzle that allows the sender g-fold parallelism has about gb bytes (Section 6.5). Whether a hash-only puzzle can be smaller is open.
4. **A quantum bound for the exact encoding.** Extending the analysis of Afshar et al. [ACH+23] to truncated links, the accumulator and the commitment would give a quantum counterpart of Theorem 1.
5. **Mechanism design.** Open problems include deposits and bonds that remain effective under fee inversion [Nar26], solver capacity under deliberate load, the simultaneous release of keys and rules for executing transactions that are opened late in a general mempool, each best evaluated within a protocol such as LUCID. The verification game of Appendix D is outlined, not specified: it needs exact encodings, gas costs and an analysis of censored moves.

Acknowledgments

We thank Benedikt Wagner and Justin Thaler for helpful discussion and feedback.

AI Assistance

Claude Opus 5.5, GPT-6 Astra and GPT-5.6 Sol were used extensively in this work, under the authors' direction. Claude Opus 5.5 wrote the implementations (the earlier C implementation, the Rust implementation and the Python reference), the benchmarks and the proof-of-concept contracts, drafted the proof of Theorem 1, and helped prepare and edit the manuscript. GPT-6 Astra reviewed all of this work: it audited the specification, the security argument and the C implementation over nine rounds, and reviewed the Rust implementation, the proof, the proof of concept and this paper. GPT-5.6 Sol audited the whole repository, and Claude Opus 5.5 audited the proof of concept; the audit reports, and the changes made in response, are in the repository [lea26]. The authors take full responsibility for the accuracy and correctness of the paper and for any issues in the implementation.

References

[AAK+26] H. Abusalah, K. Azari, C. Kamath, E. Tairi, and M. von Consbruch. Impossibility of VDFs in the ROM: The complete picture. In *Advances in Cryptology – EUROCRYPT 2026*, 2026. Cryptology ePrint Archive, Paper 2025/1773.

[ABT23] M. Ambrona, M. Beunardeau, and R. R. Toledo. Timed commitments revisited. Cryptology ePrint Archive, Paper 2023/977, 2023.

[ACH+23] A. Afshar, K.-M. Chung, Y.-C. Hsieh, Y.-T. Lin, and M. Mahmoody. On the (im)possibility of time-lock puzzles in the quantum random oracle model. Cryptology ePrint Archive, Paper 2023/932, 2023.

[ADG+26] A. Agarwal, S. Das, B. Poorebrahim Gilkalaye, B. Pinkas, and P. Rindal. Tree-BTE: Batched threshold encryption using additive homomorphism. Cryptology ePrint Archive, Paper 2026/2463, 2026.

[AK26] N. Alhaddad and A. Kavousi. DecryptChain: A permissionless proof-of-work encrypted mempool. Cryptology ePrint Archive, Paper 2026/1195, 2026.

[AMZ24] S. Agrawal, G. Malavolta, and T. Zhang. Time-lock puzzles from lattices. In *Advances in Cryptology – CRYPTO 2024*, 2024. Cryptology ePrint Archive, Paper 2025/047.

[Apt26] Aptos Foundation. AIP-144: Encrypted mempool. Aptos Improvement Proposal, 2026.

[BBBF18] D. Boneh, J. Bonneau, B. Bünz, and B. Fisch. Verifiable delay functions. In *Advances in Cryptology – CRYPTO 2018*, 2018. Cryptology ePrint Archive, Paper 2018/601.

[BCF+20] L. Baldanzi, L. Crocetti, F. Falaschi, M. Bertolucci, J. Belli, L. Fanucci, and S. Saponara. Cryptographically secure pseudo-random number generator IP-core based on SHA2 algorithm. *Sensors*, 20(7):1869, 2020.

[BD21] J. Burdges and L. De Feo. Delay encryption. In *Advances in Cryptology – EUROCRYPT 2021*, 2021. Cryptology ePrint Archive, Paper 2020/638.

[BLT25] D. Boneh, E. Laufer, and E. N. Tas. Threshold batch identity-based encryption without epochs. Cryptology ePrint Archive, Paper 2025/1254, 2025.

[BN00] D. Boneh and M. Naor. Timed commitments. In *Advances in Cryptology – CRYPTO 2000*, 2000.

[Bra11] G. Branwen. Time-lock encryption. Essay, 2011.

[CGPP24] A. R. Choudhuri, S. Garg, J. Piet, and G.-V. Policharla. Mempool privacy via batched threshold encryption: Attacks and defenses. USENIX Security, 2024.

[CGPW24] A. R. Choudhuri, S. Garg, G.-V. Policharla, and M. Wang. Practical mempool privacy via one-time setup batched threshold encryption. Cryptology ePrint Archive, Paper 2024/1516, 2024.

[CP18] B. Cohen and K. Pietrzak. Simple proofs of sequential work. In *Advances in Cryptology – EUROCRYPT 2018*, 2018. Cryptology ePrint Archive, Paper 2018/183.

[DE20] Y. Doweck and I. Eyal. Multi-party timed commitments. arXiv:2005.04883, 2020.

[DGM24] J. Dujmovic, R. Garg, and G. Malavolta. Time-lock puzzles with efficient batch solving. In *Advances in Cryptology – EUROCRYPT 2024*, 2024. Cryptology ePrint Archive, Paper 2023/1582.

[Dra18] J. Drake. VDF-based RNG with linear lookahead. Ethereum Research forum, July 2018.

[EFM26] A. Elowsson, J. Florentine, and J. Ma. EIP-8184: LUCID encrypted mempool. Ethereum Improvement Proposal, draft, 2026.

[Eth24] EtherDream. Timelock online. Browser implementation; 2024 design with PBKDF2: https://raw.githubusercontent.com/EtherDream/timelock/e087ed1da8702244a8359097bd26ce2aca57f770/README.md, 2024.

[GBH25] P. Garimidi, J. Bonneau, and L. Heimbach. On the limits of encrypted mempools. a16z crypto, 2025.

[GMR23] N. Gailly, K. Melissaris, and Y. Romailler. tlock: Practical timelock encryption from threshold BLS. Cryptology ePrint Archive, Paper 2023/189, 2023.

[GRY25] Z. Guan, A. Riazanov, and W. Yuan. Breaking verifiable delay functions in the random oracle model. In *Advances in Cryptology – CRYPTO 2025*, 2025. Cryptology ePrint Archive, Paper 2024/766.

[Her26] G. Herold. Towards encrypted mempools from threshold IBE without batching. Ethereum Research forum, September 2026.

[HS03] D. Harris and I. Sutherland. Logical effort of carry propagate adders. In *Asilomar Conference on Signals, Systems and Computers*, 2003.

[Joh13] D. Johnson. timelock. Go implementation, 2013.

[KAJF23] A. Khajehpour, H. Akbarinodehi, M. Jahanara, and C. Feng. A mempool encryption scheme for Ethereum via multiparty delay encryption. Cryptology ePrint Archive, Paper 2023/1612, 2023.

[KGC+18] H. Kalodner, S. Goldfeder, X. Chen, S. M. Weinberg, and E. W. Felten. Arbitrum: Scalable, private smart contracts. In *27th USENIX Security Symposium*, 2018.

[LCV07] Y. K. Lee, H. Chan, and I. Verbauwhede. Iteration bound analysis and throughput optimum architecture of SHA-256 (384, 512) for hardware implementations. In *Information Security Applications (WISA)*, 2007.

[lea26] leanSeal: Specification, implementation, tests, audit reports and benchmark logs. https://github.com/leanEthereum/leanSeal, 2026.

[LHZ+22] J. Li, W. He, B. Zhang, G. He, J. Yang, and M. Seok. TICA: A 0.3V, variation-resilient 64-stage deeply-pipelined Bitcoin mining core with timing slack inference and clock frequency adaption. In *IEEE Custom Integrated Circuits Conference (CICC)*, pages 1–2, 2022.

[LJKW18] J. Liu, T. Jager, S. A. Kakvi, and B. Warinschi. How to build time-lock encryption. *Designs, Codes and Cryptography*, 86, 2018. Cryptology ePrint Archive, Paper 2015/482.

[MMV11] M. Mahmoody, T. Moran, and S. Vadhan. Time-lock puzzles in the random oracle model. In *Advances in Cryptology – CRYPTO 2011*, 2011. Harvard DASH copy.

[MMV13] M. Mahmoody, T. Moran, and S. Vadhan. Publicly verifiable proofs of sequential work. In *4th Innovations in Theoretical Computer Science Conference (ITCS)*, 2013.

[MSW20] M. Mahmoody, C. Smith, and D. Wu. Can verifiable delay functions be based on random oracles? In *47th International Colloquium on Automata, Languages, and Programming (ICALP)*, 2020. Cryptology ePrint Archive, Paper 2019/663.

[Nar26] Aria Naraghi. Reveal optionality in encrypted mempools: Separation, pricing, and blind simultaneous release with post-quantum time-locks. Manuscript, summarized on the Ethereum Research forum, October 2026.

[Nat15] National Institute of Standards and Technology. Secure hash standard (SHS). Federal Information Processing Standards Publication 180-4, NIST, 2015.

[NCTI21] S. Nikolić, F. Catthoor, Z. Tőkei, and P. Ienne. Global is the new local: FPGA architecture at 5nm and beyond. In *ACM/SIGDA International Symposium on Field-Programmable Gate Arrays (FPGA)*, 2021. Table 5.

[PP26] J. Passerat-Palmbach. SoK: Encrypted mempools through the MEV lens. In *Advances in Financial Technologies (AFT 2026)*, volume 395 of *LIPIcs*, 2026.

[PR26] K. Pietrzak and L. Reyzin. Optimal proofs of sequential work. Cryptology ePrint Archive, Paper 2026/2569, 2026.

[Rad22] Radius. MEV-resistant ZK-rollups with practical VDE (PVDE). Ethereum Research forum, 2022.

[RSW96] R. Rivest, A. Shamir, and D. Wagner. Time-lock puzzles and timed-release crypto. Technical Report MIT/LCS/TR-684, MIT Laboratory for Computer Science, 1996.

[Shu] Shutter Network. The road towards an encrypted mempool on Ethereum L1.

[SKR+22] V. B. Suresh, C. S. Katta, S. Rajagopalan, T. Z. Zhou, A. K. Patel, R. Rakha, N. K. Gopalakrishna, S. Mathew, and A. Hukkoo. Bonanza mine: An ultra-low-voltage energy-efficient Bitcoin mining ASIC. In *IEEE International Solid-State Circuits Conference (ISSCC)*, pages 354–356, 2022.

[SSM18] V. Suresh, S. Satpathy, and S. Mathew. Bitcoin mining hardware accelerator with optimized message digest and message scheduler datapath. US patent application 2018/0089642 A1 (Intel), 2018.

[TEE25] TEE.fail: Breaking trusted execution environments via DDR5 memory bus interposition, 2025.

[Tod14] P. Todd. timelock. Software, with an announcement of a funded puzzle on the bitcoin-development mailing list, June 2014: `https://www.mail-archive.com/bitcoin-development@lists.sourceforge.net/msg05547.html`, 2014.

[TR17] J. Teutsch and C. Reitwießner. A scalable verification solution for blockchains. TrueBit white paper, 2017.

[WM25] B. Wagner and J. Ma. Hybrid encrypted mempools. Ethereum Research forum, 2025.

A Proof of the Delay Theorem

Proof of Theorem 1. We compare the real experiment with an ideal one in which the values Open computes are drawn only when the attacker reaches them, show that the ideal experiment is sequential, and bound the probability that the two differ.

Path values. For each chain i, let $y_{i,0} = s_i = \mathsf{H}_{\mathsf{start}}(ctx, i, x_i)$ and $y_{i,k} = F_i(y_{i,k-1})$ for $k = 1, \ldots, m$, so that $y_{i,m} = y_i$. Let $\mu_i = \mathsf{H}_{\mathsf{mask}}(ctx, y_i)$ for $i < n$, $a_0 = ctx$, $a_i = \mathsf{H}_{\mathsf{acc}}(a_{i-1}, y_i)$, $K = \mathsf{H}_{\mathsf{key}}(ctx, a_n)$ and $C = \mathsf{H}_{\mathsf{commit}}(ctx, K)$. These P values are the *path values*. Each path value v is the answer on one *path input* $u(v)$. The *predecessors* of v are the path values in $u(v)$, at most two; in addition, μ_{i-1} is a predecessor of s_i for $i \geq 2$, since $x_i = z_{i-1} \oplus [\mu_{i-1}]_b$.

Let $\rho(v)$ be the oracle round in which Open receives v:

$$\rho(s_i) = (i-1)(m+2)+1, \qquad \rho(y_{i,k}) = \rho(s_i) + k, \qquad \rho(\mu_i) = \rho(a_i) = \rho(y_i) + 1, \qquad \rho(K) = T_{\mathrm{key}}.$$

Every path value v other than s_1 satisfies $\rho(v) = 1 + \max_w \rho(w)$, the maximum taken over its predecessors w.

The two experiments. In the real experiment R, the oracles are random functions sampled lazily; $\mathcal{A}_0$ runs, Build runs, and $\mathcal{A}_1$ receives Z. The ideal experiment G uses the same lazily sampled oracles, but Build makes no queries. It draws the salt and x_1 as before, and draws $z_1, \ldots, z_{n-1}$ and C uniformly. A query of $\mathcal{A}_1$ is *legitimate* if it equals $u(v)$ for a path value v whose predecessors were all revealed before the query was submitted, that is, in earlier rounds; for s_i with $i \geq 2$ this defines $x_i = z_{i-1} \oplus [\mu_{i-1}]_b$. G answers a legitimate query with v, drawing v uniformly the first time (C was drawn already), and marks v revealed at the end of the round; a repeated legitimate query receives the same v. It answers every other query, and all queries of $\mathcal{A}_0$, from the lazily sampled oracles. When $\mathcal{A}_1$ stops, G draws the path values never revealed, which fixes the remaining links.

Drawing in advance. G reads a path value only after revealing it, and C only to publish it: deciding whether a query is legitimate uses only the values of revealed predecessors, and uses x_i only once μ_{i-1} is revealed. So G has the same distribution if all its randomness is drawn at the start: the salt, x_1 and $z_1, \ldots, z_{n-1}$; an independent uniform value $\nu(v)$ for every path value v, with $\nu(C)$ published as C; and lazily sampled oracles H'. We use this form below. The path values are the $\nu(v)$, and they determine the path inputs: $u(s_1)$ from the salt and x_1, $x_i = z_{i-1} \oplus [\nu(\mu_{i-1})]_b$ for $i \geq 2$, and every other $u(v)$ from the values of the predecessors of v.

Claim 2. *In* G*, no path value v is revealed before oracle round $\rho(v)$.*

Proof of the claim. By induction on $\rho(v)$; for s_1, with $\rho = 1$, there is nothing to show. A value is revealed only by a legitimate query, which is submitted after all its predecessors are revealed. Answers arrive at the end of a round, so if a predecessor w is revealed in round $\rho(w)$ or later, v is revealed in round $\rho(w) + 1$ or later; hence in round $1 + \max_w \rho(w) = \rho(v)$ or later. ◊

Claim 3. *Let* Bad *be the event, in* G*, that (a) two path values are equal, or (b) a query that is not legitimate equals a path input, evaluated with the path values as finally drawn. Then the probability that $\mathcal{A}_1$ outputs K early in* R *is at most the probability that it does so in* G *plus* $\Pr_{\mathsf{G}}[\mathsf{Bad}]$.

Proof of the claim. We build R from the randomness of G, drawn in advance.

Links. Set $x_{i+1} = z_i \oplus [\nu(\mu_i)]_b$ for $i < n$. Since z_i is uniform and independent of everything else, the links $x_2, \ldots, x_n$ are uniform and independent of the salt, x_1, ν and H', as Build draws them.

Oracle. Define H by following the honest path in order of ρ (ties in a fixed order): the input $u(v)$ of each path value v receives the answer $\nu(v)$, unless an earlier path value has the same input; every other input receives the answer of H'. Each path input is determined by the salt, the links and earlier answers, and each new path input receives its own answer $\nu(v)$, drawn independently and uniformly. By the usual lazy-sampling argument, H is a uniformly random oracle independent of the salt and the links, so running $\mathcal{A}_0$, Build and $\mathcal{A}_1$ with H is the experiment R. Because H is a single function, an answer that $\mathcal{A}_0$ obtains and that Build or $\mathcal{A}_1$ later obtains again is the same answer.

Commitment and puzzle. Suppose (a) fails. Then the path inputs are distinct: inputs to different oracles are different points, the starts carry their chain index, and two equal inputs to one oracle

contain equal path values. So H answers every path input $u(v)$ with $v(v)$, and the values that Build computes are the $v(v)$. Its commitment is $H(u(C)) = v(C)$, the C that G publishes, and its masked links are $[v(\mu_i)]_b \oplus x_{i+1} = z_i$. The two puzzles are equal.

Queries. Off (a), H agrees with H' at every input that is not a path input. Compare the two runs query by query. A query of $\mathcal{A}_0$ is never legitimate; if it is not a path input, it receives the answer of H' in both experiments. A legitimate query of $\mathcal{A}_1$ equals some $u(v)$ and receives $v(v)$ in both, also when it is repeated. A query of $\mathcal{A}_1$ that is not legitimate and is not a path input receives the answer of H' in both. By induction on the queries, the transcripts, and so the sets of revealed values, agree up to the first query that is not legitimate and equals a path input. That query is event (b); in particular, a path input that $\mathcal{A}_0$ queried, whose answer Build would reuse, is event (b). So the outputs of the two experiments agree unless Bad happens. ◊

Claim 4. *The probability of* Bad *in* G *is at most*

$$\Pr_{\mathsf{G}}[\mathsf{Bad}] \le \frac{Q_{\text{on}}}{2^{8b}} + \frac{Q_{\text{pre}}}{2^{128+8b}} + \frac{QP + P^2}{2^{256}}.$$

Proof of the claim. In G, a query depends only on the values revealed before it was submitted, on the puzzle and on answers of H'. A path value other than C that is not revealed when a query is submitted is therefore independent of that query. So is $x_i = z_{i-1} \oplus [v(\mu_{i-1})]_b$ for $i \ge 2$ while μ_{i-1} is not revealed, and so are the salt and every link for every query of $\mathcal{A}_0$. The commitment C is public, but it is no predecessor of any path value and is independent of the others. Nothing is conditioned on: each bound below is the probability that a fixed query equals a value independent of it.

- Event (a): there are at most P^2 pairs of independent uniform 32-byte values, so its probability is at most $P^2/2^{256}$.
- Event (b), queries to $\mathsf{H}_{\mathsf{start}}$: a query names one index i and equals $u(s_i)$ only if it contains x_i. A query of $\mathcal{A}_1$ with $i = 1$ is legitimate whenever it equals $u(s_1)$. One with $i \ge 2$ that is not legitimate was submitted while μ_{i-1} was not revealed, so it contains x_i with probability 2^{-8b}; this case needs $n \ge 2$. A query of $\mathcal{A}_0$ must also contain the salt, so it succeeds with probability $2^{-(128+8b)}$.
- Event (b), all other queries: a query that is not legitimate but equals $u(v)$ contains, in a 32-byte field, a predecessor of v that was not revealed when it was submitted. That happens with probability at most 2^{-256} for each of the at most P path inputs, so at most $P/2^{256}$ per query.

Summing over the Q_{on} and Q_{pre} queries gives the claim. ◊

Conclusion. In G, if $\mathcal{A}_1$ stops before round T_{key}, then K is not revealed by Claim 2, so $v(K)$ is independent of $\mathcal{A}_1$'s output, and the output equals it with probability 2^{-256}; $C = v(C)$ is independent of $v(K)$ and tells $\mathcal{A}$ nothing about it. Claims 3 and 4 add $\Pr_{\mathsf{G}}[\mathsf{Bad}]$. □

The proof follows the structure of Pietrzak and Reyzin's soundness proof for proofs of sequential work (their Lemmas 6 and 9) [PR26].

B Proof of the Hiding Theorem

Proof of Theorem 2. We extend the proof of Theorem 1. Draw the Q_{enc} nonces $\eta_1, \ldots, \eta_{Q_{\text{enc}}}$ at the start, and add $2Q_{\text{enc}}$ path values: for envelope j, the subkeys $e_j = \mathsf{H}_{\mathsf{enc}}(K \| \eta_j)$ and $t_j = \mathsf{H}_{\mathsf{mac}}(K \| \eta_j)$. The only predecessor of each is K, so $\rho(e_j) = \rho(t_j) = T_{\text{key}} + 1$, and there are now $P' = P + 2Q_{\text{enc}}$ path values. In R, the challenger computes the subkeys by querying the oracles, as Build computes C; in G, it makes no queries and uses $v(e_j)$ and $v(t_j)$. In both, it computes the keystream and the tag with HMAC, which we treat as a function outside the oracles (A4).

Claim 2 holds unchanged, so in G neither K nor any subkey is revealed while $\mathcal{A}_1$ runs. The proof of Claim 3 shows that the runs of R and G agree unless a bad event happens; here it needs one more: (c) two nonces are equal. Off (a) and (c), the subkey inputs differ from each other, since their nonces or labels differ, and from every other path input, since their labels differ; so H answers them with $v(e_j)$ and $v(t_j)$, and the envelopes of the two experiments agree.

Event (c) has probability at most $Q_{\text{enc}}^2/2^{129}$, since the nonces are 16 random bytes. In the proof of Claim 4, the envelopes are a new part of the attacker's view, but they depend only on the messages, the puzzle, the nonces and the subkeys, and no path input contains a subkey, so the argument applies as before with P' in place of P; in particular, a query that equals a subkey input contains K, which is not revealed. Hence, for each value of β, the probability that $\mathcal{A}_1$ outputs 1 differs between R and G by at most

$$\frac{Q_{\text{on}}}{2^{8b}} + \frac{Q_{\text{pre}}}{2^{128+8b}} + \frac{QP' + P'^2}{2^{256}} + \frac{Q_{\text{enc}}^2}{2^{129}}.$$

In G, the $2Q_{\text{enc}}$ subkeys are never revealed. They are independent uniform values, independent of the salt, the links, the other path values and H', and the attacker's view depends on them only through the envelopes. Replacing HMAC under each subkey by an independent random function therefore changes the probability that $\mathcal{A}_1$ outputs 1 by at most $\text{Adv}^{\text{prf}}_{2Q_{\text{enc}}}(t + O(Q + P'))$ (Definition 2): a distinguisher runs G itself, answering the attacker's queries by lazy sampling in time $O(Q + P')$, and computes the envelopes with its own functions.

After the replacement, each envelope has its own encryption function, whose keystream blocks are values at distinct points, so each ciphertext is uniform given its length, which does not depend on β; and each tag is the value of its own random function at one point, so it is uniform and independent of the rest. The attacker's view is then independent of β. Adding the two differences for $\beta = 0$ and for $\beta = 1$ gives the theorem. □

C Estimating the Hardware Speed

This appendix gives the reasoning behind assumption A2 and the advantage factor A of Section 4.3.

SHA-256. We recall the parts of SHA-256 [Nat15] that determine the latency of a chain step.

Definition 3 (SHA-256 compression)**.** Words are 32 bits, + is addition modulo 2^{32}, and $x^{\gg r}$ and $x^{\gg r}$ are x rotated and shifted right by r bits. Let

$$\begin{aligned} \text{Ch}(e,f,g) &= (e \wedge f) \oplus (\neg e \wedge g), & \text{Maj}(a,b,c) &= (a \wedge b) \oplus (a \wedge c) \oplus (b \wedge c), \\ \Sigma_0(a) &= a^{\gg 2} \oplus a^{\gg 13} \oplus a^{\gg 22}, & \Sigma_1(e) &= e^{\gg 6} \oplus e^{\gg 11} \oplus e^{\gg 25}, \\ \sigma_0(x) &= x^{\gg 7} \oplus x^{\gg 18} \oplus x^{\gg 3}, & \sigma_1(x) &= x^{\gg 17} \oplus x^{\gg 19} \oplus x^{\gg 10}. \end{aligned}$$

The compression function maps a state V of eight words and a block $M = W_0 \parallel \cdots \parallel W_{15}$ of sixteen words to a new state. It extends the block by $W_t = \sigma_1(W_{t-2}) + W_{t-7} + \sigma_0(W_{t-15}) + W_{t-16}$ for $16 \le t < 64$.

The rounds start from $(a,b,c,d,e,f,g,h) = V$. For $t = 0, \ldots, 63$, with fixed round constants K_t, round t computes

$$\begin{aligned} T_1 &= h + \Sigma_1(e) + \text{Ch}(e,f,g) + K_t + W_t, \qquad T_2 = \Sigma_0(a) + \text{Maj}(a,b,c), \\ (a,b,c,d,e,f,g,h) &\leftarrow (T_1 + T_2,\ a,\ b,\ c,\ d + T_1,\ e,\ f,\ g). \end{aligned}$$

The output is $V + (a,b,c,d,e,f,g,h)$, added word by word.

For a message x of at most 55 bytes, $\mathsf{SHA256}(x)$ is the compression of the fixed initial state with the single block $x \parallel \texttt{0x80} \parallel 0^{55-|x|} \parallel \mathsf{be64}(8|x|)$.




Figure 4: One SHA-256 round as a circuit, with the path that limits a chain's latency in red. Inputs on the left are the current state words; a' and e' return to the state registers for the next round. (a) A direct implementation adds the terms with 32-bit carry-propagate adders, which puts several of them in series. (b) With carry-save adders and retiming [LCV07], $u_t = h + K_t + W_t$ is computed during the previous round, since h is the previous g. The remaining terms are reduced to two numbers in a carry-save layer, whose depth does not depend on the word length, and each new word needs one carry-propagate addition. The drawing is schematic; the retimed datapath of [LCV07] differs in detail.

A chain step F_i hashes 52 bytes, so it is one compression. The message words W_t depend only on the step's input and can be computed alongside the rounds, so the latency of a step is that of the 64 rounds.

How SHA-256 is computed in hardware. Assumption A2 can be examined against the structure of SHA-256. One SHA-256 compression is 64 rounds, and each round needs the exact output of the previous one. The new state words are sums of up to five 32-bit terms. Some of them, such as the round constant and the message word, can be added ahead of time, but the next round applies rotations and bitwise functions to the exact bits of the result. Every round must therefore finish at least one 32-bit addition with full carry propagation, plus a few levels of logic. Lee, Chan and Verbauwhede [LCV07] show that this much is also enough: with carry-save adders and retiming, the loop through one round needs one carry-propagate addition, one carry-save layer and the choice function Ch. Figure 4 shows both datapaths.

Pipelining raises throughput but not the latency of one chain, since each step starts from the previous step's output. Unrolling removes the registers between rounds, so the relevant floor is the one for logic alone. Hence ℓ is roughly 64 times the shortest critical path of one round, measured over many unrolled rounds.

The circuit model. The model row of Table 4 quantifies this argument. Its unit is the FO4, the delay of an inverter driving four copies of itself. It estimates the round loop of Lee et al. at 10–17 FO4: 7–12 for a fast 32-bit adder [HS03] and 3–5 that we assume for the carry-save layer and Ch. Predicted FO4 delays for 3–5 nm processes are 4.3–4.7 ps [NCTI21]. Then 64 rounds take

$$64 \times 10 \times 4.3\,\text{ps} = 2.75\,\text{ns} \quad \text{to} \quad 64 \times 17 \times 4.7\,\text{ps} = 5.11\,\text{ns},$$

and with 0.1–0.3 ns for the final addition and startup, 2.85–5.41 ns. Our allowance of 1 to 1.8 times for wires, cell choice and registers gives 2.9–9.7 ns, that is, $A \approx 1.3$–4.5.

As a cross-check, Intel's mining patent describes a state update 13 logic levels deep [SSM18]; if each level cost one FO4, which is optimistic, a hash would take 3.6–3.9 ns. A process shrink by itself gives only $A \approx 1.3$. At 3.5 ns a round has 55 ps, about 12 FO4, so the design point needs a

highly optimized custom datapath and sits near the aggressive end of the model. The model's lower end is a conditional estimate, not a physical bound, and no published design that we know of comes close to it.

Mining hardware. Bitcoin mining chips are the SHA-256 circuits built in the largest numbers, but they are designed for energy per hash, not latency. Intel's Bonanza Mine [SKR+22] has 258 fully unrolled double-SHA-256 engines on a 7 nm die. It runs at 355 mV and 1.35–1.6 GHz and computes 137 billion hashes per second at 55 J per terahash. TICA [LHZ+22] pipelines the 64 rounds into 64 stages at 0.3 V in 28 nm. Both lower the supply voltage close to the threshold, where gates are several times slower, and recover throughput with many engines. Neither reports the latency of one hash. If each cycle of Bonanza Mine advanced one round, one compression would take 40–47 ns, ten times our 3.5 ns. A chain attacker would build the opposite: one engine at high voltage, with no registers between rounds.

The precedent of verifiable delay functions. Work on verifiable delay functions faced the same question and also answered it with a stated factor: Drake proposed $A_{\max} = 10$ as a conservative parameter for RSA-based VDFs, hoping that public ASICs would bring it to about 5 [Dra18]. Here $A = 10$ means $\ell = 1.3$ ns, about 4.5 FO4 per round, outside the model but not ruled out. Section 8.3 lists a careful estimate as the most important open question.

D The Bond and the Auction in Detail

This appendix gives the rules behind the bond of Section 6.3 and the auction of Section 6.4.

D.1 The verification game and solver pay

Proving a failed opening. Given a key K with $\mathsf{H}_{\mathsf{commit}}(ctx, K) = C$, a contract checks the envelope's authentication tag directly, which needs no decryption and costs work linear in the envelope's length, which admission caps (Section D.2). A failing tag establishes malformation at once. Chains that do not lead to the committed key are harder: the evidence is the whole computation of Open, $N + O(n)$ steps, which no contract can repeat. An optimistic verification game, as in TrueBit [TR17] and Arbitrum [KGC+18], can establish it in about $\log_2 N$ rounds. We outline one here; a deployment needs a full specification and its gas costs (Section 8.3).

The game. A *state* of Open is the solver's checkpoint (`SPEC.md`, Section 6.4: the chain index, the steps done in that chain, the chain state and the accumulator) together with the current link, a few hundred bytes. The contract computes the hash of the initial state from the puzzle itself. A claimant stakes and posts the final state, whose key K' the contract checks to satisfy $\mathsf{H}_{\mathsf{commit}}(ctx, K') \neq C$. Within a challenge period, anyone may stake and dispute the claim. Each challenger then plays its own game against the claimant: the claimant posts the hash of the state at the midpoint of the interval still in dispute, and the challenger says whether it agrees, which halves the interval.

When one step remains, the claimant opens the state both sides agreed on, which for the first step is the initial state. The contract recomputes its successor, one SHA-256 compression or, at a chain boundary, a few labelled hashes, and compares the result's hash with the claimant's hash for the end of the interval: the claimant wins that game if they match, and the challenger otherwise. A party that misses a move's deadline loses the game, and the loser forfeits its stake. For the reference puzzle, $N + O(n)$ is just above 2^{33}, so a game takes 34 rounds of two moves, each a transaction carrying at most one 32-byte hash, and one final step. Naraghi assumes a similar mechanism, without analysis, for the pads of blind simultaneous release [Nar26].

Who decides. A claim stands only if no one challenges it within the period, or if the claimant wins every game. Games run in parallel, so a challenger colluding with the claimant that loses on purpose cannot defeat an honest one. Since Open is deterministic and its input public, anyone who has solved a well-formed puzzle can challenge a false claim, so a sender that went offline needs no one to act for it. This is the usual assumption of optimistic verification: at least one honest party solves the puzzle within the challenge period and gets each move included before its deadline. A key that matches C does not refute a claim, since a malicious sender knows such a key; posted before the claim stands, it opens the transaction, ends the games, returns every stake and returns the bond.

Paying solvers. A sender that withholds its key can still publish it after the deadline, so a reward for the first matching key would go to the sender and leave the solvers that did the work unpaid, and a solver of a malformed puzzle has no key to post.

The protocol therefore assigns each missed reveal to a solver drawn from a staked registry. Within a deadline D_s, the solver must submit a key matching C, evidence that the tag fails under such a key, or a malformation claim; a key posted by anyone also counts. A timely claim keeps the assignment until the claim is decided. The solver is paid from the forfeited deposit, and recovers its stake, for a payable outcome: a valid opening, a failing tag, or its claim standing. A solver that submits nothing in time, or whose claim fails, loses its stake, and the transaction passes to the next solver. Designation prevents outsiders from copying an assignment's reward, but does not exclude solvers that the sender controls. The effective penalty is therefore $d - r$, or $d + B - r$ when malformation is established, where r is every payment the sender or its coalition can recover; a forfeited bond is burned, so that r is at most the solver's payment.

Denial of service. A missed reveal can induce nearly a full solve while costing only the net deposit penalty $d - r$: a sender whose chains are malformed, but who holds a key matching C and a valid envelope under it, can post the key just before the solvers finish, which opens the transaction and returns the bond. The bond is additionally forfeited only when malformation is established before a successful opening. The net deposit must therefore pay for a solve at the admission limits, together with any claim, game and redundant solver. For the reference puzzle, a solve takes about 3.3 minutes of a laptop core, or 30 s of a circuit as fast as the assumed attacker; on rented laptop-class cores at four cents per core-hour it costs about a fifth of a cent.

Deposits price demand; they do not by themselves provide solver capacity, and capacity at attacker speed is scarcer. An attacker that exhausts it delays forced openings; it does not make any transaction readable earlier, since secrecy rests on the delay, not on the solvers. A cap on open puzzles per sender does not bound the total load when the attacker uses many accounts; admission limits and deposits do.

D.2 The auction rules

The auction sells, in each slot, a fixed quantity of one asset for a quote asset at a uniform price. Its parameters are the deposit d, the bond B, a reveal window of W slots, a solver deadline D_s, a challenge period D_c and a move deadline τ.

1. **Supply and bids.** Before batch k opens, the seller deposits its quantity Q_k in the contract, so each batch settles from its own supply and escrows. A bid is a plaintext (k, p, x): the batch, a unit price and a quantity, each a 32-byte unsigned integer, 96 bytes in all. It is *valid* if its batch is k, p is at least the reserve price, $x \leq Q_k$, and $px \leq E$, where E is the escrow posted in plaintext with the bid.
2. **Admission.** The contract accepts a sealed bid for batch k only in the block of slot k, with its escrow, d and B, and only with the reference work and fixed limits: $nm = 2^{33}$, $n \leq 16$, $b = 24$,

an envelope of the bid's fixed length, and at most a fixed number of bids per batch. Checking the commitment, deriving the subkey and checking the tag then take at most 17 SHA-256 compressions.

3. **Exposure.** A bid is exposed when it first leaves the bidder, to a builder or a mempool, and the set of bids is fixed when slot k's block is final. The bidder sends its bid only to the builders of slot k, during that slot. The auction assumes the fast finality planned for lean consensus, under which the set is fixed within the reference $T = 30$ s of exposure (Table 3). Under today's finality the delay would have to cover about 13 minutes, with the larger work and costs of the last row of Table 3 (Section 6.5).

4. **Reveal.** The reveal phase begins once slot k's block is final, so no key is published before the set of bids is fixed. Within the next W slots, the bidder publishes its key. The contract checks it against C, checks the tag, decrypts the bid and returns d and B. An invalid bid is excluded and forfeits d.

5. **Forced opening.** A bid still sealed after the window is assigned to a solver, as in Section 6.3, drawn with the randomness of a later slot. A key matching C, from anyone, opens the bid, which is then checked as in a reveal and returns B; d pays the solver. A failing tag, or a malformation claim that stands, excludes the bid and forfeits d and B.

6. **Settlement.** Once every bid is open or excluded, the contract sorts the valid bids by price, highest first, breaking ties by a hash of the sealed bid and the randomness of a later slot, fills them from Q_k in that order, the last one partly, and charges every filled bid the lowest filled price. The rest of each escrow is refunded, and unsold units return to the seller. Later batches do not wait for this one.

Settlement follows the reveal window at once if every bidder reveals. After a missed reveal, if the first solver assigned is honest and live and its moves are included in time, it waits from the assignment at most D_s for an opening or a failing tag, $D_s + D_c$ for an unchallenged claim, and $D_s + D_c + 69\tau$ for a disputed one. With $D_s = D_c = 10$ minutes and $\tau = 2$ minutes, these are 10, 20 and 158 minutes. Each failed assignment can add as much again, and costs a staked solver its stake.