```
In [1]: import numpy as np
        from scipy.integrate import odeint
        from scipy.optimize import curve_fit
        from scipy.optimize import differential evolution
        %matplotlib inline
        import matplotlib.pyplot as plt
        from matplotlib.backends.backend_pdf import PdfPages
        import pandas as pd
In [2]: from endpoint_maker import sqres
        from endpoint maker import func
        from endpoint maker import t
        from endpoint maker import new
        from endpoint maker import lightdata
        from endpoint maker import rawdata
In [3]: if name == ' main ':
            def initparams():
                \#bounds = ([0.00001,10000],[0,4],[0.00001,1000],[0.00001,1000],[0.00001,100
                bounds = ([0.00001,1000],[0.00001,1000],[0.00001,10000],[0.00001,10000])
                result = differential evolution(sqres,bounds,maxiter=100,popsize=20,polish=
                return result
In [4]: initialp = initparams()
        print(initialp)
        message: Maximum number of iterations has been exceeded.
        success: False
            fun: 2.9696749412043038
              x: [ 1.286e+02 9.509e+02 5.694e+03 2.502e+03]
            nit: 100
           nfev: 8080
In [5]: #def tester(t,Kd,n,d2,k2,k3,i):
        def tester(t,d2,k2,k3,k7,i):
            inivalues = [1,0,0,0,0,0,0]
            arrayvalues = np.asarray([])
            #for i in range(len(lightdata[:,0])):
            def I(t):
                tindex = t/5
                if tindex > 12241:
                    tindex = 12240
                return lightdata[i][int(tindex)]
            \#def\ odes(z,t,Kd,n,d2,k2,k3):
            def odes(z,t,d2,k2,k3,k7):
                Pu, Pb, Pa, mRNA, mCherry1, mCherry2, mCherry3 = z
                d1 = 0.019905
                k1 = 0.08299
                Kd = 90.41
                n = 0.964487
                #d2= 486.67
```

```
\#k2 = 6.597
                 #k3= 0.0539
                 d3 = 0.000077
                 k4 = 1.25
                 d4 = 0.000031
                 k5 = 0.00283
                 k6 = 0.00283
                 Pu = z[0]
                 Pb = z[1]
                 Pa = z[2]
                 mRNA = z[3]
                 mCherry1 = z[4]
                 mCherry2 = z[5]
                 mCherry3 = z[6]
                 dPudt = d1*Pb - k1*I(t)*Pu - k7*I(t)*Pu
                 dPbdt = k1*I(t)*Pu - k2*Pb - d1*Pb + d2*Pa
                 dPadt = k2*Pb - d2*Pa + k7*I(t)*Pu
                 dmRNAdt = k3*Pa - d3*mRNA
                 dmCherry1dt = k4*mRNA-(d4 + k5)*mCherry1
                 dmCherry2dt = k5*mCherry1-(d4+k6)*mCherry2
                 dmCherry3dt = k6*mCherry2 - d4*mCherry3
                 return [dPudt,dPbdt,dPadt,dmRNAdt,dmCherry1dt,dmCherry2dt,dmCherry3dt]
            #solver = odeint(odes,inivalues,t,args = (Kd,n,d2,k2,k3),hmax=0.1)
             solver = odeint(odes,inivalues,t,args = (d2,k2,k3,k7),hmax=0.1)
            mCherryout = solver[:,6]
             #mCherryout = mCherryout[0:24480:240]
             return mCherryout
In [6]: print(initialp.x)
       [ 128.59949445    950.90049285    5693.8881506    2501.64041538]
In [7]: popt, covt = curve_fit(func,t,new,initialp.x,maxfev=1000000)
        \#popt, covt = curve fit(func,t,newdata,initialp.x, <math>maxfev=10000000, bounds=((0.0000)
        #popt, covt = curve_fit(func,t,newdata,initialp.x, maxfev=1000000)
        \#Kd,n,d2,k2,k3 = popt
        #print('Kd=',Kd,'n=',n,'d2=',d2,'k2=',k2,'k3=',k3)
        \#d3, k4, d4, k5, k6 = popt
        #print('d3=',d3,'k4=',k4,'d4=',d4,'k5=',k5,'k6=',k6)
```

d2,k2,k3,k7 = popt

print('d2=',d2,'k2=',k2,'k3=',k3,'k7=',k7)

```
C:\Users\Leandra\anaconda3\Lib\site-packages\scipy\integrate\_odepack_py.py:248: ODE
intWarning: Excess work done on this call (perhaps wrong Dfun type). Run with full_o
utput = 1 to get quantitative information.
   warnings.warn(warning_msg, ODEintWarning)
d2= 128.59949445334564 k2= 950.9004928545289 k3= 5693.888150603836 k7= 2501.64041538
1583
C:\Users\Leandra\anaconda3\Lib\site-packages\scipy\optimize\_minpack_py.py:1010: Opt
imizeWarning: Covariance of the parameters could not be estimated
   warnings.warn('Covariance of the parameters could not be estimated',
```


```
In [8]: import sys
        import numpy
        \#params = [1,1,1,1,1,1,1]
        params = [1,1,1,1]
        numpy.set printoptions(threshold=10)
        \#model1 = np.asarray(func(t,Kd,n,d2,k2,k3))
        model1 = np.asarray(func(t,d2,k2,k3,k7))
        print(len(model1))
        #print(model1)
        \#a,b,c,d,e,f,g = params
        a,b,c,d= params
        ydata = np.asarray(new)
        print(len(ydata))
        ssr = np.sum((ydata-model1)**2)
        #ssr2 = np.sum((ydata-model2)**2)
        sst = np.sum((ydata-np.mean(ydata))**2)
        R2=1-ssr/sst
        print('R2 is:', R2)
```

102 102 R2 is: -1.7735601382497155

```
In [9]: pp = PdfPages('multipage.pdf')
         ydata = np.asarray(new)
         \#condition = [1,2,3,4,5,6,7,8,9]
         for i in range(2):
             \#model = tester(t, Kd, n, d2, k2, k3, i)
             model = tester(t, d2, k2, k3, k7, i)
             #print(model)
             \#a,b,c,d,e,f,g= params
             a,b,c,d= params
             plt.plot(t,model,'.', label = 'model')
             #print(model)
             \#t = np.linspace(0,34800, num=6961)
             #raw = rawdata[0:13920:240]
             plt.plot(t,raw[i],'.',label = 'data')
             #print(rawdata[i])
             plt.legend()
             pp.savefig()
```

```
plt.show()

pp.close
```



```
In [ ]:
In [ ]:
```