```
In [1]: import numpy as np
        from scipy.integrate import odeint
        from scipy.optimize import curve_fit
        from scipy.optimize import differential evolution
        %matplotlib inline
        import matplotlib.pyplot as plt
        from matplotlib.backends.backend_pdf import PdfPages
        import pandas as pd
In [2]: from endpoint_maker import sqres
        from endpoint maker import func
        from endpoint maker import t
        from endpoint maker import new
        from endpoint maker import lightdata
        from endpoint maker import rawdata
In [3]: if name == ' main ':
            def initparams():
                bounds = ([0.00001,10000],[0,4],[0.00001,1000],[0.00001,1000],[0.00001,1000
                \#bounds = ([0.00001, 1000], [0.00001, 1000], [0.00001, 10000])
                result = differential evolution(sqres,bounds,maxiter=100,popsize=20,polish=
                return result
In [4]: initialp = initparams()
        print(initialp)
        message: Maximum number of iterations has been exceeded.
        success: False
            fun: 2.9341685751433646
              x: [ 4.554e+03 1.509e+00 2.282e+02 2.135e-01 2.931e+01]
            nit: 100
           nfev: 10100
In [5]: def tester(t,Kd,n,d2,k2,k3,i):
        #def tester(t,d2,k2,k3,i):
            inivalues = [1,0,0,0,0,0,0]
            arrayvalues = np.asarray([])
            #for i in range(len(lightdata[:,0])):
            def I(t):
                tindex = t/5
                if tindex > 12241:
                    tindex = 12240
                return lightdata[i][int(tindex)]
            def odes(z,t,Kd,n,d2,k2,k3):
            #def odes(z,t,d2,k2,k3):
                Pu, Pb, Pa, mRNA, mCherry1, mCherry2, mCherry3 = z
                d1 = 0.019905
                k1 = 0.08299
                \#Kd = 90.41
                #n = 0.964487
                #d2 = 486.67
```

```
\#k2 = 6.597
               #k3= 0.0539
              d3 = 0.000077
              k4 = 1.25
              d4 = 0.000031
              k5 = 0.00283
              k6 = 0.00283
              Pu = z[0]
              Pb = z[1]
               Pa = z[2]
              mRNA = z[3]
               mCherry1 = z[4]
               mCherry2 = z[5]
               mCherry3 = z[6]
               dPudt = d1*Pb - k1*I(t)**n/(Kd**n+I(t)**n)*Pu
               dPbdt = k1*I(t)**n/(Kd**n+I(t)**n)*Pu - k2*I(t)**n/(Kd**n+I(t)**n)*Pb - d1**n*I(t)**n/(Kd**n+I(t)**n)*Pb - d1**n*I(t)**n/(Kd**n)*Pb - d1**n/(Kd**n)*Pb - d
               dPadt = k2*I(t)**n/(Kd**n+I(t)**n)*Pb - d2*Pa
               dmRNAdt = k3*Pa - d3*mRNA
               dmCherry1dt = k4*mRNA-(d4 + k5)*mCherry1
               dmCherry2dt = k5*mCherry1-(d4+k6)*mCherry2
               dmCherry3dt = k6*mCherry2 - d4*mCherry3
               return [dPudt,dPbdt,dPadt,dmRNAdt,dmCherry1dt,dmCherry2dt,dmCherry3dt]
solver = odeint(odes,inivalues,t,args = (Kd,n,d2,k2,k3),hmax=0.1)
#solver = odeint(odes,inivalues,t,args = (d2,k2,k3),hmax=0.1)
mCherryout = solver[:,6]
#mCherryout = mCherryout[0:24480:240]
return mCherryout
```

```
In [6]: print(initialp.x)
[4.55386119e+03 1.50881128e+00 2.28190011e+02 2.13469661e-01
2.93067459e+01]
In [7]: popt, covt = curve_fit(func,t,new,initialp.x,maxfev=1000000)
#popt, covt = curve_fit(func,t,newdata,initialp.x, maxfev=10000000, bounds=((0.0000 #popt, covt = curve_fit(func,t,newdata,initialp.x, maxfev=1000000)


Kd,n,d2,k2,k3 = popt
print('Kd=',Kd,'n=',n,'d2=',d2,'k2=',k2,'k3=',k3)

#d3,k4,d4,k5,k6 = popt
#print('d3=',d3,'k4=',k4,'d4=',d4,'k5=',k5,'k6=',k6)

#d2,k2,k3 = popt
#print('d2=',d2,'k2=',k2,'k3=',k3)
```

Kd= 4553.465692586647 n= 1.5086590800895874 d2= 228.20035157168365 k2= 0.21345783159 76421 k3= 29.277026181315186

```
In [8]: import sys
        import numpy
        \#params = [1,1,1,1,1,1,1]
        params = [1,1,1,1,1]
         numpy.set printoptions(threshold=10)
        model1 = np.asarray(func(t,Kd,n,d2,k2,k3))
        \#model1 = np.asarray(func(t,d2,k2,k3))
         print(len(model1))
         #print(model1)
        \#a,b,c,d,e,f,g = params
         a,b,c,d,e = params
        ydata = np.asarray(new)
         print(len(ydata))
        ssr = np.sum((ydata-model1)**2)
        #ssr2 = np.sum((ydata-model2)**2)
        sst = np.sum((ydata - np.mean(ydata))**2)
        R2 = 1 - ssr/sst
        \#R2_2 = 1 - ssr2/sst
        print('R2 is: ', R2)
        #print(R2_2)
       102
       102
       R2 is: -0.18402077134801265
In [9]: pp = PdfPages('multipage.pdf')
        ydata = np.asarray(new)
        \#condition = [1,2,3,4,5,6,7,8,9]
         for i in range(2):
            model = tester(t, Kd, n, d2, k2, k3, i)
            #model = tester(t, d2, k2, k3, i)
            #print(model)
            \#a,b,c,d,e,f,g= params
            a,b,c,d,e= params
            plt.plot(t,model,'.', label = 'model')
            #print(model)
            \#t = np.linspace(0,34800, num=6961)
            \#raw = rawdata[0:13920:240]
            plt.plot(t,raw[i],'.',label = 'data')
            #print(rawdata[i])
            plt.legend()
            pp.savefig()
            plt.show()
         pp.close
```



In []: