

```
In [1]: import numpy as np
from scipy.integrate import odeint
from scipy.optimize import curve_fit
from scipy.optimize import differential_evolution
%matplotlib inline
import matplotlib.pyplot as plt
from matplotlib.backends.backend_pdf import PdfPages
import pandas as pd
```

```
In [2]: from endpoint_maker import sqres
from endpoint_maker import func
from endpoint_maker import t
from endpoint_maker import new
from endpoint_maker import lightdata
from endpoint_maker import rawdata
```

```
In [3]: if __name__ == '__main__':
def initparams():
    bounds = ([0.00001,10000],[0,4],[0.00001,1000],[0.00001,1000],[0.00001,10000])
    #bounds = ([0.00001,1000],[0.00001,1000],[0.00001,10000])
    result = differential_evolution(sqres,bounds,maxiter=100,popsize=20,polipopsize=20)
    return result
```

```
In [4]: initialp = initparams()
print(initialp)
```

```
message: Maximum number of iterations has been exceeded.
success: False
  fun: 0.5470239637941295
   x: [ 9.346e+03  2.878e+00  8.833e+02  6.213e-01  2.367e+01]
  nit: 100
 nfev: 10100
```



```

In [5]: def tester(t,Kd,n,d2,k2,k3,i):
#def tester(t,d2,k2,k3,i):

    inivalues = [1,0,0,0,0,0,0]
    arrayvalues = np.asarray([])

    #for i in range(len(Lightdata[:,0])):
    def I(t):
        tindex = t/5
        if tindex > 12241:
            tindex = 12240
        return lightdata[i][int(tindex)]

    def odes(z,t,Kd,n,d2,k2,k3):
#def odes(z,t,d2,k2,k3):
        Pu,Pb,Pa,mRNA,mCherry1,mCherry2,mCherry3 = z
        d1 = 0.019905
        k1 = 0.08299
        #Kd = 90.41
        #n = 0.964487
        #d2= 486.67
        #k2= 6.597
        #k3= 0.0539

        d3 = 0.000077
        k4 = 1.25
        d4 = 0.000031
        k5 = 0.00283
        k6 = 0.00283

        Pu = z[0]
        Pb = z[1]
        Pa = z[2]
        mRNA = z[3]
        mCherry1 = z[4]
        mCherry2 = z[5]
        mCherry3 = z[6]

        dPudt = d1*Pb - k1*I(t)*Pu
        dPbdt = k1*I(t)*Pu - k2*I(t)**n/(Kd**n+I(t)**n)*Pb - d1*Pb + d2*Pa
        dPadt = k2*I(t)**n/(Kd**n+I(t)**n)*Pb - d2*Pa
        dmRNA dt = k3*Pa - d3*mRNA
        dmCherry1dt = k4*mRNA-(d4 + k5)*mCherry1
        dmCherry2dt = k5*mCherry1-(d4+k6)*mCherry2
        dmCherry3dt = k6*mCherry2 - d4*mCherry3

        return [dPudt,dPbdt,dPadt,dmRNA dt, dmCherry1dt, dmCherry2dt, dmCherry3dt]

    solver = odeint(odes,inivalues,t,args = (Kd,n,d2,k2,k3),hmax=0.1)
    #solver = odeint(odes,inivalues,t,args = (d2,k2,k3),hmax=0.1)

    mCherryout = solver[:,6]
    #mCherryout = mCherryout[0:24480:240]
    return mCherryout

```

In [6]: `print(initialp.x)`

```
[9.34579412e+03 2.87750526e+00 8.83316606e+02 6.21287463e-01
 2.36738206e+01]
```

In [7]: `popt, covt = curve_fit(func,t,new,initialp.x,maxfev=1000000)`

```
#popt, covt = curve_fit(func,t,newdata,initialp.x, maxfev=10000000, bounds=((0
#popt, covt = curve_fit(func,t,newdata,initialp.x, maxfev=1000000)
```

```
Kd,n,d2,k2,k3 = popl
print('Kd=',Kd,'n=',n,'d2=',d2,'k2=',k2,'k3=',k3)
```

```
#d3,k4,d4,k5,k6 = popl
#print('d3=',d3,'k4=',k4,'d4=',d4,'k5=',k5,'k6=',k6)
```

```
#d2,k2,k3 = popl
#print('d2=',d2,'k2=',k2,'k3=',k3)
```

```
C:\Users\Leandra\anaconda3\Lib\site-packages\scipy\integrate\_odepack_py.py:2
48: ODEintWarning: Excess work done on this call (perhaps wrong Dfun type). R
un with full_output = 1 to get quantitative information.
  warnings.warn(warning_msg, ODEintWarning)
```

```
Kd= 9567.034238378648 n= 2.8193089433520817 d2= 909.9836216184395 k2= 0.62128
74628347944 k3= 24.478178116287545
```

```
In [8]: 1 import sys
2 import numpy
3 #params = [1,1,1,1,1,1,1]
4 params = [1,1,1,1,1]
5 numpy.set_printoptions(threshold=10)
6 model1 = np.asarray(func(t,Kd,n,d2,k2,k3))
7 #model1 = np.asarray(func(t,d2,k2,k3))
8 print(len(model1))
9 #print(model1)
10
11 #a,b,c,d,e,f,g = params
12 a,b,c,d,e = params
13
14 ydata = np.asarray(new)
15 print(len(ydata))
16
17 ssr = np.sum((ydata-model1)**2)
18 #ssr2 = np.sum((ydata-model2)**2)
19 sst = np.sum((ydata - np.mean(ydata))**2)
20 R2 = 1 - ssr/sst
21 #R2_2 = 1 - ssr2/sst
22
23 print('R2 is: ', R2)
24 #print(R2_2)
```

102

102

R2 is: -0.9635287440508797

```

In [9]: pp = PdfPages('multipage.pdf')
        ydata = np.asarray(new)

        #condition = [1,2,3,4,5,6,7,8,9]
        for i in range(2):
            model = tester(t,Kd,n,d2,k2,k3,i)
            #model = tester(t,d2,k2,k3,i)

            #print(model)
            #a,b,c,d,e,f,g= params
            a,b,c,d,e= params

            plt.plot(t,model,'.', label = 'model')
            #print(model)
            #t = np.linspace(0,34800, num=6961)
            #raw = rawdata[0:13920:240]
            plt.plot(t,raw[i],'.',label = 'data')
            #print(rawdata[i])
            plt.legend()
            pp.savefig()
            plt.show()

pp.close

```

-----  
**NameError**

Traceback (most recent call last)


Cell In[9], line 17

```

13 plt.plot(t,model,'.', label = 'model')
14 #print(model)
15 #t = np.linspace(0,34800, num=6961)
16 #raw = rawdata[0:13920:240]
---> 17 plt.plot(t,raw[i],'.',label = 'data')
18 #print(rawdata[i])
19 plt.legend()

```

**NameError**: name 'raw' is not defined



In [ ]: