



Secure Collaborative Document Editor

Master's in Segurança Informática

June 3, 2025

Diogo Teixeira, up202408889

Guilherme Coutinho, up202108872

Leandro Costa, up202408816

Group **Salpicos De Aquarela**

Contents

1	Project Overview	2
2	Architecture Documentation	3
2.1	System Architecture	3
2.1.1	Project Structure (Site Map)	3
2.1.2	Component Relationships	4
2.1.3	Security Layers	5
2.1.4	Dependencies	5
2.1.5	Configuration Files	6
2.2	Database Design	6
2.3	API Documentation	7
2.3.1	Authentication Endpoints	7
2.3.2	Document Endpoints	8
2.3.3	Invitation Endpoints	10
2.3.4	Security Considerations	11
3	Security Analysis	12
3.1	GitHub Workflows	12
3.1.1	Jobs Breakdown	12
3.2	Security Development Tools	15
3.2.1	DOMPurify	15
3.2.2	The EJS template framework	15
3.2.3	better-sqlite3	15
3.3	Pentest Executed	16
3.3.1	Client Side	16
3.3.2	Server Side	17
3.3.3	Business/Code Logic Flaws	19
4	Conclusion and Future Work	21

1 Project Overview

The developed application is a **secure, collaborative document editor** that enables multiple authenticated users to create, manage, and edit shared documents in real-time. The project prioritizes both functionality and security by combining real-time collaboration features with strict access control mechanisms.

The system adopts a modular architecture, built on a Node.js backend with the Express framework and SQLite for data persistence. The frontend leverages EJS templates to render dynamic views. Core functionalities include user registration and authentication, role-based document collaboration, invitation management, and real-time document editing using WebSockets. The application enforces distinct roles for document owners, editors, and read-only collaborators, ensuring secure and structured access to content.

Security is a cornerstone of the project. Several layers of protection have been implemented:

- **Input sanitization** is performed using **DOMPurify** on both the client and server sides to mitigate **XSS (Cross-Site Scripting)** risks.
- **Passwords** are securely hashed using cryptographic algorithms before storage.
- **WebSocket communication** includes authentication and permission checks to prevent unauthorized access during live editing sessions.

To support secure development practices, the project integrates a CI/CD pipeline using GitHub Actions. This pipeline automates static code analysis, linting, and dependency auditing using tools such as ESLint, Horusec, Semgrep, and npm audit. Additionally, Docker hardening is enforced through Checkov to ensure secure container configurations.

Overall, this application demonstrates a comprehensive approach to building a secure, collaborative web platform, adhering to modern software engineering and security best practices.

2 Architecture Documentation

2.1 System Architecture

2.1.1 Project Structure (Site Map)

The project features a modular directory structure that separates server-side logic, client-side views, utilities, and configuration files. The `src` directory contains core backend logic, including route definitions, middleware, database operations, and utility modules. The `views` directory holds EJS templates for rendering dynamic HTML pages, while static assets like client-side JavaScript are in the `static` folder. The `db.sqlite` file serves as the embedded database, and `package.json` defines project dependencies and scripts for development and deployment.

```
project/
  src/
    index.js           # Main application entry point
    database.js        # Database configuration and queries
    middlewares.js     # Express middleware functions
    text_editor.js     # Text editor component
    routes/
      auth.js          # Authentication routes
      documents.js     # Document management routes
      invites.js       # Invitation management routes
      main.js          # Main application routes
    utils/
      auth.js          # Authentication utilities
      crypto.js        # Cryptographic functions
      sanitize.js      # Input sanitization
  views/
    layouts/           # Layout templates
    errors/            # Error pages
    document.ejs       # Document view
    documents.ejs      # Documents list
    document_options.ejs # Document settings
    invites.ejs        # Invitations view
    login.ejs          # Login page
```

```
register.ejs      # Registration page
home.ejs         # Home page
static/          # Static assets
js/              # Client-side JavaScript
db.sqlite        # SQLite database
package.json     # Project dependencies
```

2.1.2 Component Relationships

Server-Side Components

- **Main Application (index.js):** Initializes the Express application, configures middleware, sets up routes, and launches the WebSocket server.
- **Database Layer (database.js):** Manages SQLite configuration and CRUD operations for users, documents, collaborations, and invitations.
- **Route Handlers:**
 - `auth.js`: Handles user authentication and session management.
 - `documents.js`: Manages documents and collaboration logic.
 - `invites.js`: Manages sending and receiving invitations.
 - `main.js`: Handles general routes (e.g., homepage, fallback).
- **Utilities:**
 - `auth.js`: Helper functions for authentication.
 - `crypto.js`: Password hashing and cookie generation.
 - `sanitize.js`: Input sanitization and XSS prevention.

Client-Side Components

- **EJS Views:**
 - `document.ejs`: Real-time editor interface.
 - `documents.ejs`: Lists owned and collaborated documents.
 - `document_options.ejs`: Document configuration page.
 - `invites.ejs`: Interface to manage invitations.
 - `login.ejs` / `register.ejs`: Authentication forms.

- **WebSocket Events:** Used for document synchronization, live updates, and collaborator presence tracking.

2.1.3 Security Layers

Authentication Layer: The application uses sessions and cookies to authenticate users, ensuring that only valid sessions can access protected features. Passwords are securely stored using cryptographic hashing functions, preventing direct retrieval even if the database is compromised.

Authorization Layer: Access to documents and features is enforced through middleware that checks user permissions. The system distinguishes between owners, editors, and read-only collaborators, maintaining a consistent and secure permission model.

Input Validation Layer: All client inputs are validated and sanitized. DOMPurify is used to prevent XSS attacks, and SQL queries are parameterized to mitigate injection risks. This protects both the integrity of the system and the users' data.

WebSocket Security: Connections require authentication during the initial handshake and are subject to ongoing permission checks during document editing. This prevents unauthorized users from accessing or modifying shared content in real-time.

2.1.4 Dependencies

Server-Side: The server relies on several core dependencies to provide its functionality. The `express` framework is used to handle routing and middleware in a modular and efficient way. For data persistence, the application uses `better-sqlite3`, an embedded database engine offering synchronous and performant SQLite access. Real-time communication is handled by `socket.io`, which enables bi-directional WebSocket support. The server-side rendering of views is done through the `ejs` template engine. Session management is facilitated by `cookie-parser`, while input sanitization and XSS prevention are ensured using `dompurify`.

Client-Side: On the client side, the application uses `socket.io-client` to establish and maintain WebSocket connections with the server, enabling real-time collaborative editing. Views are rendered using EJS templates, allowing dynamic data to be injected directly into HTML on the server before being sent to the client.

2.1.5 Configuration Files

The project includes several important configuration files. The `package.json` file outlines the project dependencies and defines the scripts for development and deployment. A `Dockerfile` is used to specify the environment and instructions for building the application into a containerized image. Finally, the `.gitignore` file excludes sensitive or unnecessary files, such as the database, local environment settings, and node modules, from version control to maintain repository cleanliness and security.

2.2 Database Design




Figure 1: Database Design

The database schema supports secure collaboration on shared documents and consists of four main entities: **users**, **documents**, **invites**, and **collaborations**. Each user has a unique identifier, `username`, and a hashed `password`. The **documents** table includes an `owner_id`, `title`, `content`, and a flag `isPublic` for accessibility. There is a one-to-many relationship from users to their owned documents.

The **collaborations** table establishes a many-to-many relationship between users and documents, linking `user_id` to `document_id` and including an `isEditor` flag for permission levels.

The `invites` table manages collaboration requests, recording `document_id`, `sender_id`, and `receiver_id` for tracking invitations.

2.3 API Documentation

2.3.1 Authentication Endpoints

This section documents the RESTful API provided by the system, organized by functionality. All endpoints follow a clear authentication model and return appropriate HTTP status codes. Unless otherwise noted, endpoints require the user to be authenticated.

GET /login Renders the login page.

POST /login Authenticates a user.

- **Request Body:**

- `username`: string
- `password`: string

- **Responses:**

- Success: Redirects to `/documents`
- Error: Renders login page with error message

- **Status Codes:**

- 401: Invalid credentials

GET /register Renders the user registration page.

POST /register Registers a new user.

- **Request Body:**

- `username`: string
- `password`: string

- **Responses:**

- Success: Redirects to `/login`
- Error: Renders registration page with error message

- **Status Codes:**

- 401: Username already exists

GET /logout Logs out the current user and redirects to the login page.

2.3.2 Document Endpoints

GET /documents Lists all documents owned by or shared with the user.

- **Response:** Renders `documents.ejs` with:
 - `documents`: Array of owned documents
 - `collaboratedDocuments`: Array of shared documents

POST /documents/create Creates a new document.

- **Request Body:**
 - `title`: string
- **Response (JSON):**
 - Success: { `documentId`: number, `message`: string }
 - Error: { `error`: string }
- **Status Codes:**
 - 400: Invalid title

GET /documents/:id Retrieves a specific document.

- **Response:** Renders `document.ejs`
- **Status Codes:**
 - 400: Invalid document ID
 - 403: Access denied
 - 404: Document not found

GET /documents/:id/options Shows document settings and collaborators.

- **Response:** Renders `document_options.ejs`
- **Status Codes:**
 - 400: Invalid document ID
 - 403: Not document owner
 - 404: Document not found

POST /documents/:id/delete Deletes a document.

- **Response (JSON):**
 - Success: { `message`: string }

- Error: { error: string }

- **Status Codes:**

- 400: Invalid document ID
- 403: Not document owner
- 404: Document not found

POST /documents/:id/invite Sends a collaboration invite.

- **Request Body:**

- username: string

- **Response (JSON):**

- Success: { message: string }
- Error: { error: string }

- **Status Codes:**

- 400: Invalid input
- 403: Not document owner
- 404: Document or user not found

POST /documents/:id/visibility-change Toggles public visibility of a document.

- **Response (JSON):**

- Success: { message: string, isPublic: boolean }
- Error: { error: string }

- **Status Codes:**

- 400: Invalid document ID
- 403: Not document owner
- 404: Document not found

POST /documents/:id/collaborator-permission-change Updates a collaborator's permissions.

- **Request Body:**

- username: string

- **Response (JSON):**

- Success: { message: string }

- Error: { `error:` `string` }

- **Status Codes:**

- 400: Invalid input
- 403: Not document owner
- 404: Document not found

2.3.3 Invitation Endpoints

GET /invites Lists all pending collaboration invitations.

POST /invites/accept Accepts a pending invite.

- **Request Body:**

- `invite_id`: number

- **Responses:**

- Success: Redirects to the corresponding document
- Error: Renders error page

- **Status Codes:**

- 400: Invalid invite ID
- 403: Not invite recipient
- 404: Invite not found

POST /invites/decline Declines a pending invite.

- **Request Body:**

- `invite_id`: number

- **Response (JSON):**

- Success: { `message:` `string` }
- Error: { `error:` `string` }

- **Status Codes:**

- 400: Invalid invite ID
- 403: Not invite recipient
- 404: Invite not found

2.3.4 Security Considerations

The web application implements several essential security measures to ensure strong protection of user data and functionality.

First, access to the application is strictly controlled: only the login and registration endpoints are publicly available, while all other routes require proper authentication. To reduce the risk of injection attacks, all user input is carefully sanitized before processing. Furthermore, user passwords are never stored in plain text; instead, they are securely hashed using industry-standard cryptographic algorithms, which enhances protection against credential theft. The application also enforces strict access control policies, ensuring that users can only interact with documents they are authorized to access. Lastly, safeguard against Cross-Site Request Forgery (CSRF) attacks is provided through the use of session tokens, which validate the origin of requests and help maintain the integrity of user sessions.

Collectively, these measures contribute to a secure and resilient application architecture.

3 Security Analysis

3.1 GitHub Workflows

As part of a robust Secure Software Development Lifecycle (SSDLC), this project integrates GitHub Actions to enforce continuous security and code quality validation throughout the development process. The security.yml workflow is automatically triggered on every push or pull request to the main branch and orchestrates a set of independent jobs, each targeting a specific aspect of software assurance. Its core objective is proactively identifying and mitigating potential security and quality issues before code reaches production.

3.1.1 Jobs Breakdown

Horusec A static code analysis tool that helps identify security vulnerabilities in source code across multiple languages. In our workflow, we execute Horusec using the ‘fike/horusec-action’ GitHub Action, which is configured via a dedicated ‘horusec-config.json’ file and applied to the entire project directory. By identifying issues such as hardcoded secrets and insecure functions early in development, Horusec enabled us to refactor insecure logic, particularly regarding critical, high and medium vulnerabilities.

```

54 Language: Leaks
55 Severity: CRITICAL
56 Line: 47
57 Column: 47
58 SecurityTool: HorusecEngine
59 Confidence: MEDIUM
60 File: /github/workspace/project/src/routes/auth.js
61 Code: word === 'string' || username.length === 0 || password.length === 0 {
62 RuleID: HS-LEAKS-26
63 Type: Vulnerability
64 ReferenceHash: 2a2d51506d4d503c61da056de10ceb5059d757fb395e3e7d72f27ecb65a
65 Details: (1/1) * Possible vulnerability detected: Hard-coded password
66 The software contains hard-coded credentials, such as a password or cryptographic key, which it uses for its own inbound authentication, outbound communication to external components, or encryption of internal data. For more
67 Information checkout the Cve-798 (https://cve.mitre.org/data/definitions/798.html) advisory.
68 =====
69
70 Language: JavaScript
71 Severity: HIGH
72 Line: 146
73 Column: 8
74 SecurityTool: HorusecEngine
75 Confidence: MEDIUM
76 File: /github/workspace/project/public/js/main.js
77 Code: document.addEventListener('DOMContentLoaded', () => {
78 RuleID: HS-JAVASCRIPT-11
79 Type: Vulnerability
80 ReferenceHash: 5b5f0e17622c02a3158030721cfdab3fa462713fc37e827e9c7682116fd4546
81 Details: (1/1) * Possible vulnerability detected: Origins should be verified during cross-origin communications
82 Browsers allow message exchanges between Window objects of different origins. Because any window can send / receive messages from other window it is important to verify the sender's / receiver's identity: When sending message with
83 postMessage method, the identity's receiver should be defined the wildcard keyword (*) should not be used).
84 When receiving message with message event, the sender's identity should be verified using the origin and possibly source properties. For more information checkout the OWAASP A2:2017 (https://owasp.org/www-project-top-ten/2017/A2\_2017-Broken\_Authentication) and (https://developer.mozilla.org/en-US/docs/Web/API/Window/postMessage) advisory.

```

Figure 2: Horusec Analysis - High and Critical vulnerabilities

eslint ESLint is a linter for JavaScript and TypeScript that enforces coding standards and helps detect common bugs. In our project, we run ESLint after installing dependencies to ensure consistent style rules across the codebase and to avoid unsafe coding patterns. ESLint has been instrumental in maintaining code quality, catching potential logic errors, and promoting best coding practices.

It identified a significant number of code style violations across several project files. The most common issues included the inconsistent use of double quotes (") instead of the configured standard of single quotes (') for string literals, as well as several missing semicolons at the end of statements. These violations were found in core files such as index.js, route handlers like auth.js and documents.js, and utility modules including auth.js and crypto.js.

```
113 /home/runner/work/tp-salpicos-de-aquarela/tp-salpicos-de-aquarela/project/src/routes/main.js
114 Error: 6:12 error Strings must use singlequote quotes
115 Error: 7:16 error Strings must use singlequote quotes
116 Error: 10:12 error Strings must use singlequote quotes
117 Error: 12:16 error Strings must use singlequote quotes
118
119 /home/runner/work/tp-salpicos-de-aquarela/tp-salpicos-de-aquarela/project/src/utlis/auth.js
120 Error: 1:39 error Strings must use singlequote quotes
121 Error: 2:30 error Strings must use singlequote quotes
122 Error: 2:41 error Missing semicolon semi
123 Error: 7:46 error Strings must use singlequote quotes
124 Error: 13:2 error Missing semicolon semi
125 Error: 15:34 error Missing semicolon semi
126
127 /home/runner/work/tp-salpicos-de-aquarela/tp-salpicos-de-aquarela/project/src/utlis/crypto.js
128 Error: 1:24 error Strings must use singlequote quotes
129 Error: 4:39 error Strings must use singlequote quotes
130 Error: 8:45 error Strings must use singlequote quotes
131 Error: 8:72 error Strings must use singlequote quotes
132 Error: 11:17 error Strings must use singlequote quotes
133 Error: 13:13 error Strings must use singlequote quotes
134 Error: 22:25 error Strings must use singlequote quotes
```


Figure 3: Some ESLint errors flagged

code-quality The ‘npm audit’ command is utilized in this job to scan project dependencies for known vulnerabilities, comparing them against the official npm advisory database. This process provides actionable insights into security issues stemming from third-party packages. By swiftly identifying and patching vulnerable packages, some with high-severity issues, we effectively reduced risks associated with the software supply chain and enhanced the security of our application stack.

```
✓ Run npm audit
1 ▶ Run npm audit --production
4 npm warn config production Use '--omit=dev' instead.
5 found 0 vulnerabilities
```

Figure 4: nmp audit run

dependency-check We used ‘npm outdated’ in the dependency-check job to identify lagging packages. This is crucial for both leveraging new features and ensuring critical security fixes are applied. The job helps us maintain long-term code health by alerting us to outdated dependencies, allowing for proactive planning of updates that prevent long-term technical debt or potential security liabilities.




	Package	Current	Wanted	Latest	Location	Depended by
5	better-sqlite3	9.6.0	9.6.0	11.10.0	node_modules/better-sqlite3	project
6	body-parser	1.20.3	1.20.3	2.2.0	node_modules/body-parser	project
7	eslint	9.27.0	9.28.0	9.28.0	node_modules/eslint	project
8	express	4.21.2	4.21.2	5.1.0	node_modules/express	project
9	sanitize-html	2.16.0	2.17.0	2.17.0	node_modules/sanitize-html	project

Figure 5: nmp outdated run

Semgrep/ci Employs semantic pattern matching to uncover security issues, anti-patterns, and logic bugs in our code. It provided insights beyond those of traditional linters, identifying complex security issues such as hardcoded credentials and unvalidated inputs. This enabled us to detect non-trivial bugs that may not have been caught otherwise, enhancing our confidence in the application's resilience.

Checkov A static analysis tool focused on infrastructure as code (IaC) that helps identify misconfigurations in Dockerfiles. By running Checkov against the 'project/' directory, we were able to detect insecure deployment settings early on.

It triggered the policy CKV_DOCKER_2, which ensures that every container image includes a HEALTHCHECK instruction. This is crucial for reducing downtime and improving observability, allowing us to detect failed containers early and helping orchestrators like Kubernetes respond to unhealthy services. Additionally, the application was running with the default root user, which needed to be fixed.



```

250 Check: CKV_DOCKER_2: "Ensure that HEALTHCHECK instructions have been added to container images"
251 FAILED for resource: /Dockerfile.
252 File: /Dockerfile:1-21
253 Guide: https://docs.prismacloud.io/en/enterprise-edition/policy-reference/docker-policies/docker-policy-index/ensure-that-healthcheck-instructions-have-been-added-to-container-images
254
255 1 | FROM node:16-alpine3.19
256 2 |
257 3 | WORKDIR /app
258 4 |
259 5 | COPY package*.json ./
260 6 |
261 7 | RUN apt-get update -y && \
262 8 |   apt-get install -y sqlite3
263 9 |
264 10 | RUN npm ci
265 11 |
266 12 | COPY ./src ./src
267 13 | COPY ./views ./views
268 14 | COPY ./static ./static
269 15 |
270 16 | ENV PORT=1337
271 17 | EXPOSE $PORT
272 18 |
273 19 | ENV OPENSSL_CONF=/dev/null
274 20 |
275 21 | CMD ["npm", "start"]
276
277 Error: Process completed with exit code 1.

```

Figure 6: Checkov Analysis on HEALTHCHECK

```

1 RUN addgroup --system appgroup && adduser --system --ingroup appgroup appuser
2 ...
3 HEALTHCHECK --interval=30s --timeout=10s --start-period=5s --retries=3 \

```

```
4 CMD wget --quiet --spider http://localhost:1337/ || exit 1
5
6 RUN chown -R appuser:appgroup /app
7
8 USER appuser
```

Listing 1: Proceeded fixes onto the Dockerfile

3.2 Security Development Tools

3.2.1 DOMPurify

DOMPurify is a widely-used JavaScript library that sanitizes HTML to prevent XSS (Cross-Site Scripting) attacks. It accomplishes this by parsing and cleaning HTML input to eliminate any potentially harmful code, such as script tags or malicious event handlers.

We used the tool in the code like this:

```
DOMPurify.sanitize(input,
  {
    ALLOWED_TAGS: [],
    ALLOWED_ATTR: []
  }
);
```

We set **ALLOWED_TAGS** and **ALLOWED_ATTR** as an empty array, saying that we want **DOMPurify** to remove every HTML tag and attribute that it encounters. This way, no kind of XSS is going to be possible in our application.

3.2.2 The EJS template framework

DOMPurify only removes HTML tags, so it does not prevent **SSTI (Server Side Template Injection)** attacks. By default, **EJS** escapes user input by default using

$$< \% = \% >$$

So, we made sure that every template generated with user input used this tag.

3.2.3 better-sqlite3

We used the **Node.js** package **better-sqlite3** as our database manager. This package helps us perform safe, synchronous SQL parameterized queries (also called prepared statements).


3.3 Pentest Executed

As the developers of this project, we have full access to the entire codebase and a deep understanding of its logic and data flow. In this section, we will describe how we conducted a **White Box Penetration Test** on our application.

3.3.1 Client Side

XSS - Cross-Site Scripting


To test for XSS, we used a simple payload like in Figure 7 in the create document form as the document's title.



The screenshot shows a dark-themed web interface titled "Create a Document". Below the title is a text input field containing the payload: `testetesteeee2`. Below the input field is a prominent red button labeled "Create".

Figure 7: XSS attempt on Create Document

To analyze better the request being sent, we used **Burp Suite's Interceptor** to capture it and analyze it. As we can observe in Figure 8, the title field does not have the HTML tag with the malicious event handler, because **DOMPurify** was able to clean it.



The screenshot displays the "Request" tab in Burp Suite. It shows an intercepted HTTP POST request to `/documents/create`. The request headers include `Host: localhost:1337`, `Content-Length: 20`, `sec-ch-ua-platform: "Linux"`, `Accept-Language: en-US,en;q=0.9`, `sec-ch-ua: "Not.A/Brand";v="99", "Chromium";v="136"`, `Content-Type: application/x-www-form-urlencoded`, `sec-ch-ua-mobile: ?0`, and `User-Agent: Mozilla/5.0 (X11; Linux x86_64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/136.0.0.0 Safari/537.36`. The request body is `title=testetesteeee2`, where the payload has been cleaned by DOMPurify.

Figure 8: Intercepted Request of XSS attempt on Create Document

Even though, the payload was already wiped before the request was sent, we can change the data being sent to the server again and put the same payload on the title field and forward the intercepted request.

Good thing that we also use **DOMPurify** on the backend and the HTML tag is also going

to cleaned up again as we can see by the server's response and the title of the created document on Figure 9:




Figure 9: Response of XSS attempt on Create Document

3.3.2 Server Side

SSTI

Even though we previously mentioned that we are using EJS's special tag that escapes tags, we obviously still needed to test if we missed something and if it was indeed vulnerable to SSTI attacks. These attacks are on the server side because the template is going to be generated on the server side and then sent in the response.

We followed the same behavior as in the XSS attacks and sent payloads like the one in Figure 10 in every field that was going to be reflected on the page.




Figure 10: SSTI attempt on Create Document

Another place where this input is reflected is in the user's invites page, where we tell the user the title of the document he has been invited to. As we can see by looking at Figure 11, the payload was also sanitized.




Figure 11: SSTI attempt reflected on the Invites page

SQL Injection

An SQL Injection occurs when user input is unsafely included in a SQL query, meaning that the input is interpreted as part of the SQL command, not just as data.

We tried to attempt this on our Login page sending the payload seen in Figure 12.




Figure 12: SQLi attempt on Login page

As expected, we received the response "Invalid username".

We already mentioned the usage of **better-sqlite3**, that allows us to perform safe parametrized queries like this one:

```
db.prepare('SELECT * FROM users WHERE username = ?').get(username);
```

This way, SQLite treats the provided input by the user as a literal string, not as part of the SQL logic.

Every developer should implement their code like this, and never interpolate user input directly into SQL strings.

3.3.3 Business/Code Logic Flaws

One of the main causes for vulnerabilities in the web and reports on Bug Bounty programs are **Business/Code Logic flaws**. An application must have a strong data flow logic to prevent attacks, a simple attack like sending 2 requests in opposite order might be enough to break the system's logic.

On our github repository is a Python script on the **tests** folder that tests for IDORs (Insecure Direct Object Reference) and Broken Access Controls. The tests consist of creating three accounts on the application and performing multiple actions that should not be done, like trying to change a document's visibility or deleting the document as a user that is not the owner, attempting to access private documents as a user that is not a collaborator, etc.

In Figure 13 is a print of the output of the performed security tests showing that all tests passed:

```
🚀 Starting Security Tests
=====
Setting up test users...
User 1 login status: 200
User 2 login status: 200
User 3 login status: 200
Users setup!

=== Testing Document Privacy ===
Attempting to view a private document as a non-collaborator
✔ PASS: Account 2 was denied access to private document

=== Testing Document Permissions ===
Testing the document's options security

Attempt to change the document's visibility as a non-owner
✔ PASS: Account 2 was denied to change document visibility

Attempt to invite another user to the document as a non-owner
✔ PASS: Account 2 was denied to inviting other users

Attempt to delete the document as a non-owner
✔ PASS: Account 2 was denied to deleting the document

=== Testing Collaboration Permissions ===
Attempt to change a collaborator's editing permission as a non-owner
✔ PASS: Non-owner was denied to changing collaboration editing permissions

=====
🚩 TEST RESULTS SUMMARY
=====
✔ PASS: Document Privacy
✔ PASS: Document Permissions
✔ PASS: Collaboration Permissions

Total: 3/3 tests passed
🎉 All security tests passed!
```

Figure 13: Security tests output

4 Conclusion and Future Work

The development of this secure collaborative document editor showcased the combination of real-time functionality with robust security practices. We focused on modularity, maintainability, and secure software engineering. The application features role-based access, real-time collaboration via WebSockets, and strong input validation. We successfully implemented a CI/CD pipeline with automated security tools to uphold best practices throughout the development lifecycle.

Built with Node.js, Express, SQLite, and EJS templates, the architecture is efficient and easy to deploy. Key security elements, including XSS protection with DOMPurify, secure password hashing, CSRF protection, and WebSocket permission enforcement were validated through internal analysis and penetration testing. GitHub Actions, using tools like ESLint, Horusec, and Semgrep, helped maintain code quality.

Future Work

Although the project achieved its main goals, there are opportunities for improvement and the addition of new features:

- **Scalability:** Transitioning to PostgreSQL for better performance with more users.
- **Authorization Granularity:** Introducing finer access control options.
- **Version Control:** Adding document versioning and edit history for rollback capabilities.

In summary, this project provides a solid foundation for secure collaborative platforms, with potential to evolve into a production-ready solution for various environments.