INTERNATIONAL UNIVERSITY

DEPARTMENT OF PHYSICS

REPORT
MIDTERM PROJECT

Lecturer: Truong Thi Ngoc Phuong

LIBRARY RESOURCE MANAGEMENT SYSTEM

Students 's Name:

Le Vo Anh Thu – SESEIU24024

TABLE OF CONTENTS

1. INTRODUCTION & PROBLEM ANALYSIS.....2
2. CLASS IDENTIFICATION & ARCHITECTURAL OVERVIEW.....3
3. ATTRIBUTES, METHODS & BEHAVIORS..... 4
4. OBJECT-ORIENTED DESIGN PRINCIPLES & JUSTIFICATION.....6
5. DATA ENCAPSULATION & STATE INVARIANT PROTECTION.....7
6. SWIFTUI IMPLEMENTATION & EXPERIMENTAL DEMONSTRATION..... 8
7. CONCLUSION & COMPLIANCE..... 15

FIGURE

Figure 1: Complete UML Class Diagram of the University Library Resource Management System.....4
Figure 2: Main catalog list interface displaying diverse resource categories, availability statuses, and role-selection controls..... 10
Figure 3: Successful physical book checkout and dynamic deposit/fee calculation.....11
Figure 4: Role-based fee waiver and concurrent seat allocation for digital learning materials..... 12
Figure 5: Validation failure alert triggered by exceeding maximum loan duration on short-loan items..... 13
Figure 6: State invariant protection alert rejecting illegal return of an available resource..... 15

1. INTRODUCTION & PROBLEM ANALYSIS

1. System Overview & Context

Modern university libraries host heterogeneous learning resources ranging from physical books and rare periodicals to digital online repositories. Managing these diverse assets necessitates a robust software architecture capable of tracking resource availability, validating circulation policies, preventing unauthorized state modification, and calculating dynamic borrowing fees.

This project delivers an object-oriented domain model and a native iOS application built with Swift and SwiftUI. The architecture coordinates three fundamental resource categories: **Printed Books**, **Academic Journals**, and **Digital Learning Materials**. The system enforces data integrity through strict encapsulation, models domain interactions via inheritance and dynamic polymorphism, and provides a reactive user interface demonstrating both valid workflows and error-handling mechanisms.

2. Key Design Assumptions & Operational Constraints

To resolve the deliberately open-ended requirements of the specification, the following concrete business rules and assumptions have been defined:

- **User Roles & Discount Policies:** Borrowers belong to one of two roles: `Student` or `Lecturer`. Lecturers receive fee waivers for digital access and discounted daily overdue rates ($0.50/day vs. $1.00/day for students).
- **Loan Duration Constraints:** Standard printed books permit borrowing periods up to 21 days. Books cataloged under the *Short-Loan Reserve* collection are capped at a maximum of 3 days. Any request exceeding 3 days for a short-loan item is strictly rejected.
- **Circulation Restrictions on Periodicals:** Academic journals designated as *Reference-Only* (`isReferenceOnly == true`) are restricted entirely to internal library reading rooms and cannot be borrowed under any circumstances.
- **Virtual Resource Governance:** Digital learning materials do not physically leave the library and incur no overdue penalties. Instead, access is governed by license validity dates (`currentDate <= licenseExpiration`) and simultaneous seat thresholds (`activeSeats < maxSeats`).
- **Deposit Requirements:** Printed books require an upfront refundable deposit upon borrowing ($5.00 for standard books, $10.00 for short-loan books) to ensure asset recovery.

2. CLASS IDENTIFICATION & ARCHITECTURAL OVERVIEW

1. Core Domain Entity Identification

The domain architecture employs a shared base class taxonomy complemented by specialized subclasses and encapsulated enumerations.




Figure 1: Complete UML Class Diagram of the University Library Resource Management System.

2. Class Responsibilities & Allocation

2.1. Base Class: LibraryResource: Represents the abstract root of all library assets. It encapsulates persistent identity (`id`), bibliographic attributes (`title`,`publicationYear`), reference indicators (`isReferenceOnly`), and the dynamic state tracker (`status`). It exposes template methods for borrowing, returning, and fee evaluation.

2.2. Subclass: PrintedBook: Extends `LibraryResource` by modeling physical monographs. It maintains physical catalog numbers (`isbn`), creator metadata (`author`), and loan classification (`isShortLoan`), while overriding borrowing validation and fee calculation.

2.3. Subclass: AcademicJournal: Extends `LibraryResource` by managing serial metadata (`volume`, `issue`). It enforces in-library circulation constraints and applies strict daily overdue penalties to encourage timely returns of scholarly serials.

2.4. Subclass: DigitalMaterial: Extends `LibraryResource` to govern virtual assets. It tracks concurrent user seats (`maxSeats`, `activeSeats`) and license expiration timestamps (`licenseExpiration`), handling online session check-in and check-out.

3. **Supporting Data Types & State Models**
   3.1. Circulation Lifecycle: BorrowStatus: A Swift enumeration modeling item availability: `.available`, `.borrowed(dueDate: Date, borrowerId: String)`,`.referenceOnly`, and `.licenseExpired`.
   3.2. Access Levels: UserRole: An enumeration (`.student`, `.lecturer`) establishing borrower privileges and financial discount calculations.
   3.3. Error Boundaries: LibraryError: A custom enumeration conforming to `LocalizedError` providing typed, descriptive failure cases for business logic violations.
   3.4. State Repository / ViewModel: LibraryStore: An `ObservableObject` acting as the central data store and ViewModel, supplying seed data and publishing state updates to SwiftUI views.

3. ATTRIBUTES, METHODS & BEHAVIORS

1. Shared Attributes & Lifecycle Methods (Base Layer)

The base class `LibraryResource` defines the core data contracts shared across all entities:

- **Stored Properties:**
  - `let id: UUID` — Unique catalog identifier.
  - `let title: String` — Title of the resource.
  - `let publicationYear: Int` — Year of publication.
  - `let isReferenceOnly: Bool` — Indicates if the item is restricted to internal reading.
  - `private(set) var status: BorrowStatus` — Encapsulated lifecycle state.
- **Computed Properties:**
  - `var isAvailable: Bool` — Checks whether `status == .available`.

    - `var typeTag: String` — Human-readable tag identifying the resource category.
- **Lifecycle Methods:**
    - `borrow(by: UserRole, days: Int) throws` — Validates availability and transitions status to `.borrowed`.
    - `returnResource() throws` — Validates borrowed state and resets status to `.available`.
    - `calculateFee(days: Int, overdueDays: Int, role: UserRole) -> Double` — Polymorphic hook returning total costs.

2. **Specialized Attributes & Domain Logic (Subclass Layer)**

- **`PrintedBook`:**
    - Additional attributes: `author: String`, `isbn: String`, `isShortLoan: Bool`.
    - Overridden `borrow(...)`: Enforces `days <= 3` if `isShortLoan` is true.
- **`AcademicJournal`:**
    - Additional attributes: `volume: Int`, `issue: Int`.
    - Overridden `borrow(...)`: Disallows borrowing if `isReferenceOnly` is active.
- **`DigitalMaterial`:**
    - Additional attributes: `licenseExpiration: Date`, `maxSeats: Int`, `private(set) var activeSeats: Int`.
    - Specialized methods: `accessOnline() throws` and `releaseOnline()`.

3. **Polymorphic Fee Calculation Rules**

The method `calculateFee(...)` dynamically resolves calculations at runtime:

$$\text{PrintedBook Fee} = \text{Deposit} + (\text{Overdue Days} \times \text{Daily Rate})$$

Where Deposit is $10.00 (short loan) or $5.00 (standard loan). Daily overdue rate is $1.00 for students and $0.50 for lecturers.

AcademicJournal Fee=Overdue Days×$3.00(if borrowable; otherwise $0.00)

$$\text{DigitalMaterial Fee} = \begin{cases} \$0.00 & \text{if Lecturer} \\ \$2.50 & \text{if Student} \end{cases}$$

4. OBJECT-ORIENTED DESIGN PRINCIPLES & JUSTIFICATION

1. Class Hierarchy & Inheritance Justification

An inheritance hierarchy is justified because `PrintedBook`, `AcademicJournal`, and `DigitalMaterial` inherently exhibit an **"IS-A"** relationship with `LibraryResource`. They share common lifecycles, identifiers, and state requirements.Inheritance eliminates code duplication and permits SwiftUI to hold heterogeneous resources in a unified collection:

```
@Published var resources: [LibraryResource] = []
```

2. Dynamic Dispatch & Method Overriding

Polymorphism is realized through Swift's dynamic table dispatch. When `calculateFee(...)` or `borrow(...)` is invoked on an instance of `LibraryResource`, the runtime resolves the call to the corresponding subclass implementation without requiring brittle type inspections (`is` or `as?` checks):

```
let fee = resource.calculateFee(days: requestedDays, overdueDays: simulatedOverdue, role: userRole)
```

3. Architectural Trade-offs: Inheritance vs. Protocols & Composition

Suitability of Inheritance: Inheritance cleanly aligns with the current academic catalog taxonomy. Base behaviors (`returnResource`, `status` management) are reused across all subclasses without boilerplate.

When Protocols & Composition are Preferable: If the library system expands to manage physical non-literary assets (e.g., `StudyRoom`, `LaptopHardware`, `3DPrinter`), these facilities cannot logically inherit from `LibraryResource`. In that scenario, decomposing behaviors into granular Swift protocols (such as `Loanable`,

`FeeChargeable`, and `SeatTrackable`) combined via composition would prevent deep, fragile class hierarchies.

4. **Extensibility & Open/Closed Principle (OCP)**

The design respects the Open/Closed Principle: the architecture is open for extension but closed for modification.Introducing a new resource category (such as `AudioBook` or `Microfilm`) requires creating a new subclass of `LibraryResource` and overriding `calculateFee(...)` or `borrow(...)`, requiring zero modifications to existing classes or UI views.

5. DATA ENCAPSULATION & STATE INVARIANT PROTECTION

1. **Identification of Critical Domain Data**

Direct external manipulation of the following attributes would corrupt system integrity:

- Mutating `status` directly to `.available` while a resource is actively borrowed.
- Incrementing or decrementing `activeSeats` in digital materials arbitrarily.
- Overwriting `dueDate` or borrowing parameters without business rule checks.

2. **Swift Access Control Strategy (`private` & `private(set)`)**

The system enforces language-level access boundaries:

- `private(set) var status: BorrowStatus`: Views and controllers can read the status to update UI states, but mutations are restricted strictly to the internal logic of `borrow()` and `returnResource()`.
- `private(set) var activeSeats: Int`: Ensures concurrent seat counters can only increment via `accessOnline()` and decrement via `releaseOnline()`.

3. **State Transition Validation & Exception Handling**

Every state transition is guarded by explicit precondition validations throwing `LibraryError`:

- Returning an available item throws `LibraryError.itemNotBorrowed`.
- Borrowing an already loaned item throws `LibraryError.alreadyBorrowed(dueDate:)`.
- Borrowing a reference periodical throws `LibraryError.referenceOnlyItem`.
- Requesting >3>3 days on a short-loan book throws `LibraryError.invalidLoanPeriod(maxDays: 3)`.
- Accessing an expired digital asset throws `LibraryError.licenseExpired`.
- Exceeding digital concurrent seats throws `LibraryError.concurrencyLimitReached(limit:)`.

6. SWIFTUI IMPLEMENTATION & EXPERIMENTAL DEMONSTRATION

1. Architecture & MVVM Pattern Overview



Figure 2: *Main catalog list interface displaying diverse resource categories, availability statuses, and role-selection controls.*

The application follows Apple's standard Model-View-ViewModel (MVVM) architecture:

- **Model:** Domain classes (`LibraryResource` hierarchy) and value models (`BorrowStatus`, `UserRole`,`LibraryError`).
- **ViewModel:** `LibraryStore` conforming to `ObservableObject`, managing the catalog state and broadcasting updates via `@Published`.
- **View:** `ContentView` (master list with user role segmented picker) and `ResourceDetailView` (catalog inspection, fee simulator, and circulation actions).

2. Valid Operations Demonstration

2.1. Physical Resource Borrowing & Return




Figure 3: *Successful physical book checkout and dynamic deposit/fee calculation.*

User Action: Select an available standard book, specify 14 loan days, and tap "Mượn Tài Nguyên".

Observed Result: The status updates immediately to `Đang được mượn`. Tapping "Trả Tài Nguyên (Hợp lệ)" clears the checkout and resets the status badge to `Sẵn sàng`.

2.2. Digital Seat Management & Concurrency Tracking

User Action: Open an active digital material (e.g., *Cơ sở dữ liệu Vệ tinh Landsat*) with 0/2 seats used and tap "Truy Cập Trực Tuyến".

Observed Result: The counter updates to 1/2 seats used. Tapping "Kết Thúc Phiên Truy Cập" restores the count to 0/2.

2.3. Dynamic Role-Based Fee Recalculation




Figure 4: *Role-based fee waiver and concurrent seat allocation for digital learning materials.*

User Action: Adjust the overdue stepper from 0 to 5 days and toggle the user role picker between `Sinh viên` and `Giảng viên`.

Observed Result: The total fee recalculates reactively in the UI via dynamic dispatch.

3. Invalid Operations & Rejection Demonstration (Screenshots & Analysis)

3.1. Short-Loan Duration Violation




Figure 5: *Validation failure alert triggered by exceeding maximum loan duration on short-loan items.*

Trigger: Select a short-loan book (*Tài liệu Dự bị Không gian*), set the loan duration stepper to 5 days, and tap "Mượn Tài Nguyên".

Rejection Message: An alert displays: *"Vượt quá thời gian mượn tối đa cho phép (3 ngày)."*

3.2. Reference-Only Circulation Rejection

Trigger: Open a reference journal (*Tạp chí Vật lý Địa cầu & Vũ trụ*). The borrow button is disabled in the UI; programmatic invocation triggers `LibraryError.referenceOnlyItem`.

3.3. Expired License Access Rejection

Trigger: Open an expired digital material (*Kho lưu trữ Viễn thám Cũ*) and tap "Truy Cập Trực Tuyến".

Rejection Message: An alert displays: *"Bản quyền tài liệu điện tử đã hết hạn. Truy cập bị từ chối."*

3.4. Illegal State Transition: Returning an Available Resource



Figure 6: *State invariant protection alert rejecting illegal return of an available resource.*

Trigger: Tap the deliberate testing button "Thao Tác Sai: Cố tình trả khi chưa mượn" on an available resource.

Rejection Message: An alert displays: *"Không thể trả tài nguyên chưa từng được mượn."*

4. Xcode Project Setup & iOS Simulator Execution Guide

- Launch **Xcode** (version 15.0 or later).
- Open the project folder or `.xcodeproj` file.
- Ensure the deployment target is configured to **iOS 16.0** or later.
- Select an active iOS Simulator device (e.g., **iPhone 15 Pro**).
- Press **`Cmd + R`** to compile and run the application.

7. CONCLUSION & COMPLIANCE

1. Project Summary & Reflection

The project successfully realizes an extensible, maintainable, and robust library resource management system. By combining domain-driven object-oriented principles (inheritance, polymorphism, access control) with modern declarative UI paradigms (SwiftUI and MVVM), the application satisfies all operational and architectural requirements.

2. Grading Rubric Compliance Checklist

[x] **Class Identification & Responsibilities (2.0 pts):** Base class, 3 subclasses, and supporting enumerations clearly identified and justified.

[x] **Attributes & Methods (2.0 pts):** Shared attributes separated from specialized attributes; complete methods defined.

[x] **Inheritance & Polymorphism (2.0 pts):** Inheritance tree justified; polymorphic fee calculations and protocol trade-offs thoroughly analyzed.

[x] **Encapsulation & Validation (2.0 pts):** Direct modification prevented via `private(set)`; all state changes validated through typed errors.

[x] **SwiftUI Implementation & Demonstration (2.0 pts):** Complete Xcode SwiftUI project provided, demonstrating valid flows and visible error rejection alerts.