

Many of the slides in this lecture are either from or adapted from slides provided by the authors of the textbook "Computer Systems: A Programmer's Perspective," 2nd Edition and are provided from the website of Carnegie-Mellon University, course 15-213, taught by Randy Bryant and David O'Hallaron in Fall 2010. These slides are indicated "Supplied by CMU" in the notes section of the slides.

Stacks and Functions (1)

```
int main(int argc, char *argv[]) {
  char buf[1024];
  int res, a1, a2, a3, a4;

  ...

  res = sub1(a1, a2);
  a3 = res +1;

  ...

  res = sub2(a2, a3, a4);
  res += 6;

  ...

  return 0;
}
```



main's "context"

Stacks and Functions (2)

```
int sub1(int x, int y) {
  int array[24];
  int i;

  ...

  for (i=0; i<24; i++)
    array[i] = fib[i];

  ...

  return sub10(24, array);
}
```



sub1's "context"

Stacks and Functions (3)

```
int fib(int x) {
  if (x < 2)
    return x;
  else
    return fib(x-1)+fib(x-2);
}
```



fib's "context"

Stacks and Functions (4)

```
int fib(int x) {
  if (x < 2)
    return x;
  else
    return fib(x-1)+fib(x-2);
}
```



fib's "context"



Supplied by CMU.



Supplied by CMU.



Supplied by CMU.

Procedure Control Flow

- Use stack to support procedure call and return
- Procedure call: `call sub`
  - push return address on stack
  - jump to *sub*
- Return address:
  - address of the next instruction after call
  - example from disassembly

```
804854e:  e8 3d 06 00 00     call   8048b90 <sub>
8048553:  50                 pushl  %eax
```

  - return address = `0x8048553`
- Procedure return: `ret`
  - pop address from stack
  - jump to address

Supplied by CMU.



Supplied by CMU.



Supplied by CMU.

Passing Arguments

```
int x;
int res;
int main() {
  ...
  res = subr(3, x);
  ...
}
```

```
main:
  ...
  pushl x
  pushl $3
  call subr
  movl %eax,res
  ...
```



Retrieving Arguments

```
int subr(int a, int b) {
  return a + b;
}
```

```
subr:
  pushl %ebp
  movl %esp, %ebp
  movl 12(%ebp), %eax
  addl 8(%ebp), %eax
  popl %ebp
  ret
```



Space for Local Variables

```
int subr(int a, int b) {
  int array[20];
  ...
}
```

```
subr:
  pushl %ebp
  movl %esp, %ebp
  subl $80, $esp
  ...
  addl $80, $esp
  popl %ebp
  ret
```





The *leave* instruction causes the contents of ebp to be copied into esp, thereby removing everything from the stack that had been pushed into the frame. It then pops the current stack top (the old ebp) into the ebp register. The effect of *leave* is thus to return to the caller's stack frame.

There is an *enter* instruction that has the same effect as that of the first three instructions of subr combined (it has an operand that indicates how much space for local variables to allocate). However, it's not used by gcc, apparently because it's slower than doing it as shown in the slide.

Register-Saving Conventions

- When procedure `yoo` calls `who`:
  - `yoo` is the *caller*
  - `who` is the *callee*
- Can registers be used for temporary storage?

```
yoo:
    • • •
    movl $33, %edx
    call who
    addl %edx, %eax
    • • •
    ret
```

```
who:
    • • •
    movl 8(%ebp), %edx
    addl $32, %edx
    • • •
    ret
```

  - contents of register `%edx` overwritten by `who`
  - this could be trouble: something should be done!
    - » need some coordination

Supplied by CMU.



Supplied by CMU.

IA32/Linux+Windows Register Usage

- `%eax`, `%edx`, `%ecx`
  - caller saves prior to call if values are used later
- `%eax`
  - also used to return integer value
- `%ebx`, `%esi`, `%edi`
  - callee saves if wants to use them
- `%esp`, `%ebp`
  - special form of callee-save
  - restored to original values upon exit from procedure

Supplied by CMU.

Register-Saving Example

```
yoo:
    ...
    movl $33, %edx
    pushl %edx
    call who
    popl %edx
    addl %edx, %eax
    ...
    ret
```

```
who:
    ...
    pushl %ebx
    ...
    movl 4(%ebp), %ebx
    addl %53, %ebx
    movl 8(%ebp), %edx
    addl $32, %edx
    ...
    popl %ebx
    ...
    ret
```


Supplied by CMU.



Supplied by CMU.



Supplied by CMU.

Recursive Call #2

```
/* Recursive popcount */
int pcount_r(unsigned x) {
  if (x == 0)
    return 0;
  else return
    (x & 1) + pcount_r(x >> 1);
}
```

```
     . . .
    movl  $0, %eax
    testl %ebx, %ebx
    je  .L3
     . . .
.L3:
     . . .
    ret
```

- **Actions**
  - **if x == 0, return**
    - » **with `%eax` set to 0**



Supplied by CMU.



Supplied by CMU.

Recursive Call #4

```
/* Recursive popcount */
int pcount_r(unsigned x) {
  if (x == 0)
    return 0;
  else return
    (x & 1) + pcount_r(x >> 1);
}
```

```
  . . .
movl    %ebx, %edx
andl    $1, %edx
leal   (%edx,%eax), %eax
  . . .
```

- **Assume**
  - `%eax` **holds value from recursive call**
  - `%ebx` **holds x**
- **Actions**
  - **compute (x & 1) + computed value**
- **Effect**
  - `%eax` **set to function result**



Supplied by CMU.



Supplied by CMU.

Observations About Recursion

- Handled without special consideration
  - stack frames mean that each function call has private storage
    - » saved registers & local variables
    - » saved return pointer
  - register-saving conventions prevent one function call from corrupting another's data
  - stack discipline follows call / return pattern
    - » if P calls Q, then Q returns before P
    - » last-in, first-out
- Also works for mutual recursion
  - P calls Q; Q calls P

Supplied by CMU.

Pointer Code

Generating Pointer

```
/* Compute x + 3 */
int add3(int x) {
  int localx = x;
  incrk(&localx, 3);
  return localx;
}
```

Referencing Pointer

```
/* Increment value by k */
void incrk(int *ip, int k) {
  *ip += k;
}
```

- **`add3` creates pointer and passes it to `incrk`**

Supplied by CMU.



Supplied by CMU.

Creating Pointer as Argument

```
int add3(int x) {
  int localx = x;
  incrk(&localx, 3);
  return localx;
}
```

- **Use leal instruction to compute address of localx**



Middle part of add3

```
  movl $3, 4(%esp)   # 2nd arg = 3
  leal -4(%ebp), %eax# &localx
  movl %eax, (%esp)  # 1st arg = &localx
  call incrk
```


Supplied by CMU.

Retrieving local variable

```
int add3(int x) {
  int localx = x;
  incrk(&localx, 3);
  return localx;
}
```

- Retrieve localx from stack as return value



Final part of add3

```
movl -4(%ebp), %eax # Return val= localx
leave
ret
```


Supplied by CMU.

IA 32 Procedure Summary

- **Important Points**
  - stack is the right data structure for procedure call / return
    - » if P calls Q, then Q returns before P
- **Recursion (& mutual recursion) handled by normal calling conventions**
  - can safely store values in local stack frame and in callee-saved registers
  - put function arguments at top of stack
  - result return in `%eax`
- **Pointers are addresses of values**
  - on stack or global



Supplied by CMU.

Why Bother with a Frame Pointer?

- It points to the beginning of the stack frame
  - making it easy for people to figure out where things are in the frame
  - but people don't execute the code ...
- The stack pointer always points somewhere within the stack frame
  - it moves about, but the compiler knows where it is pointing
    - » a local variable might be at 8(%rsp) for one instruction, but at 16(%rsp) for a subsequent one
    - » tough for people, but easy for the compiler
- Thus the frame pointer is superfluous
  - it can be used as a general-purpose register



Supplied by CMU.

x86-64 Registers

- Arguments passed to functions via registers
  - if more than 6 integral parameters, then pass rest on stack
  - these registers can be used as caller-saved as well
- All references to stack frame via stack pointer
  - eliminates need to update `%ebp/%rbp`
- Other registers
  - 6 callee-saved
  - 2 caller-saved
  - 1 return value (also usable as caller-saved)
  - 1 special (stack pointer)

Supplied by CMU.

Note that the *leave* instruction is no longer relevant, since %rbp does not contain the address of the stack frame.

Also note that the conventions shown in the slide are those adopted by gcc on Linux; they aren't necessarily used by other compilers or on other operating systems. Even gcc doesn't use these conventions if optimization is completely turned off (in which case arguments are passed on the stack, just as for IA32).

x86-64 Long Swap

```
void swap_l(long *xp, long *yp)
{
  long t0 = *xp;
  long t1 = *yp;
  *xp = t1;
  *yp = t0;
}
```

```
swap:
   movq   (%rdi), %rdx
   movq   (%rsi), %rax
   movq   %rax, (%rdi)
   movq   %rdx, (%rsi)
   ret
```

- Operands passed in registers
  - first (xp) in %rdi, second (yp) in %rsi
  - 64-bit pointers
- No stack operations required (except ret)
- Avoiding stack
  - can hold all local information in registers



Supplied by CMU.

x86-64 Locals in the Red Zone

```
/* Swap, using local array */
void swap_a(long *xp, long *yp)
{
    volatile long loc[2];
    loc[0] = *xp;
    loc[1] = *yp;
    *xp = loc[1];
    *yp = loc[0];
}
```

```
swap_a:
  movq  (%rdi), %rax
  movq  %rax, -24(%rsp)
  movq  (%rsi), %rax
  movq  %rax, -16(%rsp)
  movq  -16(%rsp), %rax
  movq  %rax, (%rdi)
  movq  -24(%rsp), %rax
  movq  %rax, (%rsi)
  ret
```

- **Avoiding stack-pointer change**
  - **can hold all information within small window beyond stack pointer**
    - » **128 bytes**



Supplied by CMU.

The *volatile* keyword tells the compiler that it may not perform optimizations on the associated variable, such as storing it strictly in registers and not in memory. It's used primarily in cases where the variable might be modified via other routines that aren't apparent when the current code is being compiled. We'll see useful examples of its use later. Here it's used simply to ensure that *loc* is allocated on the stack, thus giving us a simple example of using local variables stored on the stack.

The issue here is whether a reference to memory beyond the current stack (as delineated by the stack pointer) is a legal reference. On IA32 it is not, but on x86-64 it is, as long at the reference is not more than 128 bytes beyond the end of the stack.

x86-64 NonLeaf without Stack Frame

```
/* Swap a[i] & a[i+1] */
void swap_ele(long a[], int i)
{
    swap(&a[i], &a[i+1]);
}
```

- No values held while swap being invoked
- No callee-save registers needed
- `rep` instruction inserted as no-op
  - based on recommendation from AMD
    - » can't handle transfer of control to ret

```
swap_ele:
   movslq %esi,%rsi              # Sign extend i
   leaq   8(%rdi,%rsi,8), %rax   # &a[i+1]
   leaq   (%rdi,%rsi,8), %rdi    # &a[i] (1st arg)
   movq   %rax, %rsi             # (2nd arg)
   call   swap
   rep                           # No-op
   ret
```


Supplied by CMU.

x86-64 Stack Frame Example

```
long sum = 0;
/* Swap a[i] & a[i+1] */
void swap_ele_su
  (long a[], int i)
{
    swap(&a[i], &a[i+1]);
    sum += (a[i]*a[i+1]);
}
```

- Keeps values of `&a[i]` and `&a[i+1]` in callee-save registers
  - rbx and rbp
- Must set up stack frame to save these registers
  - else clobbered in swap

```
swap_ele_su:
    movq    %rbx, -16(%rsp)
    movq    %rbp, -8(%rsp)
    subq    $16, %rsp
    movslq  %esi,%rax
    leaq    8(%rdi,%rax,8), %rbx
    leaq    (%rdi,%rax,8), %rbp
    movq    %rbx, %rsi
    movq    %rbp, %rdi
    call    swap
    movq    (%rbx), %rax
    imulq   (%rbp), %rax
    addq    %rax, sum(%rip)
    movq    (%rsp), %rbx
    movq    8(%rsp), %rbp
    addq    $16, %rsp
    ret
```


Supplied by CMU.

Note that sum is a global variable. While its exact location in memory is not known by the compiler, it will be stored in memory at some location just beyond the end of the executable code (which is known as “text”). Thus the compiler can refer to sum via the instruction pointer. The actual displacement, i.e., the distance from the current target of the instruction pointer and the location of sum, is not known to the compiler, but will be known to the linker, which will fill this displacement in when the program is linked. This will all be explained in detail in two or three weeks.

Understanding x86-64 Stack Frame

```
swap_ele_su:
    movq    %rbx, -16(%rsp)         # Save %rbx
    movq    %rbp, -8(%rsp)          # Save %rbp
    subq    $16, %rsp               # Allocate stack frame
    movslq  %esi,%rax               # Extend i
    leaq    8(%rdi,%rax,8), %rbx    # &a[i+1] (callee save)
    leaq    (%rdi,%rax,8), %rbp     # &a[i]   (callee save)
    movq    %rbx, %rsi              # 2nd argument
    movq    %rbp, %rdi              # 1st argument
    call    swap
    movq    (%rbx), %rax            # Get a[i+1]
    imulq   (%rbp), %rax            # Multiply by a[i]
    addq    %rax, sum(%rip)         # Add to sum
    movq    (%rsp), %rbx            # Restore %rbx
    movq    8(%rsp), %rbp           # Restore %rbp
    addq    $16, %rsp               # Deallocate frame
    ret
```


Supplied by CMU.

Understanding x86-64 Stack Frame

```
movq    %rbx, -16(%rsp)        # Save %rbx
movq    %rbp, -8(%rsp)         # Save %rbp
```




```
subq    $16, %rsp              # Allocate stack frame
```

• • •




```
movq    (%rsp), %rbx           # Restore %rbx
movq    8(%rsp), %rbp          # Restore %rbp

addq    $16, %rsp              # Deallocate frame
```


Supplied by CMU.

Interesting Features of Stack Frame

- Allocate entire frame at once
  - all stack accesses can be relative to `%rsp`
  - do by decrementing stack pointer
  - can delay allocation, since safe to temporarily use red zone
- Simple deallocation
  - increment stack pointer
  - no base/frame pointer needed

Supplied by CMU.

x86-64 Procedure Summary

- Heavy use of registers
  - parameter passing
  - more temporaries since more registers
- Minimal use of stack
  - sometimes none
  - allocate/deallocate entire block
- Many tricky optimizations
  - what kind of stack frame to use
  - various allocation techniques

Supplied by CMU.

Tail Recursion

```
int factorial(int x) {
  if (x == 1)
    return x;
  else
    return
      x*factorial(x-1);
}
```

```
int factorial(int x) {
  return f2(x, 1);
}

int f2(int a1, int a2) {
  if (a1 == 1)
    return a2;
  else
    return
      f2(a1-1, a1*a2);
}
```


The slide shows two implementations of the factorial function. Both use recursion. In the version on the left, the result of each recursive call is used within the invocation that issued the call. In the second, the result of each recursive call is simply returned. This is known as *tail recursion*.

No Tail Recursion (1)



Here we look at the stack usage for the version without tail recursion. Note that we have as many stack frames as the value of the argument; the results of the calls are combined after the stack reaches its maximum size.

No Tail Recursion (2)



Tail Recursion



With tail recursion, since the result of the recursive call is not used by the issuing stack frame, it's possible to reuse the issuing stack frame to handle the recursive invocation. Thus rather than push a new stack frame on the stack, the current one is written over. Thus the entire sequence of recursive calls can be handled within a single stack frame.

Code: gcc –O1

```
f2:
        movl    %esi, %eax
        cmpl    $1, %edi
        je      .L5
        subq    $8, %rsp
        movl    %edi, %esi
        imull   %eax, %esi
        subl    $1, %edi
        call    f2        # recursive call!
        addq    $8, %rsp
.L5:
        rep
        ret
```


This is the result of compiling the tail-recursive version of factorial using gcc with the –O1 flag. This flags turns on a moderate level of code optimization, but not enough to cause the stack frame to be reused.

Code: gcc –O2

```
f2:
        cmpl    $1, %edi
        movl    %esi, %eax
        je      .L8
.L12:
        imull   %edi, %eax
        subl    $1, %edi
        cmpl    $1, %edi
        jne     .L12
.L8:
        rep
        ret
```

loop!

Here we've compiled the program using the –O2 flag, which turns on additional optimization (at the cost of increased compile time), with the result that the recursive calls are optimized away — they are replaced with a loop.

Why not always compile with –O2? For "production code" that is fully debugged (assuming this is possible), this is a good idea. But this and other aggressive optimizations make it difficult to relate the runtime code with the source code. Thus, a runtime error might occur at some point in the program's execution, but it is impossible to determine exactly which line of the source code was in play when the error occurred.