



An IoT-Enabled System for Real-Time Fuel Monitoring, GPS Tracking, and Anomaly
Detection in Trucks Using Non-Parametric Unsupervised Machine Learning

A Thesis Proposal
Presented to the Faculty of the
Department of Electronics and Computer Engineering
Gokongwei College of Engineering
De La Salle University

In Partial Fulfillment of the
Requirements for the Degree of
Bachelor of Science in Computer Engineering

by
BARJA Samuelle P.
CASTELO Konrad Romel C.
DE LA ROSA Eliza Rica R.
MONTEMAYOR Alyssa S.

June, 2026



ABSTRACT

The logistics and transportation industry continues to face challenges in fuel management, anomaly detection, and real-time fleet monitoring. Existing solutions often operate in silos, resulting in fragmented data, undetected fuel irregularities, and delayed maintenance responses. This study developed and evaluated an IoT-based, context-aware fleet monitoring system that acquires real-time fuel level via OBD-II, tracks GPS location, and detects anomalous fuel consumption in trucks using non-parametric unsupervised machine learning models, including Matrix Profile and Isolation Forest. The system leverages CAN Bus/OBD-II interfacing for ECU fuel data, GPS modules for location logging, LoRa and GSM modules for reliable IoT-based communication, and embedded alert hardware for driver rest and maintenance notifications. Sensor and vehicle data are synchronized and transmitted to a cloud-based dashboard where anomalies are automatically flagged, and actionable alerts are generated. The system will be evaluated in real-world driving scenarios to measure detection accuracy, false positive rates, and response latency. This integrated platform aims to enhance operational safety, improve fuel efficiency, and enable proactive, data-driven fleet management decisions. Three user-facing interfaces were delivered: an embedded in-truck HMI for drivers, a mobile driver web application for companion GPS and trip-state synchronisation, and an administrative dashboard for SGSA fleet monitoring.

Index Terms—Fuel Monitoring, GPS Tracking, Anomaly Detection, Internet Of Things, Unsupervised Model Learning, Isolation Forest, Matrix Profile



41

TABLE OF CONTENTS

42

Abstract	ii
-----------------	-----------

43

Table of Contents	iii
--------------------------	------------

44

List of Figures	vi
------------------------	-----------

45

List of Tables	vii
-----------------------	------------

46

Abbreviations and Acronyms	viii
-----------------------------------	-------------

47

Notations	ix
------------------	-----------

48

Glossary	x
-----------------	----------

49

Chapter 1 INTRODUCTION	1
-------------------------------	----------

50

1.1 Background of the Study	2
---------------------------------------	---

51

1.2 Prior Studies	6
-----------------------------	---

52

1.2.1 Research Gaps Identified	8
--	---

53

1.2.2 to Address the Gaps	9
-------------------------------------	---

54

1.3 Problem Statement	10
---------------------------------	----

55

1.4 Objectives and Deliverables	12
---	----

56

1.4.1 General Objective (GO)	12
--	----

57

1.4.2 Specific Objectives (SOs)	13
---	----

58

1.4.3 Expected Deliverables	14
---------------------------------------	----

59

1.5 Expected Deliverables per Objective	14
---	----

60

1.6 Significance of the Study	16
---	----

61

1.6.1 Technical Benefit	16
-----------------------------------	----

62

1.6.2 Social Impact	17
-------------------------------	----

63

1.6.3 Environmental Welfare	17
---------------------------------------	----

64

1.7 Assumptions, Scope, and Delimitations	18
---	----

65

1.7.1 Assumptions	18
-----------------------------	----

66

1.7.2 Scope	20
-----------------------	----

67

1.7.3 Delimitations	21
-------------------------------	----

68

1.8 Description and Methodology	23
---	----

69

1.9 Research Dissemination Plan	24
---	----

70

1.10 Conflict of Interest	26
-------------------------------------	----



71	1.11 Estimated Work Schedule and Budget	26
72	1.11.1 Gantt Chart	26
73	1.11.2 Estimated Budget	28
74	1.12 Overview of the Thesis Proposal	28
75	Chapter 2 LITERATURE REVIEW	30
76	2.0.1 Literature Review	31
77	2.1 Existing Work	32
78	2.1.1 Vehicle Tracking and Fuel Sensing Technologies	32
79	2.1.2 LoRa Technology	34
80	2.1.3 LoRa Gateway	35
81	2.1.4 Technical Performance Metrics and Environmental Factors	36
82	2.1.5 Real-World Implementation: LoRa-Based Telemetry and Fleet	
83	Management Systems	37
84	2.1.6 GSM and LTE Technologies	37
85	2.1.7 Anomaly Detection	42
86	2.1.8 Machine Learning Applications	44
87	2.2 Comparison of Commercial Fleet Management Systems	49
88	2.3 Lacking in the Approaches	51
89	2.4 Summary	55
90	Chapter 3 THEORETICAL CONSIDERATIONS	57
91	3.1 Overview	58
92	3.2 Theoretical Foundations	58
93	3.2.1 Cyber-Physical Systems (CPS)	58
94	3.2.2 Sensor Theory and Signal Measurement	59
95	3.2.3 Time-Series Synchronization Theory	59
96	3.2.4 IoT Communication Theory	60
97	3.2.5 GPS Temporal and Spatial Theory	60
98	3.2.6 Unsupervised Anomaly Detection Theory	61
99	3.2.6.1 Matrix Profile Theory	61
100	3.2.6.2 Isolation Forest Theory	61
101	3.3 Summary	62
102	Chapter 4 DESIGN CONSIDERATIONS	63
103	4.1 Standards	64
104	4.1.1 Adherence to Technical Standards	64
105	4.1.2 Observance of Research Ethics	66
106	4.2 Technical Design Considerations	68
107	4.2.1 Hardware Selection and Integration	68



108	4.2.2 Software Architecture	69
109	4.2.3 Machine Learning and Algorithms	70
110	4.2.4 Communication and Security	70
111	4.3 Alternative Software Designs and Cost Considerations	71
112	4.4 Summary	72
113	Chapter 5 METHODOLOGY	73
114	5.1 System Architecture and Conceptual Design	77
115	5.2 Implementation	80
116	5.2.1 Data Acquisition and Preprocessing	80
117	5.2.2 System Methodology	86
118	5.2.3 Anomaly Detection and ML Methodology	86
119	5.2.4 IPO Chart and Design Pipeline	87
120	5.2.5 IPO Chart	87
121	5.3 Evaluation	89
122	5.4 Summary	90
123	References	92



124

LIST OF FIGURES

125	1.1	Individul Gantt Chart for Barja	26
126	1.2	Individul Gantt Chart for Castelo	27
127	1.3	Individul Gantt Chart for De La Rosa	27
128	1.4	Individul Gantt Chart for Montemayor	27
129	2.1	PRISMA Diagram	31
130	2.2	Globe GSM (pink) and LTE (orange) Coverage Map Philippines (GSMA	
131		Intelligence)	39
132	2.3	Smart GSM (pink) and LTE (orange) Coverage Map Philippines (GSMA	
133		Intelligence)	40
134	5.1	Proposed Conceptual Diagram	77
135	5.2	Proposed System Architecture Diagram	79
136	5.3	IPO Chart	88



137

LIST OF TABLES

138	1.1	List of Prior Studies	6
139	1.2	Expected Deliverables per Objective	14
140	1.3	Detailed Budget Breakdown for the Project	28
141	2.1	Comparison between GSM and LTE	41
142	2.2	Summary of Existing Works	46
143	2.3	Comparison of Commercial Fleet Management Systems	50
144	2.4	Identified Gaps, Limitations, and Proposed Solutions	52
145	4.1	Alternative Software Designs Evaluated for the Prototype	72
146	5.1	Summary of methods for reaching the objectives	74



147

ABBREVIATIONS

148

GSM Global Systems For Mobile Communications 5

149

IOT Internet Of Things 5

150

RFID Radio Frequency Identification 4



151

NOTATION

152	L	data transmission latency	90
153	TP	true positive	89
154	FP	false positive	89
155	TN	true negative	89
156	FN	false negative	89
157	T_{detected}	timestamp when an anomaly is detected	90
158	T_{actual}	timestamp of actual anomaly occurrence	90



159

GLOSSARY

160

cloud analytics

Data analysis performed on cloud-based platforms, enabling real-time access to fleet data (e.g., GPS and fuel metrics) and supporting informed decision-making.

161

deep learning

A subset of machine learning involving deep neural networks with multiple layers. Used in predictive analytics and anomaly detection in real-time fleet systems.

162

fleet management

The administration and coordination of commercial vehicle operations, including monitoring of fuel use, driver behavior, vehicle maintenance, and routing.

163

Isolation Forest

An unsupervised machine learning algorithm for anomaly detection that isolates outliers based on random partitioning of data points.

164

Matrix Profile

A time-series data mining method used for pattern recognition and anomaly detection in sequential datasets like fuel usage over time.

165

unsupervised machine learning

A type of machine learning where the model learns patterns from unlabeled data. Useful for anomaly detection where normal vs. abnormal behavior is not predefined.



De La Salle University

166

Chapter 1

167

INTRODUCTION



1.1 Background of the Study

The transportation and logistics industry is a critical driver of economic development but is increasingly facing operational inefficiencies and security challenges, especially in fuel management and vehicle tracking. Fuel theft, inaccurate fuel monitoring, inefficient routing, and lack of real-time data remain persistent issues for fleet operators, particularly in developing countries. These challenges are exacerbated by the absence of scalable, integrated technological systems that provide reliable data-driven solutions [Ahmed et al., 2017, Alquhali et al., 2019, Crisgar et al., 2021].

Fuel is one of the most substantial and recurring expenses in logistics operations, with its accurate monitoring being essential to maintaining profitability and operational efficiency. Even minor inconsistencies in fuel tracking—such as errors in manual readings, unreported consumption, or unnoticed leakage—can accumulate into significant losses over time. Komal Shoukat Ali et al. (2018) [Komal Shoukat Ali et al., 2018] report that fuel-related fraud and inefficiencies can contribute up to 30% of the total operational overhead in large fleet operations. These losses are often compounded by issues such as unauthorized vehicle use, fuel siphoning, and unoptimized driving routes, which not only drive up fuel costs but also disrupt delivery schedules, vehicle maintenance cycles, and driver accountability. Despite efforts to manage these concerns, many logistics providers continue to rely on fragmented or outdated systems that offer limited visibility into fuel-related metrics and driver behavior [Dhivyasri and Mariappan, 2015, Obikoya, 2014].

These pressures are especially acute in the Philippine setting, where fleet operations contend with some of the most severe road and logistics conditions in the region. The Japan International Cooperation Agency estimates that traffic congestion costs Metro Manila



roughly PHP 3.5 billion per day, a figure projected to reach PHP 5.4 billion per day by 2035 without intervention [Japan International Cooperation Agency, 2022, Japan International Cooperation Agency, 2025]. Logistics operations are further constrained by congestion at the Port of Manila, which has operated at roughly 94% utilization against an ideal of about 80%, and by regulatory measures such as the 2014 Manila truck ban, which the Philippine Institute for Development Studies estimated caused around PHP 43.85 billion in economic losses and doubled container trucking costs [Patalinghug et al., 2015b, Llanto, 2017, Patalinghug et al., 2015a]. Compounding these conditions, fuel fraud and adulteration in the national supply chain have been estimated to cost up to USD 750 million annually [Asian Development Bank, 2016]. For trucks operating under such conditions, prolonged idling, stop-and-go consumption, and route variability are routine rather than exceptional, which makes fixed-threshold fuel-monitoring rules, calibrated for free-flowing conditions, especially unreliable.

In addition to financial implications, traditional fuel monitoring systems struggle to detect abnormal fuel consumption patterns in real time. These anomalies may be caused by aggressive or inefficient driving habits, extended engine idling, mechanical malfunctions (such as injector faults or fuel line leaks), or variable environmental conditions like terrain and traffic. However, without intelligent tools that correlate fuel data with contextual factors—such as vehicle speed, route topography, and time of day—fleet managers are often unable to distinguish between acceptable fuel use and problematic deviations. As highlighted by Mumcuoglu et al. (2023) [Mumcuoglu et al., 2023], conventional systems lack the sophistication to perform this level of analysis, leading to delayed detection of inefficiencies and reduced responsiveness. This underscores the urgent need for smart, data-driven solutions that combine fuel monitoring with GPS tracking and anomaly detection



models to proactively manage consumption and enhance overall fleet performance [Barbado and Corcho, 2022, Beteto et al., 2022, Fortela et al., 2023].

To address these problems, researchers and engineers are increasingly exploring the convergence of IoT, GPS, and AI—particularly machine learning—to develop smart, real-time monitoring systems [Alquhali et al., 2019, Joshi et al., 2024, Prabhu et al., 2022]. These systems aim to optimize fuel usage, enhance fleet security, and improve operational efficiency through automation and predictive analytics.

The transportation and logistics sector has attracted significant scholarly attention, particularly in the development of smart systems for operational efficiency and security. The academic literature reflects a growing interest in leveraging IoT, GPS, and AI technologies to enhance fleet management, particularly in areas such as fuel monitoring, vehicle tracking, and anomaly detection. Several studies in recent years have investigated IoT-enabled fuel monitoring, GPS tracking, and anomaly detection solutions [G et al., 2022, G, 2023, Patil and Patil, 2024, Prabhu et al., 2022, RS et al., 2024, S et al., 2024].

- **Intelligent IoT-Enabled Real-Time Monitoring System for Logistics Management:** Joshi et al. [Joshi et al., 2024] developed a hybrid logistics management system that integrates IoT sensors, GPS, Radio Frequency Identification (RFID), and cloud analytics. Their solution achieved real-time tracking of assets and vehicles, enhancing transparency and decision-making in logistics operations. However, the study was limited by the type of hardware used and did not include advanced AI components for anomaly detection.
- **Fuel Consumption Classification for Heavy-Duty Vehicles:** Mumcuoglu et al. [Mumcuoglu et al., 2023] employed machine learning to classify fuel consumption



anomalies based on naturalistic driving data from 57 trucks. With an accuracy of 92.2%, their approach effectively identified abnormal fuel consumption linked to driver behavior. Nevertheless, the dataset was relatively small (606 records), and integration with real-time vehicle diagnostics was not tested.

- **Development of an Intelligent Fuel Monitoring and Theft Detection System Equipped with GPS & GSM Integration:** Mathi et al. [Mathi et al., 2024] introduced an Internet of Things (IoT)-based solution combining resistance-based fuel level sensors, GPS, Global Systems for Mobile Communications (GSM), and real-time alarm mechanisms. Their system successfully monitored fuel and battery anomalies in hybrid vehicles but lacked higher-precision sensors and deep learning integration for smarter detection.

Despite these advancements, several limitations and research gaps remain:

- **Scalability Constraints:** Many existing solutions are limited to small-scale deployments or specific vehicle types (e.g., motorcycles, generators) and have not been validated for large truck fleets in diverse environments [RS et al., 2024, Tatababu et al., 2024].
- **Data and Sensor Limitations:** Several studies rely on basic sensors (resistance, ultrasonic) that may lack the accuracy and robustness needed for high-volume commercial operations. Furthermore, datasets used are often small or simulated, limiting generalizability [Nada, 2017, aut, 2019].
- **Fragmented Solutions:** Many systems only address a single issue — fuel monitoring, GPS tracking, or theft detection — without offering a comprehensive, unified solution



260 integrating these components using AI and IoT [G et al., 2022, Crisgar et al., 2021].

261 These gaps underline the need for a robust, scalable, and integrated IoT-enabled system

262 capable of monitoring fuel levels in real time, tracking vehicle location, and detecting

263 operational anomalies using machine learning algorithms. Such a system holds the poten-

264 tial to significantly reduce fuel fraud, enhance operational efficiency, and support more

265 informed decision-making in fleet management. This study focuses on designing and

266 implementing such a system within an active fleet operation, specifically addressing the

267 technical and logistical challenges encountered by commercial truck fleets operating across

268 varied conditions. By leveraging IoT sensors, GPS modules, and unsupervised machine

269 learning-based analytics, the proposed solution aims to deliver a comprehensive, automated,

270 and intelligent monitoring platform that advances the current landscape of smart logistics

271 technologies. Because partner HINO in the Philippines do not permit tank-cap or sender-

272 loom modifications on production trucks, any field-deployable monitoring approach must

273 be non-invasive. This constraint was the dominant driver of the acquisition-layer design

274 adopted in this study.

275 **1.2 Prior Studies**

TABLE 1.1 LIST OF PRIOR STUDIES

Literature Title (APA Citation)	Research Problem	Method	Results	Limitations
Intelligent IoT-Enabled Real-Time Monitoring System for Logistics Management [Joshi et al., 2024]	Logistics systems lack integration and real-time monitoring capabilities for secure and efficient operations.	Hybrid IoT-based logistics management combining sensors, GPS, RFID, and cloud analytics for real-time monitoring and decision-making.	Provides real-time tracking of assets, vehicles, and equipment.	Constrained by hardware type and limited test cases; lacks advanced AI for anomaly detection.



Literature Title (APA Citation)	Research Problem	Method	Results	Limitations
Real Time Automatic Vehicle Monitoring System Using IoT [G et al., 2022]	Lack of real-time vehicle tracking and passenger/driver identity verification in institutional transport.	Used RFID, GPS, and NodeMCU ESP8266 with cloud storage and mobile app.	Enabled real-time tracking of location, speed, and passenger count.	Limited to institutional use; lacks anomaly detection and commercial scalability.
GPS-Based Vehicle Tracking and Theft Detection Systems using Google Cloud IoT Core & Firebase [Crisgar et al., 2021]	Ineffective vehicle recovery due to delayed or limited GPS/GSM tracking.	Implemented GPS-based tracking using Google Cloud IoT Core, MQTT, Firebase, and PWA interface.	Enabled real-time vehicle tracking, theft detection, and remote monitoring.	Designed for passenger cars; may require hardware adaptation for trucks/fleets.
Fuel Quantity and Quality Detection in Automobiles Using IoT [RS et al., 2024]	Fuel fraud through inaccurate dispensing and poor fuel quality in motorcycles.	IoT-enabled fuel management using strain gauges and quality sensors with real-time display/logging.	Achieved accurate real-time quantity and quality measurement.	Designed for motorcycles; not validated for larger fleets.
Fuel Consumption Classification for Heavy-Duty Vehicles [Mumcuoglu et al., 2023]	Identifying abnormal fuel consumption due to driver behavior or system faults.	Machine learning models using driving data from 57 trucks, considering weight and road slope.	92.2% accuracy; F1 score 0.78 for outlier detection.	Dataset limited to 606 records; lacks real-time integration.
Automatic Fuel Tank Monitoring, Tracking & Theft Detection System [Komal Shoukat Ali et al., 2018]	Inefficiency of manual fuel monitoring.	Fuel sensors, Arduino, GSM, GPS, LabView for data logging.	Real-time monitoring, alerts for theft/leakage.	Tested on basic hardware; lacks advanced analytics and large-scale validation.
Development of an Intelligent Fuel Monitoring and Theft Detection System [Mathi et al., 2024]	Fuel theft and battery anomalies in hybrid/electric vehicles.	Resistance-based fuel sensor, voltage sensor, GPS, GSM, buzzer, LCD.	Reliable monitoring and anomaly detection.	Lacks advanced sensors for enhanced leak detection.
Unsupervised Machine Learning to Detect Impending Anomalies in Testing of Fuel Economy and Emissions [Fortela et al., 2023]	Impending anomalies in fuel economy and emissions testing of light-duty vehicles.	Unsupervised ML methods (PCA, K-Means, SOM) on 34,602 test samples.	Trend detection in large datasets.	Limited to historical datasets; not validated on real-time operational data.
Smart Fuel Monitoring System for Diesel Generator [Tatababu et al., 2024]	Fuel quantity indication and theft in generators.	Ultrasonic/capacitive sensors, flow sensors, GSM, GPS, intelligent theft detection.	Accurate real-time monitoring, theft prevention.	Findings specific to tested generators; limited generalizability.
Design and Implementation for Trucks Tracking System Using GPS Based on Semantic Web [Nada, 2017]	Inefficient GPS-based truck tracking for fleet management.	GPS tracking system integrated with semantic web platform.	Accurate location tracking and reporting via web interface.	Dependent on GSM/GPS reliability; lacks IoT integration and anomaly detection.



Literature Title (APA Citation)	Research Problem	Method	Results	Limitations
Automatic Fuel Monitoring System [aut, 2019]	Accurate fuel monitoring and theft prevention.	Fuel sensors and GSM module with SMS alerts.	Monitors fuel, triggers alarms, and sends GPS alerts.	Basic sensors; limited scalability and analytics in complex environments.
Interpretable Machine Learning Models for Vehicle Fuel Consumption Anomalies [Barbado and Corcho, 2022]	Detecting/explaining fuel anomalies in fleets to optimize usage.	Unsupervised anomaly detection combined with interpretable ML.	Up to 80% anomalous instances explained; potential fuel reduction up to 88%.	Only analyzed individual feature relevance; not fully integrated in real-time systems.

1.2.1 Research Gaps Identified

A review of existing literature in fuel monitoring and anomaly detection for logistics and fleet management reveals persistent gaps that point to a need for more robust, integrated solutions. Although many systems incorporate IoT elements—such as sensors, GSM, and GPS—these are often limited in scope, typically designed for specific applications like diesel generators or motorcycles, rather than being adaptable for broader fleet use.

For example, systems like the Smart Fuel Monitoring System for Diesel Generators [Tatababu et al., 2024] and the Automatic Fuel Monitoring System [aut, 2019] demonstrate basic real-time monitoring and theft detection capabilities. However, these systems heavily rely on elementary sensor technology and offer minimal integration with advanced analytics or anomaly detection methods. Similarly, the machine learning-based approach in [Mumcuoglu et al., 2023] was limited in its use of data and did not incorporate real-time or unsupervised learning techniques.

While [Barbado and Corcho, 2022] explored the potential of interpretable machine learning and unsupervised anomaly detection, their models were evaluated on constrained datasets and not integrated into real-time operational systems. [Fortela et al., 2023] also



demonstrated effective anomaly detection using unsupervised learning in emissions and fuel economy testing, but again, their data was static and gathered in controlled environments. These findings were not validated using on-vehicle, operational data, which limits their applicability in dynamic, real-world conditions.

Additionally, studies such as those by [Joshi et al., 2024] and [Nada, 2017] underscore the need for real-time GPS tracking in fleet operations, but they stop short of presenting a cohesive system that incorporates GPS, fuel monitoring, and intelligent anomaly detection into one unified platform.

The core research gap, therefore, lies in the absence of a fully integrated, real-time, IoT-based system that combines fuel monitoring, GPS tracking, and anomaly detection powered by unsupervised machine learning. Addressing this gap is vital to improving operational efficiency, fuel security, and predictive maintenance in modern fleet management.

1.2.2 to Address the Gaps

This study developed and evaluated an integrated IoT-based fleet monitoring system that unifies fuel level monitoring, GPS-based vehicle tracking, and unsupervised machine learning for anomaly detection. Unlike previous solutions that focus on isolated functions or static datasets, the developed system operated in real time using vehicle telemetry acquired through the OBD-II interface and GPS module. The prototype was evaluated using controlled-environment trip data and live telemetry data to assess fuel monitoring performance, anomaly detection capability, and communication latency.

The system architecture will incorporate scalable and cost-efficient components such as , GPS modules, and cloud-based transmission via mobile networks, ensuring compatibility with a variety of fleet vehicles and usage environments.



For anomaly detection, the system will employ unsupervised, non-parametric machine learning algorithms like Matrix Profile and Isolation Forest. These models excel in identifying outliers within time-series data without the need for labeled datasets—making them ideal for fleet scenarios where data behavior varies with routes, driver habits, or environmental conditions. Unlike traditional parametric approaches, non-parametric models are more flexible and adaptive, as they do not assume any fixed data distribution.

In addition, a context-aware dashboard will be developed to provide fleet managers with meaningful insights by correlating fuel usage patterns with routes and travel times. The dashboard will support real-time notifications such as driver rest alerts, maintenance prompts, and efficiency summaries—enabling data-informed decision-making and operational improvements.

By addressing the limitations of prior research—especially the lack of integration, real-time analysis, and adaptive anomaly detection—this study offers a practical and scalable solution for enhancing fuel management and fleet operations in dynamic environments.

1.3 Problem Statement

Efficient fuel monitoring and route tracking are essential components of sustainable and cost-effective truck fleet operations. However, existing systems face significant challenges, including inaccurate fuel measurement, disconnected data sources, delayed anomaly detection, and limited support for safety-based decision-making, as outlined below.

1. PS1: The Ideal Scenario

- Trucking companies should have real-time access to accurate fuel usage and



GPS tracking data to ensure efficient operations, reduce fuel theft, and improve route planning.

- Drivers should receive timely rest alerts and vehicle maintenance reminders based on actual driving and fuel metrics to promote safety, avoid overfatigue, and extend vehicle life.
- Fleet managers should be able to detect unusual fuel consumption patterns automatically, enabling early intervention and optimized scheduling.
- All of these should operate through automated, cloud-based systems that integrate IoT sensors, machine learning, and remote dashboard monitoring.

2. PS2: The Reality of the Situation

- Most trucking operations lack real-time visibility into fuel usage, relying instead on manual readings or delayed reports that are prone to error and manipulation.
- GPS tracking is often siloed from other performance indicators like fuel consumption and driving behavior, making behavior-based analysis or route optimization difficult.
- Anomalous fuel consumption events (e.g., theft, leakage, or inefficiency) are rarely detected until long after they've occurred, resulting in financial loss and operational delays.
- Rest and maintenance schedules are typically based on fixed intervals rather than real-time usage data, increasing the risk of driver fatigue, breakdowns, and missed service opportunities.



- Existing technologies are either too costly, fragmented, or lack contextual intelligence to automatically correlate GPS, fuel, and operational metrics.

3. PS3: The Consequences for the Audience

- Truck fleet operators face increasing operational costs due to undetected fuel inefficiencies and theft, impacting business sustainability.
- Driver safety is compromised when rest is not scheduled based on actual driving patterns or system recommendations.
- Vehicle lifespan shortens and maintenance costs rise when alerts are not tied to real-time usage, resulting in unexpected breakdowns and downtime.
- Decision-makers are unable to make informed, data-driven decisions due to fragmented systems and the absence of an integrated monitoring and alert platform.
- These issues collectively hinder operational efficiency, safety, and environmental responsibility, particularly for logistics providers in developing regions lacking advanced fleet management tools.

1.4 Objectives and Deliverables

1.4.1 General Objective (GO)

GO: To develop and evaluate an IoT-based system for trucks, in collaboration with the partner truck company Hino Parañaque Subic GS Auto Inc. (SGSA), that monitors real-time fuel levels, tracks routes using GPS, and detects unusual fuel consumption using



machine learning, with the goal of improving driver safety, supporting rest scheduling, and facilitating proactive vehicle maintenance through automated alerts using fuel and distance metrics, based on established service guidelines.;

1.4.2 Specific Objectives (SOs)

- SO1: To measure fuel levels using digital float sensors integrated via the truck's ECU/diagnostic connector and GPS module, ensuring non-invasive installation and real-time accuracy within $\pm 5\%$.
- SO2: To transmit real-time fuel and GPS data through IoT-based communication to a cloud server, accessible through a centralized dashboard.
- SO3: To capture and log GPS location data every 5 seconds via an embedded module, correlating route information with fuel and time data for behavior tracking.
- SO4: To design and evaluate a context-aware fuel usage deviation modeling approach using non-parametric unsupervised machine learning models, like Matrix Profile or Isolation Forest, achieving 90% precision and 10% false positives in identifying anomalous fuel consumption patterns within controlled environments.
- SO5: To develop and integrate hardware-based rest and maintenance alert mechanisms (e.g., Start/Stop button, buzzer indicators) tied to the web dashboard using cumulative fuel and distance data.

395 **1.4.3 Expected Deliverables**396 **1.5 Expected Deliverables per Objective**

TABLE 1.2 EXPECTED DELIVERABLES PER OBJECTIVE

Objectives	Expected Deliverables
GO: To develop and evaluate an IoT-based system for trucks in collaboration with Hino Parañaque Subic GS Auto Inc. (SGSA) that monitors real-time fuel levels, tracks routes using GPS, and detects unusual fuel consumption using machine learning, improving driver safety, supporting rest scheduling, and facilitating proactive vehicle maintenance through automated alerts.	Trained Unsupervised Machine Learning Model - A validated ML model (Matrix Profile or Isolation Forest) trained on SGSA-reflective datasets for detecting anomalous fuel consumption. Web-Based Monitoring Interface - Real-time dashboard showing GPS location, fuel level, distance, and operating hours for each truck. Embedded In-Truck HMI - Driver-friendly interface displaying driver credentials (name, PIN, and assigned truck), current trip activity, and alert notifications. Cloud Backend Infrastructure - Cloud-based data aggregation, processing, and automated alert generation accessible from SGSA's base. Performance Documentation - Complete validation results under laboratory and SGSA field conditions.
SO1: To measure fuel levels using digital float sensors integrated via the truck's ECU/diagnostic connector and GPS module, ensuring non-invasive installation and real-time accuracy within $\pm 5\%$.	- Calibrated fuel-level acquisition module interfaced through the truck ECU/OBD2 connector. - Accuracy validation report comparing gotten data with fuel gauge levels. - Embedded firmware for fuel data acquisition, filtering, and preprocessing. - Drift, noise, and variance analysis across different tank levels and conditions.



Objectives	Expected Deliverables
SO2: To transmit real-time fuel and GPS data through IoT-based communication to a cloud server, accessible through a centralized dashboard.	1. Integrated IoT communication module with Lora as the primary communication path, Cellular Modules (LTE & GSM) as backup, with an option to connect to other existing hotspots are WIFI Connections. 2. Cloud backend with secure API endpoints for receiving fuel and GPS data. 3. Latency benchmarking report under variable network environments. 4. Optimized MQTT/HTTP transmission logic with buffering and fail-safe retries. 5. Security documentation covering packet integrity and encryption features.
SO3: To capture and log GPS location data every 5 seconds via an embedded module, correlating route information with fuel and time data for behavior tracking.	1. Integrated GPS module capturing coordinates and timestamps at 5-second intervals. 2. Data fusion algorithm linking GPS location, fuel levels, and time progression. 3. Route visualization through a map interface on the dashboard. 4. Recommended route engine with truck-ban zone awareness. 5. Database structure storing synchronized fuel–location–time datasets. 6. Behavioral analytics showing fuel usage per route segment.
SO4: Design and evaluate a context-aware fuel usage deviation modeling approach using non-parametric unsupervised ML models (Matrix Profile or Isolation Forest), achieving 90% precision and 10% false positives.	1. Labeled normal and anomalous fuel consumption datasets. 2. Implementation of Isolation Forest and/or Matrix Profile in Python/MATLAB. 3. Evaluation metrics report including precision, recall, and FPR 10%. 4. Exportable model (PMML/ONNX) for real-time pipeline integration. 5. Context-aware analytics combining slope, route, load, and time-of-day factors.
SO5: To develop and integrate hardware-based rest and maintenance alert mechanisms (e.g., Start/Stop button, buzzer indicators) tied to the web dashboard using cumulative fuel and distance data.	1. Cloud dashboard showing fuel usage, distance, operating hours, and maintenance status. 2. Rule-based alert engine for configurable driver safety and vehicle maintenance notifications, with example thresholds such as 300 km or 6-hour rest reminders and 5,000 km oil maintenance alerts. 3. Physical embedded module: Start/Stop button, buzzer/light indicators for rest and maintenance alerts. 4. Backend logic computing distance-based and time-based safety thresholds. 5. Dashboard filters for alert logs and historical events. 6. Extended safety monitoring: speed tracking and overspeed alerts.



1.6 Significance of the Study

1.6.1 Technical Benefit

This research will introduce a context-aware, cloud-connected fleet monitoring system that integrates digital float sensors, GPS route tracking, and unsupervised machine learning to enhance real-time monitoring of fuel usage and detection of anomalous consumption events. Fuel levels will be measured using digital float sensors interfaced through the truck's ECU or diagnostic connector, with the system targeting an accuracy of $\pm 5\%$ compared to manual readings under controlled test conditions. Real-time fuel and GPS data will be transmitted to a cloud server with a maximum latency of three seconds using IoT-based communication modules, ensuring continuous data availability to fleet managers.

GPS modules embedded in the vehicles will log location data every 5 seconds, enabling the system to correlate fuel consumption with time, distance, and route conditions for behavioral tracking and operational analysis. The study will implement non-parametric unsupervised learning methods—specifically Matrix Profile and Isolation Forest—to identify deviations in fuel usage without the need for labeled datasets, allowing scalable and adaptive anomaly detection. In addition, a cloud-based dashboard will integrate hardware-driven rest alerts and maintenance reminders, leveraging cumulative fuel and distance data to generate intelligent break schedules and service interval notifications. Through these combined capabilities, the system aims to improve technical performance by enhancing measurement accuracy, communication responsiveness, anomaly detection reliability, and overall automation in fleet fuel management and driver safety support.



1.6.2 Social Impact

Through an implementation of automatic rest alerts and preemptive maintenance cues, the study encourages safety and health of the drivers to prevent accidents commonly caused by fatigue as well as breakdowns. The system will feature the ability to inform drivers when they are near critical or recommended limits (e.g. 300 km of continuous driving or 6 hours of operation) this will encourage healthy driving practices and compliance with regulations, especially for long distance hauls. These practices will empower the fleet managers who can systematically enforce them, relaying the culture of safety and responsibility into the industry.

In addition, the GPS-based route monitoring and fuel usage logging will help reinforce accountability and transparency, two essentials in preventing fuel misuse. This will help to build trust between management and drivers, and also allow the transport logistics to be data led in the decision making.

1.6.3 Environmental Welfare

The system will improve operational efficiency through minimizing waste in fuel, optimizing route performance and decreasing unplanned maintenance downtime. Through precise anomaly detection and maintenance forecasting, the platform enables cost effective operation of the fleet and longer life of vehicles. It will also help achieve environmental sustainability by minimizing unneeded fuel consumption and emissions from inefficient routes, fuel leaks or late maintenance. By promoting timely service interventions (e.g. oil changes at every 5,000 kilometers) the study aims to support cleaner engine performance and reduced environmental impact over time.



1.7 Assumptions, Scope, and Delimitations

1.7.1 Assumptions

1. Technical Infrastructure

- Consistent internet connection is required to maintain real time data exchange between the IoT sensors, GPS module, and cloud sensor.
- The system integration between the hardware and cloud based infrastructure operates smoothly without significant technical issues.
- The system will have access to a stable power supply for an uninterrupted operation of the on board IoT system.
- Mobile network coverage is able to handle a low latency data communication.

2. Data Accuracy

- Digitally calibrated float sensors integrated through the truck's OBD2 are able to provide fuel-level measurements with a validated accuracy of $\pm 5\%$ when compared to manual dipstick readings.
- The GPS module captures and logs precise coordinates at 5-second intervals, enabling accurate route reconstruction and correlation with fuel consumption and time data.

3. Machine Learning Model Performance

- The unsupervised learning models (e.g., Matrix Profile, Isolation Forest) are capable of identifying anomalous fuel consumption with 90% precision and 10% false positives in controlled environments.



- The training and evaluation data of anomaly detection will be representative of normal fuel consumption and truck behavior under different operating conditions.

4. User Interaction

- It is assumed that users (e.g., truck drivers, fleet operators, and system administrators) will interact with the system according to their roles and available tools.
- Truck drivers are not required to use personal mobile devices; instead, they will rely on a simple onboard interface consisting of a small display and buzzer for receiving rest alerts, maintenance reminders, and status notifications. However, a mobile web application was also developed as a supplementary HMI component to support navigation and provide additional convenience for drivers with personal mobile devices.
- Fleet operators and system administrators will interact with the cloud-based dashboard using standard office computers to monitor fuel data, GPS routes, alerts, and maintenance logs.
- Fleet personnel are expected to follow system recommendations (e.g., rest intervals, maintenance reminders) based on real-time fuel, distance, and performance metrics.

5. Operating Environment

- Environmental conditions, together with power and network breakdowns, will not significantly affect system performance.



- System maintenance is performed routinely and at normal intervals to ensure operational continuity.

1.7.2 Scope

The scope of the study encompasses the development and implementation of a smart fleet monitoring system that utilizes IoT and machine learning technologies for enhanced fuel usage, route monitoring and vehicle maintenance reminder.

The system includes three user-facing interfaces: an embedded in-truck HMI for drivers (ESP32 + ILI9341 TFT + capacitive buttons + buzzer), a mobile driver web application for companion GPS and trip-state synchronisation, and an administrative web dashboard for SGSA fleet monitoring, alert management, and trip analytics. Driver, mobile, and dashboard states are reconciled at the backend via the `trip_sessions`, `telemetry_logs`, and `alerts` tables to ensure a single source of truth across interfaces.

1. Real-Time Fuel Monitoring

- a) Deployment of a calibrated fuel-level acquisition module interfaced through the truck's ECU/OBD-II diagnostic connector, providing continuous fuel-level monitoring with a validated accuracy of $\pm 5\%$ using the non-invasive validation approach defined in the delimitations.

2. Cloud Based Data Transmission

- a) Implementation of GSM-based communication protocols to transmit fuel-level and GPS data from the vehicle to a centralized cloud server with a latency not exceeding 3 seconds.



3. GPS Enabled Route Tracking

- a) Incorporation of GPS modules for logging vehicle location at a sampling rate of 5 seconds, allowing correlation of fuel consumption with route patterns and driving behavior.

4. Anomaly Detection via Machine Learning

- a) Context-aware fuel deviation detection model development by means of unsupervised learning methods (e.g., Isolation Forest, Matrix Profile).
- b) Analysis of precision and false positive rate of the model in a controlled setting.

5. Driver Rest Alerts and Maintenance Reminders

- a) Incorporation of embedded driver alerts, mobile trip-state synchronisation, and administrative fleet monitoring to show cumulative fuel and distance measures across the system interfaces.
- b) Production of automated rest alerts (e.g. every 300 km or after 6 hours) and maintenance reminders (e.g. after every 5,000 km for checking oil).

1.7.3 Delimitations

Direct manual dipstick fuel-volume calibration was not within the delimitations of this study because the partner fleet operator does not authorize tank-cap opening or fuel-system modifications on production trucks used in normal operations. Consequently, fuel-accuracy validation was based on (a) operational-agreement checks against the manufacturer dashboard gauge and (b) per-tank-level variance characterization of the filtered signal relative to the raw OBD-II sender measurements.

**1. Focus on Fuel Monitoring and Anomaly Detection**

- The system will be designed to focus specifically on fuel level monitoring, detecting consumption anomalies, and providing maintenance guidance based on fuel usage and distance traveled. It will not incorporate other real-time diagnostic data from the vehicle's onboard systems.

2. Hardware and Communication Constraints

- The system utilizes digitally calibrated float sensors, an embedded GPS module, and a microcontroller interfaced through the truck's ECU/diagnostic connector; higher-end industrial sensing platforms are not employed.
- Real-time data transmission primarily uses IoT communication protocols, enabling low-latency delivery of fuel and GPS data to the cloud backend.
- A cellular module (LTE & GSM) functions as a fallback communication pathway, activated only during LoRa connectivity loss, and is limited to transmitting essential alerts and critical status messages due to bandwidth and cost constraints.
- Other wireless communication technologies beyond the selected IoT modules are not implemented within the system.

3. Limited Fleet Size and Geography

- The system testing will be limited to the number of vehicles provided for use by the trucking company within a specific geographic area. Large scale testing and deployment across a wider range of fleet types and terrains are not covered.



4. User Features

- The system includes three user-facing interfaces: an embedded in-truck HMI for drivers (ESP32 + ILI9341 TFT + capacitive buttons + buzzer), a mobile driver web application for companion GPS and trip-state synchronisation, and an administrative web dashboard for SGSA fleet monitoring, alert management, and trip analytics. Driver, mobile, and dashboard states are reconciled at the backend via the `trip_sessions`, `telemetry_logs`, and `alerts` tables to ensure a single source of truth across interfaces.
- Advanced analytics features beyond SGSA fleet monitoring, alert management, trip analytics, companion GPS, and trip-state synchronisation are not part of the current interface scope.

1.8 Description and Methodology

This study employs a quantitative research paradigm combined with a data-centric, system development approach to implement an AI-driven fleet fuel monitoring and anomaly detection system. The methodology integrates theoretical foundations from Chapter 3 on cyber-physical systems and IoT architectures, system design principles from Chapter 4, and practical implementation strategies detailed in Chapter 5. The system leverages real-time sensor data, including digitally calibrated float sensors interfaced via the vehicle’s CAN bus or OBD-II port, GPS modules for location tracking, and embedded alert subsystems for driver safety. These components feed into a microcontroller that preprocesses signals, synchronizes time-series data, and transmits information to a cloud platform primarily via LoRa, with GSM as a backup channel.



Offline, historical and hybrid datasets, combining fleet telemetry and publicly available vehicle logs, are used to train non-parametric unsupervised machine learning models such as Matrix Profile and Isolation Forest. These models identify anomalous fuel consumption patterns and provide context-aware alerts. In the cloud, a Python-based engine continuously evaluates incoming data, logs anomaly events, and stores synchronized measurements in a centralized database. Users access the information through a web-based dashboard that displays real-time truck status, historical fuel usage, route playback, and operational alerts.

The methodology includes signal preprocessing (smoothing via moving averages), time synchronization using linear interpolation, hybrid dataset construction, and rigorous evaluation metrics (precision, false positive rate, accuracy, detection latency) to validate system objectives, as elaborated in Chapter 5. The approach follows iterative, agile development cycles, allowing continuous refinement of sensor integration, communication protocols, and anomaly detection algorithms, thereby ensuring reliability, scalability, and actionable fleet monitoring insights.

1.9 Research Dissemination Plan

The findings of this study will be disseminated to relevant academic, industrial, and technical stakeholders to promote the adoption and further development of intelligent fleet monitoring technologies. Upon approval of the study, the final manuscript will be submitted to the institutional repository of De La Salle University, including the Animo Repository, in accordance with university research archiving policies. Primary target audiences include the research partner Hino Paranaque Subic GS Auto Inc. (SGSA), fleet managers, logistics operators, academic researchers, engineering students, and faculty members within the



590 field of IoT, transportation systems, and machine learning.

591 The dissemination process will occur in multiple stages. During the implementation
592 and testing phase, progress updates and preliminary findings will be presented to SGSA
593 representatives and thesis advisers for technical evaluation and operational feedback. Upon
594 completion of the study, the final results, including system performance metrics, anomaly
595 detection accuracy, latency measurements, and operational observations, will be formally
596 presented through the thesis defense at De La Salle University. A digital and printed copy of
597 the approved manuscript will also be submitted to the institutional repository of De La Salle
598 University, Animo Repository, in accordance with institutional requirements. In addition,
599 the proponents may present selected findings in future academic conferences, research
600 exhibits, or technology demonstrations related to IoT systems, intelligent transportation, or
601 artificial intelligence applications.

602 The dissemination timeline will follow the project completion schedule presented in
603 Section 1.9, including the individual Gantt charts of the proponents. Preliminary techni-
604 cal findings and prototype demonstrations will be shared during the system testing and
605 validation phase. Final dissemination activities, including the thesis defense, manuscript
606 submission, and partner presentation, will occur after the completion of data analysis,
607 evaluation, and manuscript revisions. Any future publication or presentation derived
608 from the study will only use anonymized and non-sensitive operational data to preserve
609 confidentiality and comply with ethical and data privacy standards.

610 The effectiveness of the dissemination activities will be evaluated through several
611 criteria, including feedback from thesis panel members, adviser evaluations, partner com-
612 pany assessments, and audience engagement during presentations and demonstrations.
613 Additional indicators of dissemination effectiveness include successful acceptance of the



manuscript, utilization of recommendations by the partner company, and the potential application or continuation of the proposed system in future research or operational deployments.

1.10 Conflict of Interest

None.

1.11 Estimated Work Schedule and Budget

1.11.1 Gantt Chart




Fig. 1.1 Individual Gantt Chart for Barja

1. Introduction



De La Salle University




Fig. 1.2 Individual Gantt Chart for Castelo




Fig. 1.3 Individual Gantt Chart for De La Rosa




Fig. 1.4 Individual Gantt Chart for Montemayor



621

1.11.2 Estimated Budget

TABLE 1.3 DETAILED BUDGET BREAKDOWN FOR THE PROJECT

Item / Activity	Unit	Qty	Unit Cost (PHP)	Total Cost (PHP)	Remarks
A. Covered by Hino Motors					
Use of truck for testing	Truck	2	Sponsored	-	Provided by Hino
B. Covered by Research Team					
Hardware Components					
CAN Bus / OBD-II Inter-face Module	-	1	1,200	1,200	Reads fuel levels and vehicle pa-rameters from ECU
GPS Module	-	1	650	650	Route tracking and speed monitor-ing
ESP32 DevKit 30 pins	-	2	350	700	Main microcontroller boards
A7670E	-	1	1,300	1,300	Cellular communication module
MCP2515 CAN Bus Mod-ule	-	1	91	91	CAN bus interface module
Buzzer Module	-	1	45	45	Audio alert component
Buttons	-	2	10	20	Driver input controls
Arduino TFT Screen 3.5 in	-	1	648	648	In-vehicle display interface
LoRa Module Ra-02 433 MHz	-	2	218	436	Long-range communication mod-ules
OBD2 16-pin connector	-	1	154	154	Vehicle diagnostic connector
GPS Module NEO-M8N	-	1	600	600	GPS tracking module
Resistors (1x220 ohms, 1x5 kohms)	-	2	1	2	Circuit protection components
SIM card (TNT)	-	1	100	100	Cellular network access
Prototype Case					
3D Model and Printing	-	1	4,500	4,500	Prototype enclosure fabrication
Total Estimated Budget				10,446	

622

1.12 Overview of the Thesis Proposal

623

624

625

626

627

628

629

This chapter provides an overview of the study, which addresses inefficiencies in logistics and trucking operations while tackling safety concerns related to fuel monitoring, vehicle tracking, and anomaly detection. Modern trucking operations involve complex coordination, and current approaches—manual fuel measurements, fragmented GPS tracking, and delayed anomaly detection—are insufficient for ensuring operational efficiency and driver safety. This work proposes an integrated, IoT-based intelligent monitoring platform that leverages CAN bus fuel data, GPS, and cloud-deployed machine learning models to provide real-time



insights and actionable alerts.

The problem statement highlights a fragmented monitoring environment with limited automation, reactive maintenance scheduling, and the inability to detect unusual fuel consumption proactively. The objectives of the research focus on developing a real-time system that reads fuel levels from the truck’s ECU via CAN bus, tracks location and speed using GPS, and identifies anomalies in consumption patterns using unsupervised machine learning models (Matrix Profile and Isolation Forest). The system is supported by a cloud-based dashboard, which provides fleet managers with fuel usage insights, rest alerts, route tracking, and preventive maintenance notifications. This approach promotes operational efficiency, enhances driver safety, and reduces fuel wastage, making it a technically and environmentally relevant solution.

Building on this foundation, Chapter 2: Literature Review examines previous research on IoT-based fleet monitoring systems, GPS-enabled tracking technologies, and machine learning methods for anomaly detection. The review compares existing methods, identifies gaps in real-time deployment, system integration, and context-aware alerting, and evaluates technology innovations and algorithmic limitations. This analysis establishes the academic basis for the study and demonstrates how the proposed system advances the state of the art in smart fleet management by providing a fully integrated, real-time, and context-aware monitoring solution.



De La Salle University

649

Chapter 2

650

LITERATURE REVIEW



651

2.0.1 Literature Review




Fig. 2.1 PRISMA Diagram

The PRISMA diagram illustrates the systematic process used for selecting studies for review through screening and identification. The search identified a total of 41 records from three databases: Scopus, IEEE Xplore, and Google Scholar. Five (5) duplicate records were excluded from the 41 records, resulting in 36 records screened. The evaluation of 36 records resulted in five exclusions due to records being outdated/irrelevant, which reduced the number of reports needed for retrieval to 31. Three (3) reports were not retrieved upon retrieval, resulting in 28 reports assessed for eligibility. The final review included 28 studies



only, while no new studies were reported.

2.1 Existing Work

2.1.1 Vehicle Tracking and Fuel Sensing Technologies

Fuel Monitoring Systems

Various fuel monitoring systems have been proposed, discussed, and developed in existing studies, emphasizing real-time fuel level, theft indication, and enhanced operational efficiency. In the work of Joshi et al. [Joshi et al., 2024], a system combines ESP32 and Arduino UNO microcontrollers with the ThingSpeak cloud-based platform to measure fuel levels, control transactions, and enable predictive maintenance at fuel stations. Similarly, Ahmed et al. [Ahmed et al., 2017] developed a fuel management system using Raspberry Pi and both ultrasonic and chemical Etape sensors to acquire real-time fuel level data, displayed through a web application.

In the automotive domain, several studies aim to enhance the accuracy of fuel management through sensor integration. The digital system by Sakthimohan et al. [M, 2021] employs ultrasonic and flow sensors with an Arduino UNO to display real-time measurements on an LCD, providing a replacement for imprecise analog gauges. Meanwhile, Farzana et al. [Farzana, 2020] proposed a motion-based fuel monitoring technique that integrates vehicle motion parameters with fuel level sensor readings, achieving 80% success in accurately determining fuel levels and 100% detection success in identifying fuel theft and refills via a smartphone application.

Studies focused on fuel theft detection, such as those by Tatababu et al. [Tatababu et al., 2024] and Mathi et al. [Mathi et al., 2024], utilize capacitive or ultrasonic sensors,



681 GPS tracking, and GSM-based alerts to detect tampering or fuel loss and notify operators
682 immediately. In the Intelligent Fuel Monitoring and Theft Detection System using GPS
683 & GSM, Mathi et al. [Mathi et al., 2024] also monitored battery charge (SoC), with
684 applicability for both hybrid and conventional vehicles, making it suitable for logistics and
685 fleet management.

686 Ali et al. [Komal Shoukat Ali et al., 2018] presented an automatic fuel tank monitoring,
687 tracking, and theft detection system integrating Arduino-based fuel circuits with GSM/GPS
688 modules and LabVIEW for database management. This system replaces manual fuel
689 tracking with automated alerts and volume monitoring, offering a cost-effective solution for
690 transportation industries. Overall, these systems indicate a trend toward inexpensive, sensor-
691 based, remotely accessible fuel monitoring technologies with high priority on accuracy,
692 security, and real-time data analysis.

693 **GPS and Vehicle Telematics**

694 Global Positioning System (GPS) and vehicle telematics technologies have become
695 essential components in modern vehicle monitoring and fleet management systems. These
696 technologies allow real-time tracking, remote diagnostics, and performance analysis by
697 collecting and reporting data such as location, speed, fuel consumption, and engine status.
698 A common trend in these studies is the combination of GPS and GSM modules to facilitate
699 real-time vehicle tracking, usually complemented by cloud-based or mobile-supported
700 platforms. Joshi et al. [Joshi et al., 2024] proposed a system enabling real-time monitoring
701 for logistic management using sensors, GPS tracking, and cloud-based data analytics.
702 Similarly, Alquhali et al. [Alquhali et al., 2019] and Nada [Nada, 2017] employed GPS and
703 GSM modules to send live location data, show vehicle tracks on electronic maps, and record
704 location history for future reference and analysis. Vigneshwaran et al. [Vigneshwaran et al.,



2020] presented a GPS-GSM-based bus tracking system supporting student notifications for bus arrival, emergency notifications, and route alerts, enhancing safety and saving waiting time. The system further offered a framework for real-time fuel monitoring with implications for broader fleet management applications.

2.1.2 LoRa Technology

LoRa (Long Range) is a wireless communication technology engineered for Internet of Things (IoT) and machine-to-machine (M2M) communication. It supports low-power, battery-operated embedded systems that transmit small amounts of data over long distances [Orange Connected Objects & Partnerships, 2016]. Traditional cellular networks such as GSM, 2G, 3G, and 4G prioritize high data throughput, which can result in inefficient power consumption for IoT applications that require infrequent, small data transmissions [Majeed, 2015, Lee et al., 2007]. Unlike cellular networks or short-range protocols such as Wi-Fi and Bluetooth, LoRa is optimized for applications where energy efficiency and communication range are more important than high throughput [Devalal and Karthikeyan, 2018].

The LoRa communication architecture follows a structured flow of information so that small data packets can reach cloud-based systems efficiently:

- **LoRa Node or End Device:** This component includes the sensors or applications where sensing and control take place. It collects telemetry data and transmits them as small, optimized data packets.
- **LoRa Gateway:** The gateway receives packets from end nodes and acts as a bridge between LoRa nodes and the internet.



- **Cloud Backend:** Once the gateway forwards data through a backhaul connection, the information reaches a network or application server where it can be processed, visualized on dashboards, or stored for further analysis.

2.1.3 LoRa Gateway

LoRa gateways are multi-channel, multi-modem transceivers capable of simultaneous reception and decoding of LoRa packets from numerous end nodes. Each gateway acts as a bridge that connects LoRa nodes to the internet by capturing transmitted node data and forwarding them through standard backhaul connections such as Wi-Fi, Ethernet, or cellular data. Data from different gateways are processed through a network server, which functions as the central intelligence of the LoRa architecture. This server performs security authentication, filters messages, manages adaptive data rates, and relays appropriate acknowledgments back to the gateways [Orange Connected Objects & Partnerships, 2016].

Gateway deployment varies according to coverage requirements. Micro gateways are typically deployed in public networks to provide broad city-wide or nationwide connectivity, while pico gateways are used in dense or challenging environments to improve network capacity and service quality. To support these deployment scenarios, LoRa base stations may use omni-directional or multi-sector antenna configurations [Devalal and Karthikeyan, 2018].



2.1.4 Technical Performance Metrics and Environmental Factors

The operational effectiveness of LoRa networks depends on the interaction between transceiver hardware configuration and environmental conditions. According to Chengdu Ebyte Electronic Technology, the communication distance of a LoRa module is influenced by transmit power, receiver sensitivity, and antenna gain [Chengdu Ebyte Electronic Technology Co., Ltd., 2024]. In open rural areas, a standard LoRa layout can achieve communication links of approximately 15 to 20 kilometers. In dense urban environments, however, coverage may decrease to approximately 1 to 5 kilometers because of building penetration losses and multipath propagation effects [Chengdu Ebyte Electronic Technology Co., Ltd., 2024].

Manalu et al. [Manalu et al., 2023] evaluated the performance of a LoRa-based vehicle tracking system using a HopeRF-RFM95W transceiver module operating at 915 MHz on a moving vehicle. The study analyzed link-quality parameters in a Non-Line-of-Sight (N-LoS) suburban environment at speeds of 10 km/h, 20 km/h, and 30 km/h. The evaluation focused on how buildings, vegetation, and other wireless signals affect key performance metrics. Received Signal Strength Indicator (RSSI) measures absolute signal power and degrades behind thick barriers, vegetation, or dense buildings. Signal-to-Noise Ratio (SNR) measures signal clarity against electromagnetic interference and may drop significantly because of disruptions from pedestrians, structures, vehicles, and Wi-Fi towers. Packet loss may also increase sharply near major structural obstacles, showing that LoRa performance in mobile fleet applications must account for physical barriers and N-LoS conditions [Manalu et al., 2023].



2.1.5 Real-World Implementation: LoRa-Based Telemetry and Fleet Management Systems

The long-range and low-power characteristics of LoRa make it suitable for geographic areas with limited commercial telecommunication infrastructure. Common applications include smart agriculture, pasture health monitoring, and isolated industrial operations. However, reliance on a single low-power wide-area network (LPWAN) protocol may introduce communication risks when asset-tracking nodes move between remote rural spaces and dense urban areas.

To reduce blind spots, industrial systems may use hybrid communication architectures. The Meitrack LoRa Fleet Tracking Solution illustrates this approach in large-scale agricultural operations, such as orchards and palm plantations, where GSM coverage may be unreliable or unavailable [Meitrack,]. In such environments, multi-modem tracking hardware can use a dual LoRa and GPRS switching configuration based on network availability. While operating in cellular dead zones, localized sensor payloads, including ultrasonic fuel-level data, driver authentication logs, and safety alerts, can be routed through LoRa to a local base station. This architecture helps preserve asset visibility when standard cellular infrastructure is unavailable [Meitrack,].

2.1.6 GSM and LTE Technologies

The Global System for Mobile Communication (GSM) is a widely recognized standard for digital cellular technology. It originated from a group formed in 1982 to develop a unified European mobile telephone standard for cellular radio systems operating at 900 MHz [The International Engineering Consortium,]. GSM is known for broad geographic



789 coverage and supports voice calls and basic data services through second-generation
790 cellular communication. Long-Term Evolution (LTE), by contrast, is a wireless broadband
791 communication standard that succeeded 3G and became a cornerstone of 4G mobile
792 networks. LTE development began as a Third Generation Partnership Project (3GPP) effort
793 in 2004 to provide a new radio access technology focused on packet-switched data [Miyim
794 and Wakili, 2019].

795 LTE was developed to address increasing demand for mobile broadband services by
796 improving network capacity, data rates, quality of service, and latency. These improvements
797 support mobile wireless connectivity that aligns with performance benchmarks established
798 by the International Telecommunication Union (ITU). After LTE was established in 2009,
799 further performance requirements led to LTE-Advanced (LTE-A), which satisfied Interna-
800 tional Mobile Telecommunications (IMT) requirements for fourth-generation networks and
801 achieved peak data rates of up to 1 Gbps [Miyim and Wakili, 2019, Kanchi et al., 2013].



Fig. 2.2 Globe GSM (pink) and LTE (orange) Coverage Map Philippines (GSMA Intelligence)




Fig. 2.3 Smart GSM (pink) and LTE (orange) Coverage Map Philippines (GSMA Intelligence)



TABLE 2.1 COMPARISON BETWEEN GSM AND LTE

Feature	GSM (2G)	LTE (4G)
Network Architecture	Circuit-switched	Packet-switched (All-IP)
Primary Focus	Voice and text services	High-speed mobile broadband
Coverage	Extensive broad geographical reach, including rural and remote areas	High-capacity and density-dependent coverage that requires closer proximity to modern cell towers
Frequency Band	900 MHz and 1800 MHz	Bands 1 to 25 for Frequency Division Duplex and bands 33 to 41 for Time Division Duplex
Signal Propagation	Excellent because of lower frequencies	Variable because higher frequencies generally have shorter range
Infrastructure Needs	Lower base station density	Higher base station density
Data Capability	Low, supporting basic data and messaging	Very high, supporting multimedia and internet access



802 The coverage maps in Figures 2.2 and 2.3 illustrate GSM and LTE coverage patterns in
803 the Philippines based on GSMA Intelligence coverage data [GSMA, 2026]. Comparing
804 the two networks, Globe shows a noticeably denser and more contiguous spread of both
805 GSM and LTE coverage, particularly through the Visayas and Mindanao, where its colored
806 patches connect more continuously along coastal and lowland routes. Smart's coverage,
807 while still following the same population centers, appears comparatively more fragmented,
808 with more isolated patches and gaps between cities, especially in the southern islands.

809 In both cases, LTE coverage appears as a smaller subset within the broader GSM
810 footprint. This indicates that 4G service is generally concentrated in and around cities and
811 main highway corridors, while 2G/GSM extends farther into surrounding rural areas as
812 a fallback connectivity layer. This difference is important for fleet monitoring systems
813 because mobile assets may move between high-capacity LTE areas and wider but lower-
814 bandwidth GSM fallback zones [Opensignal, , GSMA, 2026].

815 **2.1.7 Anomaly Detection**

816 Several studies on anomaly detection in vehicular systems aim to improve operational
817 safety, combat theft and fraud, and optimize fuel efficiency. Various technological means,
818 such as GPS tracking, machine learning, and time series analysis, have been used to identify
819 abnormal vehicle behaviors. Crisgar et al. [Crisgar et al., 2021] developed a vehicle
820 tracking system using Google Cloud IoT Core and Firebase to monitor vehicle movements
821 and engine activity for theft detection. Unauthorized ignition or unexpected movement
822 beyond a 50-meter radius is flagged as potential theft, with real-time notifications pushed
823 to a Progressive Web App, enabling users to respond quickly.

824 Studies focusing on fuel efficiency in heavy-duty vehicles (HDVs) through anomaly



825 detection models include Turan et al. [Turan et al., 2024], who proposed an ensemble of
826 unsupervised machine-learning models (Isolation Forest, Autoencoder, k-NN Regression)
827 combined via weighted majority voting to detect abnormal fuel consumption patterns based
828 on road slope and speed variations. Mumcuoglu et al. [Mumcuoglu et al., 2023] used
829 decision tree ensembles to classify fuel usage as normal or anomalous, achieving 92.2%
830 accuracy and an F1 score of 0.78. Both studies indicate that repeated detection of outliers
831 can highlight anomalies such as mechanical issues or inefficient driving.

832 Aquize et al. [Aquize et al., 2017] applied Self-Organizing Maps (SOM) to detect
833 abnormal fuel consumption in RFID-registered vehicles in Bolivia. By learning conven-
834 tional consumption patterns, the SOM model achieved an 80% confidence rate in flagging
835 suspicious activity indicative of fraud. Semenov et al. [Semenov et al., 2024] employed
836 DBSCAN clustering and Local Outlier Factor (LOF) in a three-level telematics platform
837 to forecast and detect truck breakdowns in real-time. This system tracks multiple vehicle
838 parameters, labeling them as normal or outliers based on deviation from learned patterns,
839 minimizing surprise breakdowns and providing early driver alerts. Aquize et al. [Aquize
840 et al., 2017] proposed a fuel anomaly detection framework based on Self-Organizing
841 Maps (SOM) using RFID-registered vehicle data collected from fleet operations in Bolivia.
842 The SOM algorithm learned normal fuel consumption patterns and identified suspicious
843 deviations associated with potential fuel fraud. The study achieved approximately 80%
844 confidence in detecting anomalous fuel usage and demonstrated the effectiveness of unsu-
845 pervised learning approaches for identifying irregular fuel consumption behavior without
846 requiring labeled datasets.

847 Similarly, Kaleem Habib and Arif Iqbal Umar [Habib and Umar, 2015] utilized data
848 mining techniques to calculate and detect anomalies in fuel expenses by analyzing historical



fuel transaction records and consumption patterns. Their approach identified abnormal expenditure behaviors that could indicate fuel theft, reporting errors, or operational inefficiencies. The findings demonstrate the value of data-driven anomaly detection methods in supporting cost control and fraud prevention within fleet management environments.

Garcia Vega [Garcia Vega, 2022] emphasized time series anomaly detection for vehicle monitoring, developing an iterative approach to detect unusual driving patterns through pre-processing, subsequence segmentation, scoring, clustering, and expert validation. Applied in an industrial context, it identified over 120 validated anomalies, helping diagnose mechanical failures or unsafe driving behavior. The study highlights the importance of visual interpretability tools and recommends future improvements via real-time data processing.

Because published fleet fuel-anomaly work (Barbado and Corcho, 2022) [Barbado and Corcho, 2022] uses boxplot/IQR-based unsupervised detection as an interpretable baseline before applying explainable models, the present study compares Isolation Forest and Matrix Profile against a rule-based / IQR baseline under leave-one-trip-out evaluation. This baseline serves both as a fairness check (to show that the non-parametric models genuinely add value over a thresholding heuristic) and as an ablation reference in Chapter 5.

2.1.8 Machine Learning Applications

Barbado and Corcho (2022) [Barbado and Corcho, 2022] developed an explainable machine-learning framework for vehicle fuel-consumption anomalies using real-world telematics data from diesel and petrol fleet vehicles. Their study emphasised that anomaly detection should not only identify abnormal fuel consumption but also explain the operational causes behind the anomaly, using XAI techniques on top of an unsupervised detection layer. They first identified candidate anomalies via a univariate boxplot/IQR outlier method and then



872 trained a contextual model that incorporates domain knowledge such as vehicle subgroup,
873 route type, and driver behaviour. This is directly relevant to the present thesis because fuel
874 anomalies in Philippine logistics must be interpreted with operational context - the same
875 context (driver, route, vehicle, fuel-consumption baseline) is encoded in the Isolation Forest
876 Model C feature set used in Chapter 5.

877 Recent advances in machine learning have been integrated into vehicle systems to
878 improve fuel efficiency, detect anomalies, and enhance operational transparency. In fuel
879 monitoring and anomaly detection, machine learning methodologies extract actionable
880 insights from complex, high-dimensional vehicle data. Fortela et al. [Fortela et al., 2023] ap-
881 plied unsupervised machine learning algorithms (Principal Components Analysis, K-Means
882 Clustering, Self-Organizing Maps) to detect anomalies in fuel economy and emission
883 data from light-duty vehicles (2015–2023). These methods revealed clusters where CO
884 emissions were positively linked to fuel economy, contrary to expected patterns, highlight-
885 ing irregularities caused by specific fuel test procedures. Barbado and Corcho [Barbado
886 and Corcho, 2022] combined unsupervised anomaly detection with domain knowledge
887 and interpretable machine learning (XAI) to explain potential causes of fuel consumption
888 anomalies. Their models demonstrated up to 88% potential fuel savings on larger datasets
889 and across various user roles.

890 Barbado and Corcho [Barbado and Corcho, 2022] further demonstrated that inter-
891 pretable machine learning models such as Explainable Boosting Machines (EBM) can
892 be used not only to detect anomalous fuel consumption but also to explain the factors
893 contributing to those anomalies. Their methodology combines unsupervised anomaly de-
894 tection, domain knowledge, and explainable artificial intelligence (XAI) metrics to provide
895 actionable recommendations for fleet managers and operators. The study highlights the



importance of model transparency in fleet monitoring systems, allowing stakeholders to understand the causes of abnormal fuel usage rather than merely identifying anomalous events.

More recent work sharpens the methodological basis for unsupervised, on-vehicle detection. Cherdo et al. [Cherdo et al., 2023] applied small recurrent and convolutional neural networks to automotive CAN sensor time series, demonstrating that bus data of the kind exposed through an OBD-II interface is amenable to unsupervised anomaly detection, although their models still require gradient-based training. Surveying the domain, Hirth et al. [Hirth et al., 2025] formalize anomaly detection in trucks as identifying deviations across multivariate signals at each time step of a stream, and observe that deep architectures impose retraining and computational burdens that complicate continuous deployment. These observations motivate the two non-parametric methods adopted in this study: Isolation Forest [Liu et al., 2008], which isolates anomalous individual observations without modeling a distribution of normal behavior, and the Matrix Profile [Yeh et al., 2016], which detects anomalous subsequences and has been extended to live data streams [Lu et al., 2022] and to multiple sensor channels [Yeh et al., 2024]. The mathematical formulation of both methods is presented in Chapter 3.

TABLE 2.2 SUMMARY OF EXISTING WORKS

Study	Technology Used	Key Features	Strengths	Limitations
Tatababu et al. (2024) [Tatababu et al., 2024]	Ultrasonic/Capacitive sensors, GSM, GPS, Smartphone/Web interface	Theft detection, fuel level alert, real-time remote access	Accurate for remote generator monitoring, GPS-based tracking	Findings specific to the tested generator systems and environments



Study	Technology Used	Key Features	Strengths	Limitations
Joshi et al. (2024) [Joshi et al., 2024]	IoT, GPS, RFID, Cloud Computing	Real-time vehicle/asset tracking, data analytics, cloud-based monitoring	High tracking accuracy, improved logistics efficiency, responsive alert system	Limited by hardware and logistics test case set
Vigneshwaran et al. (2020) [Vigneshwaran et al., 2020]	GPS, GSM	Real-time bus tracking, emergency alert system, communication to students, route updates	Improves safety, scheduling, and passenger information	Not highly scalable; lacks detailed integration with modern telematics platforms
Patil & Patil (2024) [Patil and Patil, 2024]	IoT, GPS, GSM, Accelerometer, IR Sensors	Tracking system with SMS-based communication; remote ignition cut-off mechanism and vehicle password protection	Comprehensive vehicle security, real-time alerts, detection of tampering/impacts	Low adaptability to harsh conditions like GPS/GSM signal loss in remote areas
Fortela et al. (2023) [Fortela et al., 2023]	Unsupervised Machine Learning: PCA, K-Means, SOM	Detects hidden trends and impending anomalies; analyzes correlation between CO emissions and fuel economy	Effectively identifies non-obvious patterns within clusters; highlights flaws in standardized testing procedures	Lacks integration with real-time or operational vehicle data; conclusions depend on historical datasets
Barbado & Corcho (2022) [Barbado and Corcho, 2022]	Unsupervised Anomaly Detection; Explainable Boosting Machine (EBM)	Provides fuel anomaly detection and cause explanations, tailored recommendations for fleet operators	High interpretability via XAI metrics; role-based recommendations; potential fuel savings up to 88%	Performance depends heavily on quality of telematics data or feature relevance
Aquize et al. (2017) [Aquize et al., 2017]	Self-Organizing Maps (SOM)	Detects fraudulent fuel usage based on RFID data patterns	80% accuracy applied to real socioeconomic problem	Used only simple SOM model; accuracy can improve with more context variables



Study	Technology Used	Key Features	Strengths	Limitations
Liu et al. (2008) [Liu et al., 2008]	Isolation Forest	Ensemble of isolation trees that identify anomalies through random partitioning	Non-parametric anomaly detection with linear-time complexity and low memory requirements	No labeled data required; superior AUC compared with ORCA and LOF; computationally efficient
Yeh et al. (2016) [Yeh et al., 2016]	Matrix Profile (STAMP)	Z-normalized nearest-neighbor similarity profile for motif and discord discovery	Exact subsequence anomaly detection with minimal parameter tuning	Deterministic, interpretable, and near parameter-free
Lu et al. (2022) [Lu et al., 2022]	DAMP Streaming Matrix Profile	Real-time Matrix Profile computation for high-volume streaming data	Detects discords in continuously arriving data streams at very large scales	Suitable for online and real-time deployment
Yeh et al. (2024) [Yeh et al., 2024]	Multidimensional Matrix Profile	Extension of Matrix Profile for multivariate time-series anomaly detection	Simultaneously analyzes multiple sensor channels	Competitive performance across numerous benchmark datasets and highly interpretable results
Hirth et al. (2025) [Hirth et al., 2025]	Deep Learning-Based Truck Anomaly Detection (Survey)	Comprehensive review and taxonomy of anomaly detection methods for trucks	Defines anomaly detection in multivariate truck telemetry streams	Provides truck-specific insights and identifies current research directions
Cherdo et al. (2023) [Cherdo et al., 2023]	Small RNN and CNN Models	Unsupervised anomaly detection using automotive CAN-bus sensor data	Demonstrates feasibility of on-vehicle anomaly detection under limited hardware resources	Effective for OBD-II/CAN sensor environments and embedded deployment



2.2 Comparison of Commercial Fleet Management Systems

Beyond the academic literature, six widely deployed commercial fleet management platforms were examined to establish the detection methodologies available to operators in practice: Geotab, Samsara, Fleetio, Wialon, Fleet Complete, and Navixy. Each platform's own product documentation was used as primary evidence of its capabilities. Despite mature telematics infrastructure, fuel-loss detection across these systems reduces to fixed or manually configured rules. Samsara's documentation describes its fuel theft detection as a configurable alert on any sudden fuel drop of five percent or more [Samsara, 2026]. Navixy requires operators to configure rate-of-change drain thresholds per sensor and can be set to ignore drains while a vehicle is moving [Navixy, 2026]. Geotab and Fleetio approach the problem from the fuel-card transaction side, flagging exceptions such as purchases exceeding tank capacity or fueling locations inconsistent with vehicle position [Geotab, 2024, Fleetio, 2026]. Wialon detects drain events from fuel-level sensor data and commonly relies on operator review for verification [Wialon, 2026], while Fleet Complete's public documentation centers on fuel usage reporting without specifying an adaptive detection method [Fleet Complete, 2026]. Across all six, no platform learns a vehicle's normal consumption behavior, adapts to operating context, or is designed specifically for Philippine fleet conditions.



TABLE 2.3 COMPARISON OF COMMERCIAL FLEET MANAGEMENT SYSTEMS

System	Data Sources	Fuel Monitoring Method	ML for Fuel Anomalies?	Detection Methodology	Limitations
Geotab [Geotab, 2024]	OBD/telematics device, fuel cards, GPS	Fuel-up records and engine data reporting	No (rule checks)	Capacity mismatch, purchase greater than capacity, and location discrepancy	Transaction-rule logic; no learned consumption behavior
Samsara [Samsara, 2026]	Telematics gateway, fuel sensor/OBD, fuel cards, GPS	Real-time fuel level and usage reports	No (threshold)	Configurable sudden-drop alert ($\geq 5\%$)	Static threshold; blind to gradual loss; one rule for all conditions
Fleetio [Fleetio, 2026]	Fuel card transactions and telematics integrations	Transaction-based fuel management	No	Exception alerts for location mismatch and volume greater than tank capacity	Sees only fill-up events; blind between refuels
Wialon [Wialon, 2026]	Fuel level sensors, GPS trackers, optional cameras	Sensor-based fuel charts and drain/refill detection	No	Sensor-threshold drain events with human/video verification	Threshold-based and manually reviewed; reactive
Fleet Complete [Fleet Complete, 2026]	Telematics device, GPS, vehicle data, fuel reports	Fuel usage and fleet reporting	No specified adaptive model	Reporting-based fuel monitoring and exception review	Public documentation does not specify adaptive anomaly detection
Navixy [Navixy, 2026]	Fuel level sensors, OBD/CAN, GPS	Drain/refill event detection from sensor data	No	Per-sensor rate-of-change drain thresholds; option to ignore in-motion drains	Manual tuning; in-motion exclusion can hide moving theft or leaks



2.3 Lacking in the Approaches

While existing technologies in vehicle tracking, fuel sensing, and anomaly detection form the foundation upon which developments can be built, they suffer from critical limitations that prevent their use in real-time, fleet-wide operations. Research works such as Krishnasamy [Krishnasamy, 2019] have employed basic sensor technologies without any validation of fuel measurements in real-time driving environments or estimation of accuracy parameters relative to manual readings. Besides, current systems are limited to specific uses and are not tested for scalability or integration with fleet vehicles like trucks such as institutional/organizational level of motorcycles in the study of RS et al. [RS et al., 2024]. Some works do consider machine learning techniques for anomaly detection, but such techniques are mostly based on static and post-processed datasets, with no real-time on-vehicle analysis. Very few implementations include unsupervised machine learning and advanced context-aware modeling, and precision benchmarks are usually left unreported, if at all addressed.

Across the surveyed commercial systems, including Geotab, Samsara, Fleetio, Wialon, Fleet Complete, and Navixy, several operational capabilities remain insufficiently addressed. First, closed-loop in-cab driver feedback is largely missing because most platforms push alerts to a manager dashboard, whereas this thesis pushes alerts to a driver-facing HMI inside the truck cab with rest/snooze acknowledgments captured in the `alerts` table. Second, offline-tolerant telemetry with explicit replay accounting is rarely documented in academic prototypes or commercial fuel-monitoring systems; this thesis tags every telemetry row with `channel_used`, including `offline_replay`, which lets the backend distinguish live data from replayed data. Third, multi-interface state reconciliation is not



typically addressed, while this thesis uses partial unique indexes to enforce one-active-trip-per-truck/driver across three concurrent client surfaces: HMI, mobile, and dashboard.

Ultimately, there is no prior system that provides a full solution that brings together a cloud-connected solution for real-time fuel monitoring with integration of GPS tracking and anomaly detection. Further, it completely lacks features such as automatic rest alerts and predictive maintenance reminders, which are necessary for safe, efficient, and compliant operations. Such shortcomings create an opportunity for a more integrated, intelligent, and real-time solution, and this is what the thesis proposes to address.

TABLE 2.4 IDENTIFIED GAPS, LIMITATIONS, AND PROPOSED SOLUTIONS

Study / Gap	What they did	Limitation	How this thesis responds
Area of precision	Existing models lack context-awareness and show lower precision. Models presented in the study of Barbado & Corcho [Barbado and Corcho, 2022] performed up to 80% of anomalous instances explained.	Prior work does not establish the same precision and false-positive benchmark required for this deployment.	(SO4) To design and evaluate a context-aware fuel usage deviation modeling approach using non-parametric unsupervised machine learning models, like Matrix Profile and Isolation Forest, achieving $\geq 90\%$ precision and $\leq 10\%$ false positives in identifying anomalous fuel consumption patterns within controlled environments.



Study / Gap	What they did	Limitation	How this thesis responds
Barbado & Corcho (2022) [Barbado and Corcho, 2022]	Used real-world telematics and interpretable ML to detect and explain fleet fuel-consumption anomalies; combined box-plot/IQR pre-filtering with contextual XAI models.	Focused on fleet-level analytics and explanation; did not produce an embedded HMI + OBD-II + multi-channel-communication + live-alert prototype that closes the loop in the vehicle cab.	This thesis integrates OBD-II fuel acquisition (Toyota Mode 22 PID 21/29), embedded HMI, GPS tracking, four-channel communication fallback, backend dashboard, mobile driver web app, and unsupervised anomaly detection (IF Model C + Matrix Profile) in one working prototype evaluated under LOTO.
Absence of a comprehensive system integrating fuel anomaly detection with GPS-based tracking, and predictive maintenance and alerts	Previous works, including those by Joshi et al. [Joshi et al., 2024] and Nada [Nada, 2017], focus on real-time tracking using GPS/GSM.	These works lack integration with anomaly detection methods for analyzing fuel consumption patterns or predicting vehicle maintenance issues.	(SO3, SO4, SO5) To capture and log GPS location data via an embedded module, correlating route information with fuel and time data for behavior tracking; design and evaluate a context-aware fuel usage deviation modeling approach using non-parametric unsupervised machine learning models; develop and integrate rest alerts and maintenance reminders into a cloud-based dashboard.



Study / Gap	What they did	Limitation	How this thesis responds
No Philippine transportation context	Reviewed studies and platforms do not model local conditions such as Metro Manila congestion, Port of Manila utilization, the 2014 Manila truck ban, and fuel fraud costs [Japan International Cooperation Agency, 2025, Patalinghug et al., 2015a, Llanto, 2017, Asian Development Bank, 2016].	Models may misclassify congestion-shaped idling and consumption as anomalies when Philippine operating conditions are absent.	(GO, SO4) Collect and train on operational data from the partner fleet, Hino Paranaque Subic GS Auto Inc., so congestion-shaped idling and consumption are learned as baseline behavior.
One detection rule for all trucks	Commercial systems use single fleet-wide settings [Samsara, 2026] or manual per-sensor tuning [Navixy, 2026]; prior studies were validated on one vehicle class, generators [Tatababu et al., 2024], or motorcycles [RS et al., 2024].	Shared thresholding cannot represent each truck's normal consumption profile.	(SO4) Learn per-vehicle baselines that update from each truck's own operating history, removing dependence on a shared manual threshold.
Detection of sudden drops only	Threshold and transaction logic are commonly used to detect sudden losses [Samsara, 2026, Fleetio, 2026]; Navixy can ignore in-motion drains [Navixy, 2026].	These approaches may miss slow siphoning and gradual leaks.	(SO4) Apply the Matrix Profile for anomalous-subsequence or discord detection of gradual loss, paired with Isolation Forest for sudden point anomalies.
No real-time analytics or live alerts	Machine learning studies were validated offline [Fortela et al., 2023, Barbado and Corcho, 2022]; deep models burden streams [Hirth et al., 2025, Cherdo et al., 2023]; and Wialon relies on human review [Wialon, 2026].	Prior approaches do not provide live anomaly scoring and alert delivery across operational interfaces.	(SO2, SO5) Deploy a cloud pipeline scoring live OBD-II/GPS streams with Isolation Forest and a streaming Matrix Profile [Lu et al., 2022], issuing live alerts to the dashboard, HMI, and mobile application.



2.4 Summary

With this chapter, it was discovered that there have been various studies on vehicle tracking, fuel sensing, and anomaly detection. The PRISMA diagram shows the systematic approach that was used in the identification of the studies, out of which the 41 initial records were narrowed down to 28 after excluding the duplicates, outdated/irrelevant, and not retrieved records. Moreover, the existing studies presented that though a lot has been done to develop individual systems for fuel level monitoring, GPS tracking, and anomaly detection, most of these works are either narrowly focused or operate in isolation. Many rely on basic sensor integrations without advanced analytics, or implement machine learning models without connecting them to real-time, in-vehicle data streams.

Numerous studies have exhibited the application of different sensor-based systems for fuel monitoring in real-time and detecting theft, in many cases involving microcontrollers, GSM, and GPS modules. Likewise, research on vehicle telematics illustrates the application of GPS in route tracking and fleet management. In the field of anomaly detection, some methods based on unsupervised machine learning and clustering techniques have been utilized to detect abnormal fuel consumption patterns and flag fraudulent or inefficient activity. Yet, most of these researches are based on special scenarios, are not integrated with real-time operational data, or depend on historical data.

While advances have been made in each of these domains, a significant void exists in creating a holistic, real-time solution that integrates fuel level measurement, GPS tracking, and intelligent anomaly detection through machine learning. Current systems exist in silos, are vehicle type- or use case-specific, and do not commonly incorporate predictive maintenance or driver feedback mechanisms.



986 This research seeks to fill these gaps by designing and testing an integrated IoT-based
987 system tailored for trucks. The system will be an integrated system that combines real-time
988 fuel monitoring, GPS tracking, and advanced anomaly detection using machine learning
989 which aims to improve operational efficiency, driver safety, and maintenance planning.



990

Chapter 3

991

THEORETICAL CONSIDERATIONS



992 This chapter establishes the theoretical foundations underpinning the proposed IoT-
993 based fleet fuel monitoring and anomaly detection system. It presents the essential concepts,
994 mathematical models, and scientific principles that guide the development of the system.
995 These theories act as the main foundation of the study, supporting the methodological
996 decisions described in Chapter 5. By understanding the underlying theories—ranging from
997 cyber-physical systems to signal processing and machine learning—the relevance and rigor
998 of the chosen approach become clear.

999 3.1 Overview

1000 The methodologies used in the system are grounded in established theories in embedded
1001 systems, time-series processing, IoT architectures, unsupervised machine learning, and
1002 vehicular telematics. These theoretical concepts justify the design choices made in the
1003 development of real-time fuel monitoring components, GPS-based tracking, and anomaly
1004 detection models. This chapter explains the foundations behind the signal models, commu-
1005 nication processes, and machine learning algorithms that make accurate and robust system
1006 performance possible.

1007 3.2 Theoretical Foundations

1008 3.2.1 Cyber-Physical Systems (CPS)

1009 The proposed solution functions as a Cyber-Physical System, integrating embedded sensors,
1010 microcontroller-based processing, cloud computation, and real-time communication. CPS
1011 theory emphasizes:



- the tight coupling between physical signals and digital processing,
- deterministic timing and synchronized data flow,
- continuous monitoring and computational feedback loops.

These principles justify the system's architecture, where fuel-level signals, GPS data, and operational states are processed and transmitted in real time.

3.2.2 Sensor Theory and Signal Measurement

Fuel-level readings extracted through the CAN bus/OBD-II interface follow digital measurement theory. Sensor signals can exhibit noise, quantization error, and environmental fluctuation. To improve stability, the system uses a Simple Moving Average (SMA) filter, a standard smoothing method defined as:

$$x_t^{\text{smooth}} = \frac{1}{N} \sum_{i=0}^{N-1} x_{t-i} \quad (3.1)$$

This reduces high-frequency noise and creates a clearer trend for anomaly detection algorithms.

3.2.3 Time-Series Synchronization Theory

Sensor streams often arrive at irregular timestamps. Synchronizing them requires interpolation theory. For two samples at timestamps T_i and T_{i+1} , the interpolated point at t_j is computed as:

$$x_j = x_i + \left(\frac{x_{i+1} - x_i}{T_{i+1} - T_i} \right) (t_j - T_i) \quad (3.2)$$

This ensures aligned and consistent time-series data across fuel level, GPS speed, and distance.



3.2.4 IoT Communication Theory

The communication subsystem relies on Internet of Things (IoT) principles and long-range wireless communication theory. LoRa operates using Chirp Spread Spectrum (CSS) modulation, characterized by:

- long-range transmission,
- low power consumption,
- robustness to interference.

Theoretical latency between sender and cloud receiver is expressed as:

$$L = T_{\text{received}} - T_{\text{sent}} \quad (3.3)$$

Understanding latency is essential for analyzing responsiveness and real-time performance.

3.2.5 GPS Temporal and Spatial Theory

GPS logging follows Global Navigation Satellite System (GNSS) principles. To evaluate consistency of GPS sampling, the inter-arrival interval is computed as:

$$t_i = T_i - T_{i-1} \quad (3.4)$$

Maintaining a stable interval ensures accurate reconstruction of routes and distance traveled.



1045

3.2.6 Unsupervised Anomaly Detection Theory

1046

1047

1048

1049

1050

1051

1052

1053

1054

1055

The anomaly detection component relies on non-parametric, unsupervised machine learning, which identifies unusual behavior in multivariate time-series data without labeled training samples. Following the taxonomy adopted for vehicle anomaly detection [Hirth et al., 2025], three anomaly types are distinguished: point anomalies, or individual observations that are anomalous with respect to the data, such as a sudden fuel drop while stationary; contextual anomalies, which are anomalous only in context, such as high consumption at zero speed; and collective or subsequence anomalies, where a sequence of individually unremarkable observations forms an anomalous pattern, such as gradual siphoning. The system assigns point and contextual anomalies to Isolation Forest, operating on engineered contextual features, and collective anomalies to the Matrix Profile.

1056

3.2.6.1 Matrix Profile Theory

1057

1058

Matrix Profile computes similarity between subsequences within a time series. For a time series T of length n and window size m , the profile value is:

$$P[i] = \min_{j \neq i} \|T_{i:i+m-1} - T_{j:j+m-1}\| \tag{3.5}$$

1059

1060

The subsequences with the highest $P[i]$ values, known as discords, are likely anomalies. This method is ideal for detecting sudden fuel drops or siphoning patterns.

1061

3.2.6.2 Isolation Forest Theory

1062

1063

Isolation Forest isolates anomalies through random partitioning. An anomaly score is expressed as:

$$s(x) = 2^{-\frac{E(h(x))}{c(n)}} \tag{3.6}$$



Where:

- $E(h(x))$ is the expected path length for observation x ,
- $c(n)$ normalizes the tree depth by dataset size.

Higher scores indicate higher likelihood of anomalous fuel behavior.

3.3 Summary

This chapter presented the theoretical foundation for the system's methodology. It discussed the key concepts supporting real-time sensing, signal preprocessing, GPS logging, IoT communication, and unsupervised anomaly detection. By establishing these theoretical pillars, this chapter clarifies the scientific basis that makes the system's design viable, accurate, and aligned with established models in engineering and data science.



De La Salle University

1074

Chapter 4

1075

DESIGN CONSIDERATIONS



1076 This chapter presents the design considerations that guided the development of the
 1077 proposed IoT- and AI-driven fuel monitoring and anomaly detection system. Whereas
 1078 Chapter 3 established the theoretical foundations of IoT architectures, cyber-physical
 1079 systems, signal processing, and unsupervised anomaly detection, the present chapter
 1080 translates those theories into practical engineering decisions that were directly implemented
 1081 in Chapter 5.

1082 These design considerations serve as the structural “columns” of the system: grounded
 1083 in accepted standards, ethical guidelines, and engineering best practices, but tailored
 1084 to support the procedural steps carried out in Chapter 5. The discussion begins with a
 1085 comprehensive account of the technical standards that ensure reliability, safety, interoper-
 1086 ability, and data security, followed by software and hardware design decisions. Ethical
 1087 considerations—including privacy, responsible AI, and driver safety—are also presented.

1088 4.1 Standards

1089 4.1.1 Adherence to Technical Standards

1090 To ensure reliability, accuracy, and safety, the proposed fuel anomaly detection system is
 1091 developed in accordance with established engineering and IT standards. These standards
 1092 ensure interoperability, scalability, and long-term viability. They directly influence the
 1093 system architecture, data handling, and model implementation workflows outlined in
 1094 Chapter 5.

1095 1. Standards for Sensors and Hardware

1096 The system integrates sensors and modules that employ standard communication



1097 protocols—**CAN bus/OBD-II, UART, I2C, and GPIO**—consistent with IEEE 1451
1098 smart transducer guidelines [IEEE Standards Association,]. The CAN bus/OBD-II
1099 fuel data acquisition aligns with industry telematics conventions [iso, 2020], while
1100 the GPS module adheres to global navigation and timing standards [NASA EarthData,
1101 2025].

1102 Safety-related components (buzzer, indicators, MCU GPIO outputs) comply with
1103 IEC 61131-2 and ISO 7637 automotive power and electromagnetic compatibility
1104 guidelines [iec, , iso, d]. All embedded electronics meet CE and FCC certifications
1105 [cec, 2022, fcc,] to ensure environmental and electrical safety.

1106 **2. Data Acquisition and Signal Processing**

1107 Signal conditioning and acquisition follow recommended standards for reliable
1108 sensor data handling [iso, e]. A Simple Moving Average (SMA) filter is applied to
1109 the fuel-level signal to reduce noise while preserving sharp variations indicative of
1110 anomalies.

1111 Time alignment of fuel, GPS, speed, and engine readings follows ISO/IEC 19510 prin-
1112 ciples for structured time-series data [iso, e]. These standard-aligned preprocessing
1113 steps feed into the anomaly detection models described in Chapter 5.

1114 **3. Communication and Data Transmission**

1115 Communication follows TCP/IP standards under IETF and IEEE 802.11 [rfc, ,
1116 Samainstage, 2025], while MQTT serves as the primary IoT protocol following OA-
1117 SIS specifications. End-to-end encryption via TLS/SSL aligns with ISO/IEC 27001
1118 cybersecurity requirements [iso, 2022a].



1119 These communication strategies form the basis for the system's message-handling
1120 and cloud-upload mechanisms in Chapter 5.

1121 4. Machine Learning and Model Validation

1122 The Matrix Profile and Isolation Forest models are implemented using open-source
1123 libraries, and their evaluation follows ISO/IEC 29119 software quality standards
1124 [iso, 2022b]. Validation metrics—confusion matrices, ROC curves, precision–recall
1125 graphs—provide statistical grounding for model evaluation, as presented in Chapter 5.

1126 5. Software Architecture and Data Management

1127 The modular software design complies with ISO/IEC/IEEE 42010 architectural
1128 principles [iso, g]. ACID-compliant storage and GDPR-/ISO 27018-aligned data
1129 protection protocols [iso, f] ensure data integrity and privacy. All processed datasets
1130 follow FAIR principles.

1131 4.1.2 Observance of Research Ethics

1132 Ethical considerations guide the responsible deployment of the system, especially given the
1133 safety-critical and privacy-sensitive context of transportation fleets. Three major ethical
1134 domains were identified: data privacy, system safety, and responsible AI.

1135 Data Privacy and Security

1136 The system adopts:

- 1137 • informed consent prior to any data collection,
- 1138 • strict access control and secure data storage,



- 1139 • anonymization and aggregation when feasible,
- 1140 • transparency in data usage and access rights,
- 1141 • compliance with national and international privacy regulations.

1142 **System Safety and Occupational Risk Management**

1143 Given the operational risks of fleet environments, the design aligns with ISO 45001,
 1144 ISO 26262, and ISO 39001 [iso, c, iso, a, iso, b]. Safety-oriented measures include:

- 1145 • minimizing driver distraction,
- 1146 • reducing false alarms through validation,
- 1147 • providing adequate training for users,
- 1148 • implementing clear protocols for anomaly response.

1149 **Responsible AI and Algorithmic Accountability**

1150 Consistent with IEEE P7003 [iee,], the system incorporates:

- 1151 • explainability mechanisms for anomaly outputs,
- 1152 • documentation of roles and responsibilities in alert handling,
- 1153 • defined liability procedures for system errors,
- 1154 • safeguards against algorithmic bias.



4.2 Technical Design Considerations

This section elaborates on the engineering decisions and standards that guided the development of the proposed IoT- and AI-driven fuel monitoring and anomaly detection system. Each component, software layer, algorithm, and communication protocol is grounded in established standards to ensure reliability, safety, interoperability, and security. The references indicate where each design decision is applied in the implementation procedures described in Chapter 5.

4.2.1 Hardware Selection and Integration

The hardware configuration is designed to support the end-to-end workflow of the system (see Chapter 5.2). The following standards and implementation points apply:

- **MCU:** ESP32/NodeMCU serves as the edge processing device for real-time acquisition and preprocessing of fuel, GPS, and vehicle telemetry data. It complies with IEC 61131-2 for embedded controllers [iec,] and ISO 7637 for automotive electrical transients [iso, d]. In Chapter 5.2, the MCU handles sensor filtering, timestamping, and local anomaly scoring.
- **GPS Module:** The UART-connected GPS module provides geolocation and speed data, adhering to global navigation standards [NASA EarthData, 2025]. Its signals are synchronized with fuel readings during preprocessing in Chapter 5.2.
- **CAN/OBD-II Interface:** Vehicle telemetry (engine RPM, ignition status, and ECU-reported fuel consumption) is captured using the CAN/OBD-II interface, following



ISO 15765 and ISO 15031 telematics standards [iso, 2020]. Chapter 5.2 details how this data is collected and correlated with sensor readings.

- **Safety Indicators:** Buzzer output comply with IEC 61131-2 and ISO 26262 functional safety requirements [iso, a]. These indicators provide immediate alerts to drivers (Chapter 5.2, Subsection on Driver Alerts).

4.2.2 Software Architecture

The modular software layers are designed according to ISO/IEC/IEEE 42010 software architecture standards [iso, g], supporting scalability, maintainability, and interoperability. Each layer's function is mapped to its implementation in Chapter 5.2:

- **Data Acquisition Layer:** Captures sensor and telemetry data, applies SMA and median filters, and performs anomaly threshold checks. Implementation details are in Chapter 5.2.
- **Processing Layer:** Performs edge anomaly detection, timestamping, and data aggregation. Standards for real-time processing and task scheduling ensure predictable latency. Implementation is in Chapter 5.2.
- **Cloud Integration Layer:** MQTT-based JSON payloads are used for cloud ingestion, following OASIS MQTT v5 and ISO/IEC 27001 security standards [iso, 2022a]. TLS/SSL ensures encrypted transmission (Chapter 5.2).
- **User Interface Layer:** Dashboards display real-time fuel levels, GPS locations, anomaly alerts, and historical trends. Web standards (HTML5, CSS3, JavaScript) and secure REST APIs are employed, as described in Chapter 5.2.



4.2.3 Machine Learning and Algorithms

Machine learning components follow ISO/IEC 29119 software quality standards [iso, 2022b] and IEEE P7003 AI accountability guidelines [iee,]:

- **Models:** Isolation Forest and Matrix Profile detect anomalies both at edge and cloud levels. Their implementation and evaluation are detailed in Chapter 5.2.
- **Evaluation Metrics:** Confusion matrices, ROC curves, and precision–recall graphs are used for model validation, ensuring alignment with ISO/IEC 25010 software quality characteristics. Chapter 5.2, Chapter 5.3 provides practical application in performance evaluation.
- **Alternative Models:** Autoencoders and LSTM networks were considered but excluded due to edge processing constraints, as justified in Chapter 4.3.

4.2.4 Communication and Security

Communication protocols and security measures are aligned with ISO/IEC 27018, ISO/IEC 27001, and GDPR standards to ensure data privacy, encryption, and secure access control:

- **MQTT Protocol:** Supports lightweight, reliable IoT messaging, implemented with QoS 1 to guarantee delivery. Applied in Chapter 5.2.
- **TLS/SSL Encryption:** Provides end-to-end encryption for transmitted data. Compliance with ISO/IEC 27001 ensures data integrity and confidentiality. Applied in Chapter 5.2.



1215 • **Role-Based Access and Anonymization:** Enforces secure data access policies and
1216 anonymizes sensitive driver information, complying with ISO/IEC 27018 and GDPR
1217 principles. Applied in Chapter 5.2.

1218 • **JSON Serialization:** Standardized data format for cloud compatibility, ensuring
1219 interoperability with cloud services and dashboards. Applied in Chapter 5.2.

1220 4.3 Alternative Software Designs and Cost Consid- 1221 erations

1222 During the planning and prototype development phase, several candidate software designs
1223 were evaluated for their suitability to the system’s requirements. Table 4.1 summarizes
1224 the strengths, potential risks, and fit relative to the system specifications. Matrix Profile
1225 (MP), Isolation Forest (IF), and a combined Matrix Profile + Isolation Forest (MP + IF)
1226 configuration were implemented and tested to compare their effectiveness in detecting
1227 fuel-related anomalies. The comparison considered detection accuracy, computational
1228 efficiency, and deployment feasibility on the target hardware platform. The findings from
1229 these tests were used to determine the most appropriate approach for the final system
1230 implementation.

1231 A cost study was conducted after prototype testing to confirm that the system con-
1232 figuration was cost-effective. This study reviewed hardware, software, and development
1233 resources, comparing the chosen open-source and local execution setup against alternative
1234 configurations such as commercial analytics tools, cloud-based computing, or hardware-
1235 integrated telemetry systems.



TABLE 4.1 ALTERNATIVE SOFTWARE DESIGNS EVALUATED FOR THE PROTOTYPE

Candidate	Strengths	Risks / Trade-offs	Fit vs. Spec
Isolation Forest (IF)	Fast, unsupervised, handles multivariate data; simple to deploy using scikit-learn	Limited temporal context; sensitivity to contamination parameter may affect false alarms	High
Matrix Profile (MP)	Shape-based time-series discord detection; ideal for sudden fuel drops or irregular usage patterns; efficient in local runtime	Requires window-size tuning; primarily one-dimensional unless extended for multivariate data	Very High

The total estimated budget for developing and implementing the prototype system is **PHP 10,446**, confirming that the selected configuration remains the optimal and sustainable choice for achieving the project’s objectives.

4.4 Summary

This chapter presented the key technical and ethical design considerations that shape the system. By grounding the project in ISO, IEEE, OASIS, GDPR, and FAIR standards, the system ensures reliable data acquisition, secure communication, validated machine learning, and responsible AI use.

These design elements establish the foundation for the procedures described in Chapter 5, bridging theoretical concepts from Chapter 3 with the practical implementation steps of the system.



De La Salle University

1247

Chapter 5

1248

METHODOLOGY



1249 This chapter presents the research methodology employed for the development of an
1250 Machine Learning-driven fuel monitoring and anomaly detection system for fleet vehi-
1251 cles. The methodology integrates a multi-layered approach combining sensor-level data
1252 acquisition, edge computing, IoT communication, cloud-based machine learning, and
1253 client-side visualization. The approach emphasizes real-time anomaly detection, accurate
1254 fuel monitoring, operational transparency, and actionable driver and fleet management
1255 insights.

1256 The research methodology is structured to address both general and specific objectives,
1257 ensuring that the system is technically feasible, scalable, and reliable. Figure 5.2 and
1258 Table 5.1 summarize the methods and approaches for each objective.

TABLE 5.1 SUMMARY OF METHODS FOR REACHING THE OBJECTIVES

Objectives	Methods / Approaches	Locations
------------	----------------------	-----------



GO: Develop and evaluate an IoT-based system for trucks in collaboration with Hino Parañaque Subic GS Auto Inc. (SGSA) that monitors real-time fuel levels, tracks routes using GPS, and detects unusual fuel consumption using machine learning, improving driver safety, supporting rest scheduling, and facilitating proactive vehicle maintenance through automated alerts.	• Embedded MCU preprocessing and aggregation • LoRa/Cellular communication for low-latency and fail-safe data transfer • Cloud-based machine learning for anomaly detection • Web dashboard for visualization • Driver alert subsystem for operational safety	Sec. 5.2
SO1: Measure fuel levels using digital float sensors integrated via the truck's ECU/diagnostic connector and GPS module, ensuring non-invasive installation and real-time accuracy within $\pm 5\%$.	• Digital fuel sensors interfaced with ECU/OBD-II • Signal filtering and smoothing • Calibration against manual measurements • Continuous validation for measurement reliability	Sec. 5.2



SO2: Transmit real-time fuel and GPS data through IoT-based communication to a cloud server, accessible through a centralized dashboard.	• Real-time IoT transmission via LoRa (primary) and Cellular Connection (backup) • Cloud ingestion APIs • Latency measurement and benchmarking to ensure timely reporting	Sec. 5.2
SO3: Capture and log GPS location data every 5 seconds via an embedded module, correlating route information with fuel and time data for behavior tracking.	• GPS-based location logging at 5-second intervals • Synchronization with fuel data • Structured cloud database for multi-source data storage and route-fuel correlation	Sec. 5.2
SO4: Design and evaluate a context-aware fuel usage deviation modeling approach using non-parametric unsupervised ML models (Matrix Profile or Isolation Forest), achieving 90% precision and 10% false positives.	• Offline training of anomaly detection models using Isolation Forest and Matrix Profile • Evaluation using precision, FPR, and accuracy • Context-aware thresholding to reduce false positives	Sec. 5.2
SO5: Develop and integrate hardware-based rest and maintenance alert mechanisms (e.g., Start/Stop button, buzzer indicators) tied to the web dashboard using cumulative fuel and distance data.	• Driver rest and maintenance alert system with cumulative distance/time tracking • Cloud-based monitoring and logging • Alert notification via dashboard and in-vehicle signals	Sec. 5.2



5.1 System Architecture and Conceptual Design




Fig. 5.1 Proposed Conceptual Diagram

The system follows a layered architecture with a focus on modularity, scalability, and reliability. The conceptual framework (Figure 5.1) integrates the following:

- **Vehicle Sensing Subsystem:** Digitally calibrated fuel-level sensors, GPS modules, and driver rest-time monitors. Sensor signals are collected via ECU or OBD-II ports.
- **Edge Processing:** The MCU performs signal preprocessing, filtering, smoothing, synchronization, and timestamping before transmission.



1266 • **IoT Communication:** LoRa transceivers enable low-power, long-range data trans-
1267 mission; cellular backup, balancing cost and bandwidth considerations.

1268 • **Cloud Intelligence:** Historical data is used to train unsupervised ML models (Iso-
1269 lation Forest, Matrix Profile) to detect anomalies. The cloud evaluates incoming
1270 real-time data and triggers alerts.

1271 • **Client Visualization:** A web-based dashboard provides real-time visualization of
1272 fuel levels, routes, alerts, and historical playback for decision-making.

1273 The system architecture (Figure 5.2) follows a layered, end-to-end IoT design composed
1274 of three major layers: the data acquisition layer, the communication and cloud processing
1275 layer, and the data visualization layer. This structure supports real-time fuel monitoring,
1276 GPS-based route tracking, driver safety alerts, and cloud-based anomaly detection.

1277 At the data acquisition layer, the vehicle is outfitted with digitally calibrated float
1278 sensors integrated through the truck’s ECU/diagnostic connector to obtain accurate fuel-
1279 level measurements. The microcontroller (MCU) serves as the primary edge device,
1280 interfacing with the float sensor, GPS module (logging coordinates at 5-second intervals),
1281 rest alert subsystem, and time-tracking module. A LoRa transceiver functions as the main
1282 channel for transmitting fuel, location, and operating-hour data to the cloud, while the
1283 cellular module is used as fallback.

1284 The communication and cloud processing layer handles real-time data ingestion and
1285 anomaly detection. Incoming packets from the vehicle are received through cloud-based
1286 API endpoints and routed to processing services where the trained machine learning
1287 model—developed offline using Matrix Profile or Isolation Forest—is deployed for fuel
1288 anomaly evaluation. A Python-based alert engine evaluates fuel–location–time patterns




Fig. 5.2 Proposed System Architecture Diagram

and generates automated rest reminders, maintenance notifications, and anomaly flags. All validated data and event logs are stored in a centralized cloud database for long-term analysis.

The data visualization layer consists of a web-based monitoring dashboard that retrieves information from the cloud database. Through this interface, clients can view real-time truck locations, fuel levels, distance traveled, driver operating hours, and alert notifications. The dashboard also supports historical playback of route and fuel usage trends, enabling



1296 improved operational awareness and proactive decision-making.

1297 Overall, the architecture highlights the complete data flow—from ECU-integrated
1298 sensing and MCU preprocessing, to IoT communication, to cloud-based machine learning
1299 and dashboard visualization—demonstrating a scalable and modular IoT system for fleet
1300 monitoring and anomaly detection.

1301 **5.2 Implementation**

1302 **5.2.1 Data Acquisition and Preprocessing**

1303 Data acquisition and preprocessing are crucial for reliable anomaly detection. The method-
1304 ology includes:

- 1305 1. **Sensor Calibration:** Fuel-level sensors are calibrated using known volumes, verified
1306 with manual measurements, and cross-checked with historical data trends.
- 1307 2. **Signal Filtering:** Raw sensor signals are filtered using moving-average and median
1308 filters to reduce noise caused by vehicle motion or fuel sloshing.
- 1309 3. **Synchronization:** Fuel, GPS, and operating-hour data are timestamped and synchro-
1310 nized to ensure consistent data alignment for model evaluation.
- 1311 4. **Feature Engineering:** Derived features include fuel consumption rate, distance-to-
1312 fuel ratio, route segment performance, and driver behavior metrics, which feed into
1313 anomaly detection models.



Study Procedures

Upon voluntary agreement to participate, the study procedures will be conducted as follows:

1. Before the trip begins, a member of the research team will install a monitoring device or IoT module unit in the truck assigned to the participant.
2. Once installed, the device will automatically record fuel-level readings at regular intervals, distance and travel time, and GPS location data during normal vehicle operations.
3. For randomly selected trips, participants may be asked to perform a supervised task simulating fuel draining from the tank. This procedure will be conducted to test the accuracy of the prototype's anomaly detection function.
4. Participants will not be required to change their normal driving behavior during the data collection period.
5. After the data collection period is completed, a member of the research team will remove the monitoring device from the vehicle.
6. The study will also conduct a survey with the fleet administrator to gather feedback on the device's functionality and any problems encountered during its use. The survey will not be administered to the drivers and will not include personal questions directed at them.

Risks and Discomforts

This study involves minimal risk. The following potential risks and discomforts have been identified:



- The monitoring device will not control, modify, or interfere with the vehicle's systems and will not affect driving performance or safety. It will passively record only fuel-level data, GPS data, and travel information.
- Participants may experience minor inconvenience or brief disruption during the installation and removal of the monitoring device before and after the trip.
- GPS location data will be collected during normal operations, which may raise privacy concerns. However, the data will be anonymized through a unique code number assigned to each dataset and will be shared only with authorized members of the research team and Hino Paranaque's fleet administrator for academic research purposes.
- No foreseeable psychological, physical, or occupational risks are expected to result from participation in this study.

Steps to Minimize Risks

The research team will undertake the following measures to minimize and mitigate potential risks:

- The monitoring device will be installed and removed only by a member of the research team to ensure that the vehicle's systems are not disrupted.
- All collected data will be anonymized by replacing participant names with unique code numbers before analysis.
- Access to raw data will be restricted to authorized members of the research team and Hino Paranaque's fleet administrator only.



- All digital data will be stored in a secure, password-protected system to prevent unauthorized access.
- Physical documents, such as signed consent forms, will be kept in a locked cabinet accessible only to the principal investigator and faculty adviser.
- Data will be used only for academic purposes, and only summarized and anonymized results will be included in reports or publications.

Benefits

Participants will not receive direct financial benefits from participation. However, the results of this study may contribute to the following non-monetary benefits:

- **For the partner company and fleet managers:** The system may improve fuel efficiency monitoring and support the detection and prevention of fuel misuse, leakage, or theft.
- **For the transportation and logistics industry:** The study contributes to research on non-parametric machine learning approaches for fleet management, which may inform future industry practices.
- **For the public and the environment:** Improved fuel monitoring systems may help reduce fuel waste and contribute to lower carbon emissions.
- **For the research community:** The findings may add to academic knowledge on IoT-based monitoring systems and anomaly detection methods in real-world applications.

**Compensation**

Participants will not receive any compensation, tokens, or gifts for their participation in this study.

Data Storage, Duration, and Disposal

Storage of Digital Data: All digital data collected by the monitoring device will be stored in a Supabase cloud database, a secure and password-protected platform accessible only to authorized members of the research team. Files and database entries will be protected by unique credentials known only to the principal investigator and faculty adviser.

Storage of Physical Data: Signed consent forms and any printed documents will be stored in a locked filing cabinet located at the research team's office. Only the principal investigator and faculty adviser will have access to these physical documents.

Duration of Storage: All digital and physical data will be retained for five (5) years from the date of completion of the study, in accordance with De La Salle University's data retention policy.

Disposal: After the retention period, all digital data will be permanently deleted from the Supabase database and any local copies using secure deletion procedures. All physical documents will be cross-shredded and disposed of in a secure manner.

Confidentiality

For Digital Data: Participant names will not appear in any reports, datasets, publications, or presentations. A unique code number will be assigned to each participant's data in place of the participant's name. All digital files will be stored in a password-protected Supabase cloud database accessible only to the research team. Data will be used strictly for academic



research purposes, and only summarized and anonymized results will be presented in the final thesis or any related publications.

For Physical Data: Signed consent forms and any printed documents will be stored in a locked cabinet. Only the principal investigator and faculty adviser will have access to these hard copy documents.

Withdrawal Procedure

Participation in this study is entirely voluntary, and participants may withdraw at any time without penalty. To withdraw, participants may follow these steps:

1. Inform the principal investigator, Samuelle P. Barja, of the decision to withdraw, either verbally or in writing.
2. Contact the principal investigator through the following:
 - samuelle_barja@dlsu.edu.ph
 - 09564054471
3. Upon notification of withdrawal, the research team will immediately stop collecting data from the participant's assigned vehicle.
4. Any data already collected that is identifiable to the participant will be permanently deleted from all storage systems within a reasonable timeframe.
5. Participants will not be required to provide any reason for withdrawal, and the decision to withdraw will not result in any consequence to their employment or relationship with their employer.



1417

5.2.2 System Methodology

1418

The system was implemented as follows:

1419

- **MCU and Edge Layer:** ESP32/NodeMCU microcontrollers for filtering, timestamping, and initial anomaly scoring.

1420

1421

- **Vehicle Interfaces:** CAN bus or OBD-II for fuel-level readings; GPS module for location and speed tracking.

1422

1423

- **Communication Layer:** LoRa transceivers for real-time cloud updates; cellular backup for critical alerts.

1424

1425

- **Cloud Layer:** Python-based ML models for anomaly detection deployed on cloud servers; REST APIs for data ingestion; PostgreSQL database for structured storage.

1426

1427

- **Visualization Layer:** Web dashboard for real-time monitoring, historical trend analysis, and alert management.

1428

1429

5.2.3 Anomaly Detection and ML Methodology

1430

The anomaly detection workflow is as follows:

1431

1. **Offline Model Training:** Historical datasets are used to train Isolation Forest and Matrix Profile models to detect abnormal fuel usage patterns.

1432

1433

2. **Context-Aware Thresholding:** Thresholds are dynamically adjusted based on vehicle type, route segment, and driver behavior to reduce false positives.

1434

1435

3. **Evaluation Metrics:** Precision, FPR, accuracy, and detection latency are calculated; confusion matrices, ROC, and PR curves visualize performance.

1436



1437 **5.2.4 IPO Chart and Design Pipeline**

1438 The data design outlines a cohesive pipeline which integrates sensor acquisition, syn-
1439 chronization, cloud transmission, and model-based analysis to enable real-time anomaly
1440 detection in fleet fuel systems. Data collection begins with embedded sensors capturing raw
1441 signals such as fuel level, fuel flow, GPS coordinates, and ignition events. These signals
1442 are preprocessed using filters and signal conditioning circuits to reduce noise and ensure
1443 clean input for analysis.

1444 To ensure temporal alignment, all sensor outputs are timestamped and resampled
1445 onto a uniform time grid using linear interpolation. This synchronization step is critical
1446 for comparing trends across sensor modalities and detecting correlated anomalies. The
1447 processed signals are then uploaded to a cloud-based platform for storage and remote
1448 access.

1449 For anomaly detection, the synchronized time-series data are used to train and evaluate
1450 unsupervised models such as Isolation Forest and Matrix Profile. These models are tested
1451 on a dataset composed of real-world and simulated scenarios to reflect both normal and
1452 anomalous behavior. Key performance metrics (including MAPE, timestamp drift, detection
1453 latency, precision, and false positive rate) are used to assess system effectiveness. This
1454 pipeline supports scalable, automated monitoring while laying the groundwork for further
1455 model refinement in future stages.

1456 **5.2.5 IPO Chart**

1457 The IPO (Input-Process-Output) chart provides a structured overview of the IoT-based fleet
1458 fuel monitoring and anomaly detection system (Figure 5.3). The input data consists of




Fig. 5.3 IPO Chart

1459 real-time readings from the truck’s CAN bus/OBD-II fuel signal, GPS module capturing
1460 coordinates and speed at 5-second intervals, ignition status, and in-cab rest alert subsystem
1461 signals. These inputs are supplemented by historical fuel anomaly datasets and synthetic
1462 anomalies to simulate rare or edge-case events. Moderating variables such as driving
1463 behavior (idle times, acceleration patterns, terrain), network conditions (signal strength,
1464 transmission delays), and environmental factors (temperature, vibration) also influence the
1465 data.

1466 The process begins with signal preprocessing, where the MCU filters, calibrates, and
1467 timestamps fuel, GPS, and ignition data to reduce noise and ensure synchronization. The
1468 preprocessed data is then transmitted through LoRa as the primary communication channel,
1469 with GSM acting as a backup for essential alerts, and stored in a cloud-based backend.
1470 Anomaly detection is carried out in the cloud using machine learning models, including
1471 Matrix Profile (STUMPY) for time-series discord identification and Isolation Forest for
1472 feature-based outlier detection. Model validation and evaluation are performed using
1473 labeled and test datasets, calculating performance metrics such as precision, false positive
1474 rate (FPR), detection latency, and overall accuracy.

1475 The system outputs include fuel anomaly flags, such as potential theft or leakage, and



1476 driver rest alerts based on cumulative distance or driving duration. Additionally, it provides
1477 real-time GPS tracking on a web dashboard, estimated fuel levels as a percentage of tank
1478 capacity, and quantitative performance metrics for operational evaluation. This end-to-end
1479 flow ensures accurate, real-time monitoring, proactive safety notifications, and actionable
1480 insights for fleet management.

1481 **5.3 Evaluation**

1482 To evaluate these models, the outputs are validated against manually labeled ground truth
1483 data. From this, the number of true positives (TP), false positives (FP), true negatives (TN),
1484 and false negatives (FN) are counted. Key metrics are computed as follows:

1485 **Precision**

$$\text{Precision} = \frac{TP}{TP + FP} \tag{5.1}$$

1486 Precision reflects how many detected anomalies are truly anomalous. A high precision
1487 means fewer false alarms, which is important for maintaining trust in the alerting system.

1488 **False Positive Rate (FPR)**

$$\text{FPR} = \frac{FP}{FP + TN} \tag{5.2}$$

1489 FPR quantifies the likelihood of incorrectly classifying normal behavior as anomalous.
1490 Lower FPR values are desired to reduce noise in the system’s alerts.

1491 **Accuracy Accuracy**

$$\text{Accuracy} = \frac{TP + TN}{TP + TN + FP + FN} \tag{5.3}$$

1492 Accuracy provides an overall view of model correctness but can be misleading in
1493 imbalanced datasets, which is why it’s used alongside precision and FPR.



1494

All these metrics use the following classification outcomes:

TP (True Positives) = Number of correctly identified anomalies,

FP (False Positives) = Number of normal events incorrectly flagged as anomalies,

TN (True Negatives) = Number of correctly identified normal cases,

FN (False Negatives) = Anomalies that were missed by the model.

1495

Detection Latency

$$L_{\text{det}} = T_{\text{detected}} - T_{\text{actual}} \tag{5.4}$$

1496

where:

T_{detected} = the time the anomaly truly occurred,

T_{actual} = the time it was identified by the system.

1497

The objective is achieved if the unsupervised system attains at least 90% precision

1498

(indicating that the majority of flagged events are correct), a false positive rate not exceeding

1499

10%, and average detection latency under 10 seconds. For interpretability, confusion

1500

matrices and performance plots such as ROC and PR curves will be used. Detection

1501

events will also be overlaid on synchronized GPS location maps and fuel-level graphs for

1502

context-aware validation.

1503

5.4 Summary

1504

This chapter presented a comprehensive methodology for an AI-driven fuel monitoring and

1505

anomaly detection system. The approach integrates sensor-level calibration, edge prepro-



1506 censing, IoT-based communication, cloud ML evaluation, and client-side visualization to
1507 achieve accurate, real-time, and actionable insights.



REFERENCES

- [iec,] Iec 61131-2:2017. <https://webstore.iec.ch/en/publication/31007>. Accessed: 2025-11-27.
- [iee,] Ieee p7003: Algorithmic bias considerations. <https://standards.ieee.org/ieee/7003/11357/>. Accessed: 2025-11-27.
- [fcc,] Ieee xplore full-text pdf. <https://ieeexplore.ieee.org/stamp/stamp.jsp?arnumber=10602499>. Accessed: 2025-11-27.
- [iso, a] Iso 26262-1:2011. <https://www.iso.org/standard/43464.html>. Accessed: 2025-11-27.
- [iso, b] Iso 39001:2012. <https://www.iso.org/standard/44958.html>. Accessed: 2025-11-27.
- [iso, c] Iso 45001:2018. <https://www.iso.org/standard/63787.html>. Accessed: 2025-11-27.
- [iso, d] Iso 7637-2:2011. <https://www.iso.org/standard/50925.html>. Accessed: 2025-11-27.
- [iso, e] Iso/iec 19510:2013. <https://www.iso.org/standard/62652.html>. Accessed: 2025-11-27.
- [iso, f] Iso/iec 27018:2025. <https://www.iso.org/standard/27018>. Accessed: 2025-11-27.
- [iso, g] Iso/iec/ieee 42010:2022. <https://www.iso.org/standard/74393.html>. Accessed: 2025-11-27.
- [rfc,] Rfc 791: Internet protocol. <https://datatracker.ietf.org/doc/html/rfc791>. Accessed: 2025-11-27.
- [iso, 2015] (2015). Iso 14001:2015 environmental management systems. <https://www.iso.org/standard/60857.html>. ISO.
- [aut, 2019] (2019). Automatic fuel monitoring system. *International Journal of Recent Technology and Engineering*, 8(4S2):348–352.
- [iso, 2020] (2020). Iso/ts 15143-3:2020: Earth-moving machinery and mobile machines — work-site data exchange — part 3: Telematics data. <https://www.iso.org/standard/76394.html>. ISO.
- [cec, 2022] (2022). Ce marking – obtaining the certificate, eu requirements. https://europa.eu/youreurope/business/product-requirements/labels-markings/ce-marking/index_en.htm. Accessed: 2025-11-27.
- [iso, 2022a] (2022a). Iso/iec 27001:2022 information security management systems. <https://www.iso.org/standard/27001>. ISO.
- [iso, 2022b] (2022b). Iso/iec/ieee 29119-1:2022 software and systems engineering — software testing. <https://www.iso.org/standard/81291.html>. ISO.
- [iso, 2023] (2023). Iso 50001 — energy management systems. <https://www.iso.org/iso-50001-energy-management.html>. ISO.
- [iso, 2024] (2024). Iso/pas 8800:2024 road vehicles — safety and artificial intelligence. <https://www.iso.org/standard/83303.html>. ISO.



- [Ahmed et al., 2017] Ahmed, A. A. I., Mohammed, S. A. E., and Satte, M. A. M. H. (2017). Fuel management system. In *2017 International Conference on Communication, Control, Computing and Electronics Engineering (ICCCCEE)*, pages 1–7.
- [Alquhali et al., 2019] Alquhali, A. H., Roslee, M., Alias, M. Y., and Mohamed, K. S. (2019). IoT based real-time vehicle tracking system. In *2019 IEEE Conference on Sustainable Utilization and Development in Engineering and Technologies (CSUDET)*, pages 265–270.
- [Alsanad et al., 2020] Alsanad, H. R., Ucan, O. N., Ilyas, M., Khan, A. U. R., and Bayat, O. (2020). Real-time fuel truck detection algorithm based on deep convolutional neural network. *IEEE Access*, 8:118808–118817.
- [Aquize et al., 2017] Aquize, V. G., Emery, E., and de Lima Neto, F. B. (2017). Self-organizing maps for anomaly detection in fuel consumption. case study: Illegal fuel storage in bolivia. In *2017 IEEE Latin American Conference on Computational Intelligence (LA-CCI)*, pages 1–6.
- [Asian Development Bank, 2016] Asian Development Bank (2016). Fuel smuggling: 12 things to know. <https://www.adb.org/news/features/fuel-smuggling-12-things-know>. Accessed: 2026-06-21.
- [Barbado and Corcho, 2022] Barbado, A. and Corcho, Ó. (2022). Interpretable machine learning models for predicting and explaining vehicle fuel consumption anomalies. *Engineering Applications of Artificial Intelligence*, 115:105222.
- [Beteto et al., 2022] Beteto, A. et al. (2022). Anomaly and cyber fraud detection in pipelines and supply chains for liquid fuels. *Environment Systems and Decisions*, 42(2):306–324.
- [Chengdu Ebyte Electronic Technology Co., Ltd., 2024] Chengdu Ebyte Electronic Technology Co., Ltd. (2024). Lora module range: Key factors affecting lora communication. <https://www.cdebyte.com/news/622>. Accessed: 2026-06-19.
- [Cherdo et al., 2023] Cherdo, Y., Miramond, B., Pegatoquet, A., and Vallauri, A. (2023). Unsupervised anomaly detection for cars can sensors time series using small recurrent and convolutional neural networks. *Sensors*, 23(11):5013–5013.
- [Crisgar et al., 2021] Crisgar, P. V. et al. (2021). GPS-based vehicle tracking and theft detection systems using google cloud IoT core & firebase. In *2021 International Symposium on Electronics and Smart Devices (ISESD)*, pages 1–6.
- [Devalal and Karthikeyan, 2018] Devalal, S. and Karthikeyan, A. (2018). Lora technology - an overview. In *2018 Second International Conference on Electronics, Communication and Aerospace Technology (ICECA)*, pages 284–290, Coimbatore, India.
- [Dhiviyasri and Mariappan, 2015] Dhiviyasri, G. and Mariappan, R. (2015). Advanced fuel level tracking system using telematic unit. In *2015 IEEE International Conference on Electrical, Computer and Communication Technologies (ICECCT)*.
- [Farzana, 2020] Farzana, F. e. a. (2020). A real-time motion based fuel monitoring technique for vehicle tracking systems. In *2020 Emerging Technology in Computing, Communication and*



- 1577 *Electronics (ETCCE)*, pages 1–6.
- 1578 [Fleet Complete, 2026] Fleet Complete (2026). Fleet management and fuel reporting. <https://www.fleetcomplete.com/>. Accessed: 2026-06-21.
- 1579
- 1580 [Fleetio, 2026] Fleetio (2026). Fuel management system. [https://www.fleetio.com/solutions/](https://www.fleetio.com/solutions/fuel-management-software)
- 1581 [fuel-management-software](https://www.fleetio.com/solutions/fuel-management-software). Accessed: 2026-06-08.
- 1582 [Fortela et al., 2023] Fortela, D. L. B. et al. (2023). Unsupervised machine learning to detect
- 1583 impending anomalies in testing of fuel economy and emissions of light-duty vehicles. *Clean*
- 1584 *Technologies*, 5(1):418–435.
- 1585 [G et al., 2022] G, P. et al. (2022). Real time automatic vehicle monitoring system using IoT. In
- 1586 *2022 8th International Conference on Smart Structures and Systems (ICSSS)*, pages 1–6.
- 1587 [G, 2023] G, Y. e. a. (2023). Fuel monitoring in bike vehicles based on iot. In *2023 Intelligent*
- 1588 *Computing and Control for Engineering and Business Systems (ICCEBS)*, pages 1–5.
- 1589 [Garcia Vega, 2022] Garcia Vega, P. (2022). Development of a method for anomaly detection in
- 1590 time series applied to vehicle monitoring. Master’s thesis, Polytechnique Montréal.
- 1591 [Geotab, 2024] Geotab (2024). Fleet fuel management systems. [https://www.geotab.com/](https://www.geotab.com/fleet-management-solutions/fleet-fuel-management/)
- 1592 [fleet-management-solutions/fleet-fuel-management/](https://www.geotab.com/fleet-management-solutions/fleet-fuel-management/). Accessed: 2026-06-09.
- 1593 [GSMA, 2026] GSMA (2026). Network coverage maps. <https://www.gsma.com/coverage/#433>.
- 1594 Accessed: 2026-06-19.
- 1595 [Habib and Umar, 2015] Habib, K. and Umar, A. I. (2015). Anomalies calculation and detection in
- 1596 fuel expense through data mining. *Research Journal of Information Technology*, 6(4):44–50.
- 1597 [Hirth et al., 2025] Hirth, M., Meier, D., Gehring, O., Jazdi, N., and Kasneci, E. (2025). Unsuper-
- 1598 vised deep learning for anomaly detection in automotive trucks: A survey. *ACM Computing*
- 1599 *Surveys*, 58(5).
- 1600 [Husak,] Husak, V. e. a. Intelligent real-time vehicle tracking information system. n.d.
- 1601 [IEEE Standards Association,] IEEE Standards Association. Ieee standards association. <https://standards.ieee.org/ieee/1451.0/11001/>.
- 1602 Accessed: 2025-11-27.
- 1603 [Japan International Cooperation Agency, 2022] Japan International Cooperation Agency (2022).
- 1604 The project for comprehensive traffic management plan for metro manila final report main text.
- 1605 Technical report, Japan International Cooperation Agency.
- 1606 [Japan International Cooperation Agency, 2025] Japan International Cooperation Agency (2025).
- 1607 Jica and mmda commence a project on intelligent transportation system in line with the com-
- 1608 prehensive traffic management plan for metro manila. [https://www.jica.go.jp/english/overseas/](https://www.jica.go.jp/english/overseas/philippine/information/press/2024/rdsigningctmp02212025.html)
- 1609 [philippine/information/press/2024/rdsigningctmp02212025.html](https://www.jica.go.jp/english/overseas/philippine/information/press/2024/rdsigningctmp02212025.html). Accessed: 2026-06-21.
- 1610 [Jose, 2015] Jose, D. e. a. (2015). Intelligent vehicle monitoring using global positioning system
- 1611 and cloud computing. *Procedia Computer Science*, 50:440–446.
- 1612 [Joshi et al., 2024] Joshi, P. et al. (2024). Intelligent IoT-enabled real-time monitoring system



- for logistics management. In *2024 International Conference on Computing, Sciences and Communications (ICCSC)*, pages 1–5.
- [Kanchi et al., 2013] Kanchi, S., Sandilya, S., Bhosale, D., Pitkar, A., and Gondhalekar, M. (2013). Overview of lte-a technology. In *2013 IEEE Global High Tech Congress on Electronics*, pages 195–200, Shenzhen, China.
- [Komal Shoukat Ali et al., 2018] Komal Shoukat Ali, K. et al. (2018). Automatic fuel tank monitoring, tracking & theft detection system. In *MATEC Web of Conferences*, volume 184.
- [Krishnasamy, 2019] Krishnasamy, R. (2019). Automatic fuel monitoring system. *International Journal of Recent Technology and Engineering (IJRTE)*, 8(4S2):348–352. Accessed: 2025-11-18.
- [Lee et al., 2007] Lee, J. S., Su, Y. W., and Shen, C. C. (2007). A comparative study of wireless protocols: Bluetooth, uwb, zigbee, and wi-fi. In *Proceedings of the 33rd Annual Conference of the IEEE Industrial Electronics Society*, China.
- [Liu et al., 2008] Liu, F. T., Ting, K. M., and Zhou, Z.-H. (2008). Isolation forest. In *2008 Eighth IEEE International Conference on Data Mining*, pages 413–422, Pisa, Italy.
- [Llanto, 2017] Llanto, G. (2017). Cargo truck ban: Bad timing, faulty analysis, policy failure. Technical report, Philippine Institute for Development Studies.
- [Lu et al., 2022] Lu, Y., Wu, R., Mueen, A., Zuluaga, M. A., and Keogh, E. (2022). Matrix profile xxiv: Scaling time series anomaly detection to trillions of datapoints and ultra-fast arriving data streams. In *Proceedings of the 28th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*.
- [M, 2021] M, S. e. a. (2021). Digital fuel monitoring system for automobiles. In *2021 Second International Conference on Electronics and Sustainable Communication Systems (ICESC)*, pages 6–10.
- [Majeed, 2015] Majeed, A. (2015). Comparative studies of 3g, 4g & 5g mobile network & data offloading method a survey. *International Journal of Research in Information Technology*.
- [Manalu et al., 2023] Manalu, I. P., Sigiro, M. M. T., Wowiling, G. I., and Simatupang, F. (2023). Lora performance analysis with study case a moving object. *International Journal of Engineering Research in Computer Science and Engineering*, 10(12):11–16.
- [Mathi et al., 2024] Mathi, S. C. et al. (2024). Development of an intelligent fuel monitoring and theft detection system equipped with GPS & GSM integration, state of charge monitoring and realtime alarm generation. In *2024 International Conference on Innovative Computing and Communication Technologies (ICICT)*, pages 2095–2102.
- [Maurya,] Maurya, K. e. a. Real time vehicle tracking system using gsm and gps technology- an anti-theft tracking system. n.d.
- [Meitrack,] Meitrack. Lora-based fleet tracking solution. <https://www.meitrack.com/lora-based-fleet-tracking-solution/>. Accessed: 2026-06-19.
- [Miyim and Wakili, 2019] Miyim, A. and Wakili, A. (2019). Performance evaluation of lte net-



- works. In *2019 15th International Conference on Electronics, Computer and Computation (ICECCO)*.
- [Mukesh, 2010] Mukesh, P. R. (2010). Real time web based vehicle tracking using gps.
- [Mumcuoglu et al., 2023] Mumcuoglu, M. E. et al. (2023). Fuel consumption classification for heavy-duty vehicles: A novel approach to identifying driver behavior and system anomalies. In *2023 AEIT International Conference on Electrical and Electronic Technologies for Automotive (AEIT AUTOMOTIVE)*, pages 1–6.
- [Nada, 2017] Nada, Y. A. (2017). Design and implementation for trucks tracking system using gps based on semantic web. *International Journal of Trend in Scientific Research and Development*, 1(4).
- [NASA EarthData, 2025] NASA EarthData (2025). Global navigation satellite system. <https://www.earthdata.nasa.gov/data/space-geodesy-techniques/gnss>. Accessed: 2025-11-27.
- [Navixy, 2026] Navixy (2026). Sensors setup and configuration. <https://www.navixy.com/docs/expert-center/vehicle-telematics-technology/fuel-management/fuel-control-in-navixy/sensors-setup-and-configuration>. Accessed: 2026-06-08.
- [Obikoya, 2014] Obikoya, G. D. (2014). Design, construction, and implementation of a remote fuel-level monitoring system. *EURASIP Journal on Wireless Communications and Networking*, 2014(1):76.
- [Opensignal,] Opensignal. Se asia - coverage. <https://www.tutela.com/state-of-mobile-networks-southeast-asia/coverage>. Accessed: 2026-06-19.
- [Orange Connected Objects & Partnerships, 2016] Orange Connected Objects & Partnerships (2016). *LoRa Device Developer Guide*.
- [Patalinghug et al., 2015a] Patalinghug, E. et al. (2015a). Port congestion and underutilization in the greater capital region: Unpacking the issues. Technical report, Philippine Institute for Development Studies.
- [Patalinghug et al., 2015b] Patalinghug, E. et al. (2015b). A system-wide study of the logistics industry in the greater capital region. Technical report, Philippine Institute for Development Studies.
- [Patil and Patil, 2024] Patil, A. and Patil, S. (2024). Iot enabled vehicle monitoring and theft prevention system (i-vmtps). In *2024 2nd International Conference on Advancements and Key Challenges in Green Energy and Computing (AKGEC)*, pages 1–7.
- [Prabhu et al., 2022] Prabhu, S. B., Deepa, K., and Nithya, M. (2022). IoT enabled fuel level monitoring and automatic fuel theft detection system. In *2022 13th International Conference on Computing Communication and Networking Technologies (ICCCNT)*.
- [Prasanna et al., 2023] Prasanna, J. L., Santhosh, C., Kumar, M. R., and Gayathri, K. (2023). Iot based automatic fuel level monitoring system for automobiles. In *IET Conference Proceedings*, volume 2023, pages 56–61.



- 1687 [RS et al., 2024] RS, S., Narayanan CS, S., G, R., S, P., Alagarsamy, M., and William, P. (2024).
 1688 Fuel quantity and quality detection in automobiles using IoT. In *2024 4th International Confer-*
 1689 *ence on Innovative Practices in Technology and Management (ICIPTM)*, pages 1–6.
- 1690 [S et al., 2024] S, S., Sowmya, J. M., Siva, M. V., Rishitha, N., Sagar, M. K. G. S., and Ganesh, M.
 1691 (2024). Iot enabled smart fuel station management system. In *2024 2nd International Conference*
 1692 *on Networking and Communications (ICNWC)*, pages 1–5.
- 1693 [Samainstage, 2025] Samainstage (2025). The evolution of wi-fi technology and standards. <https://standards.ieee.org/beyond-standards/the-evolution-of-wi-fi-technology-and-standards/>. Ac-
 1694 cessed: 2025-11-27.
- 1696 [Samsara, 2026] Samsara (2026). Fleet fuel management. [https://www.samsara.com/products/](https://www.samsara.com/products/telematics/fleet-fuel-management-system)
 1697 [telematics/fleet-fuel-management-system](https://www.samsara.com/products/telematics/fleet-fuel-management-system). Accessed: 2026-06-09.
- 1698 [Semenov et al., 2024] Semenov, I., Świdorski, A., Borucka, A., and Guzanek, P. (2024). Concept
 1699 of early prediction and identification of truck vehicle failures supported by in-vehicle telematics
 1700 platform based on abnormality detection algorithm. *Applied Sciences (Switzerland)*, 14(16).
- 1701 [Tatababu et al., 2024] Tatababu, D., Ranga, M. R., Satyannarayana, D., Jyothi, Y., and Devi, A. R.
 1702 (2024). Smart fuel monitoring system for diesel generator. In *2024 International Conference on*
 1703 *Computational Intelligence for Green and Sustainable Technologies (ICCIGST)*, pages 1–6.
- 1704 [Thajudheen et al., 2023] Thajudheen, S., Shanmugarathinum, G., and Jesudoss, A. G. (2023).
 1705 Vehicular data retrieval system. In *2023 International Conference on New Frontiers in Communi-*
 1706 *cation, Automation, Management and Security (ICCAMS)*.
- 1707 [The International Engineering Consortium,] The International Engineering Consortium. *Global*
 1708 *System for Mobile Communication (GSM)*. Web ProForum Tutorials. Tutorial.
- 1709 [Turan et al., 2024] Turan, B. B., Gene, E., Akcig, I. N., Goztepe, N., Mumeuoglu, M. E., and Unel,
 1710 M. (2024). Detecting high fuel consumption in hdvs with ensemble of anomaly detection models.
 1711 In *2024 IEEE 22nd International Conference on Industrial Informatics (INDIN)*, pages 1–6.
- 1712 [Uddin et al., 2017] Uddin, M. S., Ahmed, M. M., Alam, J. B., and Islam, M. (2017). Smart anti-
 1713 theft vehicle tracking system for bangladesh based on internet of things. In *2017 4th International*
 1714 *Conference on Advances in Electrical Engineering (ICAEE)*, pages 624–628.
- 1715 [Usama et al., 2019] Usama, M., Qadir, J., Raza, A., Arif, H., Yau, K.-L. A., Elkhatab, Y., Hussain,
 1716 A., and Al-Fuqaha, A. (2019). Unsupervised machine learning for networking: Techniques,
 1717 applications and research challenges. *IEEE Access*, 7:65579–65615.
- 1718 [Vigneshwaran et al., 2020] Vigneshwaran, S., Nithya, B., Raghul, K., Nivas, B., and Kishore,
 1719 V. M. (2020). Design of bus tracking and fuel monitoring system. In *2020 6th International*
 1720 *Conference on Advanced Computing and Communication Systems (ICACCS)*, pages 348–351.
- 1721 [Weiwei et al., 2024] Weiwei, Q., Longbin, L., Xingyu, W., Yulong, L., and Weiqian, D. (2024).
 1722 Research on diesel consumption prediction and early warning analysis of dump trucks in smart
 1723 mines. In *2024 IEEE 22nd International Conference on Industrial Informatics (INDIN)*, pages



1724 1–6.

1725 [Wialon, 2026] Wialon (2026). Fuel control. <https://wialon.com/en/fuel-control>. Accessed: 2026-

1726 06-21.

1727 [Yeh et al., 2016] Yeh, C.-C. M. et al. (2016). Matrix profile i: All pairs similarity joins for

1728 time series: A unifying view that includes motifs, discords and shapelets. In *2016 IEEE 16th*

1729 *International Conference on Data Mining (ICDM)*, pages 1317–1322, Barcelona, Spain.

1730 [Yeh et al., 2024] Yeh, C.-C. M. et al. (2024). Matrix profile for anomaly detection on multidimensional time series. In *2024 IEEE International Conference on Data Mining (ICDM)*, pages

1731 911–916, Abu Dhabi, United Arab Emirates.

1732