```
[package]
        name = "bitwarden"
        description = "Rust command line client for bitwarden"
version = "0.1.0"
authors = ["Birl.org"]
        publish = false
publish = laise
    license = "MIT"
    homepage = "https://github.com/tjyang/binwarden-cli/"
    readme = "README.md"
    categories = ["command-line-utilities"]
    keywords = ["bitwarden", "password"]
 12
 13
      [dependencies]
daemonize = "^0.3"
 14
 15
      rust-crypto = "^0.2"
rand = "^0.4"
18 rustc-serialize = "^0.3"
19 serde = "1.0"
19  serde = "1.0"
20  serde_derive = "1.0"
21  serde_json = "1.0"
22  reqwest = "0.8.5"
23  rpassword = "2.1.0"
24  #rouille = { git= "https://github.com/birlorg/rouille"}
25  tiny_http = "0.6.0"
26  secstr = "0.3.0"
27  openssl-sys = "0.9.40"
28  hmac = "0.7.0"
29  openssl = { version = "0.0.10"}
       openssl = { version = "^0.10"}
uuid = { version = "^0.7", features = ["v5"]}
clap = {version = "^2.32", features = ["yaml"]}
 31
 32
      [package.metadata.rpm.cargo]
buildflags = ["--release"]
 33
 34
 35
      [package.metadata.rpm.targets]
agent = { path = "/usr/bin/agent" }
```